

OPSAWG  
Internet-Draft  
Obsoletes: [7630](#) (if approved)  
Intended status: Standards Track  
Expires: September 19, 2016

J. Merkle, Ed.  
Secunet Security Networks  
M. Lochter  
BSI  
March 18, 2016

HMAC-SHA-2 Authentication Protocols in USM for SNMPv3  
draft-ietf-opsawg-hmac-sha-2-usm-snmp-new-05

## Abstract

This document specifies several authentication protocols based on the SHA-2 hash functions for the User-based Security Model (USM) for SNMPv3 defined in [RFC 3414](#). It obsoletes [RFC 7630](#), in which the MIB MODULE-IDENTITY value was incorrectly specified.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 19, 2016.

## Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Internet-Draft

HMAC-SHA-2\_Auth\_USM\_new

March 2016

## Table of Contents

|                     |  |                    |
|---------------------|--|--------------------|
| <a href="#">1.</a>  | Introduction . . . . .                                   | <a href="#">2</a>  |
| <a href="#">2.</a>  | The Internet-Standard Management Framework . . . . .     | <a href="#">3</a>  |
| <a href="#">3.</a>  | Conventions . . . . .                                    | <a href="#">3</a>  |
| <a href="#">4.</a>  | The HMAC-SHA-2 Authentication Protocols . . . . .        | <a href="#">3</a>  |
| 4.1.                | Deviations from the HMAC-SHA-96 Authentication Protocol  | 4                  |
| 4.2.                | Processing . . . . .                                     | <a href="#">5</a>  |
| 4.2.1.              | Processing an Outgoing Message . . . . .                 | <a href="#">5</a>  |
| 4.2.2.              | Processing an Incoming Message . . . . .                 | <a href="#">6</a>  |
| <a href="#">5.</a>  | Key Localization and Key Change . . . . .                | <a href="#">6</a>  |
| <a href="#">6.</a>  | Structure of the MIB Module . . . . .                    | <a href="#">6</a>  |
| <a href="#">7.</a>  | Relationship to Other MIB Modules . . . . .              | <a href="#">7</a>  |
| 7.1.                | Relationship to SNMP-USER-BASED-SM-MIB . . . . .         | <a href="#">7</a>  |
| 7.2.                | Relationship to SNMP-FRAMEWORK-MIB . . . . .             | <a href="#">7</a>  |
| 7.3.                | MIB Modules Required for IMPORTS . . . . .               | <a href="#">7</a>  |
| <a href="#">8.</a>  | Definitions . . . . .                                    | <a href="#">7</a>  |
| <a href="#">9.</a>  | Security Considerations . . . . .                        | <a href="#">9</a>  |
| 9.1.                | Use of the HMAC-SHA-2 Authentication Protocols in USM .  | 9                  |
| 9.2.                | Cryptographic Strength of the Authentication Protocols . | 9                  |
| 9.3.                | Derivation of Keys from Passwords . . . . .              | <a href="#">10</a> |
| 9.4.                | Access to the SNMP-USM-HMAC-SHA2-MIB . . . . .           | <a href="#">11</a> |
| <a href="#">10.</a> | IANA Considerations . . . . .                            | <a href="#">11</a> |
| <a href="#">11.</a> | References . . . . .                                     | <a href="#">12</a> |
| 11.1.               | Normative References . . . . .                           | <a href="#">12</a> |
| 11.2.               | Informative References . . . . .                         | <a href="#">13</a> |
|                     | Authors' Addresses . . . . .                             | <a href="#">13</a> |

[1.](#) Introduction

Within the Architecture for describing Simple Network Management Protocol (SNMP) Management Frameworks [[RFC3411](#)], the User-based Security Model (USM) [[RFC3414](#)] for SNMPv3 is defined as a Security Subsystem within an SNMP engine. In [RFC 3414](#), two different authentication protocols, HMAC-MD5-96 and HMAC-SHA-96, are defined based on the hash functions MD5 and SHA-1, respectively.

This memo specifies new HMAC-SHA-2 authentication protocols for USM using a Hashed Message Authentication Code (HMAC) based on the SHA-2 family of hash functions [[SHA](#)] and truncated to 128 bits for SHA-224, to 192 bits for SHA-256, to 256 bits for SHA-384, and to 384 bits for SHA-512. These protocols are straightforward adaptations of the authentication protocols HMAC-MD5-96 and HMAC-SHA-96 to the

SHA-2-based HMAC.

This document obsoletes [RFC 7630](#), in which the MIB MODULE-IDENTITY value was incorrectly specified.

## [2.](#) The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of \[RFC3410\]](#).

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in [\[RFC2578\]](#), [\[RFC2579\]](#), and [\[RFC2580\]](#).

## [3.](#) Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#), [RFC 2119](#) [\[RFC2119\]](#).

## [4.](#) The HMAC-SHA-2 Authentication Protocols

This section describes the HMAC-SHA-2 authentication protocols, which use the SHA-2 hash functions (described in FIPS PUB 180-4 [\[SHA\]](#) and [\[RFC6234\]](#)) in the HMAC mode (described in [\[RFC2104\]](#) and [RFC 6234](#)), truncating the output to 128 bits for SHA-224, 192 bits for SHA-256, 256 bits for SHA-384, and 384 bits for SHA-512. [RFC 6234](#) also provides source code for all the SHA-2 algorithms and HMAC (without truncation). It also includes test harness and standard test vectors for all the defined hash functions and HMAC examples.

The following protocols are defined:

usmHMAC128SHA224AuthProtocol: uses SHA-224 and truncates the output to 128 bits (16 octets);

usmHMAC192SHA256AuthProtocol: uses SHA-256 and truncates the output to 192 bits (24 octets);

usmHMAC256SHA384AuthProtocol: uses SHA-384 and truncates the output to 256 bits (32 octets);

usmHMAC384SHA512AuthProtocol: uses SHA-512 and truncates the output to 384 bits (48 octets).

Implementations conforming to this specification MUST support usmHMAC192SHA256AuthProtocol and SHOULD support

usmHMAC384SHA512AuthProtocol. The protocols usmHMAC128SHA224AuthProtocol and usmHMAC256SHA384AuthProtocol are OPTIONAL.

#### 4.1. Deviations from the HMAC-SHA-96 Authentication Protocol

All the HMAC-SHA-2 authentication protocols are straightforward adaptations of the HMAC-MD5-96 and HMAC-SHA-96 authentication protocols. Specifically, they differ from the HMAC-MD5-96 and HMAC-SHA-96 authentication protocols in the following aspects:

- o The SHA-2 hash function is used to compute the message digest in the HMAC computation according to [RFC 2104](#) and [RFC 6234](#), as opposed to the MD5 hash function [[RFC1321](#)] and SHA-1 hash function [[SHA](#)] used in HMAC-MD5-96 and HMAC-SHA-96, respectively. Consequently, the length of the message digest prior to truncation is 224 bits for the SHA-224-based protocol, 256 bits for the SHA-256-based protocol, 384 bits for the SHA-384-based protocol, and 512 bits for the SHA-512-based protocol.
- o The resulting message digest (output of HMAC) is truncated to
  - \* 16 octets for usmHMAC128SHA224AuthProtocol
  - \* 24 octets for usmHMAC192SHA256AuthProtocol
  - \* 32 octets for usmHMAC256SHA384AuthProtocol
  - \* 48 octets for usmHMAC384SHA512AuthProtocol

as opposed to the truncation to 12 octets in HMAC-MD5-96 and HMAC-SHA-96.

- o The user's secret key to be used when calculating a digest MUST be
  - \* 28 octets long and derived with SHA-224 for the SHA-224-based protocol `usmHMAC128SHA224AuthProtocol`
  - \* 32 octets long and derived with SHA-256 for the SHA-256-based protocol `usmHMAC192SHA256AuthProtocol`
  - \* 48 octets long and derived with SHA-384 for the SHA-384-based protocol `usmHMAC256SHA384AuthProtocol`
  - \* 64 octets long and derived with SHA-512 for the SHA-512-based protocol `usmHMAC384SHA512AuthProtocol`

as opposed to the keys being 16 and 20 octets long in HMAC-MD5-96 and HMAC-SHA-96, respectively.

#### [4.2.](#) Processing

This section describes the procedures for the HMAC-SHA-2 authentication protocols. The descriptions are based on the definition of services and data elements specified for HMAC-SHA-96 in [RFC 3414](#) with the deviations listed in [Section 4.1](#).

Values of constants M (the length of the secret key in octets) and N (the length of the Message Authentication Code (MAC) output in octets), and the hash function H used below are:

`usmHMAC128SHA224AuthProtocol`: M=28, N=16, H=SHA-224;

`usmHMAC192SHA256AuthProtocol`: M=32, N=24, H=SHA-256;

`usmHMAC256SHA384AuthProtocol`: M=48, N=32, H=SHA-384;

`usmHMAC384SHA512AuthProtocol`: M=64, N=48, H=SHA-512.

#### [4.2.1.](#) Processing an Outgoing Message

This section describes the procedure followed by an SNMP engine whenever it must authenticate an outgoing message using one of the authentication protocols defined above. Values of the constants M and N, and the hash function H are as defined in [Section 4.2](#) and are selected based on which authentication protocol is configured for the given USM `usmUser` Table entry.

1. The `msgAuthenticationParameters` field is set to the serialization of an OCTET STRING containing N zero octets; it is serialized according to the rules in [\[RFC3417\]](#).
2. Using the secret `authKey` of M octets, the HMAC is calculated over the `wholeMsg` according to [RFC 6234](#) with hash function H.
3. The N first octets of the above HMAC are taken as the computed MAC value.
4. The `msgAuthenticationParameters` field is replaced with the MAC obtained in the previous step.
5. The `authenticatedWholeMsg` is then returned to the caller together with the `statusInformation` indicating success.

#### [4.2.2.](#) Processing an Incoming Message

This section describes the procedure followed by an SNMP engine whenever it must authenticate an incoming message using one of the HMAC-SHA-2 authentication protocols. Values of the constants M and N, and the hash function H are as defined in [Section 4.2](#) and are selected based on which authentication protocol is configured for the given USM `usmUser` Table entry.

1. If the digest received in the `msgAuthenticationParameters` field is not N octets long, then a failure and an `errorIndication` (`authenticationError`) are returned to the calling module.
2. The MAC received in the `msgAuthenticationParameters` field is saved.

3. The digest in the msgAuthenticationParameters field is replaced by the N zero octets.
4. Using the secret authKey of M octets, the HMAC is calculated over the wholeMsg according to [RFC 6234](#) with hash function H.
5. The N first octets of the above HMAC are taken as the computed MAC value.
6. The msgAuthenticationParameters field is replaced with the MAC value that was saved in step 2.
7. The newly calculated MAC is compared with the MAC saved in step 2. If they do not match, then a failure and an errorIndication (authenticationFailure) are returned to the calling module.
8. The authenticatedWholeMsg and statusInformation indicating success are then returned to the caller.

## [5.](#) Key Localization and Key Change

For any of the protocols defined in [Section 4](#), key localization and key change SHALL be performed according to [[RFC3414](#)] using the same SHA-2 hash function as in the HMAC-SHA-2 authentication protocol.

## [6.](#) Structure of the MIB Module

The MIB module specified in this memo does not define any managed objects, subtrees, notifications, or tables; rather, it only defines object identities (for authentication protocols) under a subtree of an existing MIB.

## [7.](#) Relationship to Other MIB Modules

### [7.1.](#) Relationship to SNMP-USER-BASED-SM-MIB

[RFC 3414](#) specifies the MIB module for USM for SNMPv3 (SNMP-USER-BASED-SM-MIB), which defines authentication protocols for USM based on the hash functions MD5 and SHA-1, respectively. The following MIB module defines new HMAC-SHA2 authentication protocols for USM based

on the SHA-2 hash functions [[SHA](#)]. The use of the HMAC-SHA2 authentication protocols requires the usage of the objects defined in the SNMP-USER-BASED-SM-MIB.

## [7.2.](#) Relationship to SNMP-FRAMEWORK-MIB

[RFC3411] specifies the SNMP-FRAMEWORK-MIB, which defines a subtree `snmpAuthProtocols` for SNMP authentication protocols. The following MIB module defines new authentication protocols in the `snmpAuthProtocols` subtree.

## [7.3.](#) MIB Modules Required for IMPORTS

The following MIB module IMPORTS definitions from SNMPv2-SMI [[RFC2578](#)] and SNMP-FRAMEWORK-MIB [[RFC3411](#)].

## [8.](#) Definitions

```
SNMP-USM-HMAC-SHA2-MIB DEFINITIONS ::= BEGIN
    IMPORTS
        MODULE-IDENTITY, OBJECT-IDENTITY,
        mib-2 FROM SNMPv2-SMI -- [RFC2578]
        snmpAuthProtocols FROM SNMP-FRAMEWORK-MIB; -- [RFC3411]

    snmpUsmHmacSha2MIB MODULE-IDENTITY
        LAST-UPDATED      "201603180000Z" -- 18 March 2016, midnight
        -- RFC Ed.: replace with publication date & remove this line
        ORGANIZATION      "SNMPv3 Working Group"
        CONTACT-INFO       "WG email: OPSAWG@ietf.org
        Subscribe:
            https://www.ietf.org/mailman/listinfo/opsawg
        Editor:            Johannes Merkle
                           secunet Security Networks
        postal:            Mergenthaler Allee 77
                           D-65760 Eschborn
                           Germany
        phone:             +49 20154543091
        email:             johannes.merkle@secunet.com
```

Bundesamt fuer Sicherheit in der  
Informationstechnik (BSI)  
postal: Postfach 200363  
D-53133 Bonn  
Germany  
phone: +49 228 9582 5643  
email: manfred.lochter@bsi.bund.de"

#### DESCRIPTION

"Definitions of Object Identities needed for the use of  
HMAC-SHA2 Authentication Protocols by SNMP's User-based Security  
Model.

Copyright (c) 2014 IETF Trust and the persons identified  
as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with  
or without modification, is permitted pursuant to, and  
subject to the license terms contained in, the Simplified  
BSD License set forth in [Section 4.c](#) of the IETF Trust's  
Legal Provisions Relating to IETF Documents  
(<http://trustee.ietf.org/license-info>)."

REVISION "201603180000Z" -- 18 March 2016, midnight  
-- RFC Ed.: replace with publication date & remove this line  
"Version correcting the MODULE-IDENTITY value,  
published as RFC TBD"  
-- RFC Ed.: replace TBD with actual RFC number & remove this line

REVISION "201510140000Z" -- 14 October 2015, midnight

#### DESCRIPTION

"Initial version, published as [RFC 7630](#)"

::= { mib-2 235 }

#### usmHMAC128SHA224AuthProtocol OBJECT-IDENTITY

STATUS current

DESCRIPTION "The Authentication Protocol  
usmHMAC128SHA224AuthProtocol uses HMAC-SHA-224 and  
truncates output to 128 bits."

REFERENCE "- Krawczyk, H., Bellare, M., and R. Canetti, HMAC:  
Keyed-Hashing for Message Authentication, [RFC 2104](#).  
- National Institute of Standards and Technology,  
Secure Hash Standard (SHS), FIPS PUB 180-4, 2012."

::= { snmpAuthProtocols 4 }

---

usmHMAC192SHA256AuthProtocol OBJECT-IDENTITY  
STATUS current  
DESCRIPTION "The Authentication Protocol  
usmHMAC192SHA256AuthProtocol uses HMAC-SHA-256 and  
truncates output to 192 bits."  
REFERENCE "- Krawczyk, H., Bellare, M., and R. Canetti, HMAC:  
Keyed-Hashing for Message Authentication, [RFC 2104](#).  
- National Institute of Standards and Technology,  
Secure Hash Standard (SHS), FIPS PUB 180-4, 2012."  
 ::= { snmpAuthProtocols 5 }

usmHMAC256SHA384AuthProtocol OBJECT-IDENTITY  
STATUS current  
DESCRIPTION "The Authentication Protocol  
usmHMAC256SHA384AuthProtocol uses HMAC-SHA-384 and  
truncates output to 256 bits."  
REFERENCE "- Krawczyk, H., Bellare, M., and R. Canetti, HMAC:  
Keyed-Hashing for Message Authentication, [RFC 2104](#).  
- National Institute of Standards and Technology,  
Secure Hash Standard (SHS), FIPS PUB 180-4, 2012."  
 ::= { snmpAuthProtocols 6 }

usmHMAC384SHA512AuthProtocol OBJECT-IDENTITY  
STATUS current  
DESCRIPTION "The Authentication Protocol  
usmHMAC384SHA512AuthProtocol uses HMAC-SHA-512 and  
truncates output to 384 bits."  
REFERENCE "- Krawczyk, H., Bellare, M., and R. Canetti, HMAC:  
Keyed-Hashing for Message Authentication, [RFC 2104](#).  
- National Institute of Standards and Technology,  
Secure Hash Standard (SHS), FIPS PUB 180-4, 2012."  
 ::= { snmpAuthProtocols 7 }

END

## [9.](#) Security Considerations

### [9.1.](#) Use of the HMAC-SHA-2 Authentication Protocols in USM

The security considerations of [[RFC3414](#)] also apply to the HMAC-SHA-2 authentication protocols defined in this document.

### [9.2.](#) Cryptographic Strength of the Authentication Protocols

At the time of publication of this document, all of the HMAC-SHA-2 authentication protocols provide a very high level of security. The

security of each HMAC-SHA-2 authentication protocol depends on the parameters used in the corresponding HMAC computation, which are the

length of the key (if the key has maximum entropy), the size of the hash function's internal state, and the length of the truncated MAC. For the HMAC-SHA-2 authentication protocols, these values are as follows (values are given in bits).

| Protocol                     | Key length | Size of internal state | MAC length |
|------------------------------|------------|------------------------|------------|
| usmHMAC128SHA224AuthProtocol | 224        | 256                    | 128        |
| usmHMAC192SHA256AuthProtocol | 256        | 256                    | 192        |
| usmHMAC256SHA384AuthProtocol | 384        | 512                    | 256        |
| usmHMAC384SHA512AuthProtocol | 512        | 512                    | 384        |

Table 1: HMAC Parameters of the HMAC-SHA-2 Authentication Protocols

The security of the HMAC scales with both the key length and the size of the internal state: longer keys render key guessing attacks more difficult, and a larger internal state decreases the success probability of MAC forgeries based on internal collisions of the hash function.

The role of the truncated output length is more complicated: according to [\[BCK\]](#), there is a trade-off in that

by outputting less bits the attacker has less bits to predict in a MAC forgery but, on the other hand, the attacker also learns less about the output of the compression function from seeing the authentication tags computed by legitimate parties.

Thus, truncation weakens the HMAC against forgery by guessing but, at the same time, strengthens it against chosen message attacks aiming at MAC forgery based on internal collisions or at key guessing. [RFC 2104](#) and [\[BCK\]](#) allow truncation to any length that is not less than half the size of the internal state.

Further discussion of the security of the HMAC construction is given in [RFC 2104](#).

### 9.3. Derivation of Keys from Passwords

If secret keys to be used for HMAC-SHA-2 authentication protocols are derived from passwords, the derivation SHOULD be performed using the password-to-key algorithm from [Appendix A.1 of RFC 3414](#) with MD5 being replaced by the SHA-2 hash function H used in the HMAC-SHA-2 authentication protocol. Specifically, the password is converted into the required secret key by the following steps:

- o forming a string of length 1,048,576 octets by repeating the value of the password as often as necessary, truncating accordingly, and using the resulting string as the input to the hash function H. The resulting digest, termed "digest1", is used in the next step.
- o forming a second string by concatenating digest1, the SNMP engine's snmpEngineID value, and digest1. This string is used as input to the hash function H.

### 9.4. Access to the SNMP-USM-HMAC-SHA2-MIB

The SNMP-USM-HMAC-SHA2-MIB module defines OBJECT IDENTIFIER values for use in other MIB modules. It does not define any objects that can be accessed. As such, the SNMP-USM-HMAC-SHA2-MIB does not, by itself, have any effect on the security of the Internet.

The values defined in this module are expected to be used with the usmUserTable defined in the SNMP-USER-BASED-SM-MIB [[RFC3414](#)]. The considerations in [Section 11.5 of RFC 3414](#) should be taken into account.

## 10. IANA Considerations

IANA has assigned an OID for the MIB as follows.

| Descriptor         | OBJECT IDENTIFIER value |
|--------------------|-------------------------|
| snmpUsmHmacSha2MIB | { mib-2 235 }           |

Table 2: OID of MIB

Furthermore, IANA has assigned a value in the SntpAuthProtocols registry for each of the following protocols.

| Description                  | Value | Reference |
|------------------------------|-------|-----------|
| usmHMAC128SHA224AuthProtocol | 4     | RFC XXX   |
| usmHMAC192SHA256AuthProtocol | 5     | RFC XXX   |
| usmHMAC256SHA384AuthProtocol | 6     | RFC XXX   |
| usmHMAC384SHA512AuthProtocol | 7     | RFC XXX   |

Table 3: Code Points Assigned to HMAC-SHA-2 Authentication Protocols

-- RFC Ed.: replace XXX with actual RFC number and remove this line

## [11.](#) References

### [11.1.](#) Normative References

- [RFC2104] Krawczyk, H., Bellare, M., and R. Canetti, "HMAC: Keyed-Hashing for Message Authentication", [RFC 2104](#), DOI 10.17487/RFC2104, February 1997, <<http://www.rfc-editor.org/info/rfc2104>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIV2)", STD 58, [RFC 2578](#), DOI 10.17487/RFC2578, April 1999, <<http://www.rfc-editor.org/info/rfc2578>>.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIV2", STD 58, [RFC 2579](#), DOI 10.17487/RFC2579, April 1999, <<http://www.rfc-editor.org/info/rfc2579>>.

- [RFC2580] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Conformance Statements for SMIV2", STD 58, [RFC 2580](#), DOI 10.17487/RFC2580, April 1999, <<http://www.rfc-editor.org/info/rfc2580>>.
- [RFC3414] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", STD 62, [RFC 3414](#), DOI 10.17487/RFC3414, December 2002, <<http://www.rfc-editor.org/info/rfc3414>>.
- [RFC6234] Eastlake 3rd, D. and T. Hansen, "US Secure Hash Algorithms (SHA and SHA-based HMAC and HKDF)", [RFC 6234](#), DOI 10.17487/RFC6234, May 2011, <<http://www.rfc-editor.org/info/rfc6234>>.
- [SHA] National Institute of Standards and Technology, "Secure Hash Standard (SHS)", FIPS PUB 180-4, DOI 10.6028/NIST.FIPS.180-4, March 2012, <<http://nvlpubs.nist.gov/nistpubs/FIPS/NIST.FIPS.180-4.pdf>>.

## [11.2](#). Informative References

- [RFC1321] Rivest, R., "The MD5 Message-Digest Algorithm", [RFC 1321](#), DOI 10.17487/RFC1321, April 1992, <<http://www.rfc-editor.org/info/rfc1321>>.
- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", [RFC 3410](#), DOI 10.17487/RFC3410, December 2002, <<http://www.rfc-editor.org/info/rfc3410>>.
- [RFC3411] Harrington, D., Presuhn, R., and B. Wijnen, "An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks", STD 62, [RFC 3411](#), DOI 10.17487/RFC3411, December 2002, <<http://www.rfc-editor.org/info/rfc3411>>.

[RFC3417] Presuhn, R., Ed., "Transport Mappings for the Simple Network Management Protocol (SNMP)", STD 62, [RFC 3417](#), DOI 10.17487/RFC3417, December 2002, <<http://www.rfc-editor.org/info/rfc3417>>.

[BCK] Bellare, M., Canetti, R., and H. Krawczyk, "Keyed Hash Functions for Message Authentication", Advances in Cryptology - CRYPTO 96, Lecture Notes in Computer Science 1109, Springer-Verlag Berlin Heidelberg, DOI 10.1007/3-540-68697-5\_1, 1996.

#### Authors' Addresses

Johannes Merkle (editor)  
Secunet Security Networks  
Mergenthaler Allee 77  
65760 Eschborn  
Germany

Phone: +49 201 5454 3091  
EMail: [johannes.merkle@secunet.com](mailto:johannes.merkle@secunet.com)

Merkle & Lochter

Expires September 19, 2016

[Page 13]

---

Internet-Draft

HMAC-SHA-2\_Auth\_USM\_new

March 2016

Manfred Lochter  
BSI  
Postfach 200363  
53133 Bonn  
Germany

Phone: +49 228 9582 5643  
EMail: [manfred.lochter@bsi.bund.de](mailto:manfred.lochter@bsi.bund.de)

