

Network Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: August 20, 2015

A. Lindem  
S. Mirtorabi  
A. Roy  
F. Baker  
Cisco Systems  
February 16, 2015

**OSPFv3 LSA Extendibility**  
**draft-ietf-ospf-ospfv3-lsa-extend-06.txt**

**Abstract**

OSPFv3 requires functional extension beyond what can readily be done with the fixed-format Link State Advertisement (LSA) as described in [RFC 5340](#). Without LSA extension, attributes associated with OSPFv3 links and advertised IPv6 prefixes must be advertised in separate LSAs and correlated to the fixed-format LSAs. This document extends the LSA format by encoding the existing OSPFv3 LSA information in Type-Length-Value (TLV) tuples and allowing advertisement of additional information with additional TLVs. Backward compatibility mechanisms are also described.

**Status of This Memo**

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 20, 2015.

**Copyright Notice**

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of

publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	<a href="#">Introduction</a>	<a href="#">3</a>
<a href="#">1.1.</a>	<a href="#">Requirements notation</a>	<a href="#">3</a>
<a href="#">1.2.</a>	<a href="#">Acknowledgments</a>	<a href="#">3</a>
<a href="#">2.</a>	<a href="#">OSPFv3 Extended LSA Types</a>	<a href="#">4</a>
<a href="#">3.</a>	<a href="#">OSPFv3 Extended LSA TLVs</a>	<a href="#">5</a>
<a href="#">3.1.</a>	<a href="#">Prefix Options Extensions</a>	<a href="#">6</a>
<a href="#">3.1.1.</a>	<a href="#">N-bit Prefix Option</a>	<a href="#">6</a>
<a href="#">3.2.</a>	<a href="#">Router-Link TLV</a>	<a href="#">7</a>
<a href="#">3.3.</a>	<a href="#">Attached-Routers TLV</a>	<a href="#">7</a>
<a href="#">3.4.</a>	<a href="#">Inter-Area-Prefix TLV</a>	<a href="#">9</a>
<a href="#">3.5.</a>	<a href="#">Inter-Area-Router TLV</a>	<a href="#">10</a>
<a href="#">3.6.</a>	<a href="#">External-Prefix TLV</a>	<a href="#">11</a>
<a href="#">3.7.</a>	<a href="#">Intra-Area-Prefix TLV</a>	<a href="#">12</a>
<a href="#">3.8.</a>	<a href="#">IPv6 Link-Local Address TLV</a>	<a href="#">13</a>
<a href="#">3.9.</a>	<a href="#">IPv4 Link-Local Address TLV</a>	<a href="#">14</a>
<a href="#">3.10.</a>	<a href="#">IPv6-Forwarding-Address Sub-TLV</a>	<a href="#">15</a>
<a href="#">3.11.</a>	<a href="#">IPv4-Forwarding-Address Sub-TLV</a>	<a href="#">15</a>
<a href="#">3.12.</a>	<a href="#">Route-Tag Sub-TLV</a>	<a href="#">16</a>
<a href="#">4.</a>	<a href="#">OSPFv3 Extended LSAs</a>	<a href="#">16</a>
<a href="#">4.1.</a>	<a href="#">OSPFv3 E-Router-LSA</a>	<a href="#">16</a>
<a href="#">4.2.</a>	<a href="#">OSPFv3 E-Network-LSA</a>	<a href="#">18</a>
<a href="#">4.3.</a>	<a href="#">OSPFv3 E-Inter-Area-Prefix-LSA</a>	<a href="#">19</a>
<a href="#">4.4.</a>	<a href="#">OSPFv3 E-Inter-Area-Router-LSA</a>	<a href="#">20</a>
<a href="#">4.5.</a>	<a href="#">OSPFv3 E-AS-External-LSA</a>	<a href="#">21</a>
<a href="#">4.6.</a>	<a href="#">OSPFv3 E-NSSA-LSA</a>	<a href="#">22</a>
<a href="#">4.7.</a>	<a href="#">OSPFv3 E-Link-LSA</a>	<a href="#">23</a>
<a href="#">4.8.</a>	<a href="#">OSPFv3 E-Intra-Area-Prefix-LSA</a>	<a href="#">25</a>
<a href="#">5.</a>	<a href="#">Malformed OSPFv3 Extended LSA Handling</a>	<a href="#">25</a>
<a href="#">6.</a>	<a href="#">LSA Extension Backward Compatibility</a>	<a href="#">26</a>
<a href="#">6.1.</a>	<a href="#">Extended LSA Mixed-Mode Backward Compatibility</a>	<a href="#">27</a>
<a href="#">6.1.1.</a>	<a href="#">Area Extended LSA Mixed-Mode Backward Compatibility</a>	<a href="#">28</a>
<a href="#">6.2.</a>	<a href="#">LSA TLV Processing Backward Compatibility</a>	<a href="#">29</a>
<a href="#">7.</a>	<a href="#">Security Considerations</a>	<a href="#">29</a>
<a href="#">8.</a>	<a href="#">IANA Considerations</a>	<a href="#">29</a>
<a href="#">9.</a>	<a href="#">References</a>	<a href="#">30</a>
<a href="#">9.1.</a>	<a href="#">Normative References</a>	<a href="#">30</a>
<a href="#">9.2.</a>	<a href="#">Informative References</a>	<a href="#">31</a>
<a href="#">Appendix A.</a>	<a href="#">Global Configuration Parameters</a>	<a href="#">31</a>
<a href="#">Appendix B.</a>	<a href="#">Area Configuration Parameters</a>	<a href="#">32</a>



Authors' Addresses . . . . .	<a href="#">33</a>
------------------------------	--------------------

## **[1.](#) Introduction**

OSPFv3 requires functional extension beyond what can readily be done with the fixed-format Link State Advertisement (LSA) as described in [RFC 5340](#) [OSPFV3]. Without LSA extension, attributes associated with OSPFv3 links and advertised IPv6 prefixes must be advertised in separate LSAs and correlated to the fixed-format LSAs. This document extends the LSA format by encoding the existing OSPFv3 LSA information in Type-Length-Value (TLV) tuples and allowing advertisement of additional information with additional TLVs. Backward compatibility mechanisms are also described.

A similar extension was previously proposed in support of multi-topology routing. Additional requirements for OSPFv3 LSA extension include source/destination routing, route tagging, and others.

A final requirement is to limit the changes to OSPFv3 to those necessary for TLV-based LSAs. For the most part, the semantics of existing OSPFv3 LSAs are retained for their TLV-based successor LSAs described herein. Additionally, encoding details, e.g., the representation of IPv6 prefixes as described in section A.4.1 in [RFC 5340](#) [OSPFV3], have been retained. This requirement was included to increase the expedience of IETF adoption and deployment.

The following aspects of OSPFv3 LSA extension are described:

1. Extended LSA Types
2. Extended LSA TLVs
3. Extended LSA Formats
4. Backward Compatibility

### **[1.1.](#) Requirements notation**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC-KEYWORDS](#)].

### **[1.2.](#) Acknowledgments**

OSPFv3 TLV-based LSAs were first proposed in "Multi-topology routing in OSPFv3 (MT-OSPFv3)" [[MT-OSPFV3](#)].



Thanks for Peter Psenak for significant contributions to the backward compatibility mechanisms.

Thanks go to Michael Barnes, Mike Dubrovsky, Anton Smirnov, and Tony Przygienda for review of the draft versions and discussions of backward compatibility.

Thanks to Alan Davey for review and comments including the suggestion to separate the extended LSA TLV definitions from the extended LSAs definitions.

Thanks to David Lamparter for review and suggestions on backward compatibility.

Thanks to Karsten Thomann for review and editorial comments.

The RFC text was produced using Marshall Rose's xml2rfc tool.

## **2. OSPFv3 Extended LSA Types**

In order to provide backward compatibility, new LSA codes must be allocated. There are eight fixed-format LSAs defined in [RFC 5340 \[OSPFV3\]](#). For ease of implementation and debugging, the LSA function codes are the same as the fixed-format LSAs only with 32, i.e., 0x20, added. The alternative to this mapping was to allocate a bit in the LS Type indicating the new LSA format. However, this would have used one half the LSA function code space for the migration of the eight original fixed-format LSAs. For backward compatibility, the U-bit will be set in LS Type so that the LSAs will be flooded by OSPFv3 routers that do not understand them.

LSA function code	LS Type	Description
-----		
33	0xA021	E-Router-LSA
34	0xA022	E-Network-LSA
35	0xA023	E-Inter-Area-Prefix-LSA
36	0xA024	E-Inter-Area-Router-LSA
37	0xC025	E-AS-External-LSA
38	N/A	Unused (Not to be allocated)
39	0xA027	E-Type-7-LSA
40	0x8028	E-Link-LSA
41	0xA029	E-Intra-Area-Prefix-LSA

### OSPFv3 Extended LSA Types



- o 0 - Reserved
- o 1 - Router-Link TLV
- o 2 - Attached-Routers TLV
- o 3 - Inter-Area Prefix TLV
- o 4 - Inter-Area Router TLV
- o 5 - External Prefix TLV
- o 6 - Intra-Area Prefix TLV
- o 7 - IPv6 Link-Local Address TLV
- o 8 - IPv4 Link-Local Address TLV





Additionally, this document defines the following sub-TLV types:

- o 0 - Reserved
- o 1 - IPv6 Forwarding Address sub-TLV
- o 2 - IPv4 Forwarding Address sub-TLV
- o 3 - Route Tag sub-TLV

In general, TLVs and sub-TLVs MAY occur in any order and the specification should define whether the TLV or sub-TLV is required and the behavior when there are multiple occurrences of the TLV or sub-TLVs.

### **3.1. Prefix Options Extensions**

The prefix options are extended from [Appendix A.4.1.1 \[OSPFV3\]](#). The applicability of the LA-bit is expanded and it SHOULD be set in Inter-Area-Prefix-TLVs and MAY be set in External-Prefix-TLVs when the advertised host IPv6 address, i.e., PrefixLength = 128, is an interface address. In [RFC 5340](#), the LA-bit is only set in Intra-Area-Prefix-LSAs (Section 4.4.3.9 in [\[OSPFV3\]](#)). This will allow a stable address to be advertised without having to configure a separate loopback address in every OSPFv3 area.

#### **3.1.1. N-bit Prefix Option**

Additionally, the N-bit prefix option is defined. The figure below shows the position of the N-bit in the prefix options (pending IANA allocation). This corresponds to the value 0x20.

```

      0  1  2  3  4  5  6  7
+---+---+---+---+---+---+---+
|   |   | N|DN| P| x|LA|NU|
+---+---+---+---+---+---+---+

```

The Prefix Options field

The N-bit is set in PrefixOptions for a host address (PrefixLength=128) that identifies the advertising router. While it is similar to the LA-bit, there are two differences. The advertising router MAY choose NOT to set the N-bit even when the above conditions are met. If the N-bit is set and the PrefixLength is NOT 128, the N-bit MUST be ignored. Additionally, the N-bit is propagated in the PrefixOptions when an OSPFv3 Area Border Router (ABR) originates an



The Attached-Routers TLV defines all the routers attached to an OSPFv3 multi-access network. The field definitions correspond directly to content of the OSPFv3 Network-LSA, section A.4.4, [OSPFV3]. The Attached-Routers TLV is only applicable to the E- Network-LSA (Section 4.2). Inclusion in other Extended LSAs MUST be ignored.



```

      0                               1                               2                               3
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|           2 (Attached-Routers)      |      TLV Length              |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|           Adjacent Neighbor Router ID                               |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
.                                     .
.           Additional Adjacent Neighbors                             .
.                                     .
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```


#### Attached-Routers TLV

There are two reasons for not having a separate TLV or sub-TLV for each adjacent neighbor. The first is to discourage using the E-Network-LSA for more than its current role of solely advertising the routers attached to a multi-access network. The router's metric as well as the attributes of individual attached routers should be advertised in their respective E-Router-LSAs. The second reason is that there is only a single E-Network-LSA per multi-access link with the Link State ID set to the Designated Router's Interface ID and, consequently, compact encoding has been chosen to decrease the likelihood that the size of the E-Network-LSA will require IPv6 fragmentation when advertised in an OSPFv3 Link State Update packet.



### 3.4. Inter-Area-Prefix TLV

The Inter-Area-Prefix TLV defines a single OSPFv3 inter-area prefix. The field definitions correspond directly to the content of an OSPFv3 IPv6 Prefix as defined in Section A.4.1, [OSPFV3] and an OSPFv3 Inter-Area-Prefix-LSA, as defined in section A.4.5, [OSPFV3]. Additionally, the PrefixOptions are extended as described in [Section 3.1](#). The Inter-Area-Prefix TLV is only applicable to the E-Inter-Area-Prefix-LSA ([Section 4.3](#)). Inclusion in other Extended LSAs MUST be ignored.




Inter-Area Prefix TLV





### 3.5. Inter-Area-Router TLV

The Inter-Area-Router TLV defines a single OSPFv3 Autonomous System Boundary Router (ASBR) reachable in another area. The field definitions correspond directly to the content of an OSPFv3 Inter-Area-Router-LSA, as defined in section A.4.6, [OSPFV3]. The Inter-Area-Router TLV is only applicable to the E-Inter-Area-Router-LSA (Section 4.4). Inclusion in other Extended LSAs MUST be ignored.




Inter-Area Router TLV



### 3.6. External-Prefix TLV

The External-Prefix TLV defines a single OSPFv3 external prefix. The field definitions correspond directly to the content of an OSPFv3 IPv6 Prefix as defined in Section A.4.1, [OSPFV3] and an OSPFv3 AS-External-LSA, as defined in section A.4.7, [OSPFV3]. The External-Prefix TLV is only applicable to the E-AS-External-LSA (Section 4.5) and the E-NSSA-LSA (Section 4.6). Additionally, the PrefixOptions are extended as described in Section 3.1. Inclusion in other Extended LSAs MUST be ignored.



External Prefix TLV

In the External-Prefix TLV, the optional IPv6/IPv4 Forwarding Address and External Route Tag are now sub-TLVs. Given the Referenced LS type and Referenced Link State ID from the AS-External-LSA have never been used or even specified, they have been omitted from the External Prefix TLV. If there were ever a requirement for a referenced LSA, it could be satisfied with a sub-TLV.


The following sub-TLVs are defined for optional inclusion in the External Prefix TLV:

- o 1 - IPv6 Forwarding Address sub-TLV (Section 3.10)
- o 2 - IPv4 Forwarding Address sub-TLV (Section 3.11)
- o 3 - Route Tag sub-TLV (Section 3.12)



### 3.7. Intra-Area-Prefix TLV

The Intra-Area-Prefix TLV defines a single OSPFv3 intra-area prefix. The field definitions correspond directly to the content of an OSPFv3 IPv6 Prefix as defined in Section A.4.1, [OSPFV3] and an OSPFv3 Link-LSA, as defined in section A.4.9, [OSPFV3]. The Intra-Area-Prefix TLV is only applicable to the E-Link-LSA (Section 4.7) and the Additionally, the PrefixOptions are extended as described in Section 3.1. E-Intra-Area-Prefix-LSA (Section 4.8). Inclusion in other Extended LSAs MUST be ignored.




Intra-Area Prefix TLV



### 3.8. IPv6 Link-Local Address TLV

The IPv6 Link-Local Address TLV is to be used with IPv6 address families as defined in [[OSPFV3-AF](#)]. The IPv6 Link-Local Address TLV is only applicable to the E-Link-LSA ([Section 4.7](#)). Inclusion in other Extended LSAs MUST be ignored.



IPv6 Link-Local Address TLV














The E-Router-LSA has an LS Type of 0xA021 and has the same base information content as the Router-LSA defined in section A.4.3 of [OSPFV3]. However, unlike the existing Router-LSA, it is fully extendable and represented as TLVs.





#### Extended Router-LSA


All LSA Header fields are the same as defined for the Router-LSA. Initially, only the top-level Router-Link TLV [Section 3.2](#) is applicable and an E-Router-LSA may include multiple Router-Link TLVs. Like the existing Router-LSA, the LSA length is used to determine the end of the LSA including TLVs.





#### 4.2. OSPFv3 E-Network-LSA

The E-Network-LSA has an LS Type of 0xA022 and has the same base information content as the Network-LSA defined in section A.4.4 of [OSPFV3]. However, unlike the existing Network-LSA, it is fully extendable and represented as TLVs.




#### E-Network-LSA

All LSA Header fields are the same as defined for the Network-LSA. Like the existing Network-LSA, the LSA length is used to determine the end of the LSA including TLVs. Initially, only the top-level Attached-Routers TLV [Section 3.3](#) is applicable. If the Attached-Router TLV is not included in the E-Network-LSA, it is treated as malformed as described in [Section 5](#). Instances of the Attached-Router TLV subsequent to the first MUST be ignored.



### 4.3. OSPFv3 E-Inter-Area-Prefix-LSA

The E-Inter-Area-Prefix-LSA has an LS Type of 0xA023 and has the same base information content as the Inter-Area-Prefix-LSA defined in section A.4.5 of [OSPFV3]. However, unlike the existing Inter-Area-Prefix-LSA, it is fully extendable and represented as TLVs.



#### E-Inter-Area-Prefix-LSA


All LSA Header fields are the same as defined for the Inter-Area-Prefix-LSA. In order to retain compatibility and semantics with the current OSPFv3 specification, each Inter-Area-Prefix LSA MUST contain a single Inter-Area Prefix TLV. This will facilitate migration and avoid changes to functions such as incremental SPF computation.

Like the existing Inter-Area-Prefix-LSA, the LSA length is used to determine the end of the LSA including TLV. Initially, only the top-level Inter-Area-Prefix TLV ([Section 3.4](#)) is applicable. If the Inter-Area-Prefix TLV is not included in the E-Inter-Area-Prefix-LSA, it is treated as malformed as described in [Section 5](#). Instances of the Inter-Area-Prefix TLV subsequent to the first MUST be ignored.



#### 4.4. OSPFv3 E-Inter-Area-Router-LSA

The E-Inter-Area-Router-LSA has an LS Type of 0xA024 and has the same base information content as the Inter-Area-Router-LSAE defined in section A.4.6 of [OSPFV3]. However, unlike the Inter-Area-Router-LSA, it is fully extendable and represented as TLVs.



#### E-Inter-Area-Router-LSA


All LSA Header fields are the same as defined for the Inter-Area-Router-LSA. In order to retain compatibility and semantics with the current OSPFv3 specification, each Inter-Area-Router LSA MUST contain a single Inter-Area Router TLV. This will facilitate migration and avoid changes to functions such as incremental SPF computation.

Like the existing Inter-Area-Router-LSA, the LSA length is used to determine the end of the LSA including TLV. Initially, only the top-level Inter-Area-Router TLV ([Section 3.5](#)) is applicable. If the Inter-Area-Router TLV is not included in the E-Inter-Area-Router-LSA, it is treated as malformed as described in [Section 5](#). Instances of the Inter-Area-Router TLV subsequent to the first MUST be ignored.



#### 4.5. OSPFv3 E-AS-External-LSA

The E-AS-External-LSA has an LS Type of 0xC025 and has the same base information content as the AS-External-LSA defined in section A.4.7 of [OSPFV3]. However, unlike the existing AS-External-LSA, it is fully extendable and represented as TLVs.



#### E-AS-External-LSA

All LSA Header fields are the same as defined for the AS-External-LSA. In order to retain compatibility and semantics with the current OSPFv3 specification, each LSA MUST contain a single External Prefix TLV. This will facilitate migration and avoid changes to OSPFv3 processes such as incremental SPF computation.

Like the existing AS-External-LSA, the LSA length is used to determine the end of the LSA including sub-TLVs. Initially, only the top-level External-Prefix TLV ([Section 3.6](#)) is applicable. If the External-Prefix TLV is not included in the E-External-AS-LSA, it is treated as malformed as described in [Section 5](#). Instances of the External-Prefix TLV subsequent to the first MUST be ignored.






#### **4.6. OSPFv3 E-NSSA-LSA**

The E-NSSA-LSA will have the same format and TLVs as the Extended AS-External-LSA [Section 4.5](#). This is the same relationship as exists between the NSSA-LSA defined in section A.4.8 of [[OSPFV3](#)], and the AS-External-LSA. The NSSA-LSA will have type 0xA027 which implies area flooding scope. Future requirements may dictate that supported TLVs differ between the E-AS-External-LSA and the E-NSSA-LSA. However, future requirements are beyond the scope of this document.

#### 4.7. OSPFv3 E-Link-LSA

The E-Link-LSA has an LS Type of 0x8028 and will have the same base information content as the Link-LSA defined in section A.4.9 of [OSPFV3]. However, unlike the existing Link-LSA, it is extendable and represented as TLVs.



All LSA Header fields are the same as defined for the Link-LSA.

Only the Intra-Area-Prefix TLV ([Section 3.7](#)), IPv6 Link-Local Address TLV ([Section 3.8](#)), and IPv4 Link-Local Address TLV ([Section 3.9](#)) are applicable to the E-Link-LSA. Like the Link-LSA, the E-Link-LSA affords advertisement of multiple intra-area prefixes. Hence, multiple Intra-Area Prefix TLVs ([Section 3.7](#)) may be specified and the LSA length defines the end of the LSA including all TLVs.

A single instance of the IPv6 Link-Local Address TLV ([Section 3.8](#)) SHOULD be included in the E-Link-LSA. Instances following the first MUST be ignored. For IPv4 address families as defined in [OSPFV3-AF], this TLV MUST be ignored.

Similarly, only a single instance of the IPv4 Link-Local Address TLV ([Section 3.9](#)) SHOULD be included in the E-Link-LSA. Instances following the first MUST be ignored. For OSPFv3 IPv6 address families as defined in [OSPFV3-AF], this TLV MUST be ignored.




If the IPv4/IPv6 Link-Local Address TLV corresponding to the OSPFv3 Address Family is not included in the E-Link-LSA, it is treated as malformed as described in [Section 5](#).

Future specifications may support advertisement of routing and topology information for multiple address families. However, this is beyond the scope of this document.

#### 4.8. OSPFv3 E-Intra-Area-Prefix-LSA

The E-Intra-Area-Prefix-LSA has an LS Type of 0xA029 and has the same base information content as the Intra-Area-Prefix-LSA defined in section A.4.10 of [OSPFV3]. However, unlike the Intra-Area-Prefix-LSA, it is fully extendable and represented as TLVs.



#### E-Intra-Area-Prefix-LSA

All LSA Header fields are the same as defined for the Intra-Area-Prefix-LSA.

Like the Intra-Area-Prefix-LSA, the E-Intra-Area-Link-LSA affords advertisement of multiple intra-area prefixes. Hence, multiple Intra-Area Prefix TLVs may be specified and the LSA length defines the end of the LSA including all TLVs.

### 5. Malformed OSPFv3 Extended LSA Handling

Extended LSAs that have inconsistent length or other encoding errors, as described herein, MUST NOT be installed in the Link State Database, acknowledged, or flooded. Reception of malformed LSAs



SHOULD be counted and/or logged for examination by the administrator of the OSPFv3 Routing Domain.

## 6. LSA Extension Backward Compatibility

In the context of this document, backward compatibility is solely related to the capability of an OSPFv3 router to receive, process, and originate the TLV-based LSAs defined herein. Unrecognized TLVs and sub-TLVs are ignored. Backward compatibility for future OSPFv3 extensions utilizing the TLV-based LSAs is out of scope and must be covered in the documents describing those extensions. Both full and, if applicable, partial deployment SHOULD be specified for future TLV-based OSPFv3 LSA extensions.

Two distinct backward compatibility modes are supported dependent on the OSPFv3 routing domain migration requirements. For simplicity and to avoid the scaling impact of maintaining both TLV and non-TLV based versions of the same LSA within a routing domain, the basic backward compatibility mode will not allow mixing of LSA formats. Different LSA formats could still be supported with multiple OSPFv3 instances and separate OSPFv3 routing domains. Additionally, a more flexible mode is provided in [Section 6.1](#), where both formats of LSA coexist. In order to facilitate backward compatibility, the OSPFv3 options field (as described in [Appendix A.2 of RFC 5340 \[OSPFV3\]](#)), will contain two additional options bits. The EL-bits will be used to indicate that the OSPFv3 router's level of Extended LSA support. An OSPFv3 router configured to support extended LSAs MUST set its options field EL-bits in OSPFv3 Hello and Database Description packets as follows:

B'00'

None - Extended LSAs are not originate nor used in the SPF calculation.

B'01'

MixedModeOriginateOnly - Both extended and non-extended LSAs are originated. Non-extended LSAs are used in the SPF computation.

B'10'

MixedModeOriginateSPF - Both extended and non-extended LSAs are originated. Extended LSAs are used in the SPF computation.

B'11'

Full - Only extended LSAs are originated and used in the SPF computation.





If Full is specified for ExtendedLSASupport, the OSPFv3 router MUST NOT form adjacencies with OSPFv3 Routers sending OSPFv3 Hello and Database Description packets with the options field EL-bits set to MixedModeOriginateOnly or None. Similarly, if MixModeOriginateSPF is specified for ExtendedLSASupport, the OSPFv3 router MUST NOT form adjacencies with OSPFv3 Routers sending OSPFv3 Hello and Database Description packets with the options field EL-bits set to None (B'00'). In this manner, OSPFv3 routers using new encodings can be completely isolated from those OSPFv3 routers depending on the [RFC 5340](#) encoding and not setting their options field EL-bits since the default setting indicates no support for extended LSAs.

```

          1               2
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
          The Options field

```

#### EL-bits

These bits indicate the level of Extended LSA support.

- B'00' - Extended LSAs are not originate nor used in the SPF calculation.
- B'01' - Both extended and non-extended LSAs are originated. Non-extended LSAs are used in the SPF computation.
- B'10' - Both extended and non-extended LSAs are originated. Extended LSAs are used in the SPF computation.
- B'11' - Only extended LSA are originated and used in the SPF computation.

#### Options Field EL-bits

The EL-bits will also be set in the LSA options field in Extended and Non-Extended LSAs. While the value of the EL-bits has no functional significance in the LSA options field, visibility of every OSPFv3 Router's extended LSA support is expected to be very useful for management and troubleshooting during the migration period.

### [6.1.](#) Extended LSA Mixed-Mode Backward Compatibility

An implementation MAY support configuration allowing a graceful transition from the non-extended (non-TLV-based) LSAs to the extended (TLV-based) LSAs in an OSPFv3 routing domain. In these routing domains, the OSPFv3 routers configured with a value of MixedModeOriginateOnly or MixedModeOriginateSPF for ExtendedLSASupport, (Appendix A), MUST originate both the extended and non-extended versions of the OSPFv3 LSAs described herein. For the purposes of Shortest Path First (SPF) computation, the non-



extended OSPFv3 LSAs are used for SPF computation when `MixedModeOriginateOnly` is configured and the extended LSAs are used when `MixedModeOriginateSPF` is specified. The extended LSAs MAY be used for functions other than routing computation as long as backward compatibility is specified in the documents specifying those functions.

In this manner, OSPFv3 routing domains utilizing the new encodings can be gradually migrated with a worst-case overhead cost of approximately doubling the number of LSAs in the routing domain. The transition within an OSPFv3 routing domain would progress as follows:

1. Configure OSPFv3 Router `ExtendedLSASupport` to `MixedModeOriginateOnly` so that routers originate the extended LSAs.
2. When all the OSPFv3 Routers have been reconfigured to `MixedModeOriginateOnly`, gradually reconfigure OSPFv3 Routers to use the extended LSAs by configuring `ExtendedLSASupport` to `MixedModeOriginateSPF`. This can be done on a small subset of OSPFv3 Routers and the route tables can be verified.
3. When all the OSPFv3 Routers have been reconfigured to `MixedModeOriginateSPF` and the routing has been verified, reconfigure OSPFv3 Routers to purge or simply not refresh the non-extended OSPFv3 LSA by configuring `ExtendedLSASupport` to `Full`.

In order to prevent OSPFv3 routing domain routing loops, the advertised metrics in the extended and non-extended OSPFv3 LSAs MUST be identical.

#### **6.1.1.1. Area Extended LSA Mixed-Mode Backward Compatibility**

An implementation MAY also support configuration allowing graceful transition from the non-extended LSAs to the extended LSAs within a single area. In these areas, the parameter `AreaExtendedLSASupport` (Appendix B) may be configured to take precedence over the global parameter `ExtendedLSASupport`. However, the `AreaExtendedLSASupport` will only apply to link and area scoped LSAs within the area and area based SPF calculations. The default is for the `AreaExtendedLSASupport` to be inherited from the `ExtendedLSASupport`. The configuration of `ExtendedLSASupport` will apply to AS-External LSAs even when `AreaExtendedLSASupport` takes precedence.

When performing a graceful restart [[GRACEFUL-RESTART](#)], an OSPFv3 router configured with `MixedModeOriginate` will use the non-extended OSPFv3 LSAs to determine whether or not the graceful restart has



completed successfully. Similarly, an OSPFv3 router configured with MixedModeOriginateSPF will use the extended LSAs. In other words, successful OSPFv3 graceful restart determination will follow the SPF calculation.

## **6.2. LSA TLV Processing Backward Compatibility**

This section defines the general rules for processing LSA TLVs. To ensure compatibility of future TLV-based LSA extensions, all implementations MUST adhere to these rules:

1. Unrecognized TLVs and sub-TLVs are ignored when parsing or processing Extended-LSAs.
2. Whether or not partial deployment of a given TLV is supported MUST be specified.
3. If partial deployment is not supported, mechanisms to ensure the corresponding feature are not deployed MUST be specified in the document defining the new TLV or sub-TLV.
4. If partial deployment is supported, backward compatibility and partial deployment MUST be specified in the document defining the new TLV or sub-TLV.

## **7. Security Considerations**

In general, extendible OSPFv3 LSAs are subject to the same security concerns as those described in [RFC 5340 \[OSPFV3\]](#). Additionally, implementations must assure that malformed TLV and sub-TLV permutations do not result in errors that cause hard OSPFv3 failures.

If there were ever a requirement to digitally sign OSPFv3 LSAs as described for OSPFv2 LSAs in [RFC 2154 \[OSPF-DIGITAL-SIGNATURE\]](#), the mechanisms described herein would greatly simplify the extension.

## **8. IANA Considerations**

This specification defines nine OSPFv3 Extended LSA types as described in [Section 2](#).

This specification also creates two registries OSPFv3 Extended-LSAs TLVs and sub-TLVs. The TLV and sub-TLV code-points in these registries are common to all Extended-LSAs and their respective definitions must define where they are applicable.

The OSPFv3 Extend-LSA TLV registry will define top-level TLVs for Extended-LSAs and should be placed in the existing OSPFv3 IANA



registry. New values can be allocated via IETF Consensus or IESG Approval.

Nine values are allocated by this specification:

- o 0 - Reserved
- o 1 - Router-Link TLV
- o 2 - Attached-Routers TLV
- o 3 - Inter-Area Prefix TLV
- o 4 - Inter-Area Router TLV
- o 5 - External Prefix TLV
- o 6 - Intra-Area Prefix TLV
- o 7 - IPv6 Link-Local Address TLV
- o 8 - IPv4 Link-Local Address TLV

The OSPFv3 Extend-LSA sub-TLV registry will define sub-TLVs at any level of nesting for Extended-LSAs and should be placed in the existing OSPFv3 IANA registry. New values can be allocated via IETF Consensus or IESG Approval.

Three values are allocated by this specification:

- o 0 - Reserved
- o 1 - Forwarding Address
- o 2 - Route Tag

The OSPFv3 Prefix Options registry will define a new code point for the N-bit. The value 0x20 is suggested.

## **9. References**

### **9.1. Normative References**

[GRACEFUL-RESTART]

Lindem, A. and P. Pillay-Esnault, "OSPFv3 Graceful Restart", [RFC 5187](#), June 2008.





- [NSSA] Murphy, P., "The OSPF Not-So-Stubby Area (NSSA) Option", [RFC 3101](#), January 2003.
- [OSPFV3] Coltun, R., Ferguson, D., Moy, J., and A. Lindem, "OSPF for IPv6", [RFC 5340](#), July 2008.
- [OSPFV3-AF] Lindem, A., Mirtorabi, S., Roy, A., Barnes, M., and R. Aggarwal, "Support of Address Families in OSPFv3", [RFC 5838](#), April 2010.
- [RFC-KEYWORDS] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [RFC 2119](#), March 1997.
- [TE] Katz, D., Yeung, D., and K. Kompella, "Traffic Engineering Extensions to OSPF", [RFC 3630](#), September 2003.

## **[9.2.](#) Informative References**

- [MT-OSPFV3] Mirtorabi, S. and A. Roy, "Multi-topology routing in OSPFv3 (MT-OSPFV3)", [draft-ietf-ospf-mt-ospfv3-03.txt](#) (work in progress), January 2008.
- [OSPF-DIGITAL-SIGNATURE] Murphy, S., Badger, M., and B. Wellington, "OSPF with Digital Signatures", [RFC 2154](#), June 1997.
- [SEGMENT-ROUTING] Psenak, P., Previdi, S., Filsfils, C., Gredler, H., Shakir, R., Henderickx, W., and J. Tantsura, "OSPF Extensions for Segment Routing", [draft-ietf-ospf-segment-routing-extensions-04.txt](#) (work in progress), February 2015.

## **[Appendix A.](#) Global Configuration Parameters**

An additional global configurable parameter will be added to the OSPFv3 protocol.

### **ExtendedLSASupport**

This is an enumeration type indicating the extent to which the OSPFv3 instance supports the TLV format described herein for Extended LSAs. The valid values for the enumeration are:



- \* None - Extended LSAs will not be originated or used in the SPF calculation. This is the default.
- \* MixedModeOriginateOnly - Both extended and non-extended LSAs will be originated. OSPFv3 adjacencies will be formed with OSPFv3 routers not supporting this specification. The non-extended LSAs are used for the SPF computation.
- \* MixedModeOriginateSPF - Both extended and non-extended LSAs will be originated. OSPFv3 adjacencies will be formed with OSPFv3 routers not supporting this specification. The extended LSAs are used for the SPF computation.
- \* Full - Extended LSAs will be originated and adjacencies will not be formed with OSPFv3 routers not supporting this specification. Only Extended LSAs will be originated.

## [Appendix B](#). Area Configuration Parameters

An additional area configurable parameter will be added to the OSPFv3 protocol.

### AreaExtendedLSASupport

This is an enumeration type indicating the extent to which the OSPFv3 area supports the TLV format described herein for Extended LSAs. The valid value for the enumeration are:

- \* InheritGlobal - The AreaExtendedLSASupport will be inherited from ExtendedLSASupport. This is the default.
- \* None - Non-extended LSAs will not be originated or used in the SPF calculation.
- \* MixedModeOriginateOnly - Both extended and non-extended link and area scoped LSAs will be originated. OSPFv3 adjacencies will be formed with OSPFv3 routers not supporting this specification. The non-extended LSAs are used for the SPF computation.
- \* MixedModeOriginateSPF - Both extended and non-extended link and area scoped LSAs will be originated. OSPFv3 adjacencies will be formed with OSPFv3 routers not supporting this specification. The extended LSAs are used for the area SPF computation.



- \* Full - Link and area scoped extended LSAs will be originated and adjacencies will not be formed with OSPFv3 routers not supporting this specification. Only Extended LSAs will be originated.

For regular areas, i.e., areas where AS scoped LSAs are flooded, configuring None or MixedModeOriginateOnly for AreaExtendedLSASupport when Full is specified for ExtendedLSASupport is contradictory and MAY be prohibited by the implementation.

#### Authors' Addresses

Acee Lindem  
Cisco Systems  
301 Midenhall Way  
Cary, NC 27513  
USA

Email: [acee@cisco.com](mailto:acee@cisco.com)

Sina Mirtorabi  
Cisco Systems  
170 Tasman Drive  
San Jose, CA 95134  
USA

Email: [sina@cisco.com](mailto:sina@cisco.com)

Abhay Roy  
Cisco Systems  
170 Tasman Drive  
San Jose, CA 95134  
USA

Email: [akr@cisco.com](mailto:akr@cisco.com)

Fred Baker  
Cisco Systems  
Santa Barbara, CA 93117  
USA

Email: [fred@cisco.com](mailto:fred@cisco.com)

