

Internet
Internet-Draft
Intended status: Informational
Expires: September 14, 2017

D. Yeung
Arrcus
Y. Qu
Huawei
J. Zhang
Juniper Networks
I. Chen
Jabil Circuit
A. Lindem
Cisco Systems
March 13, 2017

Yang Data Model for OSPF SR (Segment Routing) Protocol
draft-ietf-ospf-sr-yang-01

Abstract

This document defines a YANG data model that can be used to configure and manage OSPF Segment Routing.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 14, 2017.

Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Overview	2
1.1.	Requirements Language	2
2.	OSPF Segment Routing	2
3.	OSPF Segment Routing Yang Module	10
4.	Security Considerations	25
5.	Acknowledgements	25
6.	References	25
6.1.	Normative References	25
6.2.	Informative References	27
Appendix A.	Contributors' Addresses	28
	Authors' Addresses	28

1. Overview

YANG [[RFC6020](#)] [[RFC7950](#)] is a data definition language used to define the contents of a conceptual data store that allows networked devices to be managed using NETCONF [[RFC6241](#)]. YANG is proving relevant beyond its initial confines, as bindings to other interfaces (e.g., ReST) and encodings other than XML (e.g., JSON) are being defined. Furthermore, YANG data models can be used as the basis for implementation of other interfaces, such as CLI and programmatic APIs.

This document defines a YANG data model that can be used to configure and manage OSPF Segment Routing and it is an augmentation to the OSPF YANG data model.

1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

2. OSPF Segment Routing

This document defines a model for OSPF Segment Routing feature. It is an augmentation of the OSPF base model.

The OSPF SR YANG module requires support for the base segment routing module [[I-D.ietf-spring-sr-yang](#)], which defines the global segment routing configuration independent of any specific routing protocol.

Yeung, et al.

Expires September 14, 2017

[Page 2]

configuration, and support of OSPF base model [I-D.ietf-ospf-yang] which defines basic OSPF configuration and state.

```

module: ietf-ospf-sr
  augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/ospf:ospf/ospf:instance:
      +-rw segment-routing
        | +-rw enabled? boolean
        | +-rw bindings
        |   +-rw advertise
        |     | +-rw policies* string
        |     +-rw receive? boolean
      +-rw protocol-srgb {sr:protocol-srgb}?
        +-rw srgb* [lower-bound upper-bound]
          +-rw lower-bound uint32
          +-rw upper-bound uint32
  augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/ospf:ospf
      /ospf:instance/ospf:areas/ospf:area
        /ospf:interfaces/ospf:interface:
          +-rw segment-routing
            +-rw adjacency-sid
              +-rw advertise-adj-group-sid* [group-id]
              | +-rw group-id uint32
              +-rw advertise-protection? enumeration
  augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/ospf:ospf
      /ospf:instance/ospf:areas/ospf:area
        /ospf:interfaces/ospf:interface/ospf:fast-reroute:
          +-rw ti-lfa {ti-lfa}?
            +-rw enable? boolean
  augment /rt:routing-state/rt:control-plane-protocols
    /rt:control-plane-protocol/ospf:ospf/ospf:instance:
      +-ro segment-routing
        | +-ro enabled? boolean
        | +-ro bindings
        |   +-ro advertise
        |     | +-ro policies* string
        |     +-ro receive? boolean
      +-ro protocol-srgb {sr:protocol-srgb}?
        +-ro srgb* [lower-bound upper-bound]
          +-ro lower-bound uint32
          +-ro upper-bound uint32
  augment /rt:routing-state/rt:control-plane-protocols
    /rt:control-plane-protocol/ospf:ospf
      /ospf:instance/ospf:areas/ospf:area
        /ospf:interfaces/ospf:interface:
          +-ro segment-routing

```

Yeung, et al.

Expires September 14, 2017

[Page 3]

```

    +-+ro adjacency-sid
    +-+ro advertise-adj-group-sid* [group-id]
    |   +-+ro group-id      uint32
    |   +-+ro advertise-protection?      enumeration
augment /rt:routing-state/rt:control-plane-protocols
    /rt:control-plane-protocol/ospf:ospf/ospf:instance
    /ospf:areas/ospf:area/ospf:interfaces/ospf:interface
    /ospf:database/ospf:link-scope-lsa-type
    /ospf:link-scope-lsas/ospf:link-scope-lsa/ospf:version
    /ospfv2/ospfv2/ospfv2/ospf:body/ospf:opaque
    /ospf:extended-prefix-tlvs/ospf:extended-prefix-tlv:
    +-+ro prefix-sid-sub-tlvs
    |   +-+ro prefix-sid-sub-tlv*
    |       +-+ro flags?          bits
    |       +-+ro mt-id?         uint8
    |       +-+ro algorithm?     uint8
    |       +-+ro sid?          uint32
    +-+ro sid-binding-sub-tlvs
        +-+ro sid-binding-sub-tlv*
            +-+ro flags?          bits
            +-+ro mt-id?         uint8
            +-+ro weight?        uint8
            +-+ro sid-sub-tlv
                |   +-+ro sid?          uint32
            +-+ro ero-metric-sub-tlv
                |   +-+ro metric?      uint32
            +-+ro ipv4-ero-sub-tlv
                |   +-+ro flags?          bits
                |   +-+ro ipv4-address?    inet:ipv4-address
            +-+ro unnumbered-ero-sub-tlv
                |   +-+ro flags?          bits
                |   +-+ro router-id?      yang:dotted-quad
                |   +-+ro interface-id?    uint32
            +-+ro ipv4-backup-ero-sub-tlv
                |   +-+ro flags?          bits
                |   +-+ro ipv4-address?    inet:ipv4-address
            +-+ro unnumbered-backup-ero-sub-tlv
                +-+ro flags?          bits
                +-+ro router-id?      yang:dotted-quad
                +-+ro interface-id?    uint32
augment /rt:routing-state/rt:control-plane-protocols
    /rt:control-plane-protocol/ospf:ospf/ospf:instance
    /ospf:areas/ospf:area/ospf:database
    /ospf:area-scope-lsa-type/ospf:area-scope-lsas
    /ospf:area-scope-lsa/ospf:version/ospfv2
    /ospfv2/ospfv2/ospf:body/ospf:opaque
    /ospf:extended-prefix-tlvs/ospf:extended-prefix-tlv:
    +-+ro prefix-sid-sub-tlvs

```

Yeung, et al.

Expires September 14, 2017

[Page 4]

```

|   +-+ro prefix-sid-sub-tlv*
|   +-+ro flags?          bits
|   +-+ro mt-id?          uint8
|   +-+ro algorithm?      uint8
|   +-+ro sid?            uint32
+-+ro sid-binding-sub-tlvs
    +-+ro sid-binding-sub-tlv*
        +-+ro flags?          bits
        +-+ro mt-id?          uint8
        +-+ro weight?         uint8
        +-+ro sid-sub-tlv
            |   +-+ro sid?  uint32
        +-+ro ero-metric-sub-tlv
            |   +-+ro metric?  uint32
        +-+ro ipv4-ero-sub-tlv
            |   +-+ro flags?      bits
            |   +-+ro ipv4-address?  inet:ipv4-address
        +-+ro unnumbered-ero-sub-tlv
            |   +-+ro flags?      bits
            |   +-+ro router-id?  yang:dotted-quad
            |   +-+ro interface-id?  uint32
        +-+ro ipv4-backup-ero-sub-tlv
            |   +-+ro flags?      bits
            |   +-+ro ipv4-address?  inet:ipv4-address
        +-+ro unnumbered-backup-ero-sub-tlv
            +-+ro flags?          bits
            +-+ro router-id?      yang:dotted-quad
            +-+ro interface-id?  uint32
augment /rt:routing-state/rt:control-plane-protocols
    /rt:control-plane-protocol/ospf:ospf/ospf:instance
    /ospf:database/ospf:as-scope-lsa-type/ospf:as-scope-lsas
    /ospf:as-scope-lsa/ospf:version/ospf:ospfv2/ospf:ospfv2
    /ospf:body/ospf:opaque/ospf:extended-prefix-tlvs
    /ospf:extended-prefix-tlv:
        +-+ro prefix-sid-sub-tlvs
            |   +-+ro prefix-sid-sub-tlv*
            |   +-+ro flags?          bits
            |   +-+ro mt-id?          uint8
            |   +-+ro algorithm?      uint8
            |   +-+ro sid?            uint32
        +-+ro sid-binding-sub-tlvs
            +-+ro sid-binding-sub-tlv*
                +-+ro flags?          bits
                +-+ro mt-id?          uint8
                +-+ro weight?         uint8
                +-+ro sid-sub-tlv
                    |   +-+ro sid?  uint32
                +-+ro ero-metric-sub-tlv

```

Yeung, et al.

Expires September 14, 2017

[Page 5]

```

    |   +-+ro metric?      uint32
    +-+ro ipv4-ero-sub-tlv
    |   +-+ro flags?       bits
    |   +-+ro ipv4-address?  inet:ipv4-address
    +-+ro unnumbered-ero-sub-tlv
    |   +-+ro flags?       bits
    |   +-+ro router-id?    yang:dotted-quad
    |   +-+ro interface-id? uint32
    +-+ro ipv4-backup-ero-sub-tlv
    |   +-+ro flags?       bits
    |   +-+ro ipv4-address?  inet:ipv4-address
    +-+ro unnumbered-backup-ero-sub-tlv
        +-+ro flags?       bits
        +-+ro router-id?    yang:dotted-quad
        +-+ro interface-id? uint32
augment /rt:routing-state/rt:control-plane-protocols
    /rt:control-plane-protocol/ospf:ospf/ospf:instance
    /ospf:areas/ospf:area/ospf:database
    /ospf:area-scope-lsa-type/ospf:area-scope-lsas
    /ospf:area-scope-lsa/ospf:version/ospf:ospfv2
    /ospf:ospfv2/ospf:body/ospf:opaque
    /ospf:extended-link-tlvs/ospf:extended-link-tlv:
    +-+ro adj-sid-sub-tlvs
    |   +-+ro adj-sid-sub-tlv*
    |   +-+ro flags?       bits
    |   +-+ro mt-id?       uint8
    |   +-+ro weight?      uint8
    |   +-+ro sid?         uint32
    +-+ro lan-adj-sid-sub-tlvs
        +-+ro lan-adj-sid-sub-tlv*
            +-+ro flags?       bits
            +-+ro mt-id?       uint8
            +-+ro weight?      uint8
            +-+ro neighbor-router-id? yang:dotted-quad
            +-+ro sid?         uint32
augment /rt:routing-state/rt:control-plane-protocols
    /rt:control-plane-protocol/ospf:ospf/ospf:instance
    /ospf:areas/ospf:area/ospf:interfaces/ospf:interface
    /ospf:database/ospf:link-scope-lsa-type
    /ospf:link-scope-lsas/ospf:link-scope-lsa
    /ospf:version/ospf:ospfv2/ospf:ospfv2
    /ospf:body/ospf:opaque:
    +-+ro extended-prefix-range-tlvs
    |   +-+ro extended-prefix-range-tlv*
    |   +-+ro range-size?      uint16
    |   +-+ro flags?          bits
    |   +-+ro prefix?         inet:ip-prefix
    |   +-+ro prefix-sid-sub-tlvs

```

Yeung, et al.

Expires September 14, 2017

[Page 6]

```

    |   +-+ro prefix-sid-sub-tlv*
    |   |   +-+ro flags?          bits
    |   |   +-+ro mt-id?         uint8
    |   |   +-+ro algorithm?     uint8
    |   |   +-+ro sid?           uint32
    +-+ro sid-binding-sub-tlvs
    |   +-+ro sid-binding-sub-tlv*
    |   |   +-+ro flags?          bits
    |   |   +-+ro mt-id?         uint8
    |   |   +-+ro weight?        uint8
    |   |   +-+ro sid-sub-tlv
    |   |   |   +-+ro sid?         uint32
    |   |   +-+ro ero-metric-sub-tlv
    |   |   |   +-+ro metric?      uint32
    |   |   +-+ro ipv4-ero-sub-tlv
    |   |   |   +-+ro flags?          bits
    |   |   |   +-+ro ipv4-address?   inet:ipv4-address
    |   |   +-+ro unnumbered-ero-sub-tlv
    |   |   |   +-+ro flags?          bits
    |   |   |   +-+ro router-id?     yang:dotted-quad
    |   |   |   +-+ro interface-id?  uint32
    |   |   +-+ro ipv4-backup-ero-sub-tlv
    |   |   |   +-+ro flags?          bits
    |   |   |   +-+ro ipv4-address?   inet:ipv4-address
    |   |   +-+ro unnumbered-backup-ero-sub-tlv
    |   |   |   +-+ro flags?          bits
    |   |   |   +-+ro router-id?     yang:dotted-quad
    |   |   |   +-+ro interface-id?  uint32
    +-+ro unknown-tlvs
    |   +-+ro unknown-tlv*
    |   |   +-+ro type?           uint16
    |   |   +-+ro length?          uint16
    |   |   +-+ro value?           yang:hex-string
    +-+ro sr-algorithm-tlv
    |   +-+ro sr-algorithm*      uint8
    +-+ro sid-range-tlvs
    |   +-+ro sid-range-tlv*
    |   |   +-+ro range-size?     ospf:uint24
    |   |   +-+ro sid-sub-tlv
    |   |   |   +-+ro sid?         uint32
augment /rt:routing-state/rt:control-plane-protocols
    /rt:control-plane-protocol/ospf:ospf/ospf:instance
    /ospf:areas/ospf:area/ospf:database
    /ospf:area-scope-lsa-type/ospf:area-scope-lsas
    /ospf:area-scope-lsa/ospf:version/ospf:ospfv2
    /ospf:ospfv2/ospf:body/ospf:opaque:
    +-+ro extended-prefix-range-tlvs
    |   +-+ro extended-prefix-range-tlv*

```

Yeung, et al.

Expires September 14, 2017

[Page 7]

```

|   +-+ro range-size?          uint16
|   +-+ro flags?              bits
|   +-+ro prefix?             inet:ip-prefix
|   +-+ro prefix-sid-sub-tlvs
|     |   +-+ro prefix-sid-sub-tlv*
|     |     +-+ro flags?          bits
|     |     +-+ro mt-id?         uint8
|     |     +-+ro algorithm?    uint8
|     |     +-+ro sid?          uint32
|   +-+ro sid-binding-sub-tlvs
|     |   +-+ro sid-binding-sub-tlv*
|     |       +-+ro flags?        bits
|     |       +-+ro mt-id?        uint8
|     |       +-+ro weight?       uint8
|     |       +-+ro sid-sub-tlv
|     |         |   +-+ro sid?  uint32
|     |       +-+ro ero-metric-sub-tlv
|     |         |   +-+ro metric?  uint32
|     |       +-+ro ipv4-ero-sub-tlv
|     |         |   +-+ro flags?    bits
|     |         |   +-+ro ipv4-address?  inet:ipv4-address
|     |       +-+ro unnumbered-ero-sub-tlv
|     |         |   +-+ro flags?    bits
|     |         |   +-+ro router-id?  yang:dotted-quad
|     |         |   +-+ro interface-id?  uint32
|     |       +-+ro ipv4-backup-ero-sub-tlv
|     |         |   +-+ro flags?    bits
|     |         |   +-+ro ipv4-address?  inet:ipv4-address
|     |       +-+ro unnumbered-backup-ero-sub-tlv
|     |         |   +-+ro flags?    bits
|     |         |   +-+ro router-id?  yang:dotted-quad
|     |         |   +-+ro interface-id?  uint32
|   +-+ro unknown-tlvs
|     |   +-+ro unknown-tlv*
|       |     +-+ro type?      uint16
|       |     +-+ro length?    uint16
|       |     +-+ro value?      yang:hex-string
|   +-+ro sr-algorithm-tlv
|     |   +-+ro sr-algorithm*  uint8
|   +-+ro sid-range-tlvs
|     |   +-+ro sid-range-tlv*
|       |         +-+ro range-size?  ospf:uint24
|       |         +-+ro sid-sub-tlv
|         |           +-+ro sid?  uint32
augment /rt:routing-state/rt:control-plane-protocols
  /rt:control-plane-protocol/ospf:ospf/ospf:instance
  /ospf:database/ospf:as-scope-lsa-type
  /ospf:as-scope-lsas/ospf:as-scope-lsa/ospf:version

```

Yeung, et al.

Expires September 14, 2017

[Page 8]

```
/ospfv2/ospfv2/ospfv2/ospf:body/ospf:opaque:  
++-ro extended-prefix-range-tlvs  
| +-+ro extended-prefix-range-tlv*  
| | +-ro range-size?          uint16  
| | +-ro flags?              bits  
| | +-ro prefix?             inet:ip-prefix  
| | +-ro prefix-sid-sub-tlvs  
| | | +-+ro prefix-sid-sub-tlv*  
| | | | +-ro flags?          bits  
| | | | +-ro mt-id?           uint8  
| | | | +-ro algorithm?      uint8  
| | | | +-ro sid?             uint32  
| | +-ro sid-binding-sub-tlvs  
| | | +-+ro sid-binding-sub-tlv*  
| | | | +-ro flags?          bits  
| | | | +-ro mt-id?           uint8  
| | | | +-ro weight?          uint8  
| | | +-ro sid-sub-tlv  
| | | | +-ro sid?             uint32  
| | | +-ro ero-metric-sub-tlv  
| | | | +-ro metric?          uint32  
| | | +-ro ipv4-ero-sub-tlv  
| | | | +-ro flags?          bits  
| | | | +-ro ipv4-address?    inet:ipv4-address  
| | | +-ro unnumbered-ero-sub-tlv  
| | | | +-ro flags?          bits  
| | | | +-ro router-id?       yang:dotted-quad  
| | | | +-ro interface-id?    uint32  
| | | +-ro ipv4-backup-ero-sub-tlv  
| | | | +-ro flags?          bits  
| | | | +-ro ipv4-address?    inet:ipv4-address  
| | | +-ro unnumbered-backup-ero-sub-tlv  
| | | | +-ro flags?          bits  
| | | | +-ro router-id?       yang:dotted-quad  
| | | | +-ro interface-id?    uint32  
| | +-ro unknown-tlvs  
| | | +-+ro unknown-tlv*  
| | | | +-ro type?            uint16  
| | | | +-ro length?          uint16  
| | | | +-ro value?           yang:hex-string  
| +-+ro sr-algorithm-tlv  
| | +-ro sr-algorithm*      uint8  
| +-+ro sid-range-tlvs  
| | +-+ro sid-range-tlv*  
| | | +-ro range-size?      ospfv2:uint24  
| | | +-ro sid-sub-tlv  
| | | | +-ro sid?             uint32
```

Yeung, et al.

Expires September 14, 2017

[Page 9]

3. OSPF Segment Routing Yang Module

```
<CODE BEGINS> file "ietf-ospf-sr@2017-03-13.yang"
module ietf-ospf-sr {
    namespace "urn:ietf:params:xml:ns:yang:ietf-ospf-sr";

    prefix ospf-sr;

    import ietf-inet-types {
        prefix "inet";
    }

    import ietf-yang-types {
        prefix "yang";
    }

    import ietf-routing {
        prefix "rt";
    }
    import ietf-segment-routing-common {
        prefix "sr-cmn";
    }
    import ietf-segment-routing {
        prefix "sr";
    }
    import ietf-ospf {
        prefix "ospf";
    }

organization
    "Cisco Systems
     170 West Tasman Drive
     San Jose, CA 95134-1706
     USA";

contact
    "WG Web: <http://tools.ietf.org/wg/ospf/>
     WG List: <mailto:ospf@ietf.org>

     WG Chair: Acee Lindem
                 <mailto:acee@cisco.com>

     WG Chair: Abhay Roy
                 <mailto:akr@cisco.com>

     Editor: Derek Yeung
                 <mailto:derek@arccus.com>
     Author: Derek Yeung
```

Yeung, et al.

Expires September 14, 2017

[Page 10]

```

        <mailto:derek@arrcus.com>
Author: Yingzhen Qu
        <mailto:yingzhen.qu@huawei.com>
Author: Acee Lindem
        <mailto:acee@cisco.com>
Author: Jeffrey Zhang
        <mailto:zzhang@juniper.net>
Author: Ing-Wher Chen
        <mailto:ing-wher_chen@jabil.com>
Author: Greg Hankins
        <mailto:greg.hankins@alcatel-lucent.com>";

```

description

"This YANG module defines the generic configuration and operational state for OSPF Segment Routing, which is common across all of the vendor implementations. It is intended that the module will be extended by vendors to define vendor-specific OSPF Segment Routing configuration and operational parameters and policies.

Terms and Acronyms

OSPF (ospf): Open Shortest Path First

IP (ip): Internet Protocol

IPv4 (ipv4): Internet Protocol Version 4

IPv6 (ipv6): Internet Protocol Version 6
";

```

revision 2017-03-13 {
    description
        "* Add p-flag in adj-sid sub-tlv.";
    reference
        "RFC XXXX: A YANG Data Model for OSPF Segment Routing.";
}
```

```

revision 2016-10-31 {
    description
        "* Update authors information.
         * Add import of ietf-segment-routing-common module.";
    reference
        "RFC XXXX: A YANG Data Model for OSPF Segment Routing.";
}
```

```

revision 2016-07-07 {
    description
```

Yeung, et al.

Expires September 14, 2017

[Page 11]

```
    /* Change routing-protocol to control-plane-protocol.*/;
reference
    "RFC XXXX: A YANG Data Model for OSPF Segment Routing.";
}

revision 2016-03-20 {
    description
        /* Remove routing-instance.*/;
reference
    "RFC XXXX: A YANG Data Model for OSPF Segment Routing.";
}

revision 2015-10-19 {
    description
        /* Add per-protocol SRGB support.
         * Editorial changes.*/;
reference
    "RFC XXXX: A YANG Data Model for OSPF Segment Routing.";
}

revision 2015-09-02 {
    description
        /* Author list update.
         * Editorial changes.*/;
reference
    "RFC XXXX: A YANG Data Model for OSPF Segment Routing.";
}

revision 2015-07-06 {
    description
        "Initial revision.*/;
reference
    "RFC XXXX: A YANG Data Model for OSPF Segment Routing.";
}

feature ti-lfa {
    description
        "Topology-Independent Loop-Free Alternate (TI-LFA)
         computation using segment routing.";
}

/* Configuration */

augment "/rt:routing/rt:control-plane-protocols"
    + "/rt:control-plane-protocol/ospf:ospf/ospf:instance" {
when ".../rt:type = 'ospf:ospfv2' or "
    + ".../rt:type = 'ospf:ospfv3'" {
    description
```

Yeung, et al.

Expires September 14, 2017

[Page 12]

```

        "This augments the OSPF routing protocol when used.";
    }
    description
      "This augments the OSPF protocol configuration
       with segment routing.";
  uses sr:controlplane-cfg;
  container protocol-srgb {
    if-feature sr:protocol-srgb;
    uses sr-cmn:srgb-cfg;
    description
      "Per-protocol SRGB.";
  }
}

augment "/rt:routing/rt:control-plane-protocols/"
  + "rt:control-plane-protocol/ospf:ospf/ospf:instance/"
  + "ospf:areas/ospf:area/ospf:interfaces/ospf:interface" {
when ".../.../.../.../.../rt:type = 'ospf:ospfv2' or "
  + ".../.../.../.../.../rt:type = 'ospf:ospfv3'" {
  description
    "This augments the OSPF interface configuration
     when used.";
}
  description
    "This augments the OSPF protocol interface
     configuration with segment routing.';

  uses sr:igp-interface-cfg;
}

augment "/rt:routing/rt:control-plane-protocols/"
  + "rt:control-plane-protocol/ospf:ospf/ospf:instance/"
  + "ospf:areas/ospf:area/ospf:interfaces/ospf:interface/"
  + "ospf:fast-reroute" {
when ".../.../.../.../.../rt:type = 'ospf:ospfv2' or "
  + ".../.../.../.../.../rt:type = 'ospf:ospfv3'" {
  description
    "This augments the OSPF routing protocol when used.";
}
  description
    "This augments the OSPF protocol IP-FRR with TI-LFA.";

  container ti-lfa {
    if-feature ti-lfa;
    leaf enable {
      type boolean;
      description
        "Enables TI-LFA computation.";
  }
}

```

Yeung, et al.

Expires September 14, 2017

[Page 13]

```

    }
    description
      "Topology Independent Loop Free Alternate
       (TI-LFA) support.";
  }
}

/* Operational states */

augment "/rt:routing-state/"
  + "rt:control-plane-protocols/rt:control-plane-protocol/"
  + "ospf:ospf/ospf:instance" {
when ".../rt:type = 'ospf:ospfv2' or "
  + ".../rt:type = 'ospf:ospfv3'" {
  description
    "This augments the OSPF routing protocol when used.";
}
  description
    "This augments the OSPF protocol operational state
     with segment routing.";
  uses sr:controlplane-cfg;
  container protocol-srgb {
    if-feature sr:protocol-srgb;
    uses sr-cmn:srgb-cfg;
    description
      "Per-protocol SRGB.";
  }
}

augment "/rt:routing-state/"
  + "rt:control-plane-protocols/rt:control-plane-protocol/"
  + "ospf:ospf/ospf:instance/ospf:areas/ospf:area/"
  + "ospf:interfaces/ospf:interface" {
when ".../.../.../.../rt:type = 'ospf:ospfv2' or "
  + ".../.../.../.../rt:type = 'ospf:ospfv3'" {
  description
    "This augments the OSPF routing protocol when used.";
}
  description
    "This augments the OSPF protocol interface
     operational state with segment routing.";

  uses sr:igp-interface-cfg;
}

/* Database */

grouping sid-sub-tlv {

```

Yeung, et al.

Expires September 14, 2017

[Page 14]

```
description "SID/Label sub-TLV grouping.";
container sid-sub-tlv {
    description
        "Used to advertise the SID/Label associated with a
         prefix or adjacency.";
    leaf sid {
        type uint32;
        description
            "Segment Identifier (SID) - A 20 bit label or
             32 bit SID.";
    }
}
}

grouping prefix-sid-sub-tlvs {
    description "Prefix Segment ID (SID) sub-TLVs.";
    container prefix-sid-sub-tlvs{
        description "Prefix SID sub-TLV.";
        list prefix-sid-sub-tlv {
            description "Prefix SID sub-TLV.";
            leaf flags {
                type bits {
                    bit NP {
                        description
                            "No-PHP flag.";
                    }
                    bit M {
                        description
                            "Mapping server flag.";
                    }
                    bit E {
                        description
                            "Explicit-NUL flag.";
                    }
                    bit V {
                        description
                            "Value/Index flag.";
                    }
                    bit L {
                        description
                            "Local flag.";
                    }
                }
            }
            description "Segment Identifier (SID) Flags.";
        }
        leaf mt-id {
            type uint8;
            description "Multi-topology ID.";
```

Yeung, et al.

Expires September 14, 2017

[Page 15]

```
    }
    leaf algorithm {
        type uint8;
        description
            "The algorithm associated with the prefix-SID.";
    }
    leaf sid {
        type uint32;
        description "An index or label.";
    }
}
}

grouping sid-binding-sub-tlvs {
    description "SID/Label binding sub-TLV grouping.";
    container sid-binding-sub-tlvs {
        description "SID binding sub-TLVs.";
        list sid-binding-sub-tlv {
            description "SID binding sub-TLV.";
            leaf flags {
                type bits {
                    bit M {
                        description
                            "Mirroring context flag.";
                    }
                }
                description "Flags.";
            }
            leaf mt-id {
                type uint8;
                description "Multi-topology ID.";
            }
            leaf weight {
                type uint8;
                description "Weight for load-balancing purposes.";
            }
        }
        uses sid-sub-tlv;

        container ero-metric-sub-tlv {
            description
                "The cost of an Explicit Route Object (ERO) path.";
            leaf metric {
                type uint32;
                description "The aggregate IGP or TE path cost.";
            }
        }
    }
}
```

Yeung, et al.

Expires September 14, 2017

[Page 16]

```
container ipv4-ero-sub-tlv {
    description
        "The IPv4 ERO sub-TLV describes a path segment
         using IPv4 address.";
    leaf flags {
        type bits {
            bit L {
                description
                    "If set, then the segment path is designated as
                     'loose'. Otherwise, the path is 'strict'.";
            }
        }
        description "ERO Flags.";
    }
    leaf ipv4-address {
        type inet:ipv4-address;
        description "The address of the explicit route hop.";
    }
}
container unnumbered-ero-sub-tlv {
    description "The unnumbered interface ID ERO sub-TLV
                 describes a path segment that includes an
                 unnumbered interface.";
    leaf flags {
        type bits {
            bit L {
                description
                    "If set, then the segment path is designated as
                     'loose'. Otherwise as 'strict'.";
            }
        }
        description "ERO Flags.";
    }
    leaf router-id {
        type yang:dotted-quad;
        description "Router-id of the next-hop.";
    }
    leaf interface-id {
        type uint32;
        description
            "The identifier assigned to the link by the
             router specified by the router-id.";
    }
}
container ipv4-backup-ero-sub-tlv {
    description
        "The IPv4 backup ERO sub-TLV describes a path
         segment using IPv4 address.";
```

Yeung, et al.

Expires September 14, 2017

[Page 17]

```

leaf flags {
    type bits {
        bit L {
            description
                "If set, then the segment path is designated as
                'loose'. Otherwise as 'strict'.";
        }
    }
    description "Flags.";
}
leaf ipv4-address {
    type inet:ipv4-address;
    description "The address of the explicit route hop.";
}
container unnumbered-backup-ero-sub-tlv {
    description
        "The unnumbered interface ID backup ERO sub-TLV
        describes a path segment that includes an
        unnumbered interface.";
    leaf flags {
        type bits {
            bit L {
                description
                    "If set, then the segment path is designated as
                    'loose'. Otherwise, the path is 'strict'.";
            }
        }
        description "Flags.";
    }
    leaf router-id {
        type yang:dotted-quad;
        description "Router-id of the next-hop.";
    }
    leaf interface-id {
        type uint32;
        description
            "The identifier assigned to the link by the
            router specified by the router-id.";
    }
}
grouping extended-prefix-range-tlvs {
    description "Extended prefix range TLV grouping.";
}

```

Yeung, et al.

Expires September 14, 2017

[Page 18]

```
container extended-prefix-range-tlvs {
    description "The list of range of prefixes.";
    list extended-prefix-range-tlv { //type=2?
        description "The range of prefixes.";
        leaf range-size {
            type uint16;
            description "The number of prefixes covered by the
                        advertisement.";
        }
        leaf flags {
            type bits {
                bit IA {
                    description
                        "Inter-Area flag.";
                }
            }
            description "Flags.";
        }
        leaf prefix {
            type inet:ip-prefix;
            description "Address prefix.";
        }
        uses prefix-sid-sub-tlvs;
        uses sid-binding-sub-tlvs;
        uses ospf:unknown-tlvs;
    }
}
}

grouping sr-algorithm-tlv {
    description "SR algorithm TLV grouping.";
    container sr-algorithm-tlv {
        description "All SR algorithm TLVs.";
        leaf-list sr-algorithm {
            type uint8;
            description
                "The Segment Routing (SR) algorithms that the router is
                currently using.";
        }
    }
}

grouping sid-range-tlvs {
    description "SID Range TLV grouping.";
    container sid-range-tlvs {
        description "List of SID range TLVs.";
        list sid-range-tlv {
            description "SID range TLV.";
```

Yeung, et al.

Expires September 14, 2017

[Page 19]

```

leaf range-size {
    type ospf:uint24;
    description "The SID range.";
}
uses sid-sub-tlv;
}
}

augment "/rt:routing-state/"
+ "rt:control-plane-protocols/rt:control-plane-protocol/"
+ "ospf:ospf/ospf:instance/ospf:areas/ospf:area/"
+ "ospf:interfaces/ospf:interface/ospf:database/"
+ "ospf:link-scope-lsa-type/ospf:link-scope-lsas/"
+ "ospf:link-scope-lsa/ospf:version/ospf:ospfv2/"
+ "ospf:ospfv2/ospf:body/ospf:opaque/"
+ "ospf:extended-prefix-tlvs/ospf:extended-prefix-tlv" {
when ".../.../.../.../.../.../.../.../.../.../.../.../..."
+ "rt:type = 'ospf:ospfv2'" {
description
    "This augmentation is only valid for OSPFv2.";
}
description
    "SR specific TLVs for OSPFv2 extended prefix TLV
     in type 9 opaque LSA.";
uses prefix-sid-sub-tlvs;
uses sid-binding-sub-tlvs;
}

augment "/rt:routing-state/"
+ "rt:control-plane-protocols/rt:control-plane-protocol/"
+ "ospf:ospf/ospf:instance/ospf:areas/"
+ "ospf:area/ospf:database/"
+ "ospf:area-scope-lsa-type/ospf:area-scope-lsas/"
+ "ospf:area-scope-lsa/ospf:version/ospf:ospfv2/"
+ "ospf:ospfv2/ospf:body/ospf:opaque/"
+ "ospf:extended-prefix-tlvs/ospf:extended-prefix-tlv" {
when ".../.../.../.../.../.../.../.../.../.../..."
+ "rt:type = 'ospf:ospfv2'" {
description
    "This augmentation is only valid for OSPFv2.";
}
description
    "SR specific TLVs for OSPFv2 extended prefix TLV
     in type 10 opaque LSA.";
uses prefix-sid-sub-tlvs;
uses sid-binding-sub-tlvs;
}

```

Yeung, et al.

Expires September 14, 2017

[Page 20]

```

augment "/rt:routing-state/"
  + "rt:control-plane-protocols/rt:control-plane-protocol/"
  + "ospf:ospf/ospf:instance/ospf:database/"
  + "ospf:as-scope-lsa-type/ospf:as-scope-lsas/"
  + "ospf:as-scope-lsa/ospf:version/ospf:ospfv2/"
  + "ospf:ospfv2/ospf:body/ospf:opaque/"
  + "ospf:extended-prefix-tlvs/ospf:extended-prefix-tlv" {
when ".../.../.../.../.../.../.../.../.../..."
  + "rt:type = 'ospf:ospfv2'" {
description
  "This augmentation is only valid for OSPFv2.";
}
description
  "SR specific TLVs for OSPFv2 extended prefix TLV
  in type 11 opaque LSA.";
uses prefix-sid-sub-tlvs;
uses sid-binding-sub-tlvs;
}

augment "/rt:routing-state/"
  + "rt:control-plane-protocols/rt:control-plane-protocol/"
  + "ospf:ospf/ospf:instance/ospf:areas/"
  + "ospf:area/ospf:database/"
  + "ospf:area-scope-lsa-type/ospf:area-scope-lsas/"
  + "ospf:area-scope-lsa/ospf:version/ospf:ospfv2/"
  + "ospf:ospfv2/ospf:body/ospf:opaque/"
  + "ospf:extended-link-tlvs/ospf:extended-link-tlv" {
when ".../.../.../.../.../.../.../.../.../..."
  + "rt:type = 'ospf:ospfv2'" {
description
  "This augmentation is only valid for OSPFv2.";
}
description
  "SR specific TLVs for OSPFv2 extended link TLV
  in type 10 opaque LSA.";

container adj-sid-sub-tlvs {
  description "Adjacency SID optional sub-TLVs.";
  list adj-sid-sub-tlv {
    description "List of Adjacency SID sub-TLVs.";
    leaf flags {
      type bits {
        bit B {
          description
            "Backup flag.";
        }
        bit V {
          description
        }
      }
    }
  }
}

```

Yeung, et al.

Expires September 14, 2017

[Page 21]

```

        "Value/Index flag.";
    }
    bit L {
        description
        "Local/Global flag.";
    }
    bit G {
        description
        "Group flag.";
    }
    bit P {
        description
        "Persistent flag.";
    }
}
description "Flags.";

leaf mt-id {
    type uint8;
    description "Multi-topology ID.";
}
leaf weight {
    type uint8;
    description "Weight used for load-balancing.";
}
leaf sid {
    type uint32;
    description "Segment Identifier (SID) index/label.";
}
}

container lan-adj-sid-sub-tlvs {
    description "LAN Adjacency SID optional sub-TLVs.";
    list lan-adj-sid-sub-tlv {
        description "List of LAN adjacency SID sub-TLVs.";
        leaf flags {
            type bits {
                bit B {
                    description
                    "Backup flag.";
                }
                bit V {
                    description
                    "Value/Index flag.";
                }
                bit L {
                    description

```

Yeung, et al.

Expires September 14, 2017

[Page 22]

```

        "Local/Global flag.";
    }
    bit G {
        description
        "Group flag.";
    }
    bit P {
        description
        "Persistent flag.";
    }
}
description "Flags.';

leaf mt-id {
    type uint8;
    description "Multi-topology ID.";
}
leaf weight {
    type uint8;
    description "Weight used for load-balancing.";
}
leaf neighbor-router-id {
    type yang:dotted-quad;
    description "Neighbor router ID.";
}
leaf sid {
    type uint32;
    description "Segment Identifier (SID) index/label.";
}
}

augment "/rt:routing-state/"
+ "rt:control-plane-protocols/rt:control-plane-protocol/"
+ "ospf:ospf/ospf:instance/ospf:areas/ospf:area/"
+ "ospf:interfaces/ospf:interface/ospf:database/"
+ "ospf:link-scope-lsa-type/ospf:link-scope-lsas/"
+ "ospf:link-scope-lsa/ospf:version/ospf:ospfv2/"
+ "ospf:ospfv2/ospf:body/ospf:opaque" {
when ".../.../.../.../.../.../.../.../.../.../...""
+ "rt:type = 'ospf:ospfv2'" {
description
"This augmentation is only valid for OSPFv2.";
}

description
"SR specific TLVs for OSPFv2 type 9 opaque LSA.";
```

Yeung, et al.

Expires September 14, 2017

[Page 23]

```

uses extended-prefix-range-tlvs;
uses sr-algorithm-tlv;
uses sid-range-tlvs;
}

augment "/rt:routing-state/"
  + "rt:control-plane-protocols/rt:control-plane-protocol/"
  + "ospf:ospf/ospf:instance/ospf:areas/"
  + "ospf:area/ospf:database/"
  + "ospf:area-scope-lsa-type/ospf:area-scope-lsas/"
  + "ospf:area-scope-lsa/ospf:version/ospf:ospfv2/"
  + "ospf:ospfv2/ospf:body/ospf:opaque" {
when ".../.../.../.../.../.../.../.../.../..."
  + "rt:type = 'ospf:ospfv2'" {
description
  "This augmentation is only valid for OSPFv2.";
}

description
  "SR specific TLVs for OSPFv2 type 10 opaque LSA./";

uses extended-prefix-range-tlvs;
uses sr-algorithm-tlv;
uses sid-range-tlvs;
}

augment "/rt:routing-state/"
  + "rt:control-plane-protocols/rt:control-plane-protocol/"
  + "ospf:ospf/ospf:instance/ospf:database/"
  + "ospf:as-scope-lsa-type/ospf:as-scope-lsas/"
  + "ospf:as-scope-lsa/ospf:version/ospf:ospfv2/"
  + "ospf:ospfv2/ospf:body/ospf:opaque" {
when ".../.../.../.../.../.../.../..."
  + "rt:type = 'ospf:ospfv2'" {
description
  "This augmentation is only valid for OSPFv2.";
}

description
  "SR specific TLVs for OSPFv2 type 11 opaque LSA./";

uses extended-prefix-range-tlvs;
uses sr-algorithm-tlv;
uses sid-range-tlvs;
}

}
<CODE ENDS>
```

Yeung, et al.

Expires September 14, 2017

[Page 24]

4. Security Considerations

The data model defined does not create any security implications.

This draft does not change any underlying security issues inherent in [I-D.ietf-netmod-routing-cfg].

5. Acknowledgements

The authors wish to thank Yi Yang, Alexander Clemm, Gaurav Gupta, Ladislav Lhotka, Stephane Litkowski, Greg Hankins, Manish Gupta and Alan Davey for their thorough reviews and helpful comments.

This document was produced using Marshall Rose's xml2rfc tool.

6. References

6.1. Normative References

- [RFC1793] Moy, J., "Extending OSPF to Support Demand Circuits", [RFC 1793](#), DOI 10.17487/RFC1793, April 1995,
<<http://www.rfc-editor.org/info/rfc1793>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997,
<<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC2328] Moy, J., "OSPF Version 2", STD 54, [RFC 2328](#), DOI 10.17487/RFC2328, April 1998,
<<http://www.rfc-editor.org/info/rfc2328>>.
- [RFC3101] Murphy, P., "The OSPF Not-So-Stubby Area (NSSA) Option", [RFC 3101](#), DOI 10.17487/RFC3101, January 2003,
<<http://www.rfc-editor.org/info/rfc3101>>.
- [RFC3623] Moy, J., Pillay-Esnault, P., and A. Lindem, "Graceful OSPF Restart", [RFC 3623](#), DOI 10.17487/RFC3623, November 2003,
<<http://www.rfc-editor.org/info/rfc3623>>.
- [RFC3630] Katz, D., Komella, K., and D. Yeung, "Traffic Engineering (TE) Extensions to OSPF Version 2", [RFC 3630](#), DOI 10.17487/RFC3630, September 2003,
<<http://www.rfc-editor.org/info/rfc3630>>.

- [RFC4577] Rosen, E., Psenak, P., and P. Pillay-Esnault, "OSPF as the Provider/Customer Edge Protocol for BGP/MPLS IP Virtual Private Networks (VPNs)", [RFC 4577](#), DOI 10.17487/RFC4577, June 2006, <<http://www.rfc-editor.org/info/rfc4577>>.
- [RFC4750] Joyal, D., Ed., Galecki, P., Ed., Giacalone, S., Ed., Coltun, R., and F. Baker, "OSPF Version 2 Management Information Base", [RFC 4750](#), DOI 10.17487/RFC4750, December 2006, <<http://www.rfc-editor.org/info/rfc4750>>.
- [RFC5187] Pillay-Esnault, P. and A. Lindem, "OSPFv3 Graceful Restart", [RFC 5187](#), DOI 10.17487/RFC5187, June 2008, <<http://www.rfc-editor.org/info/rfc5187>>.
- [RFC5340] Coltun, R., Ferguson, D., Moy, J., and A. Lindem, "OSPF for IPv6", [RFC 5340](#), DOI 10.17487/RFC5340, July 2008, <<http://www.rfc-editor.org/info/rfc5340>>.
- [RFC5643] Joyal, D., Ed. and V. Manral, Ed., "Management Information Base for OSPFv3", [RFC 5643](#), DOI 10.17487/RFC5643, August 2009, <<http://www.rfc-editor.org/info/rfc5643>>.
- [RFC5838] Lindem, A., Ed., Mirtorabi, S., Roy, A., Barnes, M., and R. Aggarwal, "Support of Address Families in OSPFv3", [RFC 5838](#), DOI 10.17487/RFC5838, April 2010, <<http://www.rfc-editor.org/info/rfc5838>>.
- [RFC5880] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD)", [RFC 5880](#), DOI 10.17487/RFC5880, June 2010, <<http://www.rfc-editor.org/info/rfc5880>>.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), DOI 10.17487/RFC6020, October 2010, <<http://www.rfc-editor.org/info/rfc6020>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), DOI 10.17487/RFC6241, June 2011, <<http://www.rfc-editor.org/info/rfc6241>>.
- [RFC6565] Pillay-Esnault, P., Moyer, P., Doyle, J., Ertekin, E., and M. Lundberg, "OSPFv3 as a Provider Edge to Customer Edge (PE-CE) Routing Protocol", [RFC 6565](#), DOI 10.17487/RFC6565, June 2012, <<http://www.rfc-editor.org/info/rfc6565>>.

- [RFC7223] Bjorklund, M., "A YANG Data Model for Interface Management", [RFC 7223](#), DOI 10.17487/RFC7223, May 2014, <<http://www.rfc-editor.org/info/rfc7223>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016, <<http://www.rfc-editor.org/info/rfc7950>>.
- [RFC8022] Lhotka, L. and A. Lindem, "A YANG Data Model for Routing Management", [RFC 8022](#), DOI 10.17487/RFC8022, November 2016, <<http://www.rfc-editor.org/info/rfc8022>>.

6.2. Informative References

- [I-D.ietf-ospf-yang]
Yeung, D., Qu, Y., Zhang, Z., Chen, I., and A. Lindem, "Yang Data Model for OSPF Protocol", [draft-ietf-ospf-yang-06](#) (work in progress), October 2016.
- [I-D.ietf-spring-sr-yang]
Litkowski, S., Qu, Y., Sarkar, P., and J. Tantsura, "YANG Data Model for Segment Routing", [draft-ietf-spring-sr-yang-06](#) (work in progress), March 2017.

Appendix A. Contributors' Addresses

Dean Bogdanovic
Volta Networks, Inc.

EMail: dean@voltanet.io

Kiran Koushik Agrahara Sreenivasa
Cisco Systems
12515 Research Blvd, Bldg 4
Austin, TX 78681
USA

EMail: kkoushik@cisco.com

Authors' Addresses

Derek Yeung
Arrcus

EMail: derek@arrcus.com

Yingzhen Qu
Huawei
2330 Central Expressway
Santa Clara, CA 95050
USA

EMail: yingzhen.qu@huawei.com

Jeffrey Zhang
Juniper Networks
10 Technology Park Drive
Westford, MA 01886
USA

EMail: zzhang@juniper.net

Ing-Wher Chen
Jabil Circuit

EMail: Ing-Wher_chen@jabil.com

Acee Lindem
Cisco Systems
301 Midenhall Way
Cary, NC 27513

EMail: acee@cisco.com