

Internet
Internet-Draft
Intended status: Standards Track
Expires: 6 July 2022

D. Yeung
Arrcus
Y. Qu
Futurewei
J. Zhang
Juniper Networks
I. Chen
The MITRE Corporation
A. Lindem
Cisco Systems
2 January 2022

YANG Data Model for OSPF Segment Routing
draft-ietf-ospf-sr-yang-17

Abstract

This document defines a YANG data module that can be used to configure and manage OSPF Extensions for Segment Routing. It also defines a module for management of Signaling Maximum SID Depth (MSD) Using OSPF.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 6 July 2022.

Copyright Notice

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document.

Internet-Draft OSPF SR (Segment Routing) YANG Data Model January 2022

Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Revised BSD License.

Table of Contents

1.	Overview	2
1.1.	Requirements Language	3
1.2.	Tree Diagrams	3
2.	OSPF MSD	3
2.1.	OSPF MSD YANG Module	4
3.	OSPF Segment Routing	11
3.1.	OSPF Segment Routing YANG Module	16
4.	Security Considerations	30
5.	Acknowledgements	31
6.	IANA Considerations	31
7.	References	32
7.1.	Normative References	32
7.2.	Informative References	34
Appendix A.	Contributors' Addresses	34
	Authors' Addresses	34

[1.](#) Overview

YANG [[RFC7950](#)] is a data definition language used to define the contents of a conceptual data store that allows networked devices to be managed using NETCONF [[RFC6241](#)]. YANG is proving relevant beyond its initial confines, as bindings to other interfaces (e.g., ReST) and encodings other than XML (e.g., JSON) are being defined. Furthermore, YANG data models can be used as the basis for implementation of other interfaces, such as CLI and programmatic APIs.

This document defines a YANG data model that can be used to configure and manage OSPFv2 extensions for Segment Routing [[RFC8665](#)] and it is an augmentation to the OSPF YANG data model.

This document also defines a YANG data model for Signaling Maximum SID Depth (MSD) Using OSPF [[RFC8476](#)], which augments the base OSPF YANG data model.

The YANG module in this document conforms to the Network Management Datastore Architecture (NMDA) [[RFC8342](#)].

Internet-Draft OSPF SR (Segment Routing) YANG Data Model January 2022

[1.1.](#) Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

[1.2.](#) Tree Diagrams

This document uses the graphical representation of data models defined in [[RFC8340](#)].

[2.](#) OSPF MSD

This document defines a model for Signaling Maximum SID Depth (MSD) Using OSPF [[RFC8476](#)]. It is an augmentation of the OSPF base model.

```
module: ietf-ospf-msd
  augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/ospf:ospf/ospf:areas/ospf:area
    /ospf:database/ospf:area-scope-lsa-type/ospf:area-scope-lsas
    /ospf:area-scope-lsa/ospf:version/ospf:ospfv2/ospf:ospfv2
    /ospf:body/ospf:opaque/ospf:ri-opaque:
  +--ro node-msd-tlv
    +--ro node-msds* [msd-type]
      +--ro msd-type      identityref
      +--ro msd-value?    uint8
  augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/ospf:ospf/ospf:database
    /ospf:as-scope-lsa-type/ospf:as-scope-lsas/ospf:as-scope-lsa
    /ospf:version/ospf:ospfv2/ospf:ospfv2/ospf:body/ospf:opaque
    /ospf:ri-opaque:
  +--ro node-msd-tlv
    +--ro node-msds* [msd-type]
      +--ro msd-type      identityref
      +--ro msd-value?    uint8
  augment /rt:routing/rt:control-plane-protocols
```

```

        /rt:control-plane-protocol/ospf:ospf/ospf:areas/ospf:area
        /ospf:database/ospf:area-scope-lsa-type/ospf:area-scope-lsas
        /ospf:area-scope-lsa/ospf:version/ospf:ospfv3/ospf:ospfv3
        /ospf:body/ospf:router-information:
+--ro node-msd-tlv
+--ro node-msds* [msd-type]
+--ro msd-type      identityref
+--ro msd-value?    uint8
augment /rt:routing/rt:control-plane-protocols
        /rt:control-plane-protocol/ospf:ospf/ospf:database
        /ospf:as-scope-lsa-type/ospf:as-scope-lsas/ospf:as-scope-lsa
        /ospf:version/ospf:ospfv3/ospf:ospfv3/ospf:body

```

```

        /ospf:router-information:
+--ro node-msd-tlv
+--ro node-msds* [msd-type]
+--ro msd-type      identityref
+--ro msd-value?    uint8
augment /rt:routing/rt:control-plane-protocols
        /rt:control-plane-protocol/ospf:ospf/ospf:areas/ospf:area
        /ospf:interfaces/ospf:interface/ospf:database
        /ospf:link-scope-lsa-type/ospf:link-scope-lsas
        /ospf:link-scope-lsa/ospf:version/ospf:ospfv2/ospf:ospfv2
        /ospf:body/ospf:opaque/ospf:extended-link-opaque
        /ospf:extended-link-tlv:
+--ro link-msd-sub-tlv
+--ro link-msds* [msd-type]
+--ro msd-type      identityref
+--ro msd-value?    uint8
augment /rt:routing/rt:control-plane-protocols
        /rt:control-plane-protocol/ospf:ospf/ospf:areas/ospf:area
        /ospf:database/ospf:area-scope-lsa-type/ospf:area-scope-lsas
        /ospf:area-scope-lsa/ospf:version/ospf:ospfv2/ospf:ospfv2
        /ospf:body/ospf:opaque/ospf:extended-link-opaque
        /ospf:extended-link-tlv:
+--ro link-msd-sub-tlv
+--ro link-msds* [msd-type]
+--ro msd-type      identityref
+--ro msd-value?    uint8
augment /rt:routing/rt:control-plane-protocols
        /rt:control-plane-protocol/ospf:ospf/ospf:database
        /ospf:as-scope-lsa-type/ospf:as-scope-lsas/ospf:as-scope-lsa

```

```

        /ospf:version/ospf:ospfv2/ospf:ospfv2/ospf:body/ospf:opaque
        /ospf:extended-link-opaque/ospf:extended-link-tlv:
+--ro link-msd-sub-tlv
  +--ro link-msds* [msd-type]
    +--ro msd-type      identityref
    +--ro msd-value?    uint8
augment /rt:routing/rt:control-plane-protocols
  /rt:control-plane-protocol/ospf:ospf/ospf:areas/ospf:area
  /ospf:database/ospf:area-scope-lsa-type/ospf:area-scope-lsas
  /ospf:area-scope-lsa/ospf:version/ospf:ospfv3/ospf:ospfv3
  /ospf:body/ospfv3-e-lsa:e-router/ospfv3-e-lsa:e-router-tlvs:
+--ro link-msd-sub-tlv
  +--ro link-msds* [msd-type]
    +--ro msd-type      identityref
    +--ro msd-value?    uint8

```

2.1. OSPF MSD YANG Module

```

<CODE BEGINS> file "ietf-ospf-msd@2022-01-02.yang"
module ietf-ospf-msd {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-ospf-msd";
  prefix ospf-msd;

  import ietf-routing {
    prefix rt;
    reference "RFC 8349: A YANG Data Model for Routing
              Management (NMDA Version)";
  }

  import ietf-ospf {
    prefix ospf;
  }

  import ietf-ospfv3-extended-lsa {
    prefix ospfv3-e-lsa;
  }

  organization
    "IETF LSR - LSR Working Group";

```

contact

"WG Web: <<https://tools.ietf.org/wg/mps/>>
WG List: <<mailto:mps@ietf.org>>

Author: Yingzhen Qu
<<mailto:yingzhen.qu@futurewei.com>>
Author: Acee Lindem
<<mailto:acee@cisco.com>>
Author: Stephane Litkowski
<<mailto:slitkows.ietf@gmail.com>>
Author: Jeff Tantsura
<jefftant.ietf@gmail.com>

";

description

"The YANG module augments the base OSPF model to manage different types of MSDs.

This YANG model conforms to the Network Management Datastore Architecture (NMDA) as described in [RFC 8342](#).

Copyright (c) 2022 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to

the license terms contained in, the Revised BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.

The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED', 'MAY', and 'OPTIONAL' in this document are to be interpreted as described in [BCP 14](#) ([RFC 2119](#)) ([RFC 8174](#)) when, and only when, they appear in all capitals, as shown here.";

```

reference "RFC XXXX: YANG Data Model for OSPF MSD.";

revision 2022-01-02 {
  description
    "Initial Version";
  reference "RFC XXXX: YANG Data Model for OSPF MSD.";
}

identity msd-base-type {
  description
    "Base identity for MSD Type";
}

identity base-mpls-msd {
  base msd-base-type;
  description
    "Base MPLS Imposition MSD.";
  reference
    "RFC 8491: Singling MSD using IS-IS.";
}

identity erld-msd {
  base msd-base-type;
  description
    "ERLD-MSD is defined to advertise the ERLD.";
  reference
    "RFC 8662: Entropy Label for Source Packet Routing in
      Networking (SPRING) Tunnels";
}

grouping node-msd-tlv {
  description
    "Grouping for node MSD.";
}

```

```

container node-msd-tlv {
  list node-msds {
    key "msd-type";
    leaf msd-type {
      type identityref {
        base msd-base-type;
      }
      description

```

```

        "MSD-Types";
    }
    leaf msd-value {
        type uint8;
        description
            "MSD value, in the range of 0-255.";
    }
    description
        "Node MSD is the smallest link MSD supported by
        the node.";
}
description
    "Node MSD is the number of SIDs supported by a node.";
reference
    "RFC 8476: Signaling Maximum SID Depth (MSD) Using OSPF";
}
}

grouping link-msd-sub-tlv {
    description
        "Link Maximum SID Depth (MSD) grouping for an interface.";
    container link-msd-sub-tlv {
        list link-msds {
            key "msd-type";
            leaf msd-type {
                type identityref {
                    base msd-base-type;
                }
                description
                    "MSD-Types";
            }
            leaf msd-value {
                type uint8;
                description
                    "MSD value, in the range of 0-255.";
            }
            description
                "List of link MSDs";
        }
        description
            "Link MSD sub-tlvs.";
    }
}

```



```

    }
}

/* Node MSD TLV */
augment "/rt:routing/"
  + "rt:control-plane-protocols/rt:control-plane-protocol/"
  + "ospf:ospf/ospf:areas/"
  + "ospf:area/ospf:database/"
  + "ospf:area-scope-lsa-type/ospf:area-scope-lsas/"
  + "ospf:area-scope-lsa/ospf:version/ospf:ospfv2/"
  + "ospf:ospfv2/ospf:body/ospf:opaque/"
  + "ospf:ri-opaque" {
when "../..../..../..../..../..../..../..../..../"
  + "rt:type = 'ospf:ospfv2'" {
  description
    "This augmentation is only valid for OSPFv2.";
}
description
  "Node MSD TLV is an optional TLV of OSPFv2 RI Opaque
  LSA (RFC7770) and has a type of 12.";

uses node-msd-tlv;
}

augment "/rt:routing/"
  + "rt:control-plane-protocols/rt:control-plane-protocol/"
  + "ospf:ospf/ospf:database/"
  + "ospf:as-scope-lsa-type/ospf:as-scope-lsas/"
  + "ospf:as-scope-lsa/ospf:version/ospf:ospfv2/"
  + "ospf:ospfv2/ospf:body/ospf:opaque/"
  + "ospf:ri-opaque" {
when "../..../..../..../..../..../..../..../..../"
  + "rt:type = 'ospf:ospfv2'" {
  description
    "This augmentation is only valid for OSPFv2.";
}
description
  "Node MSD TLV is an optional TLV of OSPFv2 RI Opaque
  LSA (RFC7770) and has a type of 12.";

uses node-msd-tlv;
}

augment "/rt:routing/"
  + "rt:control-plane-protocols/rt:control-plane-protocol/"
  + "ospf:ospf/ospf:areas/"
  + "ospf:area/ospf:database/"

```

```
        + "ospf:area-scope-lsa-type/ospf:area-scope-lsas/"
        + "ospf:area-scope-lsa/ospf:version/ospf:ospfv3/"
        + "ospf:ospfv3/ospf:body/ospf:router-information" {
when "../.../.../.../.../.../.../.../.../..."
    + "rt:type = 'ospf:ospfv3'" {
    description
        "This augmentation is only valid for OSPFv3.";
    }
    description
        "Node MSD TLV is an optional TLV of OSPFv3 RI Opaque
        LSA (RFC7770) and has a type of 12.";

    uses node-msd-tlv;
}

augment "/rt:routing/"
    + "rt:control-plane-protocols/rt:control-plane-protocol/"
    + "ospf:ospf/ospf:database/"
    + "ospf:as-scope-lsa-type/ospf:as-scope-lsas/"
    + "ospf:as-scope-lsa/ospf:version/ospf:ospfv3/"
    + "ospf:ospfv3/ospf:body/ospf:router-information" {
when "../.../.../.../.../.../.../.../..."
    + "rt:type = 'ospf:ospfv3'" {
    description
        "This augmentation is only valid for OSPFv3.";
    }
    description
        "Node MSD TLV is an optional TLV of OSPFv3 RI Opaque
        LSA (RFC7770) and has a type of 12.";

    uses node-msd-tlv;
}

/* link MSD sub-tlv */
augment "/rt:routing/"
    + "rt:control-plane-protocols/rt:control-plane-protocol/"
    + "ospf:ospf/ospf:areas/ospf:area/"
    + "ospf:interfaces/ospf:interface/ospf:database/"
    + "ospf:link-scope-lsa-type/ospf:link-scope-lsas/"
    + "ospf:link-scope-lsa/ospf:version/ospf:ospfv2/"
    + "ospf:ospfv2/ospf:body/ospf:opaque/"
    + "ospf:extended-link-opaque/ospf:extended-link-tlv" {
when "../.../.../.../.../.../.../.../.../.../.../..."
    + "rt:type = 'ospf:ospfv2'" {
    description
        "This augmentation is only valid for OSPFv2.";
```

```
}  
description
```

Internet-Draft OSPF SR (Segment Routing) YANG Data Mode January 2022

```
    "Link MSD sub-TLV is an optional sub-TLV of OSPFv2 extended  
    link TLV as defined in RFC 7684 and has a type of 6.";

    uses link-msd-sub-tlv;
}

augment "/rt:routing/"
+ "rt:control-plane-protocols/rt:control-plane-protocol/"
+ "ospf:ospf/ospf:areas/"
+ "ospf:area/ospf:database/"
+ "ospf:area-scope-lsa-type/ospf:area-scope-lsas/"
+ "ospf:area-scope-lsa/ospf:version/ospf:ospfv2/"
+ "ospf:ospfv2/ospf:body/ospf:opaque/"
+ "ospf:extended-link-opaque/ospf:extended-link-tlv" {
when "../..../..../..../..../..../..../..../..../"
+ "rt:type = 'ospf:ospfv2'" {
    description
        "This augmentation is only valid for OSPFv2.";
}
description
    "Link MSD sub-TLV is an optional sub-TLV of OSPFv2 extended  
    link TLV as defined in RFC 7684 and has a type of 6.";

    uses link-msd-sub-tlv;
}

augment "/rt:routing/"
+ "rt:control-plane-protocols/rt:control-plane-protocol/"
+ "ospf:ospf/ospf:database/"
+ "ospf:as-scope-lsa-type/ospf:as-scope-lsas/"
+ "ospf:as-scope-lsa/ospf:version/ospf:ospfv2/"
+ "ospf:ospfv2/ospf:body/ospf:opaque/"
+ "ospf:extended-link-opaque/ospf:extended-link-tlv" {
when "../..../..../..../..../..../..../..../..../"
+ "rt:type = 'ospf:ospfv2'" {
    description
        "This augmentation is only valid for OSPFv2.";
}
description
```

"Link MSD sub-TLV is an optional sub-TLV of OSPFv2 extended link TLV as defined in [RFC 7684](#) and has a type of 6.";

```
uses link-msd-sub-tlv;
}

augment "/rt:routing/"
+ "rt:control-plane-protocols/rt:control-plane-protocol/"
+ "ospf:ospf/ospf:areas/ospf:area/ospf:database/"
```

```
+ "ospf:area-scope-lsa-type/ospf:area-scope-lsas/"
+ "ospf:area-scope-lsa/ospf:version/ospf:ospfv3/"
+ "ospf:ospfv3/ospf:body/ospfv3-e-lsa:e-router"
+ "/ospfv3-e-lsa:e-router-tlvs" {
when "'ospf:../../../../../../../../../../'"
+ "rt:type" = 'ospf:ospfv3' {
description
  "This augmentation is only valid for OSPFv3
  E-Router LSAs";
}
description
  "Augment OSPFv3 Area scope router-link TLV.";

uses link-msd-sub-tlv;
}
}
<CODE ENDS>
```

[3.](#) OSPF Segment Routing

This document defines a model for OSPF Segment Routing feature [\[RFC8665\]](#). It is an augmentation of the OSPF base model.

The OSPF SR YANG module requires support for the base segment routing module [\[RFC9020\]](#), which defines the global segment routing configuration independent of any specific routing protocol configuration, and support of OSPF base model [\[I-D.ietf-ospf-yang\]](#) which defines basic OSPF configuration and state.

```
module: ietf-ospf-sr
  augment /rt:routing/rt:control-plane-protocols
```

```

        /rt:control-plane-protocol/ospf:ospf:
+--rw segment-routing
|   +--rw enabled?      boolean
|   +--rw bindings {mapping-server}?
|       +--rw advertise
|           |   +--rw policies*  -> /rt:routing/sr:segment-routing
|           |                               /sr-mpls:sr-mpls/bindings
|           |                               /mapping-server/policy/name
|           +--rw receive?      boolean
+--rw protocol-srgb {sr-mpls:protocol-srgb}?
    +--rw srgb* [lower-bound upper-bound]
        +--rw lower-bound      uint32
        +--rw upper-bound      uint32
augment /rt:routing/rt:control-plane-protocols
        /rt:control-plane-protocol/ospf:ospf/ospf:areas/ospf:area
        /ospf:interfaces/ospf:interface:

```

```

+--rw segment-routing
    +--rw adjacency-sid
        +--rw adj-sids* [value]
            |   +--rw value-type?  enumeration
            |   +--rw value        uint32
            |   +--rw protected?   boolean
            |   +--rw weight?      uint8
        +--rw advertise-adj-group-sid* [group-id]
            |   +--rw group-id      uint32
        +--rw advertise-protection?  enumeration
augment /rt:routing/rt:control-plane-protocols
        /rt:control-plane-protocol/ospf:ospf/ospf:areas/ospf:area
        /ospf:interfaces/ospf:interface/ospf:fast-reroute:
+--rw ti-lfa {ti-lfa}?
    +--rw enable?      boolean
augment /rt:routing/rt:control-plane-protocols
        /rt:control-plane-protocol/ospf:ospf/ospf:areas/ospf:area
        /ospf:interfaces/ospf:interface/ospf:database
        /ospf:link-scope-lsa-type/ospf:link-scope-lsas
        /ospf:link-scope-lsa/ospf:version/ospf:ospfv2/ospf:ospfv2
        /ospf:body/ospf:opaque/ospf:extended-prefix-opaque:
+--ro extended-prefix-range-tlvs
    +--ro extended-prefix-range-tlv* []
        +--ro prefix-length?          uint8
        +--ro af?                      uint8

```

```

+---ro range-size?                               uint16
+---ro extended-prefix-range-flags
|  +---ro bits*   identityref
+---ro prefix?                                   inet:ip-prefix
+---ro prefix-sid-sub-tlvs
|  +---ro prefix-sid-sub-tlv* []
|      +---ro prefix-sid-flags
|          |  +---ro bits*   identityref
|          +---ro mt-id?      uint8
|          +---ro algorithm?  uint8
|          +---ro sid?        uint32
+---ro unknown-tlvs
    +---ro unknown-tlv* []
        +---ro type?      uint16
        +---ro length?    uint16
        +---ro value?     yang:hex-string
augment /rt:routing/rt:control-plane-protocols
/rt:control-plane-protocol/ospf:ospf/ospf:areas/ospf:area
/ospf:database/ospf:area-scope-lsa-type/ospf:area-scope-lsas
/ospf:area-scope-lsa/ospf:version/ospf:ospfv2/ospf:ospfv2
/ospf:body/ospf:opaque/ospf:extended-prefix-opaque:
+---ro extended-prefix-range-tlvs
    +---ro extended-prefix-range-tlv* []

```

```

+---ro prefix-length?                             uint8
+---ro af?                                         uint8
+---ro range-size?                               uint16
+---ro extended-prefix-range-flags
|  +---ro bits*   identityref
+---ro prefix?                                   inet:ip-prefix
+---ro prefix-sid-sub-tlvs
|  +---ro prefix-sid-sub-tlv* []
|      +---ro prefix-sid-flags
|          |  +---ro bits*   identityref
|          +---ro mt-id?      uint8
|          +---ro algorithm?  uint8
|          +---ro sid?        uint32
+---ro unknown-tlvs
    +---ro unknown-tlv* []
        +---ro type?      uint16
        +---ro length?    uint16
        +---ro value?     yang:hex-string

```

```

augment /rt:routing/rt:control-plane-protocols
  /rt:control-plane-protocol/ospf:ospf/ospf:database
  /ospf:as-scope-lsa-type/ospf:as-scope-lsas
  /ospf:as-scope-lsa/ospf:version/ospf:ospfv2/ospf:ospfv2
  /ospf:body/ospf:opaque/ospf:extended-prefix-opaque:
+--ro extended-prefix-range-tlvs
  +--ro extended-prefix-range-tlv* []
    +--ro prefix-length?                uint8
    +--ro af?                          uint8
    +--ro range-size?                  uint16
    +--ro extended-prefix-range-flags
    | +--ro bits* identityref
    +--ro prefix?                      inet:ip-prefix
    +--ro prefix-sid-sub-tlvs
    | +--ro prefix-sid-sub-tlv* []
    |   +--ro prefix-sid-flags
    |   | +--ro bits* identityref
    |   +--ro mt-id?                  uint8
    |   +--ro algorithm?              uint8
    |   +--ro sid?                    uint32
    +--ro unknown-tlvs
    | +--ro unknown-tlv* []
    |   +--ro type?                  uint16
    |   +--ro length?                uint16
    |   +--ro value?                 yang:hex-string
augment /rt:routing/rt:control-plane-protocols
  /rt:control-plane-protocol/ospf:ospf/ospf:areas/ospf:area
  /ospf:interfaces/ospf:interface/ospf:database
  /ospf:link-scope-lsa-type/ospf:link-scope-lsas
  /ospf:link-scope-lsa/ospf:version/ospf:ospfv2/ospf:ospfv2

```

```

  /ospf:body/ospf:opaque/ospf:extended-prefix-opaque
  /ospf:extended-prefix-tlv:
+--ro prefix-sid-sub-tlvs
  +--ro prefix-sid-sub-tlv* []
    +--ro prefix-sid-flags
    | +--ro bits* identityref
    +--ro mt-id?                  uint8
    +--ro algorithm?              uint8
    +--ro sid?                    uint32
augment /rt:routing/rt:control-plane-protocols
  /rt:control-plane-protocol/ospf:ospf/ospf:areas/ospf:area

```

```

        /ospf:database/ospf:area-scope-lsa-type/ospf:area-scope-lsas
        /ospf:area-scope-lsa/ospf:version/ospf:ospfv2/ospf:ospfv2
        /ospf:body/ospf:opaque/ospf:extended-prefix-opaque
        /ospf:extended-prefix-tlv:
+--ro prefix-sid-sub-tlvs
  +--ro prefix-sid-sub-tlv* []
    +--ro prefix-sid-flags
      | +--ro bits* identityref
    +--ro mt-id? uint8
    +--ro algorithm? uint8
    +--ro sid? uint32
augment /rt:routing/rt:control-plane-protocols
  /rt:control-plane-protocol/ospf:ospf/ospf:database
  /ospf:as-scope-lsa-type/ospf:as-scope-lsas/ospf:as-scope-lsa
  /ospf:version/ospf:ospfv2/ospf:ospfv2/ospf:body/ospf:opaque
  /ospf:extended-prefix-opaque/ospf:extended-prefix-tlv:
+--ro prefix-sid-sub-tlvs
  +--ro prefix-sid-sub-tlv* []
    +--ro prefix-sid-flags
      | +--ro bits* identityref
    +--ro mt-id? uint8
    +--ro algorithm? uint8
    +--ro sid? uint32
augment /rt:routing/rt:control-plane-protocols
  /rt:control-plane-protocol/ospf:ospf/ospf:areas/ospf:area
  /ospf:database/ospf:area-scope-lsa-type/ospf:area-scope-lsas
  /ospf:area-scope-lsa/ospf:version/ospf:ospfv2/ospf:ospfv2
  /ospf:body/ospf:opaque/ospf:extended-link-opaque
  /ospf:extended-link-tlv:
+--ro adj-sid-sub-tlvs
  | +--ro adj-sid-sub-tlv* []
  |   +--ro adj-sid-flags
  |     | +--ro bits* identityref
  |     +--ro mt-id? uint8
  |     +--ro weight? uint8
  |     +--ro sid? uint32
+--ro lan-adj-sid-sub-tlvs

```

```

+--ro lan-adj-sid-sub-tlv* []
  +--ro lan-adj-sid-flags
    | +--ro bits* identityref
    +--ro mt-id? uint8

```



```

        +---ro weight?                uint8
        +---ro neighbor-router-id?    yang:dotted-quad
        +---ro sid?                   uint32
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/ospf:ospf/ospf:areas/ospf:area
    /ospf:interfaces/ospf:interface/ospf:database
    /ospf:link-scope-lsa-type/ospf:link-scope-lsas
    /ospf:link-scope-lsa/ospf:version/ospf:ospfv2/ospf:ospfv2
    /ospf:body/ospf:opaque/ospf:ri-opaque:
+---ro sr-algorithm-tlv
| +---ro sr-algorithm*   uint8
+---ro sid-range-tlvs
| +---ro sid-range-tlv* []
|   +---ro range-size?   uint24
|   +---ro sid-sub-tlv
|       +---ro sid?      uint32
+---ro local-block-tlvs
| +---ro local-block-tlv* []
|   +---ro range-size?   uint24
|   +---ro sid-sub-tlv
|       +---ro sid?      uint32
+---ro srms-preference-tlv
    +---ro preference?   uint8
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/ospf:ospf/ospf:areas/ospf:area
    /ospf:database/ospf:area-scope-lsa-type/ospf:area-scope-lsas
    /ospf:area-scope-lsa/ospf:version/ospf:ospfv2/ospf:ospfv2
    /ospf:body/ospf:opaque/ospf:ri-opaque:
+---ro sr-algorithm-tlv
| +---ro sr-algorithm*   uint8
+---ro sid-range-tlvs
| +---ro sid-range-tlv* []
|   +---ro range-size?   uint24
|   +---ro sid-sub-tlv
|       +---ro sid?      uint32
+---ro local-block-tlvs
| +---ro local-block-tlv* []
|   +---ro range-size?   uint24
|   +---ro sid-sub-tlv
|       +---ro sid?      uint32
+---ro srms-preference-tlv
    +---ro preference?   uint8
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/ospf:ospf/ospf:database

```

```

        /ospf:as-scope-lsa-type/ospf:as-scope-lsas/ospf:as-scope-lsa
        /ospf:version/ospf:ospfv2/ospf:ospfv2/ospf:body/ospf:opaque
        /ospf:ri-opaque:
+--ro sr-algorithm-tlv
|   +--ro sr-algorithm*   uint8
+--ro sid-range-tlvs
|   +--ro sid-range-tlv* []
|       +--ro range-size?   uint24
|       +--ro sid-sub-tlv
|           +--ro sid?   uint32
+--ro local-block-tlvs
|   +--ro local-block-tlv* []
|       +--ro range-size?   uint24
|       +--ro sid-sub-tlv
|           +--ro sid?   uint32
+--ro srms-preference-tlv
    +--ro preference?   uint8

```

3.1. OSPF Segment Routing YANG Module

```

<CODE BEGINS> file "ietf-ospf-sr@2022-01-02.yang"
module ietf-ospf-sr {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-ospf-sr";

  prefix ospf-sr;

  import ietf-inet-types {
    prefix "inet";
    reference "RFC 6991 - Common YANG Data Types";
  }

  import ietf-yang-types {
    prefix "yang";
    reference "RFC 6991 - Common YANG Data Types";
  }

  import ietf-routing {
    prefix "rt";
    reference "RFC 8349 - A YANG Data Model for Routing
              Management (NMDA Version)";
  }

  import ietf-segment-routing-common {
    prefix "sr-cmn";
    reference "RFC 9020 - YANG Data Model for Segment

```

Internet-Draft OSPF SR (Segment Routing) YANG Data Mode January 2022

```

}
import ietf-segment-routing-mpls {
  prefix "sr-mpls";
  reference "RFC 9020 - YANG Data Model for Segment
    Routing";
}
import ietf-ospf {
  prefix "ospf";
}

```

```

organization
  "IETF LSR - Link State Routing Working Group";

```

```

contact
  "WG Web:  <http://tools.ietf.org/wg/lsr/>
   WG List: <mailto:lsr@ietf.org>

   Editor:  Derek Yeung
            <mailto:derek@arrcus.com>
   Author:  Derek Yeung
            <mailto:derek@arrcus.com>
   Author:  Yingzhen Qu
            <mailto:yingzhen.qu@futurewei.com>
   Author:  Acee Lindem
            <mailto:acee@cisco.com>
   Author:  Jeffrey Zhang
            <mailto:zzhang@juniper.net>
   Author:  Ing-Wher Chen
            <mailto:ingwherchen@mitre.org>
   Author:  Greg Hankins
            <mailto:greg.hankins@alcatel-lucent.com>";

```

```

description
  "This YANG module defines the generic configuration
   and operational state for OSPF Segment Routing, which is
   common across all of the vendor implementations. It is
   intended that the module will be extended by vendors to
   define vendor-specific OSPF Segment Routing configuration
   and operational parameters and policies.

```

This YANG model conforms to the Network Management Datastore Architecture (NMDA) as described in [RFC 8342](#).

Copyright (c) 2022 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to

Yeung, et al.

Expires 6 July 2022

[Page 17]

Internet-Draft OSPF SR (Segment Routing) YANG Data Model January 2022

the license terms contained in, the Revised BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX (<https://www.rfc-editor.org/info/rfcXXXX>); see the RFC itself for full legal notices.

The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED', 'MAY', and 'OPTIONAL' in this document are to be interpreted as described in [BCP 14](#) ([RFC 2119](#)) ([RFC 8174](#)) when, and only when, they appear in all capitals, as shown here.

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices."

reference "RFC XXXX";

```
revision 2022-01-02 {  
  description  
    "Initial revision."  
  reference  
    "RFC XXXX: A YANG Data Model for OSPF Segment Routing."  
}
```

```
feature ti-lfa {  
  description  
    "Topology-Independent Loop-Free Alternate (TI-LFA)  
    computation using segment routing."  
}
```

```

identity prefix-sid-bit {
    description
        "Base identity for prefix sid sub-tlv bits.";
}

identity np-bit {
    base prefix-sid-bit;
    description
        "No-PHP flag.";
}

identity m-bit {
    base prefix-sid-bit;
    description

```

```

        "Mapping server flag.";
    }

identity e-bit {
    base prefix-sid-bit;
    description
        "Explicit-NULL flag.";
}

identity v-bit {
    base prefix-sid-bit;
    description
        "Value/Index flag.";
}

identity l-bit {
    base prefix-sid-bit;
    description
        "Local flag.";
}

identity extended-prefix-range-bit {
    description
        "Base identity for extended prefix range TLV bits.";
}

```

```

identity ia-bit {
    base extended-prefix-range-bit;
    description
        "Inter-Area flag. If set, advertisement is of inter-area type.";
}

identity adj-sid-bit {
    description
        "Base identity for adj sid sub-tlv bits.";
}

identity b-bit {
    base adj-sid-bit;
    description
        "Backup flag.";
}

identity vi-bit {
    base adj-sid-bit;
    description
        "Value/Index flag.";
}

```

```

identity lo-bit {
    base adj-sid-bit;
    description
        "Local/Global flag.";
}

identity g-bit {
    base adj-sid-bit;
    description
        "Group flag.";
}

identity p-bit {
    base adj-sid-bit;
    description
        "Persistent flag.";
}

typedef uint24 {

```

```

    type uint32 {
        range "0 .. 16777215";
    }
    description
        "24-bit unsigned integer.";
}

/* Groupings */
grouping sid-sub-tlv {
    description "SID/Label sub-TLV grouping.";
    container sid-sub-tlv {
        description
            "Used to advertise the SID/Label associated with a
            prefix or adjacency.";
        leaf sid {
            type uint32;
            description
                "Segment Identifier (SID) - A 20 bit label or
                32 bit SID.";
        }
    }
}

grouping prefix-sid-sub-tlvs {
    description "Prefix Segment ID (SID) sub-TLVs.";
    container prefix-sid-sub-tlvs {
        description "Prefix SID sub-TLV.";
        list prefix-sid-sub-tlv {
            description "Prefix SID sub-TLV.";
        }
    }
}

```

```

    container prefix-sid-flags {
        leaf-list bits {
            type identityref {
                base prefix-sid-bit;
            }
            description
                "Prefix SID Sub-TLV flag bits list.";
        }
        description "Segment Identifier (SID) Flags.";
    }
    leaf mt-id {
        type uint8;
    }
}

```

```

        description "Multi-topology ID.";
    }
    leaf algorithm {
        type uint8;
        description
            "The algorithm associated with the prefix-SID.";
    }
    leaf sid {
        type uint32;
        description "An index or label.";
    }
}
}
}

```

```

grouping extended-prefix-range-tlvs {
    description "Extended prefix range TLV grouping.";

```

```

    container extended-prefix-range-tlvs {
        description "The list of range of prefixes.";
        list extended-prefix-range-tlv {
            description "The range of prefixes.";
            leaf prefix-length {
                type uint8;
                description "Length of prefix in bits.";
            }
            leaf af {
                type uint8;
                description "Address family for the prefix.";
            }
            leaf range-size {
                type uint16;
                description "The number of prefixes covered by the
                    advertisement.";
            }
            container extended-prefix-range-flags {

```

```

        leaf-list bits {
            type identityref {
                base extended-prefix-range-bit;
            }
            description "Extended prefix range TLV flags list.";

```



```

        }
        description "Extended Prefix Range TLV flags.";
    }
    leaf prefix {
        type inet:ip-prefix;
        description "Address prefix.";
    }
    uses prefix-sid-sub-tlvs;
    uses ospf:unknown-tlvs;
}
}

grouping sr-algorithm-tlv {
    description "SR algorithm TLV grouping.";
    container sr-algorithm-tlv {
        description "All SR algorithm TLVs.";
        leaf-list sr-algorithm {
            type uint8;
            description
                "The Segment Routing (SR) algorithms that the router is
                currently using.";
        }
    }
}

grouping sid-range-tlvs {
    description "SID Range TLV grouping.";
    container sid-range-tlvs {
        description "List of SID range TLVs.";
        list sid-range-tlv {
            description "SID range TLV.";
            leaf range-size {
                type uint24;
                description "The SID range.";
            }
            uses sid-sub-tlv;
        }
    }
}

grouping local-block-tlvs {
    description "The SR local block TLV contains the

```

```

        range of labels reserved for local SIDs.";
    container local-block-tlvs {
        description "List of SRLB TLVs.";
        list local-block-tlv {
            description "SRLB TLV.";
            leaf range-size {
                type uint24;
                description "The SID range.";
            }
            uses sid-sub-tlv;
        }
    }
}

grouping srms-preference-tlv {
    description "The SRMS preference TLV is used to advertise
        a preference associated with the node that acts
        as an SR Mapping Server.";
    container srms-preference-tlv {
        description "SRMS Preference TLV.";
        leaf preference {
            type uint8 {
                range "0 .. 255";
            }
            description "SRMS preference TLV, value from 0 to 255.";
        }
    }
}

/* Configuration */
augment "/rt:routing/rt:control-plane-protocols"
    + "/rt:control-plane-protocol/ospf:ospf" {
    when "../rt:type = 'ospf:ospfv2' or "
        + "../rt:type = 'ospf:ospfv3'" {
        description
            "This augments the OSPF routing protocol when used.";
    }
    description
        "This augments the OSPF protocol configuration
            with segment routing.";
    uses sr-mpls:sr-control-plane;
    container protocol-srgb {
        if-feature sr-mpls:protocol-srgb;
        uses sr-cmn:srgb;
        description
            "Per-protocol SRGB.";
    }
}
}

```

Internet-Draft OSPF SR (Segment Routing) YANG Data Mode January 2022

```
augment "/rt:routing/rt:control-plane-protocols/"
  + "rt:control-plane-protocol/ospf:ospf/"
  + "ospf:areas/ospf:area/ospf:interfaces/ospf:interface" {
when "../.../rt:type = 'ospf:ospfv2' or "
  + "../.../rt:type = 'ospf:ospfv3'" {
  description
    "This augments the OSPF interface configuration
    when used.";
}
description
  "This augments the OSPF protocol interface
  configuration with segment routing.";

uses sr-mpls:igp-interface;
}

augment "/rt:routing/rt:control-plane-protocols/"
  + "rt:control-plane-protocol/ospf:ospf/"
  + "ospf:areas/ospf:area/ospf:interfaces/ospf:interface/"
  + "ospf:fast-reroute" {
when "../.../rt:type = 'ospf:ospfv2' or "
  + "../.../rt:type = 'ospf:ospfv3'" {
  description
    "This augments the OSPF routing protocol when used.";
}
description
  "This augments the OSPF protocol IP-FRR with TI-LFA.";

container ti-lfa {
  if-feature ti-lfa;
  leaf enable {
    type boolean;
    description
      "Enables TI-LFA computation.";
  }
  description
    "Topology Independent Loop Free Alternate
    (TI-LFA) support.";
}
}

/* Database */
```



```

    + "rt:control-plane-protocols/rt:control-plane-protocol/"
    + "ospf:ospf/ospf:database/"
    + "ospf:as-scope-lsa-type/ospf:as-scope-lsas/"
    + "ospf:as-scope-lsa/ospf:version/ospf:ospfv2/"
    + "ospf:ospfv2/ospf:body/ospf:opaque/"
    + "ospf:extended-prefix-opaque" {
when "../..../..../..../..../..../..../..../..../"
    + "rt:type = 'ospf:ospfv2'" {
    description
        "This augmentation is only valid for OSPFv2.";
    }
description
    "SR specific TLVs for OSPFv2 extended prefix LSA

```

```

    in type 11 opaque LSA.";

uses extended-prefix-range-tlvs;
}

augment "/rt:routing/"
    + "rt:control-plane-protocols/rt:control-plane-protocol/"
    + "ospf:ospf/ospf:areas/ospf:area/"
    + "ospf:interfaces/ospf:interface/ospf:database/"
    + "ospf:link-scope-lsa-type/ospf:link-scope-lsas/"
    + "ospf:link-scope-lsa/ospf:version/ospf:ospfv2/"
    + "ospf:ospfv2/ospf:body/ospf:opaque/"
    + "ospf:extended-prefix-opaque/ospf:extended-prefix-tlv" {
when "../..../..../..../..../..../..../..../..../"
    + "rt:type = 'ospf:ospfv2'" {
    description
        "This augmentation is only valid for OSPFv2.";
    }
description
    "SR specific TLVs for OSPFv2 extended prefix TLV
    in type 9 opaque LSA.";
uses prefix-sid-sub-tlvs;
}

augment "/rt:routing/"
    + "rt:control-plane-protocols/rt:control-plane-protocol/"
    + "ospf:ospf/ospf:areas/"
    + "ospf:area/ospf:database/"

```

```

    + "ospf:area-scope-lsa-type/ospf:area-scope-lsas/"
    + "ospf:area-scope-lsa/ospf:version/ospf:ospfv2/"
    + "ospf:ospfv2/ospf:body/ospf:opaque/"
    + "ospf:extended-prefix-opaque/ospf:extended-prefix-tlv" {
when "../..../..../..../..../..../..../..../..../"
    + "rt:type = 'ospf:ospfv2'" {
description
    "This augmentation is only valid for OSPFv2.";
}
description
    "SR specific TLVs for OSPFv2 extended prefix TLV
    in type 10 opaque LSA.";
uses prefix-sid-sub-tlvs;
}

augment "/rt:routing/"
    + "rt:control-plane-protocols/rt:control-plane-protocol/"
    + "ospf:ospf/ospf:database/"
    + "ospf:as-scope-lsa-type/ospf:as-scope-lsas/"
    + "ospf:as-scope-lsa/ospf:version/ospf:ospfv2/"

```

```

    + "ospf:ospfv2/ospf:body/ospf:opaque/"
    + "ospf:extended-prefix-opaque/ospf:extended-prefix-tlv" {
when "../..../..../..../..../..../..../..../..../"
    + "rt:type = 'ospf:ospfv2'" {
description
    "This augmentation is only valid for OSPFv2.";
}
description
    "SR specific TLVs for OSPFv2 extended prefix TLV
    in type 11 opaque LSA.";
uses prefix-sid-sub-tlvs;
}

augment "/rt:routing/"
    + "rt:control-plane-protocols/rt:control-plane-protocol/"
    + "ospf:ospf/ospf:areas/"
    + "ospf:area/ospf:database/"
    + "ospf:area-scope-lsa-type/ospf:area-scope-lsas/"
    + "ospf:area-scope-lsa/ospf:version/ospf:ospfv2/"
    + "ospf:ospfv2/ospf:body/ospf:opaque/"
    + "ospf:extended-link-opaque/ospf:extended-link-tlv" {

```

```

when "../../../../../../../../../../../../../../../../../../"
  + "rt:type = 'ospf:ospfv2'" {
  description
    "This augmentation is only valid for OSPFv2.";
}
description
  "SR specific TLVs for OSPFv2 extended link TLV
  in type 10 opaque LSA.";

container adj-sid-sub-tlvs {
  description "Adjacency SID optional sub-TLVs.";
  list adj-sid-sub-tlv {
    description "List of Adjacency SID sub-TLVs.";
    container adj-sid-flags {
      leaf-list bits {
        type identityref {
          base adj-sid-bit;
        }
        description "Adj sid sub-tlv flags list.";
      }
      description "Adj-sid sub-tlv flags.";
    }
    leaf mt-id {
      type uint8;
      description "Multi-topology ID.";
    }
    leaf weight {

```

```

      type uint8;
      description "Weight used for load-balancing.";
    }
    leaf sid {
      type uint32;
      description "Segment Identifier (SID) index/label.";
    }
  }
}

container lan-adj-sid-sub-tlvs {
  description "LAN Adjacency SID optional sub-TLVs.";
  list lan-adj-sid-sub-tlv {
    description "List of LAN adjacency SID sub-TLVs.";

```

```

    container lan-adj-sid-flags {
        leaf-list bits {
            type identityref {
                base adj-sid-bit;
            }
            description "LAN adj sid sub-tlv flags list.";
        }
        description "LAN adj-sid sub-tlv flags.";
    }
    leaf mt-id {
        type uint8;
        description "Multi-topology ID.";
    }
    leaf weight {
        type uint8;
        description "Weight used for load-balancing.";
    }
    leaf neighbor-router-id {
        type yang:dotted-quad;
        description "Neighbor router ID.";
    }
    leaf sid {
        type uint32;
        description "Segment Identifier (SID) index/label.";
    }
}
}
}

```

```

augment "/rt:routing/"
+ "rt:control-plane-protocols/rt:control-plane-protocol/"
+ "ospf:ospf/ospf:areas/ospf:area/"
+ "ospf:interfaces/ospf:interface/ospf:database/"
+ "ospf:link-scope-lsa-type/ospf:link-scope-lsas/"

```

```

+ "ospf:link-scope-lsa/ospf:version/ospf:ospfv2/"
+ "ospf:ospfv2/ospf:body/ospf:opaque/ospf:ri-opaque" {
when "../.../.../.../.../.../.../.../.../.../.../.../.../"
+ "rt:type = 'ospf:ospfv2'" {
description
    "This augmentation is only valid for OSPFv2.";
}
}

```



```

description
  "SR specific TLVs for OSPFv2 type 9 opaque LSA.";

uses sr-algorithm-tlv;
uses sid-range-tlvs;
uses local-block-tlvs;
uses srms-preference-tlv;
}

augment "/rt:routing/"
  + "rt:control-plane-protocols/rt:control-plane-protocol/"
  + "ospf:ospf/ospf:areas/"
  + "ospf:area/ospf:database/"
  + "ospf:area-scope-lsa-type/ospf:area-scope-lsas/"
  + "ospf:area-scope-lsa/ospf:version/ospf:ospfv2/"
  + "ospf:ospfv2/ospf:body/ospf:opaque/ospf:ri-opaque" {
when "../..../..../..../..../..../..../..../..../.."
  + "rt:type = 'ospf:ospfv2'" {
  description
    "This augmentation is only valid for OSPFv2.";
}

description
  "SR specific TLVs for OSPFv2 type 10 opaque LSA.";

uses sr-algorithm-tlv;
uses sid-range-tlvs;
uses local-block-tlvs;
uses srms-preference-tlv;
}

augment "/rt:routing/"
  + "rt:control-plane-protocols/rt:control-plane-protocol/"
  + "ospf:ospf/ospf:database/"
  + "ospf:as-scope-lsa-type/ospf:as-scope-lsas/"
  + "ospf:as-scope-lsa/ospf:version/ospf:ospfv2/"
  + "ospf:ospfv2/ospf:body/ospf:opaque/ospf:ri-opaque" {
when "../..../..../..../..../..../..../..../..../.."
  + "rt:type = 'ospf:ospfv2'" {
  description

```

```

        "This augmentation is only valid for OSPFv2.";
    }
    description
        "SR specific TLVs for OSPFv2 type 11 opaque LSA.";

    uses sr-algorithm-tlv;
    uses sid-range-tlvs;
    uses local-block-tlvs;
    uses srms-preference-tlv;
}
}
<CODE ENDS>

```

4. Security Considerations

The YANG modules specified in this document define a schema for data that is designed to be accessed via network management protocols such as NETCONF [\[RFC6241\]](#) or RESTCONF [\[RFC8040\]](#). The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure transport is Secure Shell (SSH) [\[RFC6242\]](#). The lowest RESTCONF layer is HTTPS, and the mandatory-to-implement secure transport is TLS [\[RFC8446\]](#).

The NETCONF Configuration Access Control model (NACM) [\[RFC8341\]](#) provides the means to restrict access for particular NETCONF or RESTCONF users to a pre-configured subset of all available NETCONF or RESTCONF protocol operations and content.

There are a number of data nodes defined in the modules that are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations. These are the subtrees and data nodes and their sensitivity/vulnerability:

/ospf:ospf/segment-routing/enabled - Modification to the enablement for SR could result in a Denial-of-Service (Dos) attack. If an attacker disables SR, it will cause traffic disruption.

/ospf:ospf/segment-routing/bindings - Modification to the local bindings could result in a Denial-of-Service (Dos) attack.

/ospf:ospf/protocol-srgb - Modification of the protocol SRGB could be used to mount a DoS attack. For example, if the protocol SRBG size is reduced to a very small value, a lot of existing segments could no longer be installed leading to a traffic disruption.

Internet-Draft OSPF SR (Segment Routing) YANG Data Mode January 2022

/ospf:interfaces/ospf:interface/segment-routing - Modification of the Adjacency Segment Identifier (Adj-SID) could be used to mount a DoS attack. Change of an Adj-SID could be used to redirect traffic.

/ospf:interfaces/ospf:interface/ospf:fast-reroute/ti-lfa - Modification of the TI-LFA enablement could lead to traffic disruption.

Some of the readable data nodes in the modules may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes.

Both module ietf-ospf-sr and ietf-ospf-msd augment base OSPF module data base with various TLVs. Knowledge of these data nodes can be used to attack other routers in the OSPF domain.

[5.](#) Acknowledgements

The authors wish to thank Yi Yang, Alexander Clemm, Gaurav Gupta, Ladislav Lhotka, Stephane Litkowski, Greg Hankins, Manish Gupta and Alan Davey for their thorough reviews and helpful comments.

This document was produced using Marshall Rose's xml2rfc tool.

Author affiliation with The MITRE Corporation is provided for identification purposes only, and is not intended to convey or imply MITRE's concurrence with, or support for, the positions, opinions or viewpoints expressed. MITRE has approved this document for Public Release, Distribution Unlimited, with Public Release Case Number 18-3281.

[6.](#) IANA Considerations

This document registers a URI in the IETF XML registry [[RFC3688](#)]. Following the format in [[RFC3688](#)], the following registration is requested to be made:

URI: urn:ietf:params:xml:ns:yang:ietf-ospf-sr
Registrant Contact: The IESG.
XML: N/A, the requested URI is an XML namespace.

URI: urn:ietf:params:xml:ns:yang:ietf-ospf-msd
Registrant Contact: The IESG.
XML: N/A, the requested URI is an XML namespace.

Internet-Draft OSPF SR (Segment Routing) YANG Data Mode January 2022

This document registers a YANG module in the YANG Module Names registry [[RFC6020](#)].

name: ietf-ospf-sr
namespace: urn:ietf:params:xml:ns:yang:ietf-ospf-sr
prefix: ospf-sr
reference: RFC XXXX

name: ietf-ospf-msd
namespace: urn:ietf:params:xml:ns:yang:ietf-ospf-msd
prefix: ospf-msd
reference: RFC XXXX

[7](#). References

[7.1](#). Normative References

- [I-D.ietf-ospf-yang]
Yeung, D., Qu, Y., Zhang, J., Chen, I., and A. Lindem,
"YANG Data Model for OSPF Protocol", Work in Progress,
Internet-Draft, [draft-ietf-ospf-yang-29](#), 17 October 2019,
<<https://www.ietf.org/archive/id/draft-ietf-ospf-yang-29.txt>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate
Requirement Levels", [BCP 14](#), [RFC 2119](#),
DOI 10.17487/RFC2119, March 1997,
<<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC2328] Moy, J., "OSPF Version 2", STD 54, [RFC 2328](#),
DOI 10.17487/RFC2328, April 1998,
<<https://www.rfc-editor.org/info/rfc2328>>.
- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#),
DOI 10.17487/RFC3688, January 2004,
<<https://www.rfc-editor.org/info/rfc3688>>.

- [RFC4750] Joyal, D., Ed., Galecki, P., Ed., Giacalone, S., Ed., Coltun, R., and F. Baker, "OSPF Version 2 Management Information Base", [RFC 4750](#), DOI 10.17487/RFC4750, December 2006, <<https://www.rfc-editor.org/info/rfc4750>>.
- [RFC5340] Coltun, R., Ferguson, D., Moy, J., and A. Lindem, "OSPF for IPv6", [RFC 5340](#), DOI 10.17487/RFC5340, July 2008, <<https://www.rfc-editor.org/info/rfc5340>>.

- [RFC5643] Joyal, D., Ed. and V. Manral, Ed., "Management Information Base for OSPFv3", [RFC 5643](#), DOI 10.17487/RFC5643, August 2009, <<https://www.rfc-editor.org/info/rfc5643>>.
- [RFC5838] Lindem, A., Ed., Mirtorabi, S., Roy, A., Barnes, M., and R. Aggarwal, "Support of Address Families in OSPFv3", [RFC 5838](#), DOI 10.17487/RFC5838, April 2010, <<https://www.rfc-editor.org/info/rfc5838>>.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", [RFC 6242](#), DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC7223] Bjorklund, M., "A YANG Data Model for Interface Management", [RFC 7223](#), DOI 10.17487/RFC7223, May 2014, <<https://www.rfc-editor.org/info/rfc7223>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016,

<<https://www.rfc-editor.org/info/rfc7950>>.

- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", [RFC 8040](#), DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.
- [RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, [RFC 8341](#), DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", [RFC 8446](#), DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.
- [RFC8476] Tantsura, J., Chunduri, U., Aldrin, S., and P. Psenak, "Signaling Maximum SID Depth (MSD) Using OSPF", [RFC 8476](#), DOI 10.17487/RFC8476, December 2018, <<https://www.rfc-editor.org/info/rfc8476>>.

Yeung, et al.

Expires 6 July 2022

[Page 33]

Internet-Draft OSPF SR (Segment Routing) YANG Data Model January 2022

- [RFC8665] Psenak, P., Ed., Previdi, S., Ed., Filsfils, C., Gredler, H., Shakir, R., Henderickx, W., and J. Tantsura, "OSPF Extensions for Segment Routing", [RFC 8665](#), DOI 10.17487/RFC8665, December 2019, <<https://www.rfc-editor.org/info/rfc8665>>.
- [RFC9020] Litkowski, S., Qu, Y., Lindem, A., Sarkar, P., and J. Tantsura, "YANG Data Model for Segment Routing", [RFC 9020](#), DOI 10.17487/RFC9020, May 2021, <<https://www.rfc-editor.org/info/rfc9020>>.

7.2. Informative References

- [RFC8022] Lhotka, L. and A. Lindem, "A YANG Data Model for Routing Management", [RFC 8022](#), DOI 10.17487/RFC8022, November 2016, <<https://www.rfc-editor.org/info/rfc8022>>.
- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", [BCP 215](#), [RFC 8340](#), DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.
- [RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K.,

and R. Wilton, "Network Management Datastore Architecture (NMDA)", [RFC 8342](https://www.rfc-editor.org/info/rfc8342), DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.

[Appendix A](#). Contributors' Addresses

Dean Bogdanovic
Volta Networks, Inc.

EMail: dean@voltanet.io

Kiran Koushik Agrahara Sreenivasa
Cisco Systems
12515 Research Blvd, Bldg 4
Austin, TX 78681
USA

EMail: kkoushik@cisco.com

Authors' Addresses

Yeung, et al.

Expires 6 July 2022

[Page 34]

Internet-Draft OSPF SR (Segment Routing) YANG Data Mode January 2022

Derek Yeung
Arrcus

Email: derek@arrcus.com

Yingzhen Qu
Futurewei
2330 Central Expressway
Santa Clara, CA 95050
United States of America

Email: yingzhen.qu@futurewei.com

Jeffrey Zhang
Juniper Networks
10 Technology Park Drive
Westford, MA 01886
United States of America

Email: zzhang@juniper.net

Ing-Wher Chen
The MITRE Corporation

Email: ingwherchen@mitre.org

Acee Lindem
Cisco Systems
301 Midenhall Way
Cary, NC 27513

Email: acee@cisco.com