PAWS Internet-Draft Intended status: Standards Track Expires: August 17, 2013 V. Chen, Ed. Google S. Das Applied Communication Sciences L. Zhu Huawei J. Malyar Telcordia Technologies Inc. P. McCann Huawei February 13, 2013

Protocol to Access Spectrum Database draft-ietf-paws-protocol-03

Abstract

Portions of the radio spectrum that are allocated to licensees are available for non-interfering use. This available spectrum is called "White Space." Allowing secondary users access to available spectrum "unlocks" existing spectrum to maximize its utilization and to provide opportunities for innovation, resulting in greater overall spectrum utilization.

One approach to manage spectrum sharing uses databases to report spectrum availability to devices. To achieve interoperability among multiple devices and databases, a standardized protocol must be defined and implemented. This document defines such a protocol, the "Protocol to Access White Space database" (PAWS).

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of <u>BCP 78</u> and <u>BCP 79</u>.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <u>http://datatracker.ietf.org/drafts/current/</u>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 17, 2013.

Chen, et al.

Expires August 17, 2013

Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to <u>BCP 78</u> and the IETF Trust's Legal Provisions Relating to IETF Documents (<u>http://trustee.ietf.org/license-info</u>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

$\underline{1}$. Introduction	<u>5</u>
 Conventions and Terminology . 	<u>5</u>
<u>2.1</u> . Conventions Used in This Do	ocument
<u>2.2</u> . Terminology	<u>6</u>
<u>3</u> . Protocol Overview	<u>6</u>
<u>3.1</u> . Multi-ruleset Support	
<u>4</u> . Protocol Functionalities	
<u>4.1</u> . Database Discovery	
<u>4.2</u> . Initialization	
<u>4.2.1</u> . INIT_REQ	<u>9</u>
4.2.2. INIT_RESP	<u>9</u>
<u>4.3</u> . Device Registration	
4.3.1. REGISTRATION_REQ	<u>11</u>
4.3.2. REGISTRATION_RESP	<u>11</u>
<u>4.4</u> . Available Spectrum Query .	
4.4.1. AVAIL_SPECTRUM_REQ	<u>14</u>
4.4.2. AVAIL_SPECTRUM_RESP .	
4.4.3. AVAIL_SPECTRUM_BATCH_RE	EQ
4.4.4. AVAIL_SPECTRUM_BATCH_RE	ESP <u>18</u>
4.4.5. SPECTRUM_USE_NOTIFY .	
4.4.6. SPECTRUM_USE_RESP	
4.5. Device Validation	
4.5.1. DEV_VALID_REQ	
4.5.2. DEV_VALID_RESP	
5. Protocol Parameters	
5.1. GeoLocation	
5.2. DeviceDescriptor	
5.3. AntennaCharacteristics	
5.4. DeviceCapabilities	
<u>5.5</u> . DeviceOwner	

<u>5.6</u> . RulesetInfo	•	. <u>28</u>
<u>5.7</u> . Spectrum	•	. <u>29</u>
<u>5.8</u> . FrequencyRange		. <u>29</u>
<u>5.9</u> . EventTime		. <u>30</u>
<u>5.10</u> . SpectrumSchedule		. <u>30</u>
<u>5.11</u> . GeoSpectrumSchedule		. <u>31</u>
5.12. DeviceValidity		. <u>31</u>
5.13. Error Element		. 32
5.13.1. REQUIRED Error		. 33
6. Message Encoding		. 34
6.1. JSON-RPC Binding		. 34
6.2. init Method		. 35
6.2.1. INIT REO Parameters		35
6.2.2 INIT RESP Parameters	•	37
6.3 register Method	•	. <u>07</u>
6.2.1 DECISTRATION DEC Darameters	• •	· <u>57</u> 27
6.2.2 DECISTRATION_REQ Farameters	•	· <u>31</u> 20
0.3.2. REDISTRATION_RESP Parameters	•	. <u>39</u>
	•	. <u>40</u>
6.4.1. AVAILABLE_SPECTRUM_REQ Parameters	•	. <u>40</u>
<u>6.4.2</u> . AVAIL_SPECIRUM_RESP Parameters	•	. <u>42</u>
<u>6.5</u> . getSpectrumBatch Method	•	. <u>45</u>
<u>6.5.1</u> . AVAIL_SPECTRUM_BATCH_REQ Parameters	•	. <u>45</u>
<u>6.5.2</u> . AVAIL_SPECTRUM_BATCH_RESP Parameters	•	. <u>47</u>
<u>6.6</u> . notifySpectrumUse Method	•	. <u>50</u>
<u>6.6.1</u> . SPECTRUM_USE_NOTIFY Parameters	•	. <u>50</u>
<pre>6.6.2. SPECTRUM_USE_RESP Parameters</pre>	•	. <u>52</u>
<u>6.7</u> . verifyDevice Method	•	. <u>53</u>
<u>6.7.1</u> . DEV_VALID_REQ Parameters	•	. <u>53</u>
6.7.2. DEV_VALID_RESP Parameters		. <u>54</u>
<u>6.8</u> . Sub-message Schemas		. <u>55</u>
<u>6.8.1</u> . GeoLocation		. <u>55</u>
<u>6.8.2</u> . DeviceDescriptor		. <u>57</u>
6.8.3. AntennaCharacteristics		. <u>58</u>
<u>6.8.4</u> . DeviceCapabilities		. <u>59</u>
<u>6.8.5</u> . DeviceOwner		. <u>60</u>
<u>6.8.6</u> . RulesetInfo		. <u>61</u>
6.8.7. Spectrum		. 62
6.8.8. FrequencyRange		. 63
6.8.9. EventTime		. 64
6.8.10. SpectrumSchedule		65
6.8.11 GeoSpectrumSchedule	•	66
6.8.12 DeviceValidity	•	66
6.8.13 Additional Properties	•	67
7 HTTPS Rinding	•	67
$\frac{1}{2}$. In FORE Definiting $\frac{1}{2}$. \frac	•	. <u>01</u> 69
2. Excension New Message Decomptore	•	. <u>00</u> 60
0.1, Defining Pulocot Idontifiance	•	. <u>00</u>
0.2. Defining Additional Error Cadaa	•	. 09
0.3. Defining Additional Error Codes	•	. <u>69</u>

9. IANA Considerations	<u>69</u>
<u>9.1</u> . PAWS Parameters Registry	<u>70</u>
<u>9.1.1</u> . Registration Template	<u>70</u>
<u>9.1.2</u> . Initial Registry Contents	<u>70</u>
<u>9.2</u> . PAWS Ruleset ID Registry	<u>71</u>
<u>9.2.1</u> . Registration Template	<u>71</u>
<u>9.2.2</u> . Initial Registry Contents	<u>72</u>
<u>9.3</u> . PAWS Error Code Registry	<u>72</u>
<u>9.3.1</u> . Registration Template	<u>73</u>
<u>9.3.2</u> . Initial Registry Contents	<u>73</u>
<u>10</u> . Security Considerations	<u>73</u>
<u>10.1</u> . Assurance of Proper Database	<u>74</u>
<u>10.2</u> . Protection Against Modification	<u>74</u>
<u>10.3</u> . Protection Against Eavesdropping	<u>75</u>
<u>10.4</u> . Client Authentication Considerations	<u>75</u>
<u>11</u> . Contributors	<u>75</u>
<u>12</u> . Acknowledgments	<u>76</u>
<u>13</u> . References	76
13.1. Normative References	76
<u>13,2</u> . Informative References	77
Appendix A. Changes / Author Notes	78
Authors' Addresses	78

<u>1</u>. Introduction

This section provides some high level introductory material. Readers are strongly encouraged to read Protocol to Access White Space database: PS, use cases and rqmts [<u>I-D.ietf-paws-problem-stmt-usecases-rqmts</u>] for use cases, requirements, and additional background.

A geospatial database can track available spectrum (in accordance with the rules of one or more regulatory domains) and make this information available to devices. This approach shifts the complexity of spectrum-policy conformance out of the device and into the Database. This approach also simplifies adoption of policy changes, limiting updates to a handful of databases, rather than numerous devices. It opens the door for innovations in spectrum management that can incorporate a variety of parameters, including user location and time. In the future, it also can include other parameters, such as user priority, time, signal type and power, spectrum supply and demand, payment or micro-auction bidding, and more.

In providing this service, a database records and updates information necessary to protect primary users -- for example, this information may include parameters such as a fixed transmitter's call sign, its geo-location, antenna height, power, and periods of operation. The rules that the Database must follow, including its schedule for obtaining and updating protection information, protection rules, and information reported to devices, vary according to regulatory domain. Such variations, however, should be handled by each database, and exposure to the variations by devices should be minimized.

This specification defines an extensible protocol to obtain available spectrum from a geospatial database by a device with geo-location capability. It enables a device to operate in any regulatory domain that implements the same protocol and in which the device is authorized to operate. The document describes the use of HTTP/TLS as transport for the protocol.

2. Conventions and Terminology

2.1. Conventions Used in This Document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in Key words for use in RFCs to Indicate Requirement Levels [RFC2119].

2.2. Terminology

- Database or Spectrum Database: A database that provides spectrum availability information to devices.
- Master Device: A device with geo-location capability that queries a database to find available spectrum.
- Slave Device: A device without geo-location capability that uses the spectrum made available by a Master Device. It does not query the Database directly.

RAT: Radio Access Technology

3. Protocol Overview

A Master Device uses the PAWS protocol to obtain a schedule of available spectrum at its location. The security necessary to ensure the accuracy, privacy, and confidentiality of the Device's location is described in the Security Considerations (<u>Section 10</u>). This document assumes that the Master Device and the Database are connected to the Internet.

A typical sequence of PAWS operations is outlined as follows. See Protocol Functionalities (<u>Section 4</u>) and Protocol Parameters (<u>Section 5</u>) for details:

- The Master Device locates or discovers the regulatory domain for its location and the URI for the Database to send subsequent PAWS messages. [Editor's Note: It is an open item whether database discovery should be a separate document.]
- 2. The Master Device establishes an HTTPS session with the Database.
- 3. The Master Device optionally sends an initialization message to the Database to exchange capabilities.
- 4. If the Database receives an initialization message, it responds with a message in the body of the HTTP response.
- 5. If required by regulatory domain, the Database registers the Master Device.
- 6. The Master Device sends an available-spectrum request message to the Database.
- 7. If the Master Device is obtaining the schedule on behalf of a Slave Device, and if required by the regulatory domain, the Database validates the Slave Device.
- 8. The Database responds with an available-spectrum response message in the body of the HTTP response.
- 9. Depending on regulatory domain requirements and database implementation, the Master Device sends a spectrum-usage notification message to the Database.

 If the Database receives a spectrum-usage notification message, it responds by sending the Master Device a spectrum-usage acknowledgement message.

3.1. Multi-ruleset Support

For a Master Device that supports multiple rule sets and operates with multiple databases in multiple regulatory domains, the PAWS protocol supports the following sequence of operations for each request by the Master Device:

- 1. The Master Device includes in its request the identifier of one or more of the rule sets it supports
- 2. The Database may use the rule-set list to determine its response, for example, to select the list of required parameters
- If required parameters are missing from the request, the Database responds with a REQUIRED error and a list of the missing parameters
- 4. The Master Device makes the request again, adding the missing parameters
- 5. The Database responds to the request, including the identifier of the applicable rule set
- 6. The Master Device uses the indicated rule set to determine how to interpret the Database response

NOTE: Regulatory rules contain many device-only requirements that govern device behavior, independent of any database rules. These requirements may be complex and involve device behavior that are not easily parameterized. The ruleset-id parameter provides a mechanism for the Database to inform the Master Device of the applicable rule set without having to express device-side behavior within the protocol. The rule-set identifier could be a string that contains the entity that established the rules and version information, such as "FccTvBandWhiteSpace-2010".

By separating the regulatory "authority" from the "ruleset-id", it allows the protocol to support multiple regulatory authorities that use the same device-side rule set. It also allows support for a single authority to define multiple rule sets.

<u>4</u>. Protocol Functionalities

The PAWS protocol consists of several components:

o Database Discovery (<u>Section 4.1</u>) MUST be supported by the Master Device

- o Initialization (<u>Section 4.2</u>) MAY be used by the Master Device and MUST be implemented by the Database.
- o Device Registration (<u>Section 4.3</u>) MAY be used by the Master Device and MAY be implemented by the Database.
- o Available Spectrum Query (<u>Section 4.4</u>) MUST be supported by Master Device and the Database.
- o Device Validation (<u>Section 4.5</u>) MAY be used by the Master Device and MUST be implemented by the Database if the regulatory domain requires device validation.

This section describes the protocol components and their messages. Protocol Parameters (<u>Section 5</u>) contains a more thorough discussion of the parameters that comprise the PAWS request and response messages. Message Encoding (<u>Section 6</u>) provides details of the message encodings. HTTPS Binding (<u>Section 7</u>) describes the use of HTTPS HTTP Over TLS [<u>RFC2818</u>] for transporting PAWS messages and optional device authentication.

4.1. Database Discovery

The Device MUST determine the URI for the Database and applicable regulatory domain before it can send PAWS messages. The URI for the Database SHOULD be obtained from an authorized and authenticated entity, but it MAY be statically configured into the Device. [Editor's Note: It is an open item whether database discovery should be a separate document.]

4.2. Initialization

A Master Device SHOULD use the initialization procedure to exchange capability information with the Database whenever the Master Device powers up or initiates communication with the Database. The initialization response informs the Master Device of specific regulatory-dependent parameterized-rule values, such as threshold distances and time periods beyond which the Device must update its available-spectrum data (see RuleSetInfo (Section 5.6)). The Master Device MAY manually configure these parameterized-rule values. The initialization message also represents extension points for database implementations or regulatory domains that require the extra handshake.

The Initialization request procedure is depicted in Figure 1. o INIT_REQ (<u>Section 4.2.1</u>) is the initialization request message o INIT_RESP (<u>Section 4.2.2</u>) is the initialization response message



Figure 1

4.2.1. INIT_REQ

The initialization request message allows the Master Device to initiate exchange of capabilities with the Database.

+	+
INIT_REQ	
+	+
deviceDesc:DeviceDescriptor location:GeoLocation	required required
1	
*other:any	depends
+	++

Parameters:

deviceDesc: The DeviceDescriptor (Section 5.2) for the Device is REQUIRED. If the Database does not support the regulatory domain specified by the "authority" parameter, it MUST return an error with the UNSUPPORTED (Table 1) code in the error response. location: The GeoLocation (Section 5.1) for the Device is REQUIRED. other: Depending on the regulatory domain or database implementation, the Master Device MAY specify additional handshake parameters in the INIT_REQ message. The Database MUST ignore all parameters it does not understand.

4.2.2. INIT_RESP

The initialization response message communicates database parameters to the requesting device.

+	+
INIT_RESP	I
+	++
rulesetInfo:RulesetInfo	required
*other:any	depends
+	++

- rulesetInfo: This RulesetInfo (Section 5.6) parameter MUST be included in the response. This parameter specifies the regulatory domain and parameters applicable for that domain. The Database MUST include the "authority" that defines the regulatory domain for the location specified in the INIT_REQ (Section 4.2.1) message.
- other: Depending on the regulatory domain or database implementation, the Database MAY include additional handshake parameters in the INIT_RESP (<u>Section 4.2.2</u>) message. The Master Device MUST ignore all parameters it does not understand.

4.3. Device Registration

When a regulatory domain requires registration of a Master Device, the Device MUST send its registration information to the Database to establish certain operational parameters. FCC rules, for example, require that a 'Fixed Device' MUST register its owner and operator contact information, its device identifier, its location, and its antenna height.

The Database MAY support device registration as a separate Device Registration component, or as part of the Spectrum Availability component. If the Database does not support a separate Device Registration request, it MUST return an error with the UNIMPLEMENTED (Table 1) code in the error-response message.

The Device Registration request procedure is depicted in Figure 2.

- o REGISTRATION_REQ (<u>Section 4.3.1</u>) is the device-registration request message
- o REGISTRATION_RESP (<u>Section 4.3.2</u>) is the device-registration response message





4.3.1. REGISTRATION_REQ

The registration request message contains the required registration parameters.

```
+----+

|REGISTRATION_REQ |

+----+

|deviceDesc:DeviceDescriptor | required |

|location:GeoLocation | required |

|deviceOwner:DeviceOwner | required |

|.....|

|*other:any | depends |

+----+
```

Parameters:

location: The GeoLocation (Section 5.1) for the Device is REQUIRED. deviceOwner: The DeviceOwner (Section 5.5) information is REQUIRED. other: Regulatory domains MAY require additional registration parameters. To simplify its registration logic, the Device MAY send a union of the registration information required by all supported regulatory domains. The Database MUST ignore all parameters it does not understand .

4.3.2. REGISTRATION_RESP

The registration response message simply acknowledges receipt of the request and is otherwise empty. Future extensions may add parameters to this message.

+			-+
REGISTRATION_RESP			Ι
+	-+-		- +
*other:any		depends	Ι
+	-+-		- +

<u>4.4</u>. Available Spectrum Query

To obtain the available spectrum from the Database, a Master Device sends a request that contains its geo-location and any parameters required by the regulatory rules (such as device identifier, capabilities, and characteristics). The Database returns a response that describes what frequencies are available, at what permissible operating power levels, and a schedule of when they are available.

The Available Spectrum Query procedure is depicted in Figure 3.

- o AVAIL_SPECTRUM_REQ (<u>Section 4.4.1</u>) is the available-spectrum request message
- o AVAIL_SPECTRUM_RESP (<u>Section 4.4.2</u>) is the available-spectrum response message
- o AVAIL_SPECTRUM_BATCH_REQ (Section 4.4.3) is an OPTIONAL batch version of the available-spectrum request message that allows multiple locations to be specified in the request
- o AVAIL_SPECTRUM_BATCH_RESP (<u>Section 4.4.4</u>) is the response message for the batch version of the available-spectrum request that contains available spectrum for each location
- o SPECTRUM_USE_NOTIFY (<u>Section 4.4.5</u>) is the spectrum-usage notification message
- o SPECTRUM_USE_RESP (<u>Section 4.4.6</u>) is the spectrum-usage acknowledgment message



Figure 3

- 1. First, the Master Device sends an available-spectrum request message to the Database.
- The Database MUST respond with an error using the NOT_REGISTERED (Table 1) code if:
 - * registration information is required, and
 - * the request does not include registration information, and
 - * the Device has not previously registered
- 3. If the location specified in the request is outside the regulatory domain, the Database MUST respond with an OUTSIDE_COVERAGE (Table 1) error. If some locations within a batch request are outside the regulatory domain, the Database MAY return an OK response with available spectrum for only the valid locations. If all locations within a batch request are outside the regulatory domain, the Database MUST respond with an OUTSIDE_COVERAGE error.
- 4. The Database MAY perform other validation of the request, (e.g., checking for missing required parameters, authorizations). It MUST return an error with appropriate error code (Table 1), if validation fails. If the request is missing required parameters, the Database MUST respond with a REQUIRED (Table 1) error and SHOULD include a list of the missing parameters.
- 5. If the request is valid, the Database responds with an availablespectrum response message. If the regulatory domain requires that devices must report anticipated spectrum usage, the Database MUST indicate so in the response message.

- If the available-spectrum response indicates that the Master Device must send a spectrum-usage notification message, the Master Device MUST send the notification message to the Database.
- If the Database receives a spectrum-usage notification message, it MUST send a spectrum-usage acknowledgment message to the Master Device.

The procedure for asking for available spectrum on behalf of a Slave Device is similar, except that the process is initiated by the Slave Device. Also, the device identifier, capabilities, and characteristics communicated in the AVAIL_SPECTRUM_REQ message SHALL be those of the Slave Device. Although the communication and protocol between the Slave Device and Master Device is outside the scope of this document, the expected message sequence is shown in Figure 4.

++ +	·+	++
Slave Device	Master Device	Spectrum Database
++ +	•+	++
	I	I
AVAIL_SPEC_REQ	2	I
	.>	I
		I
	AVAIL_SPECTRUM	_REQ
		>
		I
	AVAIL_SPECTRUM	_RESP
	<	
		I
AVAIL_SPEC_RES	<pre>SP (SPECTRUM_USE_N</pre>	OTIFY)
<		>
		I
	(SPECTRUM_USE_	RESP)
	<	



4.4.1. AVAIL_SPECTRUM_REQ

The request message for the Available Spectrum Query protocol MUST include the Device's geo-location. If allowed by the regulatory domain, the location MAY be an anticipated location.

+	+
AVAIL_SPECTRUM_REQ	
++	+
<pre> deviceDesc:DeviceDescriptor location:GeoLocation antenna:AntennaCharacteristics owner:DeviceOwner capabilities:DeviceCapabilities +</pre>	required required depends on regulatory domain depends on regulatory domain optional

deviceDesc: The DeviceDescriptor (<u>Section 5.2</u>) for the Device is REQUIRED.

- location: The GeoLocation (Section 5.1) for the Device is REQUIRED. The location SHOULD be the current location of the Device, but more precisely, the location of the radiation center of the Device's antenna. Depending on the regulatory domain, the location MAY be an anticipated position of the Device to support mobile devices. If the location specifies a region, rather than a point, the Database MAY return an error with the UNIMPLEMENTED (Table 1) code, if it does not support guery by region.
- antenna: Depending on the device type and regulatory domain, the AntennaCharacteristics (<u>Section 5.3</u>) MAY be required.
- owner: Depending on the device type and regulatory domain, the DeviceOwner (<u>Section 5.5</u>) information MAY be included to register the Device with the Database. This enables the Device to register and get spectrum-availability information in a single request.
- capabilities: The Master Device MAY include its DeviceCapabilities (Section 5.4) to limit the available-spectrum response to the spectrum that is compatible with its capabilities. The Database SHOULD NOT return spectrum that is not compatible with the specified capabilities.

4.4.2. AVAIL_SPECTRUM_RESP

The response message for the Available Spectrum Query contains a schedule of available spectrum for the Device.

+	+
AVAIL_SPECTRUM_RESP	++
<pre> timestamp:string deviceDesc:DeviceDescriptor spectrumSchedules:list needsSpectrumReport:bool rulesetId:string </pre>	required required required + optional optional optional ++ 0* V
	SpectrumSchedule ++ time:EventTime required spectrum:Spectrum required

timestamp: Timestamp of the response of the form, YYYY-MM-DDThh:mm:ssZ, as defined by Date and Time on the Internet: Timestamps [RFC3339]. This SHOULD be used by the Device as a reference for the start and stop times in the spectrum schedules. deviceDesc: The Database MUST include the DeviceDescriptor (Section 5.2) specified in the AVAIL_SPECTRUM_REQ message spectrumSchedules: The SpectrumSchedule (Section 5.10) list is REQUIRED (though it MAY be empty if no spectrum is available). The Database MAY return more than one SpectrumSchedule (Section 6.8.10) to represent future changes to the available spectrum. How far in advance a schedule may be provided depends on the regulatory domain.

- needsSpectrumReport: For regulatory domains that require a spectrumusage report from devices, the Database MUST return true for this parameter. The default value is false.
- rulesetId: The Database SHOULD return the identifier of the applicable rule set for the response (see Ruleset ID Registry (Section 9.2)). If included, the Device MUST use the corresponding rule set to interpret the response.
- location: The Database MAY copy other elements from the request, such as the GeoLocation (Section 5.1) of the Device. The Device MUST ignore any parameters it does not understand.

4.4.2.1. Update Requirements

When the stop time specified in the schedule has been reached, the Device:

- o MUST obtain a new spectrum-availability schedule, either by using the next one in the list (if provided) or making another Available Spectrum Query (Section 4.4)
- o If the new schedule indicates the in-use spectrum is no longer available, the Device MUST stop operation immediately.
- o If the Device is unable to contact the Database to obtain a new schedule, depending on the regulatory domain, the Device MAY continue to operate for a period of time, as indicated by parameters returned in the INIT_RESP (Section 4.2.2) message.

When the Device moves beyond a threshold distance (established by regulatory rules) away from the actual location and all anticipated location(s) it reported in previous AVAIL_SPECTRUM_REQ or AVAIL_SPECTRUM_BATCH_REQ requests (see "maxLocationChange" in RulesetInfo (Section 5.6)), it:

- o MUST obtain a new spectrum-availability schedule by making another Available Spectrum Query (<u>Section 4.4</u>).
- o If the new response indicates the in-use spectrum is no longer available, the Device MUST stop operation immediately.
- o If the Device is unable to contact the Database to obtain a new schedule, depending on the regulatory domain, the Device MUST stop operation immediately.

4.4.3. AVAIL_SPECTRUM_BATCH_REQ

The Database MAY support the batch request that allows multiple locations to be specified. This allows a portable Master Device to get available spectrum for a sequence of anticipated locations using a single request. The Database MUST interpret each location in the batch request as if it were an independent request and MUST return results consistent with multiple individual AVAIL_SPECTRUM_REQ (Section 4.4.1) requests. The request message for the batch Available Spectrum Query protocol MUST include at least one GeoLocation (Section 5.1). If the Database does not support batch requests, it MUST return a UNIMPLEMENTED (Table 1) error.

+-----+ AVAIL_SPECTRUM_BATCH_REQ +-----+ |deviceDesc:DeviceDescriptor | required |locations:list | required |--+ |antenna:AntennaCharacteristics | depends on regulatory domain | | |owner:DeviceOwner | depends on regulatory domain | | |capabilities:DeviceCapabilities| optional +----+ | 1..* V +---+ | GeoLocation | +----+

Parameters:

- locations: The GeoLocation (Section 5.1) list for the Device is REQUIRED. This allows the Device to specify its actual location plus additional anticipated locations, when allowed by the regulatory domain. At least one location MUST be included. This specification places no upper limit on the number of locations, but the Database MAY restrict the number of locations it supports by returning a response with fewer locations than specified in the request.
- antenna: Depending on the device type and regulatory domain, the AntennaCharacteristics (<u>Section 5.3</u>) MAY be required.
- owner: Depending on the device type and regulatory domain, the DeviceOwner (<u>Section 5.5</u>) information MAY be included to register the Device with the Database. This enables the Device to register and get spectrum-availability information in a single request.
- capabilities: The Master Device MAY include its DeviceCapabilities
 (Section 5.4) to limit the available-spectrum response to the
 spectrum that is compatible with its capabilities. The Database
 SHOULD NOT return spectrum that is not compatible with the
 specified capabilities.

4.4.4. AVAIL_SPECTRUM_BATCH_RESP

The response message for the batch Available Spectrum Query contains a schedule of available spectrum for the Device at multiple locations.



timestamp: Timestamp of the response of the form, YYYY-MM-DDThh:mm:ssZ, as defined by Date and Time on the Internet: Timestamps [RFC3339]. This SHOULD be used by the Device as a reference for the start and stop times in the spectrum schedules. deviceDesc: The Database MUST include the DeviceDescriptor (<u>Section 5.2</u>) specified in the AVAIL_SPECTRUM_REQ message geoSpectrumSchedules: The geoSpectrumSchedule (Section 5.11) list is REQUIRED (though it MAY be empty if spectrum is unavailable). For each location, the Database MAY return more than one GeoSpectrumSchedule (Section 6.8.11) to represent future changes to the available spectrum. How far in advance a schedule may be provided depends on the regulatory domain. The Database MAY return available spectrum for fewer locations than requested. The Device MUST NOT make any assumptions on the order of the entries in the list and MUST use the location value in each GeoSpectrumSchedule entry to match available spectrum to a location. needsSpectrumReport: For regulatory domains that require a spectrum-

usage report from devices, the Database MUST return true for this parameter. The default value is false.

rulesetId: The Database SHOULD return the identifier of the applicable rule set for the response (see Ruleset ID Registry (Section 9.2)). If included, the Device MUST use the corresponding rule set to interpret the response.

See Update Requirements (<u>Section 4.4.2.1</u>) for when the Device must update its available spectrum data.
4.4.5. SPECTRUM_USE_NOTIFY

The spectrum-use notification message MUST contain the geo-location of the Device and parameters required by the regulatory domain.



Parameters:

location: The GeoLocation (<u>Section 5.1</u>) for the Device is REQUIRED. spectra: The Spectrum (<u>Section 5.7</u>) list is REQUIRED, and specifies

- the spectrum anticipated to be used by the Device, which includes frequency ranges and maximum power levels. For consistency, the "bandwidth" value SHOULD match that from one of the Spectrum (Section 5.7) elements in the corresponding AVAIL_SPECTRUM_RESP message, and the maximum power levels in the Spectrum element MUST be expressed as total power (EIRP) computed over the specified "bandwidth" value. The actual bandwidth to be used (as computed from the start and stop frequencies) MAY be different from the "bandwidth" value. As an example, when regulatory rules express maximum power spectral density in terms of maximum power over any 100 kHz band, then the "bandwidth" value should be set to 100 kHz, even though the actual bandwidth used can be 20 kHz.
- other: Depending on the regulatory domain, other parameters MAY be required. To simplify its logic, the Device MAY include the union of all parameters required by all supported regulatory domains. The Database MUST ignore all parameters it does not understand.

4.4.6. SPECTRUM_USE_RESP

The spectrum-use response message simply acknowledges receipt of the notification.

<u>4.5</u>. Device Validation

Typically, a Slave Device needs a Master Device to ask the Database on its behalf for available spectrum. Depending on the regulatory domain, the Master Device also must validate with the Database that the Slave Device is permitted to operate. When regulatory rules allow a Master Device to "cache" the available spectrum for a period of time, the Master Device MAY use the simpler Device Validation component, instead of the full Available Spectrum Query component, to validate a Slave Device.

When validating one or more Slave Devices, the Master Device sends the Database a request that includes the device identifier -- and any other parameters required by the regulatory rules -- for each Slave Device. The Database MUST return a response that indicates whether each device is permitted to use the spectrum.

A typical sequence for using the Device Validation request is illustrated in Figure 5, where the Master Device already has a valid set of available spectrum for Slave Devices. Note that the communication and protocol between the Slave Device and Master Device is outside the scope of this document.

- o DEV_VALID_REQ (<u>Section 4.5.1</u>) is the device-validation request message
- o DEV_VALID_RESP (<u>Section 4.5.2</u>) is the device-validation response message



Figure 5

4.5.1. DEV_VALID_REQ

+----+ |DEV_VALID_REQ | +-----+ |deviceDescs:list | required |----+----+ | V 1..* +----+ |DeviceDescriptor | +----+

Parameters:

deviceDescs: A DeviceDescriptor (<u>Section 5.2</u>) list is REQUIRED, which specifies the list of Slave Devices that to be validated.

4.5.2. DEV_VALID_RESP

+ DEV_VALID_RESP	+ 	
deviceValidities:list required ++ V 1*		
	+ DeviceValidity +	+ +
	deviceDesc:DeviceDescriptor required isValid:boolean required	d d

Parameters:

deviceValidities: A DeviceValidities (Section 5.12) list is REQUIRED to report the list of Slave Devices and whether each listed Device is valid. The number of entries MUST match the number of DeviceDescriptors (Section 5.2) listed in the DEV_VALID_REQ message.

5. Protocol Parameters

This section presents more details of the parameters that make up the PAWS request and response messages. It also includes a sub-section defining response codes.

5.1. GeoLocation

This parameter is used to specify the geo-location of the Device. It may be used to specify one of the following:

- o A single point with optoinal uncertainty
- o A region described by a polygon

These are represented using geometric shapes defined in GEORIV Presence Information Data Format Location Object [<u>RFC5491</u>], where:

- o A "point" with uncertainty is represented using the Ellipse shape
- o A region represented using the Polygon shape

The coordinates are expressed using the WGS84 datum, and units are degrees or meters. The data model for GeoLocation is illustrated below:

+----+

+		+	
GeoLocation			
<pre> point:Ellipse region:Polygon confidence:int </pre>	optional optional optioanl	+ 	
Note: point and polyg	jon are mutu	+ ally exclusive	
1			
Ellipse		+ 	
+	+	+ +	+
center:Point	required	> Point	
semiMajorAxis:float	optional	++ llatitude:float r	required
orientation:float	optional	longitude:float r	equired
+	+	+ ++	+
+		+	
Polygon			
++		+ 3* +	+
exterior:list ++	required	> Point + +	 ++-
		latitude:float	required
		longitude:float	required

Parameters:

- point: If present, it indicates that the GeoLocation represents a point. Paradoxically, a "point" is parameterized using an Ellipse, where the center represents the location of the point and the distances along the major and minor axes represent the uncertainty. The uncertainty values MAY be required, depending on the regulatory domain.
- region: If present. in indicates that the GeoLocation represents a region. Database support for regions is OPTIONAL.
- center: The center refers to the location of a GeoLocation pont and is the represented as the center of an ellipse. REQUIRED.
- latitude, longitude: Floating-point numbers that express the latitude and longitude in degrees using the WGS84 datum. REQUIRED.

Internet-Draft

- semiMajorAxis, semiMinorAxis: If required by the regulator domain, the location uncertainty, in meters, is parameterized using distances along the major and minor axes of the ellipse. When uncertainty is optional, the default value of each is 0.
- orientation: This defines the orientation of the ellipse, expressed as the rotation, in degrees, of the semi-major axis from North towards the East. For example, when the uncertainty is greatest along the North-South direction, orientation is 0 degrees; conversely, if the uncertainty is greatest along the East-West direction, orientation is 90 degrees. When orientation is optoinal, its default value is 0.
- exterior: When GeoLocation describes a region, the "exterior" field refers to a list of latitude/longitude points that represents the vertices of a polygon. A minimum of 3 points is required, and they must be in counter-clockwise direction.
- confidence: The location confidence level, as an integer percentage, MAY be required, depending on the regulatory domain. When the parameter is optional, its default value is 100. This values is only meaningful when GeoLocation refers to a point.

5.2. DeviceDescriptor

The device descriptor contains parameters that identify the specific device, such as its manufacturer serial number, regulatory-specific ID (e.g., FCC ID), and any other device characteristics required by regulatory domains.

+		-
DeviceDescriptor		_
serialNumber:string rulesetIds:list fccId:string	required optional depends on regulatory domain	
*deviceType:string *RAT:string *other:any	depends on regulatory domain depends on regulatory domain	_

Parameters:

serialNumber: The manufacturer's device serial number is REQUIRED.
rulesetIds: List of identifiers for rule sets supported by the
 device (see Ruleset ID Registry (Section 9.2)). A Database MAY
 require that the device provides this list before servicing the
 device requests. If the Database does not support any of the rule
 sets specified in the list, the Database MAY refuse to service the
 device requests. See Section 5.6 for discussion on rule-set

identifier.

fccId: The Device's FCC ID may be required for some regulatory
 domains.

Additional parameters in the DeviceDescriptor depend on each regulatory domain and are listed in the figure for illustrative purposes. It can be extended, for example, to include certification IDs for additional regulatory domains.

5.3. AntennaCharacteristics

Antenna characteristics provide additional information, such as the antenna height, antenna type, etc. Whether antenna characteristics must be provided in a request depends on the device type and regulatory domain.

+	+
AntennaCharacteristics	
+	++
height:float	depends on regulatory domain
heightType:enum	optional
heightUncertainty:float	depends on regulatory domain
<pre> *characteristics:</pre>	depends on regulatory domain
various	
+	++

Parameters:

- height: The antenna height in meters. Whether the antenna height is required depends on the device type and the regulatory domain. Note that the height may be negative.
- - AGL Above ground level (default)
 - AMSL Above mean sea level
- heightUncertainty: The height uncertainty in meters. Whether this is required depends on the regulatory domain.

Depending on the regulatory authority, additional antenna characteristics may be required, such as:

- o antenna direction
- o antenna radiation pattern
- o antenna gain
- o antenna polarization

<u>5.4</u>. DeviceCapabilities

Device capabilities provide additional information that MAY be used by the Device to provide additional information to the Database that may help it to determine available spectrum. If the Database does not support device capabilities it MUST ignore the parameter altogether.

++		
DeviceCapabilities	+	
<pre> frequencyRanges:list optional </pre>	-> FrequencyRange	
0	startHz:float stopHz:float maxPowerDBm:float channelId:string	required required : unused optional

Parameters:

frequencyRanges: Optional FrequencyRange (Section 5.8) list. Each
FrequencyRange element MUST contain start and stop frequencies,
and optionally, channel IDs, in which the Device can operate.
When specified, the Database SHOULD NOT return available spectrum
that falls outside these ranges (or channel IDs).

5.5. DeviceOwner

This parameter contains device-owner information required as part of device registration. Regulatory domains MAY require additional parameters.

+	+
DeviceOwner	I
+	++
owner:vcard operator:vcard	required optional
+	++

Parameters:

owner: The vCard contact information for the individual or business that owns the Device is REQUIRED.

operator: The vCard contact information for the device operator is OPTIONAL, but may be required by specific regulatory domains

NOTE: Depending on the regulatory domain, the Database MAY be required to validate the device-owner information. In these cases, the Database MUST respond with an error if validation fails.

All contact information MUST be expressed using the vCard Format [RFC6350]. Only the contact fields of vCard are supported:

fn Full name of an individual
org Name of the organization
adr Address fields
tel Telephone numbers
email Email addresses

5.6. RulesetInfo

This contains parameters for the rule set of a regulatory domain that is communicated using the Initialization component (<u>Section 4.2</u>).

+	+
RulesetInfo	
authority:string maxLocationChange:float maxPollingSecs:int rulesetIds: list 	<pre> required required required optional </pre>
*other:any +	depends ++

Parameters:

- authority: A string that indicates the regulatory domain to which the rule set applies is REQUIRED. It MUST use the 2-letter country codes defined by Country Codes - ISO 3166 [ISO3166-1].
- maxLocationChange: The maximum location change in meters is REQUIRED. When the Device changes location by more than this specified distance, it MUST contact the Database to get the available spectrum for the new location. If the Device is using spectrum that is no longer available, it MUST stop operation in those frequencies immediately.
- maxPollingSecs: The maximum duration, in seconds, between requests for available spectrum is REQUIRED. The Device MUST contact the Database to get available spectrum no less frequently than this duration. If the new spectrum information indicates that the Device is using spectrum that is no longer available, it MUST stop operation in those frequencies immediately.

- rulesetIds: The Database SHOULD return the identifier of the applicable rule set (see Ruleset ID Registry (<u>Section 9.2</u>)). If included, the Device MUST use the corresponding rule set to interpret the response.
- other: This message is intended to be extensible with other regulatory-specific parameters. Devices MUST ignore all parameters in the message it does not understand.

5.7. Spectrum

Available spectrum can logically be characterized by a list of frequency ranges and permissible power levels for each range.

Spectrum ++ bandwidth:float required +> FrequencyRange ++ 0* ++ startHz:float required stopHz:float required maxPowerDBm:float optional channelId:string optional	+	+				
<pre> bandwidth:float required ++ frequencyRanges:list required > FrequencyRange ++ 0* ++ startHz:float required stopHz:float required maxPowerDBm:float optional channelId:string optional ++</pre>	Spectrum +	 ++				
	bandwidth:float frequencyRanges:list +	required required ++	+ Freque 0* + startH stopHz maxPow channe	encyRange Iz:float :float werDBm:float elId:string	+ required required optional optional	+ + + + + + + + + + + + + + + + + + + +

Parameters:

- bandwidth: This parameter is REQUIRED to define the operating bandwidth for which permissible power levels is to be specified. For example, FCC regulation would require only one spectrum specification at 6MHz bandwidth, but Ofcom regulation would require 2 specifications, at 0.1MHz and 8MHz. This parameter MAY be empty if there is no available spectrum.
- frequencyRanges: A FrequencyRange (Section 5.8) list is REQUIRED to specify frequency ranges and permissible power levels. The list MAY be empty if there is no available spectrum.

<u>5.8</u>. FrequencyRange

The FrequencyRange parameter specifies the maximum permissible power levels within a frequency range. startHz: The inclusive start of the frequency range is REQUIRED. stopHz: The exclusive end of the frequency range is REQUIRED. maxPowerDBm: The maximum total power level (EIRP) -- computed over the corresponding operating bandwidth -- that is permitted within the frequency range. Depending on the context in which the FrequencyRange element appears, maxPowerDBm may be REQUIRED. For example, it is REQUIRED in the AVAIL_SPECTRUM_RESP

(<u>Section 4.4.2</u>), AVAIL_SPECTRUM_BATCH_RESP (<u>Section 4.4.4</u>), and SPECTRUM_USE_NOTIFY (<u>Section 4.4.5</u>) messages, but it would not be REQUIRED (nor applicable) when the FrequencyRange element appears in Device Capabilities (<u>Section 5.4</u>).

channelId: The server MAY include a channel identifier, when applicable. When it is included, the Master Device SHOULD treat it as informative.

NOTE: (maxPowerDBm / bandwidth) defines the maximum permitted EIRP spectral density.

5.9. EventTime

The EventTime element specifies the start and stop times of an "event". This is used to indicate the time period for which a Spectrum (<u>Section 5.7</u>) is valid.

+	+
EventTime	I
+	++
startTime:string	required
stopTime:string	required
+	++

Parameters:

startTime: The inclusive start of the event is REQUIRED. stopTime: The exclusive end of the event is REQUIRED.

Both times are expressed using the format, YYYY-MM-DDThh:mm:ssZ, as defined by Date and Time on the Internet: Timestamps [<u>RFC3339</u>]. The times MUST be expressed using UTC.

5.10. SpectrumSchedule

The SpectrumSchedule element combines EventTime with Spectrum to define a time period in which the spectrum is valid.

+	+		
' SpectrumSchedule			
eventTime:EventTime spectra:list +	required required -	+	+- +-
		bandwidth:float frequencyRanges:lis	 t -+

Parameters:

eventTime: The EventTime (<u>Section 5.9</u>) is REQUIRED to express "when" this specification is valid.

spectra: Spectrum (Section 5.7) list is REQUIRED to specify the available spectrum and permissible power levels, one per bandwidth. The list MAY be empty when there is no available spectrum.

5.11. GeoSpectrumSchedule

The GeoSpectrumSchedule element encapsulates the schedule of available spectrum at a location.

+	- +
GeoSpectrumSchedule	 _+
location:GeoLocation required spectrumSchedules:list required +	 + 0* V
	<pre> SpectrumSchedule ++ time:EventTime required spectrum:Spectrum required </pre>
	++

Parameters:

location: The GeoLocation (Section 5.1) is REQUIRED to identify the location at which the spectrum schedule applies

spectrumSchedules: The SpectrumSchedule (Section 5.10) list is REQUIRED. At least one schedule MUST be included (though it MAY be empty if there is no available spectrum). More than one schedule MAY be included to represent future changes to the available spectrum.

5.12. DeviceValidity

The DeviceValidity element is used to indicate whether a device is valid. See <u>Section 4.5.2</u>.

+			- + -
DeviceValidity	т		
deviceDesc:DeviceDescriptor isValid:boolean reason:string		required required optional	
T	· • •		

Parameters:

deviceDesc: The DeviceDescriptor (<u>Section 5.2</u>) that was used to check for validity is REQUIRED.

isValid: A REQUIRED boolean value that indicates whether the Device is valid.

reason: If the device identifier is not valid, the Database MAY include a reason. The reason MAY be in any language.

5.13. Error Element

If the Database responds to a PAWS request message with an error, it MUST include an Error element.

+	+
Error	
+	-++
code:int	required
message:string	optional
data:any	optional
+	-++

Parameters:

code An integer code that indicates the error type.
message A short description of the error. It MAY be in any
language.

data The Database MAY include additional data. For some errors, additional data may be required. The Device MUST ignore any data parameters it does not understand.

The following table defines valid error codes. They are loosely grouped into the following categories:

- -100s Indicates compatibility issues, e.g., version mismatch, unsupported or unimplemented features.
- -200s Indicates that the Device request contains an error that needs to be modified before making another request.

Internet-Draft

paws-protocol

-300s Indicates authorization-related issues.

Code	Name	Description
-100	(reserved)	
-101	VERSION	The Database does not support the specified version of the message.
-102	UNSUPPORTED	The Database does not support the Device. For example, it does not support the regulatory domain specified in the request.
-103	UNIMPLEMENTED	The Database does not implement the optional request or optional feature.
-104	OUTSIDE_COVERAGE	The specified geo-location is outside the coverage area of the Database.
-200	(reserved)	
-201	REQUIRED	A required parameter is missing. The Database MUST include a list of the required parameter names. The Database MAY include only names of parameters that are missing, but MAY include a full list. When providing only a listing of missing parameters, the Database SHOULD include the full list of missing parameters to minimize number of re-queries from the Device.
-202	INVALID_VALUE	A parameter value is invalid in some way. The Database SHOULD include a message indicating which parameter(s) and why the value is invalid.
-300	(reserved)	
-301	UNAUTHORIZED	The Device is not authorized to used the Database. Authorization may be determined by regulatory rules or be dependent on prior arrangement between the Device and Database.
-302	NOT_REGISTERED	Device registration required, but the Device is not registered.

Table 1: Error Codes

5.13.1. REQUIRED Error

When the error code is REQUIRED, the Error element MUST include a Parameters element as its "data" field.

+	+		
Error			
code:int message:string data:Parameters +	required optional optional > ++	+ Parameters +	+
		parameters:list *other:any +	required optional ++

Parameters:

- parameters List of parameter names. The name of a parameter SHOULD be expressed using dotted notation, when appropriate, e.g., "deviceDesc.serialNumber".
- other The Database MAY include other parameters. The Device MUST ignore all parameters it does not understand.

<u>6</u>. Message Encoding

The PAWS protocol is encoded using JSON-RPC [JSON-RPC] (see also JavaScript Object Notation (JSON) [RFC4627]). Each component described in Protocol Functionalities (Section 4) corresponds to one or more JSON-RPC methods. This section provides the JSON schema for each of the protocol messages and parameters defined in sections Protocol Functionalities (Section 4) and Protocol Parameters (Section 5). JSON schemas are presented in accordance with A JSON Media Type for Describing the Structure and Meaning of JSON Documents [I-D.zyp-json-schema].

NOTE: In general, all messages defined in this section are extensible by adding additional properties to support regulatory-specific and database-specific requirements. In all cases, the Device or Database MUST ignore any parameter it does not understand.

6.1. JSON-RPC Binding

The JSON-RPC [<u>JSON-RPC</u>] protocol consists of two basic objects, Request and Response:

- o The JSON-RPC Request object encapsulates a PAWS functionality (operation) and the request message
- o The JSON-RPC Response object encapsulates a PAWS response message and Error element

The JSON-RPC Request for PAWS has the following form:

```
{
  "method": string,
  "params": <PAWS_REQ>,
  "id": string
}
where "method" is the name of a PAWS functionality (operation), and
<PAWS_REQ> represents one of the PAWS request objects associated with
the method.
The non-error JSON-RPC Response for PAWS has the following form:
{
  "result": <PAWS_RESP>,
 "id": string
}
where <PAWS_RESP> represents one of the PAWS response objects
associated with the method.
The error JSON-RPC Response for PAWS has the following form:
{
  "error": {
    "code": integer,
    "message": string,
    "data": object,
 },
 "id": string
}
```

where the Error object and error codes are described by Error Element (Section 5.13).

Depending on prior arrangement between a Database and Device, the Request and Response MAY contain additional parameters. The Database or Device MUST ignore all parameters it does not understand.

6.2. init Method

This section describes the encoding for the JSON-RPC "init" method that represents the Initialization functionality (<u>Section 4.2</u>).

<u>6.2.1</u>. INIT_REQ Parameters

The JSON encoding of the Initialization request message INIT_REQ (<u>Section 4.2.1</u>) is described by the following schema:

```
{
  "name": "INIT_REQ",
  "type": "object",
  "properties": {
    "type": "INIT_REQ",
    "version": {
      "type": "string",
      "required": true
    },
    "deviceDesc": {
      "type": "DeviceDescriptor",
      "required": true
    },
    "location": {
      "type": "GeoLocation",
      "description": "The location SHOULD be the current location " +
          "of the Device's antenna. Depending on the regulatory " +
          "domain, the location MAY be the anticipated position of " +
          "the Device.",
      "required": true
    }
 }
}
 Example "init" JSON-RPC request:
 {
  "method": "init",
  "params": {
   "type": "INIT_REQ",
   "version": "1.0",
   "deviceDesc": {
   "serialNumber": "XXX",
   "fccId": "YYY",
   . . .
   },
   "location": {
   "point": {
     "center": {"latitude": 37.0, "longitude": -101.3}
   }
   }
  }
  "id": "xxxxxx"
 }
```

<u>6.2.2</u>. INIT_RESP Parameters

The JSON encoding of the Initialization response message INIT_RESP (<u>Section 4.2.2</u>) is described by the following schema:

```
{
  "name": "INIT_RESP",
  "type": "object",
  "properties": {
    "type": "INIT_RESP",
    "version": {
      "type": "string",
      "required": true
    },
    "rulesetInfo": {
      "type": "RulesetInfo",
      "description": "Indicates the active regulatory domain and " +
          "attributes that define the applicable rule set that " +
          "govern the device",
      "required": true
    }
  }
}
Example "init" JSON-RPC response:
{
 "result": {
  "type": "INIT_RESP",
  "version": "1.0",
  "rulesetInfo": {
    . . .
  }
 },
 "id": "xxxxxx"
}
```

6.3. register Method

This section describes the encoding for the JSON-RPC "register" method that represents Device Registration functionality (<u>Section 4.3</u>).

6.3.1. REGISTRATION_REQ Parameters

The JSON encoding of the Registration request message REGISTRATION_REQ (<u>Section 4.3.1</u>) is described by the following schema:
```
{
  "name": "REGISTRATION_REQ",
  "type": "object",
  "properties": {
    "type": "REGISTRATION_REQ",
    "version": {
      "type": "string",
      "required": true
    },
    "deviceDesc": {
      "type": "DeviceDescriptor",
      "required": true
    },
    "deviceOwner": {
      "type": "DeviceOwner",
      "required": true
    },
    "location": {
      "type": "GeoLocation",
      "description": "The location SHOULD be the current location " +
          "of the Device's antenna. Depending on the regulatory " +
          "domain, the location MAY be the anticipated position of " +
          "the Device.",
      "required": true
    },
    "antenna": {
      "type": "AntennaCharacteristics",
      "description": "Antenna characteristics, including its " +
          "height and height type",
      "required": false
   }
  }
}
 Example "register" JSON-RPC request:
```

```
{
 "method": "register",
 "params": {
 "type": "REGISTRATION_REQ",
  "version": "1.0",
  "deviceDesc": {
  "serialNumber": "XXX",
  "fccId": "YYY",
  . . .
  },
  "deviceOwner": {
  "owner": {
   "fn": "John A. Smith",
   "org": {
    "text": "ACME",
   },
    "adr": {
     "street": "1234 A Street",
      "locality": "San Jose",
     "region": "CA",
     "code": "94423",
     "country": "US"
   },
    "tel": {
     "uri": "tel:+1-333-555-1212"
   },
   "email": {
     "text": "j.smith@email.com"
   }
  }
  },
  "location": {
  "point": {
   "center": {"latitude": 37.0, "longitude": -101.3}
  }
 },
 "antenna": {"height": 10.2, "heightType": "AGL"}
 },
"id": "xxxxxx"
}
```

6.3.2. REGISTRATION_RESP Parameters

The JSON encoding of the Registraion response message REGISTRATION_RESP (<u>Section 4.3.2</u>) is described by the following schema:

```
{
  "name": "REGISTRATION_RESP",
  "type": "object",
  "properties": {
    "type": "REGISTRATION_RESP",
    "version": {
      "type": "string",
      "required": true
    }
 }
}
Example "register" JSON-RPC response:
{
 "result": {
 "type": "REGISTRATION_RESP",
 "version": "1.0"
 },
 "id": "xxxxxx"
}
```

<u>6.4</u>. getSpectrum Method

This section describes the encoding for the JSON-RPC "getSpectrum" method that represents the single-location query of the Available Spectrum Query functionality (<u>Section 4.4</u>) that enables a Device to obtain a set of available spectrum from the Database.

6.4.1. AVAILABLE_SPECTRUM_REQ Parameters

The JSON encoding of the Available Spectrum request message AVAIL_SPECTRUM_REQ (<u>Section 4.4.1</u>) is described by the following schema:

```
{
  "name": "AVAILABLE_SPECTRUM_REQ",
  "type": "object",
  "properties": {
    "type": "AVAILABLE_SPECTRUM_REQ",
    "version": {
      "type": "string",
      "required": true
    },
    "deviceDesc": {
      "type": "DeviceDescriptor",
      "required":true
    },
    "location": {
      "type": "GeoLocation",
      "description": "The location SHOULD be the current location " +
          "of the Device's antenna. Depending on the regulatory " +
          "domain, the location MAY be the anticipated position of " +
          "the Device.",
      "required": false
    },
    "antenna": {
      "type": "AntennaCharacteristics",
      "description": "Antenna characteristics, including its " +
          "height and height type. May required depending on " +
          "device type and regulatory domain",
      "required":false
    },
    "owner": {
      "type": "DeviceOwner",
      "description": "May be required if the Device is not yet " +
          "registered or if the DB does not implement a separate " +
          "device-registration request. Also depends on device type " +
          "and regulatory domain",
      "required": false
    },
    "capabilities": {
      "type": "DeviceCapabilities",
      "description": "The Database SHOULD NOT return spectrum that " +
          "is incompatible with the specified capabilities.",
      "required": false
    }
 }
}
  Example "getSpectrum" JSON-RPC request:
```

```
{
 "method": "getSpectrum",
 "params": {
 "type": "AVAILABLE_SPECTRUM_REQ",
  "version": "1.0",
  "deviceDesc": {
  "serialNumber": "XXX",
  "fccId": "YYY",
  . . .
  },
  "location": {
  "point": {
   "center": {"latitude": 37.0, "longitude": -101.3}
  }
 },
 "antenna": {"height": 10.2, "heightType": "AGL"}
 }
 "id": "xxxxxx",
}
```

6.4.2. AVAIL_SPECTRUM_RESP Parameters

The JSON encoding of the Available Spectrum response message AVAIL_SPECTRUM_RESP (<u>Section 4.4.2</u>) is described by the following schema:

```
{
  "name": "AVAIL_SPECTRUM_RESP",
  "type": "object",
  "properties": {
    "type": "AVAILABLE_SPECTRUM_RESP",
    "version": {
     "type": "string",
     "required": true
    },
    "timestamp": {
      "type": "string",
      "description": "Timestamp of the response, using " +
          "YYYY-MM-DDThh:mm:ssZ RFC3339 format. This SHOULD be used " +
          "by the Device as a reference for the start and stop times " +
          "in the spectrum schedule",
      "format": "date-time",
      "required": true
    },
    "deviceDesc": {
      "type": "DeviceDescriptor",
      "required": true
    },
    "spectrumSchedules": {
      "type": "array",
      "description": "The Database MAY return more than one " +
          "schedule to represent future changes to the available " +
          "spectrum. This array MAY be empty if no spectrum is " +
          "is available.",
      "items": "SpectrumSchedule",
      "required": true
    },
    "needsSpectrumReport": {
      "type": "boolean",
      "description": "For regulatory domains that require a " +
          "spectrum-usage report from devices, the Database MUST " +
          "return true for this parameter.",
      "default": false,
      "required": false
    },
    "rulesetId": {
      "type": "string",
      "description": "The identifier of the applicable rule set.",
      "required": false
    }
 }
}
   Example "getSpectrum" JSON-RPC response:
```

```
{
 "result": {
  "type": "AVAILABLE_SPECTRUM_RESP",
  "version": "1.0",
  "timestamp": "2013-03-02T14:30:21Z",
  "deviceDesc": {
  "serialNumber": "XXX",
  "fccId": "YYY",
  . . .
  },
  "spectrumSchedules": [
   {
    "eventTime": {
    "startTime": "2013-03-02T14:30:21Z",
    "stopTime": "2013-03-02T20:00:00Z",
    },
    "spectra": [
      {
       "bandwidth": 6e6,
       "frequencyRanges": [
         {"startHz":5.18e8, "stopHz":5.36e8, "maxPowerDBm":30.0},
         {"startHz":5.36e8, "stopHz":5.42e8, "maxPowerDBm":36.0},
         . . .
       ]
      },
      {
       "bandwidth": 1e5,
       "frequencyRanges": [
         {"startHz":5.18e8, "stopHz":5.36e8, "maxPowerDBm":27.0},
         {"startHz":5.36e8, "stopHz":5.42e8, "maxPowerDBm":33.0},
         . . .
      ]
      }
    ]
   },
   {
    "eventTime": {
    "startTime": "2013-03-02T22:00:00Z",
     "stopTime": "2013-03-03T14:30:21Z",
    },
    "spectra": [
    . . .
   ]
  }
  ],
  "needsSpectrumReport": false
 },
 "id": "xxxxxx"
```

}

<u>6.5</u>. getSpectrumBatch Method

This section describes the encoding for the JSON-RPC "getSpectrumBatch" method that represents the multiple-location query of the Available Spectrum Query functionality (<u>Section 4.4</u>) that enables a Device to obtain a set of available spectrum for multiple locations from the Database.

6.5.1. AVAIL_SPECTRUM_BATCH_REQ Parameters

The JSON encoding of the Batch Available Spectrum request AVAIL_SPECTRUM_BATCH_REQ (<u>Section 4.4.3</u>) is described by the following schema. This an OPTIONAL feature of the Database.

```
{
  "name": "AVAIL_SPECTRUM_BATCH_REQ",
  "type": "object",
  "properties": {
    "type": "AVAILABLE_SPECTRUM_BATCH_REQ",
    "version": {
     "type": "string",
     "required": true
     },
    "deviceDesc": {
      "type": "DeviceDescriptor",
      "required": true
    },
    "locations": {
      "type": "array",
      "description": "At least one device location is required. " +
          "Additional (anticipated) locations can also be included, " +
          "as permitted by regulatory domain,",
      "items": "GeoLocation",
      "required": true
    },
    "antenna": {
      "type": "AntennaCharacteristics",
      "description": "Antenna characteristics, including its " +
          "height and height type. May required depending on " +
          "device type and regulatory domain", "AntennaCharacteristics",
      "required": false
    },
    "owner": {
      "type": "DeviceOwner",
      "description": "May be required if the Device is not yet " +
          "registered or if the DB does not implement a separate " +
          "device-registration request. Also depends on device type " +
          "and regulatory domain",
      "required": false
    },
    "capabilities": {
      "type": "DeviceCapabilities",
      "description": "The Database SHOULD NOT return spectrum that " +
          "is incompatible with the specified capabilities.",
      "required": false
    }
 }
}
  Example "getSpectrumBatch" JSON-RPC request:
```

```
{
 "method": "getSpectrumBatch",
 "params": {
  "type": "AVAILABLE_SPECTRUM_BATCH_REQ",
  "version": "1.0",
  "deviceDesc": {
  "serialNumber": "XXX",
  "fccId": "YYY",
  . . .
  },
  "locations": [
   {
    "point": {
    "center": {"latitude": 37.0, "longitude": -101.3}
    }
   },
   {
    "point": {
    "center": {"latitude": 37.0005, "longitude": -101.3005}
    }
   },
   . . .
  ],
  "antenna": {"height": 10.2, "heightType": "AGL"}
 }
 "id": "xxxxxx",
}
```

6.5.2. AVAIL_SPECTRUM_BATCH_RESP Parameters

The JSON encoding of the Batch Available Spectrum response AVAIL_SPECTRUM_BATCH_RESP (<u>Section 4.4.4</u>) is described by the following schema:

```
{
  "name": "AVAIL SPECTRUM BATCH RESP",
  "type": "object",
  "properties": {
    "type": "AVAILABLE_SPECTRUM_BATCH_RESP",
    "version": {
     "type": "string",
     "required": true
    },
    "timestamp": {
      "type": "string",
      "description": "Timestamp of the response, using " +
          "YYYY-MM-DDThh:mm:ssZ RFC3339 format. This SHOULD be used " +
          "by the Device as a reference for the start and stop times " +
          "in the spectrum schedule",
      "format": "date-time",
      "required": true
    },
    "deviceDesc": {
      "type": "DeviceDescriptor",
      "required": true
    },
    "geoSpectrumSchedules": {
      "type": "array",
      "description": "For each location, the Database MAY return " +
          "more than one schedule to represent future changes " +
          "to the available spectrum. This array MAY be empty if " +
          "there is no available spectrum.",
      "items": "GeoSpectrumSchedule",
      "required": true
    },
    "needsSpectrumReport": {
      "type": "boolean",
      "description": "For regulatory domains that require a " +
          "spectrum-usage report from devices, the Database MUST " +
          "return true for this parameter.",
      "default": false,
      "required": false
    },
    "rulesetId": {
      "type": "string",
      "description": "The identifier of the applicable rule set.",
      "required": false
    }
 }
}
   Example "getSpectrumBatch" JSON-RPC response:
```

```
{
 "result": {
  "type": "AVAILABLE_SPECTRUM_BATCH_RESP",
  "version": "1.0",
  "timestamp": "2013-03-02T14:30:21Z",
  "deviceDesc": {
  "serialNumber": "XXX",
  "fccId": "YYY",
  . . .
  },
  "geoSpectrumSchedules": [
   {
    "location": {
    "point": {
      "center": {"latitude": 37.0, "longitude": -101.3}
    }
    },
    "spectrumSchedules": [
     {
      "eventTime": {
       "startTime": "2013-03-02T14:30:21Z",
       "stopTime": "2013-03-02T20:00:00Z",
      },
      "spectra": [
        {
         "bandwidth": 6e6,
         "frequencyRanges": [
           {"startHz":5.18e8, "stopHz":5.36e8, "maxPowerDBm":30.0},
           {"startHz":5.36e8, "stopHz":5.42e8, "maxPowerDBm":36.0},
           . . .
         ]
        },
        {
         "bandwidth": 1e5,
         "frequencyRanges": [
           {"startHz":5.18e8, "stopHz":5.36e8, "maxPowerDBm":27.0},
           {"startHz":5.36e8, "stopHz":5.42e8, "maxPowerDBm":33.0},
           . . .
         ]
        },
      ]
     },
     {
      "eventTime": {
       "startTime": "2013-03-02T22:00:00Z",
       "stopTime": "2013-03-03T14:30:21Z",
      },
      "spectra": [
```

```
. . .
      ]
     }
    ],
   },
   {
    "location": {
     "point": {
      "center": {"latitude": 37.0005, "longitude": -101.3005}
     }
    },
    "spectrumSchedules": [
     . . .
    ]
   }
  ],
  "needsSpectrumReport": false
 },
 "id": "xxxxxx"
}
```

6.6. notifySpectrumUse Method

This section describes the encoding for the JSON-RPC "notifySpectrumUse" method that represents the Spectrum-usage notification of Available Spectrum Query functionality (<u>Section 4.4.5</u>) for notifying the Database of anticipated spectrum usage.

6.6.1. SPECTRUM_USE_NOTIFY Parameters

The JSON encoding of the Spectrum Notification message SPECTRUM_USE_NOTIFY (<u>Section 4.4.5</u>) is described by the following schema:

```
{
  "name": "SPECTRUM_USE_NOTIFY",
  "type": "object",
  "properties": {
    "type": "SPECTRUM_USE_NOTIFY",
    "version": {
     "type": "string",
     "required": true
    },
    "deviceDesc": {
      "type": "DeviceDescriptor",
      "required": true
    },
    "location": {
      "type": "GeoLocation",
      "required": true
    },
    "spectra": {
      "type": "array",
      "description": "The spectrum anticipated to be used by " +
          "the Device.",
      "items": "Spectrum",
      "required": true
    }
 }
}
```

Example "notifySpectrumUse" JSON-RPC notification:

```
{
 "method": "notifySpectrumUse",
 "params": {
 "type": "SPECTRUM_USE_NOTIFY",
  "version": "1.0",
  "deviceDesc": {
  "serialNumber": "XXX",
  "fccId": "YYY",
  . . .
  },
  "location": {
  "point": {
   "center": {"latitude": 37.0005, "longitude": -101.3005}
  }
  },
  "spectra": [
  {
    "bandwidth": 6e6,
    "frequencyRanges": [
     {"startHz":5.18e8, "stopHz":5.24e8, "maxPowerDBm":30.0}
   ]
  },
  ]
 },
  "needsSpectrumReport": false
 },
 "id": "xxxxxx"
}
```

6.6.2. SPECTRUM_USE_RESP Parameters

The JSON encoding of the Spectrum-usage response SPECTRUM_USE_RESP (<u>Section 4.4.6</u>) is decribed by the following schema:

```
{
   "name": "SPECTRUM_USE_RESP",
   "type": "object",
   "properties": {
      "type": "SPECTRUM_USE_RESP",
      "version": {
         "type": "string",
         "required": true
      }
   }
}
Example "notifySpectrumUse" JSON-RPC response:
```

```
{
    "result": {
        "type": "SPECTRUM_USE_RESP",
        "version": "1.0"
    },
    "id": "xxxxxx"
}
```

<u>6.7</u>. verifyDevice Method

This section describes the encoding for the JSON-RPC "verifyDevice" method that represents the Device Validation functionality (<u>Section 4.5</u>). This is used by a Master Device to validate Slave Devices.

6.7.1. DEV_VALID_REQ Parameters

The JSON encoding of the Device Validation request DEV_VALID_REQ (<u>Section 4.5.1</u>) is described by the following schema:

```
{
  "name": "DEV_VALID_REQ",
  "type": "object",
  "properties": {
    "type": "DEV_VALID_REQ",
    "version": {
      "type": "string",
      "required": true
    },
    "deviceDescs": {
      "type": "array",
      "description": "List of Slave Devices to be validated",
      "items": "DeviceDescriptor",
      "required": true
    }
 }
}
```

```
Example "verifyDevice" JSON-RPC request:
```

```
{
 "method": "verifyDevice",
 "params": {
 "type": "DEV_VALID_REQ",
  "version": "1.0",
  "deviceDescs": [
   {
    "serialNumber": "XXX",
    "fccId": "YYY",
    . . .
   },
   {
    "serialNumber": "XXX3",
    "fccId": "YYY2",
   . . .
   },
   . . .
  1
},
 "id": "xxxxxx"
}
```

6.7.2. DEV_VALID_RESP Parameters

```
The JSON encoding of the Device Validation response DEV_VALID_RESP
  (Section 4.5.2) is described by the following schema:
{
  "name": "DEV_VALID_RESP",
  "type": "object",
  "properties": {
    "type": "DEV_VALID_RESP",
    "version": {
      "type": "string",
     "required": true
    },
    "deviceValidities": {
      "type": "array",
      "description": "List of DeviceValidity objects that shows the " +
          "validity of each device included in the original Device " +
          "Validity Request message.",
      "items": "DeviceValidity",
      "required": true
    }
 }
}
 Example "verifyDevice" JSON-RPC response:
```

```
{
 "result": {
  "type": "DEV_VALID_RESP",
  "version": "1.0",
  "deviceValidities": [
   {
    "deviceDesc": {
      "serialNumber": "XXX",
      "fccId": "YYY",
      . . .
    },
    "isValid": true
   },
   {
    "deviceDesc": {
      "serialNumber": "XXX3",
      "fccId": "YYY2",
      . . .
    },
    "isValid": false,
    "reason": "Not authorized"
  }
 ]
 },
"id": "xxxxxx"
}
```

<u>6.8</u>. Sub-message Schemas

This section defines the schema for Protocol Parameters (<u>Section 5</u>) embedded in PAWS request and response messages.

6.8.1. GeoLocation

This parameter is used to specify the GeoLocation (Section 5.1) of the Device. The geometric shapes represent the JSON encoding shapes defined in GEOPRIV Presence Information Data Format Location Object [RFC5491].

```
{
   "name": "GeoLocation",
   "type": "object",
   "properties": {
      "point": {
        "description": "A single location, with optional " +
            "uncertainty measures",
        "type": "Ellipse",
        "required": false
```
```
},
    "region": {
     "description": "A region described by a polygon",
      "type": "Polygon",
     "required": false
   },
    "confidence": {
      "description": "Confidence interval when location " +
          "is a point with uncertainty. 0 to 100.",
      "type": "integer",
      "required": false,
      "default": 100
   }
 }
}
{
 "name": "Point",
 "type": "object",
 "properties": {
   "latitude": {
      "description: "Floating-point degrees. WGS84 datum.",
      "type": "number",
     "required": true
   },
   "longitude": {
      "type": "number",
      "description: "Floating-point degree. WGS84 datum.",
      "required":true
   }
 }
}
{
 "name": "Ellipse",
 "type": "object",
 "properties": {
   "center": {
     "type": "Point",
     "required": true
   },
   "semiMajorAxis": {
     "description": "Floating-point meters that describe " +
          "location uncertainty along the major axis of " +
          "the ellipse.",
      "type": "number",
      "required": false,
     "default": 0
   },
    "semiMinorAxis": {
```

```
"description": "Floating-point meters that describe " +
          "location uncertainty along the minor axis of " +
          "the ellipse.",
      "type": "number",
      "required": false,
      "default": 0
    },
    "orientation": {
      "description": "Orientation of the ellipse, as rotation " +
          "of the major axis from North towards East. Degrees.",
      "type": "number",
      "required": false,
      "default": 0
    }
 }
}
{
  "name": "Polygon",
  "type": "object",
  "properties": {
    "exterior": {
      "description": "List of Points in counter-clockwise " +
          "order. They must form a loop with no edges that " +
          "cross each other. Minimum of 3 points.",
      "type": "array",
      "items": "Point",
      "required": true
    }
 }
}
```

6.8.2. DeviceDescriptor

The DeviceDescriptor (<u>Section 5.2</u>) contains parameters that identify the specific device, such as its manufacturer serial number, regulatory-specific ID (e.g., FCC ID), and any other device characteristics required by regulatory domains, such as device-type classification.

```
{
  "name": "DeviceDescriptor",
  "type": "object",
  "properties": {
    "serialNumber": {
      "type": "string",
      "required": true
    },
    "rulesetIds": {
      "type": "array",
      "description": "List of identifiers for rule sets supported " +
          "by the device",
      "items": "string",
      "required": false
    },
    "fccId": {
      "type": "string",
      "description":"The device's FCC ID.",
      "required": false
   }
 }
}
```

<u>6.8.3</u>. AntennaCharacteristics

AntennaCharacteristics (<u>Section 5.3</u>) provide additional information, such as the antenna height, antenna type, etc.

```
{
   "name": "AntennaCharacteristics",
   "type": "object",
   "properties": {
     "height": {
       "description": "Height of the antenna, in meters",
       "type": "number",
       "required": false
     },
     "heightType": {
       "description": "Reference type for height: " +
           "Above Ground Level (AGL), or Above Mean Sea " +
           "Level (AMSL).",
       "type": "string",
       "enum": "["AGL", "AMSL"]",
       "default": "AGL",
       "required": false
     },
     "heightUncertainty": {
       "description": "Uncertainty of the height measurement, " +
           "in meters.",
       "type": "number",
       "required": false
     }
  }
 }
```

<u>6.8.4</u>. DeviceCapabilities

Device capabilities (<u>Section 5.4</u>) provide additional information that MAY be used by the Device to provide additional information to the Database to help the Database determine available spectrum. If the Database does not support device capabilities, it MUST ignore the parameter.

```
{
   "name": "DeviceCapabilities",
   "type": "object",
   "description": "Device capabilities to help DB determine " +
        "available spectrum. The DB SHOULD NOT return available " +
        "spectrum that falls outside the given frequency ranges.",
   "properties": {
        "frequencyRanges": {
            "type": "array",
            "items": "FrequencyRange",
            "required": false
        }
    }
}
```

```
}
```

6.8.5. DeviceOwner

The DeviceOwner (<u>Section 5.5</u>) parameter contains device-owner information required as part of device registration. Regulatory domains MAY require additional parameters. JSON encoding of vCard is described in A JavaScript Object Notation (JSON) Representation for vCard [<u>I-D.bhat-vcarddav-json</u>].

```
{
  "name": "DeviceOwner",
 "type": "object",
 "description": "Device-owner information required as part of " +
      "Device registration. Regulatory domains MAY require " +
      "additional parameters.",
  "properties": {
    "owner": {
      "type": "vCard",
      "description":"Contact information for the individual " +
           "or business that owns the device.",
      "required": true
   },
    "operator": {
      "type": "vCard",
      "description":"Contact information for the device operator.",
      "required": false
   }
 }
}
```

```
Example:
```

```
{
  "deviceOwner": {
    "owner": {
     "org": {
       "text": "Racafrax, Inc."
     }
    },
    "operator": {
     "fn": "John Frax",
      "adr": {
       "street": "100 Main Street",
        "locality": "Summersville",
        "region": "CA",
        "code": "90034",
        "country": "USA"
      },
      "tel": {
        "uri": "tel:+1-213-555-1212"
      },
      "email": {
        "text": "j.frax@rackafrax.com"
      }
   }
 }
}
```

6.8.6. RulesetInfo

RulesetInfo (<u>Section 5.6</u>) contains parameters for the rule set of a regulatory domain that is communicated using the Initialization component (<u>Section 4.2</u>).

```
{
  "name": "RulesetInfo",
  "type": "object",
  "description": "The rule set of a regulatory domain that is " +
      "communicated to Devices in the Initialization Response " +
      "message.",
  "properties": {
    "authority": {
      "type": "string",
      "description": "The regulatory domain at the specified " +
          "location. It is a 2-letter country codes defined by " +
          "IS03166-1.",
      "required": true
    },
    "maxLocationChange": {
     "type": "number",
      "description": "Maximum location change in meters.",
      "required": true
    },
    "maxPollingSecs": {
      "type": "integer",
      "description": "Maximum duration, in seconds, between " +
          "requests for available spectrum.",
      "required": true
    },
    "rulesetId": {
      "type": "string",
      "description": "The identifier of the applicable rule set",
      "required": false,
    }
 }
}
```

6.8.7. Spectrum

Available Spectrum (<u>Section 5.7</u>) can logically be characterized by a list of frequency ranges and permissible power levels for each range.

```
{
  "name": "Spectrum",
  "type": "object",
  "description": "A per-bandwidth list of frequency ranges with " +
      "permissible power levels. For example, In US, In US, FCC " +
      "requires only one spectrum specification at 6MHz " +
      "bandwidth; in UK, Ofcom requires two (at 0.1MHz and " +
      "8MHz).",
  "properties": {
    "bandwidth": {
      "type": "number",
      "description": "Operating bandwidth for which permissible " +
          "power levels are applicable.",
      "required": true
    },
    "frequencyRanges": {
      "type": "array",
      "description": "List of FrequencyRange objects to specify " +
          "frequency ranges and permissible power levels for " +
          "a given bandwidth. The list MAY be empty when there " +
          "is no available spectrum.",
      "items": "FrequencyRange",
      "required": true
    }
 }
}
```

6.8.8. FrequencyRange

The FrequencyRange (<u>Section 5.8</u>) element describes a frequency range and permissible power level within the specified range.

```
{
  "name": "FrequencyRange",
  "type": "object",
  "properties": {
    "startHz": {
      "type": "number",
      "description": "The inclusive start of the frequency range.",
     "required": true
    },
    "stopHz": {
      "type": "number",
      "description": "The exclusive end of the frequency range.",
      "required": true
    },
    "maxPowerDBm": {
      "type": "number",
      "description": "The maximum total power level (EIRP), " +
          "computed over the corresponding operating bandwidth, " +
          "that is permitted within the frequency range. This "
          "field is optional when specifying device " +
          "capabilities, but is otherwise required.",
      "required": false
    },
    "channelId": {
      "type": "string",
      "required": false
    }
 }
}
```

6.8.9. EventTime

The EventTime (Section 5.9) element specifies the start and stop times of an "event." It is used to indicate the time period for which a Spectrum (Section 5.7) is valid.

```
{
  "name": "EventTime",
  "type": "object",
  "properties": {
    "startTime": {
      "type": "string",
      "description": "YYYY-MM-DDThh:mm:ssZ RFC3339 format.",
      "format": "date-time",
      "required": false
    },
    "stopTime": {
      "type": "string",
      "description": "YYYY-MM-DDThh:mm:ssZ RFC3339 format.",
      "format": "date-time",
      "required": false
    }
  }
}
```

6.8.10. SpectrumSchedule

The SpectrumSchedule (<u>Section 5.10</u>) element combines EventTime with Spectrum to define a time period during which the spectrum is valid.

```
{
  "name": "SpectrumSchedule",
  "type": "object",
  "description": "The SpectrumSchedule element combines EventTime " +
      "with Spectrum to define a time period during which spectrum " +
      "is valid.",
  "properties": {
    "eventTime": {
      "type": "EventTime",
      "description": "Period when the spectra is valid.",
     "required": true
    },
    "spectra": {
      "type": "array",
      "description": "List of available spectra and permissible " +
          "power levels; one spectrum object per bandwidth. The " +
          "list MAY be empty when there is no available spectrum.",
      "items": "Spectrum",
      "required": true
   }
 }
}
```

6.8.11. GeoSpectrumSchedule

The GeoSpectrumSchedule (<u>Section 5.11</u>) element encapsulates the schedule of available spectrum at a location.

```
{
  "name": "GeoSpectrumSchedule",
 "type": "object",
 "description": "The GeoSpectrumSchedule element encapsulates " +
      "the schedule of available spectrum at a location.",
 "properties": {
    "location": {
      "type": "GeoLocation",
      "description": "The location at which the spectrum " +
          "schedule applies.",
      "required": true
   },
    "spectrumSchedules": {
      "type": "array",
      "description": "At least one schedule MUST be included " +
          "(though it MAY be empty if there is no available " +
          "spectrum. More than one schedule MAY be included " +
          "to represent future changes to the available spectrum.",
      "items": "SpectrumSchedule",
      "required": true
   }
 }
}
```

6.8.12. DeviceValidity

The DeviceValidity (Section 5.12) element is used to indicate whether a device is valid. See Section 4.5.2.

```
{
  "name": "DeviceValidity",
  "type": "object",
  "description": "The GeoSpectrumSchedule element encapsulates " +
      "the schedule of available spectrum at a location.",
  "properties": {
    "deviceDesc": {
      "type": "DeviceDescriptor",
      "required": true
   },
    "isValid": {
      "type": "boolean",
      "description": "Boolean that indicates if the Device is " +
          "valid",
      "required": true
   },
    "reason": {
      "type": "string",
      "description": "If the device identifier is not valid, " +
          "the Database MAY include a reason. The reason MAY be " +
          "in any language.",
      "required": false
   }
 }
}
```

6.8.13. Additional Properties

Note that A JSON Media Type for Describing the Structure and Meaning of JSON [I-D.zyp-json-schema] allows, as default behavior, the inclusion of additional properties by instances that are not explicitly defined in the JSON schema that the instance implements. The schema elaborated in this document adopts this default behavior. Hence, the instance MAY provide additional properties and associated values (which may be "any" JSON type) not explicitly listed in this schema. Further note that the Database and Device MUST ignore any such additional properties and their associated values that it does not understand.

7. HTTPS Binding

This section describes the use of HTTP over TLS (HTTPS) HTTP Over TLS [RFC2818] as the transport mechanism for the PAWS protocol. TLS provides message integrity and confidentiality between the Master Device and the Database. The Master Device MUST implement server authentication, as described in Section 3.1 of HTTP Over TLS [RFC2818]. The Device uses the URI determined (either statically

configured or dynamically discovered) to authenticate the server. The Device SHOULD fail a request if server authentication fails.

Depending on prior relationship between a database and device, the server MAY require client authentication, as described in the Transport Layer Security (TLS) Protocol [<u>RFC5246</u>], to authenticate the device.

To enable databases to handle large numbers of requests from large numbers of devices, the Database MAY support and Devices SHOULD support Stateless TLS Session Resumption [<u>RFC5077</u>].

A PAWS request message is carried in the body of an HTTP POST request. A PAWS response message is carried in the body of an HTTP response. A PAWS response SHOULD include a Content-Length header.

The POST method is the only method REQUIRED for PAWS. If a database chooses to support GET, it MUST be an escaped URL, but the encoding of the URL is outside the scope of this document. The database MAY refuse to support the GET request by returning an HTTP error code, such as 404 (not found).

The Database MAY redirect a PAWS request. The Master Device MUST handle redirects by using the Location header provided by the server in a 3xx response. When redirecting, the Master Device MUST observe the delay indicated by the Retry-After header. The Master Device MUST authenticate the Database that returns the redirect response before following the redirect. The Master Device MUST authenticate the Database indicated in the redirect.

8. Extensibility

8.1. Defining New Message Parameters

New request or response parameters for use with the PAWS protocol are defined and registered in the parameters registry following the procedure in <u>Section 9.1</u>.

Parameter names MUST conform to the param-name ABNF and parameter values syntax MUST be well-defined (e.g., using ABNF, or a reference to the syntax of an existing parameter).

param-name = 1*name-char name-char = ALPHA / DIGIT / "_"

The parameter name SHOULD be lowerCamelCase.

Unregistered vendor-specific parameter extensions that are not commonly applicable, and are specific to the implementation details of the Database where they are used SHOULD use a vendor-specific prefix that is no likely to conflict with other registered values (e.g., begin with 'companyname_').

8.2. Defining Ruleset Identifiers

A rule set represents a set of device-side requirements for which the device has been certified. It typically corresponds to, but is not limited to, a set of rules that govern a specific set of radio spectrum for a regulatory domain.

Rule-set identifiers are defined and registered in the Ruleset ID Registry following the procedure in <u>Section 9.2</u>. Ruleset ID values MUST conform to the ruleset-id ABNF. If the Ruleset ID requires additional parameters, they MUST be registered in the PAWS Parameters Registry, as described by <u>Section 9.1</u>.

ruleset-id = 1*ruleset-char ruleset-char = ALPHA / DIGIT / "_"

The form of a Ruleset ID value SHOULD be guided by the following:

- o The value should describe the set of rules that allow a device to operate within a regulatory domain. For example, it may include the name of a regulatory body or a certification process
- o The value should include version information, such as a year or version number

<u>8.3</u>. Defining Additional Error Codes

Additional error codes MAY be defined to extend the set listed in <u>Section 5.13</u>. Additional error codes MUST be registered, following the procedures in <u>Section 9.3</u>. If the error code requires additional response parameters, they MUST be registered in the PAWS Parameters Registry, as described by <u>Section 9.1</u>.

By convention, the error code SHOULD be a negative integer value, using one of the range of values defined in Error Codes (<u>Section 5.13</u>). If an appropriate category does not exist, it MAY use values in a different range.

9. IANA Considerations

<u>9.1</u>. PAWS Parameters Registry

This specification establishes the PAWS Parameters Registry.

Additional parameters for inclusion in the PAWS protocol requests, responses, or sub-messages are registered through the Specification Required [RFC5226] process, after a two-week review period on the [TBD]@ietf.org mailing list, on the advice of one or more Designated Experts. To allow for the allocation of values prior to publication, the Designated Expert(s) may approve registration once they are satisfied that such a specification will be published.

Registration requests must be sent to the [TBD]@ietf.org mailing list for review and comment, with an appropriate subject (e.g., "Request for parameter: example"). [[Editor's Note: The name of the mailing list should be determined in consultation with the IESG and IANA. Suggested name: paws-ext-review.]]

Within the review period, the Designated Expert(s) will either approve or deny the registration request, communicating this decision to the review list and IANA. Denials should include an explanation and, if applicable, suggestions as to how to make the request successful.

IANA must only accept registry updates from the Designated Expert(s), and should direct all requests for registration to the review mailing list.

<u>9.1.1</u>. Registration Template

- Parameter name: The name of the parameter (e.g., "example").
 Parameter usage location: The location(s) where the parameter can be
 used. The possible locations are the named requests, responses,
 and messages defined in Protocol Functionalities (Section 4) and
 Protocol Parameters (Section 5).
- Specification document(s): Reference to the document that specifies the parameter, preferably including a URI that can be used to retrieve a copy of the document. An indication of the relevant sections also may be included, but is not required.

9.1.2. Initial Registry Contents

The PAWS Parameters Registry enables protocol extensibility to support any regulatory domain and rule set. The initial contents of the registry, however, include only FCC-specific entries, because, as of this writing, it is the only regulatory domain that has finalized rules. There is no intent to restrict the protocol to FCC rules.

The PAWS Parameters Registry's initial contents are:

- o Parameter name: fccId
- o Parameter usage location: DeviceDescriptor (<u>Section 5.2</u>)
- o Specification Document(s): [[this document (Section 5.2)]]
- o Parameter name: fccTvbdDeviceType
- o Parameter usage location: DeviceDescriptor (<u>Section 5.2</u>)
- o Specification Document(s): [[this document]] Specifies the TV Band White Space device type, as defined by the FCC. Valid values are "FIXED", "MODE_1", "MODE_2".

9.2. PAWS Ruleset ID Registry

This specification establishes the PAWS Ruleset ID Registry.

Ruleset type names for inclusion in the PAWS protocol messages are registered through the Specification Required [RFC5226] process, after a two-week review period on the [TBD]@ietf.org mailing list, on the advice of one or more Designated Experts. To allow for the allocation of values prior to publication, the Designated Expert(s) may approve registration once they are satisfied that such a specification will be published.

Registration requests must be sent to the [TBD]@ietf.org mailing list for review and comment, with an appropriate subject (e.g., "Request for parameter: example"). [[Editor's Note: The name of the mailing list should be determined in consultation with the IESG and IANA. Suggested name: paws-ext-review.]]

Within the review period, the Designated Expert(s) will either approve or deny the registration request, communicating this decision to the review list and IANA. Denials should include an explanation and, if applicable, suggestions as to how to make the request successful.

IANA must only accept registry updates from the Designated Expert(s), and should direct all requests for registration to the review mailing list.

<u>9.2.1</u>. Registration Template

Ruleset name: The name of the rule set. Additional message parameters: Additional parameters to associate with the rulesetId parameter. New parameters MUST be registered separately in the PAWS Parameters Registry, as described by <u>Section 8.1</u>.

Internet-Draft

Specification Document(s): Reference to the document that specifies
 the parameter, preferably including a URI that can be used to
 retrieve a copy of the document. An indication of the relevant
 sections also may be included, but is not required.

9.2.2. Initial Registry Contents

The PAWS Ruleset ID Registry enables protocol extensibility to support any regulatory domain and rule set. The initial contents of the registry, however, include only FCC-specific entries, because, as of this writing, it is the only regulatory domain that has finalized rules. There is no intent to restrict the protocol to FCC rules.

The initial content of the PAWS Ruleset ID Registry is:

- o Ruleset name: FccTvBandWhiteSpace-2010
- o Additional message parameters:
 - * fccId: Specifies a device's FCC certification ID. It is a required parameter in DeviceDescriptor (<u>Section 5.2</u>).
 - * fccTvbdDeviceType: Specifies the type of TV-band White Space device, as defined by the FCC rules. It is a required parameter in DeviceDescriptor (<u>Section 5.2</u>).
- o Specification Document(s): [[this document]] This rule set refers to the FCC rules for TV-band White Space operations established in the Code of Federal Regulations (CFR), Title 47, Part 15, Subpart H (<u>http://www.gpo.gov/fdsys/pkg/</u> <u>CFR-2010-title47-vol1/pdf/</u> CFR-2010-title47-vol1-part15-subpartH.pdf).

9.3. PAWS Error Code Registry

This specification establishes the PAWS Error Code Registry.

Additional error codes for inclusion in the PAWS protocol error message are registered through the Specification Required [RFC5226] process, after a two-week review period on the [TBD]@ietf.org mailing list, on the advice of one or more Designated Experts. To allow for the allocation of values prior to publication, the Designated Expert(s) may approve registration once they are satisfied that such a specification will be published.

Registration requests must be sent to the [TBD]@ietf.org mailing list for review and comment, with an appropriate subject (e.g., "Request for parameter: example"). [[Editor's Note: The name of the mailing list should be determined in consultation with the IESG and IANA. Suggested name: paws-ext-review.]]

Within the review period, the Designated Expert(s) will either

approve or deny the registration request, communicating this decision to the review list and IANA. Denials should include an explanation and, if applicable, suggestions as to how to make the request successful.

IANA must only accept registry updates from the Designated Expert(s), and should direct all requests for registration to the review mailing list.

<u>9.3.1</u>. Registration Template

Code: Integer value of the error code.

Name: Name of the error.

Additional parameters: Additional parameters that are returned in the data portion of the error (See <u>Section 5.13</u>). New parameters MUST be registered separately in the PAWS Parameters Registry, as described by <u>Section 9.1</u>.

Description: Description of the error and its associated parameters, if any.

<u>9.3.2</u>. Initial Registry Contents

Initial registry contents are defined in the Table of Error Codes (Table 1).

10. Security Considerations

PAWS is a protocol whereby a Master Device requests a schedule of available spectrum at its location (or location of its Slave Devices) before it (they) can operate using those frequencies. Whereas the information provided by the Database must be accurate and conform to applicable regulatory rules, the Database cannot enforce, through the protocol, that a client device uses only the spectrum it provided. In other words, devices can put energy in the air and cause interference without asking the Database. Hence, PAWS security considerations do not include protection against malicious use of the White Space spectrum. For more detailed information on specific requirements and security considerations associated with PAWS, see Protocol to Access White Space database: PAWS Use Cases and Requirements [I-D.ietf-paws-problem-stmt-usecases-rgmts].

By using the PAWS protocol, the Master Device and the Database expose themselves to the following risks:

 Accuracy: The Master Device receives incorrect spectrumavailability information.
o Privacy: An unauthorized entity intercepts identifying data for the Master Device, such as serial number and location.

Protection from these risks depends on the success of the following steps:

- 1. The Master Device must determine a proper database.
- 2. The Master Device must connect to the proper database.
- The Database must determine or compute accurate spectrumavailability information.
- PAWS messages must be transmitted unmodified between the Database and the Master Device.
- 5. PAWS messages must be encrypted between the Database and the Master Device to prevent exposing private information.
- 6. For a Slave Device, the spectrum-availability information also must be transmitted unmodified and secure between the Master Device and the Slave Device.

Of these, only steps 2, 4, and 5 are within the scope of this document. [Editor's note: It is still open whether Step 1 is within the scope of this document]. Step 3 dependent on specific database implementations and regulatory rules and is outside the scope of this document. Step 6 requires a protocol between master and slave devices and is thus outside the scope of this document.

<u>10.1</u>. Assurance of Proper Database

This document assumes that the Database is contacted using a domain name or an IP address. Using HTTP over TLS HTTP Over TLS [RFC2818], the Database authenticates its identity, either as a domain name or IP address, to the Master Device by presenting a certificate containing that identifier as a "subjectAltName" (i.e., as a dNSName or IP address). If the Master Device has external information as to the expected identity or credentials of the proper database (e.g., a certificate fingerprint), these checks MAY be omitted. Note that in order for the presented certificate to be valid at the client, the client must be able to validate the certificate. In particular, the validation path of the certificate must end in one of the client's trust anchors, even if that trust anchor is the Database certificate itself. A Master Device should allow for the fact that a Database can change its certificate authorities (CAs) over time.

<u>**10.2</u>**. Protection Against Modification</u>

To prevent a PAWS response message from being modified en route, messages must be transmitted over an integrity-protected channel. Using HTTP over TLS, the channel will be protected by appropriate cyphersuites.

<u>10.3</u>. Protection Against Eavesdropping

Using HTTP over TLS, messages protected by appropriate cyphersuites are also protected from eavesdropping or otherwise access by unauthorized parties en route

<u>10.4</u>. Client Authentication Considerations

Although the Database can inform a device of available spectrum it can use, the Database cannot enforce that the Master Device uses any/ only those frequencies. Indeed, a malicious device can operate without ever contacting a database. Consequently, client authentication is not required for the core PAWS protocol (although it may be required by specific regulators). Depending on a prior relationship between a Database and Master Device, the Database MAY require client authentication. TLS provides client authentication, but there are some considerations:

- o As indicated in <u>Section 3.2</u> of HTTP Over TLS [<u>RFC2818</u>], the TLS client authentication procedure only determines that the device has a certificate chain rooted in an appropriate CA (or a self-signed certicate). The database would not know what the client identity ought to be, unless it has some external source of information. Distribution and management of such information, including revocation lists, are outside the scope of this document.
- Authentication schemes are secure only to the extent that secrets or certificates are kept secure. When there are a vast number of deployed devices using PAWS, the possibility that device keys will not leak becomes small. Implementations should consider how to manage the system in the eventuality that there is a leak.

<u>11</u>. Contributors

This document draws heavily from the following Internet Draft documents, [I-D.das-paws-protocol] and [I-D.wei-paws-framework]. The editor would like to specifically call out and thank the contributing authors of these two documents.

Donald Joslyn Spectrum Bridge Inc. 1064 Greenwood Blvd. Lake Mary, FL 32746 U.S.A. Email: d.joslyn at spectrumbridge dot com

Xinpeng Wei Huawei Phone: +86 13436822355 Email: weixinpeng@huawei.com

12. Acknowledgments

The authors gratefully acknowledge the contributions of: Gabor Bajko, Teco Boot, Nancy Bravin, Rex Buddenberg, Gerald Chouinard, Stephen Farrell, Michael Fitch, Joel M. Halpern, Jussi Kahtava, Warren Kumari, Paul Lambert, Andy Lee, Anthony Mancuso, Basavaraj Patil, Scott Probasco, Brian Rosen, Andy Sago, Peter Stanforth, John Stine, and Juan Carlos Zuniga.

13. References

<u>13.1</u>. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", <u>BCP 14</u>, <u>RFC 2119</u>, March 1997.
- [RFC3339] Klyne, G., Ed. and C. Newman, "Date and Time on the Internet: Timestamps", <u>RFC 3339</u>, July 2002.
- [RFC5077] Salowey, J., Zhou, H., Eronen, P., and H. Tschofenig, "Transport Layer Security (TLS) Session Resumption without Server-Side State", <u>RFC 5077</u>, January 2008.
- [RFC5226] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", <u>BCP 26</u>, <u>RFC 5226</u>, May 2008.
- [RFC5246] Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2", <u>RFC 5246</u>, August 2008.
- [RFC5491] Winterbottom, J., Thomson, M., and H. Tschofenig, "GEOPRIV Presence Information Data Format Location Object (PIDF-LO)

paws-protocol

Usage Clarification, Considerations, and Recommendations", <u>RFC 5491</u>, March 2009.

[RFC6350] Perreault, S., "vCard Format Specification", <u>RFC 6350</u>, August 2011.

<u>13.2</u>. Informative References

[I-D.bhat-vcarddav-json] Bhat, R. and P. Saint-Andre, "A JavaScript Object Notation (JSON) Representation for vCard", <u>draft-bhat-vcarddav-json-00</u> (work in progress), June 2012.

[I-D.das-paws-protocol]

Das, S., Malyar, J., and D. Joslyn, "Device to Database Protocol for White Space", <u>draft-das-paws-protocol-02</u> (work in progress), July 2012.

[I-D.ietf-paws-problem-stmt-usecases-rqmts]

Mancuso, A. and B. Patil, "Protocol to Access White Space (PAWS) Database: Use Cases and Requirements", <u>draft-ietf-paws-problem-stmt-usecases-rqmts-12</u> (work in progress), January 2013.

[I-D.wei-paws-framework]

Wei, X., Zhu, L., and P. McCann, "PAWS Framework", <u>draft-wei-paws-framework-00</u> (work in progress), July 2012.

[I-D.zyp-json-schema]

Galiegue, F., Zyp, K., and G. Court, "JSON Schema: core definitions and terminology", <u>draft-zyp-json-schema-04</u> (work in progress), January 2013.

[IS03166-1]

"Country Codes",
<<u>http://www.iso.org/iso/country_codes.htm</u>>.

[JSON-RPC]

"JSON-RPC 2.0 Specification", <<u>http://www.jsonrpc.org/specification</u>>.

- [RFC2818] Rescorla, E., "HTTP Over TLS", <u>RFC 2818</u>, May 2000.
- [RFC4627] Crockford, D., "The application/json Media Type for JavaScript Object Notation (JSON)", <u>RFC 4627</u>, July 2006.

<u>Appendix A</u>. Changes / Author Notes.

Changes from 02:

- o Added timestamp to the AVAIL_SPECTRUM_RESP (<u>Section 4.4.2</u>) and AVAIL_SPECTRUM_BATCH_RESP (<u>Section 4.4.4</u>) data models to serve as a reference for the event times in the response. This was accidentally omitted (but was specified in their JSON encodings (<u>Section 6</u>)).
- Fixed typos throughout the JSON encoding (<u>Section 6</u>) sections, typically adding missing commas.

Changed from 01:

- o Added a description of message sequences to support multiple rule sets and multiple jurisdictions <u>Section 3.1</u>.
- o Modified DeviceDescriptor (<u>Section 5.2</u>) to add rulesetIds
 parameter
- o Modified RulesetInfo (<u>Section 5.6</u>), AvailableSpectrumResponse (<u>Section 4.4.2</u>) to add rulesetId parameter.
- o Add Extensibility (<u>Section 8</u>) section.
- o Filled in IANA (Section 9) section.
- o Removed blank Example Messages section

Changes from 00:

- o Add JSON encoding
- o Adopt <u>RFC5491</u> for GeoLocation
- o Adopt vCard for contact information
- o Add Response Code section and update text referencing the defined response codes
- Change DeviceIdentifier to be DeviceDescriptor, allowing identifiers and device-characteristic fields to be included.

Authors' Addresses

Vincent Chen (editor) Google 1600 Amphitheatre Parkway Mountain View, CA 94043 US

Email: vchen@google.com

Internet-Draft

paws-protocol

Subir Das Applied Communication Sciences 444 Hoes Lane Piscataway, NJ 08854 U.S.A.

Phone: Fax: Email: sdas at appcomsci dot com URI:

Lei Zhu Huawei

Phone: +86 13910157020 Fax: Email: lei.zhu@huawei.com URI:

John Malyar Telcordia Technologies Inc. 1 Ericsson Drive Piscataway, NJ 08854 U.S.A.

Phone: Fax: Email: jmalyar at telcordia dot com URI:

Peter J. McCann Huawei 400 Crossing Blvd, 2nd Floor Bridgewater, NJ 08807 USA

Phone: +1 908 541 3563 Fax: Email: peter.mccann@huawei.com URI: