

PCE Working Group
Sivabalan
Internet-Draft
Inc.
Intended status: Standards Track
Tantsura
Expires: October 27, 2017
Individual

S.
Cisco Systems,
J.
I.
Minei
Google,
Inc.
R.
Varga
Pantheon Technologies
SR0
J.
Hardwick
Metaswitch
Networks
April 25,
2017

**Conveying path setup type in PCEP messages
draft-ietf-pce-lsp-setup-type-04**

Abstract

A Path Computation Element can compute traffic engineering paths (TE paths) through a network that are subject to various constraints. Currently, TE paths are label switched paths (LSPs) which are set up using the RSVP-TE signaling protocol. However, other TE path setup methods are possible within the PCE architecture. This document proposes an extension to PCEP to allow support for different path setup methods over a given PCEP session.

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any

time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on October 27, 2017.

Sivabalan, et al.
1]

Expires October 27, 2017

[Page

Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

- [1](#). Introduction
- [2](#)
- [2](#). Terminology
- [3](#)
- [3](#). Path Setup Type TLV
- [3](#)
- [4](#). Operation
- [4](#)
- [5](#). Security Considerations
- [5](#)
- [6](#). IANA Considerations
- [5](#)
- [6.1](#). PCEP TLV Type Indicators
- [5](#)
- [6.2](#). New Path Setup Type Registry
- [6](#)
- [6.3](#). PCEP-Error Object
- [6](#)
- [7](#). Contributors
- [6](#)
- [8](#). Acknowledgements
- [6](#)
- [9](#). Normative References
- [6](#)
- Authors' Addresses
- [7](#)

[1](#). Introduction

[RFC5440] describes the Path Computation Element Protocol (PCEP) for communication between a Path Computation Client (PCC) and a Path Control Element (PCE) or between one a pair of PCEs. A PCC requests a path subject to various constraints and optimization criteria from a PCE. The PCE responds to the PCC with a hop-by-hop path in an

Explicit Route Object (ERO). The PCC uses the ERO to set up the path in the network.

[I-D.ietf-pce-stateful-pce] specifies extensions to PCEP that allow a PCC to delegate its LSPs to a PCE. The PCE can then update the state of LSPs delegated to it. In particular, the PCE may modify the path of an LSP by sending a new ERO. The PCC uses this ERO to re-route the LSP in a make-before-break fashion.

[[I-D.ietf-pce-pce-initiated-lsp](#)] specifies a mechanism allowing a PCE to dynamically instantiate an LSP on a PCC by sending the ERO and

characteristics of the LSP. The PCC signals the LSP using the ERO and other attributes sent by the PCE.

So far, the PCEP protocol and its extensions implicitly assume that the TE paths are label switched, and are established via the RSVP-TE protocol. However, other methods of LSP setup are not precluded. When a new path setup method (other than RSVP-TE) is introduced for setting up a path, a new capability TLV pertaining to the new path setup method MAY be advertised when the PCEP session is established. Such capability TLV MUST be defined in the specification of the new path setup type. When multiple path setup methods are deployed in a network, a given PCEP session may have to simultaneously support more

than one path setup types. In this case, the intended path setup method needs to be either explicitly indicated or implied in the appropriate PCEP messages (when necessary) so that both the PCC and the PCE can take the necessary steps to set up the path. This document introduces a generic TLV called "PATH-SETUP-TYPE TLV" and specifies the base procedures to facilitate such operational model.

2. Terminology

The following terminologies are used in this document:

ERO: Explicit Route Object.

LSR: Label Switching Router.

PCC: Path Computation Client.

PCE: Path Computation Element

PCEP: Path Computation Element Protocol.

TLV: Type, Length, and Value.

3. Path Setup Type TLV

When a PCEP session is used to set up TE paths using different methods, the corresponding PCE and PCC must be aware of the path setup method used. That means, a PCE must be able to specify paths in the correct format and a PCC must be able take control and take forwarding plane actions appropriate to the path setup type.




Figure 1: PATH-SETUP-TYPE TLV

PATH-SETUP-TYPE TLV is an optional TLV associated with the RP ([RFC5440]) and the SRP ([I-D.ietf-pce-stateful-pce]) objects. Its format is shown in the above figure. The type of the TLV is to be defined by IANA. The one octet value contains the Path Setup Type (PST). This document specifies the following PST value:

- o PST = 0: Path is setup via RSVP-TE signaling protocol(default).

The absence of the PATH-SETUP-TYPE TLV is equivalent to an PATH-SETUP-TYPE TLV with an PST value of 0. It is recommended to omit the TLV in the default case. If the RP or SRP object contains more than one PATH-SETUP-TYPE TLVs, only the first TLV MUST be processed and the rest MUST be ignored.

If a PCEP speaker does not recognize the PATH-SETUP-TYPE TLV, it MUST ignore the TLV in accordance with ([RFC5440]). If a PCEP speaker recognizes the TLV but does not support the TLV, it MUST send PCerr with Error-Type = 2 (Capability not supported).

4. Operation

When requesting a path from a PCE using a PCReq message ([RFC5440]), a PCC MAY include the PATH-SETUP-TYPE TLV in the RP object. If the PCE is capable of expressing the path in a format appropriate to the setup method used, it MUST use the appropriate ERO format in the PCRep message. If the path setup type cannot be inferred from the ERO or any other object or TLV in the PCRep message, PATH-SETUP-TYPE TLV may be included in the RP object of the PCRep message.

Regardless of whether PATH-SETUP-TYPE TLV is used or not, if the PCE does not support the intended path setup type it MUST send PCerr with

Error-Type = TBD (Traffic engineering path setup error) (recommended value is 21) and Error-Value = 1 (Unsupported path setup type) and close the PCEP session. If the path setup types corresponding to

the PCReq and PCRep messages do not match, the PCC MUST send a PCerr with

Error-Type = 21 (Traffic engineering path setup error) and Error-Value = 2 (Mismatched path setup type) and close the PCEP session.

In the case of stateful PCE, if the path setup type cannot be unambiguously inferred from ERO or any other object or TLV, PATH-SETUP-TYPE TLV MAY be used in PCRpt and PCUpd messages. If PATH-SETUP-TYPE TLV is used in PCRpt message, the SRP object MUST be present even in cases when the SRP-ID-number is the reserved value

of

0x00000000. Regardless of whether PATH-SETUP-TYPE TLV is used or not, if a PCRpt message is triggered due to a PCUpd message (in this case SRP-ID-number is not equal to 0x00000000), the path setup types corresponding to the PCRpt and PCUpd messages should match. Otherwise, the PCE MUST send PCErr with Error-Type = 21 (Traffic engineering path setup error) and Error-Value = 2 (Mismatched path setup type) and close the connection.

In the case of PCE initiated LSPs, a PCE MAY include PATH-SETUP-TYPE TLV in PCInitiate message if the message does not have any other means of indicating path setup type. If a PCC does not support the path setup type associated with the PCInitiate message, the PCC MUST send PCErr with Error-Type = 21 (Traffic engineering path setup error) and Error-Value = 1 (Unsupported path setup type) and close the PCEP session. Similarly, as mentioned above, if the path setup type cannot be unambiguously inferred from ERO or any other object

or

TLV, the PATH-SETUP-TYPE TLV MAY be included in PCRpt messages triggered by PCInitiate message. Regardless of whether PATH-SETUP-TYPE TLV is used or not, if a PCRpt message is triggered by a PCInitiate message, the path setup types corresponding to the PCRpt and the PCInitiate messages should match. Otherwise, the PCE MUST send PCErr message with Error-Type = 21 (Traffic engineering path setup error) and Error-Value = 2 (Mismatched path setup type).

5. Security Considerations

No additional security measure is required.

6. IANA Considerations

6.1. PCEP TLV Type Indicators

IANA is requested to allocate a new code point in the PCEP TLV Type Indicators registry, as follows:

Value	Description	Reference
TBD (recommended 28)	PATH-SETUP-TYPE	This document

6.2. New Path Setup Type Registry

IANA is requested to create a new sub-registry within the "Path Computation Element Protocol (PCEP) Numbers" registry called "PATH-SETUP-TYPE TLV PST Field". The allocation policy for this new registry should be by IETF Consensus. The new registry should contain the following value:

Value	Description	Reference
0	Traffic engineering path is setup using RSVP signaling protocol	This document

6.3. PCEP-Error Object

IANA is requested to allocate code-points in the PCEP-ERROR Object Error Types and Values registry for a new error-type and the following new error-values:

Error-Type	Meaning
21	Invalid traffic engineering path setup type
Error-value=0:	Unassigned
Error-value=1:	Unsupported path setup type
Error-value=2:	Mismatched path setup type

7. Contributors

The following people contributed to this document:

- Jan Medved
- Edward Crabbe

8. Acknowledgements

We like to thank Marek Zavodsky for valuable comments.

9. Normative References

[I-D.ietf-pce-pce-initiated-lsp]
Crabbe, E., Minei, I., Sivabalan, S., and R. Varga, "PCEP Extensions for PCE-initiated LSP Setup in a Stateful PCE Model", [draft-ietf-pce-pce-initiated-lsp-09](#) (work in progress), March 2017.

[I-D.ietf-pce-stateful-pce]

Crabbe, E., Minei, I., Medved, J., and R. Varga, "PCEP Extensions for Stateful PCE", [draft-ietf-pce-stateful-pce-18](#) (work in progress), December 2016.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.

[RFC5440] Vasseur, JP., Ed. and JL. Le Roux, Ed., "Path Computation Element (PCE) Communication Protocol (PCEP)", [RFC 5440](#), DOI 10.17487/RFC5440, March 2009, <<http://www.rfc-editor.org/info/rfc5440>>.

Authors' Addresses

Siva Sivabalan
Cisco Systems, Inc.
2000 Innovation Drive
Kanata, Ontario K2K 3E8
Canada

Email: msiva@cisco.com

Jeff Tantsura
Individual

Email: jefftant.ietf@gmail.com

Ina Minei
Google, Inc.
1600 Amphitheatre Parkway
Mountain View, CA 94043
USA

Email: inaminei@google.com

Robert Varga
Pantheon Technologies SR0
Mlynske Nivy 56
Bratislava, 821 05
Slovakia

Email: robert.varga@pantheon.sk

Internet-Draft
2017

PCE path setup type

April

Jon Hardwick
Metaswitch Networks
100 Church Street
Enfield, Middlesex
UK

Email: jon.hardwick@metaswitch.com

