

Network Working Group  
Internet-Draft  
Intended status: Standards Track

Xian Zhang  
Young Lee  
Fatai Zhang  
Huawei  
Ramon Casellas  
CTTC  
Oscar Gonzalez de Dios  
Telefonica I+D  
Zafar Ali  
Cisco Systems

Expires: June 5, 2014

December 4, 2013

**Path Computation Element (PCE) Protocol Extensions for Stateful PCE  
Usage in GMPLS-controlled Networks**

[draft-ietf-pce-pcep-stateful-pce-gmpls-00.txt](#)

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on June 5, 2014.

Abstract

The Path Computation Element (PCE) facilitates Traffic Engineering (TE) based path calculation in large, multi-domain, multi-region, or multi-layer networks. [Stateful-PCE] provides the fundamental PCE communication Protocol (PCEP) extensions needed to support stateful PCE functions, without specifying the technology-specific extensions. This memo provides extensions required for PCEP so as to enable the usage of a stateful PCE capability in GMPLS-controlled networks.

Conventions used in this document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC-2119 [RFC2119].

Table of Contents

- Table of Contents ..... 2
- 1. Introduction ..... 3
- 2. PCEP Extensions ..... 3
  - 2.1. Overview of Requirements..... 3
  - 2.2. Stateful PCE Capability Advertisement..... 4
    - 2.2.1. PCE Capability Advertisement in Multi-layer Networks 4
  - 2.3. LSP Delegation in GMPLS-controlled Networks..... 5
  - 2.4. LSP Synchronization in GMPLS-controlled networks.....6
  - 2.5. Modification of Existing PCEP Messages and Procedures....7
    - 2.5.1. Use cases ..... 8
    - 2.5.2. Modification for LSP Re-optimization .....8
    - 2.5.3. Modification for Route Exclusion .....9
  - 2.6. Additional Error Type and Error Values Defined.....10
- 3. IANA Considerations ..... 10
- 4. Manageability Considerations..... 10
  - 4.1. Requirements on Other Protocols and Functional Components 10
- 5. Security Considerations..... 11
- 6. Acknowledgement ..... 11
- 7. References ..... 11
  - 7.1. Normative References..... 11
  - 7.2. Informative References..... 11
- 8. Contributors' Address..... 12
- Authors' Addresses ..... 13

## **1. Introduction**

[RFC 4655] presents the architecture of a Path Computation Element (PCE)-based model for computing Multiprotocol Label Switching (MPLS) and Generalized MPLS (GMPLS) Traffic Engineering Label Switched Paths (TE LSPs). To perform such a constrained computation, a PCE stores the network topology (i.e., TE links and nodes) and resource information (i.e., TE attributes) in its TE Database (TED). To request path computation services to a PCE, [RFC 5440] defines the PCE communication Protocol (PCEP) for interaction between a Path Computation Client (PCC) and a PCE, or between two PCEs. PCEP as specified in [RFC 5440] mainly focuses on MPLS networks and the PCEP extensions needed for GMPLS-controlled networks are provided in [PCEP-GMPLS].

Stateful PCEs are shown to be helpful in many application scenarios, in both MPLS and GMPLS networks, as illustrated in [Stateful-APP]. In order for these applications to be able to exploit the capability of stateful PCEs, extensions to the PCE communication protocol (i.e., PCEP) are required.

[Stateful-PCE] provides the fundamental extensions needed for stateful PCE to support general functionality, but leaves out the specification for technology-specific objects/TLVs. Complementarily, this document focuses on the extensions that are necessary in order for the deployment of stateful PCEs in GMPLS-controlled networks.

## **2. PCEP Extensions**

### **2.1. Overview of Requirements**

This section notes the main functional requirements for PCEP extensions to support stateful PCE for use in GMPLS-controlled networks, based on the description in [Stateful-APP]. Many requirements are common across a variety of network types (e.g., MPLS-TE networks and GMPLS networks) and the protocol extensions to meet the requirements are already described in [Stateful-PCE]. This document does not repeat the description of those protocol extensions. Other requirements that are also common across a variety of network types do not currently have protocol extensions defined in [Stateful-PCE]. In these cases, this document presents protocol extensions for discussion by the PCE working group and potential inclusion in [Stateful-PCE]. In addition, this document presents protocol extensions for a set of requirements which are specific to the use of a stateful PCE in a GMPLS-controlled network.

The basic requirements are as follows:

- o Advertisement of the stateful PCE capability. This generic requirement is covered in Section 7.1.1 of [[Stateful-PCE](#)]. [Section 2.2](#) of this document discusses other potential extensions for this functionality.
- o LSP delegation is already covered in Section 5.5 of [[Stateful-PCE](#)]. [Section 2.3](#) of this document provides extension for its application in GMPLS-controlled networks. Moreover, further discussion of some generic details that may need additional consideration is provided.
- o LSP state synchronization. This is a generic requirement already covered in Section 5.4 of [[Stateful-PCE](#)]. However, there are further extensions required specifically for GMPLS-controlled networks and discussed in [Section 2.4](#). Reference to LSPs by identifiers is discussed in Section 7.2 of [[Stateful-PCE](#)]. This feature can be applied to reduce the data carried in PCEP messages. Use cases and additional Error Codes are necessary, as described in [Section 2.5](#) and 2.6.

## **[2.2. Stateful PCE Capability Advertisement](#)**

Whether a PCE has stateful capability or not can be advertised during the PCEP session establishment process. It can also be advertised through routing protocols as described in [[RFC5088](#)]. In either case, the following additional aspects should also be considered.


### **2.2.1. PCE Capability Advertisement in Multi-layer Networks**

In multi-layer network scenarios, such as an IP-over-optical network, if there are dedicated PCEs responsible for each layer, then the PCCs should be informed of which PCEs they should synchronize their LSP states with, as well as send path computation requests to. The Layer-Cap TLV defined in [[INTER-LAYER](#)] can be used to indicate which layer a PCE is in charge of. (Editor's note: this change is currently not included in the current version of the [[INTER-LAYER](#)] draft. It is expected that it will be included in its next version.) This TLV is optional and MAY be carried in the OPEN object. It is RECOMMENDED that a PCC synchronizes its LSP states with the same PCEs that it can use for path computation in a multi-layer network. In a single layer, this TLV MAY not be used. However, if the PCE capability discovery depends on IGP and if an IGP instance spans across multiple layers, this TLV is still needed.

Alternatively, the extension to current OSPF PCED TLV is needed. A new domain-type denoting the layer information can be defined:

domain-type: T.B.D.

When it is carried in PCE-DOMAIN sub-TLV, it denotes the layer for which a PCE is responsible for path computation as well as LSP state synchronization. When carried in the PCE-NEIG-DOMAIN sub-TLV, it denotes its adjacent layers for which a PCE can compute paths and synchronize the LSP states. The DOMAIN-ID information can be represented using the following format, to denote the layer information:



2.3. LSP Delegation in GMPLS-controlled Networks

To enable the PCE to control an LSP, the PCUpd message is defined in [Stateful-PCE]. However, the specification of technology specific extensions is not covered. The following defines the <path> descriptor, present in the PCUpd message, that should be used in GMPLS-controlled networks:

<path> ::= <ERO><attribute-list>

Where:

```

<attribute-list> ::= [<LSPA>]
                    [<BANDWIDTH>]
                    [<GENERALIZED-BANDWIDTH>...]
                    [<metric-list>]

<metric-list> ::= <METRIC>[<metric-list>]

```

As explained in [stateful-APP], LSP parameter update controlled by a stateful PCE in a multi-domain network is complex and requires well-defined operational procedures as well as protocol design.

[TBD: protocol extensions]

#### **2.4. LSP Synchronization in GMPLS-controlled networks**

For LSP state synchronization of stateful PCEs in GMPLS networks, the LSP attributes, such as its bandwidth, associated route as well as protection information etc, should be updated by PCCs to PCE LSP database (LSP-DB). Note the LSP state synchronization described in this document denotes both the bulk LSP report at the initialization phase as well as the LSP state report afterwards described in [[Stateful-PCE](#)].

As per [[Stateful-PCE](#)], it does not cover technology-specific specification for state synchronization. Therefore, extensions of PCEP for stateful PCE usage in GMPLS networks are required. For LSP state synchronization, the objects/TLVs that should be used for stateful PCE in GMPLS networks are defined in [[PCEP-GMPLS](#)] and are briefly summarized as below:

- o GENERALIZED BANDWIDTH
- o GENERALIZED ENDPOINTS
- o PROTECTION ATTRIBUTE
- o Use of IF\_ID\_ERROR\_SPEC. [[Stateful-PCE](#)] [section 7.2.2](#) only considers RSVP ERROR\_SPEC TLVs. GMPLS extends this to also support IF\_ID\_ERROR\_SPEC, for example, to report about failed unnumbered interfaces.
- o Extended objects to support the inclusion of the label and unnumbered links.

Per [[Stateful-PCE](#)], the PCRpt message is defined for LSP state synchronization purposes. PCRpt is used by a PCC to report one or more of its LSPs to a stateful PCE. However, the <path> descriptor is technology-specific and left undefined.

For LSP state synchronization in GMPLS-controlled networks, the encoding of the <path> descriptor is defined as follows:

```
<path> ::= <ERO><attribute-list>
```

Where:

```
<attribute-list> ::= [LSPA]  

                    [BANDWIDTH]  

                    [GENERALIZED-BANDWIDTH...]
```

[<IRO>]

[<XRO>]

[<metric-list>]

<metric-list> ::= <METRIC> [<metric-list>]

The objects included in the <path> descriptor can be found in [\[RFC5440\]](#), [PCE-GMPLS] and [\[RFC5521\]](#).

For all the objects presented in this section, the P and I bit MUST be set to 0 since they are only used by a PCC to report its LSP information.

In GMPLS-controlled networks, the <ERO> object may include a list of the label sub-object for SDH/SONET, OTN and DWDM networks. It may also include a list of unnumbered interface IDs to denote the allocated resource. The <RRO>, <IRO> and <XRO> objects MAY include unnumbered interface IDs and labels for networks such as OTN and WDM networks.

If the LSP being reported is a protecting LSP, the <PROTECTION-ATTRIBUTE> TLV MUST be included in the <LSPA> object to denote its attributes and restrictions. Moreover, if the status of the protecting LSP changes from non-operational to operational, this should be synchronized to the stateful PCE. For example, in 1:1 protection, the combination of S=0, P=1 and O=0 denotes the protecting path is set up already but not used for carrying traffic. Upon the working path failure, the operational status of the aforementioned protecting LSP changes to in-use (i.e., O=1). This information should be synchronized with a stateful PCE through a PCRpt message.

The O bit in the <GENERALIZED-BANDWIDTH> object has no meaning for LSP state synchronization and MUST be set to 0. Furthermore, this object MAY appear twice, one with R set to 1 and the other with R set to 0. This is to denote the asymmetric bandwidth property of the updated bi-directional LSP.

## **2.5. Modification of Existing PCEP Messages and Procedures**

One of the advantages mentioned in [\[Stateful-APP\]](#) is that the stateful nature of a PCE simplifies the information conveyed in PCEP messages, notably between PCC and PCE, since it is possible to refer to PCE managed state for active LSPs. To be more specific, with a

stateful PCE, it is possible to refer to a LSP with a unique identifier in the scope of the PCC-PCEP session and thus use such identifier to refer to that LSP.

#### 2.5.1. Use cases

Use Case 1: Assuming a stateful PCE's LSP-DB is up-to-date, a PCC (e.g. NMS) requesting for a re-optimization of one or several LSPs can send the request with "R" bit set and only provides the relevant LSP unique identifiers.

Upon receiving the PCReq message, PCE should be able to correlate with one or multiple LSPs with their detailed state information and carry out optimization accordingly.

The handling of RP object specified in [[RFC5440](#)] is stated as following:

"The absence of an RRO in the PCReq message for a non-zero-bandwidth TE LSP (when the R bit of the RP object is set) MUST trigger the sending of a PCErr message with Error-Type="Required Object Missing" and Error-value="RRO Object missing for re-optimization."

If a PCE has stateful capabilities, and such capabilities have been negotiated and advertised, specific rules given in [[RFC5440](#)] may need to be relaxed. In particular, the re-optimization case: if the re-optimization request refers to a given LSP state, and the RRO information is available, the PCE can proceed.

Use Case 2: in order to set up a LSP which has a constraint that its route should not use resources used by one or more existing LSPs, a PCC can send a PCReq with the identifiers of these LSPs. A stateful PCE should be able to find the corresponding route and resource information so as to meet the constraints set by the requesting PCC. Hence, the LSP identifier TLV defined in [[Stateful-PCE](#)] can be used in XRO object for this purpose. Note that if the PCC is a node in the network, the constraint LSP ID information will be confined to the LSPs initiated by itself.

#### 2.5.2. Modification for LSP Re-optimization

For re-optimization, upon receiving a path computation request and the "R" bit is set, the stateful PCE SHOULD still perform the re-optimization in the following two cases:

Case 1: the existing bandwidth and route information of the to-be-optimized LSP is provided in the path computation request. This




information should be provided via <BANDWIDTH>, <GENERALIZED-BANDWIDTH>, <ERO> objects.

Case 2: the existing bandwidth and route information can be found locally in its LSP-DB. In this case, the PCRep and PCReq messages need to be modified to carry LSP identifiers. The stateful PCE can find this information using the per-node LSP ID together with the PCC's address.

If no LSP state information is available to carry out re-optimization, the stateful PCE should report the error "LSP state information unavailable for the LSP re-optimization" (Error Type = T.B.D., Error value= T.B.D.).

### 2.5.3. Modification for Route Exclusion

A LSP identifier sub-object is defined and its format as follows:



**L bit:**

The L bit SHOULD NOT be set, so that the subobject represents a strict hop in the explicit route.

**Type:**

Subobject Type for a per-node LSP identifier.

**Length:**

The Length contains the total length of the subobject in bytes, including the Type and Length fields.

**PLSP-ID:**

This is the identifier given to a LSP and it is unique on a node basis. It is defined in [[Stateful-PCE](#)].

**Flags:**

This field is defined in [[Stateful-PCE](#)]. It is not used in this sub-object and should be ignored upon receipt.

Optional TLVs:

Additional TLVs can be defined in the future to provide further information to identify a LSP. In this document, no TLVs are defined.

One or multiple of these sub-objects can be present in the XRO object. When a stateful PCE receives a path computation request carrying this sub-object, it should find relevant information of these LSPs and preclude the resource during the path computation process. If a stateful PCE cannot recognize one or more of the received LSP identifiers, it should reply PCErr saying "the LSP state information for route exclusion purpose cannot be found" (Error-type = T.B.D., Error-value= T.B.D.). Optionally, it may provide with the unrecognized identifier information to the requesting PCC.

## **2.6. Additional Error Type and Error Values Defined**

Error Type Meaning

21(TBD) LSP state information missing

Error-value 1: LSP state information unavailable for the LSP re-optimization

Error-value 2: the LSP state information for route exclusion purpose cannot be found

## **3. IANA Considerations**

IANA is requested to allocate new Types for the TLV/Object defined in this document.T.B.D.

## **4. Manageability Considerations**

The description and functionality specifications presented related to stateful PCEs should also comply with the manageability specifications covered in [Section 8 of \[RFC4655\]](#). Furthermore, a further list of manageability issues presented in [\[Stateful-PCE\]](#) should also be considered.

Additional considerations are presented in the next sections.

### **4.1. Requirements on Other Protocols and Functional Components**

When the detailed route information is included for LSP state synchronization (either at the initial stage or during LSP state

report process), this require the ingress node of an LSP carry the RRO object in order to enable the collection of such information.

## **5. Security Considerations**

The security issues presented in [[RFC5440](#)] and [[Stateful-PCE](#)] apply to this document.

## **6. Acknowledgement**

We would like to thank Adrian Farrel and Cyril Margaria for the useful comments and discussions.

## **7. References**

### **7.1. Normative References**

- [RFC2119] Bradner, S., "Key words for use in RFCs to indicate requirements levels", [RFC 2119](#), March 1997.
- [RFC4655] Farrel, A., Vasseur, J.-P., and Ash, J., "A Path Computation Element (PCE)-Based Architecture", [RFC 4655](#), August 2006.
- [RFC5440] Vasseur, J.-P., and Le Roux, JL., "Path Computation Element (PCE) Communication Protocol (PCEP)", [RFC 5440](#), March 2009.
- [RFC5088] Le Roux, JL., Vasseur, J.-P., Ikejiri, Y., Zhang, R., "OSPF Protocol Extensions for Path Computation Element (PCE) Discovery", [RFC 5088](#), January 2008.
- [INTER-LAYER] Oki, E., Takeda, Tomonori, Le Roux, JL., Farrel, A., Zhang, F., "Extensions to the Path Computation Element communication Protocol (PCEP) for Inter-Layer MPLS and GMPLS Traffic Engineering", [draft-ietf-pce-inter-layer-ext](#), work in progress.

### **7.2. Informative References**

- [Stateful-APP] Zhang, X., Minei, I., et al "Applicability of Stateful Path Computation Element (PCE) ", [draft-ietf-pce-stateful-pce-app](#), , work in progress.
- [[Stateful-PCE](#)]Crabbe, E., Medved, J., Varga, R., Minei, I., "PCEP Extensions for Stateful PCE", [draft-ietf-pce-stateful-pce](#), work in progress.

[PCE-IA-WSO] Lee, Y., Bernstein G., Takeda, T., Tsuritani, T.,  
"PCEP Extensions for WSO Impairments", [draft-lee-pce-wson-impairments](#), work in progress.

[PCEP-GMPLS] Margaria, C., Gonzalez de Dios, O., Zhang, F., "PCEP  
extensions for GMPLS", [draft-ietf-pce-gmpls-pcep-extensions](#), work in progress.

## **8. Contributors' Address**

Dhruv Dhody  
Huawei Technology  
Leela Palace  
Bangalore, Karnataka 560008  
INDIA

EMail: [dhruvd@huawei.com](mailto:dhruvd@huawei.com)

Yi Lin  
Huawei Technologies  
F3-5-B R&D Center, Huawei Base  
Bantian, Longgang District  
Shenzhen 518129 P.R.China

Phone: +86-755-28972914  
Email: [yi.lin@huawei.com](mailto:yi.lin@huawei.com)

Authors' Addresses

Xian Zhang  
Huawei Technologies  
F3-5-B R&D Center, Huawei Base  
Bantian, Longgang District  
Shenzhen 518129 P.R.China

Phone: +86-755-28972645  
Email: zhang.xian@huawei.com

Young Lee  
Huawei  
1700 Alma Drive, Suite 100  
Plano, TX 75075  
US

Phone: +1 972 509 5599 x2240  
Fax: +1 469 229 5397  
EMail: ylee@huawei.com

Fatai Zhang  
Huawei  
F3-5-B R&D Center, Huawei Base  
Bantian, Longgang District  
P.R. China

Phone: +86-755-28972912  
Email: zhangfatai@huawei.com

Ramon Casellas  
CTTC  
Av. Carl Friedrich Gauss n7  
Castelldefels, Barcelona 08860  
Spain

Phone:  
Email: ramon.casellas@cttc.es

Oscar Gonzalez de Dios  
Telefonica Investigacion y Desarrollo  
Emilio Vargas 6  
Madrid, 28045  
Spain

Phone: +34 913374013  
Email: ogondio@tid.es

Zafar Ali  
Cisco Systems  
Email: zali@cisco.com

## Intellectual Property

The IETF Trust takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in any IETF Document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights.

Copies of Intellectual Property disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement any standard or specification contained in an IETF Document. Please address the information to the IETF at [ietf-ipr@ietf.org](mailto:ietf-ipr@ietf.org).

The definitive version of an IETF Document is that published by, or under the auspices of, the IETF. Versions of IETF Documents that are published by third parties, including those that are translated into other languages, should not be considered to be definitive versions of IETF Documents. The definitive version of these Legal Provisions is that published by, or under the auspices of, the IETF. Versions of these Legal Provisions that are published by third parties, including those that are translated into other languages, should not be considered to be definitive versions of these Legal Provisions.

For the avoidance of doubt, each Contributor to the IETF Standards Process licenses each Contribution that he or she makes as part of the IETF Standards Process to the IETF Trust pursuant to the provisions of [RFC 5378](#). No language to the contrary, or terms,

conditions or rights that differ from or are inconsistent with the rights and licenses granted under [RFC 5378](#), shall have any effect and shall be null and void, whether published or posted by such Contributor, or included with or in such Contribution.

#### Disclaimer of Validity

All IETF Documents and the information contained therein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY, THE IETF TRUST AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION THEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

#### Full Copyright Statement

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Simplified BSD License.