

Network Working Group
Internet Draft
Intended status: Informational
Expires: April 2015

Y. Lee
Huawei
G. Bernstein
Grotto Networking
Jonas Martensson
Acreo
T. Takeda
NTT
T. Tsuritani
KDDI
O. G. de Dios
Telefonica

October 13, 2014

PCEP Requirements for WSON Routing and Wavelength Assignment

[draft-ietf-pce-wson-routing-wavelength-14.txt](#)

Abstract

This memo provides application-specific requirements for the Path Computation Element communication Protocol (PCEP) for the support of Wavelength Switched Optical Networks (WSON). Lightpath provisioning in WSONs requires a routing and wavelength assignment (RWA) process. From a path computation perspective, wavelength assignment is the process of determining which wavelength can be used on each hop of a path and forms an additional routing constraint to optical light path computation. Requirements for PCEP extensions in support of optical impairments will be addressed in a separate document.

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at
<http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at
<http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on February 13, 2009.

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Simplified BSD License.

Conventions used in this document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

Table of Contents

1.	Introduction.....	3
2.	WSON RWA Processes & Architecture.....	4
3.	Requirements.....	6
3.1.	Path Computation Type Option.....	6
3.2.	RWA Processing.....	6
3.3.	Bulk RWA Path Request/Reply.....	7
3.4.	RWA Path Re-optimization Request/Reply.....	7
3.5.	Wavelength Range Constraint.....	8
3.6.	Wavelength Assignment Preference.....	8
3.7.	Signal Processing Capability Restriction.....	8
4.	Manageability Considerations.....	9
4.1.	Control of Function and Policy.....	9
4.2.	Information and Data Models, e.g. MIB module.....	9
4.3.	Liveness Detection and Monitoring.....	10
4.4.	Verifying Correct Operation.....	10

4.5. Requirements on Other Protocols and Functional Components	10
4.6. Impact on Network Operation	10
5. Security Considerations	10
6. IANA Considerations	10
7. Acknowledgments	11
8. References	11
8.1. Normative References	11
8.2. Informative References	11
Authors' Addresses	12
Intellectual Property Statement	13
Disclaimer of Validity	13

[1. Introduction](#)

[RFC4655] defines the PCE-based architecture and explains how a Path Computation Element (PCE) may compute Label Switched Paths (LSP) in Multiprotocol Label Switching Traffic Engineering (MPLS-TE) and Generalized MPLS (GMPLS)-controlled networks at the request of Path Computation Clients (PCCs). A PCC is shown to be any network component that makes such a request and may be for instance an optical switching element within a Wavelength Division Multiplexing (WDM) network. The PCE, itself, can be located anywhere within the network, and may be within an optical switching element, a Network Management System (NMS) or Operational Support System (OSS), or may be an independent network server.

The PCE communication Protocol (PCEP) is the communication protocol used between PCC and PCE, and may also be used between cooperating PCEs. [[RFC4657](#)] sets out the common protocol requirements for PCEP. Additional application-specific requirements for PCEP are deferred to separate documents.

This document provides a set of application-specific PCEP requirements for support of path computation in Wavelength Switched Optical Networks (WSON). WSON refers to WDM-based optical networks in which switching is performed selectively based on the wavelength of an optical signal.

The path in WSON is referred to as a lightpath. A lightpath may span multiple fiber links and the path should be assigned a wavelength for each link.

A transparent optical network is made up of optical devices that can switch but not convert from one wavelength to another. In a transparent optical network, a lightpath operates on the same wavelength across all fiber links that it traverses. In such case, the lightpath is said to satisfy the wavelength-continuity

constraint. Two lightpaths that share a common fiber link cannot be assigned the same wavelength. To do otherwise would result in both signals interfering with each other. Note that advanced additional multiplexing techniques such as polarization based multiplexing are not addressed in this document since the physical layer aspects are not currently standardized. Therefore, assigning the proper wavelength on a lightpath is an essential requirement in the optical path computation process.

When a switching node has the ability to perform wavelength conversion the wavelength-continuity constraint can be relaxed, and a lightpath may use different wavelengths on different links along its path from origin to destination. It is, however, to be noted that wavelength converters may be limited for cost reasons, while the number of WDM channels that can be supported in a fiber is also limited. As a WSON can be composed of network nodes that cannot perform wavelength conversion, nodes with limited wavelength conversion, and nodes with full wavelength conversion abilities, wavelength assignment is an additional routing constraint to be considered in all lightpath computations.

In this document we first review the processes for routing and wavelength assignment (RWA) used when wavelength continuity constraints are present and then specify requirements for PCEP to support RWA. Requirements for optical impairments will be addressed in a separate document.

The remainder of this document uses terminology from [[RFC4655](#)].

2. WSON RWA Processes & Architecture

In [[RFC6163](#)] three alternative process architectures were given for performing routing and wavelength assignment. These are shown schematically in Figure 1. R stands for Routing, WA for Wavelength Assignment, and DWA for Distributed Wavelength Assignment.




Figure 1. RWA process alternatives

These alternatives have the following properties and impact on PCEP requirements in this document.

(a) Combined Processes (R&WA)

Here path selection and wavelength assignment are performed as a single process. The requirements for PCC-PCE interaction with such a combined RWA process PCE is addressed in this document.

(b) Routing separate from Wavelength Assignment (R+WA)

Here the routing process furnishes one or more potential paths to the wavelength assignment process that then performs final path selection and wavelength assignment. The requirements for PCE-PCE interaction with one PCE implementing the routing process and another implementing the wavelength assignment process are not addressed in this document.

(b') Routing and distributed Wavelength Assignment (R+DWA)

Here a standard path computation (unaware of detailed wavelength availability) takes place, then wavelength assignment is performed along this path in a distributed manner via signaling (RSVP-TE). This alternative is a particular case of R+WA and it should be covered by GMPLS PCEP extensions and does not present new WSON-specific requirements.

In the previous section various process architectures for implementing RWA have been reviewed. Figure 2 shows one typical PCE-based implementation, which is referred to as Combined Process (R&WA). With this architecture, the two processes of routing and wavelength assignment are accessed via a single PCE. This architecture is the base architecture from which the requirements are specified in this document.




Figure 2. Combined Process (R&WA) architecture

3. Requirements

The requirements for the PCC to PCE interface of Figure 2 are specified in this section.

3.1. Path Computation Type Option

A PCEP request MAY include the path computation type. This can be:

- (i) Both Routing and Wavelength Assignment (RWA),
- (ii) Routing only.

This requirement is needed to differentiate between the currently supported routing with distributed wavelength assignment option and combined RWA. In case of distributed wavelength assignment option, wavelength assignment will be performed at each node of the route.

3.2. RWA Processing

- (a) When the request is a RWA path computation type, the request MUST further include the wavelength assignment options. At the minimum, the following option should be supported:

- (i) Explicit Label Control (ELC) [[RFC3473](#)]
- (ii) A set of recommended labels for each hop. The PCC can select the label based on local policy.

Note that option (ii) may also be used in R+WA or R+DWA.

- (b) In case of a RWA computation type, the response MUST include the wavelength(s) assigned to the path and an indication of which label assignment option has been applied (ELC or label set).

- (c) In the case where a valid path is not found, the response MUST include why the path is not found (e.g., network disconnected, wavelength not found, or both, etc.). Note that 'wavelength not found' may include several sub-cases such as wavelength continuity not met, unsupported FEC/Modulation type, etc.

3.3. Bulk RWA Path Request/Reply

Sending simultaneous path requests for "routing only" computation is supported by PCEP specification [[RFC5440](#)]. To remain consistent the following requirements are added.

- (a) A PCEP request MUST be able to specify an option for bulk RWA path request. Bulk path request is an ability to request a number of simultaneous RWA path requests.
- (b) The PCEP response MUST include the path and the assigned wavelength assigned for each RWA path request specified in the original bulk request.

3.4. RWA Path Re-optimization Request/Reply

1. For a re-optimization request, the request MUST provide both the path and current wavelength to be re-optimized and MAY include the following options:
 - a. Re-optimize the path keeping the same wavelength(s)
 - b. Re-optimize wavelength(s) keeping the same path
 - c. Re-optimize allowing both the wavelength and the path to change
2. The corresponding response to the re-optimized request MUST provide the re-optimized path and wavelengths even when the request asked for the path or the wavelength to remain unchanged.
3. In case that the new path (i.e., other than the current path) is not found, the response MUST include why the path is not found (e.g., network disconnected, wavelength not found, or both, etc.). Note that 'wavelength not found' may include several sub-cases such as wavelength continuity not met, unsupported FEC/Modulation type, etc.

3.5. Wavelength Range Constraint

For any RWA computation type request, the requester (PCC) MUST be allowed to specify a restriction on the wavelengths to be used. The requester MAY use this option to restrict the assigned wavelength for explicit label or label set.

Note that the requester (e.g., PCC) is not required to furnish any range restrictions. This restriction may for example come from the tuning ability of a laser transmitter, any optical element, or a policy-based restriction.

3.6. Wavelength Assignment Preference

1. A RWA computation type request MAY include the requester preference for, e.g., random assignment, descending order, ascending order, etc. A response SHOULD follow the requestor preference unless it conflicts with operator's policy.
2. A request for two or more paths MUST allow the requester to include an option constraining the paths to have the same wavelength(s) assigned. This is useful in the case of protection with single transponder (e.g., 1+1 link disjoint paths).

In a network with wavelength conversion capabilities (e.g. sparse 3R regenerators), a request SHOULD be able to indicate whether a single, continuous wavelength should be allocated or not. In other words, the requesting PCC SHOULD be able to specify the precedence of wavelength continuity even if wavelength conversion is available.

3.7. Signal Processing Capability Restriction

Signal processing compatibility is an important constraint for optical path computation. The signal type for an end-to-end optical path must match at source and at destination.

The PCC MUST be allowed to specify the signal type at the endpoints (i.e., at source and at destination). The following signal processing capabilities should be supported at a minimum:

- o Modulation Type List
- o FEC Type List

The PCC MUST also be allowed to state whether transit modification is acceptable for the above signal processing capabilities.

4. Manageability Considerations

Manageability of WSON Routing and Wavelength Assignment (RWA) with PCE must address the following considerations:

4.1. Control of Function and Policy

In addition to the parameters already listed in [Section 8.1 of \[RFC5440\]](#), a PCEP implementation SHOULD allow configuring the following PCEP session parameters on a PCC:

- o The ability to send a WSON RWA request.

In addition to the parameters already listed in [Section 8.1 of \[RFC5440\]](#), a PCEP implementation SHOULD allow configuring the following PCEP session parameters on a PCE:

- o The support for WSON RWA.
- o The maximum number of bulk path requests associated with WSON RWA per request message.

These parameters may be configured as default parameters for any PCEP session the PCEP speaker participates in, or may apply to a specific session with a given PCEP peer or a specific group of sessions with a specific group of PCEP peers.

4.2. Information and Data Models, e.g. MIB module

As this document only concerns the requirements to support WSON RWA, no additional MIB module is defined in this document. However, the

corresponding solution draft will list the information that should be added to the PCE MIB module defined in [[PCEP-MIB](#)].

4.3. Liveness Detection and Monitoring

Mechanisms defined in this document do not imply any new liveness detection and monitoring requirements in addition to those already listed in [section 8.3 of \[RFC5440\]](#).

4.4. Verifying Correct Operation

Mechanisms defined in this document do not imply any new verification requirements in addition to those already listed in [section 8.4 of \[RFC5440\]](#).

4.5. Requirements on Other Protocols and Functional Components

If PCE discovery mechanisms ([\[RFC5089\]](#) and [\[RFC5088\]](#)) were to be extended for technology-specific capabilities, advertising WSON RWA path computation capability should be considered.

4.6. Impact on Network Operation

Mechanisms defined in this document do not imply any new network operation requirements in addition to those already listed in [section 8.6 of \[RFC5440\]](#).

5. Security Considerations

This document has no requirement for a change to the security models within PCEP [[RFC5440](#)]. However the additional information distributed in order to address the RWA problem represents a disclosure of network capabilities that an operator may wish to keep private. Consideration should be given to securing this information.

6. IANA Considerations

This informational document does not make any requests for IANA action.

7. Acknowledgments

The authors would like to thank Adrian Farrel, Cycil Margaria and Ramon Casellas for many helpful comments that greatly improved the contents of this draft.

This document was prepared using 2-Word-v2.0.template.dot.

8. References

8.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC4655] Farrel, A., Vasseur, J., and J. Ash, "A Path Computation Element (PCE)-Based Architecture", [RFC 4655](#), August 2006.
- [RFC5440] Vasseur, JP., Ed. and JL. Le Roux, Ed., "Path Computation Element (PCE) communication Protocol", [RFC 5440](#), March 2009.

8.2. Informative References

- [RFC3473] L. Berger, "Generalized Multi-Protocol Label Switching (GMPLS) Signaling Resource ReserVation Protocol-Traffic Engineering (RSVP-TE) Extensions", [RFC 3473](#), January 2003.
- [RFC4657] Ash, J. and J. Le Roux, "Path Computation Element (PCE) Communication Protocol Generic Requirements", [RFC 4657](#), September 2006.
- [RFC6163] Y. Lee, G. Bernstein, W. Imajuku, "Framework for GMPLS and PCE Control of Wavelength Switched Optical Networks", [RFC 6163](#), April 2011.
- [RFC5088] Le Roux, JL., Ed., Vasseur, JP., Ed., Ikejiri, Y., and R. Zhang, "OSPF Protocol Extensions for Path Computation Element (PCE) Discovery", [RFC 5088](#), January 2008.

[RFC5089] Le Roux, J.L., Ed., Vasseur, J.P., Ed., Ikejiri, Y., and R. Zhang, "IS-IS Protocol Extensions for Path Computation Element (PCE) Discovery", [RFC 5089](#), January 2008.

[PCEP-MIB] Koushik, K, et al., "PCE communication protocol(PCEP) Management Information Base", [draft-ietf-pce-pcep-mib](#), work in progress.

Authors' Addresses

Young Lee (Ed.)
Huawei Technologies
5340 Legacy Drive, Building 3
Plano, TX 75245, USA
Phone: (469)277-5838
Email: leeyoung@huawei.com

Greg Bernstein (Ed.)
Grotto Networking
Fremont, CA, USA
Phone: (510) 573-2237
Email: gregb@grotto-networking.com

Jonas Martensson
Acreo
Email: Jonas.Martensson@acreo.se

Tomonori Takeda
NTT Corporation
3-9-11, Midori-Cho
Musashino-Shi, Tokyo 180-8585, Japan
Email: takeda.tomonori@lab.ntt.co.jp

Takehiro Tsuritani
KDDI R&D Laboratories, Inc.
2-1-15 Ohara Kamifukuoka Saitama, 356-8502. Japan
Phone: +81-49-278-7357
Email: tsuri@kddilabs.jp

Oscar Gonzalez de Dios
Telefonica Investigacion y Desarrollo
C/ Emilio Vargas 6
Madrid, 28043
Spain
Phone: +34 91 3374013
Email: ogondio@tid.es