

Workgroup: PIM Working Group

Internet-Draft:

draft-ietf-pim-bfd-p2mp-use-case-09

Published: 7 October 2021

Intended Status: Standards Track

Expires: 10 April 2022

Authors: G. Mirsky J. Xiaoli

Ericsson ZTE Corporation

**Fast Failover in Protocol Independent Multicast - Sparse Mode (PIM-SM)
Using Bidirectional Forwarding Detection (BFD) for Multipoint Networks**

Abstract

This document specifies how Bidirectional Forwarding Detection for multipoint networks can provide sub-second failover for routers that participate in Protocol Independent Multicast - Sparse Mode (PIM-SM). An extension to the PIM Hello message used to bootstrap a point-to-multipoint BFD session is also defined in this document.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 10 April 2022.

Copyright Notice

Copyright (c) 2021 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in

Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

- [1. Introduction](#)
 - [1.1. Conventions used in this document](#)
 - [1.1.1. Terminology](#)
 - [1.1.2. Requirements Language](#)
- [2. BFD Discriminator PIM Hello Option](#)
 - [2.1. Using P2MP BFD in PIM Router Monitoring](#)
 - [2.2. P2MP BFD in PIM DR Load Balancing](#)
 - [2.3. Multipoint BFD Encapsulation](#)
- [3. IANA Considerations](#)
- [4. Security Considerations](#)
- [5. Acknowledgments](#)
- [6. References](#)
 - [6.1. Normative References](#)
 - [6.2. Informative References](#)
- [Authors' Addresses](#)

1. Introduction

Faster convergence in the control plane minimizes the periods of traffic blackholing, transient routing loops, and other situations that may negatively affect service data flow. Faster convergence in the control plane is beneficial to unicast and multicast routing protocols.

[[RFC7761](#)] is the current specification of the Protocol Independent Multicast - Sparse Mode (PIM-SM) for IPv4 and IPv6 networks. A conforming implementation of PIM-SM elects a Designated Router (DR) on each PIM-SM interface. When a group of PIM-SM nodes is connected to a shared media segment, e.g., Ethernet, the node elected as DR acts on behalf of directly connected hosts in the context of the PIM-SM protocol. Failure of the DR impacts the quality of the multicast services it provides to directly connected hosts because the default failure detection interval for PIM-SM routers is 105 seconds.

Bidirectional Forwarding Detection (BFD) [[RFC5880](#)] had been originally defined to detect a failure of a point-to-point (p2p) path, single-hop [[RFC5881](#)] or multihop [[RFC5883](#)]. In some PIM-SM deployments, a p2p BFD can be used to detect a failure and enable faster failover. [[RFC8562](#)] extends the BFD base specification [[RFC5880](#)] for multipoint and multicast networks, and it precisely characterizes deployment scenarios for PIM-SM over a LAN segment. Among specific characteristics of p2mp BFD that particularly benefit PIM-SM over a LAN segment is a faster transition to the Up state of

the p2mp BFD session due to avoidance of the three-way handshake required in p2p BFD [RFC5880]. Also, because the router that transmits BFD Control messages uses the BFD Demand mode [RFC5880], it maintains less BFD state than the Asynchronous mode. Point-to-multipoint (p2mp) BFD can enable faster detection of PIM-SM router failure and thus minimize multicast service disruption. The monitored PIM-SM router acts as the head and other routers as tails of a p2mp BFD session. This document defines the monitoring of a PIM-SM router using p2mp BFD. The document also defines the extension to PIM-SM [RFC7761] to bootstrap a PIM-SM router to join in p2mp BFD session over shared media segment.

1.1. Conventions used in this document

1.1.1. Terminology

This document uses terminology defined in [RFC5880], [RFC8562], and [RFC7761]. Familiarity with these specifications and the terminology used is expected.

1.1.2. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

2. BFD Discriminator PIM Hello Option

[Figure 1](#) displays the new optional BFD Discriminator PIM Hello option to bootstrap a tail of the p2mp BFD session.




Figure 1: BFD Discriminator PIM Hello Option

where new fields are interpreted as:

OptionType: TBA.

OptionLength: MUST be set to 4.

HeadDiscriminator: equals the value of My Discriminator ([[RFC5880](#)]) allocated by the head.

If the value of the OptionLength field is not equal to 4, the BFD Discriminator PIM Hello option is considered malformed, and the receiver MUST stop processing PIM Hello options. If the value of the HeadDiscriminator field equals zero, then the BFD Discriminator PIM Hello option MUST be considered invalid, and the receiver MUST ignore it. The receiver SHOULD log a notification regarding the malformed or invalid BFD Discriminator Hello option under the control of a throttling logging mechanism.

2.1. Using P2MP BFD in PIM Router Monitoring

If the head is no longer serving the function that prompted it to be monitored, then it MUST cease including the BFD Discriminator PIM Hello option in its PIM-Hello message, and it SHOULD shut down the BFD session following the procedures described in Section 5.9 [[RFC8562](#)].

The head MUST create a BFD session of type MultipointHead [[RFC8562](#)]. Note that any PIM-SM router, regardless of its role, MAY become a head of a p2mp BFD session. To control the volume of BFD control traffic on a shared media segment, an operator should carefully select PIM-SM routers configured as a head of a p2mp BFD session. The head MUST include the BFD Discriminator option in its Hello messages, and it MUST include a 4-byte HeadDiscriminator with a value other than zero.

If a PIM-SM router is configured to monitor the head by using p2mp BFD, referred to through this document as 'tail', receives a PIM-Hello packet with the BFD Discriminator PIM Hello option, the tail MAY create a p2mp BFD session of type MultipointTail, as defined in [[RFC8562](#)].

The node that includes the BFD Discriminator PIM Hello option transmits BFD Control packets periodically. For the tail to correctly demultiplex BFD [[RFC8562](#)], the source address, and My Discriminator values of the BFD packets MUST be the same as those of the HeadDiscriminator in the PIM Hello message. If that is not the case, the tail BFD node would not be able to monitor the state of the PIM-SM node, that is, the head of the p2mp BFD session, though the regular PIM-SM mechanisms remain fully operational.

If the tail detects a MultipointHead failure [[RFC8562](#)], it MUST delete the corresponding neighbor state and follow procedures defined in [[RFC7761](#)].

If the head ceases to include the BFD Discriminator PIM Hello option in its PIM-Hello message, tails SHOULD close the corresponding

MultipointTail BFD session without affecting the PIM state in any way. Thus the tail stops using BFD to monitor the head and reverts to the procedures defined in [\[RFC7761\]](#).

2.2. P2MP BFD in PIM DR Load Balancing

[\[RFC8775\]](#) specifies the PIM Designated Router Load Balancing (DRLB) functionality. Any PIM router that advertises the DRLB-Cap Hello Option can become the head of a p2mp BFD session, as specified in [Section 2.1](#). The head router administratively sets the bfd.SessionState to Up in the MultipointHead session [\[RFC8562\]](#) only if it is a Group Designated Router (GDR) Candidate, as specified in Sections 5.5 and 5.6 of [\[RFC8775\]](#). If the router is no longer the GDR, then it MUST shut down following the procedures described in Section 5.9 [\[RFC8562\]](#). For each GDR Candidate that includes BFD Discriminator option in its PIM Hello, the PIM DR creates a MultipointTail session [\[RFC8562\]](#). PIM DR demultiplexes BFD sessions based on the value of the My Discriminator field and the source IP address. If PIM DR detects a failure of one of the sessions, it MUST remove that router from the GDR Candidate list and immediately transmit a new DRLB-List option.

2.3. Multipoint BFD Encapsulation

The MultipointHead of a p2mp BFD session when transmitting BFD Control packets:

MUST set TTL or Hop Limit value to 255 (Section 5 [\[RFC5881\]](#));

MUST use the group address ALL-PIM-ROUTERS ('224.0.0.13' for IPv4 and 'ff02::d' for IPv6) as destination IP address

3. IANA Considerations

IANA is requested to allocate a new OptionType value from PIM-Hello Options registry according to:

Value	Length	Name	Reference
TBA	4	BFD Discriminator Option	This document

Table 1: BFD Discriminator option type

4. Security Considerations

This document defines a way to accelerate detecting a failure that affects PIM functionality by using BFD. The operation of either protocol is not changed.

The security considerations discussed in [\[RFC7761\]](#), [\[RFC5880\]](#), [\[RFC8562\]](#), and [\[RFC8775\]](#) apply to this document.

5. Acknowledgments

The authors cannot say enough to express their appreciation of the comments and suggestions we received from Stig Venaas. The authors greatly appreciate the comments and suggestions by Alvaro Retana that improved the clarity of the document.

6. References

6.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC5880] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD)", RFC 5880, DOI 10.17487/RFC5880, June 2010, <<https://www.rfc-editor.org/info/rfc5880>>.
- [RFC5881] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD) for IPv4 and IPv6 (Single Hop)", RFC 5881, DOI 10.17487/RFC5881, June 2010, <<https://www.rfc-editor.org/info/rfc5881>>.
- [RFC7761] Fenner, B., Handley, M., Holbrook, H., Kouvelas, I., Parekh, R., Zhang, Z., and L. Zheng, "Protocol Independent Multicast - Sparse Mode (PIM-SM): Protocol Specification (Revised)", STD 83, RFC 7761, DOI 10.17487/RFC7761, March 2016, <<https://www.rfc-editor.org/info/rfc7761>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8562] Katz, D., Ward, D., Pallagatti, S., Ed., and G. Mirsky, Ed., "Bidirectional Forwarding Detection (BFD) for Multipoint Networks", RFC 8562, DOI 10.17487/RFC8562, April 2019, <<https://www.rfc-editor.org/info/rfc8562>>.
- [RFC8775] Cai, Y., Ou, H., Vallepalli, S., Mishra, M., Venaas, S., and A. Green, "PIM Designated Router Load Balancing", RFC 8775, DOI 10.17487/RFC8775, April 2020, <<https://www.rfc-editor.org/info/rfc8775>>.

6.2. Informative References

- [RFC5883] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD) for Multihop Paths", RFC 5883, DOI 10.17487/

RFC5883, June 2010, <<https://www.rfc-editor.org/info/rfc5883>>.

Authors' Addresses

Greg Mirsky
Ericsson

Email: gregimirsky@gmail.com

Ji Xiaoli
ZTE Corporation
No.50 Software Avenue, Yuhuatai District
Nanjing,
China

Email: ji.xiaoli@zte.com.cn