

PIM WG
Internet-Draft
Expires: November 6, 2008

B. Joshi
Infosys Technologies Ltd.
R. Bijlani
May 5, 2008

PIM Bootstrap Router MIB
draft-ietf-pim-bsr-mib-06.txt

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on November 6, 2008.

Copyright Notice

Copyright (C) The IETF Trust (2008).

Abstract

This document defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects used for managing the Bootstrap Router (BSR) mechanism for PIM (Protocol Independent Multicast).

Table of Contents

1.	Introduction	3
2.	The Internet-Standard Management Framework	3
3.	Conventions	3
4.	Overview	3
5.	Definitions	4
6.	Security Considerations	19
7.	IANA Considerations	20
8.	Acknowledgments	21
9.	References	21
9.1.	Normative References	21
9.2.	Informative References	22
	Authors' Addresses	23
	Intellectual Property and Copyright Statements	24

1. Introduction

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects used for managing the Bootstrap Router (BSR) mechanism for PIM [[RFC4601](#)], [[RFC5059](#)].

This document was created by moving some of the PIM BSR specific MIB tables from one of the earlier version of PIM MIB [[RFC5060](#)].

2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [[RFC3410](#)].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, [RFC 2578](#) [[RFC2578](#)], STD 58, [RFC 2579](#) [[RFC2579](#)] and STD 58, [RFC 2580](#) [[RFC2580](#)].

3. Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

4. Overview

This MIB module contains four tables. The tables are:

1. The Candidate-RP Table, which contains one row for each multicast group address prefix for which the local router is configured to advertise itself as a Candidate-RP. This table exists on routers that are configured as Candidate-RP.
2. The Elected BSR RP-Set Table, which contains one row for each Group-to-RP mapping that was received in C-RP advertisements. This table exists on a router that is an elected BSR.

3. The Candidate-BSR Table, which contains one row for each Candidate-BSR configuration for the local router. This table exists on routers that are configured as Candidate-BSR.
4. The Elected BSR Table, which contains one row for each elected BSR. This table exists on a router that is an elected BSR.

This MIB module uses textual conventions defined in the INET-ADDRESS-MIB [[RFC4001](#)].

5. Definitions

```
PIM-BSR-MIB DEFINITIONS ::= BEGIN
```

```
IMPORTS
```

```
    MODULE-IDENTITY, OBJECT-TYPE,
    NOTIFICATION-TYPE,
    mib-2, Unsigned32, TimeTicks      FROM SNMPv2-SMI
    RowStatus, TruthValue,
    StorageType                      FROM SNMPv2-TC
    MODULE-COMPLIANCE, OBJECT-GROUP,
    NOTIFICATION-GROUP              FROM SNMPv2-CONF
    InetAddressType,
    InetAddressPrefixLength,
    InetAddress,
    InetZoneIndex                   FROM INET-ADDRESS-MIB;
```

```
pimBsrMIB MODULE-IDENTITY
```

```
    LAST-UPDATED "200804300000Z" -- 30 April 2008
```

```
    ORGANIZATION
```

```
        "IETF Protocol Independent Multicast (PIM) Working Group"
```

```
    CONTACT-INFO
```

```
        "Email: pim@ietf.org
```

```
        WG charter:
```

```
        http://www.ietf.org/html.charters/pim-charter.html"
```

```
    DESCRIPTION
```

```
        "The MIB module for management of the Bootstrap Router
        (BSR) mechanism for PIM routers."
```

```
        Copyright (C) The IETF Trust (2008). This version
        of this MIB module is part of RFC yyyy; see the RFC
        itself for full legal notices."
```

```
-- RFC Ed.: replace yyyy with actual RFC number & remove this note
```

```
    REVISION      "200804300000Z" -- 30 April 2008
```

```
    DESCRIPTION   "Initial version, published as RFC yyyy."
```

```
-- RFC Ed.: replace yyyy with actual RFC number & remove this note
```



```
 ::= { mib-2 XXX }
-- RFC Ed.: replace XXX with IANA-assigned number & remove this note

--
-- Top-level structure
--

pimBsrNotifications OBJECT IDENTIFIER ::= { pimBsrMIB 0 }
pimBsrObjects OBJECT IDENTIFIER ::= { pimBsrMIB 1 }

--
-- Conformance Information
--

pimBsrConformance OBJECT IDENTIFIER ::= { pimBsrMIB 2 }
pimBsrCompliances OBJECT IDENTIFIER ::= { pimBsrConformance 1 }
pimBsrGroups OBJECT IDENTIFIER ::= { pimBsrConformance 2 }

--
-- The BSR Candidate-RP Table
--

pimBsrCandidateRPTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF PimBsrCandidateRPEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The (conceptual) table listing the IP multicast group
        prefixes for which the local router is to advertise
        itself as a Candidate-RP."
    ::= { pimBsrObjects 1 }

pimBsrCandidateRPEntry OBJECT-TYPE
    SYNTAX      PimBsrCandidateRPEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry (conceptual row) in the
        pimBsrCandidateRPTable."
    INDEX      { pimBsrCandidateRPAddressType,
                pimBsrCandidateRPAddress,
                pimBsrCandidateRPGroupAddress,
                pimBsrCandidateRPGroupPrefixLength }
    ::= { pimBsrCandidateRPTable 1 }

PimBsrCandidateRPEntry ::= SEQUENCE {
    pimBsrCandidateRPAddressType      InetAddressType,
    pimBsrCandidateRPAddress          InetAddress,
```



```
pimBsrCandidateRPGroupAddress      InetAddress,
pimBsrCandidateRPGroupPrefixLength InetAddressPrefixLength,
pimBsrCandidateRPBidir              TruthValue,
pimBsrCandidateRPAAdvTimer          TimeTicks,
pimBsrCandidateRPPriority           Unsigned32,
pimBsrCandidateRPAAdvInterval       Unsigned32,
pimBsrCandidateRPHoldtime           Unsigned32,
pimBsrCandidateRPStatus             RowStatus,
pimBsrCandidateRPStorageType        StorageType
}
```

pimBsrCandidateRPAddressType OBJECT-TYPE

```
SYNTAX      InetAddressType
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The Inet address type of the Candidate-RP."
 ::= { pimBsrCandidateRPEntry 1 }
```

pimBsrCandidateRPAddress OBJECT-TYPE

```
SYNTAX      InetAddress (SIZE (4|8|16|20))
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The (unicast) address that will be advertised as a
    Candidate-RP. The InetAddressType is given by the
    pimBsrCandidateRPAddressType object."
 ::= { pimBsrCandidateRPEntry 2 }
```

pimBsrCandidateRPGroupAddress OBJECT-TYPE

```
SYNTAX      InetAddress (SIZE (4|8|16|20))
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The IP multicast group address that, when combined with
    the corresponding value of
    pimBsrCandidateRPGroupPrefixLength, identifies a group
    prefix for which the local router will advertise itself
    as a Candidate-RP. The InetAddressType is given by the
    pimBsrCandidateRPAddressType object.

    This address object is only significant up to
    pimBsrCandidateRPGroupPrefixLength bits. The
    remainder of the address bits are zero. This is
    especially important for this field, which is part of
    the index of this entry. Any non-zero bits would
    signify an entirely different entry."
 ::= { pimBsrCandidateRPEntry 3 }
```


pimBsrCandidateRPGroupPrefixLength OBJECT-TYPE

SYNTAX InetAddressPrefixLength (4..128)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The multicast group address mask that, when combined with the corresponding value of pimBsrCandidateRPGroupAddress, identifies a group prefix for which the local router will advertise itself as a Candidate-RP. The InetAddressType is given by the pimBsrCandidateRPAddressType object."

::= { pimBsrCandidateRPEntry 4 }

pimBsrCandidateRPBidir OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"If this object is set to TRUE, this group range is advertised with this RP as a BIDIR-PIM group range. If it is set to FALSE, it is advertised as a PIM-SM group range."

DEFVAL { false }

::= { pimBsrCandidateRPEntry 5 }

pimBsrCandidateRPAdvTimer OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The time remaining before the local router next sends a Candidate-RP-Advertisement to the elected BSR for this zone."

::= { pimBsrCandidateRPEntry 6 }

pimBsrCandidateRPPriority OBJECT-TYPE

SYNTAX Unsigned32 (0..255)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The priority for this Candidate RP advertised in Candidate-RP-Advertisements."

REFERENCE "[RFC5059 section 3.2](#)"

DEFVAL { 192 }

::= { pimBsrCandidateRPEntry 7 }

pimBsrCandidateRPAdvInterval OBJECT-TYPE

SYNTAX Unsigned32 (1..26214)

UNITS "seconds"
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"A Candidate RP generates Candidate-RP-Advertisements periodically. This object represents the time interval in seconds between two consecutive advertisements."

REFERENCE "[RFC5059 section 3.2](#) and [section 5](#)"
DEFVAL { 60 }

::= { pimBsrCandidateRPEntry 8 }

pimBsrCandidateRPHoldtime OBJECT-TYPE

SYNTAX Unsigned32 (0..65535)
UNITS "seconds"
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"Holdtime for this Candidate RP. The amount of time (in seconds) this Candidate-RP entry is valid.

This object's value can be zero only when this C-RP is shutting down"

REFERENCE "[RFC5059 section 4.2](#)"
DEFVAL { 150 }

::= { pimBsrCandidateRPEntry 9 }

pimBsrCandidateRPStatus OBJECT-TYPE

SYNTAX RowStatus
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The status of this row, by which new entries may be created, or old entries deleted from this table.

This status object can be set to active(1) without setting any other columnar objects in this entry

All writable objects in this entry can be modified when the status of this entry is active(1)."

::= { pimBsrCandidateRPEntry 10 }

pimBsrCandidateRPStorageType OBJECT-TYPE


```
SYNTAX      StorageType
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The storage type for this row. Rows having the value
    'permanent' need not allow write-access to any columnar
    objects in the row."
    DEFVAL { nonVolatile }
 ::= { pimBsrCandidateRPEntry 11 }

--
-- The BSR Elected BSR RP-Set Table
--

pimBsrElectedBSRRPSetTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF PimBsrElectedBSRRPSetEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The (conceptual) table listing BSR-specific information
        about PIM group mappings learned via C-RP advertisements
        or created locally using configurations. This table is
        maintained only on the Elected BSR.

        An Elected BSR uses this table to create Bootstrap
        Messages after applying a local policy to include some
        or all of the group mappings in this table."

    ::= { pimBsrObjects 2 }

pimBsrElectedBSRRPSetEntry OBJECT-TYPE
    SYNTAX      PimBsrElectedBSRRPSetEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry (conceptual row) in the
        pimBsrElectedBSRRPSetTable."
    INDEX      { pimBsrElectedBSRGrpMappingAddrType,
                  pimBsrElectedBSRGrpMappingGrpAddr,
                  pimBsrElectedBSRGrpMappingGrpPrefixLen,
                  pimBsrElectedBSRGrpMappingRPAddr }
    ::= { pimBsrElectedBSRRPSetTable 1 }

PimBsrElectedBSRRPSetEntry ::= SEQUENCE {
    pimBsrElectedBSRGrpMappingAddrType      InetAddressType,
    pimBsrElectedBSRGrpMappingGrpAddr       InetAddress,
    pimBsrElectedBSRGrpMappingGrpPrefixLen  InetAddressPrefixLength,
    pimBsrElectedBSRGrpMappingRPAddr        InetAddress,
```



```
pimBsrElectedBSRRPSetPriority      Unsigned32,
pimBsrElectedBSRRPSetHoldtime      Unsigned32,
pimBsrElectedBSRRPSetExpiryTime    TimeTicks,
pimBsrElectedBSRRPSetGrpBidir      TruthValue
}
```

pimBsrElectedBSRGrpMappingAddrType OBJECT-TYPE

```
SYNTAX      InetAddressType
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The Inet address type of the IP multicast group
    prefix."
 ::= { pimBsrElectedBSRRPSetEntry 2 }
```

pimBsrElectedBSRGrpMappingGrpAddr OBJECT-TYPE

```
SYNTAX      InetAddress (SIZE (4|8|16|20))
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The IP multicast group address which, when combined
    with pimBsrElectedBSRGrpMappingGrpPrefixLen, gives the
    group prefix for this mapping. The InetAddressType is
    given by the pimBsrElectedBSRGrpMappingAddrType object.

    This address object is only significant up to
    pimBsrElectedBSRGrpMappingGrpPrefixLen bits. The
    remainder of the address bits are zero. This is
    especially important for this field, which is part of
    the index of this entry. Any non-zero bits would
    signify an entirely different entry."
 ::= { pimBsrElectedBSRRPSetEntry 3 }
```

pimBsrElectedBSRGrpMappingGrpPrefixLen OBJECT-TYPE

```
SYNTAX      InetAddressPrefixLength (4..128)
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The multicast group prefix length that, when combined
    with pimBsrElectedBSRGrpMappingGrpAddr, gives the group
    prefix for this mapping. The InetAddressType is given by
    the pimBsrElectedBSRGrpMappingAddrType object. If
    pimBsrElectedBSRGrpMappingAddrType is 'ipv4' or 'ipv4z',
    this object must be in the range 4..32. If
    pimBsrElectedBSRGrpMappingAddrType is 'ipv6' or 'ipv6z',
    this object must be in the range 8..128."
 ::= { pimBsrElectedBSRRPSetEntry 4 }
```


pimBsrElectedBSRGrpMappingRPAAddr OBJECT-TYPE

SYNTAX InetAddress (SIZE (4|8|16|20))

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The IP address of the RP to be used for groups within this group prefix. The InetAddressType is given by the pimBsrElectedBSRGrpMappingAddrType object."

::= { pimBsrElectedBSRRPSetEntry 5 }

pimBsrElectedBSRRPSetPriority OBJECT-TYPE

SYNTAX Unsigned32 (0..255)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The priority for RP. Numerically higher values for this object indicate lower priorities, with the value zero denoting the highest priority."

REFERENCE "[RFC5059 section 4.1](#)"

::= { pimBsrElectedBSRRPSetEntry 6 }

pimBsrElectedBSRRPSetHolddtime OBJECT-TYPE

SYNTAX Unsigned32 (0..65535)

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The holddtime for RP"

REFERENCE "[RFC5059 section 4.1](#)"

::= { pimBsrElectedBSRRPSetEntry 7 }

pimBsrElectedBSRRPSetExpiryTime OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The minimum time remaining before this entry will be aged out. The value zero indicates that this entry will never be aged out."

::= { pimBsrElectedBSRRPSetEntry 8 }

pimBsrElectedBSRRPSetGrpBidir OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"If this object is TRUE, this group range with this RP is a BIDIR-PIM group range. If it is set to FALSE,


```
        it is a PIM-SM group range."
 ::= { pimBsrElectedBSRRPSetEntry 9 }

--
-- The BSR Candidate-BSR Table
--

pimBsrCandidateBSRTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF PimBsrCandidateBSREntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The (conceptual) table containing Candidate-BSR
        configuration for the local router. The table contains
        one row for each zone for which the local router is
        to advertise itself as a Candidate-BSR."
    ::= { pimBsrObjects 3 }

pimBsrCandidateBSREntry OBJECT-TYPE
    SYNTAX      PimBsrCandidateBSREntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry (conceptual row) in the
        pimBsrCandidateBSRTable."
    INDEX       { pimBsrCandidateBSRZoneIndex }
    ::= { pimBsrCandidateBSRTable 1 }

PimBsrCandidateBSREntry ::= SEQUENCE {
    pimBsrCandidateBSRZoneIndex      InetZoneIndex,
    pimBsrCandidateBSRAddressType    InetAddressType,
    pimBsrCandidateBSRAddress        InetAddress,
    pimBsrCandidateBSRPriority       Unsigned32,
    pimBsrCandidateBSRHashMaskLength Unsigned32,
    pimBsrCandidateBSRElectedBSR    TruthValue,
    pimBsrCandidateBSRBootstrapTimer TimeTicks,
    pimBsrCandidateBSRStatus         RowStatus,
    pimBsrCandidateBSRStorageType     StorageType
}

pimBsrCandidateBSRZoneIndex OBJECT-TYPE
    SYNTAX      InetZoneIndex (1..4294967295)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The zone index uniquely identifies the zone on a
        device to which this Candidate BSR is attached. There is
        one entry for each zone in ipMcastZoneTable. Scope-level
```


information for this zone can be extracted from
ipMcastZoneTable in IP Multicast MIB [[RFC5132](#)].

Zero is a special value used to request the default zone
for a given scope. Zero is not a valid value for this
object."

::= { pimBsrCandidateBSREntry 1 }

pimBsrCandidateBSRAddressType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The address type of the Candidate-BSR."

::= { pimBsrCandidateBSREntry 2 }

pimBsrCandidateBSRAddress OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The (unicast) address that the local router will
use to advertise itself as a Candidate-BSR. The
InetAddressType is given by the
pimBsrCandidateBSRAddressType object."

::= { pimBsrCandidateBSREntry 3 }

pimBsrCandidateBSRPriority OBJECT-TYPE

SYNTAX Unsigned32 (0..255)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The priority value for the local router as a
Candidate-BSR for this zone. Numerically higher
values for this object indicate higher priorities."

DEFVAL { 0 }

::= { pimBsrCandidateBSREntry 4 }

pimBsrCandidateBSRHashMaskLength OBJECT-TYPE

SYNTAX Unsigned32 (0..128)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The hash mask length (used in the RP hash function)
that the local router will advertise in its Bootstrap
messages for this zone. This object defaults
to 30 if pimBsrCandidateBSRAddressType is 'ipv4' or


```
        'ipv4z' , and defaults to 126 if
        pimBsrCandidateBSRAddressType is 'ipv6' or 'ipv6z'."
 ::= { pimBsrCandidateBSREntry 5 }
```

pimBsrCandidateBSRElectedBSR OBJECT-TYPE

```
SYNTAX      TruthValue
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "Whether the local router is the elected BSR for this
    zone."
 ::= { pimBsrCandidateBSREntry 6 }
```

pimBsrCandidateBSRBootstrapTimer OBJECT-TYPE

```
SYNTAX      TimeTicks
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The time remaining before the local router next
    originates a Bootstrap message for this zone.
    Value of this object is zero if
    pimBsrCandidateBSRElectedBSR is 'FALSE'."
 ::= { pimBsrCandidateBSREntry 7 }
```

pimBsrCandidateBSRStatus OBJECT-TYPE

```
SYNTAX      RowStatus
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The status of this row, by which new entries may
    be created, or old entries deleted from this table.

    This status object can be set to active(1) without
    setting any other columnar objects in this entry

    All writable objects in this entry can be modified
    when the status of this entry is active(1)."
```

```
 ::= { pimBsrCandidateBSREntry 8 }
```

pimBsrCandidateBSRStorageType OBJECT-TYPE

```
SYNTAX      StorageType
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The storage type for this row. Rows having the value
    'permanent' need not allow write-access to any columnar
    objects in the row."
    DEFVAL { nonVolatile }
```



```

 ::= { pimBsrCandidateBSREntry 9 }

--
-- The BSR Elected-BSR Table
--

pimBsrElectedBSRTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF PimBsrElectedBSREntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The (conceptual) table containing information about
        elected BSRs. The table contains one row for each
        zone for which there is an elected BSR."
    ::= { pimBsrObjects 4 }

pimBsrElectedBSREntry OBJECT-TYPE
    SYNTAX      PimBsrElectedBSREntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry (conceptual row) in the
        pimBsrElectedBSRTable."
    INDEX       { pimBsrElectedBSRZoneIndex }
    ::= { pimBsrElectedBSRTable 1 }

PimBsrElectedBSREntry ::= SEQUENCE {
    pimBsrElectedBSRZoneIndex      InetZoneIndex,
    pimBsrElectedBSRAddressType    InetAddressType,
    pimBsrElectedBSRAddress        InetAddress,
    pimBsrElectedBSRPriority       Unsigned32,
    pimBsrElectedBSRHashMaskLength Unsigned32,
    pimBsrElectedBSRExpiryTime     TimeTicks
}

pimBsrElectedBSRZoneIndex OBJECT-TYPE
    SYNTAX      InetZoneIndex (1..4294967295)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The zone index uniquely identifies the zone on a
        device to which this Elected BSR is attached. There
        is one entry for each zone in ipMcastZoneTable.
        Scope-level information for this zone can be extracted
        from ipMcastZoneTable in IP MCAST MIB.

        Zero is a special value used to request the default zone
        for a given scope. Zero is not a valid value for this

```


object."

::= { pimBsrElectedBSREntry 1 }

pimBsrElectedBSRAddressType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The address type of the elected BSR."

::= { pimBsrElectedBSREntry 2 }

pimBsrElectedBSRAddress OBJECT-TYPE

SYNTAX InetAddress (SIZE (4|8|16|20))

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The (unicast) address of the elected BSR. The
InetAddressType is given by the
pimBsrElectedBSRAddressType object."

::= { pimBsrElectedBSREntry 3 }

pimBsrElectedBSRPriority OBJECT-TYPE

SYNTAX Unsigned32 (0..255)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The priority value for the elected BSR for this address
type. Numerically higher values for this object indicate
higher priorities."

::= { pimBsrElectedBSREntry 4 }

pimBsrElectedBSRHashMaskLength OBJECT-TYPE

SYNTAX Unsigned32 (0..128)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The hash mask length (used in the RP hash function)
advertised by the elected BSR for this zone."

::= { pimBsrElectedBSREntry 5 }

pimBsrElectedBSRExpiryTime OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The minimum time remaining before the elected BSR for
this zone will be declared down."


```
 ::= { pimBsrElectedBSREntry 6 }

--
-- PIM BSR Notifications
--

pimBsrElectedBSRLostElection  NOTIFICATION-TYPE
    OBJECTS { pimBsrElectedBSRAddressType,
               pimBsrElectedBSRAddress,
               pimBsrElectedBSRPriority }
    STATUS      current
    DESCRIPTION
        "A pimBsrElectedBSRLostElection notification should be
        generated when current E-BSR lost election to a new
        Candidate BSR. Only an E-BSR should generate this
        notification.

        This notification is generated when
        pimBsrCandidateBSRElectedBSR becomes FALSE."

    REFERENCE "RFC5059 section 3.1"
    ::= { pimBsrNotifications 1 }

pimBsrCandidateBSRWinElection  NOTIFICATION-TYPE
    OBJECTS { pimBsrCandidateBSRElectedBSR }
    STATUS      current
    DESCRIPTION
        "A pimBsrCandidateBSRWinElection notification should be
        generated when a C-BSR wins BSR Election. Only an
        E-BSR should generate this notification.

        This notification is generated when
        pimBsrCandidateBSRElectedBSR becomes TRUE."

    REFERENCE "RFC5059 section 3.1"
    ::= { pimBsrNotifications 2 }

--
-- Compliance Statements
--

pimBsrCompliance MODULE-COMPLIANCE
    STATUS      current
    DESCRIPTION
        "The compliance statement for PIM routers that implement
        the Bootstrap Router (BSR) mechanism."
    MODULE      -- this module
    MANDATORY-GROUPS { pimBsrObjectGroup }
```



```
GROUP    pimBsrDiagnosticsGroup
DESCRIPTION
    "This group is optional."

 ::= { pimBsrCompliances 1 }

--
-- Units of Conformance
--

pimBsrObjectGroup OBJECT-GROUP
    OBJECTS { pimBsrCandidateRPBidir,
                pimBsrCandidateRPAdvTimer,
                pimBsrCandidateRPPriority,
                pimBsrCandidateRPAdvInterval,
                pimBsrCandidateRPHoldtime,
                pimBsrCandidateRPStatus,
                pimBsrCandidateRPStorageType,
                pimBsrElectedBSRRPSetPriority,
                pimBsrElectedBSRRPSetHoldtime,
                pimBsrElectedBSRRPSetExpiryTime,
                pimBsrElectedBSRRPSetGrpBidir,
                pimBsrCandidateBSRAddress,
                pimBsrCandidateBSRAddressType,
                pimBsrCandidateBSRPriority,
                pimBsrCandidateBSRHashMaskLength,
                pimBsrCandidateBSRElectedBSR,
                pimBsrCandidateBSRBootstrapTimer,
                pimBsrCandidateBSRStatus,
                pimBsrCandidateBSRStorageType,
                pimBsrElectedBSRAddress,
                pimBsrElectedBSRAddressType,
                pimBsrElectedBSRPriority,
                pimBsrElectedBSRHashMaskLength,
                pimBsrElectedBSRExpiryTime }
    STATUS current
    DESCRIPTION
        "A collection of objects for managing the Bootstrap
        Router (BSR) mechanism for PIM routers."
    ::= { pimBsrGroups 1 }

pimBsrDiagnosticsGroup NOTIFICATION-GROUP
    NOTIFICATIONS { pimBsrElectedBSRLostElection,
                    pimBsrCandidateBSRWinElection }
    STATUS current
    DESCRIPTION
        "Objects providing additional diagnostics related to
        the Bootstrap Router (BSR) mechanism for PIM routers."
```



```
::= { pimBsrGroups 2 }
```

END

6. Security Considerations

There are a number of management objects defined in this MIB module with a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations. These are the tables and objects and their sensitivity/vulnerability:

- o A new Candidate BSR with high priority or modification of priority of an existing candidate BSR can take over the functionality of Elected BSR, which can prevent and disrupt the services.
- o A new Candidate RP with lower priority or modification of priority of an existing Candidate RP can force other routers to select itself for a particular group prefix. This can prevent and disrupt the services provided through this group prefix.

The following are the read-write and read-create objects defined in this MIB module:

```
bsrCandidateRPBidir  
bsrCandidateRPPriority  
bsrCandidateRPAAdvInterval  
bsrCandidateRPHoldtime  
bsrCandidateBSRAddressType  
bsrCandidateBSRAddress  
bsrCandidateBSRPriority  
bsrCandidateBSRHashMaskLength
```

Some of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP. These are the tables and objects and their sensitivity/vulnerability:


```
pimBsrCandidateRPAAdvTimer
pimBsrElectedBSRRPSetPriority
pimBsrElectedBSRRPSetHoldtime
pimBsrElectedBSRRPSetExpiryTime
pimBsrElectedBSRRPSetGrpBidir
pimBsrCandidateBSRElectedBSR
pimBsrCandidateBSRBootstrapTimer
pimBsrElectedBSRAddressType
pimBsrElectedBSRAddress
pimBsrElectedBSRPriority
pimBsrElectedBSRHashMaskLength
pimBsrElectedBSRExpiryTime
```

In this MIB module, possible effects that can be induced by GET operations include:

- o Determination of Elected BSR, Candidate BSRs and Candidate RPs in the Multicast Network topology. This information may be sensitive and may be used in preparation for DoS attacks including any of the attacks described above.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), there is still no control over whom on the secure network is allowed to access (read/change/create/delete) the objects in this MIB module.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [\[RFC3410\]](#), [section 8](#)), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to access (read/change/create/delete) them.

7. IANA Considerations

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER values recorded in the SMI Numbers registry:

Descriptor	OBJECT IDENTIFIER value
-----	-----
pimBsrMIB	{ mib-2 XXX }

Editor's Note (to be removed prior to publication): the IANA is requested to assign a value for "XXX" under the 'mib-2' subtree and to record the assignment in the SMI Numbers registry. When the assignment has been made, the RFC Editor is asked to replace "XXX" (here and in the MIB module) with the assigned value and to remove this note.

8. Acknowledgments

This MIB module is based on the original work in [[RFC5060](#)] by R. Sivaramu, J. Lingard and B. Joshi.

Many thanks to Bill Fenner, Stig Venaas, Nidhi Bhaskar, David Mcwalter, David Harrington and J. W. Atwood for their feedback on this MIB module.

Suggested IPv6 multicast MIBs by R. Sivaramu and R. Raghunarayan have been used for comparison while editing this MIB module.

9. References

9.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), April 1999.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, [RFC 2579](#), April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIv2", STD 58, [RFC 2580](#), April 1999.
- [RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", [RFC 4001](#), February 2005.
- [RFC4601] Fenner, B., Handley, M., Holbrook, H., and I. Kouvelas, "Protocol Independent Multicast - Sparse Mode (PIM-SM): Protocol Specification (Revised)", [RFC 4601](#), August 2006.

- [RFC5060] Sivaramu, R., Lingard, J., McWalter, D., Joshi, B., and A. Kessler, "Protocol Independent Multicast MIB", [RFC 5060](#), January 2008.
- [RFC5059] Bhaskar, N., Gall, A., Lingard, J., and S. Venaas, "Bootstrap Router (BSR) Mechanism for Protocol Independent Multicast (PIM)", [RFC 5059](#), January 2008.
- [RFC5132] McWalter, D., Thaler, D., and A. Kessler, "IP Multicast MIB", [RFC 5132](#), December 2007.

9.2. Informative References

- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", [RFC 3410](#), December 2002.

Authors' Addresses

Bharat Joshi
Infosys Technologies Ltd.
44 Electronics City, Hosur Road
Bangalore 560 100
India

Email: bharat_joshi@infosys.com
URI: <http://www.infosys.com/>

Raina Bijlani

Email: rainab@gmail.com

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY, THE IETF TRUST AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The IETF Trust (2008). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.

