

PIM Working Group
Internet-Draft
Intended status: Informational
Expires: April 19, 2013

H. Asaeda
NICT
N. Leymann
Deutsche Telekom AG
October 16, 2012

IGMP/MLD-Based Explicit Membership Tracking Function for Multicast
Routers
draft-ietf-pim-explicit-tracking-02

Abstract

This document describes the IGMP/MLD-based explicit membership tracking function for multicast routers. The explicit tracking function is useful for accounting and contributes to saving network resource and fast leaves (i.e. shortened leave latency).

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 19, 2013.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as

Internet-Draft

Explicit Membership Tracking Function

October 2012

described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	Explicit Tracking Function	4
2.1.	Specific Query Surpression Mechanism	4
2.2.	Shortening Leave Latencies	5
2.3.	Considerations	5
3.	Membership State Information	6
4.	Multicast Router Behavior	7
5.	Compatibility	8
6.	IANA Considerations	8
7.	Security Considerations	8
8.	Acknowledgements	8
9.	References	9
9.1.	Normative References	9
9.2.	Informative References	9
	Authors' Addresses	9

1. Introduction

The Internet Group Management Protocol (IGMP) [[1](#)] for IPv4 and the Multicast Listener Discovery Protocol (MLD) [[2](#)] for IPv6 are the standard protocols used by listener hosts and multicast routers. When a host starts listening particular multicast channels, it sends IGMP/MLD State-Change Report messages specifying the corresponding channel information as the join/leave request to its upstream router (i.e., an adjacent multicast router or IGMP/MLD proxy [[4](#)]). This "unsolicited" Report is sent only once upon reception.

IGMP/MLD are non-reliable protocols; the unsolicited Report messages may be lost or not be reached to upstream routers. To recover the problem, the routers need to update membership information by sending IGMP/MLD General Query messages periodically. Member hosts then reply with "solicited" Report messages whenever they receive the Query messages.

Multicast routers are able to periodically maintain the multicast listener (or membership) state of downstream hosts attached on the same link by getting unsolicited Report messages and synchronize the actual membership state within the General Query timer interval (i.e., [Query Interval] value defined in [[1](#)][[2](#)].) However, this approach does not guarantee that the membership state is always perfectly synchronized. To minimize the possibility of having the outdated membership information, routers may shorten the periodic General Query timer interval. Unfortunately, this would increase the number of transmitted solicited Report messages and induce network congestion. And the more the network congestion is occurred, the more IGMP/MLD Report messages may be lost and the membership state information may be outdated in the router.

The IGMPv3 [[1](#)] and MLDv2 [[2](#)] protocols can provide the capability of keeping track of downstream (adjacent) multicast listener state to multicast routers. This document describes the "IGMP/MLD-based explicit member tracking function" for multicast routers and details

the way for routers to implement the function. By enabling the explicit tracking function, routers can keep track of the downstream multicast membership state. This function implements the following requirements:

- o Per-host accounting
- o Reducing the number of transmitted Query and Report messages
- o Shortening leave latencies

- o Maintaining multicast channel characteristics (or statistics)

where this document mainly focuses on the above second and third bullets in the following sections.

The explicit tracking function does not change message formats used by the standard IGMPv3 [\[1\]](#) and MLDv2 [\[2\]](#), and their lightweight version protocols [\[3\]](#). It does not change a multicast data sender's and receiver's behavior as well.

[2.](#) Explicit Tracking Function

[2.1.](#) Specific Query Suppression Mechanism

The explicit tracking function can reduce the number of Group-Specific or Group-and-Source Specific Query messages transmitted from a router, and then the number of Current-State Report messages transmitted from member hosts. As the result, network resources used for IGMP/MLD query-and-reply communications between a router and member hosts can be saved. This mechanism is called "specific query suppression mechanism".

According to [\[1\]](#) and [\[2\]](#), whenever a router receives the State-Change Report, it sends the corresponding Group-Specific or Group-and-Source Specific Query messages to confirm whether the Report sender is the last member host or not. After getting these Query messages, all member hosts joining the corresponding channel reply with own Current-State Report messages. This condition requires transmitting

a number of Current-State Report messages and consumes network resources especially when many hosts have been joining the same channel.

On the other hand, if a router enables the explicit tracking function, it does not need to always ask Current-State Report message transmission to the member hosts whenever it receives the State-Change Report. This is because the explicit tracking function works with the expectation that the State-Change Report sender is the last remaining member of the channel. Even if this expectation is wrong (i.e., the State-Change Report sender was not the sole member), other members remaining in the same channel will reply with identical Report messages, so the end result is the same and no problem occurs. ([Section 3](#) details the point.)

In addition, the processing of IGMP membership or MLD listener messages consumes CPU resources on each IGMP/MLD querier and report sender devices themselves. Therefore, the explicit tracking function reduces not only the network load but also the CPU load on these

devices as well.

Note that the default behavior of the router that supports the explicit tracking function disables this specific query suppression mechanism, in order to avoid the risk caused by the situation in which multiple multicast routers exist on a LAN and the querier router is not the forwarder router. When the querier suppresses the specific query message transmission, if it recognizes that the State-Change Report sender is not the sole member of the channel, it does not send the specific query and all routers on the same LAN do not receive Current-State Report message from the member hosts. The forwarder in this case may prune the routing path, although there are other member hosts subscribing the channel on the LAN.

[2.2.](#) Shortening Leave Latencies

The explicit tracking function works with the expectation that the State-Change Report sender is the last remaining member of the channel. Thanks to this functionality, a router can tune timers and values related to decide that the State-Change Report sender was the sole member.

The [Last Member Query Interval] (LMQI) and [Last Listener Query Interval] (LLQI) values specify the maximum time allowed before sending a responding Report. The [Last Member Query Count] (LMQC) and [Last Listener Query Count] (LLQC) are the number of Group-Specific Queries or Group-and-Source Specific Queries sent before the router assumes there are no local members. The [Last Member Query Time] (LMQT) and [Last Listener Query Time] (LLQT) values are the total time the router should wait for a report, after the Querier has sent the first query.

The default values for LMQI/LLQI defined in the standard specifications [1][2] are 1 second. For the router enabling the explicit tracking function, LMQI/LLQI would be set to 1 second or shorter. The LMQC/LLQC may be set to "1" for the router, whereas their default values are the [Robustness Variable] value whose default value is "2". Smaller LMQC/LLQC give smaller LMQT/LLQT; this condition shortens the leave latencies.

[2.3.](#) Considerations

As with the basic concepts of IGMP and MLD, the explicit tracking function does not guarantee the membership state is always perfectly synchronized; routers enabling the explicit tracking function still need to send IGMPv3/MLDv2 Query messages and inquire solicited IGMPv3/MLDv2 Report messages from downstream members to maintain downstream membership state.

- o IGMP/MLD messages are non-reliable and may be lost in the transmission, therefore routers need to confirm the membership by sending Query messages.
- o To preserve compatibility with older versions of IGMP/MLD, routers need to support downstream hosts that are not upgraded to the latest versions of IGMP/MLD and run the report suppression mechanism.
- o It is impossible to identify hosts when hosts send IGMP reports with a source address of 0.0.0.0.

Regarding the last bullet, the IGMPv3 specification [1] mentions that an IGMPv3 Report is usually sent with a valid IP source address, although it permits that a host uses the 0.0.0.0 source address (as

it happens that the host has not yet acquired an IP address), and routers MUST accept a report with a source address of 0.0.0.0. The MLDv2 specification [2] mentions that an MLDv2 Report MUST be sent with a valid IPv6 link-local source address, although an MLDv2 Report can be sent with the unspecified address (::), if the sending interface has not acquired a valid link-local address yet. [2] also mentions that routers silently discard a message that is not sent with a valid link-local address or sent with the unspecified address, without taking any action, because of the security consideration.

Another concern is that the explicit tracking function requires additional processing capability and a possibly large memory for routers to keep all membership states. Especially when a router needs to maintain a large number of member hosts, this resource requirement may be potentially-impacted. Operators may decide to disable this function when their routers do not have enough memory resources.

3. Membership State Information

The explicit tracking function is implemented with the following membership state information:

(S, G, number of receivers, (receiver records))

where each receiver record is of the form:

(IGMP/MLD Membership/Listener Report sender's address)

This state information must work properly when a receiver (i.e., Report sender) sends the same Report messages multiple times.

In the state information, each "S" and "G" indicates a single IPv4/IPv6 address. "S" is set to "Null" for an Any-Source Multicast (ASM) communication (i.e., (*,G) join reception). In order to simplify the implementation, the explicit tracking function does not keep the state of (S,G) join with EXCLUDE filter mode. If a router receives (S,G) join/leave request with EXCLUDE filter mode from the downstream hosts, it translates the join/leave request to (*,G) join state/leave request and records the state and the receivers' addresses into the

maintained membership state information. Note that this membership state translation does not change the routing protocol behavior; the routing protocol must deal with the original join/leave request and translate the request only for the membership state information.

[4.](#) Multicast Router Behavior

The explicit tracking function makes routers expect whether the State-Change Report sender is the last remaining member of the channel. Therefore the router transmits a corresponding Current-State Report message only when the router thinks that the State-Change Report sender is the last remaining member of the channel. This contributes to saving the network resources and also shortening leave latency.

To synchronize the membership state information, when a multicast router receives a Current-State or State-Change Report message, it adds the receiver IP address to or delete from the receiver records or creates the corresponding membership state information. If there are no more receiver records left, the membership state information is deleted from the router.

However, the membership state information may be still outdated in the router. It may be happened especially in a mobile multicast environment that some member hosts have joined to or left from the network without sending State-Change Report messages. Or, some State-Change Report messages are lost due to network congestion. Therefore, the router enabling the explicit tracking function ought to send the periodic General Query regularly.

Regarding the leave latency, as specified in [Section 2.2](#), the explicit tracking function contributes to the fast leave by setting LMQI/LLQI to "1" second or shorter and LMQC/LLQC to "1". However, if LMQC/LLQC is configured "2" or bigger value, then the router's behavior may be changed from the standard specification. According to [\[1\]](#) and [\[2\]](#), a router sends a Group- (and-Source) Specific Query [LMQC - 1] or [LLQC - 1] times when it receives State Change Report message (e.g. leave request) from a member host, in order to confirm whether or not the host is the only remaining member. However, this

function receives the corresponding Current State Report before the Specific Query retransmission, it cancels sending the same Specific Query for other [LMQC - 1] or [LLQC - 1] times.

Note that there is some risk that a router misses or loses Report messages sent from remaining members if the router adopts small LMQC/LLQC; however the wrong expectation would be lower happened for the router enabling the explicit tracking function. And to avoid the problem, a router can start sending a Group- (and-Source) Specific Query message when it expects the number of the remaining members is small, such as 5, but not 0.

[5.](#) Compatibility

The explicit tracking function does not work with the older versions of IGMP or MLD, IGMPv1 [\[5\]](#), IGMPv2 [\[6\]](#) or MLDv1 [\[7\]](#), because a member host using these protocols adopts a report suppression mechanism by which a host would cancel sending a pending membership Reports if a similar Report was observed from another member on the network.

If a multicast router enabling the explicit tracking function changes its compatibility mode to the older versions of IGMP or MLD, the router should turn off the explicit tracking function but should not flush the maintained membership state information (i.e., keep the current membership state information as is). When the router changes back to IGMPv3 or MLDv2 mode, it would resume the function with the kept membership state information, even if the state information is outdated. This manner would give "smooth state transition" that does not initiate the membership state from scratch and synchronizes the actual membership state smoothly.

[6.](#) IANA Considerations

This document has no actions for IANA.

[7.](#) Security Considerations

There is no additional security considerations.

[8.](#) Acknowledgements

Toerless Eckert, Stig Venaas, and others provided many constructive and insightful comments.

[9.](#) References

[9.1.](#) Normative References

- [1] Cain, B., Deering, S., Kouvelas, I., Fenner, B., and A. Thyagarajan, "Internet Group Management Protocol, Version 3", [RFC 3376](#), October 2002.
- [2] Vida, R. and L. Costa, "Multicast Listener Discovery Version 2 (MLDv2) for IPv6", [RFC 3810](#), June 2004.
- [3] Liu, H., Cao, W., and H. Asaeda, "Lightweight Internet Group Management Protocol Version 3 (IGMPv3) and Multicast Listener Discovery Version 2 (MLDv2) Protocols", [RFC 5790](#), February 2010.

[9.2.](#) Informative References

- [4] Fenner, B., He, H., Haberman, B., and H. Sandick, "Internet Group Management Protocol (IGMP) / Multicast Listener Discovery (MLD)-Based Multicast Forwarding ("IGMP/MLD Proxying")", [RFC 4605](#), August 2006.
- [5] Deering, S., "Host Extensions for IP Multicasting", [RFC 1112](#), August 1989.
- [6] Fenner, W., "Internet Group Management Protocol, Version 2", [RFC 2373](#), July 1997.
- [7] Deering, S., Fenner, W., and B. Haberman, "Multicast Listener Discovery (MLD) for IPv6", [RFC 2710](#), October 1999.

Authors' Addresses

Hitoshi Asaeda
National Institute of Information and Communications Technology
4-2-1 Nukui-Kitamachi
Koganei, Tokyo 184-8795
Japan

Email: asaeda@nict.go.jp

Internet-Draft

Explicit Membership Tracking Function

October 2012

Nicolai Leymann
Deutsche Telekom AG
Winterfeldtstrasse 21-27
Berlin 10781
Germany

Email: n.leymann@telekom.de

