

PIM Working Group
Internet-Draft
Intended Status: Standard Track
Expires: August 8, 2017

X. Liu
Ericsson
F. Guo
Huawei
M. Sivakumar
Cisco
P. McAllister
Metaswitch Networks
A. Peter
Juniper Networks
February 7, 2017

**A YANG data model for Internet Group Management Protocol (IGMP) and
Multicast Listener Discovery (MLD)
draft-ietf-pim-igmp-mld-yang-02**

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>

This Internet-Draft will expire on August 8, 2017.

Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents

carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Simplified BSD License.

Abstract

This document defines a YANG data model that can be used to configure and manage Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) devices.

Table of Contents

1.	Introduction	2
1.1.	Requirements Language	3
1.2.	Terminology	3
2.	Design of Data model.....	3
2.1.	Scope of model	3
2.2.	Optional capabilities.....	3
2.3.	Position of address family in hierarchy.....	4
3.	Module Structure	4
3.1.	IGMP and MLD Configuration.....	4
3.2.	IGMP and MLD Operational State.....	6
3.3.	IGMP and MLD RPC.....	10
4.	IGMP and MLD YANG Modules.....	10
5.	Security Considerations.....	31
6.	IANA Considerations	31
7.	References	31
7.1.	Normative References.....	31
7.2.	Informative References.....	32
8.	Acknowledgments	32

[1. Introduction](#)

YANG [[RFC6020](#)] [[RFC6087](#)] is a data definition language that was introduced to model the configuration and running state of a device managed using NETCONF [[RFC6241](#)]. YANG is now also being used as a component of wider management interfaces, such as CLIs.

This document defines a draft YANG data model that can be used to configure and manage Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) devices. Currently this model is incomplete, but it will support the core IGMP and MLD protocols, as well as many other features mentioned in separate IGMP and MLD RFCs. Non-core features are defined as optional in the provided data model.

1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC-2119](#) [[RFC2119](#)].

1.2. Terminology

The terminology for describing YANG data models is found in [[RFC6020](#)].

This draft employs YANG tree diagrams, which are explained in [I-D.ietf-netmod-rfc6087bis].

2. Design of Data model

2.1. Scope of model

The model covers IGMPv1 [[RFC1112](#)], IGMPv2 [[RFC2236](#)], IGMPv3 [[RFC3376](#)] and MLDv1 [[RFC2710](#)], MLDv2 [[RFC3810](#)].

The representation of some extension features of IGMP and MLD is not specified in this draft of the data model. This model is being circulated in its current form for early oversight and review of the basic hierarchy.

The operational state fields and rpcs of this model can also be extended, and the structure of what has been written may be taken as representative of the structure of the whole model.

This model does not cover other IGMP and MLD related protocols such as IGMP/MLD Proxy [[RFC4605](#)] or IGMP/MLD Snooping [[RFC4541](#)] etc., these will be specified in separate documents.

2.2. Optional capabilities

This model is designed to represent the capabilities of IGMP and MLD devices with various specifications, including some with basic subsets of the IGMP and MLD protocols. The main design goals of this draft are that any major now-existing implementation may be said to support the basic model, and that the configuration of all implementations meeting the specification is easy to express through some combination of the features in the basic model and simple vendor augmentations.

There is also value in widely-supported features being standardized, to save work for individual vendors, and so that mapping between different vendors' configuration is not needlessly complicated.

Therefore these modules declare a number of features representing capabilities that not all deployed devices support.

The extensive use of feature declarations should also substantially simplify the capability negotiation process for a vendor's IGMP and MLD implementations.

On the other hand, operational state parameters are not so widely designated as features, as there are many cases where the defaulting of an operational state parameter would not cause any harm to the system, and it is much more likely that an implementation without native support for a piece of operational state would be able to derive a suitable value for a state variable that is not natively supported.

For the same reason, wide constant ranges (for example, timer maximum and minimum) will be used in the model. It is expected that vendors will augment the model with any specific restrictions that might be required. Vendors may also extend the features list with proprietary extensions.

2.3. Position of address family in hierarchy

The current draft contains IGMP and MLD as separate schema branches in the structure. The reason for this is to make it easier for implementations which may optionally choose to support specific address families. And the names of objects may be different between the ipv4 (IGMP) and ipv6 (MLD) address families.

3. Module Structure

3.1. IGMP and MLD Configuration

The IGMP and MLD modules define the routing-instance-wide configuration options in a three-level hierarchy as listed below:

Global level: IGMP MLD configuration attributes for the entire routing instance

Interface-global: IGMP MLD configuration attributes applicable to all interfaces IGMP MLD configuration attributes applied to interfaces whose interface level attributes are not existing, with same attributes' value for those

Interface-level: IGMP MLD configuration attributes specific to the given interface

Where fields are not genuinely essential to protocol operation, they are marked as optional. Some fields will be essential but have a

default specified, so that they need not be configured explicitly. The module structure also applies, where applicable, to the operational state and notifications as well.

Our current direction is to agree to a routing-instance-centric (VRF) model as opposed to protocol-centric mainly because it fits well into the routing-instance model, and it is easier to map from the VRF-centric to the protocol-centric than the other way around due to forward references.

The IGMP and MLD model augments `/rt:routing/rt:control-plane-protocols` as opposed to augmenting `/rt:routing/rt:control-plane-protocols/rt:control-plane-protocol` as the latter would allow multiple protocol instances per VRF, which does not make sense for IGMP and MLD.

augment `/rt:routing/rt:control-plane-protocols`:

```

  +--rw igmp
  |   +--rw global
  |   |   +--rw enable?          boolean {global-admin-enable}?
  |   |   +--rw max-entries?     uint32 {global-max-entries}?
  |   |   +--rw max-groups?      uint32 {global-max-groups}?
  |   +--rw interfaces
  |       +--rw last-member-query-interval?  uint16
  |       +--rw max-groups-per-interface?    uint32 {intf-max-groups}?
  |       +--rw query-interval?              uint16
  |       +--rw query-max-response-time?     uint16
  |       +--rw require-router-alert?        boolean {intf-require-router-
alert}?
  |       +--rw robustness-variable?         uint8
  |       +--rw version?                     uint8
  |       +--rw interface* [interface]
  |           +--rw interface                if:interface-ref
  |           +--rw enable?                  boolean {intf-admin-enable}?
  |           +--rw group-policy?            string
  |           +--rw immediate-leave?         empty {intf-immediate-
leave}?
  |           +--rw last-member-query-interval?  uint16
  |           +--rw max-groups?                 uint32 {intf-max-groups}?
  |           +--rw max-group-sources?          uint32 {intf-max-group-
sources}?
  |           +--rw query-interval?             uint16
  |           +--rw query-max-response-time?    uint16
  |           +--rw require-router-alert?       boolean {intf-require-
router-alert}?
  |           +--rw robustness-variable?        uint8
  |           +--rw source-policy?              string {intf-source-policy}?
  |           +--rw verify-source-subnet?       empty {intf-verify-source-

```

```

subnet}?
  |      +--rw version?                               uint8
  |      +--rw join-group*                             inet:ipv4-address {intf-
join-group}?
  |      +--rw ssm-map* [source-addr group-policy] {intf-ssm-map}?
  |      |      +--rw source-addr      ssm-map-ipv4-addr-type
  |      |      +--rw group-policy     string

```

```

|         +--rw static-group* [group source-addr] {intf-static-group}?
|         +--rw group          inet:ipv4-address
|         +--rw source-addr    source-ipv4-addr-type
+--rw mld
  +--rw global
    | +--rw enable?            boolean {global-admin-enable}?
    | +--rw max-entries?      uint32 {global-max-entries}?
    | +--rw max-groups?      uint32 {global-max-groups}?
  +--rw interfaces
    +--rw last-member-query-interval?  uint16
    +--rw max-groups-per-interface?    uint32 {intf-max-groups}?
    +--rw query-interval?              uint16
    +--rw query-max-response-time?     uint16
    +--rw require-router-alert?       boolean {intf-require-router-
alert}?
    +--rw robustness-variable?         uint8
    +--rw version?                     uint8
    +--rw interface* [interface]
      +--rw interface                  if:interface-ref
      +--rw enable?                    boolean {intf-admin-enable}?
      +--rw group-policy?              string
      +--rw immediate-leave?           empty {intf-immediate-
leave}?
      +--rw last-member-query-interval?  uint16
      +--rw max-groups?                  uint32 {intf-max-groups}?
      +--rw max-group-sources?          uint32 {intf-max-group-
sources}?
      +--rw query-interval?              uint16
      +--rw query-max-response-time?     uint16
      +--rw require-router-alert?       boolean {intf-require-
router-alert}?
      +--rw robustness-variable?         uint8
      +--rw source-policy?               string {intf-source-policy}?
      +--rw verify-source-subnet?        empty {intf-verify-source-
subnet}?
      +--rw version?                     uint8
      +--rw join-group*                  inet:ipv6-address {intf-
join-group}?
      +--rw ssm-map* [source-addr group-policy] {intf-ssm-map}?
      | +--rw source-addr              ssm-map-ipv6-addr-type
      | +--rw group-policy              string
      +--rw static-group* [group source-addr] {intf-static-group}?
      +--rw group                      inet:ipv6-address
      +--rw source-addr                  source-ipv6-addr-type

```

3.2. IGMP and MLD Operational State

The IGMP and MLD module contains operational state information also in a three-level hierarchy as mentioned earlier.

Global level: IGMP MLD operational state attributes for the entire routing instance

Interface-global: IGMP MLD interface level operational state attributes applied to interfaces whose interface level attributes do not exist, with same attributes' value for those interfaces

Interface-specific: IGMP MLD operational state attributes specific to the given interface.

augment /rt:routing-state/rt:control-plane-protocols:

```

  +--ro igmp
  |   +--ro global
  |   |   +--ro enable?          boolean {global-admin-enable}?
  |   |   +--ro max-entries?     uint32 {global-max-entries}?
  |   |   +--ro max-groups?      uint32 {global-max-groups}?
  |   |   +--ro entries-count?   uint32
  |   |   +--ro groups-count?    uint32
  |   |   +--ro statistics
  |   |   |   +--ro discontinuity-time?  yang:date-and-time
  |   |   |   +--ro error
  |   |   |   |   +--ro total?          yang:counter64
  |   |   |   |   +--ro query?         yang:counter64
  |   |   |   |   +--ro report?        yang:counter64
  |   |   |   |   +--ro leave?         yang:counter64
  |   |   |   |   +--ro checksum?      yang:counter64
  |   |   |   |   +--ro too-short?     yang:counter64
  |   |   |   +--ro received
  |   |   |   |   +--ro total?          yang:counter64
  |   |   |   |   +--ro query?         yang:counter64
  |   |   |   |   +--ro report?        yang:counter64
  |   |   |   |   +--ro leave?         yang:counter64
  |   |   |   +--ro sent
  |   |   |   |   +--ro total?          yang:counter64
  |   |   |   |   +--ro query?         yang:counter64
  |   |   |   |   +--ro report?        yang:counter64
  |   |   |   |   +--ro leave?         yang:counter64
  |   |   +--ro interfaces
  |   |   |   +--ro last-member-query-interval?  uint16
  |   |   |   +--ro max-groups-per-interface?    uint32 {intf-max-groups}?
  |   |   |   +--ro query-interval?              uint16
  |   |   |   +--ro query-max-response-time?     uint16
  |   |   |   +--ro require-router-alert?        boolean {intf-require-router-
alert}?
  |   |   |   +--ro robustness-variable?         uint8
  |   |   |   +--ro version?                     uint8
  |   |   +--ro interface* [interface]
  |   |   |   +--ro interface                    if:interface-ref
  |   |   |   +--ro enable?                      boolean {intf-admin-enable}?
  |   |   |   +--ro group-policy?                string
  |   |   |   +--ro immediate-leave?             empty {intf-immediate-

```

```
leave}?
|      +--ro last-member-query-interval?  uint16
|      +--ro max-groups?                   uint32 {intf-max-groups}?
```

Liu & Guo, etc

Expires August 8, 2017

[Page 7]

```

    |      +--ro max-group-sources?          uint32 {intf-max-group-
source    |
    |      +--ro query-interval?             uint16
    |      +--ro query-max-response-time?    uint16
    |      +--ro require-router-alert?       boolean {intf-require-
router-alert}?
    |      +--ro robustness-variable?        uint8
    |      +--ro source-policy?              string {intf-source-policy}?
    |      +--ro verify-source-subnet?        empty {intf-verify-source-
subnet}?
    |      +--ro version?                    uint8
    |      +--ro join-group*                  inet:ipv4-address {intf-
join-group}?
    |      +--ro ssm-map* [source-addr group-policy] {intf-ssm-map}?
    |      | +--ro source-addr      ssm-map-ipv4-addr-type
    |      | +--ro group-policy     string
    |      +--ro static-group* [group source-addr] {intf-static-group}?
    |      | +--ro group            inet:ipv4-address
    |      | +--ro source-addr      source-ipv4-addr-type
    |      +--ro oper-status?          enumeration
    |      +--ro dr?                  inet:ipv4-address
    |      +--ro querier?             inet:ipv4-address
    |      +--ro joined-group*         inet:ipv4-address {intf-
join-group}?
    |      +--ro group* [address]
    |      | +--ro address           inet:ipv4-address
    |      | +--ro expire?          uint32
    |      | +--ro filter-mode?     enumeration
    |      | +--ro host-count?      uint32
    |      | +--ro up-time?         uint32
    |      | +--ro host*            inet:ipv4-address
    |      | +--ro last-reporter?   inet:ipv4-address
    |      | +--ro source* [address]
    |      | | +--ro address         inet:ipv4-address
    |      | | +--ro expire?        uint32
    |      | | +--ro up-time?       uint32
    |      | | +--ro last-reporter? inet:ipv4-address
+--ro mld
  +--ro global
    | +--ro enable?          boolean {global-admin-enable}?
    | +--ro max-entries?     uint32 {global-max-entries}?
    | +--ro max-groups?      uint32 {global-max-groups}?
    | +--ro entries-count?   uint32
    | +--ro groups-count?    uint32
    | +--ro statistics
    | | +--ro discontinuity-time? yang:date-and-time
    | | +--ro error
    | | | +--ro total?        yang:counter64

```

```
|      | +--ro query?      yang:counter64
|      | +--ro report?    yang:counter64
|      | +--ro leave?     yang:counter64
|      | +--ro checksum?  yang:counter64
|      | +--ro too-short? yang:counter64
|      +--ro received
```

```

|      | +--ro total?      yang:counter64
|      | +--ro query?     yang:counter64
|      | +--ro report?    yang:counter64
|      | +--ro leave?     yang:counter64
|      +--ro sent
|          +--ro total?    yang:counter64
|          +--ro query?    yang:counter64
|          +--ro report?   yang:counter64
|          +--ro leave?    yang:counter64
+--ro interfaces
    +--ro last-member-query-interval?  uint16
    +--ro max-groups-per-interface?    uint32 {_intf-max-groups}?
    +--ro query-interval?              uint16
    +--ro query-max-response-time?     uint16
    +--ro require-router-alert?        boolean {_intf-require-router-
alert}?
    +--ro robustness-variable?         uint8
    +--ro version?                     uint8
    +--ro interface* [interface]
        +--ro interface                if:interface-ref
        +--ro enable?                  boolean {_intf-admin-enable}?
        +--ro group-policy?            string
        +--ro immediate-leave?         empty {_intf-immediate-
leave}?
        +--ro last-member-query-interval?  uint16
        +--ro max-groups?                uint32 {_intf-max-groups}?
        +--ro max-group-sources?         uint32 {_intf-max-group-
sources}?
        +--ro query-interval?            uint16
        +--ro query-max-response-time?   uint16
        +--ro require-router-alert?      boolean {_intf-require-
router-alert}?
        +--ro robustness-variable?       uint8
        +--ro source-policy?             string {_intf-source-policy}?
        +--ro verify-source-subnet?      empty {_intf-verify-source-
subnet}?
        +--ro version?                   uint8
        +--ro join-group*                inet:ipv6-address {_intf-
join-group}?
        +--ro ssm-map* [source-addr group-policy] {_intf-ssm-map}?
        | +--ro source-addr            ssm-map-ipv6-addr-type
        | +--ro group-policy            string
        +--ro static-group* [group source-addr] {_intf-static-group}?
        | +--ro group                  inet:ipv6-address
        | +--ro source-addr            source-ipv6-addr-type
        +--ro oper-status?              enumeration
        +--ro querier?                  inet:ipv6-address
        +--ro joined-group*             inet:ipv6-address {_intf-

```

join-group}?

```
+--ro group* [address]
+--ro address          inet:ipv6-address
+--ro expire?          uint32
+--ro filter-mode?     enumeration
+--ro host-count?      uint32
+--ro up-time?         uint32
+--ro host*            inet:ipv6-address
```

```

+--ro last-reporter?  inet:ipv6-address
+--ro source* [address]
  +--ro address        inet:ipv6-address
  +--ro expire?        uint32
  +--ro up-time?        uint32
  +--ro last-reporter?  inet:ipv6-address

```

3.3. IGMP and MLD RPC

rpcs:

```

+---x clear-igmp-groups {rpc-clear-groups}?

| +---w input

|   +---w interface?  -> /rt:routing/control-plane-protocols/igmp/
interfaces/interface/interface

|   +---w group?       inet:ipv4-address

|   +---w source?      inet:ipv4-address

+---x clear-mld-groups {rpc-clear-groups}?

+---w input

+---w interface?  -> /rt:routing/control-plane-protocols/mld/
interfaces/interface/interface

+---w group?      inet:ipv6-address

+---w source?      inet:ipv6-address

```

4. IGMP and MLD YANG Modules

```

<CODE BEGINS> file "ietf-igmp-mld@2016-10-28.yang"
module ietf-igmp-mld {
  namespace "urn:ietf:params:xml:ns:yang:ietf-igmp-mld";
  // replace with IANA namespace when assigned
  prefix igmp-mld;

  import ietf-inet-types {
    prefix "inet";
  }

  import ietf-yang-types {

```



```
    prefix "yang";
  }

  import ietf-routing {
    prefix "rt";
  }

  import ietf-interfaces {
    prefix "if";
  }

  import ietf-ip {
    prefix ip;
  }

  organization
    "IETF PIM Working Group";

  contact
    "WG Web:  <http://tools.ietf.org/wg/pim/>
    WG List:  <mailto:pim@ietf.org>

    WG Chair: Stig Venaas
              <mailto:stig@venaas.com>

    WG Chair: Mike McBride
              <mailto:mmcbride7@gmail.com>

    Editors:  ";

  description
    "The module defines a collection of YANG definitions common for
    IGMP and MLD.";

  revision 2016-10-28 {
    description
      "Initial revision.";
    reference
      "RFC XXXX: A YANG Data Model for IGMP and MLD";
  }

  /*
   * Features
   */
  feature global-admin-enable {
    description
      "Support global configuration to enable or disable protocol.";
  }
```



```
feature global-interface-config {
  description
    "Support global configuration applied for all interfaces.";
}

feature global-max-entries {
  description
    "Support configuration of global max-entries.";
}

feature global-max-groups {
  description
    "Support configuration of global max-groups.";
}

feature intf-admin-enable {
  description
    "Support configuration of interface administrative enabling.";
}

feature intf-immediate-leave {
  description
    "Support configuration of interface immediate-leave.";
}

feature intf-join-group {
  description
    "Support configuration of interface join-group.";
}

feature intf-max-groups {
  description
    "Support configuration of interface max-groups.";
}

feature intf-max-group-sources {
  description
    "Support configuration of interface max-group-sources.";
}

feature intf-require-router-alert {
  description
    "Support configuration of interface require-router-alert.";
}

feature intf-source-policy {
  description
    "Support configuration of interface source policy.";
}
```



```
feature intf-ssm-map {
  description
    "Support configuration of interface ssm-map.";
}

feature intf-static-group {
  description
    "Support configuration of interface static-group.";
}

feature intf-verify-source-subnet {
  description
    "Support configuration of interface verify-source-subnet.";
}

feature per-interface-config {
  description
    "Support per interface configuration.";
}

feature rpc-clear-groups {
  description
    "Support rpc's to clear groups.";
}

/*
 * Typedefs
 */
typedef ssm-map-ipv4-addr-type {
  type union {
    type enumeration {
      enum 'policy' {
        description
          "Source address is specified in SSM map policy.";
      }
    }
    type inet:ipv4-address;
  }
  description
    "Multicast source IP address type for SSM map.";
} // source-ipv4-addr-type

typedef ssm-map-ipv6-addr-type {
  type union {
    type enumeration {
      enum 'policy' {
        description
```

"Source address is specified in SSM map policy.";

Liu & Guo, etc

Expires August 8, 2017

[Page 13]

```
    }
  }
  type inet:ipv6-address;
}
description
  "Multicast source IP address type for SSM map.";
} // source-ipv6-addr-type

typedef source-ipv4-addr-type {
  type union {
    type enumeration {
      enum '*' {
        description
          "Any source address.";
      }
    }
    type inet:ipv4-address;
  }
  description
    "Multicast source IP address type.";
} // source-ipv4-addr-type

typedef source-ipv6-addr-type {
  type union {
    type enumeration {
      enum '*' {
        description
          "Any source address.";
      }
    }
    type inet:ipv6-address;
  }
  description
    "Multicast source IP address type.";
} // source-ipv6-addr-type

/*
 * Identities
 */

/*
 * Groupings
 */
grouping global-config-attributes {
  description "Global IGMP and MLD configuration.";

  leaf enable {
    if-feature global-admin-enable;
```

```
type boolean;
```

Liu & Guo, etc

Expires August 8, 2017

[Page 14]

```
    description
      "true to enable IGMP in the routing instance;
       false to disable IGMP in the routing instance.";
  }

  leaf max-entries {
    if-feature global-max-entries;
    type uint32;
    description
      "The maximum number of entries in IGMP.";
  }
  leaf max-groups {
    if-feature global-max-groups;
    type uint32;
    description
      "The maximum number of groups that IGMP can join.";
  }
} // global-config-attributes

grouping global-state-attributes {
  description "Global IGMP and MLD state attributes.";

  leaf entries-count {
    type uint32;
    description
      "The number of entries in IGMP.";
  }
  leaf groups-count {
    type uint32;
    description
      "The number of groups that IGMP can join.";
  }
}

container statistics {
  description "Global statistics.";

  leaf discontinuity-time {
    type yang:date-and-time;
    description
      "The time on the most recent occasion at which any one
       or more of the statistic counters suffered a
       discontinuity. If no such discontinuities have occurred
       since the last re-initialization of the local
       management subsystem, then this node contains the time
       the local management subsystem re-initialized itself.";
  }
}

container error {
```

description "Statistics of errors.";

Liu & Guo, etc

Expires August 8, 2017

[Page 15]

```
    uses global-statistics-error;
  }

  container received {
    description "Statistics of received messages.";
    uses global-statistics-sent-received;
  }
  container sent {
    description "Statistics of sent messages.";
    uses global-statistics-sent-received;
  }
} // statistics
} // global-state-attributes

grouping global-statistics-error {
  description
    "A grouping defining statistics attributes for errors.";
  uses global-statistics-sent-received;
  leaf checksum {
    type yang:counter64;
    description
      "The number of checksum errors.";
  }
  leaf too-short {
    type yang:counter64;
    description
      "The number of messages that are too short.";
  }
} // global-statistics-error

grouping global-statistics-sent-received {
  description
    "A grouping defining statistics attributes.";
  leaf total {
    type yang:counter64;
    description
      "The number of total messages.";
  }
  leaf query {
    type yang:counter64;
    description
      "The number of query messages.";
  }
  leaf report {
    type yang:counter64;
    description
      "The number of report messages.";
  }
}
```

leaf leave {

Liu & Guo, etc

Expires August 8, 2017

[Page 16]

```
        type yang:counter64;
        description
            "The number of leave messages.";
    }
} // global-statistics-sent-received

grouping interfaces-config-attributes {
    description
        "Configuration attributes applied to interfaces whose
        per interface attributes are not existing.";

    leaf last-member-query-interval {
        type uint16 {
            range "1..65535";
        }
        description
            "Last Member Query Interval, which may be tuned to modify the
            leave latency of the network.";
        reference "RFC3376. Sec. 8.8.";
    }
    leaf max-groups-per-interface {
        if-feature intf-max-groups;
        type uint32;
        description
            "The maximum number of groups that IGMP can join.";
    }
    leaf query-interval {
        type uint16;
        units seconds;
        default 125;
        description
            "The Query Interval is the interval between General Queries
            sent by the Querier.";
        reference "RFC3376. Sec. 4.1.7, 8.2, 8.14.2.";
    }
    leaf query-max-response-time {
        type uint16;
        units seconds;
        description
            "Query maximum response time specifies the maximum time
            allowed before sending a responding report.";
        reference "RFC3376. Sec. 4.1.1, 8.3, 8.14.3.";
    }
    leaf require-router-alert {
        if-feature intf-require-router-alert;
        type boolean;
        description
            "";
```

}

Liu & Guo, etc

Expires August 8, 2017

[Page 17]

```
leaf robustness-variable {
  type uint8 {
    range "2..7";
  }
  default 2;
  description
    "Querier's Robustness Variable allows tuning for the expected
    packet loss on a network.";
  reference "RFC3376. Sec. 4.1.6, 8.1, 8.14.1.";
}
leaf version {
  type uint8 {
    range "1..3";
  }
  description "IGMP version.";
  reference "RFC1112, RFC2236, RFC3376.";
}
} // interfaces-config-attributes

grouping interface-config-attributes-igmp {
  description "Per interface igmp configuration for IGMP.";

  uses interface-config-attributes-igmp-mld;

  leaf-list join-group {
    if-feature intf-join-group;
    type inet:ipv4-address;
    description
      "The router joins this multicast group on the interface.";
  }

  list ssm-map {
    if-feature intf-ssm-map;
    key "source-addr group-policy";
    description "";
    leaf source-addr {
      type ssm-map-ipv4-addr-type;
      description
        "Multicast source IP address.";
    }
    leaf group-policy {
      type string;
      description
        "Name of the access policy used to filter IGMP
        membership.";
    }
  }
}
```

```
list static-group {
```

Liu & Guo, etc

Expires August 8, 2017

[Page 18]

```
    if-feature intf-static-group;
    key "group source-addr";
    description
        "A static multicast route, (*,G) or (S,G).";

    leaf group {
        type inet:ipv4-address;
        description
            "Multicast group IP address.";
    }
    leaf source-addr {
        type source-ipv4-addr-type;
        description
            "Multicast source IP address.";
    }
}
} // interface-config-attributes-igmp

grouping interface-config-attributes-igmp-mld {
    description
        "Per interface configuration for both IGMP and MLD.";

    leaf enable {
        if-feature intf-admin-enable;
        type boolean;
        description
            "true to enable IGMP on the interface;
             false to disable IGMP on the interface.";
    }
    leaf group-policy {
        type string;
        description
            "Name of the access policy used to filter IGMP membership.";
    }
    leaf immediate-leave {
        if-feature intf-immediate-leave;
        type empty;
        description
            "If present, IGMP perform an immediate leave upon receiving an
             IGMP Version 2 (IGMPv2) leave message.
             If the router is IGMP-enabled, it sends an IGMP last member
             query with a last member query response time. However, the
             router does not wait for the response time before it prunes
             off the group.";
    }
    leaf last-member-query-interval {
        type uint16 {
            range "1..65535";
```

}

Liu & Guo, etc

Expires August 8, 2017

[Page 19]

```
    description
      "Last Member Query Interval, which may be tuned to modify the
        leave latency of the network.";
    reference "RFC3376. Sec. 8.8.";
  }
  leaf max-groups {
    if-feature intf-max-groups;
    type uint32;
    description
      "The maximum number of groups that IGMP can join.";
  }
  leaf max-group-sources {
    if-feature intf-max-group-sources;
    type uint32;
    description
      "The maximum number of group sources.";
  }
  leaf query-interval {
    type uint16;
    units seconds;
    default 125;
    description
      "The Query Interval is the interval between General Queries
        sent by the Querier.";
    reference "RFC3376. Sec. 4.1.7, 8.2, 8.14.2.";
  }
  leaf query-max-response-time {
    type uint16;
    units seconds;
    description
      "Query maximum response time specifies the maximum time
        allowed before sending a responding report.";
    reference "RFC3376. Sec. 4.1.1, 8.3, 8.14.3.";
  }
  leaf require-router-alert {
    if-feature intf-require-router-alert;
    type boolean;
    description
      "";
  }
  leaf robustness-variable {
    type uint8 {
      range "2..7";
    }
    default 2;
    description
      "Querier's Robustness Variable allows tuning for the expected
        packet loss on a network.";
```

reference "[RFC3376](#). Sec. 4.1.6, 8.1, 8.14.1.";

```
    }
    leaf source-policy {
      if-feature intf-source-policy;
      type string;
      description
        "Name of the access policy used to filter sources.";
    }
    leaf verify-source-subnet {
      if-feature intf-verify-source-subnet;
      type empty;
      description
        "If present, the interface accepts packets with matching
        source IP subnet only.";
    }
    leaf version {
      type uint8 {
        range "1..3";
      }
      description "IGMP version.";
      reference "RFC1112, RFC2236, RFC3376";
    }
  } // interface-config-attributes-igmp-mld

grouping interface-config-attributes-mld {
  description "Per interface igmp configuration for mld.";

  uses interface-config-attributes-igmp-mld;

  leaf-list join-group {
    if-feature intf-join-group;
    type inet:ipv6-address;
    description
      "The router joins this multicast group on the interface.";
  }

  list ssm-map {
    if-feature intf-ssm-map;
    key "source-addr group-policy";
    description "";
    leaf source-addr {
      type ssm-map-ipv6-addr-type;
      description
        "Multicast source IP address.";
    }
  }
  leaf group-policy {
    type string;
    description
      "Name of the access policy used to filter IGMP
```

membership.";

Liu & Guo, etc

Expires August 8, 2017

[Page 21]

```
    }
  }

  list static-group {
    if-feature intf-static-group;
    key "group source-addr";
    description
      "A static multicast route, (*,G) or (S,G).";

    leaf group {
      type inet:ipv6-address;
      description
        "Multicast group IP address.";
    }
    leaf source-addr {
      type source-ipv6-addr-type;
      description
        "Multicast source IP address.";
    }
  }
} // interface-config-attributes-ml

grouping interface-state-attributes-igmp {
  description
    "Per interface state attributes for IGMP.";

  uses interface-state-attributes-igmp-mld;

  leaf dr {
    type inet:ipv4-address;
    description "";
  }
  leaf querier {
    type inet:ipv4-address;
    description "";
  }
  leaf-list joined-group {
    if-feature intf-join-group;
    type inet:ipv4-address;
    description
      "The routers that joined this multicast group.";
  }

  list group {
    key "address";
    description "";

    leaf address {
```

```
type inet:ipv4-address;
```

```
        description
            "";
    }
    uses interface-state-group-attributes-igmp-mld;
    leaf-list host {
        type inet:ipv4-address;
        description
            "";
    }
    leaf last-reporter {
        type inet:ipv4-address;
        description "";
    }
    list source {
        key "address";
        description "";

        leaf address {
            type inet:ipv4-address;
            description "";
        }
        uses interface-state-source-attributes-igmp-mld;
        leaf last-reporter {
            type inet:ipv4-address;
            description "";
        }
    } // list source
} // list group
} // interface-state-attributes-igmp

grouping interface-state-attributes-igmp-mld {
    description
        "Per interface state attributes for both IGMP and MLD.";

    leaf oper-status {
        type enumeration {
            enum up {
                description
                    "Ready to pass packets.";
            }
            enum down {
                description
                    "The interface does not pass any packets.";
            }
        }
        description "";
    }
} // interface-config-attributes-igmp-mld
```



```
grouping interface-state-attributes-mld {
  description
    "Per interface state attributes for MLD.";

  uses interface-state-attributes-igmp-mld;

  leaf querier {
    type inet:ipv6-address;
    description "";
  }
  leaf-list joined-group {
    if-feature intf-join-group;
    type inet:ipv6-address;
    description
      "The routers that joined this multicast group.";
  }

  list group {
    key "address";
    description "";

    leaf address {
      type inet:ipv6-address;
      description
        "";
    }
    uses interface-state-group-attributes-igmp-mld;
    leaf-list host {
      type inet:ipv6-address;
      description
        "";
    }
    leaf last-reporter {
      type inet:ipv6-address;
      description "";
    }
  }
  list source {
    key "address";
    description "";

    leaf address {
      type inet:ipv6-address;
      description "";
    }
  }
  uses interface-state-source-attributes-igmp-mld;
  leaf last-reporter {
    type inet:ipv6-address;
    description "";
  }
}
```

}

Liu & Guo, etc

Expires August 8, 2017

[Page 24]

```
    } // list source
  } // list group
} // interface-state-attributes-mld

grouping interface-state-group-attributes-igmp-mld {
  description
    "Per interface state attributes for both IGMP and MLD
    groups.";

  leaf expire {
    type uint32;
    units seconds;
    description "";
  }
  leaf filter-mode {
    type enumeration {
      enum "include" {
        description
          "";
      }
      enum "exclude" {
        description
          "";
      }
    }
    description "";
  }
  leaf host-count {
    type uint32;
    description "";
  }
  leaf up-time {
    type uint32;
    units seconds;
    description "";
  }
} // interface-state-group-attributes-igmp-mld

grouping interface-state-source-attributes-igmp-mld {
  description
    "Per interface state attributes for both IGMP and MLD
    groups.";

  leaf expire {
    type uint32;
    units seconds;
    description "";
  }
}
```

leaf up-time {

Liu & Guo, etc

Expires August 8, 2017

[Page 25]

```
        type uint32;
        units seconds;
        description "";
    }
} // interface-state-source-attributes-igmp-mld

/*
 * Configuration data nodes
 */
augment "/rt:routing/rt:control-plane-protocols"
{
    description
        "IGMP and MLD augmentation to routing instance configuration.";

    container igmp {
        description
            "IGMP configuration data.";

        container global {
            description
                "Global attributes.";
            uses global-config-attributes;
        }

        container interfaces {
            description
                "Containing a list of interfaces.";

            uses interfaces-config-attributes {
                if-feature global-interface-config;
            }

            list interface {
                key "interface";
                description
                    "List of IGMP interfaces.";
                leaf interface {
                    type if:interface-ref;
                    must "/if:interfaces/if:interface[if:name = current()]/"
                        + "ip:ipv4" {
                        description
                            "The interface must have IPv4 enabled.";
                    }
                }
                description
                    "Reference to an entry in the global interface
                    list.";
            }
            uses interface-config-attributes-igmp {
```

if-feature per-interface-config;

Liu & Guo, etc

Expires August 8, 2017

[Page 26]

```
    }
  } // interface
} // interfaces
} // igmp

container mld {
  description
    "MLD configuration data.";

  container global {
    description
      "Global attributes.";
    uses global-config-attributes;
  }

  container interfaces {
    description
      "Containing a list of interfaces.";

    uses interfaces-config-attributes {
      if-feature global-interface-config;
    }

    list interface {
      key "interface";
      description
        "List of MLD interfaces.";
      leaf interface {
        type if:interface-ref;
        must "/if:interfaces/if:interface[if:name = current()]/"
          + "ip:ipv6" {
          description
            "The interface must have IPv4 enabled.";
        }
        description
          "Reference to an entry in the global interface
            list.";
      }
      uses interface-config-attributes-mld {
        if-feature per-interface-config;
      }
    } // interface
  } // interfaces
} // mld
} // augment

/*
 * Operational state data nodes
```

* /

Liu & Guo, etc

Expires August 8, 2017

[Page 27]

```
augment "/rt:routing-state/rt:control-plane-protocols"
{
  description
    "IGMP and MLD augmentation to routing instance state.";

  container igmp {
    description
      "IGMP configuration data.";

    container global {
      description
        "Global attributes.";
      uses global-config-attributes;
      uses global-state-attributes;
    }

    container interfaces {
      description
        "Containing a list of interfaces.";

      uses interfaces-config-attributes {
        if-feature global-interface-config;
      }

      list interface {
        key "interface";
        description
          "List of IGMP interfaces.";
        leaf interface {
          type if:interface-ref;
          must "/if:interfaces/if:interface[if:name = current()]/"
            + "ip:ipv4" {
            description
              "The interface must have IPv4 enabled.";
          }
          description
            "Reference to an entry in the global interface
            list.";
        }
        uses interface-config-attributes-igmp {
          if-feature per-interface-config;
        }
        uses interface-state-attributes-igmp;
      } // interface
    } // interfaces
  } // igmp

  container mld {
```

description

Liu & Guo, etc

Expires August 8, 2017

[Page 28]

```
    "MLD configuration data.";

    container global {
        description
            "Global attributes.";
        uses global-config-attributes;
        uses global-state-attributes;
    }

    container interfaces {
        description
            "Containing a list of interfaces.";

        uses interfaces-config-attributes {
            if-feature global-interface-config;
        }

        list interface {
            key "interface";
            description
                "List of MLD interfaces.";
            leaf interface {
                type if:interface-ref;
                must "/if:interfaces/if:interface[if:name = current()]/"
                    + "ip:ipv6" {
                    description
                        "The interface must have IPv4 enabled.";
                }
            }
            description
                "Reference to an entry in the global interface
                list.";
        }
        uses interface-config-attributes-mld {
            if-feature per-interface-config;
        }
        uses interface-state-attributes-mld;
    } // interface
} // interfaces
} // mld
} // augment

/*
 * RPCs
 */
rpc clear-igmp-groups {
    if-feature rpc-clear-groups;
    description
        "Clears the specified IGMP cache tables.";
}
```



```
input {
  leaf interface {
    type leafref {
      path "/rt:routing/rt:control-plane-protocols/"
        + "igmp/interfaces/interface/"
        + "interface";
    }
    description
      "Name of the IGMP interface.
      If it is not specified, groups from all interfaces are
      cleared.";
  }
  leaf group {
    type inet:ipv4-address;
    description
      "Multicast group IPv4 address.
      If it is not specified, all IGMP group tables are
      cleared.";
  }
  leaf source {
    type inet:ipv4-address;
    description
      "Multicast source IPv4 address.
      If it is not specified, all IGMP source-group tables are
      cleared.";
  }
}
} // rpc clear-igmp-groups

rpc clear-mld-groups {
  if-feature rpc-clear-groups;
  description
    "Clears the specified MLD cache tables.";

  input {
    leaf interface {
      type leafref {
        path "/rt:routing/rt:control-plane-protocols/"
          + "mld/interfaces/interface/"
          + "interface";
      }
      description
        "Name of the MLD interface.
        If it is not specified, groups from all interfaces are
        cleared.";
    }
    leaf group {
      type inet:ipv6-address;
```

description

Liu & Guo, etc

Expires August 8, 2017

[Page 30]

```

        "Multicast group IPv6 address.
        If it is not specified, all MLD group tables are
        cleared.";
    }
    leaf source {
        type inet:ipv6-address;
        description
            "Multicast source IPv6 address.
            If it is not specified, all MLD source-group tables are
            cleared.";
    }
}
} // rpc clear-mld-groups

/*
 * Notifications
 */
}
<CODE ENDS>

```

5. Security Considerations

The data model defined does not introduce any security implications. This draft does not change any underlying security issues inherent in [\[RFC8022\]](#).

6. IANA Considerations

RFC Ed.: In this section, replace all occurrences of 'XXXX' with the actual RFC number (and remove this note).

This document registers the following namespace URIs in the IETF XML registry [\[RFC3688\]](#):

```

-----
URI: urn:ietf:params:xml:ns:yang:ietf-igmp-mld
Registrant Contact: The IESG.
XML: N/A, the requested URI is an XML namespace.
-----

```

This document registers the following YANG modules in the YANG Module Names registry [\[RFC7950\]](#):

```

-----
name:          ietf-igmp-mld
namespace:     urn:ietf:params:xml:ns:yang:ietf-igmp-mld
prefix:        igmp-mld
reference:     RFC XXXX
-----

```


7. References

7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), DOI 10.17487/RFC3688, January 2004.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), October 2010.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), June 2011.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016.
- [RFC8022] Lhotka, L. and A. Lindem, "A YANG Data Model for Routing Management", [RFC 8022](#), DOI 10.17487/RFC8022, November 2016.
- [I-D.ietf-netmod-rfc6087bis] Bierman, A., "Guidelines for Authors and Reviewers of YANG Data Model Documents", [draft-ietf-netmod-rfc6087bis-10](#) (work in progress), January 2017.

7.2. Informative References

- [RFC1112] Deering, S., "Host extensions for IP multicasting", STD 5, [RFC 1112](#), August 1989.
- [RFC2236] Fenner, W., "Internet Group Management Protocol, Version 2", [RFC 2236](#), November 1997.
- [RFC2710] Deering, S., Fenner, W., and B. Haberman, "Multicast Listener Discovery (MLD) for IPv6", [RFC 2710](#), October 1999.
- [RFC3376] Cain, B., Deering, S., Kouvelas, I., Fenner, B., and A. Thyagarajan, "Internet Group Management Protocol, Version 3", [RFC 3376](#), October 2002.
- [RFC3810] Vida, R. and L. Costa, "Multicast Listener Discovery Version 2 (MLDv2) for IPv6", [RFC 3810](#), June 2004.

[RFC4604] Holbrook, H., Cain, B., and B. Haberman, "Using Internet Group Management Protocol Version 3 (IGMPv3) and Multicast Listener Discovery Protocol Version 2 (MLDv2) for Source-Specific Multicast", [RFC 4604](#), August 2006.

[RFC4607] Holbrook, H. and B. Cain, "Source-Specific Multicast for IP", [RFC 4607](#), August 2006.

8. Acknowledgments

The authors would like to thank Steve Baillargeon, Hu Fangwei, Robert Kebler, Tanmoy Kundu, Liu Yisong, and Stig Venaas for their valuable contributions.

Authors' Addresses

Xufeng Liu
Ericsson
1595 Spring Hill Road, Suite 500
Vienna VA 22182
USA

EMail: xufeng.liu@ericsson.com

Feng Guo
Huawei
Huawei Bld., No.156 Beiqing Rd.
Beijing 100095
China

Email: guofeng@huawei.com

Mahesh Sivakumar
Cisco Systems, Inc.
510 McCarthy Blvd
Milpitas, California 95035
United States

Email: masivaku@cisco.com

Pete McAllister
Metaswitch Networks
100 Church Street
Enfield EN2 6BQ
UK

E-Mail: pete.mcallister@metaswitch.com

Anish Peter
Juniper Networks
Electra, Exora Business Park
Bangalore, KA 560103
India

E-Mail: anishp@juniper.net