

PIM Working Group
Internet-Draft
Intended Status: Standard Track
Expires: March 19, 2018

X. Liu
Jabil
F. Guo
Huawei
M. Sivakumar
Cisco
P. McAllister
Metaswitch Networks
A. Peter
Juniper Networks
Sep 19, 2017

**A YANG data model for Internet Group Management Protocol (IGMP) and
Multicast Listener Discovery (MLD)
draft-ietf-pim-igmp-mld-yang-05**

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>

This Internet-Draft will expire on March 20, 2017.

Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents

carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Simplified BSD License.

Abstract

This document defines a YANG data model that can be used to configure and manage Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) devices.

Table of Contents

1.	Introduction	2
1.1.	Requirements Language.....	3
1.2.	Terminology	3
2.	Design of Data model.....	3
2.1.	Scope of model	3
2.2.	Optional capabilities.....	3
2.3.	Position of address family in hierarchy.....	4
3.	Module Structure	4
3.1.	IGMP Configuration and Operational state.....	4
3.2.	MLD Configuration and Operational State.....	6
3.3.	IGMP and MLD RPC.....	8
4.	IGMP and MLD YANG Modules.....	8
5.	Security Considerations.....	30
6.	IANA Considerations	30
7.	References	31
7.1.	Normative References.....	31
7.2.	Informative References.....	32
8.	Acknowledgments	32

[1. Introduction](#)

YANG [[RFC6020](#)] [[RFC7950](#)] is a data definition language that was introduced to model the configuration and running state of a device managed using NETCONF [[RFC6241](#)]. YANG is now also being used as a component of wider management interfaces, such as CLIs.

This document defines a YANG data model that can be used to configure and manage Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) devices. This model will support the core IGMP and MLD protocols, as well as many other features mentioned in separate IGMP and MLD RFCs. Non-core features are defined as optional in the provided data model.

1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC-2119](#) [[RFC2119](#)].

1.2. Terminology

The terminology for describing YANG data models is found in [[RFC6020](#)] [[RFC7950](#)].

This document employs YANG tree diagrams, which are explained in [I-D.ietf-netmod-rfc6087bis].

2. Design of Data model

2.1. Scope of model

The model covers IGMPv1 [[RFC1112](#)], IGMPv2 [[RFC2236](#)], IGMPv3 [[RFC3376](#)] and MLDv1 [[RFC2710](#)], MLDv2 [[RFC3810](#)].

The configuration of IGMP and MLD features, and the operational state fields and RPC definitions are not all included in this document of the data model. This model can be extended, though the structure of what has been written may be taken as representative of the structure of the whole model.

This model does not cover other IGMP and MLD related protocols such as IGMP/MLD Proxy [[RFC4605](#)] or IGMP/MLD Snooping [[RFC4541](#)] etc., these will be specified in separate documents.

2.2. Optional capabilities

This model is designed to represent the capabilities of IGMP and MLD devices with various specifications, including some with basic subsets of the IGMP and MLD protocols. The main design goals of this document are that any major now-existing implementation may be said to support the basic model, and that the configuration of all implementations meeting the specification is easy to express through some combination of the features in the basic model and simple vendor augmentations.

There is also value in widely-supported features being standardized, to save work for individual vendors, and so that mapping between different vendors' configuration is not needlessly complicated. Therefore these modules declare a number of features representing capabilities that not all deployed devices support.

The extensive use of feature declarations should also substantially simplify the capability negotiation process for a vendor's IGMP and MLD implementations.

On the other hand, operational state parameters are not so widely designated as features, as there are many cases where the defaulting of an operational state parameter would not cause any harm to the system, and it is much more likely that an implementation without native support for a piece of operational state would be able to derive a suitable value for a state variable that is not natively supported.

For the same reason, wide constant ranges (for example, timer maximum and minimum) will be used in the model. It is expected that vendors will augment the model with any specific restrictions that might be required. Vendors may also extend the features list with proprietary extensions.

2.3. Position of address family in hierarchy

The current document contains IGMP and MLD as separate schema branches in the structure. The reason for this is to make it easier for implementations which may optionally choose to support specific address families. And the names of objects may be different between the IPv4 (IGMP) and IPv6 (MLD) address families.

3. Module Structure

3.1. IGMP Configuration and Operational state

The IGMP YANG model follows the Guidelines for YANG Module Authors (NMDA) [[draft-dsdt-nmda-guidelines-01](#)]. The IGMP module defines the routing-control-plane-protocol-wide configuration and operational state options separately in a three-level hierarchy as listed below:

Global level: IGMP configuration and operational state attributes for the entire routing system.

Interface-global: Only including configuration data nodes now. IGMP configuration attributes are applicable to all the interfaces whose interface-level corresponding attributes are not existing, with same attributes' value for these interfaces.

Interface-level: IGMP configuration and operational state attributes specific to the given interface.

Where fields are not genuinely essential to protocol operation, they are marked as optional. Some fields will be essential but have a default specified, so that they need not be configured explicitly.

We define the IGMP model as a protocol-centric model , and the IGMP model augments "/rt:routing/rt:control-plane-protocols/ rt:control-plane-protocol" in [[draft-acee-netmod-rfc8022bis-01](#)] and would allow a single protocol instance per VRF.

```
augment /rt:routing/rt:control-plane-protocols/rt:control-plane-protocol:
```

```
  +--rw igmp
    +--rw global
      | +--rw enable?          boolean {global-admin-enable}?
      | +--rw max-entries?     uint32 {global-max-entries}?
      | +--rw max-groups?      uint32 {global-max-groups}?
      | +--ro entries-count?   uint32
      | +--ro groups-count?    uint32
      | +--ro statistics
      |   +--ro discontinuity-time? yang:date-and-time
      |   +--ro error
      |     | +--ro total?      yang:counter64
      |     | +--ro query?     yang:counter64
      |     | +--ro report?    yang:counter64
      |     | +--ro leave?     yang:counter64
      |     | +--ro checksum?  yang:counter64
      |     | +--ro too-short? yang:counter64
      |   +--ro received
      |     | +--ro total?     yang:counter64
      |     | +--ro query?    yang:counter64
      |     | +--ro report?   yang:counter64
      |     | +--ro leave?    yang:counter64
      |   +--ro sent
      |     +--ro total?      yang:counter64
      |     +--ro query?     yang:counter64
      |     +--ro report?    yang:counter64
      |     +--ro leave?     yang:counter64
    +--rw interfaces
      +--rw last-member-query-interval?  uint16
      +--rw max-groups-per-interface?    uint32 {intf-max-groups}?
      +--rw query-interval?              uint16
      +--rw query-max-response-time?     uint16
      +--rw require-router-alert?        boolean {intf-require-router-
alert}?
      +--rw robustness-variable?         uint8
      +--rw version?                     uint8
      +--rw interface* [interface-name]
        +--rw interface-name             if:interface-ref
        +--rw enable?                    boolean {intf-admin-
enable}?
        +--rw group-policy?              string
        +--rw immediate-leave?           empty {intf-immediate-
leave}?
```

	+++rw last-member-query-interval?	uint16
	+++rw max-groups?	uint32 {intf-max-groups}?
sources}?	+++rw max-group-sources?	uint32 {intf-max-group-
	+++rw query-interval?	uint16

```

router-alert}}?
    +--rw query-max-response-time?      uint16
    +--rw require-router-alert?         boolean {_intf-require-
policy}}?
    +--rw robustness-variable?          uint8
    +--rw source-policy?                 string {_intf-source-
subnet}}?
    +--rw verify-source-subnet?         empty {_intf-verify-source-
join-group}}?
    +--rw version?                      uint8
    +--rw join-group*                   inet:ipv4-address {_intf-
group}
    +--rw ssm-map* [source-addr group-policy] {_intf-ssm-map}}?
    |   +--rw source-addr               ssm-map-ipv4-addr-type
    |   +--rw group-policy              string
    +--rw static-group* [group-addr source-addr] {_intf-static-
group}
    |   +--rw group-addr                inet:ipv4-address
    |   +--rw source-addr               source-ipv4-addr-type
    +--ro oper-status?                  enumeration
    +--ro querier?                      inet:ipv4-address
    +--ro joined-group*                 inet:ipv4-address {_intf-
join-group}}?
    +--ro group* [address]
    |   +--ro address                   inet:ipv4-address
    |   +--ro expire?                   uint32
    |   +--ro filter-mode?              enumeration
    |   +--ro host-count?               uint32
    |   +--ro up-time?                  uint32
    |   +--ro host*                     inet:ipv4-address
    |   +--ro last-reporter?            inet:ipv4-address
    |   +--ro source* [address]
    |   |   +--ro address               inet:ipv4-address
    |   |   +--ro expire?               uint32
    |   |   +--ro up-time?              uint32
    |   |   +--ro last-reporter?        inet:ipv4-address

```

[3.2. MLD Configuration and Operational State](#)

The MLD YANG model uses the same structure as IGMP YANG model. The MLD module also defines the routing-control-plane-protocol-wide configuration and operational state options separately in a three-level hierarchy.

```

augment /rt:routing/rt:control-plane-protocols/rt:control-plane-protocol:
  +--rw mld
  |   +--rw global
  |   |   +--rw enable?                boolean {global-admin-enable}}?

```

```
|  +--rw max-entries?      uint32 {global-max-entries}?
|  +--rw max-groups?       uint32 {global-max-groups}?
|  +--ro entries-count?    uint32
|  +--ro groups-count?     uint32
|  +--ro statistics
|      +--ro discontinuity-time?  yang:date-and-time
|      +--ro error
```

```

|      | +--ro total?      yang:counter64
|      | +--ro query?      yang:counter64
|      | +--ro report?     yang:counter64
|      | +--ro leave?      yang:counter64
|      | +--ro checksum?   yang:counter64
|      | +--ro too-short?  yang:counter64
|      +--ro received
|      | +--ro total?      yang:counter64
|      | +--ro query?      yang:counter64
|      | +--ro report?     yang:counter64
|      | +--ro leave?      yang:counter64
|      +--ro sent
|          +--ro total?      yang:counter64
|          +--ro query?      yang:counter64
|          +--ro report?     yang:counter64
|          +--ro leave?      yang:counter64
+--rw interfaces
+--rw last-member-query-interval?  uint16
+--rw max-groups-per-interface?    uint32 {_intf-max-groups}?
+--rw query-interval?              uint16
+--rw query-max-response-time?     uint16
+--rw require-router-alert?        boolean {_intf-require-router-
alert}?
+--rw robustness-variable?         uint8
+--rw version?                     uint8
+--rw interface* [interface-name]
+--rw interface-name               if:interface-ref
+--rw enable?                       boolean {_intf-admin-
enable}?
+--rw group-policy?                string
+--rw immediate-leave?             empty {_intf-immediate-
leave}?
+--rw last-member-query-interval?  uint16
+--rw max-groups?                  uint32 {_intf-max-groups}?
+--rw max-group-sources?           uint32 {_intf-max-group-
sources}?
+--rw query-interval?              uint16
+--rw query-max-response-time?     uint16
+--rw require-router-alert?        boolean {_intf-require-
router-alert}?
+--rw robustness-variable?         uint8
+--rw source-policy?               string {_intf-source-
policy}?
+--rw verify-source-subnet?        empty {_intf-verify-source-
subnet}?
+--rw version?                     uint8
+--rw join-group*                  inet:ipv6-address {_intf-
join-group}?

```

```

+--rw ssm-map* [source-addr group-policy] {intf-ssm-map}?
| +--rw source-addr      ssm-map-ipv6-addr-type
| +--rw group-policy     string
+--rw static-group* [group source-addr] {intf-static-group}?
| +--rw group            inet:ipv6-address
| +--rw source-addr      source-ipv6-addr-type
+--ro oper-status?      enumeration
+--ro querier?          inet:ipv6-address
+--ro joined-group*     inet:ipv6-address {intf-
join-group}?

```

```
+--ro group* [address]
  +--ro address          inet:ipv6-address
  +--ro expire?          uint32
  +--ro filter-mode?     enumeration
  +--ro host-count?      uint32
  +--ro up-time?         uint32
  +--ro host*            inet:ipv6-address
  +--ro last-reporter?   inet:ipv6-address
  +--ro source* [address]
    +--ro address        inet:ipv6-address
    +--ro expire?        uint32
    +--ro up-time?       uint32
    +--ro last-reporter? inet:ipv6-address
```

3.3. IGMP and MLD RPC

IGMP and MLD RPC clears the specified IGMP and MLD group membership.

rpcs:

```
+---x clear-igmp-groups {rpc-clear-groups}?
|
|  +---w input
|
|    +---w interface?  string
|
|    +---w group?      inet:ipv4-address
|
|    +---w source?     inet:ipv4-address
+---x clear-mlld-groups {rpc-clear-groups}?
|
|  +---w input
|
|    +---w interface?  string
|
|    +---w group?      inet:ipv6-address
|
|    +---w source?     inet:ipv6-address
```

4. IGMP and MLD YANG Modules

```
<CODE BEGINS> file "ietf-igmp-mlld@2017-09-19.yang"
module ietf-igmp-mlld {
  namespace "urn:ietf:params:xml:ns:yang:ietf-igmp-mlld";
  // replace with IANA namespace when assigned
```



```
prefix igmp-mld;

import ietf-inet-types {
  prefix "inet";
}

import ietf-yang-types {
  prefix "yang";
}

import ietf-routing-2 {
  prefix "rt";
}

import ietf-interfaces {
  prefix "if";
}

import ietf-ip {
  prefix ip;
}

organization
  "IETF PIM Working Group";

contact
  "WG Web:  <http://tools.ietf.org/wg/pim/>
  WG List:  <mailto:pim@ietf.org>

  WG Chair: Stig Venaas
             <mailto:stig@venaas.com>

  WG Chair: Mike McBride
             <mailto:mmcbride7@gmail.com>

  Editor:   Xufeng Liu
             <mailto:Xufeng_Liu@jabil.com>

  Editor:   Feng Guo
             <mailto:guofeng@huawei.com>

  Editor:   Mahesh Sivakumar
             <mailto:masivaku@cisco.com>

  Editor:   Pete McAllister
             <mailto:pete.mcallister@metaswitch.com>

  Editor:   Anish Peter
             <mailto:anish.ietf@gmail.com>;
```



```
description
  "The module defines a collection of YANG definitions common for
  IGMP and MLD.";

revision 2017-09-19 {
  description
    "Updated yang data model for NMDA version and errata.";
  reference
    "RFC XXXX: A YANG Data Model for IGMP and MLD";
}

/*
 * Features
 */
feature global-admin-enable {
  description
    "Support global configuration to enable or disable protocol.";
}

feature global-interface-config {
  description
    "Support global configuration applied for all interfaces.";
}

feature global-max-entries {
  description
    "Support configuration of global max-entries.";
}

feature global-max-groups {
  description
    "Support configuration of global max-groups.";
}

feature intf-admin-enable {
  description
    "Support configuration of interface administrative enabling.";
}

feature intf-immediate-leave {
  description
    "Support configuration of interface immediate-leave.";
}

feature intf-join-group {
  description
    "Support configuration of interface join-group.";
}
```



```
feature intf-max-groups {
  description
    "Support configuration of interface max-groups.";
}

feature intf-max-group-sources {
  description
    "Support configuration of interface max-group-sources.";
}

feature intf-require-router-alert {
  description
    "Support configuration of interface require-router-alert.";
}

feature intf-source-policy {
  description
    "Support configuration of interface source policy.";
}

feature intf-ssm-map {
  description
    "Support configuration of interface ssm-map.";
}

feature intf-static-group {
  description
    "Support configuration of interface static-group.";
}

feature intf-verify-source-subnet {
  description
    "Support configuration of interface verify-source-subnet.";
}

feature per-interface-config {
  description
    "Support per interface configuration.";
}

feature rpc-clear-groups {
  description
    "Support rpc's to clear groups.";
}

/*
 * Typedefs
 */
```



```
typedef ssm-map-ipv4-addr-type {
  type union {
    type enumeration {
      enum 'policy' {
        description
          "Source address is specified in SSM map policy.";
      }
    }
    type inet:ipv4-address;
  }
  description
    "Multicast source IP address type for SSM map.";
} // source-ipv4-addr-type
```

```
typedef ssm-map-ipv6-addr-type {
  type union {
    type enumeration {
      enum 'policy' {
        description
          "Source address is specified in SSM map policy.";
      }
    }
    type inet:ipv6-address;
  }
  description
    "Multicast source IP address type for SSM map.";
} // source-ipv6-addr-type
```

```
typedef source-ipv4-addr-type {
  type union {
    type enumeration {
      enum '*' {
        description
          "Any source address.";
      }
    }
    type inet:ipv4-address;
  }
  description
    "Multicast source IP address type.";
} // source-ipv4-addr-type
```

```
typedef source-ipv6-addr-type {
  type union {
    type enumeration {
      enum '*' {
        description
          "Any source address.";
      }
    }
  }
}
```

}

Liu & Guo, etc

Expires March 19, 2018

[Page 12]

```
    }
    type inet:ipv6-address;
  }
  description
    "Multicast source IP address type.";
} // source-ipv6-addr-type

/*
 * Identities
 */

/*
 * Groupings
 */
grouping global-config-attributes {
  description "Global IGMP and MLD configuration.";

  leaf enable {
    if-feature global-admin-enable;
    type boolean;
    description
      "true to enable IGMP or MLD in the routing instance;
       false to disable IGMP or MLD in the routing instance.";
  }

  leaf max-entries {
    if-feature global-max-entries;
    type uint32;
    description
      "The maximum number of entries in IGMP or MLD.";
  }

  leaf max-groups {
    if-feature global-max-groups;
    type uint32;
    description
      "The maximum number of groups that IGMP
       or MLD can join.";
  }
} // global-config-attributes

grouping global-state-attributes {

  description "Global IGMP and MLD state attributes.";

  leaf entries-count {
    type uint32;
    config false;
    description
```

"The number of entries in IGMP or MLD.";

Liu & Guo, etc

Expires March 19, 2018

[Page 13]

```
}
leaf groups-count {
  type uint32;
  config false;
  description
    "The number of groups that IGMP or MLD can join.";
}

container statistics {
  config false;
  description "Global statistics.";

  leaf discontinuity-time {
    type yang:date-and-time;
    description
      "The time on the most recent occasion at which any one
      or more of the statistic counters suffered a
      discontinuity. If no such discontinuities have occurred
      since the last re-initialization of the local
      management subsystem, then this node contains the time
      the local management subsystem re-initialized itself.";
  }

  container error {
    description "Statistics of errors.";
    uses global-statistics-error;
  }

  container received {
    description "Statistics of received messages.";
    uses global-statistics-sent-received;
  }

  container sent {
    description "Statistics of sent messages.";
    uses global-statistics-sent-received;
  }
} // statistics
} // global-state-attributes

grouping global-statistics-error {
  description
    "A grouping defining statistics attributes for errors.";
  uses global-statistics-sent-received;
  leaf checksum {
    type yang:counter64;
    description
      "The number of checksum errors.";
  }
}
```

leaf too-short {

Liu & Guo, etc

Expires March 19, 2018

[Page 14]

```
        type yang:counter64;
        description
            "The number of messages that are too short.";
    }
} // global-statistics-error

grouping global-statistics-sent-received {
    description
        "A grouping defining statistics attributes.";
    leaf total {
        type yang:counter64;
        description
            "The number of total messages.";
    }
    leaf query {
        type yang:counter64;
        description
            "The number of query messages.";
    }
    leaf report {
        type yang:counter64;
        description
            "The number of report messages.";
    }
    leaf leave {
        type yang:counter64;
        description
            "The number of leave messages.";
    }
} // global-statistics-sent-received

grouping interfaces-config-attributes {
    description
        "Configuration attributes applied to the interfaces whose
        per interface attributes are not existing.";

    leaf last-member-query-interval {
        type uint16 {
            range "1..65535";
        }
        units seconds;
        default 1;
        description
            "Last Member Query Interval, which may be tuned to modify the
            leave latency of the network.";
        reference "RFC3376. Sec. 8.8.";
    }
}
```

leaf max-groups-per-interface {

Liu & Guo, etc

Expires March 19, 2018

[Page 15]

```
    if-feature intf-max-groups;
    type uint32;
    description
        "The maximum number of groups that IGMP or MLD can join.";
}

leaf query-interval {
    type uint16 {
        range "1..31744";
    }
    units seconds;
    default 125;
    description
        "The Query Interval is the interval between General Queries
        sent by the Querier.";
    reference "RFC3376. Sec. 4.1.7, 8.2, 8.14.2.";
}

leaf query-max-response-time {
    type uint16 {
        range "1..65535";
    }
    units seconds;
    default 10;
    description
        "Query maximum response time specifies the maximum time
        allowed before sending a responding report.";
    reference "RFC3376. Sec. 4.1.1, 8.3, 8.14.3.";
}

leaf require-router-alert {
    if-feature intf-require-router-alert;
    type boolean;
    default false;
    description
        "Protocol packets should contain router alert IP option.";
}

leaf robustness-variable {
    type uint8 {
        range "2..7";
    }
    default 2;
    description
        "Querier's Robustness Variable allows tuning for the expected
        packet loss on a network.";
    reference "RFC3376. Sec. 4.1.6, 8.1, 8.14.1.";
}
```



```
} // interfaces-config-attributes

grouping interfaces-config-attributes-igmp {
  description "interfaces configuration for IGMP.";

  uses interfaces-config-attributes;
  leaf version {
    type uint8 {
      range "1..3";
    }
    description "IGMP version.";
    reference "RFC1112, RFC2236, RFC3376.";
  }
}

grouping interfaces-config-attributes-mld {
  description "interfaces configuration for MLD.";

  uses interfaces-config-attributes;
  leaf version {
    type uint8 {
      range "1..2";
    }
    description "MLD version.";
    reference "RFC2710, RFC3810.";
  }
}

grouping interface-config-attributes-igmp {
  description "Per interface configuration for IGMP.";

  uses interface-config-attributes-igmp-mld;

  leaf version {
    type uint8 {
      range "1..3";
    }
    description "IGMP version.";
    reference "RFC1112, RFC2236, RFC3376.";
  }
  leaf-list join-group {
    if-feature intf-join-group;
    type inet:ipv4-address;
    description
      "The router joins this multicast group on the interface.";
  }

  list ssm-map {
```



```
    if-feature intf-ssm-map;
    key "source-addr group-policy";
    description "The policy for (*,G) mapping to (S,G).";
    leaf source-addr {
        type ssm-map-ipv4-addr-type;
        description
            "Multicast source IP address.";
    }
    leaf group-policy {
        type string;
        description
            "Name of the access policy used to filter IGMP
            membership. A device can restrict the length
            and value of this name, possibly space and special
            characters are not allowed. ";
    }
}

list static-group {
    if-feature intf-static-group;
    key "group-addr source-addr";
    description
        "A static multicast route, (*,G) or (S,G).";

    leaf group-addr {
        type inet:ipv4-address;
        description
            "Multicast group IP address.";
    }
    leaf source-addr {
        type source-ipv4-addr-type;
        description
            "Multicast source IP address.";
    }
}
} // interface-config-attributes-igmp

grouping interface-config-attributes-igmp-mlld {
    description
        "Per interface configuration for both IGMP and MLD.";

    leaf enable {
        if-feature intf-admin-enable;
        type boolean;
        default false;
        description
            "true to enable IGMP or MLD on the interface;
            false to disable IGMP or MLD on the interface.";
```

}

Liu & Guo, etc

Expires March 19, 2018

[Page 18]

```
leaf group-policy {
  type string;
  description
    "Name of the access policy used to filter IGMP or MLD
    membership.A device can restrict the length
    and value of this name, possibly space and special
    characters are not allowed.";
}
leaf immediate-leave {
  if-feature intf-immediate-leave;
  type empty;
  description
    "If present, IGMP or MLD perform an immediate leave upon
    receiving an IGMPv2 or MLDv1 leave message.
    If the router is IGMP-enabled or MLD-enabled, it sends an
    IGMP or MLD last member query with a last member query
    response time. However, the router does not wait for
    the response time before it prunes off the group.";
}

leaf last-member-query-interval {
  type uint16 {
    range "1..65535";
  }
  units seconds;
  default 1;
  description
    "Last Member Query Interval, which may be tuned to modify the
    leave latency of the network.";
  reference "RFC3376. Sec. 8.8.";
}

leaf max-groups {
  if-feature intf-max-groups;
  type uint32;
  description
    "The maximum number of groups that IGMP ro MLD can join.";
}
leaf max-group-sources {
  if-feature intf-max-group-sources;
  type uint32;
  description
    "The maximum number of group sources.";
}

leaf query-interval {
  type uint16 {
    range "1..31744";
```

}

Liu & Guo, etc

Expires March 19, 2018

[Page 19]

```
    units seconds;
    default 125;
    description
        "The Query Interval is the interval between General Queries
        sent by the Querier.";
    reference "RFC3376. Sec. 4.1.7, 8.2, 8.14.2.";
}

leaf query-max-response-time {
    type uint16 {
        range "1..65535";
    }
    units seconds;
    default 10;
    description
        "Query maximum response time specifies the maximum time
        allowed before sending a responding report.";
    reference "RFC3376. Sec. 4.1.1, 8.3, 8.14.3.";
}

leaf require-router-alert {
    if-feature intf-require-router-alert;
    type boolean;
    description
        "Protocol packets should contain router alert IP option.";
}

leaf robustness-variable {
    type uint8 {
        range "2..7";
    }
    default 2;
    description
        "Querier's Robustness Variable allows tuning for the expected
        packet loss on a network.";
    reference "RFC3376. Sec. 4.1.6, 8.1, 8.14.1.";
}

leaf source-policy {
    if-feature intf-source-policy;
    type string;
    description
        "Name of the access policy used to filter sources.
        A device can restrict the length
        and value of this name, possibly space and special
        characters are not allowed.";
}

leaf verify-source-subnet {
```

```
if-feature intf-verify-source-subnet;
```

Liu & Guo, etc

Expires March 19, 2018

[Page 20]

```
    type empty;
    description
      "If present, the interface accepts packets with matching
       source IP subnet only.";
  }

} // interface-config-attributes-igmp-mld

grouping interface-config-attributes-mld {
  description "Per interface configuration for MLD.";

  uses interface-config-attributes-igmp-mld;

  leaf version {
    type uint8 {
      range "1..2";
    }
    description "MLD version.";
    reference "RFC2710, RFC3810.";
  }
  leaf-list join-group {
    if-feature intf-join-group;
    type inet:ipv6-address;
    description
      "The router joins this multicast group on the interface.";
  }

  list ssm-map {
    if-feature intf-ssm-map;
    key "source-addr group-policy";
    description "The policy for (*,G) mapping to (S,G).";
    leaf source-addr {
      type ssm-map-ipv6-addr-type;
      description
        "Multicast source IPv6 address.";
    }
    leaf group-policy {
      type string;
      description
        "Name of the access policy used to filter MLD
         membership. A device can restrict the length
         and value of this name, possibly space and special
         characters are not allowed.";
    }
  }
}

list static-group {
  if-feature intf-static-group;
```

```
key "group source-addr";
```

Liu & Guo, etc

Expires March 19, 2018

[Page 21]

```
    description
      "A static multicast route, (*,G) or (S,G).";

    leaf group {
      type inet:ipv6-address;
      description
        "Multicast group IPv6 address.";
    }
    leaf source-addr {
      type source-ipv6-addr-type;
      description
        "Multicast source IPv6 address.";
    }
  }
} // interface-config-attributes-mlt

grouping interface-state-attributes-igmp {

  description
    "Per interface state attributes for IGMP.";

  uses interface-state-attributes-igmp-mlt;

  leaf querier {
    type inet:ipv4-address;
    config false;
    description "The querier address in the subnet";
  }
  leaf-list joined-group {
    if-feature intf-join-group;
    type inet:ipv4-address;
    config false;
    description
      "The routers that joined this multicast group.";
  }

  list group {
    key "address";
    config false;
    description
      "Multicast group membership information
      that joined on the interface.";

    leaf address {
      type inet:ipv4-address;
      description
        "Multicast group address.";
    }
  }
}
```

uses interface-state-group-attributes-igmp-mld;

```
leaf-list host {
  type inet:ipv4-address;
  description
    "List of host addresses that
    joined the multicast group";
}
leaf last-reporter {
  type inet:ipv4-address;
  description
    "The last host address which has sent the
    report to join the multicast group.";
}
list source {
  key "address";
  description
    "List of multicast source information
    of the multicast group.";

  leaf address {
    type inet:ipv4-address;
    description
      "Multicast source address";
  }
  uses interface-state-source-attributes-igmp-mld;
  leaf last-reporter {
    type inet:ipv4-address;
    description
      "The last host address which has sent the
      report to join the multicast source and group.";
  }
} // list source
} // list group
} // interface-state-attributes-igmp

grouping interface-state-attributes-igmp-mld {
  description
    "Per interface state attributes for both IGMP and MLD.";

  leaf oper-status {
    type enumeration {
      enum up {
        description
          "Ready to pass packets.";
      }
      enum down {
        description
          "The interface does not pass any packets.";
      }
    }
  }
}
```

}

Liu & Guo, etc

Expires March 19, 2018

[Page 23]

```
        config false;
        description
            "interface up or down state for IGMP or MLD protocol";
    }
} // interface-config-attributes-igmp-mld

grouping interface-state-attributes-mld {

    description
        "Per interface state attributes for MLD.";

    uses interface-state-attributes-igmp-mld;

    leaf querier {
        type inet:ipv6-address;
        config false;
        description
            "The querier address in the subnet.";
    }
    leaf-list joined-group {
        if-feature intf-join-group;
        type inet:ipv6-address;
        config false;
        description
            "The routers that joined this multicast group.";
    }
}

list group {
    key "address";
    config false;
    description
        "Multicast group membership information
        that joined on the interface.";

    leaf address {
        type inet:ipv6-address;
        description
            "Multicast group address.";
    }
    uses interface-state-group-attributes-igmp-mld;
    leaf-list host {
        type inet:ipv6-address;
        description
            "List of host addresses that
            joined the multicast group";
    }
    leaf last-reporter {
        type inet:ipv6-address;
```

description

Liu & Guo, etc

Expires March 19, 2018

[Page 24]

```
        "The last host address which has sent the
        report to join the multicast group.";
    }
    list source {
        key "address";
        description
            "List of multicast source information
            of the multicast group.";

        leaf address {
            type inet:ipv6-address;
            description
                "Multicast source address";
        }
        uses interface-state-source-attributes-igmp-mld;
        leaf last-reporter {
            type inet:ipv6-address;
            description
                "The last host address which has sent the
                report to join the multicast source and group.";
        }
    } // list source
} // list group
} // interface-state-attributes-mld

grouping interface-state-group-attributes-igmp-mld {
    description
        "Per interface state attributes for both IGMP and MLD
        groups.";

    leaf expire {
        type uint32;
        units seconds;
        description
            "The time left before multicast group state expires.";
    }
    leaf filter-mode {
        type enumeration {
            enum "include" {
                description
                    "In include mode, reception of packets sent
                    to the specified multicast address is requested
                    only from those IP source addresses listed in the
                    source-list parameter";
            }
            enum "exclude" {
                description
                    "In exclude mode, reception of packets sent
```

to the given multicast address is requested

```
        from all IP source addresses except those
        listed in the source-list parameter.";
    }
}
description
    "Filter mode for a multicast group,
    may be either include or exclude.";
}
leaf host-count {
    type uint32;
    description
        "The number of host addresses.";
}
leaf up-time {
    type uint32;
    units seconds;
    description
        "The elapsed time since the device created multicast group
record.";
}
} // interface-state-group-attributes-igmp-mld

grouping interface-state-source-attributes-igmp-mld {
    description
        "Per interface state attributes for both IGMP and MLD
        source-group records.";

    leaf expire {
        type uint32;
        units seconds;
        description
            "The time left before multicast source-group state expires.";
    }
    leaf up-time {
        type uint32;
        units seconds;
        description
            "The elapsed time since the device created multicast
            source-group record.";
    }
} // interface-state-source-attributes-igmp-mld

/*
 * Configuration and Operational state data nodes (NMDA version)
 */
augment "/rt:routing/rt:control-plane-protocols/rt:control-plane-
protocol"
{
```

description

"IGMP augmentation to routing control plane protocol
configuration and state.";

Liu & Guo, etc

Expires March 19, 2018

[Page 26]

```
container igmp {
  description
    "IGMP operational state data.";

  container global {
    description
      "Global attributes.";
    uses global-config-attributes;
    uses global-state-attributes;
  }

  container interfaces {
    description
      "Containing a list of interfaces.";

    uses interfaces-config-attributes-igmp {
      if-feature global-interface-config;
    }

    list interface {
      key "interface-name";
      description
        "List of IGMP interfaces.";
      leaf interface-name {
        type if:interface-ref;
        must "/if:interfaces/if:interface[if:name = current()]/"
          + "ip:ipv4" {
          description
            "The interface must have IPv4 enabled.";
        }
      }
      description
        "Reference to an entry in the global interface list.";
    }
    uses interface-config-attributes-igmp {
      if-feature per-interface-config;
    }
    uses interface-state-attributes-igmp;
  } // interfaces
} // igmp
} // augment

augment "/rt:routing/rt:control-plane-protocols/rt:control-plane-
protocol"
{
  description
    "MLD augmentation to routing control plane protocol
```

configuration and state.";

```
container mld {
  description
    "MLD operational state data.";

  container global {
    description
      "Global attributes.";
    uses global-config-attributes;
    uses global-state-attributes;
  }

  container interfaces {
    description
      "Containing a list of interfaces.";

    uses interfaces-config-attributes-mld {
      if-feature global-interface-config;
    }

    list interface {
      key "interface-name";
      description
        "List of MLD interfaces.";
      leaf interface-name {
        type if:interface-ref;
        must "/if:interfaces/if:interface[if:name = current()]/"
          + "ip:ipv6" {
          description
            "The interface must have IPv6 enabled.";
        }
      }
      description
        "Reference to an entry in the global interface list.";
    }
    uses interface-config-attributes-mld {
      if-feature per-interface-config;
    }
    uses interface-state-attributes-mld;
  } // interfaces
} // mld
} // augment

/*
 * RPCs
 */
rpc clear-igmp-groups {
  if-feature rpc-clear-groups;
  description
```

"Clears the specified IGMP cache entries.";

Liu & Guo, etc

Expires March 19, 2018

[Page 28]

```
input {
  leaf interface {
    type string;
    description
      "Name of the IGMP interface.
      If it is not specified, groups from all interfaces are
      cleared.";
  }
  leaf group {
    type inet:ipv4-address;
    description
      "Multicast group IPv4 address.
      If it is not specified, all IGMP group entries are
      cleared.";
  }
  leaf source {
    type inet:ipv4-address;
    description
      "Multicast source IPv4 address.
      If it is not specified, all IGMP source-group entries are
      cleared.";
  }
}
} // rpc clear-igmp-groups

rpc clear-mlt-groups {
  if-feature rpc-clear-groups;
  description
    "Clears the specified MLD cache entires.";

  input {
    leaf interface {
      type string;
      description
        "Name of the MLD interface.
        If it is not specified, groups from all interfaces are
        cleared.";
    }
    leaf group {
      type inet:ipv6-address;
      description
        "Multicast group IPv6 address.
        If it is not specified, all MLD group entries are
        cleared.";
    }
    leaf source {
      type inet:ipv6-address;
```

description

Liu & Guo, etc

Expires March 19, 2018

[Page 29]

```
        "Multicast source IPv6 address.  
        If it is not specified, all MLD source-group entries are  
        cleared.";  
    }  
}  
} // rpc clear-mld-groups  
  
/*  
 * Notifications  
 */  
}  
<CODE ENDS>
```

5. Security Considerations

The data model defined does not introduce any security implications. This document does not change any underlying security issues inherent in [[RFC8022](#)].

6. IANA Considerations

RFC Ed.: In this section, replace all occurrences of 'XXXX' with the actual RFC number (and remove this note).

This document registers the following namespace URIs in the IETF XML registry [[RFC3688](#)]:

URI: urn:ietf:params:xml:ns:yang:ietf-igmp-mld

Registrant Contact: The IESG.

XML: N/A, the requested URI is an XML namespace.

This document registers the following YANG modules in the YANG Module Names registry [[RFC7950](#)]:

name: ietf-igmp-mld

namespace: urn:ietf:params:xml:ns:yang:ietf-igmp-mld

prefix: igmp-mld

reference: RFC XXXX

7. References

7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), October 2010
- [RFC6087] Bierman, A., "Guidelines for Authors and Reviewers of YANG Data Model Documents", [RFC 6087](#), January 2011
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), June 2011
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), August 2016
- [RFC8022] Lhotka, L. and A. Lindem, "A YANG Data Model for Routing Management", [RFC 8022](#), November 2016
- [I-D.dsdt-nmda-guidelines] M. Bjorklund, J. Schoenwaelder, P. Shafer, K. Watsen, R. Wilton, "Guidelines for YANG Module Authors (NMDA)", [draft-dsdt-nmda-guidelines-01](#), May 2017
- [[draft-bjorklund-netmod-rfc7223bis-00](#)] M. Bjorklund, "A YANG Data Model for Interface Management", [draft-bjorklund-netmod-rfc7223bis-00](#), August 2017
- [[draft-bjorklund-netmod-rfc7277bis-00](#)] M. Bjorklund, "A YANG Data Model for IP Management", [draft-bjorklund-netmod-rfc7277bis-00](#), August 2017
- [I-D.ietf-netmod-rfc6087bis] Bierman, A., "Guidelines for Authors and Reviewers of YANG Data Model Documents", [draft-ietf-netmod-rfc6087bis-14](#), September 2017
- [I-D.acee-netmod-rfc8022bis] L. Lhotka, A. Lindem and Y.Qu, "A YANG Data Model for Routing Management (NDMA Version)", [draft-acee-netmod-rfc8022bis-02](#), September 2017

7.2. Informative References

- [RFC1112] Deering, S., "Host extensions for IP multicasting", STD 5, [RFC 1112](#), August 1989.
- [RFC2236] Fenner, W., "Internet Group Management Protocol, Version 2", [RFC 2236](#), November 1997.
- [RFC2710] Deering, S., Fenner, W., and B. Haberman, "Multicast Listener Discovery (MLD) for IPv6", [RFC 2710](#), October 1999.
- [RFC3376] Cain, B., Deering, S., Kouvelas, I., Fenner, B., and A. Thyagarajan, "Internet Group Management Protocol, Version 3", [RFC 3376](#), October 2002.
- [RFC3810] Vida, R. and L. Costa, "Multicast Listener Discovery Version 2 (MLDv2) for IPv6", [RFC 3810](#), June 2004.
- [RFC4541] M. Christensen, K. Kimball and F. Solensky, "Considerations for Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) Snooping Switches", [RFC 4541](#), May 2006.
- [RFC4605] B. Fenner, H. He, B. Haberman, and H. Sandick, "Internet Group Management Protocol (IGMP) / Multicast Listener Discovery (MLD)-Based Multicast Forwarding ("IGMP/MLD Proxying")", [RFC 4605](#), August 2006.

8. Acknowledgments

The authors would like to thank Steve Baillargeon, Hu Fangwei, Robert Kebler, Tanmoy Kundu, Liu Yisong, and Stig Venaas for their valuable contributions.

Authors' Addresses

Xufeng Liu
Jabil
8281 Greensboro Drive, Suite 200
McLean VA 22102
USA

E-Mail: Xufeng_Liu@jabil.com

Feng Guo
Huawei
Huawei Bld., No.156 Beiqing Rd.
Beijing 100095
China

Email: guofeng@huawei.com

Mahesh Sivakumar
Cisco Systems, Inc.
510 McCarthy Boulevard
Milpitas, California 95035
USA

Email: masivaku@cisco.com

Pete McAllister
Metaswitch Networks
100 Church Street
Enfield EN2 6BQ
UK

E-Mail: pete.mcallister@metaswitch.com

Anish Peter
Individual

E-Mail: anish.ietf@gmail.com

