

Internet Engineering Task Force
INTERNET-DRAFT
[draft-ietf-pim-mib-v2-01.txt](http://www.ietf.org/drafts/ietf/pim-mib-v2-01.txt)

PIM-WG
Editor
Jonathan Nicholas
ITT A/CD
November 2002
Expires May 2003

Protocol Independent Multicast MIB

Status of this Document

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at
<http://www.ietf.org/ietf/lid-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at
<http://www.ietf.org/shadow.html>.

This document is a product of the IETF PIM WG. Comments should be addressed to the authors, or the WG's mailing list at pim@catarina.usc.edu.

Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects used for managing the Protocol Independent Multicast (PIM) protocol.

INTERNET-DRAFT

Expires: May 2002

November 2002

Table of Contents

1	Introduction	2
2	The SNMP Network Management Framework	2
3	Overview	3
4	Definitions	4
5	Security Considerations	29
6	Acknowledgements	30
7	Authors' Addresses	30
8	References	30

[1](#). Introduction

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects used for managing the Protocol Independent Multicast (PIM) protocol [[18,19](#)].

[2](#). The SNMP Network Management Framework

The SNMP Management Framework presently consists of five major components:

- * An overall architecture, described in [RFC 2571](#) [[1](#)].
- * Mechanisms for describing and naming objects and events for the purpose of management. The first version of this Structure of Management Information (SMI) is called SMIV1 and described in STD 16, [RFC 1155](#) [[2](#)], STD 16, [RFC 1212](#) [[3](#)] and [RFC 1215](#) [[4](#)]. The second version, called SMIV2, is described in STD 58, [RFC 2578](#) [[5](#)], STD 58, [RFC 2579](#) [[6](#)] and STD 58, [RFC 2580](#) [[7](#)].
- * Message protocols for transferring management information. The first version of the SNMP message protocol is called SNMPv1 and described in STD 15, [RFC 1157](#) [[8](#)]. A second version of the SNMP message protocol, which is not an Internet standards track protocol, is called

SNMPv2c and described in [RFC 1901](#) [9] and [RFC 1906](#) [10]. The third version of the message protocol is called SNMPv3 and described in [RFC 1906](#) [10], [RFC 2572](#) [11] and [RFC 2574](#) [12].

- * Protocol operations for accessing management information. The first set of protocol operations and associated PDU formats is described in STD 15, [RFC 1157](#) [8]. A second set of protocol operations and associated PDU formats is described in [RFC 1905](#) [13].
- * A set of fundamental applications described in [RFC 2573](#) [14] and the view-based access control mechanism described in [RFC 2575](#) [15].

Nicholas

[Page 2]

INTERNET-DRAFT

Expires: December 2002

June 2002

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. Objects in the MIB are defined using the mechanisms defined in the SMI.

This memo specifies a MIB module that is compliant to the SMIV2. A MIB conforming to the SMIV1 can be produced through the appropriate translations. The resulting translated MIB must be semantically equivalent, except where objects or events are omitted because no translation is possible (use of Counter64). Some machine readable information in SMIV2 will be converted into textual descriptions in SMIV1 during the translation process. However, this loss of machine readable information is not considered to change the semantics of the MIB.

[3.](#) Overview

This MIB module contains one scalar and eight tables. Some of the objects in these tables are deprecated. This MIB contains deprecated objects since they are necessary for managing PIMv1 routers, but PIMv1 itself is obsoleted by PIM v2 [[18](#),[19](#)].

The tables contained in this MIB are:

- (1) The PIM Interface Table contains one row for each of the router's PIM interfaces.
- (2) The PIM Neighbor Table contains one row for each of the router's PIM neighbors.

- (3) The PIM IP Multicast Route Table contains one row for each multicast routing entry whose incoming interface is running PIM.
- (4) The PIM Next Hop Table which contains one row for each outgoing interface list entry in the multicast routing table whose interface is running PIM, and whose state is pruned.
- (5) The (deprecated) PIM RP Table contains the PIM (version 1) information for IP multicast groups which is common to all RPs of a group.
- (6) The PIM RP-Set Table contains the PIM (version 2) information for sets of candidate Rendezvous Points (RPs) for IP multicast group addresses with particular address prefixes.
- (7) The PIM Candidate-RP Table contains the IP multicast groups for which the local router is to advertise itself as a Candidate-RP. If this table is empty, then the local router advertises itself as a Candidate-RP for all groups.
- (8) The PIM Component Table contains one row for each of the PIM domains to which the router is connected.

Nicholas

[Page 3]

INTERNET-DRAFT

Expires: May 2002

November 2002

[4.](#) Definitions

PIM-MIB DEFINITIONS ::= BEGIN

IMPORTS

```
MODULE-IDENTITY, OBJECT-TYPE, experimental,
NOTIFICATION-TYPE,
Integer32, IpAddress, TimeTicks    FROM SNMPv2-SMI
RowStatus, TruthValue              FROM SNMPv2-TC
MODULE-COMPLIANCE, OBJECT-GROUP,
NOTIFICATION-GROUP                 FROM SNMPv2-CONF
ipMRouteGroup, ipMRouteSource,
ipMRouteSourceMask, ipMRouteNextHopGroup,
ipMRouteNextHopSource, ipMRouteNextHopSourceMask,
ipMRouteNextHopIfIndex,
ipMRouteNextHopAddress             FROM IPMROUTE-STD-MIB
InterfaceIndex                    FROM IF-MIB;
```

pimMIB MODULE-IDENTITY

```
LAST-UPDATED "200210280000Z" -- October 28, 2002
ORGANIZATION "IETF PIM Working Group."
```

CONTACT-INFO

" Jonathan Nicholas
ITT Industries
Aerospace/Communications Division
100 Kingsland Rd
Clifton, NJ 07014

Phone: +1 973 284 2019

Email: jonathan.nicholas@itt.com"

DESCRIPTION

"The MIB module for management of PIM routers."

REVISION "200009280000Z" -- September 28, 2000

DESCRIPTION

"Initial version, published as [RFC 2934](#)."

REVISION "200210280000Z" -- October 28, 2002

DESCRIPTION

"Revised November 4, 2002."

::= { experimental 61 }

pimMIBObjects OBJECT IDENTIFIER ::= { pimMIB 1 }

pimTraps OBJECT IDENTIFIER ::= { pimMIBObjects 0 }

pim OBJECT IDENTIFIER ::= { pimMIBObjects 1 }

Nicholas

[Page 4]

INTERNET-DRAFT

Expires: May 2002

November 2002

pimJoinPruneInterval OBJECT-TYPE

SYNTAX Integer32

UNITS "seconds"

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The default interval at which periodic PIM-SM Join/Prune messages are to be sent."

DEFVAL { 60 }

::= { pim 1 }

-- The PIM Interface Table

pimInterfaceTable OBJECT-TYPE

SYNTAX SEQUENCE OF PimInterfaceEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The (conceptual) table listing the router's PIM interfaces.
IGMP and PIM are enabled on all interfaces listed in this
table."

::= { pim 2 }

pimInterfaceEntry OBJECT-TYPE

SYNTAX PimInterfaceEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry (conceptual row) in the pimInterfaceTable."

INDEX { pimInterfaceIfIndex }

::= { pimInterfaceTable 1 }

PimInterfaceEntry ::= SEQUENCE {

pimInterfaceIfIndex InterfaceIndex,

pimInterfaceAddress IpAddress,

pimInterfaceNetMask IpAddress,

pimInterfaceMode INTEGER,

pimInterfaceDR IpAddress,

pimInterfaceHelloInterval Integer32,

pimInterfaceStatus RowStatus,

pimInterfaceJoinPruneInterval Integer32,

pimInterfaceCBSRPreference Integer32,

pimInterfaceTrigHelloInterval Integer32,

pimInterfaceHelloHoldtime Integer32,

pimInterfaceLanPruneDelay BITS,

pimInterfacePropagationDelay Integer32,

pimInterfaceOverrideInterval Integer32,

pimInterfaceGenerationID BITS,

pimInterfaceJoinPruneHoldtime Integer32,

pimInterfaceGraftRetryInterval Integer32,

pimInterfaceMaxGraftRetries Integer32,

pimInterfaceSRTTLThreshold Integer32,

Nicholas

[Page 5]

INTERNET-DRAFT

Expires: May 2002

November 2002

pimInterfaceLanDelayEnabled TruthValue,

pimInterfaceSRCapable TruthValue,

pimInterfaceDRPriority Integer32

}

pimInterfaceIfIndex OBJECT-TYPE

SYNTAX InterfaceIndex

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The ifIndex value of this PIM interface."

::= { pimInterfaceEntry 1 }

pimInterfaceAddress OBJECT-TYPE

SYNTAX IPAddress

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The IP address of the PIM interface."

::= { pimInterfaceEntry 2 }

pimInterfaceNetMask OBJECT-TYPE

SYNTAX IPAddress

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The network mask for the IP address of the PIM interface."

::= { pimInterfaceEntry 3 }

pimInterfaceMode OBJECT-TYPE

SYNTAX INTEGER { dense(1), sparse(2), sparseDense(3) }

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The configured mode of this PIM interface. A value of sparseDense is only valid for PIMv1."

DEFVAL { dense }

::= { pimInterfaceEntry 4 }

pimInterfaceDR OBJECT-TYPE

SYNTAX IPAddress

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The Designated Router on this PIM interface."

::= { pimInterfaceEntry 5 }

INTERNET-DRAFT

Expires: May 2002

November 2002

pimInterfaceHelloInterval OBJECT-TYPE

SYNTAX Integer32

UNITS "seconds"

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The frequency at which PIM Hello messages are transmitted on this interface."

DEFVAL { 30 }

::= { pimInterfaceEntry 6 }

pimInterfaceStatus OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The status of this entry. Creating the entry enables PIM on the interface; destroying the entry disables PIM on the interface."

::= { pimInterfaceEntry 7 }

pimInterfaceJoinPruneInterval OBJECT-TYPE

SYNTAX Integer32

UNITS "seconds"

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The frequency at which PIM Join/Prune messages are transmitted on this PIM interface. The default value of this object is the pimJoinPruneInterval."

::= { pimInterfaceEntry 8 }

pimInterfaceCBSRPreference OBJECT-TYPE

SYNTAX Integer32 (-1..255)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The preference value for the local interface as a candidate bootstrap router. The value of -1 is used to indicate that the local interface is not a candidate BSR interface."

DEFVAL { 0 }

::= { pimInterfaceEntry 9 }

pimInterfaceTrigHelloInterval OBJECT-TYPE

SYNTAX Integer32
UNITS "seconds"
MAX-ACCESS read-create
STATUS current
DESCRIPTION "The maximum time before a triggered PIM Hello message
 is transmitted on this interface."
DEFVAL { 5 }
::= { pimInterfaceEntry 10 }

INTERNET-DRAFT

Expires: May 2002

November 2002

pimInterfaceHelloHoldtime OBJECT-TYPE

SYNTAX Integer32 (0..65535)
UNITS "seconds"
MAX-ACCESS read-create
STATUS current
DESCRIPTION "The value set in the Holdtime field of Hello messages
 transmitted on this interface. This should be 3.5
 times the value of pimInterfaceHelloInterval."
DEFVAL { 105 }
::= { pimInterfaceEntry 11 }

pimInterfaceLanPruneDelay OBJECT-TYPE

SYNTAX BITS { off (0), on (1) }
MAX-ACCESS read-create
STATUS current
DESCRIPTION "Turns the LAN Prune Delay Option off and on on this
 interface."
DEFVAL { on }
::= { pimInterfaceEntry 12 }

pimInterfacePropagationDelay OBJECT-TYPE

SYNTAX Integer32 (0..32767)
UNITS "milliseconds"
MAX-ACCESS read-create
STATUS current
DESCRIPTION "The value inserted into the LAN Prune Delay field of a
 LAN Prune Delay option on this interface."
DEFVAL { 500 }
::= { pimInterfaceEntry 13 }

pimInterfaceOverrideInterval OBJECT-TYPE

SYNTAX Integer32 (0..65535)
MAX-ACCESS read-create
STATUS current
DESCRIPTION "The value inserted into the Override Interval field of

a LAN Prune Delay option on this interface."
DEFVAL { 2500 }
::= { pimInterfaceEntry 14 }

pimInterfaceGenerationID OBJECT-TYPE
SYNTAX BITS { off (0), on (1) }
MAX-ACCESS read-create
STATUS current
DESCRIPTION "Turns the Generation ID Option off and on on this
 interface."
DEFVAL { off }
::= { pimInterfaceEntry 15 }

Nicholas

[Page 8]

INTERNET-DRAFT

Expires: May 2002

November 2002

pimInterfaceJoinPruneHoldtime OBJECT-TYPE
SYNTAX Integer32 (0..65535)
UNITS "seconds"
MAX-ACCESS read-create
STATUS current
DESCRIPTION "The value inserted into the Holdtime field of a Join/
 Prune message sent on this interface. The value should
 be 3.5 times pimInterfaceJoinPruneInterval."
DEFVAL { 210 }
::= { pimInterfaceEntry 16 }

pimInterfaceGraftRetryInterval OBJECT-TYPE
SYNTAX Integer32
UNITS "seconds"
MAX-ACCESS read-create
STATUS current
DESCRIPTION "The interval a PIM router waits for a Graft Ack before
 resending a Graft on this interface."
DEFVAL { 3 }
::= { pimInterfaceEntry 17 }

pimInterfaceMaxGraftRetries OBJECT-TYPE
SYNTAX Integer32
MAX-ACCESS read-create
STATUS current
DESCRIPTION "The maximum number of times this router will resend a

Graft on this interface."
DEFVAL { 2 }
::= { pimInterfaceEntry 18 }

pimInterfaceSRTTLThreshold OBJECT-TYPE

SYNTAX Integer32
MAX-ACCESS read-create
STATUS current
DESCRIPTION "The Time To Live in a PIM-DM State Refresh message at
which it is not forwarded on this interface."
DEFVAL { 0 }
::= { pimInterfaceEntry 19 }

pimInterfaceLanDelayEnabled OBJECT-TYPE

SYNTAX TruthValue
MAX-ACCESS read-only
STATUS current
DESCRIPTION "Evaluates to TRUE if all routers on this interface are
using the LAN Prune Delay Option."
::= { pimInterfaceEntry 20 }

pimInterfaceSRCapable OBJECT-TYPE

SYNTAX TruthValue
MAX-ACCESS read-only
STATUS current
DESCRIPTION "Evaluates to TRUE if all routers on this interface are
using the State Refresh Capable Option."
::= { pimInterfaceEntry 21 }

pimInterfaceDRPriority OBJECT-TYPE

SYNTAX Integer32
MAX-ACCESS read-create
STATUS current
DESCRIPTION "The Designater Router Priority inserted into the DR
priority option on this interface."
DEFVAL { 1 }
::= { pimInterfaceEntry 22 }

-- The PIM Neighbor Table

```
pimNeighborTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF PimNeighborEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The (conceptual) table listing the router's PIM neighbors."
    ::= { pim 3 }
```

```
pimNeighborEntry OBJECT-TYPE
    SYNTAX      PimNeighborEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry (conceptual row) in the pimNeighborTable."
    INDEX       { pimNeighborAddress }
    ::= { pimNeighborTable 1 }
```

```
PimNeighborEntry ::= SEQUENCE {
    pimNeighborAddress      IpAddress,
    pimNeighborIfIndex      InterfaceIndex,
    pimNeighborUpTime       TimeTicks,
    pimNeighborExpiryTime   TimeTicks,
    pimNeighborMode         INTEGER,
    pimNeighborLanPruneDelay Integer32,
    pimNeighborOverrideInterval Integer32,
    pimNeighborTBit         BITS,
    pimNeighborSRCapable    TruthValue,
    pimNeighborDRPresent    TruthValue
}
```

Nicholas

[Page 10]

INTERNET-DRAFT

Expires: May 2002

November 2002

```
pimNeighborAddress OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The IP address of the PIM neighbor for which this entry
        contains information."
    ::= { pimNeighborEntry 1 }
```

pimNeighborIfIndex OBJECT-TYPE

SYNTAX InterfaceIndex

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of ifIndex for the interface used to reach this
PIM neighbor."

::= { pimNeighborEntry 2 }

pimNeighborUpTime OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The time since this PIM neighbor (last) became a neighbor
of the local router."

::= { pimNeighborEntry 3 }

pimNeighborExpiryTime OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The minimum time remaining before this PIM neighbor will be
aged out."

::= { pimNeighborEntry 4 }

pimNeighborMode OBJECT-TYPE

SYNTAX INTEGER { dense(1), sparse(2) }

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The active PIM mode of this neighbor. This object is
deprecated for PIMv2 routers since all neighbors on the
interface must be either dense or sparse as determined by
the protocol running on the interface."

::= { pimNeighborEntry 5 }

pimNeighborLANPruneDelay OBJECT-TYPE

SYNTAX Integer32

MAX-ACCESS read-only

STATUS current

DESCRIPTION "The value of LAN Prune Delay field of the LAN Prune Delay Option received from this neighbor. A value of 0 indicates that no LAN Prune Delay Option was received from this neighbor."

::= { pimNeighborEntry 6 }

pimNeighborOverrideInterval OBJECT-TYPE

SYNTAX Integer32

MAX-ACCESS read-only

STATUS current

DESCRIPTION "The value of Override Interval field of the LAN Prune Delay Option received from this neighbor. A value of 0 indicates that no LAN Prune Delay Option was received from this neighbor."

::= { pimNeighborEntry 7 }

pimNeighborTBit OBJECT-TYPE

SYNTAX BITS

MAX-ACCESS read-only

STATUS current

DESCRIPTION "The value of the T bit field of the LAN Prune Delay Option received from this neighbor. The T bit specifies the ability of the neighbor to disable join suppression."

::= { pimNeighborEntry 8 }

pimNeighborSRCapable OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION "Evaluates to TRUE if this neighbor is using the State Refresh Capable Option."

::= { pimNeighborEntry 9 }

pimNeighborDRPresent OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION "Evaluates to TRUE if this neighbor is using the Designated Router Option."

::= { pimNeighborEntry 10 }

INTERNET-DRAFT

Expires: May 2002

November 2002

--

-- The PIM IP Multicast Route Table

--

pimIpMRouteTable OBJECT-TYPE

SYNTAX SEQUENCE OF PimIpMRouteEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The (conceptual) table listing PIM-specific information on a subset of the rows of the ipMRouteTable defined in the IP Multicast MIB."

::= { pim 4 }

pimIpMRouteEntry OBJECT-TYPE

SYNTAX PimIpMRouteEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry (conceptual row) in the pimIpMRouteTable. There is one entry per entry in the ipMRouteTable whose incoming interface is running PIM."

INDEX { ipMRouteGroup, ipMRouteSource, ipMRouteSourceMask }

::= { pimIpMRouteTable 1 }

PimIpMRouteEntry ::= SEQUENCE {

pimIpMRouteUpstreamAssertTimer TimeTicks,

pimIpMRouteAssertMetric Integer32,

pimIpMRouteAssertMetricPref Integer32,

pimIpMRouteAssertRPTBit TruthValue,

pimIpMRouteFlags BITS,

pimIpMRouteRPFNeighbor IpAddress,

pimIpMRouteSourceTimer TimeTicks,

pimIpMRouteOriginatorSRTTL Integer32

}

pimIpMRouteUpstreamAssertTimer OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The time remaining before the router changes its upstream neighbor back to its RPF neighbor. This timer is called the Assert timer in the PIM Sparse and Dense mode specification. A value of 0 indicates that no Assert has changed the upstream neighbor away from the RPF neighbor."

::= { pimIpMRouteEntry 1 }

Nicholas

[Page 13]

INTERNET-DRAFT

Expires: May 2002

November 2002

pimIpMRouteAssertMetric OBJECT-TYPE

SYNTAX Integer32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The metric advertised by the assert winner on the upstream interface, or 0 if no such assert is in received."

::= { pimIpMRouteEntry 2 }

pimIpMRouteAssertMetricPref OBJECT-TYPE

SYNTAX Integer32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The preference advertised by the assert winner on the upstream interface, or 0 if no such assert is in effect."

::= { pimIpMRouteEntry 3 }

pimIpMRouteAssertRPTBit OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of the RPT-bit advertised by the assert winner on the upstream interface, or false if no such assert is in effect."

::= { pimIpMRouteEntry 4 }

pimIpMRouteFlags OBJECT-TYPE

SYNTAX BITS {
 rpt(0),
 spt(1)


```

    }
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "This object describes PIM-specific flags related to a
        multicast state entry. See the PIM Sparse Mode
        specification for the meaning of the RPT and SPT bits."
    ::= { pimIpMRouteEntry 5 }

```

pimIpMRouterRPFNeighbor OBJECT-TYPE

```

    SYNTAX IpAddress
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION "The IP Address of the current RPF neighbor. If there
        is an upstream Assert Winner, it will be the RPF
        neighbor. Otherwise, the RPF neighbor will be
        the next hop indicated by unicast routing."
    ::= { pimIpMRouteEntry 6 }

```

Nicholas

[Page 14]

INTERNET-DRAFT

Expires: May 2002

November 2002

pimIpMRouteSourceTimer OBJECT-TYPE

```

    SYNTAX TimeTicks
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION "The time before this router ceases originating State
        Refresh messages for this route."
    ::= { pimIpMRouteEntry 7 }

```

pimIpMRouteOriginatorSRTTL OBJECT-TYPE

```

    SYNTAX Integer32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION "The TTL used in State Refresh messages originated by
        this router for this route."
    ::= { pimIpMRouteEntry 8 }

```

--

-- The PIM Next Hop Table

--

pimIpMRouteNextHopTable OBJECT-TYPE

```

    SYNTAX SEQUENCE OF PimIpMRouteNextHopEntry
    MAX-ACCESS not-accessible

```

```

STATUS      current
DESCRIPTION
    "The (conceptual) table listing PIM-specific information on
    a subset of the rows of the ipMRouteNextHopTable defined in
    the IP Multicast MIB."
 ::= { pim 7 }
pimIpMRouteNextHopEntry OBJECT-TYPE
    SYNTAX      PimIpMRouteNextHopEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry (conceptual row) in the pimIpMRouteNextHopTable.
        There is one entry per entry in the ipMRouteNextHopTable
        whose interface is running PIM and whose
        ipMRouteNextHopState is pruned(1)."
    INDEX      { ipMRouteNextHopGroup, ipMRouteNextHopSource,
                 ipMRouteNextHopSourceMask, ipMRouteNextHopIfIndex,
                 ipMRouteNextHopAddress }
 ::= { pimIpMRouteNextHopTable 1 }

PimIpMRouteNextHopEntry ::= SEQUENCE {
    pimIpMRouteNextHopPruneReason      INTEGER,
    pimIpMRouteNextHopAssertWinner     IpAddress,
    pimIpMRouteNextHopAssertTimer      TimeTicks,
    pimIpMRouteNextHopAssertMetric     Integer32,
    pimIpMRouteNextHopAssertMetricPref Integer32,
    pimIpMRouteNextHopJoinPruneTimer   TimeTicks
}

```

Nicholas

[Page 15]

INTERNET-DRAFT

Expires: May 2002

November 2002

```

pimIpMRouteNextHopPruneReason OBJECT-TYPE
    SYNTAX      INTEGER {
        other (1),
        prune (2),
        assert (3)
    }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This object indicates why the downstream interface was
        pruned, whether in response to a PIM prune message or due to
        PIM Assert processing."
 ::= { pimIpMRouteNextHopEntry 2 }

```

```

pimIpMRouteNextHopAssertWinner OBJECT-TYPE
    SYNTAX IPAddress
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION "The IP Address of the Assert Winner."
    ::= { pimIpMRouteNextHopEntry 3 }

pimIpMRouteNextHopAssertTimer OBJECT-TYPE
    SYNTAX TimeTicks
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION "The time remaining before the PIM router leaves the
                  current Assert state.  A value of 0 indicates that the
                  router is in the No Info state."
    ::= { pimIpMRouteNextHopEntry 4 }
pimIpMRouteNextHopAssertMetric OBJECT-TYPE
    SYNTAX Integer32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION "The metric advertised by the Assert Winner."
    ::= { pimIpMRouteNextHopEntry 5 }

pimIpMRouteNextHopAssertMetricPref OBJECT-TYPE
    SYNTAX Integer32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION "The metric preference advertised by the Assert Winner."
    ::= { pimIpMRouteNextHopEntry 6 }

pimIpMRouteNextHopJoinPruneTimer OBJECT-TYPE
    SYNTAX TimeTicks
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION "The time remaining before the PIM router reverts to
                  default operation on this interface.  PIM-SM will
                  cease forwarding, PIM-DM will resume forwarding."
    ::= { pimIpMRouteNextHopEntry 7 }ss, pimRPAddress }
    ::= { pimRPTable 1 }

```

Nicholas

[Page 16]

INTERNET-DRAFT

Expires: May 2002

November 2002

-- The PIM RP Table

```

pimRPTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF PimRPEntry

```

```

MAX-ACCESS not-accessible
STATUS      deprecated
DESCRIPTION
    "The (conceptual) table listing PIM version 1 information
    for the Rendezvous Points (RPs) for IP multicast groups.
    This table is deprecated since its function is replaced by
    the pimRPSetTable for PIM version 2."
 ::= { pim 5 }

```

```

pimRPEntry OBJECT-TYPE
    SYNTAX      PimRPEntry
    MAX-ACCESS not-accessible
    STATUS      deprecated
    DESCRIPTION
        "An entry (conceptual row) in the pimRPTable. There is one
        entry per RP address for each IP multicast group."
    INDEX       { pimRPGroupAddre
PimRPEntry ::= SEQUENCE {
    pimRPGroupAddress      IpAddress,
    pimRPAddress           IpAddress,
    pimRPState             INTEGER,
    pimRPStateTimer        TimeTicks,
    pimRPLastChange        TimeTicks,
    pimRPRowStatus         RowStatus
}

```

```

pimRPGroupAddress OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS not-accessible
    STATUS      deprecated
    DESCRIPTION
        "The IP multicast group address for which this entry
        contains information about an RP."
    ::= { pimRPEntry 1 }

```

```

pimRPAddress OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS not-accessible
    STATUS      deprecated
    DESCRIPTION
        "The unicast address of the RP."
    ::= { pimRPEntry 2 }

```

pimRPState OBJECT-TYPE

SYNTAX INTEGER { up(1), down(2) }
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION
 "The state of the RP."
 ::= { pimRPEntry 3 }

pimRPStateTimer OBJECT-TYPE

SYNTAX TimeTicks
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION
 "The minimum time remaining before the next state change.
 When pimRPState is up, this is the minimum time which must
 expire until it can be declared down. When pimRPState is
 down, this is the time until it will be declared up (in
 order to retry)."
 ::= { pimRPEntry 4 }

pimRPLastChange OBJECT-TYPE

SYNTAX TimeTicks
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION
 "The value of sysUpTime at the time when the corresponding
 instance of pimRPState last changed its value."
 ::= { pimRPEntry 5 }

pimRPRowStatus OBJECT-TYPE

SYNTAX RowStatus
MAX-ACCESS read-create
STATUS deprecated
DESCRIPTION
 "The status of this row, by which new entries may be
 created, or old entries deleted from this table."
 ::= { pimRPEntry 6 }

-- The PIM RP-Set Table

pimRPSetTable OBJECT-TYPE

SYNTAX SEQUENCE OF PimRPSetEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
 "The (conceptual) table listing PIM information for
 candidate Rendezvous Points (RPs) for IP multicast groups.
 When the local router is the BSR, this information is

obtained from received Candidate-RP-Advertisements. When the local router is not the BSR, this information is obtained from received RP-Set messages."

::= { pim 6 }

Nicholas

[Page 18]

INTERNET-DRAFT

Expires: May 2002

November 2002

pimRPSetEntry OBJECT-TYPE

SYNTAX PimRPSetEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry (conceptual row) in the pimRPSetTable."

INDEX { pimRPSetComponent, pimRPSetGroupAddress,
pimRPSetGroupMask, pimRPSetAddress }

::= { pimRPSetTable 1 }

PimRPSetEntry ::= SEQUENCE {

pimRPSetGroupAddress IpAddress,

pimRPSetGroupMask IpAddress,

pimRPSetAddress IpAddress,

pimRPSetHoldTime Integer32,

pimRPSetExpiryTime TimeTicks,

pimRPSetComponent Integer32

}

pimRPSetGroupAddress OBJECT-TYPE

SYNTAX IpAddress

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The IP multicast group address which, when combined with pimRPSetGroupMask, gives the group prefix for which this entry contains information about the Candidate-RP."

::= { pimRPSetEntry 1 }

pimRPSetGroupMask OBJECT-TYPE

SYNTAX IpAddress

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The multicast group address mask which, when combined with pimRPSetGroupAddress, gives the group prefix for which this entry contains information about the Candidate-RP."

::= { pimRPSetEntry 2 }

pimRPSetAddress OBJECT-TYPE
SYNTAX IpAddress
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
 "The IP address of the Candidate-RP."
::= { pimRPSetEntry 3 }

Nicholas

[Page 19]

INTERNET-DRAFT

Expires: May 2002

November 2002

pimRPSetHoldTime OBJECT-TYPE
SYNTAX Integer32 (0..255)
UNITS "seconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The holdtime of a Candidate-RP. If the local router is not
 the BSR, this value is 0."
::= { pimRPSetEntry 4 }

pimRPSetExpiryTime OBJECT-TYPE
SYNTAX TimeTicks
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The minimum time remaining before the Candidate-RP will be
 declared down. If the local router is not the BSR, this
 value is 0."
::= { pimRPSetEntry 5 }

pimRPSetComponent OBJECT-TYPE
SYNTAX Integer32 (1..255)
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
 " A number uniquely identifying the component. Each
 protocol instance connected to a separate domain should have
 a different index value."
::= { pimRPSetEntry 6 }

```
--
-- Note: { pim 8 } through { pim 10 } were used in older versions
-- of this MIB.  Since some earlier versions of this MIB have been
-- widely-deployed, these values must not be used in the future,
-- as long the MIB is rooted under { experimental 61 }.
--

-- The PIM Candidate-RP Table

pimCandidateRPTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF PimCandidateRPEnt
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The (conceptual) table listing the IP multicast groups for
        which the local router is to advertise itself as a
        Candidate-RP when the value of pimComponentCRPHoldTime is
        non-zero.  If this table is empty, then the local router
        will advertise itself as a Candidate-RP for all groups
        (providing the value of pimComponentCRPHoldTime is non-
        zero)."
```

```
 ::= { pim 11 }
```

Nicholas

[Page 20]

INTERNET-DRAFT

Expires: May 2002

November 2002

```
pimCandidateRPEnt OBJECT-TYPE
    SYNTAX      PimCandidateRPEnt
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry (conceptual row) in the pimCandidateRPTable."
```

```
INDEX      { pimCandidateRPGroupAddress,
              pimCandidateRPGroupMask }
```

```
 ::= { pimCandidateRPTable 1 }
```

```
PimCandidateRPEnt ::= SEQUENCE {
    pimCandidateRPGroupAddress  IpAddress,
    pimCandidateRPGroupMask     IpAddress,
    pimCandidateRPAddress       IpAddress,
    pimCandidateRPRowStatus     RowStatus
}
```

```
pimCandidateRPGroupAddress OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS  not-accessible
    STATUS      current
```


DESCRIPTION

"The IP multicast group address which, when combined with pimCandidateRPGroupMask, identifies a group prefix for which the local router will advertise itself as a Candidate-RP."

::= { pimCandidateRPEntry 1 }

pimCandidateRPGroupMask OBJECT-TYPE

SYNTAX IpAddress

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The multicast group address mask which, when combined with pimCandidateRPGroupMask, identifies a group prefix for which the local router will advertise itself as a Candidate-RP."

::= { pimCandidateRPEntry 2 }

pimCandidateRPAddress OBJECT-TYPE

SYNTAX IpAddress

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The (unicast) address of the interface which will be advertised as a Candidate-RP."

::= { pimCandidateRPEntry 3 }

pimCandidateRPRowStatus OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The status of this row, by which new entries may be created, or old entries deleted from this table."

::= { pimCandidateRPEntry 4 }

```

pimComponentTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF PimComponentEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The (conceptual) table containing objects specific to a PIM
        domain.  One row exists for each domain to which the router
        is connected.  A PIM-SM domain is defined as an area of the
        network over which Bootstrap messages are forwarded.
        Typically, a PIM-SM router will be a member of exactly one
        domain.  This table also supports, however, routers which
        may form a border between two PIM-SM domains and do not
        forward Bootstrap messages between them."
    ::= { pim 12 }

pimComponentEntry OBJECT-TYPE
    SYNTAX      PimComponentEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry (conceptual row) in the pimComponentTable."
    INDEX       { pimComponentIndex }
    ::= { pimComponentTable 1 }

PimComponentEntry ::= SEQUENCE {
    pimComponentIndex      Integer32,
    pimComponentBSRAAddress  IPAddress,
    pimComponentBSRExpiryTime  TimeTicks,
    pimComponentCRPHoldTime  Integer32,
    pimComponentStatus      RowStatus
}

```

```

pimComponentIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..255)
    MAX-ACCESS  not-accessible

```

STATUS current
DESCRIPTION
"A number uniquely identifying the component. Each protocol instance connected to a separate domain should have a different index value. Routers that only support membership in a single PIM-SM domain should use a pimComponentIndex value of 1."
::= { pimComponentEntry 1 }

pimComponentBSRAddress OBJECT-TYPE
SYNTAX IPAddress
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The IP address of the bootstrap router (BSR) for the local PIM region."
::= { pimComponentEntry 2 }

pimComponentBSRExpiryTime OBJECT-TYPE
SYNTAX TimeTicks
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The minimum time remaining before the bootstrap router in the local domain will be declared down. For candidate BSRs, this is the time until the component sends an RP-Set message. For other routers, this is the time until it may accept an RP-Set message from a lower candidate BSR."
::= { pimComponentEntry 3 }

pimComponentCRPHoldTime OBJECT-TYPE
SYNTAX Integer32 (0..255)
UNITS "seconds"
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The holdtime of the component when it is a candidate RP in the local domain. The value of 0 is used to indicate that the local system is not a Candidate-RP."
DEFVAL { 0 }
::= { pimComponentEntry 4 }

INTERNET-DRAFT

Expires: May 2002

November 2002

pimComponentStatus OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The status of this entry. Creating the entry creates another protocol instance; destroying the entry disables a protocol instance."

::= { pimComponentEntry 5 }

-- PIM State Refresh Objects

pimSourceLifetime OBJECT-TYPE

SYNTAX Integer32

UNITS "seconds"

MAX-ACCESS read-create

STATUS current

DESCRIPTION "The maximum time this router will continue to originate State Refresh messages in the absence of traffic from the source itself."

DEFVAL { 210 }

::= { pim 13 }

pimStateRefreshInterval OBJECT-TYPE

SYNTAX Integer32 (1..255)

UNITS "seconds"

MAX-ACCESS read-create

STATUS current

DESCRIPTION "The interval between successive State Refresh messages originated by this router."

DEFVAL { 60 }

::= { pim 14 }

pimStateRefreshLimitInterval OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-create

STATUS current

DESCRIPTION "This router will not forward successive State Refresh messages received at less than this interval."

DEFVAL { 0 }

::= { pim 15 }

pimStateRefreshTimeToLive OBJECT-TYPE

```
SYNTAX Integer32
MAX-ACCESS read-create
STATUS current
DESCRIPTION "The TTL to be used by this router's originated State
              Refresh messages if the data packet's TTL is not
              recorded."
DEFVAL { 16 }
::= { pim 16 }
```

Nicholas

[Page 24]

INTERNET-DRAFT

Expires: May 2002

November 2002

-- PIM Traps

```
pimNeighborLoss NOTIFICATION-TYPE
  OBJECTS {
    pimNeighborIfIndex
  }
  STATUS          current
  DESCRIPTION
    "A pimNeighborLoss trap signifies the loss of an adjacency
    with a neighbor. This trap should be generated when the
    neighbor timer expires, and the router has no other
    neighbors on the same interface with a lower IP address than
    itself."
  ::= { pimTraps 1 }
```

-- conformance information

```
pimMIBConformance OBJECT IDENTIFIER ::= { pimMIB 2 }
pimMIBCompliances OBJECT IDENTIFIER ::= { pimMIBConformance 1 }
pimMIBGroups      OBJECT IDENTIFIER ::= { pimMIBConformance 2 }
```

-- compliance statements

```
pimV1MIBCompliance MODULE-COMPLIANCE
  STATUS deprecated
  DESCRIPTION
    "The compliance statement for routers running PIMv1 and
    implementing the PIM MIB."
  MODULE -- this module
    MANDATORY-GROUPS { pimV1MIBGroup }

  ::= { pimMIBCompliances 1 }
```

```

pimSparseV2MIBCompliance MODULE-COMPLIANCE
    STATUS    current
    DESCRIPTION
        "The compliance statement for routers running PIM Sparse
        Mode and implementing the PIM MIB."
    MODULE    -- this module
    MANDATORY-GROUPS { pimV2MIBGroup }

    GROUP      pimV2CandidateRPMIBGroup
    DESCRIPTION
        "This group is mandatory if the router is capable of being a
        Candidate RP."

    OBJECT      pimInterfaceStatus
    MIN-ACCESS  read-only
    DESCRIPTION
        "Write access is not required."
    ::= { pimMIBCompliances 2 }

```

Nicholas

[Page 25]

INTERNET-DRAFT

Expires: May 2002

November 2002

```

pimDenseV2MIBCompliance MODULE-COMPLIANCE
    STATUS    current
    DESCRIPTION
        "The compliance statement for routers running PIM Dense Mode
        and implementing the PIM MIB."
    MODULE    -- this module

        MANDATORY-GROUPS { pimDenseV2MIBGroup }

    OBJECT      pimInterfaceStatus
    MIN-ACCESS  read-only
    DESCRIPTION
        "Write access is not required."

    ::= { pimMIBCompliances 3 }

```

-- units of conformance

```

pimNotificationGroup NOTIFICATION-GROUP
    NOTIFICATIONS { pimNeighborLoss }
    STATUS    current
    DESCRIPTION
        "A collection of notifications for signaling important PIM
        events."
    ::= { pimMIBGroups 1 }

```

INTERNET-DRAFT

Expires: May 2002

November 2002

pimV2MIBGroup OBJECT-GROUP

```
OBJECTS { pimJoinPruneInterval, pimInterfaceIfIndex,
  pimInterfaceAddress, pimInterfaceNetMask,
  pimInterfaceMode, pimInterfaceDR,
  pimInterfaceHelloInterval, pimInterfaceStatus,
  pimInterfaceJoinPruneInterval,
  pimInterfaceCBSRPreference, pimInterfaceTrigHelloInterval,
  pimInterfaceHelloHoldtime, pimInterfaceLanPruneDelay,
  pimInterfacePropagationDelay,
  pimInterfaceOverrideInterval, pimInterfaceGenerationID,
  pimInterfaceJoinPruneHoldtime,
  pimInterfaceLanDelayEnabled, pimInterfaceDRPriority,
  pimNeighborAddress, pimNeighborInterfaceIfIndex,
  pimNeighborUpTime, pimNeighborExpiryTime,
  pimNeighborLANPruneDelay, pimNeighborOverrideInterval,
  pimNeighborTBit, pimNeighborDRPresent,
  pimIpMRouteUpstreamAssertTimer, pimIpMRouteAssertMetric,
```

```

        pimIpMRouteIpRouteAssertMetricPref,
        pimIpMRouteAssertRPTBit, pimIpMRouteFlags,
        pimIpMRouteRPFNeighbor, pimIpMRouteNextHopPruneReason,
        pimRPSetGroupAddress, pimRPSetGroupMask, pimRPSetAddress,
        pimRPSetHoldTime, pimRPSetExpiryTime, pimRPSetComponent,
        pimComponentBSRAddress, pimComponentBSRExpiryTime,
        pimComponentCRPHoldTime, pimComponentStatus
    }
    STATUS current
    DESCRIPTION
        "A collection of objects to support management of PIM Sparse
        Mode (version 2) routers."
    ::= { pimMIBGroups 2 }

```

pimDenseV2MIBGroup OBJECT-GROUP

```

    OBJECTS { pimInterfaceIfIndex, pimInterfaceAddress,
        pimInterfaceNetMask, pimInterfaceHelloInterval,
        pimInterfaceStatus, pimInterfaceTrigHelloInterval,
        pimInterfaceHelloHoldtime, pimInterfaceLanPruneDelay,
        pimInterfacePropagationDelay, pimInterfaceOverrideInterval,
        pimInterfaceGenerationID, pimInterfaceJoinPruneHoldtime,
        pimInterfaceGraftRetryInterval,
        pimInterfaceMaxGraftRetries, pimInterfaceSRTTLThreshold,
        pimInterfaceLanDelayEnabled, pimInterfaceSRCapable,
        pimNeighborIfIndex, pimNeighborUpTime,
        pimNeighborExpiryTime, pimNeighborLANPruneDelay,
        pimNeighborOverrideInterval, pimNeighborSRCapable,
        pimIpMRouteSourceTimer, pimIpMRouteOriginatorSRTTL,
        pimSourceLifetime, pimStateRefreshInterval,
        pimStateRefreshLimitInterval, pimStateRefreshTimeToLive
    }
    STATUS current
    DESCRIPTION
        "A collection of objects to support management of PIM Dense
        Mode (version 2) routers."
    ::= { pimMIBGroups 5 }

```

Nicholas

[Page 27]

INTERNET-DRAFT

Expires: May 2002

November 2002

pimV2CandidateRPMIBGroup OBJECT-GROUP

```

    OBJECTS { pimCandidateRPAddress,
        pimCandidateRPRowStatus
    }
    STATUS current
    DESCRIPTION
        "A collection of objects to support configuration of which
        groups a router is to advertise itself as a Candidate-RP."

```



```
::= { pimMIBGroups 3 }
```

```
pimV1MIBGroup OBJECT-GROUP
```

```
  OBJECTS { pimJoinPruneInterval, pimNeighborIfIndex,  
             pimNeighborUpTime, pimNeighborExpiryTime,  
             pimNeighborMode,  
             pimInterfaceAddress, pimInterfaceNetMask,  
             pimInterfaceJoinPruneInterval, pimInterfaceStatus,  
             pimInterfaceMode, pimInterfaceDR,  
             pimInterfaceHelloInterval,  
             pimRPState, pimRPStateTimer,  
             pimRPLastChange, pimRPRowStatus  
          }
```

```
  STATUS deprecated
```

```
  DESCRIPTION
```

```
    "A collection of objects to support management of PIM  
    (version 1) routers."
```

```
 ::= { pimMIBGroups 4 }
```

```
pimNextHopGroup OBJECT-GROUP
```

```
  OBJECTS { pimIpMRouteNextHopPruneReason,  
             pimIpMRouteNextHopAssertWinner,  
             pimIpMRouteNextHopAssertTimer,  
             pimIpMRouteNextHopAssertMetric,  
             pimIpMRouteNextHopAssertMetricPref,  
             pimIpMRouteNextHopJoinPruneTimer  
          }
```

```
  STATUS current
```

```
  DESCRIPTION
```

```
    "A collection of optional objects to provide per-next hop  
    information for diagnostic purposes. Supporting this group  
    may add a large number of instances to a tree walk, but the  
    information in this group can be extremely useful in  
    tracking down multicast connectivity problems."
```

```
 ::= { pimMIBGroups 6 }
```

pimAssertGroup OBJECT-GROUP

OBJECTS { pimIpMRouteAssertMetric, pimIpMRouteAssertMetricPref,
pimIpMRouteAssertRPTBit, pimIpMRouteRPFNeighbor}

STATUS current

DESCRIPTION

"A collection of optional objects to provide extra information about the assert election process. There is no protocol reason to keep such information, but some implementations may already keep this information and make it available. These objects can also be very useful in debugging connectivity or duplicate packet problems, especially if the assert winner does not support the PIM and IP Multicast MIBs."

::= { pimMIBGroups 7 }

END

5. Security Considerations

This MIB contains readable objects whose values provide information related to multicast routing, including information on the network topology. There are also a number of objects that have a MAX-ACCESS clause of read-write and/or read-create, which allow an administrator to configure PIM in the router.

While unauthorized access to the readable objects is relatively innocuous, unauthorized access to the write-able objects could cause a denial of service. Hence, the support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations.

SNMPv1 by itself is such an insecure environment. Even if the network itself is secure (for example by using IPSec), even then, there is no control as to who on the secure network is allowed to access and SET (change/create/delete) the objects in this MIB.

It is recommended that the implementers consider the security features as provided by the SNMPv3 framework. Specifically, the use of the User-based Security Model [RFC 2274](#) [12] and the View-based Access Control Model [RFC 2275](#) [15] is recommended.

It is then a customer/user responsibility to ensure that the SNMP entity giving access to this MIB, is properly configured to give access to those objects only to those principals (users) that have legitimate rights to access them.

INTERNET-DRAFT

Expires: May 2002

November 2002

[6.](#) Acknowledgements

This MIB module is based on the original work in [RFC 2934](#) by K. McCloghrie, D. Farinacci, D. Thaler and W. Fenner and has been updated based on feedback from the IETF's Protocol Independent Multicast (PIM) Working Group.

[7.](#) Authors' Addresses

Jonathan Nicholas
ITT Industries
Aerospace/Communications Division
100 Kingsland Rd
Clifton, NJ 07014

Phone: +1 973 284 2019
EMail: Jonathan.Nicholas@itt.com

[8.](#) References

- [1] Wijnen, B., Harrington, D. and R. Presuhn, "An Architecture for Describing SNMP Management Frameworks", [RFC 2571](#), April 1999.
- [2] Rose, M. and K. McCloghrie, "Structure and Identification of Management Information for TCP/IP-based Internets", STD 16, [RFC 1155](#), May 1990.
- [3] Rose, M. and K. McCloghrie, "Concise MIB Definitions", STD 16, [RFC 1212](#), March 1991.
- [4] Rose, M., "A Convention for Defining Traps for use with the SNMP", [RFC 1215](#), March 1991.
- [5] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M. and S. Waldbusser, "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), April 1999.
- [6] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose,

- M. and S. Waldbusser, "Textual Conventions for SMIV2", STD 58, [RFC 2579](#), April 1999.
- [7] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M. and S. Waldbusser, "Conformance Statements for SMIV2", STD 58, [RFC 2580](#), April 1999.
- [8] Case, J., Fedor, M., Schoffstall, M. and J. Davin, "Simple Network Management Protocol", STD 15, [RFC 1157](#), May 1990.

Nicholas

[Page 30]

INTERNET-DRAFT

Expires: May 2002

November 2002

- [9] Case, J., McCloghrie, K., Rose, M. and S. Waldbusser, "Introduction to Community-based SNMPv2", [RFC 1901](#), January 1996.
- [10] Case, J., McCloghrie, K., Rose, M. and S. Waldbusser, "Transport Mappings for Version 2 of the Simple Network Management Protocol (SNMPv2)", [RFC 1906](#), January 1996.
- [11] Case, J., Harrington D., Presuhn R. and B. Wijnen, "Message Processing and Dispatching for the Simple Network Management Protocol (SNMP)", [RFC 2572](#), April 1999.
- [12] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", [RFC 2574](#), April 1999.
- [13] Case, J., McCloghrie, K., Rose, M. and S. Waldbusser, "Protocol Operations for Version 2 of the Simple Network Management Protocol (SNMPv2)", [RFC 1905](#), January 1996.
- [14] Levi, D., Meyer, P. and B. Stewart, "SNMPv3 Applications", [RFC 2573](#), April 1999.
- [15] Wijnen, B., Presuhn, R. and K. McCloghrie, "View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)", [RFC 2575](#), April 1999.
- [18] Estrin, D., Farinacci, D., Helmy, A., Thaler, D., Deering, S., Handley, M., Jacobson, V., Liu, C., Sharma, P. and L. Wei, "Protocol Independent Multicast - Sparse Mode (PIM-SM): Protocol Specification", [RFC 2362](#), June 1998.

- [19] Adams, A., Nicholas, J., Siadak, W., "Protocol Independent Multicast - Dense Mode (PIM-DM): Protocol Specification (Revised)", [draft-ietf-pim-dm-new-v2-02.txt](#), work in progress.
- [20] McCloghrie, K., Farinacci, D. and D. Thaler, "IPv4 Multicast Routing MIB", [RFC 2932](#), October 2000.
- [21] Fenner, W., Handley, M., Holbrook, H., Kouvelas, I., "Protocol Independent Multicast - Sparse Mode (PIM-SM)", [draft-ietf-pim-sm-v2-new-05.txt](#), work in progress.
- [22] McCloghrie, K., Farinacci, D., Thaler, D., Fenner, W., "Protocol Independent Multicast MIB for IPv4", [RFC 2934](#), October 2000.