

Network Working Group
Internet-Draft
Expires: April 22, 2006

S. De Cnodder
Alcatel
N. Jonnala
M. Chiba
Cisco Systems, Inc.
October 19, 2005

Dynamic Authorization Client MIB
draft-ietf-radext-dynauth-client-mib-02.txt

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on April 22, 2006.

Copyright Notice

Copyright (C) The Internet Society (2005).

Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes the RADIUS Dynamic Authorization Client (DAC) functions that support the dynamic authorization extensions as defined in [RFC3576](#).

Table of Contents

1.	Introduction	3
1.1.	Requirements notation	3
1.2.	Terminology	3
2.	The Internet-Standard Management Framework	4
3.	Overview	5
4.	RADIUS Dynamic Authorization Client MIB Definitions	6
5.	Security Considerations	20
6.	IANA considerations	22
7.	Acknowledgements	23
8.	References	24
8.1.	Normative References	24
8.2.	Informative References	24
	Authors' Addresses	26
	Intellectual Property and Copyright Statements	27

1. Introduction

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. It is becoming increasingly important to support Dynamic Authorization extensions on the network access server (NAS) devices to handle the Disconnect and Change-of-Authorization (CoA) messages as described in [[RFC3576](#)]. As a result, the effective management of RADIUS Dynamic Authorization entities is of considerable importance. This RADIUS Dynamic Authorization Client MIB complements the managed objects used for managing RADIUS authentication and accounting servers as described in [[RFC2619](#)] and [[RFC2621](#)], respectively. The corresponding version neutral IP address MIBs [[RFC2619bis](#)] and [[RFC2621bis](#)] will obsolete (if approved) [[RFC2619](#)] and [[RFC2621](#)].

1.1. Requirements notation

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

1.2. Terminology

Dynamic Authorization Server (DAS)

The component that resides on the NAS which processes the Disconnect and Change-of-Authorization (CoA) Request packets [[RFC3576](#)] sent by the Dynamic Authorization Client.

Dynamic Authorization Client (DAC)

The component which sends Disconnect and CoA-Request packets to the Dynamic Authorization Server. While often residing on the RADIUS server, it is also possible for this component to be located on a separate host, such as a Rating Engine.

Dynamic Authorization Server Port

The UDP port on which the Dynamic Authorization Server listens for the Disconnect and CoA requests sent by the Dynamic Authorization Client.

2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of \[RFC3410\]](#).

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, [RFC2578 \[RFC2578\]](#), STD 58, [RFC2579 \[RFC2579\]](#) and STD 58, [RFC2580 \[RFC2580\]](#).

3. Overview

"Dynamic Authorization Extensions to RADIUS" [[RFC3576](#)] defines the operation of Disconnect-Request, Disconnect-ACK, Disconnect-NAK, CoA-Request, CoA-ACK and CoA-NAK packets. [[DYNSESV](#)] defines the Dynamic Authorization Server MIB and the relationship with other MIB modules. This MIB module for the Dynamic Authorization Client contains the following: This MIB module for the Dynamic Authorization Client contains the following:

1. Two scalar objects.
2. One Dynamic Authorization Server table. This table contains one row for each DAS that the DAC shares a secret with.

4. RADIUS Dynamic Authorization Client MIB Definitions

RADIUS-DYNAUTH-CLIENT-MIB DEFINITIONS ::= BEGIN

IMPORTS

```
MODULE-IDENTITY, OBJECT-TYPE,  
Counter32, Gauge32, Integer32,  
mib-2, TimeTicks      FROM SNMPv2-SMI          -- [RFC2578]  
SnmAdminString        FROM SNMP-FRAMEWORK-MIB -- [RFC3411]  
InetAddressType, InetAddress,  
InetPortNumber        FROM INET-ADDRESS-MIB    -- [RFC4001]  
MODULE-COMPLIANCE,  
OBJECT-GROUP FROM SNMPv2-CONF;                -- [RFC2580]
```

radiusDynAuthClientMIB MODULE-IDENTITY

LAST-UPDATED "200510160000Z" -- 16 October 2005

ORGANIZATION "IETF RADEXT Working Group"

CONTACT-INFO

" Stefaan De Cnodder
Alcatel
Francis Wellesplein 1
B-2018 Antwerp
Belgium

Phone: +32 3 240 85 15

EMail: stefaan.de_cnodder@alcatel.be

Nagi Reddy Jonnala
Cisco Systems, Inc.
Divyasree Chambers, B Wing,
O'Shaugnessy Road,
Bangalore-560027, India.

Phone: +91 98456 99445

EMail: njonnala@cisco.com

Murtaza Chiba
Cisco Systems, Inc.
170 West Tasman Dr.
San Jose CA, 95134

Phone: +1 408 525 7198

EMail: mchiba@cisco.com "

DESCRIPTION

"The MIB module for entities implementing the client side of the Dynamic Authorization extensions Remote Authentication Dial In User Service (RADIUS) protocol.

Copyright (C) The Internet Society (2005). This initial version of this MIB module was published in RFC yyyy; for full legal notices see the RFC itself. Supplementary information may be available on

<http://www.ietf.org/copyrights/ianamib.html>."

-- RFC Ed.: replace yyyy with actual RFC number & remove this note

REVISION "200510160000Z" -- 16 October 2005

DESCRIPTION "Initial version as published in RFC yyyy"

-- RFC Ed.: replace yyyy with actual RFC number & remove this note

::= { mib-2 xxx }

-- The value xxx to be assigned by IANA.

radiusDynAuthClientMIBObjects OBJECT IDENTIFIER ::=

{ radiusDynAuthClientMIB 1 }

radiusDynAuthClient OBJECT IDENTIFIER ::=

{ radiusDynAuthClientMIBObjects 1 }

radiusDynAuthClientDisconInvalidServerAddresses OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of Disconnect messages received from unknown addresses."

::= { radiusDynAuthClient 1 }

radiusDynAuthClientCoAInvalidServerAddresses OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of CoA messages received from unknown addresses."

::= { radiusDynAuthClient 2 }

radiusDynAuthServerTable OBJECT-TYPE

SYNTAX SEQUENCE OF RadiusDynAuthServerEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The (conceptual) table listing the RADIUS Dynamic Authorization Servers with which the client shares a secret."

::= { radiusDynAuthClient 3 }

radiusDynAuthServerEntry OBJECT-TYPE


```

SYNTAX      RadiusDynAuthServerEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "An entry (conceptual row) representing one Dynamic
    Authorization Server with which the client shares a
    secret."
INDEX       { radiusDynAuthServerIndex }
 ::= { radiusDynAuthServerTable 1 }

```

```

RadiusDynAuthServerEntry ::= SEQUENCE {
    radiusDynAuthServerIndex          Integer32,
    radiusDynAuthServerAddressType    InetAddressType,
    radiusDynAuthServerAddress        InetAddress,
    radiusDynAuthServerClientPortNumber  InetPortNumber,
    radiusDynAuthServerID              SnmpAdminString,
    radiusDynAuthClientRoundTripTime   TimeTicks,
    radiusDynAuthClientDisconRequests  Counter32,
    radiusDynAuthClientDisconAuthOnlyRequests  Counter32,
    radiusDynAuthClientDisconRetransmissions  Counter32,
    radiusDynAuthClientDisconAcks      Counter32,
    radiusDynAuthClientDisconNaks      Counter32,
    radiusDynAuthClientDisconNakAuthOnlyRequest  Counter32,
    radiusDynAuthClientDisconNakSessNoContext  Counter32,
    radiusDynAuthClientMalformedDisconResponses  Counter32,
    radiusDynAuthClientDisconBadAuthenticators  Counter32,
    radiusDynAuthClientDisconPendingRequests  Gauge32,
    radiusDynAuthClientDisconTimeouts  Counter32,
    radiusDynAuthClientDisconPacketsDropped  Counter32,
    radiusDynAuthClientCoARequests      Counter32,
    radiusDynAuthClientCoAAuthOnlyRequest  Counter32,
    radiusDynAuthClientCoARetransmissions  Counter32,
    radiusDynAuthClientCoAAcks          Counter32,
    radiusDynAuthClientCoANaks          Counter32,
    radiusDynAuthClientCoANakAuthOnlyRequest  Counter32,
    radiusDynAuthClientCoANakSessNoContext  Counter32,
    radiusDynAuthClientMalformedCoAResponses  Counter32,
    radiusDynAuthClientCoABadAuthenticators  Counter32,
    radiusDynAuthClientCoAPendingRequests  Gauge32,
    radiusDynAuthClientCoATimeouts      Counter32,
    radiusDynAuthClientCoAPacketsDropped  Counter32,
    radiusDynAuthClientUnknownTypes     Counter32
}

```

```

radiusDynAuthServerIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  not-accessible

```


STATUS current

DESCRIPTION

"A number uniquely identifying each RADIUS Dynamic Authorization Server with which this Dynamic Authorization Client communicates. This number is allocated by the agent implementing this MIB module, and is unique in this context."

::= { radiusDynAuthServerEntry 1 }

radiusDynAuthServerAddressType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The type of IP-Address of the RADIUS Dynamic Authorization Server referred to in this table entry."

::= { radiusDynAuthServerEntry 2 }

radiusDynAuthServerAddress OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The IP-Address value of the RADIUS Dynamic Authorization Server referred to in this table entry."

::= { radiusDynAuthServerEntry 3 }

radiusDynAuthServerClientPortNumber OBJECT-TYPE

SYNTAX InetPortNumber

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The UDP destination port that the RADIUS Dynamic Authorization Client is using to send requests to this server."

::= { radiusDynAuthServerEntry 4 }

radiusDynAuthServerID OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The NAS-Identifier of the RADIUS Dynamic Authorization Server referred to in this table entry."

REFERENCE

"[RFC 2865, Section 5.32](#), NAS-Identifier."


```
::= { radiusDynAuthServerEntry 5 }
```

radiusDynAuthClientRoundTripTime OBJECT-TYPE

SYNTAX TimeTicks

UNITS "hundredths of a second"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The time interval (in hundredths of a second) between the most recent Disconnect or CoA request and the reception of the corresponding Disconnect or CoA reply. A value of zero is returned in case no reply has been received yet from this server."

```
::= { radiusDynAuthServerEntry 6 }
```

radiusDynAuthClientDisconRequests OBJECT-TYPE

SYNTAX Counter32

UNITS "requests"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Disconnect-Requests sent to this Dynamic Authorization Server. This includes the RADIUS Disconnect-Requests that have a Service-Type attribute with value 'Authorize Only'."

REFERENCE

"[RFC 3576, Section 2.1](#), Disconnect Messages (DM)."

```
::= { radiusDynAuthServerEntry 7 }
```

radiusDynAuthClientDisconAuthOnlyRequests OBJECT-TYPE

SYNTAX Counter32

UNITS "requests"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Disconnect-Requests including a Service-Type attribute with value 'Authorize Only' sent to this Dynamic Authorization Server."

REFERENCE

"[RFC 3576, Section 2.1](#), Disconnect Messages (DM)."

```
::= { radiusDynAuthServerEntry 8 }
```

radiusDynAuthClientDisconRetransmissions OBJECT-TYPE

SYNTAX Counter32

UNITS "retransmissions"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Disconnect-request packets retransmitted to this RADIUS Dynamic Authorization Server."

REFERENCE

"[RFC 3576, Section 2.1](#), Disconnect Messages (DM)."

::= { radiusDynAuthServerEntry 9 }

radiusDynAuthClientDisconAcks OBJECT-TYPE

SYNTAX Counter32

UNITS "replies"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Disconnect-ACK packets received from this Dynamic Authorization Server"

REFERENCE

"[RFC 3576, Section 2.1](#), Disconnect Messages (DM)."

::= { radiusDynAuthServerEntry 10 }

radiusDynAuthClientDisconNaks OBJECT-TYPE

SYNTAX Counter32

UNITS "replies"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Disconnect-NAK packets received from this Dynamic Authorization Server. This includes the RADIUS Disconnect-NAK packets received with a Service-Type attribute with value 'Authorize Only' and the RADIUS Disconnect-NAK packets received no session context was found."

REFERENCE

"[RFC 3576, Section 2.1](#), Disconnect Messages (DM)."

::= { radiusDynAuthServerEntry 11 }

radiusDynAuthClientDisconNakAuthOnlyRequest OBJECT-TYPE

SYNTAX Counter32

UNITS "replies"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Disconnect-NAK packets including an Service-Type attribute with value 'Authorize Only' received from this Dynamic Authorization Server."

REFERENCE

"[RFC 3576, Section 2.1](#), Disconnect Messages (DM)."

::= { radiusDynAuthServerEntry 12 }

radiusDynAuthClientDisconNakSessNoContext OBJECT-TYPE

SYNTAX Counter32

UNITS "replies"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Disconnect-NAK packets received from this Dynamic Authorization Server because no session context was found, i.e. it includes an Error-Cause attribute with value 503 ('Session Context Not Found')."

REFERENCE

"[RFC 3576, Section 2.1](#), Disconnect Messages (DM)."

::= { radiusDynAuthServerEntry 13 }

radiusDynAuthClientMalformedDisconResponses OBJECT-TYPE

SYNTAX Counter32

UNITS "replies"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of malformed RADIUS Disconnect-Response packets received from this Dynamic Authorization Server. Bad authenticators and unknown types are not included as malformed Disconnect-Responses."

REFERENCE

"[RFC 3576, Section 2.1](#), Disconnect Messages (DM), and [Section 2.3](#), Packet Format."

::= { radiusDynAuthServerEntry 14 }

radiusDynAuthClientDisconBadAuthenticators OBJECT-TYPE

SYNTAX Counter32

UNITS "replies"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Disconnect-Response packets which contained invalid Authenticator field received from this Dynamic Authorization Server."

REFERENCE

"[RFC 3576, Section 2.1](#), Disconnect Messages (DM), and [Section 2.3](#), Packet Format."

::= { radiusDynAuthServerEntry 15 }

radiusDynAuthClientDisconPendingRequests OBJECT-TYPE

SYNTAX Gauge32

UNITS "requests"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Disconnect-request packets destined for this server that have not yet timed out or received a response. This variable is incremented when an Disconnect-Request is sent and decremented due to receipt of an Disconnect-Ack, Disconnect-NAK or a timeout or a retransmission."

REFERENCE

["RFC 3576, Section 2.1, Disconnect Messages \(DM\)."](#)

::= { radiusDynAuthServerEntry 16 }

radiusDynAuthClientDisconTimeouts OBJECT-TYPE

SYNTAX Counter32

UNITS "timeouts"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of Disconnect request timeouts to this server. After a timeout the client may retry to the same server or give up. A retry to the same server is counted as a retransmit as well as a timeout. A send to a different server is counted as a Disconnect-Request as well as a timeout."

REFERENCE

["RFC 3576, Section 2.1, Disconnect Messages \(DM\)."](#)

::= { radiusDynAuthServerEntry 17 }

radiusDynAuthClientDisconPacketsDropped OBJECT-TYPE

SYNTAX Counter32

UNITS "replies"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of incoming Disconnect-Responses from this Dynamic Authorization Server silently discarded by the client application for some reason other than malformed, bad authenticators or unknown types."

REFERENCE

["RFC 3576, Section 2.1, Disconnect Messages \(DM\), and Section 2.3, Packet Format."](#)

::= { radiusDynAuthServerEntry 18 }

radiusDynAuthClientCoARequests OBJECT-TYPE

SYNTAX Counter32

UNITS "requests"

MAX-ACCESS read-only

STATUS current
DESCRIPTION
 "The number of RADIUS CoA-Requests sent to this
 Dynamic Authorization Server. This includes
 the CoA requests that have a Service-Type attribute
 with value 'Authorize Only'."
REFERENCE
 "[RFC 3576, Section 2.2](#), Change-of-Authorization
 Messages (CoA)."
 ::= { radiusDynAuthServerEntry 19 }

radiusDynAuthClientCoAAuthOnlyRequest OBJECT-TYPE

SYNTAX Counter32
UNITS "requests"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of RADIUS CoA-requests including a
 Service-Type attribute with value 'Authorize Only'
 sent to this Dynamic Authorization Client."
REFERENCE
 "[RFC 3576, Section 2.2](#), Change-of-Authorization
 Messages (CoA)."
 ::= { radiusDynAuthServerEntry 20 }

radiusDynAuthClientCoARetransmissions OBJECT-TYPE

SYNTAX Counter32
UNITS "retransmissions"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of RADIUS CoA-request packets
 retransmitted to this RADIUS Dynamic Authorization
 Server."
REFERENCE
 "[RFC 3576, Section 2.2](#), Change-of-Authorization
 Messages (CoA)."
 ::= { radiusDynAuthServerEntry 21 }

radiusDynAuthClientCoAAcks OBJECT-TYPE

SYNTAX Counter32
UNITS "replies"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of RADIUS CoA-ACK packets
 received from this Dynamic Authorization Server"
REFERENCE

"[RFC 3576, Section 2.2](#), Change-of-Authorization
Messages (CoA)."
::= { radiusDynAuthServerEntry 22 }

radiusDynAuthClientCoANaks OBJECT-TYPE

SYNTAX Counter32
UNITS "replies"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of RADIUS CoA-NAK packets
received from this Dynamic Authorization Server.
This includes the RADIUS CoA-NAK packets received
with a Service-Type attribute with value 'Authorize
Only' and the RADIUS CoA-NAK packets received because
no session context was found."
REFERENCE
"[RFC 3576, Section 2.2](#), Change-of-Authorization
Messages (CoA)."
::= { radiusDynAuthServerEntry 23 }

radiusDynAuthClientCoANakAuthOnlyRequest OBJECT-TYPE

SYNTAX Counter32
UNITS "replies"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of RADIUS CoA-NAK packets including a
Service-Type attribute with value 'Authorize Only'
received from this Dynamic Authorization Server."
REFERENCE
"[RFC 3576, Section 2.2](#), Change-of-Authorization
Messages (CoA)."
::= { radiusDynAuthServerEntry 24 }

radiusDynAuthClientCoANakSessNoContext OBJECT-TYPE

SYNTAX Counter32
UNITS "replies"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of RADIUS CoA-NAK packets
received from this Dynamic Authorization Server
because no session context was found, i.e. it
includes an Error-Cause attribute with value 503
('Session Context Not Found')."
REFERENCE
"[RFC 3576, Section 2.2](#), Change-of-Authorization

Messages (CoA)."
 ::= { radiusDynAuthServerEntry 25 }

radiusDynAuthClientMalformedCoAResponses OBJECT-TYPE

SYNTAX Counter32
UNITS "replies"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of malformed RADIUS CoA-Response
 packets received from this Dynamic Authorization
 Server. Bad authenticators and unknown types are
 not included as malformed CoA-Responses."

REFERENCE

"[RFC 3576, Section 2.2](#), Change-of-Authorization
 Messages (CoA), and [Section 2.3](#), Packet Format."

::= { radiusDynAuthServerEntry 26 }

radiusDynAuthClientCoABadAuthenticators OBJECT-TYPE

SYNTAX Counter32
UNITS "replies"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of RADIUS CoA-Response packets
 which contained invalid Authenticator field
 received from this Dynamic Authorization Server."

REFERENCE

"[RFC 3576, Section 2.2](#), Change-of-Authorization
 Messages (CoA), and [Section 2.3](#), Packet Format."

::= { radiusDynAuthServerEntry 27 }

radiusDynAuthClientCoAPendingRequests OBJECT-TYPE

SYNTAX Gauge32
UNITS "requests"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of RADIUS CoA-request packets destined for
 this server that have not yet timed out or received a
 response. This variable is incremented when an
 CoA-Request is sent and decremented due to receipt of
 a CoA-Ack, CoA -NAK or a timeout or a retransmission."

REFERENCE

"[RFC 3576, Section 2.2](#), Change-of-Authorization
 Messages (CoA)."

::= { radiusDynAuthServerEntry 28 }

radiusDynAuthClientCoATimeouts OBJECT-TYPE

SYNTAX Counter32

UNITS "timeouts"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of CoA request timeouts to this server.
After a timeout the client may retry to the same
server or give up. A retry to the same server is
counted as a retransmit as well as a timeout. A send to
a different server is counted as a CoA-Request as well
as a timeout."

REFERENCE

"[RFC 3576, Section 2.2](#), Change-of-Authorization
Messages (CoA)."

::= { radiusDynAuthServerEntry 29 }

radiusDynAuthClientCoAPacketsDropped OBJECT-TYPE

SYNTAX Counter32

UNITS "replies"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of incoming CoA-Responses from this Dynamic
Authorization Server silently discarded by the client
application for some reason other than malformed, bad
authenticators or unknown types."

REFERENCE

"[RFC 3576, Section 2.2](#), Change-of-Authorization
Messages (CoA), and [Section 2.3](#), Packet Format."

::= { radiusDynAuthServerEntry 30 }

radiusDynAuthClientUnknownTypes OBJECT-TYPE

SYNTAX Counter32

UNITS "replies"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of incoming packets of unknown types
which were received on the Dynamic Authorization port."

REFERENCE

"[RFC 3576, Section 2.3](#), Packet Format."

::= { radiusDynAuthServerEntry 31 }

-- conformance information

radiusDynAuthClientMIBConformance

OBJECT IDENTIFIER ::= { radiusDynAuthClientMIB 2 }


```
radiusDynAuthClientMIBCompliances
    OBJECT IDENTIFIER ::= { radiusDynAuthClientMIBConformance 1 }
radiusDynAuthClientMIBGroups
    OBJECT IDENTIFIER ::= { radiusDynAuthClientMIBConformance 2 }

-- compliance statements

radiusDynAuthClientMIBCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "The compliance statement for entities implementing
        the RADIUS Dynamic Authorization Client."
    MODULE -- this module
    MANDATORY-GROUPS { radiusDynAuthClientMIBGroup }

    GROUP                radiusDynAuthClientAuthOnlyGroup
    DESCRIPTION
        "Only required for Dynamic Authorization Clients that
        are supporting Service-Type attributes with value
        'Authorize-Only'."

    GROUP                radiusDynAuthClientNoSessGroup
    DESCRIPTION
        "This group is not required in case the Dynamic
        Authorization Server can not easily determine whether
        a session exists or not (e.g., in case of a RADIUS
        proxy)."
```

```
 ::= { radiusDynAuthClientMIBCompliances 1 }
```

```
-- units of conformance

radiusDynAuthClientMIBGroup OBJECT-GROUP
    OBJECTS { radiusDynAuthClientDisconInvalidServerAddresses,
               radiusDynAuthClientCoAInvalidServerAddresses,
               radiusDynAuthServerAddressType,
               radiusDynAuthServerAddress,
               radiusDynAuthServerClientPortNumber,
               radiusDynAuthServerID,
               radiusDynAuthClientRoundTripTime,
               radiusDynAuthClientDisconRequests,
               radiusDynAuthClientDisconRetransmissions,
               radiusDynAuthClientDisconAcks,
               radiusDynAuthClientDisconNaks,
               radiusDynAuthClientMalformedDisconResponses,
               radiusDynAuthClientDisconBadAuthenticators,
               radiusDynAuthClientDisconPendingRequests,
```



```
        radiusDynAuthClientDisconTimeouts,
        radiusDynAuthClientDisconPacketsDropped,
        radiusDynAuthClientCoARequests,
        radiusDynAuthClientCoARetransmissions,
        radiusDynAuthClientCoAAcks,
        radiusDynAuthClientCoANaks,
        radiusDynAuthClientMalformedCoAResponses,
        radiusDynAuthClientCoABadAuthenticators,
        radiusDynAuthClientCoAPendingRequests,
        radiusDynAuthClientCoATimeouts,
        radiusDynAuthClientCoAPacketsDropped,
        radiusDynAuthClientUnknownTypes
    }
    STATUS    current
    DESCRIPTION
        "The collection of objects providing management of
        a RADIUS Dynamic Authorization Client."
    ::= { radiusDynAuthClientMIBGroups 1 }

radiusDynAuthClientAuthOnlyGroup OBJECT-GROUP
    OBJECTS { radiusDynAuthClientDisconAuthOnlyRequests,
        radiusDynAuthClientDisconNakAuthOnlyRequest,
        radiusDynAuthClientCoAAuthOnlyRequest,
        radiusDynAuthClientCoANakAuthOnlyRequest
    }
    STATUS    current
    DESCRIPTION
        "The collection of objects supporting the RADIUS
        messages including Service-Type attribute with
        value 'Authorize Only'."
    ::= { radiusDynAuthClientMIBGroups 2 }

radiusDynAuthClientNoSessGroup OBJECT-GROUP
    OBJECTS { radiusDynAuthClientDisconNakSessNoContext,
        radiusDynAuthClientCoANakSessNoContext
    }
    STATUS    current
    DESCRIPTION
        "The collection of objects supporting the RADIUS
        messages that are referring to non existing sessions."
    ::= { radiusDynAuthClientMIBGroups 3 }
```

END

5. Security Considerations

There are no management objects defined in this MIB module that have a MAX-ACCESS clause of read-write and/or read-create. So, if this MIB module is implemented correctly, then there is no risk that an intruder can alter or create any management objects of this MIB module via direct SNMP SET operations

Some of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP. These are the tables and objects and their sensitivity/vulnerability:

radiusDynAuthServerAddress and radiusDynAuthServerAddressType

These can be used to determine the address of the DAS with which the DAC is communicating. This information could be useful in mounting an attack on the DAS.

radiusDynAuthServerID

This can be used to determine the Identifier of the DAS. This information could be useful in impersonating the DAS.

radiusDynAuthServerClientPortNumber

This can be used to determine the destination port number to which the DAC is sending. This information could be useful in mounting an attack on the DAS.

The other readable objects are not really considered as being sensitive or vulnerable. These objects are:

radiusDynAuthClientDisconInvalidServerAddresses,
radiusDynAuthClientCoAInvalidServerAddresses,
radiusDynAuthClientRoundTripTime,
radiusDynAuthClientDisconRequests,
radiusDynAuthClientDisconAuthOnlyRequests,
radiusDynAuthClientDisconRetransmissions,
radiusDynAuthClientDisconAcks,
radiusDynAuthClientDisconNaks,
radiusDynAuthClientDisconNakAuthOnlyRequest,
radiusDynAuthClientDisconNakSessNoContext,
radiusDynAuthClientMalformedDisconResponses,
radiusDynAuthClientDisconBadAuthenticators,
radiusDynAuthClientDisconPendingRequests,
radiusDynAuthClientDisconTimeouts,
radiusDynAuthClientDisconPacketsDropped,
radiusDynAuthClientCoARequests,
radiusDynAuthClientCoAAuthOnlyRequest,
radiusDynAuthClientCoARetranmissions,
radiusDynAuthClientCoAAcks,
radiusDynAuthClientCoANaks,
radiusDynAuthClientCoANakAuthOnlyRequest,
radiusDynAuthClientCoANakSessNoContext,
radiusDynAuthClientMalformedCoAResponses,
radiusDynAuthClientCoABadAuthenticators,
radiusDynAuthClientCoAPendingRequests,
radiusDynAuthClientCoATimeouts,
radiusDynAuthClientCoAPacketsDropped, and
radiusDynAuthClientUnknownTypes.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPSec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [\[RFC3410\]](#), [section 8](#)), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

6. IANA considerations

IANA is requested to assign an OID under mib-2.

7. Acknowledgements

This document reuses some of the work done in earlier RADIUS MIB specifications [[RFC2619](#)] and [[RFC2621](#)].

The authors would also like to acknowledge the following people for their comments to this document: Anjaneyulu Pata, Dan Romascanu, Bert Wijnen, Bernard Aboba, David Nelson, Greg Weber and Glen Zorn.

8. References

8.1. Normative References

- [DYN SERV] De Cnodder, S., Jonnala, N., and M. Chiba, "RADIUS Dynamic Authorization Server MIB", [draft-decnodder-radext-dynauth-server-mib-02.txt](#), work in progress, September 2005.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [RFC 2119](#), March 1997.
- [RFC2578] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M., and S. Waldbusser, "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), April 1999.
- [RFC2579] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M., and S. Waldbusser, "Textual Conventions for SMIv2", STD 58, [RFC 2579](#), April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M., and S. Waldbusser, "Conformance Statements for SMIv2", STD 58, [RFC 2580](#), April 1999.
- [RFC3411] Harrington, D., Presuhn, R., and B. Wijnen, "An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks", STD 62, [RFC 3411](#), December 2002.
- [RFC3576] Chiba, M., Dommety, G., Eklund, M., Mitton, D., and B. Aboba, "Dynamic Authorization Extensions to Remote Authentication Dial In User Service (RADIUS)", [RFC 3576](#), July 2003.
- [RFC4001] Daniele, M. and et al., "Textual Conventions for Internet Network Addresses", [RFC 4001](#), February 2005.

8.2. Informative References

- [RFC2619] Zorn, G. and B. Aboba, "RADIUS Authentication Server MIB", [RFC 2619](#), June 1999.
- [RFC2619bis] Nelson, D., "RADIUS Auth Server MIB (IPv6)", [draft-ietf-radext-rfc2619bis-00.txt](#) work in progress, August 2005.

[RFC2621] Zorn, G. and B. Aboba, "RADIUS Accounting Server MIB",
[RFC 2621](#), June 1999.

[RFC2621bis]

Nelson, D., "RADIUS Acct Server MIB (IPv6)",
[draft-ietf-radext-rfc2621bis-00.txt](#) work in progress,
August 2005.

[RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart,
"Introduction and Applicability Statements for Internet
Standard Management Framework", [RFC 3410](#), December 2002.

Authors' Addresses

Stefaan De Cnodder
Alcatel
Francis Wellesplein 1
B-2018 Antwerp
Belgium

Phone: +32 3 240 85 15
Email: stefaan.de_cnodder@alcatel.be

Nagi Reddy Jonnala
Cisco Systems, Inc.
Divyasree Chambers, B Wing, O'Shaugnessy Road
Bangalore-560027, India

Phone: +91 98456 99445
Email: njonnala@cisco.com

Murtaza Chiba
Cisco Systems, Inc.
170 West Tasman Dr.
San Jose CA, 95134

Phone: +1 408 525 7198
Email: mchiba@cisco.com

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The Internet Society (2005). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.

