

Network Working Group
INTERNET-DRAFT
Category: Proposed Standard
<[draft-ietf-radext-filter-07.txt](#)>
[10](#) January 2007

Paul Congdon
Mauricio Sanchez
Hewlett-Packard Company
Bernard Aboba
Microsoft Corporation

RADIUS Filter Rule Attribute

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on July 10, 2007.

Copyright Notice

Copyright (C) The IETF Trust (2007). All rights reserved.

Abstract

While [RFC 2865](#) defines the Filter-Id attribute, this requires that the Network Access Server (NAS) be pre-populated with the desired filters. However, in situations where the server operator does not know which filters have been pre-populated, it is useful to specify filter rules explicitly. This document defines the NAS-Filter-Rule attribute within the Remote Authentication Dial In User Service (RADIUS). This attribute is based on the Diameter NAS-Filter-Rule Attribute Value Pair (AVP) described in [RFC 4005](#), and the IPFilterRule syntax defined in [RFC 3588](#).

INTERNET-DRAFT

Filter Rule Attribute

10 January 2007

Table of Contents

1.	Introduction	3
1.1	Terminology	3
1.2	Requirements Language	3
1.3	Attribute Interpretation	3
2.	NAS-Filter-Rule Attribute	4
3.	Table of Attributes	5
4.	Diameter Considerations	5
5.	IANA Considerations	6
6.	Security Considerations	6
7.	References	7
7.1	Normative References	7
7.2	Informative References	7
	ACKNOWLEDGMENTS	8
	AUTHORS' ADDRESSES	8
	Intellectual Property Statement.....	9
	Disclaimer of Validity.....	9
	Full Copyright Statement	9

INTERNET-DRAFT

Filter Rule Attribute

10 January 2007

1. Introduction

This document defines the NAS-Filter-Rule attribute within the Remote Authentication Dialin User Service (RADIUS). This attribute has the same functionality as the Diameter NAS-Filter-Rule AVP (400) defined in [\[RFC4005\] Section 6.6](#) and the same syntax as an IPFilterRule defined in [\[RFC3588\] Section 4.3](#). This attribute may prove useful for provisioning of filter rules.

While [\[RFC2865\] Section 5.11](#) defines the Filter-Id attribute (11), this requires that the Network Access Server (NAS) be pre-populated with the desired filters. However, in situations where the server operator does not know which filters have been pre-populated, it useful to specify filter rules explicitly.

1.1. Terminology

This document uses the following terms:

Network Access Server (NAS)

A device that provides an access service for a user to a network.

RADIUS server

A RADIUS authentication server is an entity that provides an authentication service to a NAS.

RADIUS proxy

A RADIUS proxy acts as an authentication server to the NAS, and a RADIUS client to the RADIUS server.

1.2. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [\[RFC2119\]](#).

1.3. Attribute Interpretation

If a NAS conforming to this specification receives an Access-Accept packet containing a NAS-Filter-Rule attribute which it cannot apply, it MUST act as though it had received an Access-Reject. [RFC3576] requires that a NAS receiving a Change of Authorization Request (CoA-Request) reply with a CoA-NAK if the Request contains an unsupported attribute. It is RECOMMENDED that an Error-Cause attribute with value set to "Unsupported Attribute" (401) be included in the CoA-NAK. As noted in [RFC3576], authorization changes are atomic so that this situation does not result in session termination and the pre-existing configuration remains unchanged. As a result,

no accounting packets should be generated as a result of the CoA-Request.

2. NAS-Filter-Rule Attribute

Description


This attribute indicates filter rules to be applied for this user. Zero or more NAS-Filter-Rule attributes MAY be sent in Access-Accept, CoA-Request, or Accounting-Request packets.

The NAS-Filter-Rule attribute is not intended to be used concurrently with any other filter rule attribute, including Filter-Id (11) and NAS-Traffic-Rule [Traffic] attributes. NAS-Filter-Rule and NAS-Traffic-Rule attributes MUST NOT appear in the same RADIUS packet. If a NAS-Traffic-Rule attribute is present, a NAS implementing this specification MUST silently discard NAS-Filter-Rule attributes, if present. Filter-Id and NAS-Filter-Rule attributes SHOULD NOT appear in the same RADIUS packet. Given the absence in [RFC4005] of well-defined precedence rules for combining Filter-Id and NAS-Filter-Rule attributes into a single rule set, the behavior of NASes receiving both attributes is undefined, and therefore a RADIUS server implementation cannot assume a consistent behavior.

Where multiple NAS-Filter-Rule attributes are included in a RADIUS packet, the String field of the attributes are to be concatenated to form a set of filter rules. As noted in [RFC2865] Section 2.3, "the forwarding server MUST NOT change the order of any attributes

of the same type", so that RADIUS proxies will not reorder NAS-Filter-Rule attributes.

A summary of the NAS-Filter-Rule Attribute format is shown below. The fields are transmitted from left to right.



Type

TBD

Length

>=3

String

The String field is one or more octets. It contains filter rules in the IPFilterRule syntax defined in [\[RFC3588\] Section 4.3](#), with individual filter rules separated by a NUL (0x00). A NAS-Filter-Rule attribute may contain a partial rule, one rule, or more than one rule. Filter rules may be continued across attribute boundaries, so implementations cannot assume that individual filter rules begin or end on attribute boundaries.

The set of NAS-Filter-Rule attributes SHOULD be created by concatenating the individual filter rules, separated by a NUL (0x00) octet. The resulting data should be split on 253 byte boundaries to obtain a set of NAS-Filter-Rule attributes. On reception, the individual filter rules are determined by concatenating the contents of all NAS-Filter-Rule attributes, and then splitting individual filter rules with the the NUL octet (0x00) as a delimiter.

3. Table of Attributes

The following table provides a guide to which attributes may be found

in which kinds of packets, and in what quantity.

Access-Request	Access-Accept	Access-Reject	Access-Challenge	CoA-Req	Acct-Req	#	Attribute
0	0+	0	0	0+	0+	TBD	NAS-Filter-Rule

The following table defines the meaning of the above table entries.

- 0 This attribute MUST NOT be present in the packet.
- 0+ Zero or more instances of this attribute MAY be present in the packet.
- 0-1 Zero or one instance of this attribute MAY be present in the packet.

4. Diameter Considerations

[RFC4005] [Section 6.6](#) defines the NAS-Filter-Rule AVP (400) with the same functionality as the RADIUS NAS-Filter-Rule attribute. In order to support interoperability, Diameter/RADIUS gateways will need to be configured to translate RADIUS attribute TBD to Diameter AVP 400 and vice-versa.

When translating Diameter NAS-Filter-Rule AVPs to RADIUS NAS-Filter-Rule attributes, the set of NAS-Filter-Rule attributes is created by concatenating the individual filter rules, separated by a NUL octet. The resulting data SHOULD then be split on 253 byte boundaries.

When translating RADIUS NAS-Filter-Rule attributes to Diameter NAS-Filter-Rule AVPs, the individual rules are determined by concatenating the contents of all NAS-Filter-Rule attributes, and then splitting individual filter rules with the NUL octet as a delimiter. Each rule is then encoded as a single Diameter NAS-Filter-Rule AVP.

Note that a translated Diameter message can be larger than the maximum RADIUS packet size (4096). Where a Diameter/RADIUS gateway receives a Diameter message containing a NAS-Filter-Rule AVP that is too large to fit into a RADIUS packet, the Diameter/RADIUS gateway will respond to the originating Diameter peer with a Result-Code AVP with the value DIAMETER_RADIUS_AVP_UNTRANSLATABLE (TBD), and with a Failed-AVP AVP containing the NAS-Filter-Rule AVP. Since repairing the error will probably require re-working the filter rules, the

originating peer should treat the combination of a Result-Code AVP with value DIAMETER_RADIUS_AVP_UNTRANSLATABLE and a Failed-AVP AVP containing a NAS-Filter-Rule AVP as a terminal error.

5. IANA Considerations

This specification does not create any new registries.

This document uses the RADIUS [[RFC2865](#)] namespace, see <http://www.iana.org/assignments/radius-types>. Allocation of one update for the section "RADIUS Attribute Types" is requested. The RADIUS attribute for which a value is requested is:

TBD - NAS-Filter-Rule

This document also utilizes the Diameter [[RFC3588](#)] namespace. Allocation of a Diameter Result-Code AVP value for the DIAMETER_RADIUS_AVP_UNTRANSLATABLE error is requested. Since this is a permanent failure, an allocation should be provided in the 5xxx range.

6. Security Considerations

This specification describes the use of RADIUS for purposes of authentication, authorization and accounting. Threats and security issues for this application are described in [[RFC3579](#)] and [[RFC3580](#)]; security issues encountered in roaming are described in [[RFC2607](#)].

This document specifies a new attribute that can be included in existing RADIUS packets, which are protected as described in [[RFC3579](#)] and [[RFC3576](#)]. See those documents for a more detailed description.

A NAS-Filter-Rule attribute sent by a RADIUS server may not be understood by the NAS which receives it. A legacy NAS not compliant with this specification may silently discard the NAS-Filter-Rule attribute while permitting the user to access the network. This can lead to users improperly receiving unfiltered access to the network. As a result, the NAS-Filter-Rule attribute SHOULD only be sent to a NAS that is known to support it.

[7.](#) References

[7.1.](#) Normative references

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [RFC 2119](#), March, 1997.
- [RFC2865] Rigney, C., Rubens, A., Simpson, W. and S. Willens, "Remote Authentication Dial In User Service (RADIUS)", [RFC 2865](#), June 2000.
- [RFC3588] Calhoun, P., Loughney, J., Guttman, E., Zorn, G., and J. Arkko, "Diameter Base Protocol", [RFC 3588](#), September 2003.
- [RFC4005] Calhoun, P., Zorn, G., Spence, D. and D. Mitton, "Diameter Network Access Server Application", [RFC 4005](#), August 2005.

[7.2.](#) Informative references

- [RFC2607] Aboba, B. and J. Vollbrecht, "Proxy Chaining and Policy Implementation in Roaming", [RFC 2607](#), June 1999.
- [RFC3576] Chiba, M., Dommety, G., Eklund, M., Mitton, D. and B. Aboba, "Dynamic Authorization Extensions to Remote Authentication Dial In User Service (RADIUS)", [RFC 3576](#), July 2003.
- [RFC3579] Aboba, B. and P. Calhoun, "RADIUS Support for Extensible Authentication Protocol (EAP)", [RFC 3579](#), September 2003.
- [RFC3580] Congdon, P., Aboba, B., Smith, A., Zorn, G., Roese, J., "IEEE 802.1X Remote Authentication Dial In User Service (RADIUS) Usage Guidelines", [RFC3580](#), September 2003.
- [Traffic] Congdon, P., Sanchez, M., Lior, A., Adrangi, F. and B. Aboba, "RADIUS Attributes for Filtering and Redirection", Internet draft (work in progress), [draft-ietf-radext-filter-rules-01.txt](#), June 2006.

The authors would like to acknowledge Emile Bergen, Alan DeKok, Greg Weber, Glen Zorn, Pasi Eronen, David Mitton and David Nelson for contributions to this document.

Authors' Addresses

Paul Congdon
Hewlett Packard Company
HP ProCurve Networking
8000 Foothills Blvd, M/S 5662
Roseville, CA 95747

E-Mail: paul.congdon@hp.com
Phone: +1 916 785 5753
Fax: +1 916 785 8478

Mauricio Sanchez
Hewlett Packard Company
HP ProCurve Networking
8000 Foothills Blvd, M/S 5559
Roseville, CA 95747

E-Mail: mauricio.sanchez@hp.com
Phone: +1 916 785 1910
Fax: +1 916 785 1815

Bernard Aboba
Microsoft Corporation
One Microsoft Way
Redmond, WA 98052

E-Mail: bernarda@microsoft.com
Phone: +1 425 706 6605
Fax: +1 425 936 7329

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY, THE IETF TRUST AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The IETF Trust (2007). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.

INTERNET-DRAFT

Filter Rule Attribute

10 January 2007

Open issues

Open issues relating to this specification are tracked on the following web site:

<http://www.drizzle.com/~aboba/RADEXT/>

