

Network Working Group
Internet-Draft
Obsoletes: RFC [2619](#) (if approved)
Expires: July 24, 2006

D. Nelson
Enterasys Networks
January 20, 2006

RADIUS Auth Server MIB (IPv6)
draft-ietf-radext-rfc2619bis-02.txt

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at
<http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at
<http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on July 24, 2006.

Copyright Notice

Copyright (C) The Internet Society (2006).

Abstract

This memo defines a set of extensions which instrument RADIUS authentication server functions. These extensions represent a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. Using these extensions IP-based management stations can manage RADIUS authentication servers.

This memo obsoletes [RFC 2619](#) by deprecating the MIB table containing

IPv4-only address formats and defining a new table to add support for version neutral IP address formats. The remaining MIB objects from [RFC 2619](#) are carried forward into this document. This memo also adds UNITS and Reference clauses to selected objects.

Table of Contents

1.	Terminology	3
2.	Introduction	3
3.	The Internet-Standard Management Framework	3
4.	Scope of Changes	3
5.	Structure of the MIB Module	4
6.	Deprecated Objects	5
7.	Definitions	5
8.	IANA Considerations	20
9.	Security Considerations	20
10.	References	21
10.1.	Normative References	21
10.2.	Informative References	22
Appendix A.	Acknowledgments	22
	Author's Address	24
	Intellectual Property and Copyright Statements	25

1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

This document uses terminology from [RFC 2865](#) [[RFC2865](#)].

This document uses the word "malformed" with respect to RADIUS packets, particularly in the context of counters of "malformed packets". While [RFC 2865](#) does not provide an explicit definition of "malformed", malformed generally means that the implementation has determined the packet does not match the format defined in [RFC 2865](#). Some implementations may determine that packets are malformed when the Vendor Specific Attribute (VSA) format does not follow the [RFC 2865](#) recommendations for VSAs. Those implementations are used in deployments today, and thus set the de-facto definition of "malformed".

2. Introduction

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. The objects defined within this memo relate to the Remote Authentication Dial-In User Service (RADIUS) Authentication Server as defined in [RFC 2865](#) [[RFC2865](#)].

3. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [[RFC3410](#)].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, [RFC 2578](#) [[RFC2578](#)], STD 58, [RFC 2579](#) [[RFC2579](#)] and STD 58, [RFC 2580](#) [[RFC2580](#)].

4. Scope of Changes

This document obsoletes [RFC 2619](#) [[RFC2619](#)], RADIUS Authentication

Nelson

Expires July 24, 2006

[Page 3]

Server MIB, by deprecating the radiusAuthClientTable table and adding a new table, radiusAuthClientExtTable, containing radiusAuthClientInetAddressType and radiusAuthClientInetAddress. The purpose of these added MIB objects is to support version neutral IP addressing formats. The existing table containing radiusAuthClientAddress is deprecated. The remaining MIB objects from [RFC 2619](#) are carried forward into this document. This memo also adds UNITS and REFERENCE clauses to selected objects.

[RFC 4001](#) [[RFC4001](#)], which defines the SMI Textual Conventions for version neutral IP addresses, contains the following recommendation.

'In particular, when revising a MIB module that contains IPv4 specific tables, it is suggested to define new tables using the textual conventions defined in this memo [[RFC 4001](#)] that support all versions of IP. The status of the new tables SHOULD be "current", whereas the status of the old IP version specific tables SHOULD be changed to "deprecated". The other approach, of having multiple similar tables for different IP versions, is strongly discouraged.'

5. Structure of the MIB Module

The RADIUS authentication protocol, described in [RFC 2865](#) [[RFC2865](#)], distinguishes between the client function and the server function. In RADIUS authentication, clients send Access-Requests, and servers reply with Access-Accepts, Access-Rejects, and Access-Challenges. Typically NAS devices implement the client function, and thus would be expected to implement the RADIUS authentication client MIB, while RADIUS authentication servers implement the server function, and thus would be expected to implement the RADIUS authentication server MIB.

However, it is possible for a RADIUS authentication entity to perform both client and server functions. For example, a RADIUS proxy may act as a server to one or more RADIUS authentication clients, while simultaneously acting as an authentication client to one or more authentication servers. In such situations, it is expected that RADIUS entities combining client and server functionality will support both the client and server MIBs.

This MIB module contains fourteen scalars as well as a single table, the RADIUS Authentication Client Table, which contains one row for each RADIUS authentication client with which the server shares a secret. Each entry in the RADIUS Authentication Client Table includes twelve columns presenting a view of the activity of the RADIUS authentication server.

6. Deprecated Objects

The deprecated table in this MIB is carried forward from [RFC 2619](#) [[RFC2619](#)]. There are two conditions under which it MAY be desirable for managed entities to continue to support the deprecated table:

1. The managed entity only supports IPv4 address formats.
2. The managed entity supports both IPv4 and IPv6 address formats, and the deprecated table is supported for backwards compatibility with older management stations. This option SHOULD only be used when the IP addresses in the new table are in IPv4 format and can accurately be represented in both the new table and the deprecated table.

Managed entities SHOULD NOT instantiate row entries in the deprecated table, containing IPv4-only address objects, when the RADIUS client address represented in such a table row is not an IPv4 address. Managed entities SHOULD NOT return inaccurate values of IP address or SNMP object access errors for IPv4-only address objects in otherwise populated tables. When row entries exist in both the deprecated IPv4-only table and the new IP version neutral table that describe the same RADIUS client, the row indexes SHOULD be the same for the corresponding rows in each table, to facilitate correlation of these related rows by management applications.

7. Definitions

```
RADIUS-AUTH-SERVER-MIB DEFINITIONS ::= BEGIN
```

```
IMPORTS
```

```
    MODULE-IDENTITY, OBJECT-TYPE, OBJECT-IDENTITY,
    Counter32, Integer32,
    IpAddress, TimeTicks, mib-2          FROM SNMPv2-SMI
    SnmpAdminString                     FROM SNMP-FRAMEWORK-MIB
    InetAddressType, InetAddress        FROM INET-ADDRESS-MIB
    MODULE-COMPLIANCE, OBJECT-GROUP    FROM SNMPv2-CONF;
```

```
radiusAuthServMIB MODULE-IDENTITY
```

```
    LAST-UPDATED "200601200000Z" -- 20 Jan 2006
    ORGANIZATION "IETF RADIUS Extensions Working Group."
    CONTACT-INFO
        " Bernard Aboba
        Microsoft
        One Microsoft Way
        Redmond, WA 98052
        US
        Phone: +1 425 936 6605
```


EMail: bernarda@microsoft.com"

DESCRIPTION

"The MIB module for entities implementing the server side of the Remote Authentication Dial-In User Service (RADIUS) authentication protocol."

REVISION "200601200000Z" -- 20 Jan 2006

DESCRIPTION "Revised version as published in RFC xxxx. This version obsoletes that of [RFC 2619](#) by deprecating the MIB table containing IPv4-only address formats and defining a new table to add support for version neutral IP address formats. The remaining MIB objects from [RFC 2619](#) are carried forward into this version."

REVISION "9906110000Z" -- 11 Jun 1999

DESCRIPTION "Initial version as published in [RFC 2619](#)."

-- RFC Editor: replace xxxx with actual RFC number at the time of
-- publication, and remove this note.

::= { radiusAuthentication 1 }

radiusMIB OBJECT-IDENTITY

STATUS current

DESCRIPTION

"The OID assigned to RADIUS MIB work by the IANA."

::= { mib-2 67 }

radiusAuthentication OBJECT IDENTIFIER ::= {radiusMIB 1}

radiusAuthServMIBObjects OBJECT IDENTIFIER

::= { radiusAuthServMIB 1 }

radiusAuthServ OBJECT IDENTIFIER

::= { radiusAuthServMIBObjects 1 }

radiusAuthServIdent OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The implementation identification string for the RADIUS authentication server software in use on the system, for example; `FNS-2.1'"

::= {radiusAuthServ 1}

radiusAuthServUpTime OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"If the server has a persistent state (e.g., a process), this value will be the time elapsed (in hundredths of a second) since the server process was started. For software without persistent state, this value will be zero."

::= {radiusAuthServ 2}

radiusAuthServResetTime OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"If the server has a persistent state (e.g., a process) and supports a 'reset' operation (e.g., can be told to re-read configuration files), this value will be the time elapsed (in hundredths of a second) since the server was 'reset.' For software that does not have persistence or does not support a 'reset' operation, this value will be zero."

::= {radiusAuthServ 3}

radiusAuthServConfigReset OBJECT-TYPE

SYNTAX INTEGER { other(1),
reset(2),
initializing(3),
running(4)}

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"Status/action object to reinitialize any persistent server state. When set to reset(2), any persistent server state (such as a process) is reinitialized as if the server had just been started. This value will never be returned by a read operation. When read, one of the following values will be returned:
other(1) - server in some unknown state;
initializing(3) - server (re)initializing;
running(4) - server currently running."

::= {radiusAuthServ 4}

radiusAuthServTotalAccessRequests OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

Nelson

Expires July 24, 2006

[Page 7]

"The number of packets received on the authentication port."

REFERENCE "[RFC 2865 section 4.1](#)"

::= { radiusAuthServ 5 }

radiusAuthServTotalInvalidRequests OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Access-Request packets received from unknown addresses."

REFERENCE "[RFC 2865 section 4.1](#)"

::= { radiusAuthServ 6 }

radiusAuthServTotalDupAccessRequests OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of duplicate RADIUS Access-Request packets received."

REFERENCE "[RFC 2865 section 4.1](#)"

::= { radiusAuthServ 7 }

radiusAuthServTotalAccessAccepts OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Access-Accept packets sent."

REFERENCE "[RFC 2865 section 4.2](#)"

::= { radiusAuthServ 8 }

radiusAuthServTotalAccessRejects OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Access-Reject packets sent."

REFERENCE "[RFC 2865 section 4.3](#)"

::= { radiusAuthServ 9 }

radiusAuthServTotalAccessChallenges OBJECT-TYPE

Nelson

Expires July 24, 2006

[Page 8]

SYNTAX Counter32
UNITS "packets"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of RADIUS Access-Challenge packets sent."
REFERENCE "[RFC 2865 section 4.4](#)"
::= { radiusAuthServ 10 }

radiusAuthServTotalMalformedAccessRequests OBJECT-TYPE

SYNTAX Counter32
UNITS "packets"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of malformed RADIUS Access-Request
 packets received. Bad authenticators
 and unknown types are not included as
 malformed Access-Requests."
REFERENCE "[RFC 2865 section 4.1](#)"
::= { radiusAuthServ 11 }

radiusAuthServTotalBadAuthenticators OBJECT-TYPE

SYNTAX Counter32
UNITS "packets"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of RADIUS Authentication-Request packets
 which contained invalid Message Authenticator
 attributes received."
REFERENCE "[RFC 2865 section 3](#)"
::= { radiusAuthServ 12 }

radiusAuthServTotalPacketsDropped OBJECT-TYPE

SYNTAX Counter32
UNITS "packets"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of incoming packets
 silently discarded for some reason other
 than malformed, bad authenticators or
 unknown types."
REFERENCE "[RFC 2865 section 3](#)"
::= { radiusAuthServ 13 }

radiusAuthServTotalUnknownTypes OBJECT-TYPE

Nelson

Expires July 24, 2006

[Page 9]

SYNTAX Counter32
UNITS "packets"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of RADIUS packets of unknown type which
 were received."
REFERENCE "[RFC 2865 section 4](#)"
::= { radiusAuthServ 14 }

radiusAuthClientTable OBJECT-TYPE
 SYNTAX SEQUENCE OF RadiusAuthClientEntry
 MAX-ACCESS not-accessible
 STATUS deprecated
 DESCRIPTION
 "The (conceptual) table listing the RADIUS
 authentication clients with which the server shares
 a secret."
 ::= { radiusAuthServ 15 }

radiusAuthClientEntry OBJECT-TYPE
 SYNTAX RadiusAuthClientEntry
 MAX-ACCESS not-accessible
 STATUS deprecated
 DESCRIPTION
 "An entry (conceptual row) representing a RADIUS
 authentication client with which the server shares a
 secret."
 INDEX { radiusAuthClientIndex }
 ::= { radiusAuthClientTable 1 }

RadiusAuthClientEntry ::= SEQUENCE {
 radiusAuthClientIndex Integer32,
 radiusAuthClientAddress IpAddress,
 radiusAuthClientID SnmpAdminString,
 radiusAuthServAccessRequests Counter32,
 radiusAuthServDupAccessRequests Counter32,
 radiusAuthServAccessAccepts Counter32,
 radiusAuthServAccessRejects Counter32,
 radiusAuthServAccessChallenges Counter32,
 radiusAuthServMalformedAccessRequests Counter32,
 radiusAuthServBadAuthenticators Counter32,
 radiusAuthServPacketsDropped Counter32,
 radiusAuthServUnknownTypes Counter32
}

Nelson

Expires July 24, 2006

[Page 10]

radiusAuthClientIndex OBJECT-TYPE

SYNTAX Integer32 (1..2147483647)

MAX-ACCESS not-accessible

STATUS deprecated

DESCRIPTION

"A number uniquely identifying each RADIUS authentication client with which this server communicates."

::= { radiusAuthClientEntry 1 }

radiusAuthClientAddress OBJECT-TYPE

SYNTAX IPAddress

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The NAS-IP-Address of the RADIUS authentication client referred to in this table entry."

REFERENCE "[RFC 2865 section 2](#)"

::= { radiusAuthClientEntry 2 }

radiusAuthClientID OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The NAS-Identifier of the RADIUS authentication client referred to in this table entry. This is not necessarily the same as sysName in MIB II."

REFERENCE "[RFC 2865 section 5.32](#)"

::= { radiusAuthClientEntry 3 }

-- Server Counters

--

-- Responses = AccessAccepts + AccessRejects + AccessChallenges

--

-- Requests - DupRequests - BadAuthenticators - MalformedRequests -

-- UnknownTypes - PacketsDropped - Responses = Pending

--

-- Requests - DupRequests - BadAuthenticators - MalformedRequests -

-- UnknownTypes - PacketsDropped = entries logged

radiusAuthServAccessRequests OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

Nelson

Expires July 24, 2006

[Page 11]

"The number of packets received on the authentication
 port from this client."
REFERENCE ["RFC 2865 section 4.1"](#)
::= { radiusAuthClientEntry 4 }

radiusAuthServDupAccessRequests OBJECT-TYPE
 SYNTAX Counter32
 UNITS "packets"
 MAX-ACCESS read-only
 STATUS deprecated
 DESCRIPTION
 "The number of duplicate RADIUS Access-Request
 packets received from this client."
REFERENCE ["RFC 2865 section 4.1"](#)
::= { radiusAuthClientEntry 5 }

radiusAuthServAccessAccepts OBJECT-TYPE
 SYNTAX Counter32
 UNITS "packets"
 MAX-ACCESS read-only
 STATUS deprecated
 DESCRIPTION
 "The number of RADIUS Access-Accept packets
 sent to this client."
REFERENCE ["RFC 2865 section 4.2"](#)
::= { radiusAuthClientEntry 6 }

radiusAuthServAccessRejects OBJECT-TYPE
 SYNTAX Counter32
 UNITS "packets"
 MAX-ACCESS read-only
 STATUS deprecated
 DESCRIPTION
 "The number of RADIUS Access-Reject packets
 sent to this client."
REFERENCE ["RFC 2865 section 4.3"](#)
::= { radiusAuthClientEntry 7 }

radiusAuthServAccessChallenges OBJECT-TYPE
 SYNTAX Counter32
 UNITS "packets"
 MAX-ACCESS read-only
 STATUS deprecated
 DESCRIPTION
 "The number of RADIUS Access-Challenge packets
 sent to this client."
REFERENCE ["RFC 2865 section 4.4"](#)
::= { radiusAuthClientEntry 8 }

Nelson

Expires July 24, 2006

[Page 12]

radiusAuthServMalformedAccessRequests OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of malformed RADIUS Access-Request packets received from this client. Bad authenticators and unknown types are not included as malformed Access-Requests."

REFERENCE "[RFC 2865 section 3](#)"

::= { radiusAuthClientEntry 9 }

radiusAuthServBadAuthenticators OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of RADIUS Authentication-Request packets which contained invalid Message Authenticator attributes received from this client."

REFERENCE "[RFC 2865 section 3](#)"

::= { radiusAuthClientEntry 10 }

radiusAuthServPacketsDropped OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of incoming packets from this client silently discarded for some reason other than malformed, bad authenticators or unknown types."

REFERENCE "[RFC 2865 section 3](#)"

::= { radiusAuthClientEntry 11 }

radiusAuthServUnknownTypes OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of RADIUS packets of unknown type which were received from this client."

REFERENCE "[RFC 2865 section 4](#)"

::= { radiusAuthClientEntry 12 }

Nelson

Expires July 24, 2006

[Page 13]

-- New MIB objects added in this revision

radiusAuthClientExtTable OBJECT-TYPE

SYNTAX SEQUENCE OF RadiusAuthClientExtEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The (conceptual) table listing the RADIUS authentication clients with which the server shares a secret."

::= { radiusAuthServ 16 }

radiusAuthClientExtEntry OBJECT-TYPE

SYNTAX RadiusAuthClientExtEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry (conceptual row) representing a RADIUS authentication client with which the server shares a secret."

INDEX { radiusAuthClientExtIndex }

::= { radiusAuthClientExtTable 1 }

RadiusAuthClientExtEntry ::= SEQUENCE {

radiusAuthClientExtIndex	Integer32,
radiusAuthClientInetAddressType	InetAddressType,
radiusAuthClientInetAddress	InetAddress,
radiusAuthClientExtID	SnmpAdminString,
radiusAuthServExtAccessRequests	Counter32,
radiusAuthServExtDupAccessRequests	Counter32,
radiusAuthServExtAccessAccepts	Counter32,
radiusAuthServExtAccessRejects	Counter32,
radiusAuthServExtAccessChallenges	Counter32,
radiusAuthServExtMalformedAccessRequests	Counter32,
radiusAuthServExtBadAuthenticators	Counter32,
radiusAuthServExtPacketsDropped	Counter32,
radiusAuthServExtUnknownTypes	Counter32

}

radiusAuthClientExtIndex OBJECT-TYPE

SYNTAX Integer32 (1..2147483647)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A number uniquely identifying each RADIUS authentication client with which this server communicates."

::= { radiusAuthClientExtEntry 1 }

Nelson

Expires July 24, 2006

[Page 14]

radiusAuthClientInetAddressType OBJECT-TYPE

SYNTAX InetAddressType
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The type of address format used for the
 radiusAuthClientInetAddress object."
 ::= { radiusAuthClientExtEntry 2 }

radiusAuthClientInetAddress OBJECT-TYPE

SYNTAX InetAddress
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The IP address of the RADIUS authentication
 client referred to in this table entry, using
 the version neutral IP address format."
 ::= { radiusAuthClientExtEntry 3 }

radiusAuthClientExtID OBJECT-TYPE

SYNTAX SnmpAdminString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The NAS-Identifier of the RADIUS authentication client
 referred to in this table entry. This is not
 necessarily the same as sysName in MIB II."
REFERENCE ["RFC 2865 section 5.32"](#)
 ::= { radiusAuthClientExtEntry 4 }

-- Server Counters

--
-- Responses = AccessAccepts + AccessRejects + AccessChallenges
--
-- Requests - DupRequests - BadAuthenticators - MalformedRequests -
-- UnknownTypes - PacketsDropped - Responses = Pending
--
-- Requests - DupRequests - BadAuthenticators - MalformedRequests -
-- UnknownTypes - PacketsDropped = entries logged

radiusAuthServExtAccessRequests OBJECT-TYPE

SYNTAX Counter32
UNITS "packets"
MAX-ACCESS read-only
STATUS current
DESCRIPTION

Nelson

Expires July 24, 2006

[Page 15]

"The number of packets received on the authentication
 port from this client."
REFERENCE ["RFC 2865 section 4.1"](#)
::= { radiusAuthClientExtEntry 5 }

radiusAuthServExtDupAccessRequests OBJECT-TYPE
 SYNTAX Counter32
 UNITS "packets"
 MAX-ACCESS read-only
 STATUS current
 DESCRIPTION
 "The number of duplicate RADIUS Access-Request
 packets received from this client."
REFERENCE ["RFC 2865 section 4.1"](#)
::= { radiusAuthClientExtEntry 6 }

radiusAuthServExtAccessAccepts OBJECT-TYPE
 SYNTAX Counter32
 UNITS "packets"
 MAX-ACCESS read-only
 STATUS current
 DESCRIPTION
 "The number of RADIUS Access-Accept packets
 sent to this client."
REFERENCE ["RFC 2865 section 4.2"](#)
::= { radiusAuthClientExtEntry 7 }

radiusAuthServExtAccessRejects OBJECT-TYPE
 SYNTAX Counter32
 UNITS "packets"
 MAX-ACCESS read-only
 STATUS current
 DESCRIPTION
 "The number of RADIUS Access-Reject packets
 sent to this client."
REFERENCE ["RFC 2865 section 4.3"](#)
::= { radiusAuthClientExtEntry 8 }

radiusAuthServExtAccessChallenges OBJECT-TYPE
 SYNTAX Counter32
 UNITS "packets"
 MAX-ACCESS read-only
 STATUS current
 DESCRIPTION
 "The number of RADIUS Access-Challenge packets
 sent to this client."
REFERENCE ["RFC 2865 section 4.4"](#)
::= { radiusAuthClientExtEntry 9 }

Nelson

Expires July 24, 2006

[Page 16]

radiusAuthServExtMalformedAccessRequests OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of malformed RADIUS Access-Request packets received from this client. Bad authenticators and unknown types are not included as malformed Access-Requests."

REFERENCE "[RFC 2865](#) sections 3, 4.1"

::= { radiusAuthClientExtEntry 10 }

radiusAuthServExtBadAuthenticators OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Authentication-Request packets which contained invalid Message Authenticator attributes received from this client."

REFERENCE "[RFC 2865 section 3](#)"

::= { radiusAuthClientExtEntry 11 }

radiusAuthServExtPacketsDropped OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of incoming packets from this client silently discarded for some reason other than malformed, bad authenticators or unknown types."

REFERENCE "[RFC 2865 section 3](#)"

::= { radiusAuthClientExtEntry 12 }

radiusAuthServExtUnknownTypes OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS packets of unknown type which were received from this client."

REFERENCE "[RFC 2865 section 4](#)"

::= { radiusAuthClientExtEntry 13 }

Nelson

Expires July 24, 2006

[Page 17]

```
-- conformance information

radiusAuthServMIBConformance OBJECT IDENTIFIER
    ::= { radiusAuthServMIB 2 }

radiusAuthServMIBCompliances OBJECT IDENTIFIER
    ::= { radiusAuthServMIBConformance 1 }

radiusAuthServMIBGroups OBJECT IDENTIFIER
    ::= { radiusAuthServMIBConformance 2 }

-- compliance statements

radiusAuthServMIBCompliance MODULE-COMPLIANCE
    STATUS deprecated
    DESCRIPTION
        "The compliance statement for authentication
        servers implementing the RADIUS Authentication
        Server MIB. Implementation of this module is for
        IPv4-only entities, or for backwards compatibility
        use with entities that support both IPv4 and
        IPv6."
    MODULE -- this module
    MANDATORY-GROUPS { radiusAuthServMIBGroup }

    OBJECT      radiusAuthServConfigReset
    WRITE-SYNTAX INTEGER { reset(2) }
    DESCRIPTION "The only SETable value is 'reset' (2)."
```

```
    ::= { radiusAuthServMIBCompliances 1 }

radiusAuthServMIBExtCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "The compliance statement for authentication
        servers implementing the RADIUS Authentication
        Server IPv6 Extensions MIB. Implementation of
        this module is for entities that support IPv6,
        or support IPv4 and IPv6."
    MODULE -- this module
    MANDATORY-GROUPS { radiusAuthServExtMIBGroup }

    OBJECT      radiusAuthServConfigReset
    WRITE-SYNTAX INTEGER { reset(2) }
    DESCRIPTION "The only SETable value is 'reset' (2)."
```

```
    ::= { radiusAuthServMIBCompliances 2 }
```


-- units of conformance

radiusAuthServMIBGroup OBJECT-GROUP

OBJECTS {radiusAuthServIdent,
radiusAuthServUpTime,
radiusAuthServResetTime,
radiusAuthServConfigReset,
radiusAuthServTotalAccessRequests,
radiusAuthServTotalInvalidRequests,
radiusAuthServTotalDupAccessRequests,
radiusAuthServTotalAccessAccepts,
radiusAuthServTotalAccessRejects,
radiusAuthServTotalAccessChallenges,
radiusAuthServTotalMalformedAccessRequests,
radiusAuthServTotalBadAuthenticators,
radiusAuthServTotalPacketsDropped,
radiusAuthServTotalUnknownTypes,
radiusAuthClientAddress,
radiusAuthClientID,
radiusAuthServAccessRequests,
radiusAuthServDupAccessRequests,
radiusAuthServAccessAccepts,
radiusAuthServAccessRejects,
radiusAuthServAccessChallenges,
radiusAuthServMalformedAccessRequests,
radiusAuthServBadAuthenticators,
radiusAuthServPacketsDropped,
radiusAuthServUnknownTypes
}

STATUS deprecated

DESCRIPTION

"The collection of objects providing management of
a RADIUS Authentication Server."

::= { radiusAuthServMIBGroups 1 }

radiusAuthServExtMIBGroup OBJECT-GROUP

OBJECTS {radiusAuthServIdent,
radiusAuthServUpTime,
radiusAuthServResetTime,
radiusAuthServConfigReset,
radiusAuthServTotalAccessRequests,
radiusAuthServTotalInvalidRequests,
radiusAuthServTotalDupAccessRequests,
radiusAuthServTotalAccessAccepts,
radiusAuthServTotalAccessRejects,
radiusAuthServTotalAccessChallenges,
radiusAuthServTotalMalformedAccessRequests,
radiusAuthServTotalBadAuthenticators,
}

Nelson

Expires July 24, 2006

[Page 19]

```
        radiusAuthServTotalPacketsDropped,
        radiusAuthServTotalUnknownTypes,
        radiusAuthClientInetAddressType,
        radiusAuthClientInetAddress,
        radiusAuthClientExtID,
        radiusAuthServExtAccessRequests,
        radiusAuthServExtDupAccessRequests,
        radiusAuthServExtAccessAccepts,
        radiusAuthServExtAccessRejects,
        radiusAuthServExtAccessChallenges,
        radiusAuthServExtMalformedAccessRequests,
        radiusAuthServExtBadAuthenticators,
        radiusAuthServExtPacketsDropped,
        radiusAuthServExtUnknownTypes
    }
    STATUS current
    DESCRIPTION
        "The collection of objects providing management of
        a RADIUS Authentication Server."
    ::= { radiusAuthServMIBGroups 2 }
```

END

8. IANA Considerations

This document requires no new IANA assignments.

9. Security Considerations

There are a number of management objects defined in this MIB that have a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations. These are:

radiusAuthServConfigReset This object can be used to reinitialize the persistent state of any server. When set to reset(2), any persistent server state (such as a process) is reinitialized as if the server had just been started. Depending on the server implementation details, this action may or may not interrupt the processing of pending request in the server. Abuse of this object may lead to a Denial of Service attack on the server.

There are a number of managed objects in this MIB that may contain sensitive information. These are:

radiusAuthClientIPAddress This can be used to determine the address of the RADIUS authentication client with which the server is communicating. This information could be useful in mounting an attack on the authentication client.

radiusAuthClientInetAddress This can be used to determine the address of the RADIUS authentication client with which the server is communicating. This information could be useful in mounting an attack on the authentication client.

It is thus important to control even GET access to these objects and possibly to even encrypt the values of these object when sending them over the network via SNMP. Not all versions of SNMP provide features for such a secure environment.

SNMP versions prior to SNMPv3 do not provide a secure environment. Even if the network itself is secure (for example by using IPsec), there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [\[RFC3410\]](#), [section 8](#)), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them

[10. References](#)

[10.1. Normative References](#)

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2574] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", [RFC 2574](#), April 1999.

- [RFC2575] Wijnen, B., Presuhn, R., and K. McCloghrie, "View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)", [RFC 2575](#), April 1999.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIV2)", STD 58, [RFC 2578](#), April 1999.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIV2", STD 58, [RFC 2579](#), April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIV2", STD 58, [RFC 2580](#), April 1999.
- [RFC2865] Rigney, C., Willens, S., Rubens, A., and W. Simpson, "Remote Authentication Dial In User Service (RADIUS)", [RFC 2865](#), June 2000.
- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", [RFC 3410](#), December 2002.
- [RFC3411] Harrington, D., Presuhn, R., and B. Wijnen, "An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks", STD 62, [RFC 3411](#), December 2002.
- [RFC3418] Presuhn, R., "Management Information Base (MIB) for the Simple Network Management Protocol (SNMP)", STD 62, [RFC 3418](#), December 2002.
- [RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", [RFC 4001](#), February 2005.

[10.2. Informative References](#)

- [RFC2619] Zorn, G. and B. Aboba, "RADIUS Authentication Server MIB", [RFC 2619](#), June 1999.

[Appendix A. Acknowledgments](#)

The Authors of the original MIB are Bernard Aboba and Glen Zorn.

Many thanks to all reviewers, especially to David Harrington, Dan

Romascanu, C.M. Heard, Bruno Pape and Greg Weber.

Author's Address

David B. Nelson
Enterasys Networks
50 Minuteman Road
Andover, MA 01810
USA

Email: dnelson@enterasys.com

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The Internet Society (2006). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.

