

Network Working Group
Internet-Draft
Obsoletes: RFC [2620](#) (if approved)
Expires: December 28, 2006

D. Nelson
Enterasys Networks
June 26, 2006

RADIUS Accounting Client MIB for IPv6
draft-ietf-radext-rfc2620bis-04.txt

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on December 28, 2006.

Copyright Notice

Copyright (C) The Internet Society (2006).

Abstract

This memo defines a set of extensions, which instrument RADIUS accounting client functions. These extensions represent a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. Using these extensions IP-based management stations can manage RADIUS accounting clients.

This memo obsoletes [RFC 2620](#) by deprecating the MIB table containing IPv4-only address formats and defining a new table to add support for

Internet-Draft

RADIUS Acct Client MIB (IPv6)

June 2006

version neutral IP address formats. The remaining MIB objects from [RFC 2620](#) are carried forward into this document. This memo also adds UNITS and REFERENCE clauses to selected objects.

Table of Contents

1.	Terminology	3
2.	Introduction	3
3.	The Internet-Standard Management Framework	3
4.	Scope of Changes	3
5.	Structure of the MIB Module	4
6.	Deprecated Objects	5
7.	Definitions	5
8.	IANA Considerations	19
9.	Security Considerations	19
10.	References	20
10.1.	Normative References	20
10.2.	Informative References	21
Appendix A.	Acknowledgments	21
	Author's Address	22
	Intellectual Property and Copyright Statements	23

1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

This document uses terminology from [RFC 2866](#) [[RFC2866](#)].

This document uses the word "malformed" with respect to RADIUS packets, particularly in the context of counters of "malformed packets". While [RFC 2866](#) does not provide an explicit definition of "malformed", malformed generally means that the implementation has determined the packet does not match the format defined in [RFC 2866](#). Those implementations are used in deployments today, and thus set the de-facto definition of "malformed".

2. Introduction

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. The objects defined within this memo relate to the Remote Authentication Dial-In User Service (RADIUS) Accounting Client as defined in [RFC 2866](#) [[RFC2866](#)].

3. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [[RFC3410](#)].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the

Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, [RFC 2578](#) [[RFC2578](#)], STD 58, [RFC 2579](#) [[RFC2579](#)] and STD 58, [RFC 2580](#) [[RFC2580](#)].

[4.](#) Scope of Changes

This document obsoletes [RFC 2620](#) [[RFC2620](#)], RADIUS Authentication Client MIB, by deprecating the radiusAuthServerTable table and adding a new table, radiusAuthServerExtTable, containing radiusAuthServerInetAddressType, radiusAuthServerInetAddress, and

Nelson

Expires December 28, 2006

[Page 3]

Internet-Draft

RADIUS Acct Client MIB (IPv6)

June 2006

radiusAuthClientServerInetPortNumber. The purpose of these added MIB objects is to support version neutral IP addressing formats. The existing table containing radiusAuthServerAddress and radiusAuthClientServerPortNumber is deprecated. The remaining MIB objects from [RFC 2620](#) are carried forward into this document.

[RFC 4001](#) [[RFC4001](#)], which defines the SMI Textual Conventions for IPv6 addresses, contains the following recommendation.

'In particular, when revising a MIB module that contains IPv4 specific tables, it is suggested to define new tables using the textual conventions defined in this memo [[RFC4001](#)] that support all versions of IP. The status of the new tables SHOULD be "current", whereas the status of the old IP version specific tables SHOULD be changed to "deprecated". The other approach, of having multiple similar tables for different IP versions, is strongly discouraged.'

[5.](#) Structure of the MIB Module

The RADIUS accounting protocol, described in [RFC 2866](#) [[RFC2866](#)], distinguishes between the client function and the server function. In RADIUS accounting, clients send Accounting-Requests, and servers reply with Accounting-Responses. Typically Network Access Server (NAS) devices implement the client function, and thus would be expected to implement the RADIUS accounting client MIB, while RADIUS accounting servers implement the server function, and thus would be expected to implement the RADIUS accounting server MIB.

However, it is possible for a RADIUS accounting entity to perform both client and server functions. For example, a RADIUS proxy may act as a server to one or more RADIUS accounting clients, while simultaneously acting as an accounting client to one or more accounting servers. In such situations, it is expected that RADIUS entities combining client and server functionality will support both the client and server MIBs. The client MIB is defined in this document, and the server MIB is defined in [[2621bis](#)].

RFC Editor: Replace the above I-D reference with the assigned RFC number at the time of publication and delete this note.

This MIB module contains two scalars as well as a single table, the RADIUS Accounting Server Table, which contains one row for each RADIUS server with which the client shares a secret. Each entry in the RADIUS Accounting Server Table includes fifteen columns presenting a view of the activity of the RADIUS client.

[6.](#) Deprecated Objects

The deprecated table in this MIB is carried forward from [RFC 2620](#) [[RFC2620](#)]. There are two conditions under which it MAY be desirable for managed entities to continue to support the deprecated table:

1. The managed entity only supports IPv4 address formats.
2. The managed entity supports both IPv4 and IPv6 address formats, and the deprecated table is supported for backwards compatibility with older management stations. This option SHOULD only be used when the IP addresses in the new table are in IPv4 format and can accurately be represented in both the new table and the deprecated table.

Managed entities SHOULD NOT instantiate row entries in the deprecated table, containing IPv4-only address objects, when the RADIUS accounting server address represented in such a table row is not an IPv4 address. Managed entities SHOULD NOT return inaccurate values of IP address or SNMP object access errors for IPv4-only address objects in otherwise populated tables. When row entries exist in both the deprecated IPv4-only table and the new IP version neutral table that describe the same RADIUS accounting server, the row

indexes SHOULD be the same for the corresponding rows in each table, to facilitate correlation of these related rows by management applications.

7. Definitions

RADIUS-ACC-CLIENT-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-IDENTITY, OBJECT-TYPE, OBJECT-IDENTITY,
Counter32, Integer32, Gauge32,
IpAddress, TimeTicks, mib-2 FROM SNMPv2-SMI
SnmAdminString FROM SNMP-FRAMEWORK-MIB
InetAddressType, InetAddress,
InetPortNumber FROM INET-ADDRESS-MIB
MODULE-COMPLIANCE, OBJECT-GROUP FROM SNMPv2-CONF;

radiusAccClientMIB MODULE-IDENTITY

LAST-UPDATED "200605100000Z" -- 10 May 2006
ORGANIZATION "IETF RADIUS Extensions Working Group."
CONTACT-INFO
" Bernard Aboba
Microsoft
One Microsoft Way

Nelson

Expires December 28, 2006

[Page 5]

Internet-Draft

RADIUS Acct Client MIB (IPv6)

June 2006

Redmond, WA 98052
US
Phone: +1 425 936 6605
EMail: bernarda@microsoft.com"

DESCRIPTION

"The MIB module for entities implementing the client side of the Remote Authentication Dial-In User Service (RADIUS) accounting protocol. Copyright (C) The Internet Society (2006). This version of this MIB module is part of RFC xxxx; see the RFC itself for full legal notices."

-- RFC Editor: replace xxxx with actual RFC number at the time of
-- publication, and remove this note.

REVISION "200605100000Z" -- 10 May 2006

DESCRIPTION

"Revised version as published in RFC xxxx.
This version obsoletes that of [RFC 2620](#) by
deprecating the MIB table containing IPv4-only
address formats and defining a new table to add support
for version neutral IP address formats. The remaining
MIB objects from [RFC 2620](#) are carried forward into this
version."

-- RFC Editor: replace xxxx with actual RFC number at the time of
-- publication, and remove this note.

REVISION "199906110000Z" -- 11 Jun 1999

DESCRIPTION "Initial version as published in [RFC 2620](#)."

::= { radiusAccounting 2 }

radiusMIB OBJECT-IDENTITY

STATUS current

DESCRIPTION

"The OID assigned to RADIUS MIB work by the IANA."

::= { mib-2 67 }

radiusAccounting OBJECT IDENTIFIER ::= {radiusMIB 2}

radiusAccClientMIBObjects OBJECT IDENTIFIER

::= { radiusAccClientMIB 1 }

radiusAccClient OBJECT IDENTIFIER

::= { radiusAccClientMIBObjects 1 }

radiusAccClientInvalidServerAddresses OBJECT-TYPE

Nelson

Expires December 28, 2006

[Page 6]

Internet-Draft

RADIUS Acct Client MIB (IPv6)

June 2006

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Accounting-Response packets
received from unknown addresses."

::= { radiusAccClient 1 }

radiusAccClientIdentifier OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The NAS-Identifier of the RADIUS accounting client.
This is not necessarily the same as sysName in MIB
II."

REFERENCE "[RFC 2865 section 5.32](#)"

::= { radiusAccClient 2 }

radiusAccServerTable OBJECT-TYPE

SYNTAX SEQUENCE OF RadiusAccServerEntry

MAX-ACCESS not-accessible

STATUS deprecated

DESCRIPTION

"The (conceptual) table listing the RADIUS accounting
servers with which the client shares a secret."

::= { radiusAccClient 3 }

radiusAccServerEntry OBJECT-TYPE

SYNTAX RadiusAccServerEntry

MAX-ACCESS not-accessible

STATUS deprecated

DESCRIPTION

"An entry (conceptual row) representing a RADIUS
accounting server with which the client shares a
secret."

INDEX { radiusAccServerIndex }

::= { radiusAccServerTable 1 }

RadiusAccServerEntry ::= SEQUENCE {

radiusAccServerIndex	Integer32,
radiusAccServerAddress	IpAddress,
radiusAccClientServerPortNumber	Integer32,
radiusAccClientRoundTripTime	TimeTicks,
radiusAccClientRequests	Counter32,
radiusAccClientRetransmissions	Counter32,
radiusAccClientResponses	Counter32,


```

        radiusAccClientBadAuthenticators          Counter32,
        radiusAccClientPendingRequests            Gauge32,
        radiusAccClientTimeouts                   Counter32,
        radiusAccClientUnknownTypes               Counter32,
        radiusAccClientPacketsDropped              Counter32
    }

radiusAccServerIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  not-accessible
    STATUS      deprecated
    DESCRIPTION
        "A number uniquely identifying each RADIUS
        Accounting server with which this client
        communicates."
    ::= { radiusAccServerEntry 1 }

radiusAccServerAddress OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS  read-only
    STATUS      deprecated
    DESCRIPTION
        "The IP address of the RADIUS accounting server
        referred to in this table entry."
    ::= { radiusAccServerEntry 2 }

radiusAccClientServerPortNumber OBJECT-TYPE
    SYNTAX Integer32 (0..65535)
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The UDP port the client is using to send requests to
        this server."
    REFERENCE RFC 2866 section 3
    ::= { radiusAccServerEntry 3 }

radiusAccClientRoundTripTime OBJECT-TYPE
    SYNTAX TimeTicks
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The time interval between the most recent
        Accounting-Response and the Accounting-Request that
        matched it from this RADIUS accounting server."
    REFERENCE RFC 2866 section 2
    ::= { radiusAccServerEntry 4 }

```

```
-- Request/Response statistics
--
-- Requests = Responses + PendingRequests + ClientTimeouts
--
-- Responses - MalformedResponses - BadAuthenticators -
-- UnknownTypes - PacketsDropped = Successfully received

radiusAccClientRequests OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The number of RADIUS Accounting-Request packets
        sent. This does not include retransmissions."
    REFERENCE "RFC 2866 section 4.1"
    ::= { radiusAccServerEntry 5 }

radiusAccClientRetransmissions OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The number of RADIUS Accounting-Request packets
        retransmitted to this RADIUS accounting server.
        Retransmissions include retries where the
        Identifier and Acct-Delay have been updated, as
        well as those in which they remain the same."
    REFERENCE "RFC 2866 section 2"
    ::= { radiusAccServerEntry 6 }

radiusAccClientResponses OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The number of RADIUS packets received on the
        accounting port from this server."
    REFERENCE "RFC 2866 section 4.2"
    ::= { radiusAccServerEntry 7 }

radiusAccClientMalformedResponses OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
```

MAX-ACCESS read-only
STATUS deprecated

Nelson

Expires December 28, 2006

[Page 9]

Internet-Draft

RADIUS Acct Client MIB (IPv6)

June 2006

DESCRIPTION

"The number of malformed RADIUS Accounting-Response packets received from this server. Malformed packets include packets with an invalid length. Bad authenticators and unknown types are not included as malformed accounting responses."

REFERENCE "[RFC 2866 section 3](#)"

::= { radiusAccServerEntry 8 }

radiusAccClientBadAuthenticators OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of RADIUS Accounting-Response packets which contained invalid authenticators received from this server."

REFERENCE "[RFC 2866 section 3](#)"

::= { radiusAccServerEntry 9 }

radiusAccClientPendingRequests OBJECT-TYPE

SYNTAX Gauge32

UNITS "packets"

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of RADIUS Accounting-Request packets sent to this server that have not yet timed out or received a response. This variable is incremented when an Accounting-Request is sent and decremented due to receipt of an Accounting-Response, a timeout or a retransmission."

REFERENCE "[RFC 2866 section 2](#)"

::= { radiusAccServerEntry 10 }

radiusAccClientTimeouts OBJECT-TYPE

SYNTAX Counter32

UNITS "timeouts"

MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION

"The number of accounting timeouts to this server.
After a timeout the client may retry to the same
server, send to a different server, or give up.
A retry to the same server is counted as a
retransmit as well as a timeout. A send to a different
server is counted as an Accounting-Request as well as

Nelson

Expires December 28, 2006

[Page 10]

Internet-Draft

RADIUS Acct Client MIB (IPv6)

June 2006

a timeout."

REFERENCE "[RFC 2866 section 2](#)"

::= { radiusAccServerEntry 11 }

radiusAccClientUnknownTypes OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of RADIUS packets of unknown type which
were received from this server on the accounting port."

REFERENCE "[RFC 2866 section 4](#)"

::= { radiusAccServerEntry 12 }

radiusAccClientPacketsDropped OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of RADIUS packets which were received from
this server on the accounting port and dropped for some
other reason."

::= { radiusAccServerEntry 13 }

-- New MIB objects added in this revision

radiusAccServerExtTable OBJECT-TYPE

SYNTAX SEQUENCE OF RadiusAccServerExtEntry

MAX-ACCESS not-accessible

```

STATUS      current
DESCRIPTION
    "The (conceptual) table listing the RADIUS accounting
    servers with which the client shares a secret."
 ::= { radiusAccClient 4 }

```

```

radiusAccServerExtEntry OBJECT-TYPE
    SYNTAX      RadiusAccServerExtEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry (conceptual row) representing a RADIUS
        accounting server with which the client shares a
        secret."
    INDEX       { radiusAccServerExtIndex }
    ::= { radiusAccServerExtTable 1 }

```

Nelson

Expires December 28, 2006

[Page 11]

Internet-Draft

RADIUS Acct Client MIB (IPv6)

June 2006

```

RadiusAccServerExtEntry ::= SEQUENCE {
    radiusAccServerExtIndex          Integer32,
    radiusAccServerInetAddressType  InetAddressType,
    radiusAccServerInetAddress      InetAddress,
    radiusAccClientServerInetPortNumber  InetPortNumber,
    radiusAccClientExtRoundTripTime  TimeTicks,
    radiusAccClientExtRequests       Counter32,
    radiusAccClientExtRetransmissions Counter32,
    radiusAccClientExtResponses      Counter32,
    radiusAccClientExtMalformedResponses Counter32,
    radiusAccClientExtBadAuthenticators Counter32,
    radiusAccClientExtPendingRequests Gauge32,
    radiusAccClientExtTimeouts       Counter32,
    radiusAccClientExtUnknownTypes   Counter32,
    radiusAccClientExtPacketsDropped Counter32,
    radiusAccClientCounterDiscontinuity TimeTicks
}

```

```

radiusAccServerExtIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A number uniquely identifying each RADIUS
        Accounting server with which this client

```

```
communicates."
 ::= { radiusAccServerExtEntry 1 }
```

```
radiusAccServerInetAddressType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The type of address format used for the
         radiusAccServerInetAddress object."
    ::= { radiusAccServerExtEntry 2 }
```

```
radiusAccServerInetAddress OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The IP address of the RADIUS accounting
         server referred to in this table entry, using
         the version neutral IP address format."
    ::= { radiusAccServerExtEntry 3 }
```

Nelson

Expires December 28, 2006

[Page 12]

Internet-Draft

RADIUS Acct Client MIB (IPv6)

June 2006

```
radiusAccClientServerInetPortNumber OBJECT-TYPE
    SYNTAX InetPortNumber ( 1..65535 )
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The UDP port the client is using to send requests
         to this accounting server. The value zero (0) is
         invalid."
    REFERENCE "RFC 2866 section 3"
    ::= { radiusAccServerExtEntry 4 }
```

```
radiusAccClientExtRoundTripTime OBJECT-TYPE
    SYNTAX TimeTicks
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The time interval between the most recent
```

Accounting-Response and the Accounting-Request that
matched it from this RADIUS accounting server."
REFERENCE "[RFC 2866 section 2](#)"
::= { radiusAccServerExtEntry 5 }

-- Request/Response statistics
--
-- Requests = Responses + PendingRequests + ClientTimeouts
--
-- Responses - MalformedResponses - BadAuthenticators -
-- UnknownTypes - PacketsDropped = Successfully received

radiusAccClientExtRequests OBJECT-TYPE
SYNTAX Counter32
UNITS "packets"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of RADIUS Accounting-Request packets
 sent. This does not include retransmissions.
 This counter may experience a discontinuity when the
 RADIUS Accounting Client module within the managed
 entity is reinitialized, as indicated by the current
 value of radiusAccClientCounterDiscontinuity."
REFERENCE "[RFC 2866 section 4.1](#)"
::= { radiusAccServerExtEntry 6 }

radiusAccClientExtRetransmissions OBJECT-TYPE
SYNTAX Counter32
UNITS "packets"

MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of RADIUS Accounting-Request packets
 retransmitted to this RADIUS accounting server.
 Retransmissions include retries where the
 Identifier and Acct-Delay have been updated, as
 well as those in which they remain the same.
 This counter may experience a discontinuity when the
 RADIUS Accounting Client module within the managed
 entity is reinitialized, as indicated by the current

value of radiusAccClientCounterDiscontinuity."
REFERENCE "[RFC 2866 section 2](#)"
::= { radiusAccServerExtEntry 7 }

radiusAccClientExtResponses OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS packets received on the accounting port from this server. This counter may experience a discontinuity when the RADIUS Accounting Client module within the managed entity is reinitialized, as indicated by the current value of radiusAccClientCounterDiscontinuity."

REFERENCE "[RFC 2866 section 4.2](#)"

::= { radiusAccServerExtEntry 8 }

radiusAccClientExtMalformedResponses OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of malformed RADIUS Accounting-Response packets received from this server. Malformed packets include packets with an invalid length. Bad authenticators and unknown types are not included as malformed accounting responses. This counter may experience a discontinuity when the RADIUS Accounting Client module within the managed entity is reinitialized, as indicated by the current value of radiusAccClientCounterDiscontinuity."

REFERENCE "[RFC 2866 section 3](#)"

::= { radiusAccServerExtEntry 9 }

radiusAccClientExtBadAuthenticators OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Accounting-Response packets which contained invalid authenticators received from this server. This counter may experience a discontinuity when the RADIUS Accounting Client module within the managed entity is reinitialized, as indicated by the current value of radiusAccClientCounterDiscontinuity."

REFERENCE "[RFC 2866 section 3](#)"

::= { radiusAccServerExtEntry 10 }

radiusAccClientExtPendingRequests OBJECT-TYPE

SYNTAX Gauge32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Accounting-Request packets sent to this server that have not yet timed out or received a response. This variable is incremented when an Accounting-Request is sent and decremented due to receipt of an Accounting-Response, a timeout or a retransmission. This counter may experience a discontinuity when the RADIUS Accounting Client module within the managed entity is reinitialized, as indicated by the current value of radiusAccClientCounterDiscontinuity."

REFERENCE "[RFC 2866 section 2](#)"

::= { radiusAccServerExtEntry 11 }

radiusAccClientExtTimeouts OBJECT-TYPE

SYNTAX Counter32

UNITS "timeouts"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of accounting timeouts to this server. After a timeout the client may retry to the same server, send to a different server, or give up. A retry to the same server is counted as a retransmit as well as a timeout. A send to a different server is counted as an Accounting-Request as well as

a timeout. This counter may experience a discontinuity when the RADIUS Accounting Client module within the managed entity is reinitialized, as indicated by the current value of radiusAccClientCounterDiscontinuity."

REFERENCE "[RFC 2866 section 2](#)"

::= { radiusAccServerExtEntry 12 }

radiusAccClientExtUnknownTypes OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS packets of unknown type which were received from this server on the accounting port. This counter may experience a discontinuity when the RADIUS Accounting Client module within the managed entity is reinitialized, as indicated by the current value of radiusAccClientCounterDiscontinuity."

REFERENCE "[RFC 2866 section 4](#)"

::= { radiusAccServerExtEntry 13 }

radiusAccClientExtPacketsDropped OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS packets which were received from this server on the accounting port and dropped for some other reason. This counter may experience a discontinuity when the RADIUS Accounting Client module within the managed entity is reinitialized, as indicated by the current value of radiusAccClientCounterDiscontinuity."

::= { radiusAccServerExtEntry 14 }

radiusAccClientCounterDiscontinuity OBJECT-TYPE

SYNTAX TimeTicks

UNITS "centiseconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of centiseconds since the last discontinuity in the RADIUS Accounting Client counters. A discontinuity may be the result of a reinitialization of the RADIUS Accounting Client

module within the managed entity."

Nelson

Expires December 28, 2006

[Page 16]

Internet-Draft

RADIUS Acct Client MIB (IPv6)

June 2006

```
::= { radiusAccServerExtEntry 15 }
```

```
-- conformance information
```

```
radiusAccClientMIBConformance OBJECT IDENTIFIER  
    ::= { radiusAccClientMIB 2 }
```

```
radiusAccClientMIBCompliances OBJECT IDENTIFIER  
    ::= { radiusAccClientMIBConformance 1 }
```

```
radiusAccClientMIBGroups OBJECT IDENTIFIER  
    ::= { radiusAccClientMIBConformance 2 }
```

```
-- units of conformance
```

```
radiusAccClientMIBCompliance MODULE-COMPLIANCE  
    STATUS deprecated  
    DESCRIPTION  
        "The compliance statement for accounting clients  
        implementing the RADIUS Accounting Client MIB.  
        Implementation of this module is for IPv4-only  
        entities, or for backwards compatibility use with  
        entities that support both IPv4 and IPv6."  
    MODULE -- this module  
        MANDATORY-GROUPS { radiusAccClientMIBGroup }  
  
    ::= { radiusAccClientMIBCompliances 1 }
```

```
radiusAccClientExtMIBCompliance MODULE-COMPLIANCE  
    STATUS current  
    DESCRIPTION  
        "The compliance statement for accounting  
        clients implementing the RADIUS Accounting  
        Client IPv6 Extensions MIB. Implementation of  
        this module is for entities that support IPv6,  
        or support IPv4 and IPv6."
```

```

MODULE -- this module
    MANDATORY-GROUPS { radiusAccClientExtMIBGroup }

OBJECT radiusAccServerInetAddressType
SYNTAX InetAddressType { ipv4(1), ipv6(2) }
DESCRIPTION
    "An implementation is only required to support
    IPv4 and globally unique IPv6 addresses."

```

Nelson

Expires December 28, 2006

[Page 17]

Internet-Draft

RADIUS Acct Client MIB (IPv6)

June 2006

```

OBJECT radiusAccServerInetAddress
SYNTAX InetAddress ( SIZE (4|16) )
DESCRIPTION
    "An implementation is only required to support
    IPv4 and globally unique IPv6 addresses."

 ::= { radiusAccClientMIBCompliances 2 }

```

-- units of conformance

```

radiusAccClientMIBGroup OBJECT-GROUP
    OBJECTS { radiusAccClientIdentifier,
        radiusAccClientInvalidServerAddresses,
        radiusAccServerAddress,
        radiusAccClientServerPortNumber,
        radiusAccClientRoundTripTime,
        radiusAccClientRequests,
        radiusAccClientRetransmissions,
        radiusAccClientResponses,
        radiusAccClientMalformedResponses,
        radiusAccClientBadAuthenticators,
        radiusAccClientPendingRequests,
        radiusAccClientTimeouts,
        radiusAccClientUnknownTypes,
        radiusAccClientPacketsDropped
    }
STATUS deprecated
DESCRIPTION
    "The basic collection of objects providing management of
    RADIUS Accounting Clients."
 ::= { radiusAccClientMIBGroups 1 }

```

```

radiusAccClientExtMIBGroup OBJECT-GROUP
    OBJECTS { radiusAccClientIdentifier,
               radiusAccClientInvalidServerAddresses,
               radiusAccServerInetAddressType,
               radiusAccServerInetAddress,
               radiusAccClientServerInetPortNumber,
               radiusAccClientExtRoundTripTime,
               radiusAccClientExtRequests,
               radiusAccClientExtRetransmissions,
               radiusAccClientExtResponses,
               radiusAccClientExtMalformedResponses,
               radiusAccClientExtBadAuthenticators,
               radiusAccClientExtPendingRequests,
               radiusAccClientExtTimeouts,

```

Nelson

Expires December 28, 2006

[Page 18]

Internet-Draft

RADIUS Acct Client MIB (IPv6)

June 2006

```

               radiusAccClientExtUnknownTypes,
               radiusAccClientExtPacketsDropped,
               radiusAccClientCounterDiscontinuity
        }
    STATUS current
    DESCRIPTION
        "The basic collection of objects providing management of
        RADIUS Accounting Clients."
    ::= { radiusAccClientMIBGroups 2 }

```

END

[8.](#) IANA Considerations

This document requires no new IANA assignments.

[9.](#) Security Considerations

There are no management objects defined in this MIB that have a MAX-ACCESS clause of read-write and/or read-create. So, if this MIB is implemented correctly, then there is no risk that an intruder can alter or create any management objects of this MIB via direct SNMP SET operations.

There are a number of managed objects in this MIB that may contain sensitive information. These are:

radiusAcctServerIPAddress This can be used to determine the address of the RADIUS accounting server with which the client is communicating. This information could be useful in mounting an attack on the accounting server.

radiusAcctServerInetAddress This can be used to determine the address of the RADIUS accounting server with which the client is communicating. This information could be useful in mounting an attack on the accounting server.

radiusAcctClientServerPortNumber This can be used to determine the port number on which the RADIUS accounting client is sending. This information could be useful in impersonating the client in order to send data to the accounting server.

radiusAcctClientServerInetPortNumber This can be used to determine the port number on which the RADIUS accounting client is sending. This information could be useful in impersonating the client in order to send data to the accounting server.

It is thus important to control even GET access to these objects and possibly to even encrypt the values of these object when sending them over the network via SNMP. Not all versions of SNMP provide features for such a secure environment.

SNMP versions prior to SNMPv3 do not provide a secure environment. Even if the network itself is secure (for example by using IPsec), there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [\[RFC3410\]](#), [section 8](#)),

including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

[10.](#) References

[10.1.](#) Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), April 1999.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, [RFC 2579](#), April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIv2", STD 58, [RFC 2580](#),

Nelson	Expires December 28, 2006	[Page 20]
--------	---------------------------	-----------

Internet-Draft	RADIUS Acct Client MIB (IPv6)	June 2006
----------------	-------------------------------	-----------

April 1999.

- [RFC2866] Rigney, C., "RADIUS Accounting", [RFC 2866](#), June 2000.
- [RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", [RFC 4001](#), February 2005.

[10.2.](#) Informative References

- [2621bis] Nelson, D., "RADIUS Accounting Server MIB for IPv6", [draft-ietf-radext-rfc2621bis-04.txt](#) (work in progress),

June 2006.

- [RFC2620] Aboba, B. and G. Zorn, "RADIUS Accounting Client MIB", [RFC 2620](#), June 1999.
- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", [RFC 3410](#), December 2002.

[Appendix A](#). Acknowledgments

The authors of the original MIB are Bernard Aboba and Glen Zorn.

Many thanks to all reviewers, especially to Dave Harrington, Dan Romascanu, C.M. Heard, Bruno Pape, Greg Weber and Bert Wijnen.

Author's Address

David B. Nelson
Enterasys Networks
50 Minuteman Road

Andover, MA 01810
USA

Email: dnelson@enterasys.com

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The Internet Society (2006). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.

