

Network Working Group
Internet-Draft
Obsoletes: RFC [2621](#) (if approved)
Expires: December 28, 2006

D. Nelson
Enterasys Networks
June 26, 2006

RADIUS Accounting Server MIB for IPv6
draft-ietf-radext-rfc2621bis-04.txt

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on December 28, 2006.

Copyright Notice

Copyright (C) The Internet Society (2006).

Abstract

This memo defines a set of extensions, which instrument RADIUS accounting server functions. These extensions represent a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. Using these extensions IP-based management stations can manage RADIUS accounting servers.

This memo obsoletes [RFC 2621](#) by deprecating the MIB table containing IPv4-only address formats and defining a new table to add support for

Internet-Draft

RADIUS Acct Server MIB (IPv6)

June 2006

version neutral IP address formats. The remaining MIB objects from [RFC 2621](#) are carried forward into this document. This memo also adds UNITS and REFERENCE clauses to selected objects.

Table of Contents

1.	Terminology	3
2.	Introduction	3
3.	The Internet-Standard Management Framework	3
4.	Scope of Changes	3
5.	Structure of the MIB Module	4
6.	Deprecated Objects	5
7.	Definitions	5
8.	IANA Considerations	21
9.	Security Considerations	21
10.	References	22
10.1.	Normative References	22
10.2.	Informative References	22
Appendix A.	Acknowledgments	23
	Author's Address	24
	Intellectual Property and Copyright Statements	25

1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

This document uses terminology from [RFC 2866](#) [[RFC2866](#)].

This document uses the word "malformed" with respect to RADIUS packets, particularly in the context of counters of "malformed packets". While [RFC 2866](#) does not provide an explicit definition of "malformed", malformed generally means that the implementation has determined the packet does not match the format defined in [RFC 2866](#). Those implementations are used in deployments today, and thus set the de-facto definition of "malformed".

2. Introduction

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. The objects defined within this memo relate to the Remote Authentication Dial-In User Service (RADIUS) Accounting Server as defined in [RFC 2866](#) [[RFC2866](#)].

3. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [[RFC3410](#)].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the

Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, [RFC 2578](#) [[RFC2578](#)], STD 58, [RFC 2579](#) [[RFC2579](#)] and STD 58, [RFC 2580](#) [[RFC2580](#)].

[4.](#) Scope of Changes

This document obsoletes [RFC 2621](#) [[RFC2621](#)], RADIUS Accounting Server MIB, by deprecating the radiusAccClientTable table and adding a new table, radiusAccClientExtTable, containing radiusAccClientInetAddressType and radiusAccClientInetAddress. The

Nelson

Expires December 28, 2006

[Page 3]

Internet-Draft

RADIUS Acct Server MIB (IPv6)

June 2006

purpose of these added MIB objects is to support version neutral IP addressing formats. The existing table containing radiusAccClientAddress is deprecated. The remaining MIB objects from [RFC 2621](#) are carried forward into this document. This memo also adds UNITS and REFERENCE clauses to selected objects.

[RFC 4001](#) [[RFC4001](#)], which defines the SMI Textual Conventions for version neutral IP addresses, contains the following recommendation.

'In particular, when revising a MIB module that contains IPv4 specific tables, it is suggested to define new tables using the textual conventions defined in this memo [[RFC4001](#)] that support all versions of IP. The status of the new tables SHOULD be "current", whereas the status of the old IP version specific tables SHOULD be changed to "deprecated". The other approach, of having multiple similar tables for different IP versions, is strongly discouraged.'

[5.](#) Structure of the MIB Module

The RADIUS accounting protocol, described in [RFC 2866](#) [[RFC2866](#)], distinguishes between the client function and the server function. In RADIUS accounting, clients send Accounting-Requests, and servers reply with Accounting-Responses. Typically Network Access Server (NAS) devices implement the client function, and thus would be expected to implement the RADIUS accounting client MIB, while RADIUS accounting servers implement the server function, and thus would be expected to implement the RADIUS accounting server MIB.

However, it is possible for a RADIUS accounting entity to perform both client and server functions. For example, a RADIUS proxy may act as a server to one or more RADIUS accounting clients, while simultaneously acting as an accounting client to one or more accounting servers. In such situations, it is expected that RADIUS entities combining client and server functionality will support both the client and server MIBs. The server MIB is defined in this document, and the client MIB is defined in [[2620bis](#)].

RFC Editor: Replace the above I-D reference with the assigned RFC number at the time of publication and delete this note.

This MIB module contains thirteen scalars as well as a single table, the RADIUS Accounting Client Table, which contains one row for each RADIUS accounting client with which the server shares a secret. Each entry in the RADIUS Accounting Client Table includes twelve columns presenting a view of the activity of the RADIUS accounting server.

Nelson

Expires December 28, 2006

[Page 4]

Internet-Draft

RADIUS Acct Server MIB (IPv6)

June 2006

[6.](#) Deprecated Objects

The deprecated table in this MIB is carried forward from [RFC 2621](#) [[RFC2621](#)]. There are two conditions under which it MAY be desirable for managed entities to continue to support the deprecated table:

1. The managed entity only supports IPv4 address formats.
2. The managed entity supports both IPv4 and IPv6 address formats, and the deprecated table is supported for backwards compatibility with older management stations. This option SHOULD only be used when the IP addresses in the new table are in IPv4 format and can accurately be represented in both the new table and the deprecated table.

Managed entities SHOULD NOT instantiate row entries in the deprecated table, containing IPv4-only address objects, when the RADIUS accounting client address represented in such a table row is not an IPv4 address. Managed entities SHOULD NOT return inaccurate values of IP address or SNMP object access errors for IPv4-only address objects in otherwise populated tables. When row entries exist in both the deprecated IPv4-only table and the new IP version neutral table that describe the same RADIUS accounting client, the row

indexes SHOULD be the same for the corresponding rows in each table, to facilitate correlation of these related rows by management applications.

7. Definitions

RADIUS-ACC-SERVER-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-IDENTITY, OBJECT-TYPE, OBJECT-IDENTITY,
Counter32, Integer32,
IpAddress, TimeTicks, mib-2 FROM SNMPv2-SMI
SnmAdminString FROM SNMP-FRAMEWORK-MIB
InetAddressType, InetAddress FROM INET-ADDRESS-MIB
MODULE-COMPLIANCE, OBJECT-GROUP FROM SNMPv2-CONF;

radiusAccServMIB MODULE-IDENTITY

LAST-UPDATED "200605100000Z" -- 10 May 2006
ORGANIZATION "IETF RADIUS Extensions Working Group."
CONTACT-INFO
" Bernard Aboba
Microsoft
One Microsoft Way
Redmond, WA 98052

Nelson

Expires December 28, 2006

[Page 5]

Internet-Draft

RADIUS Acct Server MIB (IPv6)

June 2006

US

Phone: +1 425 936 6605

EMail: bernarda@microsoft.com"

DESCRIPTION

"The MIB module for entities implementing the server side of the Remote Authentication Dial-In User Service (RADIUS) accounting protocol. Copyright (C) The Internet Society (2006). This version of this MIB module is part of RFC xxxx; see the RFC itself for full legal notices."

-- RFC Editor: replace xxxx with actual RFC number at the time of
-- publication, and remove this note.

REVISION "200605100000Z" -- 10 May 2006

DESCRIPTION

"Revised version as published in RFC xxxx. This version obsoletes that of [RFC 2621](#) by deprecating the MIB table containing IPv4-only address formats and defining a new table to add support for version neutral IP address formats. The remaining MIB objects from [RFC 2621](#) are carried forward into this version."

-- RFC Editor: replace xxxx with actual RFC number at the time of
-- publication, and remove this note.

REVISION "199906110000Z" -- 11 Jun 1999

DESCRIPTION "Initial version as published in [RFC 2621](#)."

::= { radiusAccounting 1 }

radiusMIB OBJECT-IDENTITY

STATUS current

DESCRIPTION

"The OID assigned to RADIUS MIB work by the IANA."

::= { mib-2 67 }

radiusAccounting OBJECT IDENTIFIER ::= {radiusMIB 2}

radiusAccServMIBObjects OBJECT IDENTIFIER

::= { radiusAccServMIB 1 }

radiusAccServ OBJECT IDENTIFIER

::= { radiusAccServMIBObjects 1 }

radiusAccServIdent OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

Nelson

Expires December 28, 2006

[Page 6]

Internet-Draft

RADIUS Acct Server MIB (IPv6)

June 2006

STATUS current

DESCRIPTION

"The implementation identification string for the RADIUS accounting server software in use on the system, for example; `FNS-2.1'"

::= {radiusAccServ 1}

radiusAccServUpTime OBJECT-TYPE

SYNTAX TimeTicks
MAX-ACCESS read-only
STATUS current
DESCRIPTION

"If the server has a persistent state (e.g., a process), this value will be the time elapsed (in hundredths of a second) since the server process was started. For software without persistent state, this value will be zero."

::= {radiusAccServ 2}

radiusAccServResetTime OBJECT-TYPE

SYNTAX TimeTicks
MAX-ACCESS read-only
STATUS current
DESCRIPTION

"If the server has a persistent state (e.g., a process) and supports a 'reset' operation (e.g., can be told to re-read configuration files), this value will be the time elapsed (in hundredths of a second) since the server was 'reset.' For software that does not have persistence or does not support a 'reset' operation, this value will be zero."

::= {radiusAccServ 3}

radiusAccServConfigReset OBJECT-TYPE

SYNTAX INTEGER { other(1),
 reset(2),
 initializing(3),
 running(4) }

MAX-ACCESS read-write
STATUS current
DESCRIPTION

"Status/action object to reinitialize any persistent server state. When set to reset(2), any persistent server state (such as a process) is reinitialized as if the server had just been started. This value will never be returned by a read operation. When read, one of the following values will be returned:
 other(1) - server in some unknown state;

```
        running(4) - server currently running."
 ::= { radiusAccServ 4 }
```

```
radiusAccServTotalRequests OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of packets received on the
         accounting port."
    REFERENCE "RFC 2866 section 4.1"
    ::= { radiusAccServ 5 }
```

```
radiusAccServTotalInvalidRequests OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS Accounting-Request packets
         received from unknown addresses."
    REFERENCE "RFC 2866 sections 2, 4.1"
    ::= { radiusAccServ 6 }
```

```
radiusAccServTotalDupRequests OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of duplicate RADIUS Accounting-Request
         packets received."
    REFERENCE "RFC 2866 section 4.1"
    ::= { radiusAccServ 7 }
```

```
radiusAccServTotalResponses OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS Accounting-Response packets
         sent."
    REFERENCE "RFC 2866 section 4.2"
    ::= { radiusAccServ 8 }
```

radiusAccServTotalMalformedRequests OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of malformed RADIUS Accounting-Request packets received. Bad authenticators or unknown types are not included as malformed Access-Requests."

REFERENCE "[RFC 2866 section 3](#)"

::= { radiusAccServ 9 }

radiusAccServTotalBadAuthenticators OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Accounting-Request packets which contained an invalid authenticator."

REFERENCE "[RFC 2866 section 3](#)"

::= { radiusAccServ 10 }

radiusAccServTotalPacketsDropped OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of incoming packets silently discarded for a reason other than malformed, bad authenticators, or unknown types."

REFERENCE "[RFC 2866 section 3](#)"

::= { radiusAccServ 11 }

radiusAccServTotalNoRecords OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Accounting-Request packets which were received and responded to but not recorded."

::= { radiusAccServ 12 }

radiusAccServTotalUnknownTypes OBJECT-TYPE
SYNTAX Counter32

Nelson

Expires December 28, 2006

[Page 9]

Internet-Draft

RADIUS Acct Server MIB (IPv6)

June 2006

UNITS "packets"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of RADIUS packets of unknown type which
 were received."
REFERENCE "[RFC 2866 section 4](#)"
::= { radiusAccServ 13 }

radiusAccClientTable OBJECT-TYPE
SYNTAX SEQUENCE OF RadiusAccClientEntry
MAX-ACCESS not-accessible
STATUS deprecated
DESCRIPTION
 "The (conceptual) table listing the RADIUS accounting
 clients with which the server shares a secret."
::= { radiusAccServ 14 }

radiusAccClientEntry OBJECT-TYPE
SYNTAX RadiusAccClientEntry
MAX-ACCESS not-accessible
STATUS deprecated
DESCRIPTION
 "An entry (conceptual row) representing a RADIUS
 accounting client with which the server shares a
 secret."
INDEX { radiusAccClientIndex }
::= { radiusAccClientTable 1 }

RadiusAccClientEntry ::= SEQUENCE {
 radiusAccClientIndex Integer32,
 radiusAccClientAddress IpAddress,
 radiusAccClientID SnmpAdminString,
 radiusAccServPacketsDropped Counter32,
 radiusAccServRequests Counter32,
 radiusAccServDupRequests Counter32,
 radiusAccServResponses Counter32,
 radiusAccServBadAuthenticators Counter32,
 radiusAccServMalformedRequests Counter32,

radiusAccServNoRecords	Counter32,
radiusAccServUnknownTypes	Counter32

}

radiusAccClientIndex OBJECT-TYPE
 SYNTAX Integer32 (1..2147483647)
 MAX-ACCESS not-accessible
 STATUS deprecated
 DESCRIPTION

Nelson	Expires December 28, 2006	[Page 10]
--------	---------------------------	-----------

Internet-Draft	RADIUS Acct Server MIB (IPv6)	June 2006
----------------	-------------------------------	-----------

"A number uniquely identifying each RADIUS accounting client with which this server communicates."
 ::= { radiusAccClientEntry 1 }

radiusAccClientAddress OBJECT-TYPE
 SYNTAX IPAddress
 MAX-ACCESS read-only
 STATUS deprecated
 DESCRIPTION
 "The NAS-IP-Address of the RADIUS accounting client referred to in this table entry."
 ::= { radiusAccClientEntry 2 }

radiusAccClientID OBJECT-TYPE
 SYNTAX SnmpAdminString
 MAX-ACCESS read-only
 STATUS deprecated
 DESCRIPTION
 "The NAS-Identifier of the RADIUS accounting client referred to in this table entry. This is not necessarily the same as sysName in MIB II."
 REFERENCE "[RFC 2865 section 5.32](#)"
 ::= { radiusAccClientEntry 3 }

-- Server Counters
 --
 -- Requests - DupRequests - BadAuthenticators - MalformedRequests -
 -- UnknownTypes - PacketsDropped - Responses = Pending
 --
 -- Requests - DupRequests - BadAuthenticators - MalformedRequests -
 -- UnknownTypes - PacketsDropped - NoRecords = entries logged

radiusAccServPacketsDropped OBJECT-TYPE
 SYNTAX Counter32
 UNITS "packets"
 MAX-ACCESS read-only
 STATUS deprecated
 DESCRIPTION
 "The number of incoming packets received
 from this client and silently discarded
 for a reason other than malformed, bad
 authenticators, or unknown types."
 REFERENCE "[RFC 2866 section 3](#)"
 ::= { radiusAccClientEntry 4 }

radiusAccServRequests OBJECT-TYPE
 SYNTAX Counter32
 UNITS "packets"

Nelson Expires December 28, 2006 [Page 11]

Internet-Draft RADIUS Acct Server MIB (IPv6) June 2006

MAX-ACCESS read-only
 STATUS deprecated
 DESCRIPTION
 "The number of packets received from this
 client on the accounting port."
 REFERENCE "[RFC 2866 section 4.1](#)"
 ::= { radiusAccClientEntry 5 }

radiusAccServDupRequests OBJECT-TYPE
 SYNTAX Counter32
 UNITS "packets"
 MAX-ACCESS read-only
 STATUS deprecated
 DESCRIPTION
 "The number of duplicate RADIUS Accounting-Request
 packets received from this client."
 REFERENCE "[RFC 2866 section 4.1](#)"
 ::= { radiusAccClientEntry 6 }

radiusAccServResponses OBJECT-TYPE
 SYNTAX Counter32
 UNITS "packets"
 MAX-ACCESS read-only
 STATUS deprecated
 DESCRIPTION

"The number of RADIUS Accounting-Response packets
sent to this client."
REFERENCE "[RFC 2866 section 4.2](#)"
::= { radiusAccClientEntry 7 }

radiusAccServBadAuthenticators OBJECT-TYPE
SYNTAX Counter32
UNITS "packets"
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION
 "The number of RADIUS Accounting-Request packets
 which contained invalid authenticators received
 from this client."
REFERENCE "[RFC 2866 section 3](#)"
::= { radiusAccClientEntry 8 }

radiusAccServMalformedRequests OBJECT-TYPE
SYNTAX Counter32
UNITS "packets"
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION

Nelson

Expires December 28, 2006

[Page 12]

Internet-Draft

RADIUS Acct Server MIB (IPv6)

June 2006

"The number of malformed RADIUS Accounting-Request
packets which were received from this client.
Bad authenticators and unknown types
are not included as malformed Accounting-Requests."
REFERENCE "[RFC 2866 section 3](#)"
::= { radiusAccClientEntry 9 }

radiusAccServNoRecords OBJECT-TYPE
SYNTAX Counter32
UNITS "packets"
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION
 "The number of RADIUS Accounting-Request packets
 which were received and responded to but not
 recorded."
::= { radiusAccClientEntry 10 }

```

radiusAccServUnknownTypes OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The number of RADIUS packets of unknown type which
         were received from this client."
    REFERENCE "RFC 2866 section 4"
    ::= { radiusAccClientEntry 11 }

```

-- New MIB objects added in this revision

```

radiusAccClientExtTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF RadiusAccClientExtEntry
    MAX-ACCESS not-accessible
    STATUS      current
    DESCRIPTION
        "The (conceptual) table listing the RADIUS accounting
         clients with which the server shares a secret."
    ::= { radiusAccServ 15 }

```

```

radiusAccClientExtEntry OBJECT-TYPE
    SYNTAX      RadiusAccClientExtEntry
    MAX-ACCESS not-accessible
    STATUS      current
    DESCRIPTION
        "An entry (conceptual row) representing a RADIUS
         accounting client with which the server shares a

```

```

        secret."
    INDEX      { radiusAccClientExtIndex }
    ::= { radiusAccClientExtTable 1 }

```

```

RadiusAccClientExtEntry ::= SEQUENCE {
    radiusAccClientExtIndex      Integer32,
    radiusAccClientInetAddressType InetAddressType,
    radiusAccClientInetAddress  InetAddress,
    radiusAccClientExtID        SnmpAdminString,
    radiusAccServExtPacketsDropped Counter32,
    radiusAccServExtRequests    Counter32,

```

```

radiusAccServExtDupRequests      Counter32,
radiusAccServExtResponses        Counter32,
radiusAccServExtBadAuthenticators Counter32,
radiusAccServExtMalformedRequests Counter32,
radiusAccServExtNoRecords        Counter32,
radiusAccServExtUnknownTypes     Counter32,
radiusAccServerCounterDiscontinuity TimeTicks
}

radiusAccClientExtIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A number uniquely identifying each RADIUS accounting
         client with which this server communicates."
    ::= { radiusAccClientExtEntry 1 }

radiusAccClientInetAddressType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The type of address format used for the
         radiusAccClientInetAddress object."
    ::= { radiusAccClientExtEntry 2 }

radiusAccClientInetAddress OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The IP address of the RADIUS accounting
         client referred to in this table entry, using
         the IPv6 address format."
    ::= { radiusAccClientExtEntry 3 }

```

```

radiusAccClientExtID OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-only
    STATUS      current

```

DESCRIPTION

"The NAS-Identifier of the RADIUS accounting client referred to in this table entry. This is not necessarily the same as sysName in MIB II."

REFERENCE "[RFC 2865 section 5.32](#)"

::= { radiusAccClientExtEntry 4 }

-- Server Counters

--

-- Requests - DupRequests - BadAuthenticators - MalformedRequests -
-- UnknownTypes - PacketsDropped - Responses = Pending

--

-- Requests - DupRequests - BadAuthenticators - MalformedRequests -
-- UnknownTypes - PacketsDropped - NoRecords = entries logged

radiusAccServExtPacketsDropped OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of incoming packets received from this client and silently discarded for a reason other than malformed, bad authenticators, or unknown types. This counter may experience a discontinuity when the RADIUS Accounting Server module within the managed entity is reinitialized, as indicated by the current value of radiusAccServerCounterDiscontinuity."

REFERENCE "[RFC 2866 section 3](#)"

::= { radiusAccClientExtEntry 5 }

radiusAccServExtRequests OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of packets received from this client on the accounting port. This counter may experience a discontinuity when the RADIUS Accounting Server module within the managed entity is reinitialized, as indicated by the current value of radiusAccServerCounterDiscontinuity."

REFERENCE "[RFC 2866 section 4.1](#)"

::= { radiusAccClientExtEntry 6 }

radiusAccServExtDupRequests OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of duplicate RADIUS Accounting-Request packets received from this client. This counter may experience a discontinuity when the RADIUS Accounting Server module within the managed entity is reinitialized, as indicated by the current value of radiusAccServerCounterDiscontinuity."

REFERENCE "[RFC 2866 section 4.1](#)"

::= { radiusAccClientExtEntry 7 }

radiusAccServExtResponses OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Accounting-Response packets sent to this client. This counter may experience a discontinuity when the RADIUS Accounting Server module within the managed entity is reinitialized, as indicated by the current value of radiusAccServerCounterDiscontinuity."

REFERENCE "[RFC 2866 section 4.2](#)"

::= { radiusAccClientExtEntry 8 }

radiusAccServExtBadAuthenticators OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Accounting-Request packets which contained invalid authenticators received from this client. This counter may experience a discontinuity when the RADIUS Accounting Server module within the managed entity is reinitialized, as indicated by the current value of radiusAccServerCounterDiscontinuity."

```
::= { radiusAccClientExtEntry 9 }
```

radiusAccServExtMalformedRequests OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of malformed RADIUS Accounting-Request packets which were received from this client. Bad authenticators and unknown types are not included as malformed Accounting-Requests. This counter may experience a discontinuity when the RADIUS Accounting Server module within the managed entity is reinitialized, as indicated by the current value of radiusAccServerCounterDiscontinuity."

REFERENCE "[RFC 2866 section 3](#)"

```
::= { radiusAccClientExtEntry 10 }
```

radiusAccServExtNoRecords OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Accounting-Request packets which were received and responded to but not recorded. This counter may experience a discontinuity when the RADIUS Accounting Server module within the managed entity is reinitialized, as indicated by the current value of radiusAccServerCounterDiscontinuity."

```
::= { radiusAccClientExtEntry 11 }
```

radiusAccServExtUnknownTypes OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS packets of unknown type which were received from this client. This counter may experience a discontinuity when the RADIUS Accounting Server module within the managed entity is reinitialized, as indicated by the current value of radiusAccServerCounterDiscontinuity."

REFERENCE "[RFC 2866 section 4](#)"

::= { radiusAccClientExtEntry 12 }

Nelson

Expires December 28, 2006

[Page 17]

Internet-Draft

RADIUS Acct Server MIB (IPv6)

June 2006

radiusAccServerCounterDiscontinuity OBJECT-TYPE

SYNTAX TimeTicks

UNITS "centiseconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of centiseconds since the last discontinuity in the RADIUS Accounting Server counters. A discontinuity may be the result of a reinitialization of the RADIUS Accounting Server module within the managed entity."

::= { radiusAccClientExtEntry 13 }

-- conformance information

radiusAccServMIBConformance OBJECT IDENTIFIER

::= { radiusAccServMIB 2 }

radiusAccServMIBCompliances OBJECT IDENTIFIER

::= { radiusAccServMIBConformance 1 }

radiusAccServMIBGroups OBJECT IDENTIFIER

::= { radiusAccServMIBConformance 2 }

-- compliance statements

radiusAccServMIBCompliance MODULE-COMPLIANCE

STATUS deprecated

DESCRIPTION

"The compliance statement for accounting servers implementing the RADIUS Accounting Server MIB."

Implementation of this module is for IPv4-only entities, or for backwards compatibility use with entities that support both IPv4 and IPv6."

MODULE -- this module

MANDATORY-GROUPS { radiusAccServMIBGroup }

OBJECT radiusAccServConfigReset

WRITE-SYNTAX INTEGER { reset(2) }

DESCRIPTION "The only SETable value is 'reset' (2)."

::= { radiusAccServMIBCompliances 1 }

radiusAccServExtMIBCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

Nelson

Expires December 28, 2006

[Page 18]

Internet-Draft

RADIUS Acct Server MIB (IPv6)

June 2006

"The compliance statement for accounting servers implementing the RADIUS Accounting Server IPv6 Extensions MIB. Implementation of this module is for entities that support IPv6, or support IPv4 and IPv6."

MODULE -- this module

MANDATORY-GROUPS { radiusAccServExtMIBGroup }

OBJECT radiusAccServConfigReset

WRITE-SYNTAX INTEGER { reset(2) }

DESCRIPTION "The only SETable value is 'reset' (2)."

OBJECT radiusAccClientInetAddressType

SYNTAX InetAddressType { ipv4(1), ipv6(2) }

DESCRIPTION

"An implementation is only required to support IPv4 and globally unique IPv6 addresses."

OBJECT radiusAccClientInetAddress

SYNTAX InetAddress (SIZE (4|16))

DESCRIPTION

"An implementation is only required to support IPv4 and globally unique IPv6 addresses."

::= { radiusAccServMIBCompliances 2 }

-- units of conformance

```
radiusAccServMIBGroup OBJECT-GROUP
    OBJECTS {radiusAccServIdent,
              radiusAccServUpTime,
              radiusAccServResetTime,
              radiusAccServConfigReset,
              radiusAccServTotalRequests,
              radiusAccServTotalInvalidRequests,
              radiusAccServTotalDupRequests,
              radiusAccServTotalResponses,
              radiusAccServTotalMalformedRequests,
              radiusAccServTotalBadAuthenticators,
              radiusAccServTotalPacketsDropped,
              radiusAccServTotalNoRecords,
              radiusAccServTotalUnknownTypes,
              radiusAccClientAddress,
              radiusAccClientID,
              radiusAccServPacketsDropped,
              radiusAccServRequests,
              radiusAccServDupRequests,
```

Nelson

Expires December 28, 2006

[Page 19]

Internet-Draft

RADIUS Acct Server MIB (IPv6)

June 2006

```
radiusAccServResponses,
radiusAccServBadAuthenticators,
radiusAccServMalformedRequests,
radiusAccServNoRecords,
radiusAccServUnknownTypes
```

```
}
```

STATUS deprecated

DESCRIPTION

"The collection of objects providing management of
a RADIUS Accounting Server."

::= { radiusAccServMIBGroups 1 }

radiusAccServExtMIBGroup OBJECT-GROUP

```
    OBJECTS {radiusAccServIdent,
              radiusAccServUpTime,
              radiusAccServResetTime,
              radiusAccServConfigReset,
              radiusAccServTotalRequests,
              radiusAccServTotalInvalidRequests,
```

```

        radiusAccServTotalDupRequests,
        radiusAccServTotalResponses,
        radiusAccServTotalMalformedRequests,
        radiusAccServTotalBadAuthenticators,
        radiusAccServTotalPacketsDropped,
        radiusAccServTotalNoRecords,
        radiusAccServTotalUnknownTypes,
        radiusAccClientInetAddressType,
        radiusAccClientInetAddress,
        radiusAccClientExtID,
        radiusAccServExtPacketsDropped,
        radiusAccServExtRequests,
        radiusAccServExtDupRequests,
        radiusAccServExtResponses,
        radiusAccServExtBadAuthenticators,
        radiusAccServExtMalformedRequests,
        radiusAccServExtNoRecords,
        radiusAccServExtUnknownTypes,
        radiusAccServerCounterDiscontinuity
    }
    STATUS current
    DESCRIPTION
        "The collection of objects providing management of
        a RADIUS Accounting Server."
    ::= { radiusAccServMIBGroups 2 }

END

```

Nelson

Expires December 28, 2006

[Page 20]

Internet-Draft

RADIUS Acct Server MIB (IPv6)

June 2006

[8.](#) IANA Considerations

This document requires no new IANA assignments.

[9.](#) Security Considerations

There are management objects (radiusAccServConfigReset) defined in this MIB that have a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative

effect on network operations. These are:

radiusAccServConfigReset This object can be used to reinitialize the persistent state of any server. When set to reset(2), any persistent server state (such as a process) is reinitialized as if the server had just been started. Depending on the server implementation details, this action may or may not interrupt the processing of pending request in the server. Abuse of this object may lead to a Denial of Service attack on the server.

There are a number of managed objects in this MIB that may contain sensitive information. These are:

radiusAccClientIPAddress This can be used to determine the address of the RADIUS accounting client with which the server is communicating. This information could be useful in mounting an attack on the accounting client.

radiusAccClientInetAddress This can be used to determine the address of the RADIUS accounting client with which the server is communicating. This information could be useful in mounting an attack on the accounting client.

It is thus important to control even GET access to these objects and possibly to even encrypt the values of these object when sending them over the network via SNMP. Not all versions of SNMP provide features for such a secure environment.

SNMP versions prior to SNMPv3 do not provide a secure environment. Even if the network itself is secure (for example by using IPsec), there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [\[RFC3410\]](#), [section 8](#)), including full support for the SNMPv3 cryptographic mechanisms (for

authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator

responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

[10.](#) References

[10.1.](#) Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), April 1999.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, [RFC 2579](#), April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIv2", STD 58, [RFC 2580](#), April 1999.
- [RFC2866] Rigney, C., "RADIUS Accounting", [RFC 2866](#), June 2000.
- [RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", [RFC 4001](#), February 2005.

[10.2.](#) Informative References

- [2620bis] Nelson, D., "RADIUS Accounting Client MIB for IPv6", [draft-ietf-radext-rfc2620bis-04.txt](#) (work in progress), June 2006.
- [RFC2621] Zorn, G. and B. Aboba, "RADIUS Accounting Server MIB", [RFC 2621](#), June 1999.
- [RFC2865] Rigney, C., Willens, S., Rubens, A., and W. Simpson, "Remote Authentication Dial In User Service (RADIUS)", [RFC 2865](#), June 2000.

[RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart,
"Introduction and Applicability Statements for Internet-
Standard Management Framework", [RFC 3410](#), December 2002.

[Appendix A](#). Acknowledgments

The authors of the original MIB are Bernard Aboba and Glen Zorn.

Many thanks to all reviewers, especially to Dave Harrington, Dan Romascanu, C.M. Heard, Bruno Pape, Greg Weber and Bert Wijnen.

Internet-Draft

RADIUS Acct Server MIB (IPv6)

June 2006

Author's Address

David B. Nelson
Enterasys Networks
50 Minuteman Road
Andover, MA 01810
USA

Email: dnelson@enterasys.com

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The Internet Society (2006). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.