

Registration Protocols Extensions
Internet-Draft
Intended status: Standards Track
Expires: 3 November 2022

M. Loffredo
IIT-CNR/Registro.it
G. Brown
CentralNic Group plc
2 May 2022

Using JSContact in Registration Data Access Protocol (RDAP) JSON
Responses
draft-ietf-regext-rdap-jscontact-12

Abstract

This document describes an RDAP extension which represents entity contact information in JSON responses using JSContact.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 3 November 2022.

Copyright Notice

Copyright (c) 2022 IETFTrust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Revised BSD License.

Internet-Draft

Using JSContact in RDAP

May 2022

Table of Contents

1.	Introduction	3
1.1.	Rationale	3
1.2.	Conventions Used in This Document	3
2.	JSContact	4
3.	Using JSCard objects in RDAP Responses	4
3.1.	RDAP Query Parameters	10
4.	Transition Considerations	10
4.1.	RDAP Features Supporting a Transition Process	10
4.1.1.	Notices and Link Relationships	10
4.1.2.	rdapConformance Property	11
4.1.3.	Query Parameters	11
4.2.	Transition Procedure	11
4.2.1.	Goals	11
4.2.2.	Transition Stages	11
4.2.2.1.	Stage 1: only jCard provided	12
4.2.2.2.	Stage 2: jCard sunset	12
4.2.2.3.	Stage 3: jCard deprecation	13
4.2.2.4.	Stage 4: jCard deprecated	15
4.2.2.5.	Length	15
5.	Implementation Status	15
5.1.	IIT-CNR/Registro.it RDAP Server	15
5.2.	IIT-CNR/Registro.it RDAP Client	16
5.3.	client.rdap.org	16
5.4.	CentralNic Registry	16
6.	IANA Considerations	17
7.	Security Considerations	17
8.	Acknowledgements	17
9.	References	17
9.1.	Normative References	17
9.2.	Informative References	19
Appendix A.	jCard-JSContact Mapping	19
Appendix B.	Change Log	21
B.1.	Change from 00 to 01	21
B.2.	Change from 01 to 02	21
B.3.	Change from 02 to 03	22
B.4.	Change from 03 to 04	22
B.5.	Initial WG version	22
B.6.	Change from 00 to 01	22
B.7.	Change from 01 to 02	22
B.8.	Change from 02 to 03	22
B.9.	Change from 03 to 04	22

B.10 . Change from 04 to 05	23
B.11 . Change from 05 to 06	23
B.12 . Change from 06 to 07	23
B.13 . Change from 07 to 08	23
B.14 . Change from 08 to 09	23

B.15 . Change from 09 to 10	23
B.16 . Change from 10 to 11	23
B.17 . Change from 11 to 12	23
Authors' Addresses	23

[1](#). Introduction

This document specifies an extension to the Registration Data Access Protocol (RDAP) that allows RDAP servers to use JSContact [[I-D.ietf-calext-jscontact](#)] to represent the contact information associated with entities in RDAP responses, instead of jCard [[RFC7095](#)]. It also describes the process by which an RDAP server can transition from jCard to JSContact. RDAP query and response extensions are defined to facilitate the transition process.

[1.1](#). Rationale

According to the feedback from RDAP Pilot Working Group [[RDAP-PILOT-WG](#)], a group of RDAP server implementers representing registries and registrars of generic TLDs, the most commonly raised implementation concern, for both servers and client implementers, related to the use of jCard [[RFC7095](#)] to represent the contact information associated with entities. Working Group members reported jCard to be unintuitive, complicated to implement for both clients and servers, and incompatible with best practices for RESTful APIs.

JSContact [[I-D.ietf-calext-jscontact](#)] provides a simpler and more efficient representation for contact information with regard to time and effort saved in processing it. In addition, similarly to jCard, it provides a means to represent internationalised and unstructured contact information. Support for internationalised contact information has been recognised being necessary to facilitate the future internationalisation of registration data directory services.

[1.2](#). Conventions Used in This Document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

[2.](#) JSContact

The JSContact specification defines a data model and JSON representation of contact information that can be used for data storage and exchange in address book or directory applications. It aims to be an alternative to the vCard data format [[RFC6350](#)] and to be unambiguous, extendable and simple to process. In contrast with jCard, it is not a direct mapping from the vCard data model and expands semantics where appropriate.

The JSContact specification declares two main object types: "Card", which represents a single contact card, and "CardGroup" which represents a collection of Card objects. For the purpose of this document, only Card objects are considered. To avoid confusion, in the following of this document, the term "JSCard" is used to refer to "JSContact Card".

JSCard differs from jCard in that it:

- * follows an object-oriented rather than array-oriented approach;
- * is simple to process;
- * requires no extra work in serialization/deserialization from/to a data model;
- * includes no "jagged" arrays;
- * prefers maps rather than arrays to implement collections.

[I-D.ietf-calext-jscontact-vcard] provides informational guidance on the conversion of jCard into JSCard, and vice versa. [Appendix A](#) shows JSContact counterparts for the most commonly used jCard

properties in an RDAP response.

3. Using JSCard objects in RDAP Responses

Entity objects in RDAP responses MAY include a "jscard_0" property whose value is a JSCard object instead of the "vCardArray" property defined in [\[RFC9083\]](#).

Servers returning the "jscard_0" property in their response MUST include "jscard_0" in the "rdapConformance" array.

The JSCard "uid" property SHOULD contain the same value as the RDAP "handle" property.

Since most of the JSCard collections are represented as maps, map keys must be defined. To aid interoperability, RDAP providers are RECOMMENDED to use as map keys the following string values and labels defined in [\[RFC5733\]](#):

- * "org" in the "organizations" map when there is a single <contact:org> element. If both internationalised and localized forms exist, the key MUST be used for the internationalised form;
- * "addr" in the "addresses" map when there is a single <contact:addr> element. If both internationalised and localized forms exist, the key MUST be used for the internationalised form;
- * "email" in the "emails" map for the <contact:email> element;
- * "voice" in the "phones" map for the <contact:voice> element;
- * "fax" in the "phones" map for the <contact:fax> element.

If present, the localized versions of name, organization and postal address MUST be inserted into the "localizations" map. The following is an elided example of an RDAP entity lookup response including a JSCard object that presents the "localizations" map (See PDF for non-ASCII character string).

```
...
"jscard_0": {
  "@type" : "Card",
  "uid" : "7e0636f5-e48f-4a32-ab96-b57e9c07c7aa",
  "fullName" : "Vasya Pupkin",
  "organizations" : {
```

```

    "org" : {
      "@type" : "Organization",
      "name" : "My Company"
    }
  },
  "addresses" : {
    "addr" : {
      "@type" : "Address",
      "street" : [ {
        "@type" : "StreetComponent",
        "type" : "name",
        "value" : "1 Street"
      }, {
        "@type" : "StreetComponent",
        "type" : "postOfficeBox",
        "value" : "01001"
      } ],
      "locality" : "Kyiv",
      "countryCode" : "UA"
    }
  },
  "localizations" : {
    "ua" : {
      "/jscard_0/addresses/addr" : {
        "@type" : "Address",
        "street" : [ {

```

```

      "@type" : "StreetComponent",
      "type" : "name",
      "value" : "1, Улица"
    }, {
      "@type" : "StreetComponent",
      "type" : "postOfficeBox",
      "value" : "01001"
    } ],
    "locality" : "Киев",
    "countryCode" : "UA"
  },
  "/jscard_0/fullName" : "Вася Пупкин",
  "/jscard_0/organizations/org" : {
    "@type" : "Organization",
    "name" : "Моя Компания"
  }

```

```

    }
  }
}
...

```

Figure 1: Example of handling localizations in JSContact

Implementers MAY use different mapping schemes to define keys for additional entries of the aforementioned maps or others. For example, a mapping scheme may consist in using a trivial sequential number (e.g. "url-1", "url-2", etc.)

The following is an example of an RDAP entity including a JSCard object that has been converted from the example in [section 5.1 of \[RFC9083\]](#).

```

{
  "rdapConformance": [
    "rdap_level_0",
    "jscard_0"
  ],
  "objectClassName" : "entity",
  "handle": "XXXX",
  "jscard_0": {
    "@type": "Card",
    "uid": "XXXX",
    "fullName": "Joe User" ,
    "name": {
      "@type": "Name",
      "components": [
        {
          "@type": "NameComponent",

```

```

    "type": "surname",
    "value": "User"
  },
  {
    "@type": "NameComponent",
    "type": "personal",
    "value": "Joe"
  },

```

```

    {
      "@type": "NameComponent",
      "type": "suffix",
      "value": "ing. jr"
    },
    {
      "@type": "NameComponent",
      "type": "suffix",
      "value": "M.Sc."
    }
  ]
},
"kind": "individual",
"preferredContactLanguages": {
  "fr": {
    "@type": "ContactLanguage",
    "pref": 1
  },
  "en": {
    "@type": "ContactLanguage",
    "pref": 2
  }
},
"organizations": {
  "org": {
    "@type": "Organization",
    "name": "Example"
  }
},
"titles": {
  "title": {
    "@type": "Title",
    "title": "Research Scientist"
  },
  "role": {
    "@type": "Title",
    "title": "Project Lead"
  }
},
"addresses": {

```

```

"addr": {

```



```

    "@type": "Address",
    "contexts": {
      "work": true
    },
    "street": [
      {
        "@type": "StreetComponent",
        "type": "name",
        "value": "4321 Rue Somewhere"
      },
      {
        "@type": "StreetComponent",
        "type": "extension",
        "value": "Suite 1234"
      }
    ],
    "locality": "Quebec",
    "region": "QC",
    "postcode": "G1V 2M2",
    "country": "Canada",
    "countryCode": "CA",
    "coordinates": "geo:46.772673,-71.282945",
    "timeZone": "Etc/GMT+5"
  },
  "home": {
    "@type": "Address",
    "contexts": {
      "private": true
    },
    "fullAddress": "123 Maple Ave\nSuite 90001\nVancouver\nBC\n1239\n"
  },
  "phones": {
    "voice": {
      "@type": "Phone",
      "contexts": {
        "work": true
      },
      "features": {
        "voice": true,
        "cell": true,
        "video": true,
        "text": true
      },
      "pref": 1,
      "phone": "tel:+1-555-555-1234;ext=102"
    }
  }
}

```

```
,
"emails": {
  "email": {
    "@type": "EmailAddress",
    "contexts": {
      "work": true
    },
    "email": "joe.user@example.com"
  }
},
"online": {
  "key": {
    "@type": "Resource",
    "contexts": {
      "work": true
    },
    "type": "publicKey",
    "resource": "http://www.example.com/joe.user/joe.asc"
  },
  "url": {
    "@type": "Resource",
    "contexts": {
      "private": true
    },
    "type": "uri",
    "resource": "http://example.org"
  }
},
"roles": [ "registrar" ],
"publicIds": [
  {
    "type": "IANA Registrar ID",
    "identifier": "1"
  }
],
"remarks": [
  {
    "description": [
      "She sells sea shells down by the sea shore.",
      "Originally written by Terry Sullivan."
    ]
  }
],
"links": [
  {
```

```
"value":"http://example.com/entity/XXXX",
"rel":"self",
```

```
    "href":"http://example.com/entity/XXXX",
    "type" : "application/rdap+json"
  },
  "events":[
    {
      "eventAction":"registration",
      "eventDate":"1990-12-31T23:59:59Z"
    },
    {
      "eventAction":"last changed",
      "eventDate":"1991-12-31T23:59:59Z"
    }
  ],
  "asEventActor":[
    {
      "eventAction":"last changed",
      "eventDate":"1991-12-31T23:59:59Z"
    }
  ]
}
```

Figure 2: Example of using JSContact in RDAP response

[3.1.](#) RDAP Query Parameters

Two new query parameters are defined for the purpose of this document.

The query parameters are OPTIONAL extensions of path segments defined in [\[RFC9082\]](#). They are as follows:

- * "jscard": a boolean value that allows a client to request the "jscard_0" property in the RDAP response;
- * "jcard": a boolean value that allows a client to request the "vcardArray" property in the RDAP response.

These parameters are furtherly explained in [Section 4](#).

[4.](#) Transition Considerations

[4.1.](#) RDAP Features Supporting a Transition Process

[4.1.1.](#) Notices and Link Relationships

RDAP allows servers to communicate service information to clients through notices. According to [Section 4.3 of \[RFC9083\]](#), an RDAP response may contain one or more notice objects. Each notice may include a set of link objects, which can be used to provide clients with references and documentation. These link objects may have a "rel" property which defines the relationship type, as described in [\[RFC8288\], Section 4](#). The transition process outlined in this

Loffredo & Brown

Expires 3 November 2022

[Page 10]

Internet-Draft

Using JSContact in RDAP

May 2022

document uses two link relation types, namely "related" and "alternate", described in [\[RFC8288\]](#).

[4.1.2.](#) rdapConformance Property

The information about the specifications used in the construction of the response is also described by the strings which appear in the "rdapConformance" property of the RDAP response.

[4.1.3.](#) Query Parameters

Clients can ask servers to use the query parameters defined in [Section 3.1](#) in accordance with [\[RFC9082\]](#).

[4.2.](#) Transition Procedure

The principles of the procedure for jCard to JSCard transition are based on the best practices in [\[API-DEPRECATION\]](#).

The procedure consists of four contiguous stages. During the procedure, the presence of "jscard_0" tag in the rdapConformance array indicates that JSCard is returned instead of jCard. The date and time format used to notify clients about the stages of this procedure is defined in [\[RFC3339\]](#).

[4.2.1.](#) Goals

The procedure described in this document aims to achieve the following goals:

- * only one contact representation would be included in the response;
- * the response would always be compliant to [\[RFC9083\]](#) because:

- being the "jscard_0" property a response extension, its presence would be signaled by the "jscard_0" conformance tag;
- being "vcardArray" property optional in a response, its absence would be allowed;
- * clients would be informed about the transition timeline;
- * the backward compatibility would be guaranteed throughout the transition;
- * servers and clients could execute their transitions independently.

[4.2.2.](#) Transition Stages

Loffredo & Brown

Expires 3 November 2022

[Page 11]

Internet-Draft

Using JSCard in RDAP

May 2022

[4.2.2.1.](#) Stage 1: only jCard provided

This stage corresponds to providing jCard as the default contact card [[RFC9083](#)]. The RDAP server is not able to provide an alternate contact card. The rdapConformance array MUST NOT contain the "jscard_0" tag.

[4.2.2.2.](#) Stage 2: jCard sunset

During this stage, the server uses jCard by default, but the RDAP server will return JSCard if the client sets the query parameter "jscard" to 1/true/yes. The rdapConformance array MUST contain the "jscard_0" tag if JSCard is returned.

From this stage on, the RDAP server MUST include the "jscard_0" tag in the rdapConformance array of the help response to signal clients that JSCard can be returned instead of jCard.

The RDAP server SHOULD include a notice titled "jCard sunset end". Such a notice includes a description reporting the jCard sunset end date and time and two OPTIONAL links:

- * "related": a link to a URI-identified resource documenting the transition procedure;
- * "alternate": if JSCard is not requested, a link to an alternate

result view identified by the current query string plus the parameter "jscard" set to 1/true/yes (Figure 3); otherwise, only the "related" link can be provided (Figure 4).

```
"notices": [
  {
    "title": "jCard sunset end",
    "description": ["2022-07-01T00:00:00Z"],
    "links": [{
      "value": "http://example.net/entity/XXXX",
      "rel": "related",
      "type": "text/html",
      "href": "http://www.example.com/jcard_deprecation.html"
    },
    {
      "value": "http://example.net/entity/XXXX",
      "rel": "alternate",
      "type": "application/rdap+json",
      "href": " http://example.net/entity/XXXX?jscard=1"
    }
  ]
}]
```

Figure 3: jCard sunset - JSCard not requested

```
"notices": [
  {
    "title": "jCard sunset end",
    "description": ["2022-07-01T00:00:00Z"],
    "links": [
      {
        "value": "http://example.net/entity/XXXX?jscard=1",
        "rel": "related",
        "type": "text/html",
        "href": "http://www.example.com/jcard_deprecation.html"
      }
    ]
  }
]
```

Figure 4: jCard sunset - JSCard requested

[4.2.2.3](#). Stage 3: jCard deprecation

This stage corresponds to the provisioning of JSCard by default, but the RDAP will return jCard if the client sets the query parameter "jcard" to 1/true/yes. The rdapConformance array contains the "jscard_0" tag unless jCard is returned. The "jscard" query parameter MUST be ignored.

The RDAP server SHOULD return a notice titled "jCard deprecation end". Such a notice includes a description reporting the jCard deprecation end date and time and two OPTIONAL links:

- * "related": a link to a URI-identified resource documenting the transition procedure;
- * "alternate": if jCard is not requested, a link to an alternate result view identified by the current query string plus the parameter "jcard" set to 1/true/yes (Figure 5); otherwise, a link to the result view identified by the current query string without the parameter "jcard" (Figure 6).

```
"notices": [  
  {  
    "title": "jCard deprecation end",  
    "description": ["2022-12-31T23:59:59Z"],  
    "links": [  
      {  
        "value": "http://example.net/entity/XXXX",  
        "rel": "related",  
        "type": "text/html",  
        "href": "http://www.example.com/jcard_deprecation.html"  
      },  
    ],  
  },  
]
```

```

    {
      "value": "http://example.net/entity/XXXX",
      "rel": "alternate",
      "type": "application/rdap+json",
      "href": " http://example.net/entity/XXXX?jcard=1"
    }
  ]
}
]

```

Figure 5: jCard deprecation - jCard not requested

```

"notices": [
  {
    "title": "jCard deprecation end",
    "description": ["2022-12-31T23:59:59Z"],
    "links": [
      {
        "value": "http://example.net/entity/XXXX?jcard=1",
        "rel": "related",
        "type": "text/html",
        "href": "http://www.example.com/jcard_deprecation.html"
      },
      {
        "value": "http://example.net/entity/XXXX?jcard=1",
        "rel": "alternate",
        "type": "application/rdap+json",
        "href": " http://example.net/entity/XXXX"
      }
    ]
  }
]

```

Figure 6: jCard deprecation - jCard requested

[4.2.2.4](#). Stage 4: jCard deprecated

This stage corresponds to providing JSCard as default contact card. The RDAP server is not able to provide an alternate contact card.

The `rdapConformance` array always contains "jscard_0" tag. The RDAP server doesn't include any notice about the jCard deprecation process. Both "jscard" and "jcard" query parameters MUST be ignored.

[4.2.2.5](#). Length

The length of both jCard sunset and jCard deprecation periods are not fixed by this specification. Best practices in REST API deprecation suggest that, depending on the deprecated API's reach, user base and service offering, a convenient time could be anywhere between 3 – 8 months. Anyway, RDAP providers are RECOMMENDED to monitor the server log to figure out whether declared times need to be changed to meet client requirements.

[5](#). Implementation Status

NOTE: Please remove this section and the reference to [RFC 7942](#) prior to publication as an RFC.

This section records the status of known implementations of the protocol defined by this specification at the time of posting of this Internet-Draft, and is based on a proposal described in [RFC 7942](#) [[RFC7942](#)]. The description of implementations in this section is intended to assist the IETF in its decision processes in progressing drafts to RFCs. Please note that the listing of any individual implementation here does not imply endorsement by the IETF. Furthermore, no effort has been spent to verify the information presented here that was supplied by IETF contributors. This is not intended as, and must not be construed to be, a catalog of available implementations or their features. Readers are advised to note that other implementations may exist.

According to [RFC 7942](#), "this will allow reviewers and working groups to assign due consideration to documents that have the benefit of running code, which may serve as evidence of valuable experimentation and feedback that have made the implemented protocols more mature. It is up to the individual working groups to use this information as they see fit".

[5.1](#). IIT-CNR/Registro.it RDAP Server

- * Responsible Organization: Institute of Informatics and Telematics of National Research Council (IIT-CNR)/Registro.it
- * Location: <https://rdap.pubtest.nic.it/>

- * Description: This implementation includes support for RDAP queries using data from the public test environment of .it ccTLD.
- * Level of Maturity: This is an "alpha" test implementation.
- * Coverage: This implementation includes all of the features described in this specification.
- * Contact Information: Mario Loffredo, mario.loffredo@iit.cnr.it

[5.2.](#) IIT-CNR/Registro.it RDAP Client

- * Responsible Organization: Institute of Informatics and Telematics of National Research Council (IIT-CNR)/Registro.it
- * Location: <https://web-rdap.pubtest.nic.it/>
- * Description: This is a Javascript web-based RDAP client. RDAP responses are retrieved from RDAP servers by the browser, parsed into an HTML representation, and displayed in a format improving the user experience. RDAP responses containing JSCard objects are handled identically to those containing jCard objects. Raw versions of RDAP responses including either jCard or JSCard objects are provided.
- * Level of Maturity: This is an "alpha" test implementation.
- * Coverage: This implementation includes all of the features described in this specification.
- * Contact Information: Francesco Donini, francesco.donini@iit.cnr.it

[5.3.](#) client.rdap.org

- * Location: <https://client.rdap.org/>
- * Description: This is a web-based "single page" RDAP client. RDAP responses are retrieved from RDAP servers by the browser, and parsed into an HTML representation. RDAP responses containing JSCard objects are handled identically to those containing jCard objects.
- * Level of Maturity: This is an "alpha" test implementation.
- * Coverage: This implementation implements client support for parsing JSCard objects in RDAP responses.
- * Contact Information: Gavin Brown, feedback@rdap.org

[5.4.](#) CentralNic Registry

- * Responsible Organization: CentralNic Group PLC
- * Location: <https://rdap.centralnic.com/{tld}>
- * Description: This server is the product RDAP service for all top-level domains on the CentralNic registry platform.
- * Level of Maturity: Production quality.
- * Coverage: This implementation includes all of the features described in this specification.
- * Contact Information: support@centralnic.com

[6.](#) IANA Considerations

IANA is requested to register the following values in the RDAP Extensions Registry:

- * Extension identifier: jscard_0
- * Registry operator: Any
- * Published specification: This document.
- * Contact: IETF <iesg@ietf.org>
- * Intended usage: This extension represents a contact card provided in an RDAP response according to the JSContact specification [[I-D.ietf-calext-jscontact](#)].

[7.](#) Security Considerations

Unlike jCard, the formatted name as well as any other personally identifiable information is not required in JSCard. The only mandatory property, namely "uid", is not a sensitive information as it happens, instead, for the "fn" property in jCard. Therefore, redacted properties can be merely excluded without using placeholder values. This means that, with reference to what is described in [[I-D.ietf-regext-rdap-redacted](#)], only the "Removal" method can be used for redacting JSContact properties whereas the "Empty Value" is also used for redacting jCard.

[8.](#) Acknowledgements

The authors would like to acknowledge the following individuals for their contributions to this document: Jasdip Singh and Francesco Donini.

[9.](#) References

[9.1.](#) Normative References

- [[I-D.ietf-calext-jscontact](#)]
Stepanek, R. and M. Loffredo, "JSContact: A JSON representation of contact data", Work in Progress, Internet-Draft, [draft-ietf-calext-jscontact-00](#), 17 January 2020, <<https://www.ietf.org/archive/id/draft-ietf-calext->

[jscontact-00.txt](#)>.

[I-D.ietf-calext-jscontact-vcard]

Loffredo, M. and R. Stepanek, "JSContact: Converting from and to vCard", Work in Progress, Internet-Draft, [draft-ietf-calext-jscontact-vcard-00](#), 7 March 2022, <<https://www.ietf.org/archive/id/draft-ietf-calext-jscontact-vcard-00.txt>>.

Loffredo & Brown

Expires 3 November 2022

[Page 17]

Internet-Draft

Using JSContact in RDAP

May 2022

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC3339] Klyne, G. and C. Newman, "Date and Time on the Internet: Timestamps", [RFC 3339](#), DOI 10.17487/RFC3339, July 2002, <<https://www.rfc-editor.org/info/rfc3339>>.
- [RFC5733] Hollenbeck, S., "Extensible Provisioning Protocol (EPP) Contact Mapping", STD 69, [RFC 5733](#), DOI 10.17487/RFC5733, August 2009, <<https://www.rfc-editor.org/info/rfc5733>>.
- [RFC6350] Perreault, S., "vCard Format Specification", [RFC 6350](#), DOI 10.17487/RFC6350, August 2011, <<https://www.rfc-editor.org/info/rfc6350>>.
- [RFC7095] Kewisch, P., "jCard: The JSON Format for vCard", [RFC 7095](#), DOI 10.17487/RFC7095, January 2014, <<https://www.rfc-editor.org/info/rfc7095>>.
- [RFC7942] Sheffer, Y. and A. Farrel, "Improving Awareness of Running Code: The Implementation Status Section", [BCP 205](#), [RFC 7942](#), DOI 10.17487/RFC7942, July 2016, <<https://www.rfc-editor.org/info/rfc7942>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8288] Nottingham, M., "Web Linking", [RFC 8288](#), DOI 10.17487/RFC8288, October 2017, <<https://www.rfc-editor.org/info/rfc8288>>.

- [RFC8605] Hollenbeck, S. and R. Carney, "vCard Format Extensions: ICANN Extensions for the Registration Data Access Protocol (RDAP)", [RFC 8605](#), DOI 10.17487/RFC8605, May 2019, <<https://www.rfc-editor.org/info/rfc8605>>.
- [RFC9082] Hollenbeck, S. and A. Newton, "Registration Data Access Protocol (RDAP) Query Format", STD 95, [RFC 9082](#), DOI 10.17487/RFC9082, June 2021, <<https://www.rfc-editor.org/info/rfc9082>>.
- [RFC9083] Hollenbeck, S. and A. Newton, "JSON Responses for the Registration Data Access Protocol (RDAP)", STD 95, [RFC 9083](#), DOI 10.17487/RFC9083, June 2021, <<https://www.rfc-editor.org/info/rfc9083>>.

[9.2](#). Informative References

[API-DEPRECATION]

Sandoval, K., "How to Smartly Sunset and Deprecate APIs", August 2019, <<https://web.archive.org/web/20200417084255/https://nordicapis.com/how-to-smartly-sunset-and-deprecate-apis/>>.

[I-D.ietf-jsonpath-base]

Gössner, S., Normington, G., and C. Bormann, "JSONPath: Query expressions for JSON", Work in Progress, Internet-Draft, [draft-ietf-jsonpath-base-03](#), 16 January 2022, <<https://www.ietf.org/archive/id/draft-ietf-jsonpath-base-03.txt>>.

[I-D.ietf-regext-rdap-redacted]

Gould, J., Smith, D., Kolker, J., and R. Carney, "Redacted Fields in the Registration Data Access Protocol (RDAP) Response", Work in Progress, Internet-Draft, [draft-ietf-regext-rdap-redacted-02](#), 18 November 2021, <<https://www.ietf.org/archive/id/draft-ietf-regext-rdap-redacted-02.txt>>.

[RDAP-PILOT-WG]

ICANN RDAP Pilot WG, "RDAP Pilot Report", April 2019, <<https://www.icann.org/en/system/files/files/rdap-pilot->

[Appendix A](#). jCard-JSContact Mapping

Provided that the keys defined in [Section 3](#) are used for the JSContact maps, the mapping between the most commonly used jCard properties in an RDAP response and their JSContact counterparts is shown in the following. The mapping is done through the use of a JSONPath expression [[I-D.ietf-jsonpath-base](#)].

jCard property: fn

Reference: [Section 6.2.1 of \[RFC6350\]](#)

Path: `$..vcardArray[1][?(@[0]=='fn')][3]`

JSContact property: fullName

Reference: Section 2.2.2 of [[I-D.ietf-calext-jscontact](#)]

Path: `$..jscard_0.fullName`

jCard property: org

Reference: [Section 6.6.4 of \[RFC6350\]](#)

Path: `$..vcardArray[1][?(@[0]=='org')][3]`

JSContact property: Organization.name

Reference: Section 2.2.4 of [[I-D.ietf-calext-jscontact](#)]

Path: `$..jscard_0.organizations.org.name`

jCard property: tel with type="voice"

Reference: [Section 6.4.1 of \[RFC6350\]](#)

Path: `$..vcardArray[1][?(@[1].type=='voice')][3]`

JSContact property: Phone.phone

Reference: Section 2.3.2 of [[I-D.ietf-calext-jscontact](#)]

Path: `$..jscard_0.phones.voice.phone`

jCard property: tel with type="fax"

Reference: [Section 6.4.1 of \[RFC6350\]](#)

Path: `$..vcardArray[1][?(@[1].type=='fax')][3]`

JSContact property: Phone.phone

Reference: Section 2.3.2 of [[I-D.ietf-calext-jscontact](#)]

Path: `$..jscard_0.phones.fax.phone`

jCard property: email

Reference: [Section 6.4.2 of \[RFC6350\]](#)

Path: `$..vcardArray[1][?(@[0]=='email')][3]`

JSContact property: Email.email
Reference: Section 2.3.1 of [[I-D.ietf-calext-jscontact](#)]
Path: \$..jscard_0.emails.email.email

jCard property: "post office box" component of adr
Reference: [Section 6.3.1 of \[RFC6350\]](#)
Path: \$..vcardArray[1][?(@[0]=='adr')][3][1]
JSContact property: "postOfficeBox" StreetComponent of Address.street
Reference: Section 2.4.1 of [[I-D.ietf-calext-jscontact](#)]
Path: \$..jscard_0.addresses.adr.street[?(@.type=='postOfficeBox')].value

jCard property: "street address" component of adr
Reference: [Section 6.3.1 of \[RFC6350\]](#)
Path: \$..vcardArray[1][?(@[0]=='adr')][3][2]
JSContact property: "name" StreetComponent of Address.street
Reference: Section 2.4.1 of [[I-D.ietf-calext-jscontact](#)]
Path: \$..jscard_0.addresses.adr.street[?(@.type=='name')].value

jCard property: "locality" component of adr
Reference: [Section 6.3.1 of \[RFC6350\]](#)
Path: \$..vcardArray[1][?(@[0]=='adr')][3][3]
JSContact property: Address.locality
Reference: Section 2.4.1 of [[I-D.ietf-calext-jscontact](#)]
Path: \$..jscard_0.addresses.adr.locality

jCard property: "region" component of adr
Reference: [Section 6.3.1 of \[RFC6350\]](#)

Path: \$..vcardArray[1][?(@[0]=='adr')][3][4]
JSContact property: Address.region
Reference: Section 2.4.1 of [[I-D.ietf-calext-jscontact](#)]
Path: \$..jscard_0.addresses.adr.region

jCard property: "postal code" component of adr
Reference: [Section 6.3.1 of \[RFC6350\]](#)
Path: \$..vcardArray[1][?(@[0]=='adr')][3][5]
JSContact property: Address.postcode
Reference: Section 2.4.1 of [[I-D.ietf-calext-jscontact](#)]
Path: \$..jscard_0.addresses.adr.postcode

jCard property: "country name" component of adr
Reference: [Section 6.3.1 of \[RFC6350\]](#)
Path: `$..vcardArray[1][?(@[0]=='adr')][3][6]`
JSContact property: Address.country
Reference: Section 2.4.1 of [[I-D.ietf-calext-jscontact](#)]
Path: `$..jscard_0.addresses.adr.country`

jCard property: "cc" parameter of adr
Reference: [Section 3.1 of \[RFC8605\]](#)
Path: `$..vcardArray[1][?(@[0]=='adr')][1].cc`
JSContact property: Address.countryCode
Reference: Section 2.4.1 of [[I-D.ietf-calext-jscontact](#)]
Path: `$..jscard_0.addresses.adr.countryCode`

[Appendix B](#). Change Log

[B.1](#). Change from 00 to 01

1. Changed category from "Best Current Practice" to "Standards Track"
2. Replaced the example of Figure 2
3. Changed the title of the "Migration from JCard to JSCard" section to "Transition Considerations"
4. Added [Section 3.1](#)
5. Updated [Section 6](#)
6. Updated [Section 7](#)
7. Rearranged the description of stage 1 in [Section 4.2.2](#)
8. Changed the names of the transition stages 1 and 2
9. Corrected Figure 3, Figure 5, Figure 6
10. Changed the rdapConformance tag "jscard_level_0" to "jscard"
11. Removed the "Best Practices for deprecating a REST API features" section, but added a useful reference.

[B.2](#). Change from 01 to 02

1. Removed the sentence "which cannot be represented using jCard" in [Section 1.1](#).

[B.3](#). Change from 02 to 03

1. Updated section "Conventions Used in This Document".
2. Updated the contact in "IANA Considerations" section.
3. Changed the reference [draft-loffredo-calext-jscontact-vcard](#) to [draft-ietf-calext-jscontact-vcard](#).
4. Added reference to [RFC8174](#).
5. Other minor edits.

[B.4.](#) Change from 03 to 04

1. Updated the reference [draft-dalal-deprecation-header](#) to [draft-ietf-httpapi-deprecation-header](#).

[B.5.](#) Initial WG version

1. Ported from [draft-loffredo-regext-rdap-jcard-deprecation-04](#) renamed to [draft-ietf-regext-rdap-jscontact-00](#).

[B.6.](#) Change from 00 to 01

1. Updated [Section 3](#) and Figure 2.

[B.7.](#) Change from 01 to 02

1. Updated [Section 2](#) and Figure 2.

[B.8.](#) Change from 02 to 03

1. Replaced references to obsolete [RFC7482](#) and [RFC7483](#) with [RFC9082](#) and [RFC9083](#).
2. Updated [Section 3](#) and Figure 2.

[B.9.](#) Change from 03 to 04

1. Changed the references to Internet Drafts.
2. Added an example showing how localizations are treated in JSContact.
3. Changed the position of section "Goals" in [Section 4.2](#).
4. Added three more implementations to [Section 5](#).
5. Changed the rdapConformance tag "jscard" to "jscard_0"
6. Added clarifications addressing the feedback provided by Jasdip Singh about version -03.
7. Added [Section 8](#).
8. Other minor edits.

[B.10.](#) Change from 04 to 05

1. Updated Figure 2 to make it compliant with [draft-ietf-jmap-jscontact-09](#).

[B.11.](#) Change from 05 to 06

1. Reviewed the notices presented in [Section 4.2.2.2](#) and [Section 4.2.2.3](#).

[B.12.](#) Change from 06 to 07

1. Corrected the JSON Pointer expressions in Figure 1.
2. Other minor edits.

[B.13.](#) Change from 07 to 08

1. Corrected a nit in Figure 1.
2. Removed the reference to [draft-ietf-httpapi-deprecation-header](#).
3. Replaced the "deprecation" link relation type with "related".
4. Moved the references to JSContact drafts to the "Normative References" section.

[B.14.](#) Change from 08 to 09

1. Updated the references to JSContact drafts due to the transfer from JMAP to CalExt.

[B.15.](#) Change from 09 to 10

1. Updated Figure 2 to make it compliant with [draft-ietf-calex-jscontact-02](#).

[B.16.](#) Change from 10 to 11

1. Added Appendix "jCard-JSContact Mapping".

[B.17.](#) Change from 11 to 12

1. Renamed the "jscard" property to "jscard_0".
2. Corrected JSONPath expressions in [Appendix A](#).

Authors' Addresses

Internet-Draft

Using JSContact in RDAP

May 2022

Mario Loffredo
IIT-CNR/Registro.it
Via Moruzzi,1
56124 Pisa
Italy
Email: mario.loffredo@iit.cnr.it
URI: <http://www.iit.cnr.it>

Gavin Brown
CentralNic Group plc
Saddlers House, 44 Gutter Lane
London
EC2V 6BR
United Kingdom
Phone: +44 20 33 88 0600
Email: gavin.brown@centralnic.com
URI: <https://www.centralnic.com>

