

Workgroup: RIFT WG  
Internet-Draft: draft-ietf-rift-yang-07  
Published: 9 June 2023  
Intended Status: Standards Track  
Expires: 11 December 2023  
Authors: Z. Zhang                    Y. Wei                    S. Ma  
          ZTE Corporation        ZTE Corporation        Google  
          X. Liu                    B. Rijsman  
          IBM Corporation        Individual  
          **A YANG Data Model for Routing in Fat Trees (RIFT)**

## Abstract

This document defines a YANG data model for the configuration and management of Routing in Fat Trees (RIFT) Protocol.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 11 December 2023.

## Copyright Notice

Copyright (c) 2023 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

## Table of Contents

- [1. Introduction](#)
  - [1.1. Terminology](#)
  - [1.2. Conventions Used in This Document](#)
  - [1.3. Tree Diagrams](#)
  - [1.4. Prefixes in Data Node Names](#)
- [2. Design of the Data Model](#)
  - [2.1. Scope of Model](#)
  - [2.2. Specification](#)
  - [2.3. Overview](#)
  - [2.4. RIFT configuration](#)
  - [2.5. RIFT State](#)
  - [2.6. Notifications](#)
- [3. RIFT YANG model](#)
- [4. Security Considerations](#)
- [5. IANA Considerations](#)
- [6. Acknowledgement](#)
- [7. References](#)
  - [7.1. Normative References](#)
  - [7.2. Informative References](#)
- [Authors' Addresses](#)

### 1. Introduction

[[I-D.ietf-rift-rift](#)] introduces the protocol definition of RIFT. This document defines a YANG data model that can be used to configure and manage the RIFT protocol. The model is based on YANG 1.1 as defined in [[RFC7950](#)] and conforms to the Network Management Datastore Architecture (NDMA) as described in [[RFC8342](#)]

#### 1.1. Terminology

The terminology for describing YANG data models is found in [[RFC6020](#)] and [[RFC7950](#)], including:

\*augment

\*container

\*choice

\*data model

\*data node

\*grouping

\*identity

- \*leaf
- \*leaf-list
- \*list
- \*module
- \*uses

The following abbreviations are used in this document and the defined model:

RIFT: Routing in Fat Trees [[I-D.ietf-rift-rift](#)].

### 1.2. Conventions Used in This Document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

### 1.3. Tree Diagrams

Tree diagrams used in this document follow the notation defined in [[RFC8340](#)].

### 1.4. Prefixes in Data Node Names

In this document, names of data nodes, actions, and other data model objects are often used without a prefix, as long as it is clear from the context in which YANG module each name is defined. Otherwise, names are prefixed using the standard prefix associated with the corresponding YANG module, as shown in Table 1.

Prefix	YANG module	Reference
yang	ietf-yang-types	[ <a href="#">RFC6991</a> ]
inet	ietf-inet-types	[ <a href="#">RFC6991</a> ]
rt	ietf-routing	[ <a href="#">RFC8349</a> ]
if	ietf-interfaces	[ <a href="#">RFC8343</a> ]
rt-types	ietf-routing-types	[ <a href="#">RFC8294</a> ]
iana-rt-types	iana-routing-types	[ <a href="#">RFC8294</a> ]
key-chain	ietf-key-chain	[ <a href="#">RFC8177</a> ]

Table 1

## 2. Design of the Data Model

### 2.1. Scope of Model

The model covers RIFT [[I-D.ietf-rift-rift](#)].

This model can be used to configure and manage the RIFT protocol. The operational state data and statistics can be retrieved by this model. The subscription and push mechanism defined in [[RFC8639](#)] and [[RFC8641](#)] can be implemented by the user to subscribe to notifications on the data nodes in this model.

The model contains all the basic configuration parameters to operate the protocol. Depending on the implementation choices, some systems may not allow some of the advanced parameters to be configurable. The occasionally implemented parameters are modeled as optional features in this model. This model can be extended, and it has been structured in a way that such extensions can be conveniently made.

The RIFT YANG module augments the /routing/control-plane-protocols/control-plane-protocol path defined in the ietf-routing module. The ietf-rift model defines a single instance of RIFT. Multiple instances are instantiated as multiple control-plane protocols instances.

### 2.2. Specification

This model imports and augments ietf-routing YANG model defined in [[RFC8349](#)]. Both configuration branch and state branch of [[RFC8349](#)] are augmented. The configuration branch covers node base and policy configuration. The container "rift" is the top level container in this data model. The presence of this container is expected to enable RIFT protocol functionality.

The YANG data model defined in this document conforms to the Network Management Datastore Architecture (NMDA) [[RFC8342](#)]. The operational state data is combined with the associated configuration data in the same hierarchy [[RFC8407](#)].

### 2.3. Overview

The RIFT YANG module defined in this document has all the common building blocks for the RIFT protocol.

The RIFT YANG module augments the /routing/control-plane-protocols/control-plane-protocol path defined in the ietf-routing module. The ietf-rift model defines a single instance of RIFT. Multiple instances are instantiated as multiple control-plane protocols instances.

```

module: ietf-rift
augment /rt:routing/rt:control-plane-protocols
      /rt:control-plane-protocol:
  +--rw rift
    +--rw name?                string
    +--ro level?               level
    +--rw system-id            system-id
    +--rw pod?                  uint32
    +--rw configured-level?    level
    +--rw overload
      | +--rw overload?        boolean
      | +--rw (timeout-type)?
      |   +--:(on-startup)
      |   | +--rw on-startup-timeout?
      |   |   rt-types:timer-value-seconds16
      |   +--:(immediate)
      |   +--rw immediate-timeout?
      |   rt-types:timer-value-seconds16
    +--ro proto-major-ver      uint8
    +--ro proto-minor-ver      uint16
    +--rw hierarchy-indications? enumeration
    +--rw flood-reduction?     boolean
    +--rw nonce-increasing-interval? uint16
    +--rw maximum-nonce-delta? uint8 {nonce-delta-adjust}?
    +--rw adjusted-lifetime?
      | rt-types:timer-value-seconds16
    +--rw rx-lie-multicast-addr
      | +--rw ipv4? inet:ipv4-address
      | +--rw ipv6? inet:ipv6-address
    +--rw tx-lie-multicast-addr
      | +--rw ipv4? inet:ipv4-address
      | +--rw ipv6? inet:ipv6-address
    +--rw lie-tx-port?          inet:port-number
    +--rw global-link-capabilities
      | +--rw bfd?              boolean
      | +--rw v4-forwarding-capable? boolean
      | +--rw mtu-size?         uint32
    +--rw rx-flood-port?       inet:port-number
    +--rw global-holdtime?
      | rt-types:timer-value-seconds16
    +--rw tide-generation-interval?
      | rt-types:timer-value-seconds16
    +--rw tie-security {tie-security}?
      | +--rw (auth-key-chain)?
      |   +--:(auth-key-chain)
      |   | +--rw key-chain?    key-chain:key-chain-ref
      |   +--:(auth-key-explicit)
      |   +--rw key-id?         uint32
      |   +--rw key?            string

```

```

|         +--rw crypto-algorithm?  identityref
+--rw algorithm-type?                enumeration
+--rw instance-label?               uint32 {label-switching}?
+--ro hal
|   +--ro hal-value?    level
|   +--ro system-id*   system-id
+--ro miscabled-links*          linkid-type
+--rw interface* [name]
|   +--ro link-id?          linkid-type
|   +--rw name              if:interface-ref
|   +--rw cost?            uint32
|   +--rw address-families*
|   |   iana-rt-types:address-family
|   +--rw advertised-source-addr
|   |   +--rw ipv4?    inet:ipv4-address
|   |   +--rw ipv6?    inet:ipv6-address
|   +--ro direction-type?    enumeration
|   +--rw security {tie-security}?
|   |   +--rw (auth-key-chain)?
|   |   |   +---:(auth-key-chain)
|   |   |   |   +--rw key-chain?    key-chain:key-chain-ref
|   |   |   +---:(auth-key-explicit)
|   |   |   |   +--rw key-id?      uint32
|   |   |   |   +--rw key?        string
|   |   |   |   +--rw crypto-algorithm?  identityref
|   +--rw security-checking?    enumeration
|   +--ro was-the-last-lie-accepted?  boolean
|   +--ro last-lie-reject-reason?    string
|   +--ro advertised-in-lies
|   |   +--ro you-are-flood-repeater?    boolean
|   |   +--ro not-a-ztp-offer?          boolean
|   |   +--ro you-are-sending-too-quickly?  boolean
|   +--rw link-capabilities
|   |   +--rw bfd?                    boolean
|   |   +--rw v4-forwarding-capable?  boolean
|   |   +--rw mtu-size?              uint32
|   +--ro state                      enumeration
|   +--ro number-of-flaps?           uint32
|   +--ro last-state-change?        yang:date-and-time
+--ro neighbor* [system-id]
|   +--ro name?                      string
|   +--ro level?                     level
|   +--ro system-id                  system-id
|   +--ro pod?                       uint32
|   +--ro protocol-version?         uint16
|   +--ro sent-offer
|   |   +--ro level?                 level
|   |   +--ro not-a-ztp-offer?     boolean
|   +--ro received-offer

```

```

| | +--ro level? level
| | +--ro not-a-ztp-offer? boolean
| | +--ro best? boolean
| | +--ro removed-from-consideration? boolean
| | +--ro removal-reason? string
| +--ro received-source-addr
| | +--ro ipv4? inet:ipv4-address
| | +--ro ipv6? inet:ipv6-address
| +--ro link-id-pair* [remote-id]
| | +--ro local-id? uint32
| | +--ro remote-id uint32
| | +--ro if-index? uint32
| | +--ro if-name? if:interface-ref
| | +--ro address-families* iana-rt-types:address-family
| +--ro cost? uint32
| +--ro bandwidth? uint32
| +--ro received-link-capabilities
| | +--ro bfd? boolean
| | +--ro v4-forwarding-capable? boolean
| | +--ro mtu-size? uint32
| +--ro received-in-lies
| | +--ro you-are-flood-repeater? boolean
| | +--ro not-a-ztp-offer? boolean
| | +--ro you-are-sending-too-quickly? boolean
| +--ro tx-flood-port? inet:port-number
| +--ro bfd-up? boolean
| +--ro outer-security-key-id? uint8
+--ro database
  +--ro tie* [direction-type originator tie-type tie-number]
    +--ro direction-type enumeration
    +--ro originator system-id
    +--ro tie-type enumeration
    +--ro tie-number uint32
    +--ro seq? uint64
    +--ro origination-time? uint32
    +--ro origination-lifetime? uint32
    +--ro node
      | +--ro level? level
      | +--ro neighbor* [system-id]
      | | +--ro name? string
      | | +--ro level? level
      | | +--ro system-id system-id
      | | +--ro pod? uint32
      | | +--ro link-id-pair* [remote-id]
      | | | +--ro local-id? uint32
      | | | +--ro remote-id uint32
      | | | +--ro if-index? uint32
      | | | +--ro if-name? if:interface-ref
      | | | +--ro address-families*

```

```

| | | iana-rt-types:address-family
| | +--ro cost? uint32
| | +--ro bandwidth? uint32
| | +--ro received-link-capabilities
| |   +--ro bfd? boolean
| |   +--ro v4-forwarding-capable? boolean
| |   +--ro mtu-size? uint32
| +--ro proto-minor-ver? uint16
| +--ro flood-reduction? boolean
| +--ro hierarchy-indications
| | +--ro hierarchy-indications? enumeration
| +--ro overload-flag? boolean
| +--ro name? string
| +--ro pod? uint32
| +--ro startup-time? yang:date-and-time
| +--ro miscabled-links* linkid-type
+--ro prefixes
| +--ro prefix* [prefix]
|   +--ro prefix inet:ip-prefix
|   +--ro metric? uint32
|   +--ro tags* uint64
|   +--ro monotonic-clock
|   | +--ro prefix-sequence-type
|   |   +--ro timestamp
|   |   | ieee802-1as-timestamp-type
|   |   +--ro transaction-id? uint8
|   +--ro loopback? boolean
|   +--ro directly-attached? boolean
|   +--ro from-link? linkid-type
+--ro positive-disagg-prefixes
| +--ro positive-disagg-prefix*
|   [positive-disagg-prefix]
|   +--ro positive-disagg-prefix inet:ip-prefix
|   +--ro metric? uint32
|   +--ro tags* uint64
|   +--ro monotonic-clock
|   | +--ro prefix-sequence-type
|   |   +--ro timestamp
|   |   | ieee802-1as-timestamp-type
|   |   +--ro transaction-id? uint8
|   +--ro loopback? boolean
|   +--ro directly-attached? boolean
|   +--ro from-link? linkid-type
+--ro negative-disagg-prefixes
| +--ro negative-disagg-prefix*
|   [negative-disagg-prefix]
|   +--ro negative-disagg-prefix inet:ip-prefix
|   +--ro metric? uint32
|   +--ro tags* uint64

```



```

|   +--ro monotonic-clock
|   |   +--ro prefix-sequence-type
|   |   |   +--ro timestamp
|   |   |   |   ieee802-1as-timestamp-type
|   |   |   +--ro transaction-id?   uint8
|   +--ro loopback?                 boolean
|   +--ro directly-attached?        boolean
|   +--ro from-link?                 linkid-type
+--ro external-prefixes
| +--ro external-prefix* [external-prefix]
|   +--ro external-prefix           inet:ip-prefix
|   +--ro metric?                   uint32
|   +--ro tags*                      uint64
|   +--ro monotonic-clock
|   |   +--ro prefix-sequence-type
|   |   |   +--ro timestamp
|   |   |   |   ieee802-1as-timestamp-type
|   |   |   +--ro transaction-id?   uint8
|   +--ro loopback?                 boolean
|   +--ro directly-attached?        boolean
|   +--ro from-link?                 linkid-type
+--ro positive-ext-disagg-prefixes
| +--ro positive-ext-disagg-prefix*
|   [positive-ext-disagg-prefix]
|   +--ro positive-ext-disagg-prefix inet:ip-prefix
|   +--ro metric?                   uint32
|   +--ro tags*                      uint64
|   +--ro monotonic-clock
|   |   +--ro prefix-sequence-type
|   |   |   +--ro timestamp
|   |   |   |   ieee802-1as-timestamp-type
|   |   |   +--ro transaction-id?   uint8
|   +--ro loopback?                 boolean
|   +--ro directly-attached?        boolean
|   +--ro from-link?                 linkid-type
+--ro key-value
    +--ro key?      binary
    +--ro value?    binary

```

notifications:

```

+---n error-set
+--ro tie-level-error
| +--ro tie* [originator]
|   +--ro direction-type?      enumeration
|   +--ro originator           system-id
|   +--ro tie-type?            enumeration
|   +--ro tie-number?          uint32
|   +--ro seq?                 uint64
|   +--ro origination-time?    uint32

```

```

|   +--ro origination-lifetime?   uint32
+--ro neighbor-error
  +--ro neighbor* [system-id]
    +--ro name?                   string
    +--ro level?                  level
    +--ro system-id               system-id
    +--ro pod?                    uint32
    +--ro protocol-version?       uint16
    +--ro sent-offer
      | +--ro level?              level
      | +--ro not-a-ztp-offer?    boolean
    +--ro received-offer
      | +--ro level?              level
      | +--ro not-a-ztp-offer?    boolean
      | +--ro best?               boolean
      | +--ro removed-from-consideration? boolean
      | +--ro removal-reason?     string
    +--ro received-source-addr
      | +--ro ipv4?   inet:ipv4-address
      | +--ro ipv6?   inet:ipv6-address
    +--ro link-id-pair* [remote-id]
      | +--ro local-id?      uint32
      | +--ro remote-id     uint32
      | +--ro if-index?     uint32
      | +--ro if-name?      if:interface-ref
      | +--ro address-families*
      |   iana-rt-types:address-family
    +--ro cost?               uint32
    +--ro bandwidth?         uint32
    +--ro received-link-capabilities
      | +--ro bfd?           boolean
      | +--ro v4-forwarding-capable? boolean
      | +--ro mtu-size?     uint32
    +--ro received-in-lies
      | +--ro you-are-flood-repeater?    boolean
      | +--ro not-a-ztp-offer?          boolean
      | +--ro you-are-sending-too-quickly? boolean
    +--ro tx-flood-port?   inet:port-number
    +--ro bfd-up?          boolean
    +--ro outer-security-key-id?  uint8

```

## 2.4. RIFT configuration

The configuration data nodes cover node configuration attributes. RIFT configurations require node base information configurations. Some features can be used to enhance protocol, such as BFD, flooding-reducing, community attribute.

## 2.5. RIFT State

The state data nodes include node, neighbor, database and kv-store information.

## 2.6. Notifications

Unexpected TIE and neighbor's layer error should be notified.

## 3. RIFT YANG model

This module references [[I-D.ietf-rift-rift](#)], [[RFC5881](#)], [[RFC6991](#)], [[RFC8177](#)], [[RFC8294](#)], [[RFC8343](#)], [[RFC8349](#)], [[RFC8505](#)], [[IEEE8021AS](#)].

```
<CODE BEGINS> file "ietf-rift@2023-06-02.yang"
```

```
module ietf-rift {  
  
    yang-version 1.1;  
  
    namespace "urn:ietf:params:xml:ns:yang:ietf-rift";  
    prefix rift;  
  
    import ietf-inet-types {  
        prefix "inet";  
        reference "RFC 6991: Common YANG Data Types";  
    }  
  
    import ietf-yang-types {  
        prefix "yang";  
        reference "RFC 6991: Common YANG Data Types";  
    }  
  
    import ietf-routing {  
        prefix "rt";  
        reference  
            "RFC 8349: A YANG Data Model for Routing Management  
            (NMDA Version)";  
    }  
  
    import ietf-interfaces {  
        prefix "if";  
        reference  
            "RFC 8343: A YANG Data Model for Interface Management";  
    }  
  
    import ietf-routing-types {  
        prefix "rt-types";  
        reference  
            "RFC 8294: Common YANG Data Types for the Routing Area";  
    }  
  
    import iana-routing-types {  
        prefix "iana-rt-types";  
        reference  
            "RFC 8294: Common YANG Data Types for the Routing Area";  
    }  
  
    import ietf-key-chain {  
        prefix "key-chain";  
        reference  
            "RFC 8177: YANG Data Model for Key Chains";  
    }  
}
```

organization

"IETF RIFT (Routing In Fat Trees) Working Group";

contact

"WG Web: <<http://tools.ietf.org/wg/rift/>>

WG List: <<mailto:rift@ietf.org>>

Editor: Zheng Zhang  
<<mailto:zhang.zheng@zte.com.cn>>

Editor: Yuehua Wei  
<<mailto:wei.yuehua@zte.com.cn>>

Editor: Shaowen Ma  
<<mailto:mashaowen@gmail.com>>

Editor: Xufeng Liu  
<<mailto:xufeng.liu.ietf@gmail.com>>

Editor: Bruno Rijsman  
<<mailto:brunorijsman@gmail.com>>";

// RFC Ed.: replace XXXX with actual RFC number and remove

// this note

description

"The module defines the YANG definitions for Routing in Fat Trees (RIFT).

Copyright (c) 2021 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX (<https://www.rfc-editor.org/info/rfcXXXX>); see the RFC itself for full legal notices.

The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED', 'MAY', and 'OPTIONAL' in this document are to be interpreted as described in BCP 14 (RFC 2119) (RFC 8174) when, and only when, they appear in all capitals, as shown here.";

```

revision 2023-06-02 {
  description "Initial revision.";
  reference "RFC XXXX: A YANG Data Model for RIFT.";
}

/*
 * Features
 */

feature nonce-delta-adjust {
  description
    "Support weak nonce delta adjusting which is used in security
    in section 4.4.";
  reference
    "I-D.ietf-rift-rift: RIFT: Routing in Fat Trees";
}

feature label-switching {
  description
    "Support label switching for instance distinguishing in
    section 4.3.7.";
  reference
    "I-D.ietf-rift-rift: RIFT: Routing in Fat Trees";
}

feature tie-security {
  description
    "Support security function described in section 4.4.3 for
    the TIE exchange.";
  reference
    "I-D.ietf-rift-rift: RIFT: Routing in Fat Trees";
}

typedef system-id {
  type string {
    pattern
      '[0-9A-Fa-f]{4}\.[0-9A-Fa-f]{4}\.[0-9A-Fa-f]{4}\.[0-9A-Fa-f]{4}';
  }
  description
    "This type defines RIFT system id using pattern,
    the system id looks like: 0143.0438.0100.AeF0";
}

typedef level {
  type uint8 {
    range "0 .. 24";
  }
  default "0";
  description "The value of node level.";
}

```

```

}

typedef linkid-type {
    type uint32;
    description "This type defines the link id of an interface.";
}

typedef ieee802-1as-timestamp-type {
    type uint64;
    description
        "Timestamp per IEEE802.1AS. It is advertised with prefix to
        achieve mobility as described in section 4.3.3.";
    reference
        "I-D.ietf-rift-rift: RIFT: Routing in Fat Trees.
        IEEE8021AS: Timing and Synchronization for Time-Sensitive
        Applications in Bridged Local Area Networks";
}

/*
 * Identity
 */
identity rift {
    base rt:routing-protocol;
    description "Identity for the RIFT routing protocol.";
    reference
        "I-D.ietf-rift-rift: RIFT: Routing in Fat Trees";
}

/*
 * Groupings
 */

grouping address-families {
    leaf-list address-families {
        type iana-rt-types:address-family;
        description
            "Indication which address families are up on the
            interface.";
    }
    description
        "Containing address families on the interface.";
}

grouping hierarchy-indications {
    leaf hierarchy-indications {
        type enumeration {
            enum "leaf-only" {
                description
                    "The node will never leave the

```

```

        'bottom of the hierarchy'.";
    }
    enum "leaf-only-and-leaf-2-leaf-procedures" {
        description "This means leaf to leaf.";
    }
    enum "top-of-fabric" {
        description "The node is 'top of fabric'.";
    }
}
description "The hierarchy indications of this node.";
}
description "Flags indicating node configuration in case of ZTP";
}

```

```

grouping node-capability {
    leaf proto-minor-ver {
        type uint16;
        description
            "Represents the minor protocol encoding schema
            version of this node.";
    }
    leaf flood-reduction {
        type boolean;
        description
            "If this node enables the flood reduction function.";
    }
    container hierarchy-indications {
        config false;
        description "The hierarchy-indications of the node.";
        uses hierarchy-indications;
    }
    description
        "The supported capabilities of this node.";
}

```

```

grouping prefix-attribute {
    leaf metric {
        type uint32;
        description "The metric of this prefix.";
    }
    leaf-list tags {
        type uint64;
        description "The tags of this prefix.";
    }
    container monotonic-clock {
        container prefix-sequence-type {
            leaf timestamp {
                type ieee802-1as-timestamp-type;
                mandatory true;
            }
        }
    }
}

```



```

        description
            "The timestamp per 802.1AS can be advertised
            with the desired prefix North TIEs.";
    }
    leaf transaction-id {
        type uint8;
        description
            "As per RFC 8505, a sequence number called a
            Transaction ID (TID) with a prefix can be
            advertised.";
        reference
            "RFC 8505: Registration Extensions for IPv6 over
            Low-Power Wireless Personal Area Network (6LoWPAN)
            Neighbor Discovery";
    }
    description
        "As described in section 4.3.3, the prefix
        sequence attribute which can be advertised
        for mobility.";
    reference
        "I-D.ietf-rift-rift: RIFT: Routing in Fat Trees";
}
description
    "The monotonic clock for mobile addresses.";
}
leaf loopback {
    type boolean;
    description
        "Indicates if the interface is a node loopback.
        According to section 4.3.10, the node's loopback
        address can be injected into North and South
        Prefix TIEs for node reachability.";
    reference
        "I-D.ietf-rift-rift: RIFT: Routing in Fat Trees";
}
leaf directly-attached {
    type boolean;
    description
        "Indicates that the prefix is directly attached,
        i.e. should be routed to even if the node is
        in overload.";
}
leaf from-link {
    type linkid-type;
    description
        "In case of locally originated prefixes,
        i.e. interface addresses this can describe which
        link the address belongs to.";
}
}

```

```

description
  "The attributes of the prefix.";
}

grouping security {
  choice auth-key-chain {
    description
      "Key chain or explicit key parameter specification";
    case auth-key-chain {
      leaf key-chain {
        type key-chain:key-chain-ref;
        description
          "key-chain name.";
      }
    }
    case auth-key-explicit {
      leaf key-id {
        type uint32;
        description "Key Identifier";
      }
      leaf key {
        type string;
        description
          "Authentication key. The length of the key may be
          dependent on the cryptographic algorithm.";
      }
      leaf crypto-algorithm {
        type identityref {
          base key-chain:crypto-algorithm;
        }
        description
          "Cryptographic algorithm associated with key.";
      }
    }
  }
  description "The security parameters.";
}

grouping base-node-info {
  leaf name {
    type string;
    description
      "The name of this node. It won't be used as the key of node,
      just used for description.";
  }
  leaf level {
    type level;
    config false;
    description "The level of this node.";
  }
}

```

```

}
leaf system-id {
    type system-id;
    mandatory true;
    description
        "Each node is identified via a system-id which is 64 bits
        wide.";
}
leaf pod {
    type uint32 {
        range "1..max";
    }
    description
        "The identifier of the Point of Delivery (PoD).
        A PoD is the self-contained vertical slice of a
        Clos or Fat Tree network containing normally only level 0
        and level 1 nodes. It communicates with nodes in other PoDs
        via the spine. Making this leaf unspecified indicates that
        the PoD is 'undefined'.";
}
description "The base information of a node.";
} // base-node-info

grouping link-capabilities {
    leaf bfd {
        type boolean;
        default "true";
        description
            "If this value is set to true, it means that
            BFD function is enabled on the neighbor.";
        reference
            "RFC 5881: Bidirectional Forwarding Detection (BFD)
            for IPv4 and IPv6 (Single Hop)";
    }
    leaf v4-forwarding-capable {
        type boolean;
        default "true";
        description
            "If this value is set to true, it means that
            the neighbor supports v4 forwarding.";
    }
    leaf mtu-size {
        type uint32;
        default "1400";
        description
            "MTU of the link.";
    }
}
description "The features of neighbor.";
} // link-capabilities

```

```

grouping addresses {
  leaf ipv4 {
    type inet:ipv4-address;
    description "IPv4 address to be used.";
  }
  leaf ipv6 {
    type inet:ipv6-address;
    description "IPv6 address to be used.";
  }
  description "IPv4 and/or IPv6 address to be used.";
}

grouping lie-elements {
  leaf you-are-flood-repeater {
    type boolean;
    description
      "If the neighbor on this link is flooding repeater
      described in section 4.2.3.9. When this value is set
      to true, the value can be carried in exchanged
      packet.";
    reference
      "I-D.ietf-rift-rift: RIFT: Routing in Fat Trees";
  }
  leaf not-a-ztp-offer {
    type boolean;
    description
      "As described in section 4.2.7. When this value is
      set to true, the flag can be carried in the LIE
      packet. When the value received in the LIE from
      neighbor, it indicates the level on the LIE MUST
      NOT be used to derive a ZTP level by the receiving
      node.";
    reference
      "I-D.ietf-rift-rift: RIFT: Routing in Fat Trees";
  }
  leaf you-are-sending-too-quickly {
    type boolean;
    description
      "Can be optionally set to indicate to neighbor that
      packet losses are seen on reception based on packet
      numbers or the rate is too high. The receiver SHOULD
      temporarily slow down flooding rates. When this value
      is set to true, the flag can be carried in packet.";
  }
  description "The elements set in the LIEs.";
} // lie-elements

grouping link-id-pair {

```

```

leaf local-id {
    type uint32;
    description "The local-id of link connect to this neighbor.";
}
leaf remote-id {
    type uint32;
    description "The remote-id to reach this neighbor.";
}
leaf if-index {
    type uint32;
    description "The local index of this interface.";
}
leaf if-name {
    type if:interface-ref;
    description "The name of this interface.";
}
uses address-families;
description
    "A pair of local and remote link IDs to identify a link between
    two nodes.";
} // link-id-pair

grouping neighbor-node {
    list link-id-pair {
        key "remote-id";
        uses link-id-pair;
        description
            "The Multiple parallel links to this neighbor.";
    }
    leaf cost {
        type uint32;
        description "The cost value advertised by the neighbor.";
    }
    leaf bandwidth {
        type uint32;
        description
            "Total bits bandwith to neighbor, this will be
            normally sum of the bandwidths of all the
            parallel links.";
    }
    container received-link-capabilities {
        uses link-capabilities;
        description
            "The link capabilities advertised by the neighbor.";
    }
    description "The neighbor information indicated in node TIE.";
} // neighbor-node

grouping neighbor {

```

```

leaf protocol-version {
  type uint16;
  description
    "Represents the protocol encoding schema version of
    this neighbor.";
}
container sent-offer {
  leaf level {
    type level;
    description "The level value.";
  }
  leaf not-a-ztp-offer {
    type boolean;
    description "If the neighbor needs to be offer a level.";
  }
  description
    "The level sent to the neighbor in case the neighbor
    needs to be offered.";
}
container received-offer {
  leaf level {
    type level;
    description "The level value.";
  }
  leaf not-a-ztp-offer {
    type boolean;
    description
      "If this interface needs to be offered a level.";
  }
  leaf best {
    type boolean;
    description
      "If level is the best level received from all
      the neighbors.";
  }
  leaf removed-from-consideration {
    type boolean;
    description
      "If the level value is considered to be used.
      If the value is not considered to be used,
      this value is set to 'TRUE'.";
  }
  leaf removal-reason {
    type string;
    description
      "The reason why this value is not considered to
      be used.";
  }
  description

```

```

        "The level offered to the interface from the neighbor.
        And if the level value is considered to be used.";
    }
    container received-source-addr {
        uses addresses;
        description
            "The source address of LIE and TIE packets from
            the neighbor.";
    } // received-offer
    uses neighbor-node;
    container received-in-lies {
        uses lie-elements;
        description "The attributes received from this neighbor.";
    }
    leaf tx-flood-port {
        type inet:port-number;
        default "915";
        description
            "The UDP port which is used by the neighbor to flood TIEs.";
    }
    leaf bfd-up {
        type boolean;
        description
            "Indication whether the link is protected by established
            BFD session.";
    }
    leaf outer-security-key-id {
        type uint8;
        description
            "As described in section 4.4.3, the received security
            key id from the neighbor.";
        reference
            "I-D.ietf-rift-rift: RIFT: Routing in Fat Trees";
    }
    description "The neighbor information.";
} // neighbor

grouping direction-type {
    leaf direction-type {
        type enumeration {
            enum illegal {
                description "Illegal direction.";
            }
            enum south {
                description "A link to a node one level down.";
            }
            enum north {
                description "A link to a node one level up.";
            }
        }
    }
}

```

```

    enum east-west {
        description "A link to a node in the same level.";
    }
    enum max {
        description "The max value of direction.";
    }
}
config false;
description "The type of a link.";
}
description "The type of a link.";
} // direction-type

grouping tie-header {
    uses direction-type;
    leaf originator {
        type system-id;
        description "The originator's system-id of this TIE.";
    }
}

leaf tie-type {
    type enumeration {
        enum "node" {
            description "The node TIE.";
        }
        enum "prefix" {
            description "The prefix TIE.";
        }
        enum "positive-disaggregation-prefix" {
            description "The positive disaggregation prefix TIE.";
        }
        enum "negative-disaggregation-prefix" {
            description "The negative disaggregation prefix TIE.";
        }
        enum "pgp-prefix" {
            description "The policy guide prefix TIE.";
        }
        enum "key-value" {
            description "The key value TIE.";
        }
        enum "external-prefix" {
            description "The external prefix TIE.";
        }
        enum "positive-external-disaggregation-prefix" {
            description
                "The positive external disaggregation prefix TIE.";
        }
    }
}
description "The types of TIE.";

```



```

}

leaf tie-number {
  type uint32;
  description "The number of this TIE";
}

leaf seq {
  type uint64;
  description
    "As described in section 4.2.3.1, the sequence number
    of a TIE.";
  reference
    "I-D.ietf-rift-rift: RIFT: Routing in Fat Trees";
}

leaf origination-time {
  type uint32;
  description
    "Absolute timestamp when the TIE was generated. This can
    be used on fabrics with synchronized clock to prevent
    lifetime modification attacks.";
}

leaf origination-lifetime {
  type uint32;
  description
    "Original lifetime when the TIE was generated.
    This can be used on fabrics with synchronized clock to
    prevent lifetime modification attacks.";
}

description
  "TIE is the acronym for 'Topology Information Element'.
  TIEs are exchanged between RIFT nodes to describe parts
  of a network such as links and address prefixes.
  This is the TIE header information.";
} // tie-header

/*
 * Data nodes
 */
augment "/rt:routing/rt:control-plane-protocols"
  + "/rt:control-plane-protocol" {
  when "derived-from-or-self(rt:type, 'rift:rift')" {
  description
    "This augment is only valid when routing protocol
    instance type is 'RIFT'.";
  }
  description "RIFT ( Routing in Fat Trees ) YANG model.";
}

```

```

container rift {
  description "RIFT configuration and state data.";

  uses base-node-info;
  leaf configured-level {
    type level;
    description
      "The configured level value of this node.
      If the 'hierarchy-indications' is set to 'leaf-only'
      or 'leaf-only-and-leaf-2-leaf-procedures', this value
      means the leaf level.
      And the combination of this value and
      'hierarchy-indications' can also be used to indicate
      the maximum level value of 'top-of-fabric-level'.";
  }
}

container overload {
  description
    "If the overload in TIEs can be set
    and the timeout value with according type.";
  leaf overload {
    type boolean;
    description "If the overload bit in TIEs can be set.";
  }
  choice timeout-type {
    description
      "The value of timeout timer for overloading.
      This makes sense when overload is set to 'TRUE'.";
    case on-startup {
      leaf on-startup-timeout {
        type rt-types:timer-value-seconds16;
        description
          "Node goes into overload until this timer expires
          when starting up.";
      }
    }
    case immediate {
      leaf immediate-timeout {
        type rt-types:timer-value-seconds16;
        description
          "Set overload and remove after the timeout expired.";
      }
    }
  }
}

leaf proto-major-ver {
  type uint8;
  config false;
  mandatory true;
}

```

```

    description
      "Represents protocol encoding schema major version.";
  }
  leaf proto-minor-ver {
    type uint16;
    config false;
    mandatory true;
    description
      "Represents protocol encoding schema minor version.";
  }
  uses hierarchy-indications;
  leaf flood-reduction {
    type boolean;
    description
      "If the node supports flood reduction function defined in
      section 4.2.3.8. If this value is set to 'FALSE', it
      means that the flood reduction function is disabled.";
    reference
      "I-D.ietf-rift-rift: RIFT: Routing in Fat Trees";
  }
  leaf nonce-increasing-interval {
    type uint16;
    units seconds;
    description
      "The configurable nonce increasing interval.";
  }
  leaf maximum-nonce-delta {
    if-feature nonce-delta-adjust;
    type uint8 {
      range "1..5";
    }
    description
      "The configurable valid nonce delta value used for
      security. It is used as vulnerability window defined
      in section 4.4.7.
      If the nonces in received packet exceeds the range
      indicated by this value, the packet MUST be discarded.";
    reference
      "I-D.ietf-rift-rift: RIFT: Routing in Fat Trees";
  }
  leaf adjusted-lifetime {
    type rt-types:timer-value-seconds16;
    units seconds;
    description
      "The adjusted lifetime may affect the TIE stability.
      Be careful to change this parameter.";
  }
  container rx-lie-multicast-addr {
    leaf ipv4 {

```

```

    type inet:ipv4-address;
    default "224.0.0.121";
    description
        "The configurable LIE receiving IPv4 multicast
        address.
        Different multicast addresses can be used for receiving
        and sending.";
}
leaf ipv6 {
    type inet:ipv6-address;
    description
        "The configurable LIE receiving IPv6 multicast
        address.
        Different multicast addresses can be used for receiving
        and sending.";
}
description
    "The configurable LIE receiving IPv4/IPv6 multicast
    address.
    Different multicast addresses can be used for receiving
    and sending.";
}
container tx-lie-multicast-addr {
    leaf ipv4 {
        type inet:ipv4-address;
        description
            "The configurable LIE sending IPv4 multicast address.
            Different multicast addresses can be used for receiving
            and sending.";
    }
    leaf ipv6 {
        type inet:ipv6-address;
        default "FF02::A1F7";
        description
            "The configurable LIE sending IPv6 multicast address.
            Different multicast addresses can be used for receiving
            and sending.";
    }
    description
        "The configurable LIE sending IPv4/IPv6 multicast address.
        Different multicast addresses can be used for receiving
        and sending.";
}
leaf lie-tx-port {
    type inet:port-number;
    default "914";
    description
        "The UDP port of LIE packet sending. The default port
        number is 914. The value can be set to other value

```

```

        associated with different RIFT instance.";
    }

container global-link-capabilities {
    uses link-capabilities;
    description
        "The node default link capabilities. It can be overwrite
        by the configuration underneath interface and neighbor.";
}

leaf rx-flood-port {
    type inet:port-number;
    default "915";
    description
        "The UDP port which can be used to receive flooded
        TIEs. The default port number is 915. The value can
        be set to other value associated with different
        RIFT instance.";
}

leaf global-holdtime {
    type rt-types:timer-value-seconds16;
    units seconds;
    default "3";
    description "The holding time of LIE.";
}

leaf tide-generation-interval {
    type rt-types:timer-value-seconds16;
    units seconds;
    default "5";
    description "The TIDE generation interval.";
}

container tie-security {
    if-feature tie-security;
    uses security;
    description
        "As described in section 4.4.3, the security function
        used for the TIE exchange.";
    reference
        "I-D.ietf-rift-rift: RIFT: Routing in Fat Trees";
}

leaf algorithm-type {
    type enumeration {
        enum spf {
            description "The algorithm is SPF.";
        }
        enum all-path {
            description "The algorithm is all-path.";
        }
    }
}

```

```

    }
    description "The possible algorithm types.";
}
leaf instance-label {
    if-feature label-switching;
    type uint32;
    description
        "As per section 4.3.7, a locally significant, downstream
        assigned, interface specific label may be advertised in
        its LIEs. This value can be used to distinguish among
        multiple RIFT instances.";
    reference
        "I-D.ietf-rift-rift: RIFT: Routing in Fat Trees";
}

container hal {
    config false;
    leaf hal-value {
        type level;
        description
            "The highest defined level value seen from all valid
            level offers received.";
    }
    leaf-list system-id{
        type system-id;
        description
            "The node's system-id of the offered level comes from.";
    }
    description
        "The highest defined level and the offered nodes set.";
}

leaf-list miscabled-links {
    type linkid-type;
    config false;
    description "List of miscabled links.";
}

list interface {
    key "name";
    leaf link-id {
        type linkid-type;
        config false;
        description "The local id of this interface.";
    }
    leaf name {
        type if:interface-ref;
        description "The interface's name.";
    }
}

```

```

leaf cost {
    type uint32;
    description
        "The cost from this interface to the neighbor.";
}
uses address-families;
container advertised-source-addr {
    uses addresses;
    description
        "The address used in the advertised LIE and TIE
        packets.";
}
uses direction-type;

container security {
    if-feature tie-security;
    uses security;
    description
        "As described in section 4.4.3, the security function
        used for this interface.";
    reference
        "I-D.ietf-rift-rift: RIFT: Routing in Fat Trees";
}

leaf security-checking {
    type enumeration {
        enum "no-checking" {
            description
                "The security envelop does not be checked.";
        }
        enum "permissive" {
            description
                "The security envelop checking is permissive.";
        }
        enum "loose" {
            description
                "The security envelop checking is loose.";
        }
        enum "strict" {
            description
                "The security envelop checking is strict.";
        }
    }
    description
        "The possible security checking types.
        Only one type can be set at the same time.";
}

leaf was-the-last-lie-accepted {

```

```

type boolean;
config false;
description
    "If the most recently received LIE was accepted or
    rejected. If the LIE was rejected, the neighbor error
    notifications should be used to find the reason.";
}
leaf last-lie-reject-reason {
    type string;
    config false;
    description
        "Description for the reject reason of the last LIE.";
}
container advertised-in-lies {
    config false;
    uses lie-elements;
    description
        "The attributes advertised in the LIEs from
        this interface.";
}
container link-capabilities {
    uses link-capabilities;
    description
        "The interface's link capabilities.";
}
leaf state {
    type enumeration {
        enum "OneWay" {
            description "The initial state of neighbor.";
        }
        enum "TwoWay" {
            description "This means leaf to leaf.";
        }
        enum "ThreeWay" {
            description "The node is 'top of fabric'.";
        }
        enum "Multiple-Neighbors-Wait" {
            description "The node is 'top of fabric'.";
        }
    }
    config false;
    mandatory true;
    description "The hierarchy indications of this node.";
}
leaf number-of-flaps {
    type uint32;
    config false;
    description
        "The number of interface state flaps.";
}

```



```

}
leaf last-state-change {
    type yang:date-and-time;
    config false;
    description "Time duration in the current state.";
}

description "The interface information on this node.";
} // list interface

list neighbor {
    key "system-id";
    config false;
    uses base-node-info;
    uses neighbor;
    description "The neighbor's information.";
}

container database {
    config false;
    list tie {
        key "direction-type originator tie-type tie-number";
        description
            "A list of TIEs (Topology Information Elements).";
        uses tie-header;

        container node {
            leaf level {
                type level;
                config false;
                description "The level of this node.";
            }
            list neighbor {
                key "system-id";
                uses base-node-info;
                uses neighbor-node;
                description "The node TIE information of a neighbor.";
            }
        }
        uses node-capability;
        leaf overload-flag {
            type boolean;
            description
                "If the overload bit in TIEs is set.";
        }
        leaf name {
            type string;
            description
                "The name of this node. It won't be used as the key
                of node, just used for description.";
        }
    }
}

```

```

}
leaf pod {
    type uint32;
    description
        "Point of Delivery. The self-contained vertical slice
        of a Clos or Fat Tree network containing normally
        only level 0 and level 1 nodes. It communicates with
        nodes in other PoDs via the spine. We number PoDs to
        distinguish them and use PoD #0 to denote
        'undefined' PoD.";
}
leaf startup-time {
    type yang:date-and-time;
    description "Startup time of the node.";
}
leaf-list miscabled-links {
    type linkid-type;
    config false;
    description "List of miscabled links.";
}
description "The node element information in this TIE.";
} // node

container prefixes {
    description
        "The prefix element information in this TIE.";
    list prefix {
        key "prefix";
        leaf prefix {
            type inet:ip-prefix;
            description "The prefix information.";
        }
        uses prefix-attribute;
        description "The prefix set information.";
    }
}

container positive-disagg-prefixes {
    list positive-disagg-prefix {
        key "positive-disagg-prefix";
        leaf positive-disagg-prefix {
            type inet:ip-prefix;
            description "The prefix information.";
        }
        uses prefix-attribute;
        description
            "The positive disaggregation prefix information.";
    }
    description "The positive disaggregation prefixes set.";
}
}

```

```
container negative-disagg-prefixes {
  list negative-disagg-prefix {
    key "negative-disagg-prefix";
    leaf negative-disagg-prefix {
      type inet:ip-prefix;
      description "The prefix information.";
    }
    uses prefix-attribute;
    description
      "The negative disaggregation prefix information.";
  }
  description "The negative disaggregation prefixes set.";
}
container external-prefixes {
  list external-prefix {
    key "external-prefix";
    leaf external-prefix {
      type inet:ip-prefix;
      description "The prefix information.";
    }
    uses prefix-attribute;
    description "The external prefix information.";
  }
  description "The external prefixes set.";
}
container positive-ext-disagg-prefixes {
  list positive-ext-disagg-prefix {
    key "positive-ext-disagg-prefix";
    leaf positive-ext-disagg-prefix {
      type inet:ip-prefix;
      description "The prefix information.";
    }
    uses prefix-attribute;
    description
      "The positive external disaggregation prefix
      information.";
  }
  description
    "The positive external disaggregation prefixes set.";
}
container key-value {
  leaf key {
    type binary;
    description "The type of key value combination.";
  }
  leaf value {
    type binary;
    description "The value of key value combination.";
  }
}
```

```

    }
    description
        "The information used to distinguish a Key/Value
        pair. When the type of kv is set to 'node',
        node-element is making sense. When the type of
        kv is set to other values except 'node',
        prefix-info is making sense.";
    } // kv-store
} // ties
description "The TIEs information in database.";
} // container database
} // rift
} // augment

/*
 * Notifications
 */
notification error-set {
    description "The errors notification of RIFT.";
    container tie-level-error {
        list tie {
            key "originator";
            uses tie-header;
            description "The level is undefined in the LIEs.";
        }
        description "The TIE errors set.";
    }
    container neighbor-error {
        list neighbor {
            key "system-id";
            uses base-node-info;
            uses neighbor;
            description "The information of a neighbor.";
        }
        description "The neighbor errors set.";
    }
}
}
}

<CODE ENDS>

```

#### 4. Security Considerations

The YANG module specified in this document defines a schema for data that is designed to be accessed via network management protocols such as NETCONF [[RFC6241](#)] or RESTCONF [[RFC8040](#)]. The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure transport is Secure Shell (SSH) [[RFC6242](#)]. The lowest RESTCONF layer

is HTTPS, and the mandatory-to-implement secure transport is TLS [[RFC8446](#)].

The NETCONF access control model [[RFC8341](#)] provides the means to restrict access for particular NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

There are a number of data nodes defined in this YANG module that are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations. Writable data nodes represent configuration of each instance, node, interface, etc. These correspond to the following schema node:

```
*/rift
```

Modifying the configuration may cause all the RIFT neighborship to be rebuilt. For example, the configuration changing of configured-level or system-id, will lead to all the neighbor connections of this node rebuilt. The incorrect modification of authentication, except for the neighbor connection broken, will lead to the permanent connection broken. The modification of interface, will lead to the neighbor state changing. In general, unauthorized modification of most RIFT configurations will pose their own set of security risks and the "Security Considerations" in the respective reference RFCs should be consulted.

Some of the readable data nodes in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes. These are the subtrees and data nodes and their sensitivity/vulnerability:

```
*/rift
```

```
*/rift/interface
```

```
*/rift/neighbor
```

```
*/rift/database
```

The exposure of the database will expose the detailed topology of the network. Network operators may consider their topologies to be sensitive confidential data.

For RIFT authentication, configuration is supported via the specification of key-chains [[RFC8177](#)] or the direct specification of

key and authentication algorithm. Hence, authentication configuration inherits the security considerations of [RFC8177]. This includes the considerations with respect to the local storage and handling of authentication keys.

## 5. IANA Considerations

RFC Ed.: Please replace all occurrences of 'XXXX' with the actual RFC number (and remove this note).

This document registers a URI in the IETF XML registry [RFC3688]. Following the format in [RFC3688], the following registration is requested to be made:

URI: urn:ietf:params:xml:ns:yang:ietf-rift

Registrant Contact: The IESG

XML: N/A, the requested URI is an XML namespace.

This document also requests one new YANG module name in the YANG Module Names registry [RFC6020] with the following suggestion:

name: ietf-rift

namespace: urn:ietf:params:xml:ns:yang:ietf-rift

prefix: rift

reference: RFC XXXX

## 6. Acknowledgement

The authors would like to thank Tony Przygienda, Benchong Xu (xu.benchong@zte.com.cn), for their review, valuable comments and suggestions.

## 7. References

### 7.1. Normative References

#### [I-D.ietf-rift-rift]

Przygienda, T., Sharma, A., Thubert, P., Rijsman, B., Afanasiev, D., and J. Head, "RIFT: Routing in Fat Trees", Work in Progress, Internet-Draft, draft-ietf-rift-rift-17, 13 March 2023, <<https://datatracker.ietf.org/doc/html/draft-ietf-rift-rift-17>>.

[IEEE8021AS] "IEEE Standard for Local and Metropolitan Area Networks - Timing and Synchronization for Time-Sensitive

Applications in Bridged Local Area Networks", <<https://ieeexplore.ieee.org/document/5741898/>>.

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC5881] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD) for IPv4 and IPv6 (Single Hop)", RFC 5881, DOI 10.17487/RFC5881, June 2010, <<https://www.rfc-editor.org/info/rfc5881>>.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", RFC 6020, DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", RFC 6241, DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", RFC 6242, DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC6991] Schoenwaelder, J., Ed., "Common YANG Data Types", RFC 6991, DOI 10.17487/RFC6991, July 2013, <<https://www.rfc-editor.org/info/rfc6991>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", RFC 7950, DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", RFC 8040, DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8177] Lindem, A., Ed., Qu, Y., Yeung, D., Chen, I., and J. Zhang, "YANG Data Model for Key Chains", RFC 8177, DOI 10.17487/RFC8177, June 2017, <<https://www.rfc-editor.org/info/rfc8177>>.
- [RFC8294] Liu, X., Qu, Y., Lindem, A., Hopps, C., and L. Berger, "Common YANG Data Types for the Routing Area", RFC 8294,

DOI 10.17487/RFC8294, December 2017, <<https://www.rfc-editor.org/info/rfc8294>>.

- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", BCP 215, RFC 8340, DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.
- [RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, RFC 8341, DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.
- [RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture (NMDA)", RFC 8342, DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.
- [RFC8343] Bjorklund, M., "A YANG Data Model for Interface Management", RFC 8343, DOI 10.17487/RFC8343, March 2018, <<https://www.rfc-editor.org/info/rfc8343>>.
- [RFC8349] Lhotka, L., Lindem, A., and Y. Qu, "A YANG Data Model for Routing Management (NMDA Version)", RFC 8349, DOI 10.17487/RFC8349, March 2018, <<https://www.rfc-editor.org/info/rfc8349>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", RFC 8446, DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.
- [RFC8505] Thubert, P., Ed., Nordmark, E., Chakrabarti, S., and C. Perkins, "Registration Extensions for IPv6 over Low-Power Wireless Personal Area Network (6LoWPAN) Neighbor Discovery", RFC 8505, DOI 10.17487/RFC8505, November 2018, <<https://www.rfc-editor.org/info/rfc8505>>.

## 7.2. Informative References

- [RFC3688] Mealling, M., "The IETF XML Registry", BCP 81, RFC 3688, DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.
- [RFC8407] Bierman, A., "Guidelines for Authors and Reviewers of Documents Containing YANG Data Models", BCP 216, RFC 8407, DOI 10.17487/RFC8407, October 2018, <<https://www.rfc-editor.org/info/rfc8407>>.
- [RFC8639] Voit, E., Clemm, A., Gonzalez Prieto, A., Nilsen-Nygaard, E., and A. Tripathy, "Subscription to YANG Notifications",



RFC 8639, DOI 10.17487/RFC8639, September 2019, <<https://www.rfc-editor.org/info/rfc8639>>.

[RFC8641] Clemm, A. and E. Voit, "Subscription to YANG Notifications for Datastore Updates", RFC 8641, DOI 10.17487/RFC8641, September 2019, <<https://www.rfc-editor.org/info/rfc8641>>.

#### Authors' Addresses

Zheng Zhang  
ZTE Corporation

Email: [zhang.zheng@zte.com.cn](mailto:zhang.zheng@zte.com.cn)

Yuehua Wei  
ZTE Corporation

Email: [wei.yuehua@zte.com.cn](mailto:wei.yuehua@zte.com.cn)

Shaowen Ma  
Google

Email: [mashaowen@gmail.com](mailto:mashaowen@gmail.com)

Xufeng Liu  
IBM Corporation

Email: [xufeng.liu.ietf@gmail.com](mailto:xufeng.liu.ietf@gmail.com)

Bruno Rijsman  
Individual

Email: [brunorijsman@gmail.com](mailto:brunorijsman@gmail.com)