

Token Ring Extensions to the Remote Network Monitoring MIB

Mon May 10 18:45:56 1993

Steven Waldbusser
Carnegie Mellon University
waldbusser@cmu.edu

1. Status of this Memo

This memo provides information for the Internet community. It does not specify any standard. Distribution of this memo is unlimited. Please send comments to the authors.

This document is an Internet Draft. Internet Drafts are working documents of the Internet Engineering Task Force (IETF), its Areas, and its Working Groups. Note that other groups may also distribute working documents as Internet Drafts.

Internet Drafts are draft documents valid for a maximum of six months. Internet Drafts may be updated, replaced, or obsoleted by other documents at any time. It is not appropriate to use Internet Drafts as reference material or to cite them other than as a "working draft" or "work in progress."

Please check the I-D abstract listing contained in each Internet Draft directory to learn the current status of this or any other Internet Draft.

2. Abstract

This memo defines extensions to the Remote Network Monitoring MIB for managing 802.5 Token Ring networks.

The Remote Network Monitoring MIB, [RFC1271](#), defines a framework for remote monitoring functions implemented on a network probe. That MIB defines objects broken down into nine functional groups. Some of those functional groups, the statistics and the history groups, have a view of the data-link layer that is specific to the media type and require specific objects to be defined for each media type. [RFC1271](#) defined those specific objects necessary for Ethernet. This

companion memo defines those specific objects necessary for Token Ring LANs.

In addition, this memo defines some additional monitoring functions specifically for Token Ring. These are defined in the Ring Station Group, the Ring Station Order Group, the Ring Station Configuration Group, and the Source Routing Statistics Group.

3. The Network Management Framework

The Internet-standard Network Management Framework consists of three components. They are:

[RFC 1155](#)[1] which defines the SMI, the mechanisms used for describing and naming objects for the purpose of management. [RFC 1212](#)[2] defines a more concise description mechanism, which is wholly consistent with the SMI.

[RFC 1213](#)[3] which defines MIB-II, the core set of managed objects for the Internet suite of protocols.

[RFC 1157](#)[4] which defines the SNMP, the protocol used for network access to managed objects.

The Framework permits new objects to be defined for the purpose of experimentation and evaluation.

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. Within a given MIB module, objects are defined using [RFC 1212](#)'s OBJECT-TYPE macro. At a minimum, each object has a name, a syntax, an access-level, and an implementation-status.

The name is an object identifier, an administratively assigned name, which specifies an object type. The object type together with an object instance serves to uniquely identify a specific instantiation of the object. For human convenience, we often use a textual string, termed the object descriptor, to also refer to the object type.

The syntax of an object type defines the abstract data structure corresponding to that object type. The ASN.1[5] language is used for this purpose. However, [RFC 1155](#) purposely restricts the ASN.1 constructs which may be used. These restrictions are explicitly made for simplicity.

The access-level of an object type defines whether it makes "protocol sense" to read and/or write the value of an instance of the object type. (This access-level is independent of any administrative authorization policy.)

The implementation-status of an object type indicates whether the object is mandatory, optional, obsolete, or deprecated.

4. Guidelines for implementing [RFC1271](#) objects on a Token Ring network

Wherever a MacAddress is to be used in this MIB the source routing bit is stripped off. The resulting address will be consistently valid for all packets sent by a particular node.

4.1. Host Group

Only Token Ring isolating errors will increment the error counter for a particular hostEntry. The isolating errors are: lineErrors, burstErrors, ACErrors, InternalErrors, and AbortErrors. In addition, congestionErrors will also be counted for each hostEntry. These errors will be incremented in the host entry of the station that reports the errors in an error report frame.

The hostOutPkts and hostOutOctets counters shall not be incremented for packets with errors.

4.2. Matrix Group

Error counters are never incremented.

4.3. Filter Group

The following conditions make up the status bitmask for token ring networks:

bit #	Error
3	First packet after some packets were dropped
4	Packet with the Frame Copied Bit set
5	Packet with the Address Recognized Bit set

For the purpose of the packet match algorithm, the filters assume a 32 byte RIF field. Thus, when matching, the filter is compared to the packet starting at the AC byte of the packet, until the end of the RIF field; then the unused RIF bytes in the filter are skipped and matching proceeds from that point. Any filter "care" bits in the RIF that don't correspond to bytes in the input packet will cause the filter to fail.

4.4. Other comments

Because soft error report packets may be sent with assured delivery, some errors may be accidentally reported twice on devices that perform the RMON function promiscuously.

5. Overview of the RMON Token Ring Extensions MIB

The Remote Network Monitoring MIB, [RFC1271](#), defines a framework for remote monitoring functions implemented on a network probe. That MIB defines objects broken down into nine functional groups. Some of those functional groups, the statistics and the history groups, have a view of the data-link layer that is specific to the media type and require specific objects to be defined for each media type. [RFC1271](#) defined those specific objects necessary for Ethernet. This MIB defines contains four groups that define those specific objects necessary for Token Ring LANs.

In addition, this memo defines some additional monitoring functions specifically for Token Ring. These are defined in the Ring Station Group, the Ring Station Order Group, the Ring Station Configuration Group, and the Source Routing Statistics Group.

5.1. The Token Ring Statistics Groups

The Token Ring statistics groups contain current utilization and error statistics. The statistics are broken down into two groups, the Token Ring Mac-Layer Statistics Group and the Token Ring Promiscuous Statistics Group. The Token Ring Mac-Layer Statistics Group collects information from Mac Layer, including error reports for the ring and ring utilization of the Mac Layer. The Token Ring Promiscuous Statistics Group collects utilization statistics from data packets collected promiscuously.

5.2. The Token Ring History Groups

The Token Ring History Groups contain historical utilization and error statistics. The statistics are broken down into two groups, the Token Ring Mac-Layer History Group and the Token Ring Promiscuous History Group. The Token Ring Mac-Layer History Group collects information from Mac Layer, including error reports for the ring and ring utilization of the Mac Layer. The Token Ring Promiscuous History Group collects utilization statistics from data packets collected promiscuously.

5.3. The Token Ring Ring Station Group

The Token Ring Ring Station Group contains statistics and status information associated with each Token Ring station on the local ring. In addition, this group provides status information for each ring being monitored.

5.4. The Token Ring Ring Station Order Group

The Token Ring Ring Station Order Group provides the order of the stations on monitored rings.

5.5. The Token Ring Ring Station Config Group

The Token Ring Ring Station Config Group manages token ring stations through active means. Any station on a monitored ring may be removed or have configuration information downloaded from it.

5.6. The Source Routing Group

The Source Routing Group contains utilization statistics derived from source routing information optionally present in token ring packets.

6. Definitions

RFCXXX-MIB DEFINITIONS ::= BEGIN

IMPORTS

Counter, TimeTicks FROM [RFC1155](#)-SMI

OBJECT-TYPE FROM [RFC-1212](#)

-- For Internet Draft only:

OwnerString, EntryStatus -- Textual Conventions

FROM [RFC1271](#)-MIB

experimental FROM [RFC1155](#)-SMI;

rmon OBJECT IDENTIFIER ::= { experimental 27 }

statistics OBJECT IDENTIFIER ::= { rmon 1 }

history OBJECT IDENTIFIER ::= { rmon 2 }

-- For RFC only:

-- OwnerString, EntryStatus, -- Textual Conventions

-- rmon, statistics, history

-- FROM [RFC1271](#)-MIB;

-- All representations of MAC addresses in this MIB Module use,
-- as a textual convention (i.e. this convention does not affect
-- their encoding), the data type:

MacAddress ::= OCTET STRING (SIZE (6)) -- a 6 octet address in
-- the "canonical" order

-- defined by IEEE 802.1a, i.e., as if it were transmitted least
-- significant bit first, even though 802.5 (in contrast to other
-- 802.x protocols) requires MAC addresses to be transmitted most
-- significant bit first.

TimeInterval ::= INTEGER

-- A period of time, measured in units of 0.01 seconds.

-- This MIB module uses the extended OBJECT-TYPE macro as

-- defined in [\[2\]](#).

-- Token Ring Remote Network Monitoring MIB

tokenRing OBJECT IDENTIFIER ::= { rmon 10 }


```
-- The Token Ring Mac-Layer Statistics Group
--
-- Implementation of this group is optional

tokenRingMLStatsTable OBJECT-TYPE
    SYNTAX SEQUENCE OF TokenRingMLStatsEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "A list of Mac-Layer Token Ring statistics
        entries."
    ::= { statistics 2 }

tokenRingMLStatsEntry OBJECT-TYPE
    SYNTAX TokenRingMLStatsEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "A collection of Mac-Layer statistics kept for a
        particular Token Ring interface."
    INDEX { tokenRingMLStatsIndex }
    ::= { tokenRingMLStatsTable 1 }

-- As an example, an instance of the tokenRingMLStatsMacOctets object
-- might be named tokenRingMLStatsMacOctets.1

TokenRingMLStatsEntry ::= SEQUENCE {
    tokenRingMLStatsIndex                INTEGER,
    tokenRingMLStatsDataSource            OBJECT IDENTIFIER,
    tokenRingMLStatsDropEvents            Counter,
    tokenRingMLStatsMacOctets             Counter,
    tokenRingMLStatsMacPkts               Counter,
    tokenRingMLStatsRingPurgeEvents       Counter,
    tokenRingMLStatsRingPurgePkts         Counter,
    tokenRingMLStatsBeaconEvents          Counter,
    tokenRingMLStatsBeaconTime            TimeInterval,
    tokenRingMLStatsBeaconPkts            Counter,
    tokenRingMLStatsClaimTokenEvents      Counter,
    tokenRingMLStatsClaimTokenPkts        Counter,
    tokenRingMLStatsNAUNChanges           Counter,
    tokenRingMLStatsLineErrors            Counter,
    tokenRingMLStatsInternalErrors        Counter,
    tokenRingMLStatsBurstErrors           Counter,
    tokenRingMLStatsACErrors              Counter,
    tokenRingMLStatsAbortErrors           Counter,
```



```
tokenRingMLStatsLostFrameErrors      Counter,
tokenRingMLStatsCongestionErrors      Counter,
tokenRingMLStatsFrameCopiedErrors      Counter,
tokenRingMLStatsFrequencyErrors        Counter,
tokenRingMLStatsTokenErrors            Counter,
tokenRingMLStatsSoftErrorReports        Counter,
tokenRingMLStatsRingPollEvents          Counter,
tokenRingMLStatsOwner                  OwnerString,
tokenRingMLStatsStatus                  EntryStatus
}
```

tokenRingMLStatsIndex OBJECT-TYPE
SYNTAX INTEGER (1..65535)
ACCESS read-only
STATUS mandatory
DESCRIPTION
 "The value of this object uniquely identifies this
 tokenRingMLStats entry."
 ::= { tokenRingMLStatsEntry 1 }

tokenRingMLStatsDataSource OBJECT-TYPE
SYNTAX OBJECT IDENTIFIER
ACCESS read-write
STATUS mandatory
DESCRIPTION
 "This object identifies the source of the data
 that this tokenRingMLStats entry is configured to
 analyze. This source can be any tokenRing
 interface on this device. In order to identify a
 particular interface, this object shall identify
 the instance of the ifIndex object, defined in
 MIB-II [3], for the desired interface. For
 example, if an entry were to receive data from
 interface #1, this object would be set to
 ifIndex.1.

 The statistics in this group reflect all error
 reports on the local network segment attached to
 the identified interface.

 This object may not be modified if the associated
 tokenRingMLStatsStatus object is equal to
 valid(1)."
 ::= { tokenRingMLStatsEntry 2 }

tokenRingMLStatsDropEvents OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of events in which packets were dropped by the probe due to lack of resources.

Note that this number is not necessarily the number of packets dropped; it is just the number of times this condition has been detected. This value is the same as the corresponding tokenRingPStatsDropEvents."

::= { tokenRingMLStatsEntry 3 }

tokenRingMLStatsMacOctets OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of octets of data in MAC packets (excluding those in packets with FCS errors) received on the network (excluding framing bits but including FCS octets)."

::= { tokenRingMLStatsEntry 4 }

tokenRingMLStatsMacPkts OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of MAC packets (excluding packets with errors) received."

::= { tokenRingMLStatsEntry 5 }

tokenRingMLStatsRingPurgeEvents OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of times that the ring enters the ring purge state from normal ring state. The ring purge state that comes in response to the claim token or beacon state is not counted."

::= { tokenRingMLStatsEntry 6 }

tokenRingMLStatsRingPurgePkts OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of ring purge MAC packets detected by probe."

::= { tokenRingMLStatsEntry 7 }

tokenRingMLStatsBeaconEvents OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of times that the ring enters a beaconing state (beaconFrameStreamingState, beaconBitStreamingState, beaconSetRecoveryModeState, or beaconRingSignalLossState) from a non-beaconing state. Note that a change of the source address of the beacon packet does not constitute a new beacon event."

::= { tokenRingMLStatsEntry 8 }

tokenRingMLStatsBeaconTime OBJECT-TYPE

SYNTAX TimeInterval

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total amount of time that the ring has been in the beaconing state."

::= { tokenRingMLStatsEntry 9 }

tokenRingMLStatsBeaconPkts OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of beacon MAC packets detected by the probe."

::= { tokenRingMLStatsEntry 10 }

tokenRingMLStatsClaimTokenEvents OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of times that the ring enters the claim token state from normal ring state or ring purge state. The claim token state that comes in response to a beacon state is not counted."

::= { tokenRingMLStatsEntry 11 }

tokenRingMLStatsClaimTokenPkts OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of claim token MAC packets detected by the probe."

::= { tokenRingMLStatsEntry 12 }

tokenRingMLStatsNAUNChanges OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of NAUN changes detected by the probe."

::= { tokenRingMLStatsEntry 13 }

tokenRingMLStatsLineErrors OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of line errors reported in error reporting packets detected by the probe."

::= { tokenRingMLStatsEntry 14 }

tokenRingMLStatsInternalErrors OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of adapter internal errors reported in error reporting packets detected by the probe."

::= { tokenRingMLStatsEntry 15 }

tokenRingMLStatsBurstErrors OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of burst errors reported in
error reporting packets detected by the probe."

::= { tokenRingMLStatsEntry 16 }

tokenRingMLStatsACErrors OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of AC (Address Copied) errors
reported in error reporting packets detected by
the probe."

::= { tokenRingMLStatsEntry 17 }

tokenRingMLStatsAbortErrors OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of abort delimiters reported in
error reporting packets detected by the probe."

::= { tokenRingMLStatsEntry 18 }

tokenRingMLStatsLostFrameErrors OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of lost frame errors reported in
error reporting packets detected by the probe."

::= { tokenRingMLStatsEntry 19 }

tokenRingMLStatsCongestionErrors OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of receive congestion errors
reported in error reporting packets detected by
the probe."


```
::= { tokenRingMLStatsEntry 20 }
```

tokenRingMLStatsFrameCopiedErrors OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of frame copied errors reported
in error reporting packets detected by the probe."

```
::= { tokenRingMLStatsEntry 21 }
```

tokenRingMLStatsFrequencyErrors OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of frequency errors reported in
error reporting packets detected by the probe."

```
::= { tokenRingMLStatsEntry 22 }
```

tokenRingMLStatsTokenErrors OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of token errors reported in
error reporting packets detected by the probe."

```
::= { tokenRingMLStatsEntry 23 }
```

tokenRingMLStatsSoftErrorReports OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of soft error report frames
detected by the probe."

```
::= { tokenRingMLStatsEntry 24 }
```

tokenRingMLStatsRingPollEvents OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of ring poll events detected by
the probe (i.e. the number of ring polls initiated


```
        by the active monitor that were detected)."
 ::= { tokenRingMLStatsEntry 25 }
```

```
tokenRingMLStatsOwner OBJECT-TYPE
```

```
    SYNTAX OwnerString
```

```
    ACCESS read-write
```

```
    STATUS mandatory
```

```
    DESCRIPTION
```

```
        "The entity that configured this entry and is
         therefore using the resources assigned to it."
```

```
 ::= { tokenRingMLStatsEntry 26 }
```

```
tokenRingMLStatsStatus OBJECT-TYPE
```

```
    SYNTAX EntryStatus
```

```
    ACCESS read-write
```

```
    STATUS mandatory
```

```
    DESCRIPTION
```

```
        "The status of this tokenRingMLStats entry."
```

```
 ::= { tokenRingMLStatsEntry 27 }
```

```
-- The Token Ring Promiscuous Statistics Group
--
-- Implementation of this group is optional
```

```
tokenRingPStatsTable OBJECT-TYPE
    SYNTAX SEQUENCE OF TokenRingPStatsEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "A list of promiscuous Token Ring statistics
        entries."
    ::= { statistics 3 }
```

```
tokenRingPStatsEntry OBJECT-TYPE
    SYNTAX TokenRingPStatsEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "A collection of promiscuous statistics kept for
        non-MAC packets on a particular Token Ring
        interface."
    INDEX { tokenRingPStatsIndex }
    ::= { tokenRingPStatsTable 1 }
```

```
-- As an example, an instance of the tokenRingPStatsDataOctets object
-- might be named tokenRingPStatsDataOctets.1
```

```
TokenRingPStatsEntry ::= SEQUENCE {
    tokenRingPStatsIndex                INTEGER,
    tokenRingPStatsDataSource            OBJECT IDENTIFIER,
    tokenRingPStatsDropEvents            Counter,
    tokenRingPStatsDataOctets            Counter,
    tokenRingPStatsDataPkts              Counter,
    tokenRingPStatsDataBroadcastPkts     Counter,
    tokenRingPStatsDataMulticastPkts     Counter,
    tokenRingPStatsDataPkts18to63Octets  Counter,
    tokenRingPStatsDataPkts64to127Octets Counter,
    tokenRingPStatsDataPkts128to255Octets Counter,
    tokenRingPStatsDataPkts256to511Octets Counter,
    tokenRingPStatsDataPkts512to1023Octets Counter,
    tokenRingPStatsDataPkts1024to2047Octets Counter,
    tokenRingPStatsDataPkts2048to4095Octets Counter,
    tokenRingPStatsDataPkts4096to8191Octets Counter,
    tokenRingPStatsDataPkts8192to18000Octets Counter,
    tokenRingPStatsDataPktsGreaterThan18000Octets Counter,
```



```
        tokenRingPStatsOwner                OwnerString,
        tokenRingPStatsStatus                EntryStatus
    }
```

tokenRingPStatsIndex OBJECT-TYPE

SYNTAX INTEGER (1..65535)

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The value of this object uniquely identifies this
tokenRingPStats entry."

::= { tokenRingPStatsEntry 1 }

tokenRingPStatsDataSource OBJECT-TYPE

SYNTAX OBJECT IDENTIFIER

ACCESS read-write

STATUS mandatory

DESCRIPTION

"This object identifies the source of the data
that this tokenRingPStats entry is configured to
analyze. This source can be any tokenRing
interface on this device. In order to identify a
particular interface, this object shall identify
the instance of the ifIndex object, defined in
MIB-II [3], for the desired interface. For
example, if an entry were to receive data from
interface #1, this object would be set to
ifIndex.1.

The statistics in this group reflect all non-MAC
packets on the local network segment attached to
the identified interface.

This object may not be modified if the associated
tokenRingPStatsStatus object is equal to
valid(1)."

::= { tokenRingPStatsEntry 2 }

tokenRingPStatsDropEvents OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of events in which packets were
dropped by the probe due to lack of resources.

Note that this number is not necessarily the number of packets dropped; it is just the number of times this condition has been detected. This value is the same as the corresponding

tokenRingMLStatsDropEvents"

::= { tokenRingPStatsEntry 3 }

tokenRingPStatsDataOctets OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of octets of data (excluding those in bad packets) received on the network (excluding framing bits but including FCS octets) in non-MAC packets."

::= { tokenRingPStatsEntry 4 }

tokenRingPStatsDataPkts OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of non-MAC packets (excluding packets with errors) received."

::= { tokenRingPStatsEntry 5 }

tokenRingPStatsDataBroadcastPkts OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of good non-MAC packets received that were directed to an LLC broadcast address (0xFFFFFFFF or 0xC000FFFFFFFF)."

::= { tokenRingPStatsEntry 6 }

tokenRingPStatsDataMulticastPkts OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of good non-MAC packets received that were directed to a local or global multicast or functional address. Note that this number does

not include packets directed to the broadcast address."

::= { tokenRingPStatsEntry 7 }

tokenRingPStatsDataPkts18to63Octets OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of non-MAC packets (excluding packets with errors) received that were between 18 and 63 octets in length inclusive, excluding framing bits but including FCS octets."

::= { tokenRingPStatsEntry 8 }

tokenRingPStatsDataPkts64to127Octets OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of non-MAC packets (excluding packets with errors) received that were between 64 and 127 octets in length inclusive, excluding framing bits but including FCS octets."

::= { tokenRingPStatsEntry 9 }

tokenRingPStatsDataPkts128to255Octets OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of non-MAC packets (excluding packets with errors) received that were between 128 and 255 octets in length inclusive, excluding framing bits but including FCS octets."

::= { tokenRingPStatsEntry 10 }

tokenRingPStatsDataPkts256to511Octets OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of non-MAC packets (excluding packets with errors) received that were between 256 and 511 octets in length inclusive, excluding

framing bits but including FCS octets."
 ::= { tokenRingPStatsEntry 11 }

tokenRingPStatsDataPkts512to1023Octets OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of non-MAC packets (excluding packets with errors) received that were between 512 and 1023 octets in length inclusive, excluding framing bits but including FCS octets."

::= { tokenRingPStatsEntry 12 }

tokenRingPStatsDataPkts1024to2047Octets OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of non-MAC packets (excluding packets with errors) received that were between 1024 and 2047 octets in length inclusive, excluding framing bits but including FCS octets."

::= { tokenRingPStatsEntry 13 }

tokenRingPStatsDataPkts2048to4095Octets OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of non-MAC packets (excluding packets with errors) received that were between 2048 and 4095 octets in length inclusive, excluding framing bits but including FCS octets."

::= { tokenRingPStatsEntry 14 }

tokenRingPStatsDataPkts4096to8191Octets OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of non-MAC packets (excluding packets with errors) received that were between 4096 and 8191 octets in length inclusive, excluding framing bits but including FCS octets."


```
::= { tokenRingPStatsEntry 15 }
```

```
tokenRingPStatsDataPkts8192to18000Octets OBJECT-TYPE
```

```
    SYNTAX Counter
```

```
    ACCESS read-only
```

```
    STATUS mandatory
```

```
    DESCRIPTION
```

```
        "The total number of non-MAC packets (excluding
        packets with errors) received that were between
        8192 and 18000 octets in length inclusive,
        excluding framing bits but including FCS octets."
```

```
::= { tokenRingPStatsEntry 16 }
```

```
tokenRingPStatsDataPktsGreaterThan18000Octets OBJECT-TYPE
```

```
    SYNTAX Counter
```

```
    ACCESS read-only
```

```
    STATUS mandatory
```

```
    DESCRIPTION
```

```
        "The total number of non-MAC packets (excluding
        packets with errors) received that were greater
        than 18000 octets in length, excluding framing
        bits but including FCS octets."
```

```
::= { tokenRingPStatsEntry 17 }
```

```
tokenRingPStatsOwner OBJECT-TYPE
```

```
    SYNTAX OwnerString
```

```
    ACCESS read-write
```

```
    STATUS mandatory
```

```
    DESCRIPTION
```

```
        "The entity that configured this entry and is
        therefore using the resources assigned to it."
```

```
::= { tokenRingPStatsEntry 18 }
```

```
tokenRingPStatsStatus OBJECT-TYPE
```

```
    SYNTAX EntryStatus
```

```
    ACCESS read-write
```

```
    STATUS mandatory
```

```
    DESCRIPTION
```

```
        "The status of this tokenRingPStats entry."
```

```
::= { tokenRingPStatsEntry 19 }
```


-- The Token Ring History Groups

-- When an entry in the historyControlTable is created that
-- identifies a token ring interface as its
-- historyControlDataSource, the probe shall create corresponding
-- entries in the tokenRingMLHistoryTable and/or the
-- tokenRingPHistoryTable, depending on which groups it supports.

-- The Token Ring Mac-Layer History Group

--

-- Implementation of this group is optional.
-- Implementation of this group requires implementation of the
-- historyControl group from [RFC1271](#).

tokenRingMLHistoryTable OBJECT-TYPE

SYNTAX SEQUENCE OF TokenRingMLHistoryEntry

ACCESS not-accessible

STATUS mandatory

DESCRIPTION

"A list of Mac-Layer Token Ring statistics
entries."

::= { history 3 }

tokenRingMLHistoryEntry OBJECT-TYPE

SYNTAX TokenRingMLHistoryEntry

ACCESS not-accessible

STATUS mandatory

DESCRIPTION

"A collection of Mac-Layer statistics kept for a
particular Token Ring interface."

INDEX { tokenRingMLHistoryIndex, tokenRingMLHistorySampleIndex }

::= { tokenRingMLHistoryTable 1 }

-- As an example, an instance of the tokenRingMLHistoryMacOctets
-- object might be named tokenRingMLHistoryMacOctets.1.27

TokenRingMLHistoryEntry ::= SEQUENCE {

tokenRingMLHistoryIndex	INTEGER,
tokenRingMLHistorySampleIndex	INTEGER,
tokenRingMLHistoryIntervalStart	TimeTicks,
tokenRingMLHistoryDropEvents	Counter,
tokenRingMLHistoryMacOctets	Counter,
tokenRingMLHistoryMacPkts	Counter,

tokenRingMLHistoryRingPurgeEvents	Counter,
tokenRingMLHistoryRingPurgePkts	Counter,
tokenRingMLHistoryBeaconEvents	Counter,
tokenRingMLHistoryBeaconTime	TimeInterval,
tokenRingMLHistoryBeaconPkts	Counter,
tokenRingMLHistoryClaimTokenEvents	Counter,
tokenRingMLHistoryClaimTokenPkts	Counter,
tokenRingMLHistoryNAUNChanges	Counter,
tokenRingMLHistoryLineErrors	Counter,
tokenRingMLHistoryInternalErrors	Counter,
tokenRingMLHistoryBurstErrors	Counter,
tokenRingMLHistoryACErrors	Counter,
tokenRingMLHistoryAbortErrors	Counter,
tokenRingMLHistoryLostFrameErrors	Counter,
tokenRingMLHistoryCongestionErrors	Counter,
tokenRingMLHistoryFrameCopiedErrors	Counter,
tokenRingMLHistoryFrequencyErrors	Counter,
tokenRingMLHistoryTokenErrors	Counter,
tokenRingMLHistorySoftErrorReports	Counter,
tokenRingMLHistoryRingPollEvents	Counter,
tokenRingMLHistoryActiveStations	INTEGER

}

tokenRingMLHistoryIndex OBJECT-TYPE

SYNTAX INTEGER (1..65535)

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The history of which this entry is a part. The history identified by a particular value of this index is the same history as identified by the same value of historyControlIndex."

::= { tokenRingMLHistoryEntry 1 }

tokenRingMLHistorySampleIndex OBJECT-TYPE

SYNTAX INTEGER

ACCESS read-only

STATUS mandatory

DESCRIPTION

"An index that uniquely identifies the particular Mac-Layer sample this entry represents among all Mac-Layer samples associated with the same historyControlEntry. This index starts at 1 and increases by one as each new sample is taken."

::= { tokenRingMLHistoryEntry 2 }

tokenRingMLHistoryIntervalStart OBJECT-TYPE

SYNTAX TimeTicks

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The value of sysUpTime at the start of the interval over which this sample was measured. If the probe keeps track of the time of day, it should start the first sample of the history at a time such that when the next hour of the day begins, a sample is started at that instant. Note that following this rule may require the probe to delay collecting the first sample of the history, as each sample must be of the same interval. Also note that the sample which is currently being collected is not accessible in this table until the end of its interval."

::= { tokenRingMLHistoryEntry 3 }

tokenRingMLHistoryDropEvents OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of events in which packets were dropped by the probe due to lack of resources during this sampling interval. Note that this number is not necessarily the number of packets dropped, it is just the number of times this condition has been detected."

::= { tokenRingMLHistoryEntry 4 }

tokenRingMLHistoryMacOctets OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of octets of data in MAC packets (excluding those in bad MAC packets) received on the network during this sampling interval (excluding framing bits but including FCS octets)."

::= { tokenRingMLHistoryEntry 5 }

tokenRingMLHistoryMacPkts OBJECT-TYPE

SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
 "The total number of MAC packets (excluding
 packets with errors) received during this sampling
 interval."
::= { tokenRingMLHistoryEntry 6 }

tokenRingMLHistoryRingPurgeEvents OBJECT-TYPE

SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
 "The total number of times that the ring entered
 the ring purge state from normal ring state during
 this sampling interval. The ring purge state that
 comes from the claim token or beacon state is not
 counted."
::= { tokenRingMLHistoryEntry 7 }

tokenRingMLHistoryRingPurgePkts OBJECT-TYPE

SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
 "The total number of Ring Purge MAC packets
 detected by the probe during this sampling
 interval."
::= { tokenRingMLHistoryEntry 8 }

tokenRingMLHistoryBeaconEvents OBJECT-TYPE

SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
 "The total number of times that the ring enters a
 beaconing state (beaconFrameStreamingState,
 beaconBitStreamingState,
 beaconSetRecoveryModeState, or
 beaconRingSignalLossState) during this sampling
 interval. Note that a change of the source
 address of the beacon packet does not constitute a
 new beacon event."
::= { tokenRingMLHistoryEntry 9 }

tokenRingMLHistoryBeaconTime OBJECT-TYPE

SYNTAX TimeInterval

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The amount of time that the ring has been in the
beaconing state during this sampling interval."

::= { tokenRingMLHistoryEntry 10 }

tokenRingMLHistoryBeaconPkts OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of beacon MAC packets detected
by the probe during this sampling interval."

::= { tokenRingMLHistoryEntry 11 }

tokenRingMLHistoryClaimTokenEvents OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of times that the ring enters
the claim token state from normal ring state or
ring purge state during this sampling interval.
The claim token state that comes from the beacon
state is not counted."

::= { tokenRingMLHistoryEntry 12 }

tokenRingMLHistoryClaimTokenPkts OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of claim token MAC packets
detected by the probe during this sampling
interval."

::= { tokenRingMLHistoryEntry 13 }

tokenRingMLHistoryNAUNChanges OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of NAUN changes detected by the
 probe during this sampling interval."
 ::= { tokenRingMLHistoryEntry 14 }

tokenRingMLHistoryLineErrors OBJECT-TYPE

 SYNTAX Counter
 ACCESS read-only
 STATUS mandatory
 DESCRIPTION
 "The total number of line errors reported in error
 reporting packets detected by the probe during
 this sampling interval."
 ::= { tokenRingMLHistoryEntry 15 }

tokenRingMLHistoryInternalErrors OBJECT-TYPE

 SYNTAX Counter
 ACCESS read-only
 STATUS mandatory
 DESCRIPTION
 "The total number of adapter internal errors
 reported in error reporting packets detected by
 the probe during this sampling interval."
 ::= { tokenRingMLHistoryEntry 16 }

tokenRingMLHistoryBurstErrors OBJECT-TYPE

 SYNTAX Counter
 ACCESS read-only
 STATUS mandatory
 DESCRIPTION
 "The total number of burst errors reported in
 error reporting packets detected by the probe
 during this sampling interval."
 ::= { tokenRingMLHistoryEntry 17 }

tokenRingMLHistoryACErrors OBJECT-TYPE

 SYNTAX Counter
 ACCESS read-only
 STATUS mandatory
 DESCRIPTION
 "The total number of AC (Address Copied) errors
 reported in error reporting packets detected by
 the probe during this sampling interval."
 ::= { tokenRingMLHistoryEntry 18 }

tokenRingMLHistoryAbortErrors OBJECT-TYPE

SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
 "The total number of abort delimiters reported in
 error reporting packets detected by the probe
 during this sampling interval."
::= { tokenRingMLHistoryEntry 19 }

tokenRingMLHistoryLostFrameErrors OBJECT-TYPE

SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
 "The total number of lost frame errors reported in
 error reporting packets detected by the probe
 during this sampling interval."
::= { tokenRingMLHistoryEntry 20 }

tokenRingMLHistoryCongestionErrors OBJECT-TYPE

SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
 "The total number of receive congestion errors
 reported in error reporting packets detected by
 the probe during this sampling interval."
::= { tokenRingMLHistoryEntry 21 }

tokenRingMLHistoryFrameCopiedErrors OBJECT-TYPE

SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
 "The total number of frame copied errors reported
 in error reporting packets detected by the probe
 during this sampling interval."
::= { tokenRingMLHistoryEntry 22 }

tokenRingMLHistoryFrequencyErrors OBJECT-TYPE

SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
 "The total number of frequency errors reported in


```
        error reporting packets detected by the probe
        during this sampling interval."
 ::= { tokenRingMLHistoryEntry 23 }
```

tokenRingMLHistoryTokenErrors OBJECT-TYPE

```
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The total number of token errors reported in
    error reporting packets detected by the probe
    during this sampling interval."
 ::= { tokenRingMLHistoryEntry 24 }
```

tokenRingMLHistorySoftErrorReports OBJECT-TYPE

```
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The total number of soft error report frames
    detected by the probe during this sampling
    interval."
 ::= { tokenRingMLHistoryEntry 25 }
```

tokenRingMLHistoryRingPollEvents OBJECT-TYPE

```
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The total number of ring poll events detected by
    the probe during this sampling interval."
 ::= { tokenRingMLHistoryEntry 26 }
```

tokenRingMLHistoryActiveStations OBJECT-TYPE

```
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The maximum number of active stations on the ring
    detected by the probe during this sampling
    interval."
 ::= { tokenRingMLHistoryEntry 27 }
```



```

-- The Token Ring Promiscuous History Group
--
-- Implementation of this group is optional.
-- Implementation of this group requires the implementation of the
-- historyControl group from RFC1271.

tokenRingPHistoryTable OBJECT-TYPE
    SYNTAX SEQUENCE OF TokenRingPHistoryEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "A list of promiscuous Token Ring statistics
        entries."
    ::= { history 4 }

tokenRingPHistoryEntry OBJECT-TYPE
    SYNTAX TokenRingPHistoryEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "A collection of promiscuous statistics kept for a
        particular Token Ring interface."
    INDEX { tokenRingPHistoryIndex, tokenRingPHistorySampleIndex }
    ::= { tokenRingPHistoryTable 1 }

-- As an example, an instance of the tokenRingPHistoryDataPkts object
-- might be named tokenRingPHistoryDataPkts.1.27

TokenRingPHistoryEntry ::= SEQUENCE {
    tokenRingPHistoryIndex                INTEGER,
    tokenRingPHistorySampleIndex          INTEGER,
    tokenRingPHistoryIntervalStart        TimeTicks,
    tokenRingPHistoryDropEvents           Counter,
    tokenRingPHistoryDataOctets           Counter,
    tokenRingPHistoryDataPkts             Counter,
    tokenRingPHistoryDataBroadcastPkts    Counter,
    tokenRingPHistoryDataMulticastPkts    Counter,
    tokenRingPHistoryDataPkts18to630ctets Counter,
    tokenRingPHistoryDataPkts64to1270ctets Counter,
    tokenRingPHistoryDataPkts128to2550ctets Counter,
    tokenRingPHistoryDataPkts256to5110ctets Counter,
    tokenRingPHistoryDataPkts512to10230ctets Counter,
    tokenRingPHistoryDataPkts1024to20470ctets Counter,
    tokenRingPHistoryDataPkts2048to40950ctets Counter,
    tokenRingPHistoryDataPkts4096to81910ctets Counter,

```



```
tokenRingPHistoryDataPkts8192to180000octets Counter,  
tokenRingPHistoryDataPktsGreaterThan180000octets Counter  
}
```

tokenRingPHistoryIndex OBJECT-TYPE

SYNTAX INTEGER (1..65535)

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The history of which this entry is a part. The history identified by a particular value of this index is the same history as identified by the same value of historyControlIndex."

::= { tokenRingPHistoryEntry 1 }

tokenRingPHistorySampleIndex OBJECT-TYPE

SYNTAX INTEGER

ACCESS read-only

STATUS mandatory

DESCRIPTION

"An index that uniquely identifies the particular sample this entry represents among all samples associated with the same historyControlEntry. This index starts at 1 and increases by one as each new sample is taken."

::= { tokenRingPHistoryEntry 2 }

tokenRingPHistoryIntervalStart OBJECT-TYPE

SYNTAX TimeTicks

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The value of sysUpTime at the start of the interval over which this sample was measured. If the probe keeps track of the time of day, it should start the first sample of the history at a time such that when the next hour of the day begins, a sample is started at that instant. Note that following this rule may require the probe to delay collecting the first sample of the history, as each sample must be of the same interval. Also note that the sample which is currently being collected is not accessible in this table until the end of its interval."

::= { tokenRingPHistoryEntry 3 }

tokenRingPHistoryDropEvents OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of events in which packets were dropped by the probe due to lack of resources during this sampling interval. Note that this number is not necessarily the number of packets dropped, it is just the number of times this condition has been detected."

::= { tokenRingPHistoryEntry 4 }

tokenRingPHistoryDataOctets OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of octets of data (excluding those in bad packets) received on the network (excluding framing bits but including FCS octets) in non-MAC packets during this sampling interval."

::= { tokenRingPHistoryEntry 5 }

tokenRingPHistoryDataPkts OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of non-MAC packets (excluding packets with errors) received during this sampling interval."

::= { tokenRingPHistoryEntry 6 }

tokenRingPHistoryDataBroadcastPkts OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of good non-MAC packets received during this sampling interval that were directed to an LLC broadcast address (0xFFFFFFFF or 0xC000FFFFFFFF)."

::= { tokenRingPHistoryEntry 7 }

tokenRingPHistoryDataMulticastPkts OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of good non-MAC packets received during this sampling interval that were directed to a local or global multicast or functional address. Note that this number does not include packets directed to the broadcast address."

::= { tokenRingPHistoryEntry 8 }

tokenRingPHistoryDataPkts18to63Octets OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of non-MAC packets (excluding packets with errors) received during this sampling interval that were between 18 and 63 octets in length inclusive, excluding framing bits but including FCS octets."

::= { tokenRingPHistoryEntry 9 }

tokenRingPHistoryDataPkts64to127Octets OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of non-MAC packets (excluding packets with errors) received during this sampling interval that were between 64 and 127 octets in length inclusive, excluding framing bits but including FCS octets."

::= { tokenRingPHistoryEntry 10 }

tokenRingPHistoryDataPkts128to255Octets OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of non-MAC packets (excluding packets with errors) received during this sampling interval that were between 128 and 255 octets in length inclusive, excluding framing bits but


```
        including FCS octets."
 ::= { tokenRingPHistoryEntry 11 }
```

tokenRingPHistoryDataPkts256to511Octets OBJECT-TYPE

```
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The total number of non-MAC packets (excluding
    packets with errors) received during this sampling
    interval that were between 256 and 511 octets in
    length inclusive, excluding framing bits but
    including FCS octets."
 ::= { tokenRingPHistoryEntry 12 }
```

tokenRingPHistoryDataPkts512to1023Octets OBJECT-TYPE

```
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The total number of non-MAC packets (excluding
    packets with errors) received during this sampling
    interval that were between 512 and 1023 octets in
    length inclusive, excluding framing bits but
    including FCS octets."
 ::= { tokenRingPHistoryEntry 13 }
```

tokenRingPHistoryDataPkts1024to2047Octets OBJECT-TYPE

```
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The total number of non-MAC packets (excluding
    packets with errors) received during this sampling
    interval that were between 1024 and 2047 octets in
    length inclusive, excluding framing bits but
    including FCS octets."
 ::= { tokenRingPHistoryEntry 14 }
```

tokenRingPHistoryDataPkts2048to4095Octets OBJECT-TYPE

```
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The total number of non-MAC packets (excluding
```


packets with errors) received during this sampling interval that were between 2048 and 4095 octets in length inclusive, excluding framing bits but including FCS octets."

::= { tokenRingPHistoryEntry 15 }

tokenRingPHistoryDataPkts4096to8191Octets OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of non-MAC packets (excluding packets with errors) received during this sampling interval that were between 4096 and 8191 octets in length inclusive, excluding framing bits but including FCS octets."

::= { tokenRingPHistoryEntry 16 }

tokenRingPHistoryDataPkts8192to18000Octets OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of non-MAC packets (excluding packets with errors) received during this sampling interval that were between 8192 and 18000 octets in length inclusive, excluding framing bits but including FCS octets."

::= { tokenRingPHistoryEntry 17 }

tokenRingPHistoryDataPktsGreaterThan18000Octets OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of non-MAC packets (excluding packets with errors) received during this sampling interval that were greater than 18000 octets in length, excluding framing bits but including FCS octets."

::= { tokenRingPHistoryEntry 18 }


```
-- The Token Ring Ring Station Group
--
-- Implementation of this group is optional
--
-- Although the ringStationTable stores entries only for those
-- stations physically attached to the local ring and the number of
-- stations attached to a ring is limited, a probe may still need to
-- free resources when resources grow tight. In such a situation, it
-- is suggested that the probe free only inactive stations, and to
-- first free the stations that have been inactive for the longest
-- time.
```

```
ringStationControlTable OBJECT-TYPE
    SYNTAX SEQUENCE OF RingStationControlEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "A list of ringStation table control entries."
    ::= { tokenRing 1 }
```

```
ringStationControlEntry OBJECT-TYPE
    SYNTAX RingStationControlEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "A list of parameters that set up the discovery of
        stations on a particular interface and the
        collection of statistics about these stations."
    INDEX { ringStationControlIfIndex }
    ::= { ringStationControlTable 1 }
```

```
-- As an example, an instance of the ringStationControlIfIndex object
-- might be named ringStationControlIfIndex.1
```

```
RingStationControlEntry ::= SEQUENCE {
    ringStationControlIfIndex      INTEGER,
    ringStationControlTableSize    INTEGER,
    ringStationControlActiveStations INTEGER,
    ringStationControlRingState    INTEGER,
    ringStationControlBeaconSender  MacAddress,
    ringStationControlBeaconNAUN   MacAddress,
    ringStationControlActiveMonitor MacAddress,
    ringStationControlOrderChanges Counter,
    ringStationControlOwner         OwnerString,
    ringStationControlStatus        EntryStatus
}
```



```
}
```

```
ringStationControlIfIndex OBJECT-TYPE
```

```
    SYNTAX INTEGER (1..65535)
```

```
    ACCESS read-only
```

```
    STATUS mandatory
```

```
    DESCRIPTION
```

```
        "The value of this object uniquely identifies the
        interface on this remote network monitoring device
        from which ringStation data is collected.  The
        interface identified by a particular value of this
        object is the same interface as identified by the
        same value of the ifIndex object, defined in MIB-
        II [3]."
```

```
    ::= { ringStationControlEntry 1 }
```

```
ringStationControlTableSize OBJECT-TYPE
```

```
    SYNTAX INTEGER
```

```
    ACCESS read-only
```

```
    STATUS mandatory
```

```
    DESCRIPTION
```

```
        "The number of ringStationEntries in the
        ringStationTable associated with this
        ringStationControlEntry."
```

```
    ::= { ringStationControlEntry 2 }
```

```
ringStationControlActiveStations OBJECT-TYPE
```

```
    SYNTAX INTEGER
```

```
    ACCESS read-only
```

```
    STATUS mandatory
```

```
    DESCRIPTION
```

```
        "The number of active ringStationEntries in the
        ringStationTable associated with this
        ringStationControlEntry."
```

```
    ::= { ringStationControlEntry 3 }
```

```
ringStationControlRingState OBJECT-TYPE
```

```
    SYNTAX INTEGER {
```

```
        normalOperation(1),
```

```
        ringPurgeState(2),
```

```
        claimTokenState(3),
```

```
        beaconFrameStreamingState(4),
```

```
        beaconBitStreamingState(5),
```

```
        beaconRingSignalLossState(6),
```

```
        beaconSetRecoveryModeState(7)
```



```
}  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
    "The current status of this ring."  
 ::= { ringStationControlEntry 4 }
```

ringStationControlBeaconSender OBJECT-TYPE

```
SYNTAX MacAddress  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
    "The address of the sender of the last beacon  
    frame received by the probe on this ring.  If no  
    beacon frames have been received, this object  
    shall be equal to six octets of zero."  
 ::= { ringStationControlEntry 5 }
```

ringStationControlBeaconNAUN OBJECT-TYPE

```
SYNTAX MacAddress  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
    "The address of the NAUN in the last beacon frame  
    received by the probe on this ring.  If no beacon  
    frames have been received, this object shall be  
    equal to six octets of zero."  
 ::= { ringStationControlEntry 6 }
```

ringStationControlActiveMonitor OBJECT-TYPE

```
SYNTAX MacAddress  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
    "The address of the Active Monitor on this  
    segment.  If this address is unknown, this object  
    shall be equal to six octets of zero."  
 ::= { ringStationControlEntry 7 }
```

ringStationControlOrderChanges OBJECT-TYPE

```
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
    "The number of add and delete events in the
```



```
        ringStationOrderTable optionally associated with
        this ringStationControlEntry."
 ::= { ringStationControlEntry 8 }
```

```
ringStationControlOwner OBJECT-TYPE
```

```
    SYNTAX OwnerString
```

```
    ACCESS read-write
```

```
    STATUS mandatory
```

```
    DESCRIPTION
```

```
        "The entity that configured this entry and is
        therefore using the resources assigned to it."
```

```
 ::= { ringStationControlEntry 9 }
```

```
ringStationControlStatus OBJECT-TYPE
```

```
    SYNTAX EntryStatus
```

```
    ACCESS read-write
```

```
    STATUS mandatory
```

```
    DESCRIPTION
```

```
        "The status of this ringStationControl entry.
```

```

        If this object is not equal to valid(1), all
        associated entries in the ringStationTable shall
        be deleted by the agent."
```

```
 ::= { ringStationControlEntry 10 }
```


ringStationTable OBJECT-TYPE

SYNTAX SEQUENCE OF RingStationEntry

ACCESS not-accessible

STATUS mandatory

DESCRIPTION

"A list of ring station entries. An entry will exist for each station that is now or has previously been detected as physically present on this ring."

::= { tokenRing 2 }

ringStationEntry OBJECT-TYPE

SYNTAX RingStationEntry

ACCESS not-accessible

STATUS mandatory

DESCRIPTION

"A collection of statistics for a particular station that has been discovered on a ring monitored by this device."

INDEX { ringStationIfIndex, ringStationMacAddress }

::= { ringStationTable 1 }

-- As an example, an instance of the ringStationStationStatus object
-- might be named ringStationStationStatus.1.16.0.90.0.64.131

RingStationEntry ::= SEQUENCE {

ringStationIfIndex	INTEGER,
ringStationMacAddress	MacAddress,
ringStationLastNAUN	MacAddress,
ringStationStationStatus	INTEGER,
ringStationLastEnterTime	TimeTicks,
ringStationLastExitTime	TimeTicks,
ringStationDuplicateAddresses	Counter,
ringStationInLineErrors	Counter,
ringStationOutLineErrors	Counter,
ringStationInternalErrors	Counter,
ringStationInBurstErrors	Counter,
ringStationOutBurstErrors	Counter,
ringStationACErrors	Counter,
ringStationAbortErrors	Counter,
ringStationLostFrameErrors	Counter,
ringStationCongestionErrors	Counter,
ringStationFrameCopiedErrors	Counter,
ringStationFrequencyErrors	Counter,
ringStationTokenErrors	Counter,


```
        ringStationInBeaconErrors      Counter,
        ringStationOutBeaconErrors     Counter,
        ringStationInsertions          Counter
    }

ringStationIfIndex OBJECT-TYPE
    SYNTAX INTEGER
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The value of this object uniquely identifies the
        interface on this remote network monitoring device
        on which this station was detected.  The interface
        identified by a particular value of this object is
        the same interface as identified by the same value
        of the ifIndex object, defined in MIB-II [3]."
    ::= { ringStationEntry 1 }

ringStationMacAddress OBJECT-TYPE
    SYNTAX MacAddress
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The physical address of this station."
    ::= { ringStationEntry 2 }

ringStationLastNAUN OBJECT-TYPE
    SYNTAX MacAddress
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The physical address of last known NAUN of this
        station."
    ::= { ringStationEntry 3 }

ringStationStationStatus OBJECT-TYPE
    SYNTAX INTEGER {
        active(1),          -- actively participating in ring poll.
        inactive(2),        -- Not participating in ring poll
        forcedRemoval(3)    -- Forced off ring by network management.
    }
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The status of this station on the ring."
```



```
::= { ringStationEntry 4 }
```

```
ringStationLastEnterTime OBJECT-TYPE
```

```
    SYNTAX TimeTicks
```

```
    ACCESS read-only
```

```
    STATUS mandatory
```

```
    DESCRIPTION
```

```
        "The value of sysUpTime at the time this station  
        last entered the ring.  If the time is unknown,  
        this value shall be zero."
```

```
::= { ringStationEntry 5 }
```

```
ringStationLastExitTime OBJECT-TYPE
```

```
    SYNTAX TimeTicks
```

```
    ACCESS read-only
```

```
    STATUS mandatory
```

```
    DESCRIPTION
```

```
        "The value of sysUpTime at the time the probe  
        detected that this station last exited the ring.  
        If the time is unknown, this value shall be zero."
```

```
::= { ringStationEntry 6 }
```

```
ringStationDuplicateAddresses OBJECT-TYPE
```

```
    SYNTAX Counter
```

```
    ACCESS read-only
```

```
    STATUS mandatory
```

```
    DESCRIPTION
```

```
        "The number of times this station experienced a  
        duplicate address error."
```

```
::= { ringStationEntry 7 }
```

```
ringStationInLineErrors OBJECT-TYPE
```

```
    SYNTAX Counter
```

```
    ACCESS read-only
```

```
    STATUS mandatory
```

```
    DESCRIPTION
```

```
        "The total number of line errors reported by this  
        station in error reporting packets detected by the  
        probe."
```

```
::= { ringStationEntry 8 }
```

```
ringStationOutLineErrors OBJECT-TYPE
```

```
    SYNTAX Counter
```

```
    ACCESS read-only
```

```
    STATUS mandatory
```


DESCRIPTION

"The total number of line errors reported in error reporting packets sent by the nearest active downstream neighbor of this station and detected by the probe."

::= { ringStationEntry 9 }

ringStationInternalErrors OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of adapter internal errors reported by this station in error reporting packets detected by the probe."

::= { ringStationEntry 10 }

ringStationInBurstErrors OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of burst errors reported by this station in error reporting packets detected by the probe."

::= { ringStationEntry 11 }

ringStationOutBurstErrors OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of burst errors reported in error reporting packets sent by the nearest active downstream neighbor of this station and detected by the probe."

::= { ringStationEntry 12 }

ringStationACErrors OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of AC (Address Copied) errors reported in error reporting packets sent by the


```
        nearest active downstream neighbor of this station
        and detected by the probe."
 ::= { ringStationEntry 13 }
```

ringStationAbortErrors OBJECT-TYPE

```
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The total number of abort delimiters reported by
        this station in error reporting packets detected
        by the probe."
 ::= { ringStationEntry 14 }
```

ringStationLostFrameErrors OBJECT-TYPE

```
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The total number of lost frame errors reported by
        this station in error reporting packets detected
        by the probe."
 ::= { ringStationEntry 15 }
```

ringStationCongestionErrors OBJECT-TYPE

```
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The total number of receive congestion errors
        reported by this station in error reporting
        packets detected by the probe."
 ::= { ringStationEntry 16 }
```

ringStationFrameCopiedErrors OBJECT-TYPE

```
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The total number of frame copied errors reported
        by this station in error reporting packets
        detected by the probe."
 ::= { ringStationEntry 17 }
```

ringStationFrequencyErrors OBJECT-TYPE

SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
 "The total number of frequency errors reported by
 this station in error reporting packets detected
 by the probe."
::= { ringStationEntry 18 }

ringStationTokenErrors OBJECT-TYPE

SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
 "The total number of token errors reported by this
 station in error reporting frames detected by the
 probe."
::= { ringStationEntry 19 }

ringStationInBeaconErrors OBJECT-TYPE

SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
 "The total number of beacon frames sent by this
 station and detected by the probe."
::= { ringStationEntry 20 }

ringStationOutBeaconErrors OBJECT-TYPE

SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
 "The total number of beacon frames detected by the
 probe that name this station as the NAUN."
::= { ringStationEntry 21 }

ringStationInsertions OBJECT-TYPE

SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
 "The number of times the probe detected this
 station inserting onto the ring."
::= { ringStationEntry 22 }


```
-- The Token Ring Ring Station Order Group
--
-- Implementation of this group is optional
--

-- The ringStationOrderTable

ringStationOrderTable OBJECT-TYPE
    SYNTAX SEQUENCE OF RingStationOrderEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "A list of ring station entries for stations in
        the ring poll, ordered by their ring-order."
    ::= { tokenRing 3 }

ringStationOrderEntry OBJECT-TYPE
    SYNTAX RingStationOrderEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "A collection of statistics for a particular
        station that is active on a ring monitored by this
        device. This table will contain information for
        every interface that has a
        ringStationControlStatus equal to valid."
    INDEX { ringStationOrderIfIndex, ringStationOrderOrderIndex }
    ::= { ringStationOrderTable 1 }

-- As an example, an instance of the ringStationOrderMacAddress
-- object might be named ringStationOrderMacAddress.1.14

RingStationOrderEntry ::= SEQUENCE {
    ringStationOrderIfIndex          INTEGER,
    ringStationOrderOrderIndex       INTEGER,
    ringStationOrderMacAddress        MacAddress
}

ringStationOrderIfIndex OBJECT-TYPE
    SYNTAX INTEGER
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The value of this object uniquely identifies the
        interface on this remote network monitoring device"
```


on which this station was detected. The interface identified by a particular value of this object is the same interface as identified by the same value of the ifIndex object, defined in MIB-II [\[3\]](#)."

::= { ringStationOrderEntry 1 }

ringStationOrderOrderIndex OBJECT-TYPE

SYNTAX INTEGER

ACCESS read-only

STATUS mandatory

DESCRIPTION

"This index denotes the location of this station with respect to other stations on the ring. This index is one more than the number of hops downstream that this station is from the rmon probe. The rmon probe itself gets the value one."

::= { ringStationOrderEntry 2 }

ringStationOrderMacAddress OBJECT-TYPE

SYNTAX MacAddress

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The physical address of this station."

::= { ringStationOrderEntry 3 }


```
-- The Token Ring Ring Station Config Group
--
-- Implementation of this group is optional.
-- The ring station config group manages token ring nodes through
-- active means.

ringStationConfigControlTable OBJECT-TYPE
    SYNTAX SEQUENCE OF RingStationConfigControlEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "A list of ring station configuration control
        entries."
    ::= { tokenRing 4 }

ringStationConfigControlEntry OBJECT-TYPE
    SYNTAX RingStationConfigControlEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "This entry controls active management of stations
        by the probe. One entry exists in this table for
        each active station in the ringStationTable."
    INDEX { ringStationConfigControlIfIndex,
            ringStationConfigControlMacAddress }
    ::= { ringStationConfigControlTable 1 }

-- As an example, an instance of the ringStationConfigControlRemove
-- object might be named
-- ringStationConfigControlRemove.1.16.0.90.0.64.131

RingStationConfigControlEntry ::= SEQUENCE {
    ringStationConfigControlIfIndex      INTEGER,
    ringStationConfigControlMacAddress    MacAddress,
    ringStationConfigControlRemove        INTEGER,
    ringStationConfigControlUpdateStats   INTEGER
}

ringStationConfigControlIfIndex OBJECT-TYPE
    SYNTAX INTEGER
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The value of this object uniquely identifies the
        interface on this remote network monitoring device"
```


on which this station was detected. The interface identified by a particular value of this object is the same interface as identified by the same value of the ifIndex object, defined in MIB-II [\[3\]](#)."

::= { ringStationConfigControlEntry 1 }

ringStationConfigControlMacAddress OBJECT-TYPE

SYNTAX MacAddress

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The physical address of this station."

::= { ringStationConfigControlEntry 2 }

ringStationConfigControlRemove OBJECT-TYPE

SYNTAX INTEGER {

stable(1),

removing(2)

}

ACCESS read-write

STATUS mandatory

DESCRIPTION

"Setting this object to `removing(2)' causes a Remove Station MAC frame to be sent. The agent will set this object to `stable(1)' after processing the request."

::= { ringStationConfigControlEntry 3 }

ringStationConfigControlUpdateStats OBJECT-TYPE

SYNTAX INTEGER {

stable(1),

updating(2)

}

ACCESS read-write

STATUS mandatory

DESCRIPTION

"Setting this object to `updating(2)' causes the configuration information associate with this entry to be updated. The agent will set this object to `stable(1)' after processing the request."

::= { ringStationConfigControlEntry 4 }


```
-- The ringStationConfig Table
--
-- Entries exist in this table after an active
-- configuration query has completed successfully for
-- a station. This query is initiated by the associated
-- ringStationConfigControlUpdateStats variable.

ringStationConfigTable OBJECT-TYPE
    SYNTAX SEQUENCE OF RingStationConfigEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "A list of configuration entries for stations on a
        ring monitored by this probe."
    ::= { tokenRing 5 }

ringStationConfigEntry OBJECT-TYPE
    SYNTAX RingStationConfigEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "A collection of statistics for a particular
        station that has been discovered on a ring
        monitored by this probe."
    INDEX { ringStationConfigIfIndex, ringStationConfigMacAddress }
    ::= { ringStationConfigTable 1 }

-- As an example, an instance of the ringStationConfigLocation object
-- might be named ringStationConfigLocation.1.16.0.90.0.64.131

RingStationConfigEntry ::= SEQUENCE {
    ringStationConfigIfIndex      INTEGER,
    ringStationConfigMacAddress   MacAddress,
    ringStationConfigUpdateTime   TimeTicks,
    ringStationConfigLocation     OCTET STRING,
    ringStationConfigMicrocode    OCTET STRING,
    ringStationConfigGroupAddress OCTET STRING,
    ringStationConfigFunctionalAddress OCTET STRING
}

ringStationConfigIfIndex OBJECT-TYPE
    SYNTAX INTEGER
    ACCESS read-only
    STATUS mandatory
```


DESCRIPTION

"The value of this object uniquely identifies the interface on this remote network monitoring device on which this station was detected. The interface identified by a particular value of this object is the same interface as identified by the same value of the ifIndex object, defined in MIB-II [3]."

::= { ringStationConfigEntry 1 }

ringStationConfigMacAddress OBJECT-TYPE

SYNTAX MacAddress

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The physical address of this station."

::= { ringStationConfigEntry 2 }

ringStationConfigUpdateTime OBJECT-TYPE

SYNTAX TimeTicks

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The value of sysUpTime at the time this configuration information was last updated (completely)."

::= { ringStationConfigEntry 3 }

ringStationConfigLocation OBJECT-TYPE

SYNTAX OCTET STRING (SIZE(4))

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The assigned physical location of this station."

::= { ringStationConfigEntry 4 }

ringStationConfigMicrocode OBJECT-TYPE

SYNTAX OCTET STRING (SIZE(10))

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The microcode EC level of this station."

::= { ringStationConfigEntry 5 }

ringStationConfigGroupAddress OBJECT-TYPE

SYNTAX OCTET STRING (SIZE(4))

ACCESS read-only
STATUS mandatory
DESCRIPTION
 "The low-order 4 octets of the group address
 recognized by this station."
 ::= { ringStationConfigEntry 6 }

ringStationConfigFunctionalAddress OBJECT-TYPE
SYNTAX OCTET STRING (SIZE(4))
ACCESS read-only
STATUS mandatory
DESCRIPTION
 "the functional addresses recognized by this
 station."
 ::= { ringStationConfigEntry 7 }

```
-- The Source Routing group
--
-- Implementation of this group is optional.
-- The data in this group is collected from the source routing
-- information potentially present in any token ring packet.
-- This information will be valid only in a pure source route
-- bridging environment. In a transparent bridging or a mixed
-- bridging environment, this information may not be accurate.
```

```
sourceRoutingStatsTable OBJECT-TYPE
    SYNTAX SEQUENCE OF SourceRoutingStatsEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "A list of source routing statistics entries."
    ::= { tokenRing 6 }
```

```
sourceRoutingStatsEntry OBJECT-TYPE
    SYNTAX SourceRoutingStatsEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "A collection of source routing statistics kept
        for a particular Token Ring interface."
    INDEX { sourceRoutingStatsIfIndex }
    ::= { sourceRoutingStatsTable 1 }
```

```
-- As an example, an instance of the sourceRoutingStatsInFrames
-- object might be named sourceRoutingStatsInFrames.1
```

```
SourceRoutingStatsEntry ::= SEQUENCE {
    sourceRoutingStatsIfIndex          INTEGER,
    sourceRoutingStatsRingNumber       INTEGER,
    sourceRoutingStatsInFrames         Counter,
    -- in to our net

    sourceRoutingStatsOutFrames        Counter,
    -- out from our net

    sourceRoutingStatsThroughFrames    Counter,
    -- through our net

    sourceRoutingStatsAllRoutesBroadcastFrames Counter,
    sourceRoutingStatsSingleRouteBroadcastFrames Counter,
    sourceRoutingStatsInOctets         Counter,
```



```
sourceRoutingStatsOutOctets          Counter,
sourceRoutingStatsThroughOctets      Counter,
sourceRoutingStatsAllRoutesBroadcastOctets Counter,
sourceRoutingStatsSingleRoutesBroadcastOctets Counter,
sourceRoutingStatsLocalLLCFrames     Counter,
sourceRoutingStats1HopFrames         Counter,
sourceRoutingStats2HopsFrames        Counter,
sourceRoutingStats3HopsFrames        Counter,
sourceRoutingStats4HopsFrames        Counter,
sourceRoutingStats5HopsFrames        Counter,
sourceRoutingStats6HopsFrames        Counter,
sourceRoutingStats7HopsFrames        Counter,
sourceRoutingStats8HopsFrames        Counter,
sourceRoutingStatsMoreThan8HopsFrames Counter,
sourceRoutingStatsOwner              OwnerString,
sourceRoutingStatsStatus             EntryStatus
}
```

sourceRoutingStatsIfIndex OBJECT-TYPE

SYNTAX INTEGER

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The value of this object uniquely identifies the interface on this remote network monitoring device on which source routing statistics will be detected. The interface identified by a particular value of this object is the same interface as identified by the same value of the ifIndex object, defined in MIB-II [3]."

::= { sourceRoutingStatsEntry 1 }

sourceRoutingStatsRingNumber OBJECT-TYPE

SYNTAX INTEGER

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The ring number of the ring monitored by this entry. When any object in this entry is created, the probe will attempt to discover the ring number. Only after the ring number is discovered will this object be created. After creating an object in this entry, the management station should poll this object to detect when it is created. Only after this object is created can


```
        the management station set the
        sourceRoutingStatsStatus entry to valid(1)."
 ::= { sourceRoutingStatsEntry 2 }
```

sourceRoutingStatsInFrames OBJECT-TYPE

```
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The count of frames sent into this ring from
    another ring."
 ::= { sourceRoutingStatsEntry 3 }
```

sourceRoutingStatsOutFrames OBJECT-TYPE

```
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The count of frames sent from this ring to
    another ring."
 ::= { sourceRoutingStatsEntry 4 }
```

sourceRoutingStatsThroughFrames OBJECT-TYPE

```
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The count of frames sent from another ring,
    through this ring, to another ring."
 ::= { sourceRoutingStatsEntry 5 }
```

sourceRoutingStatsAllRoutesBroadcastFrames OBJECT-TYPE

```
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The total number of good frames received that
    were All Routes Broadcast."
 ::= { sourceRoutingStatsEntry 6 }
```

sourceRoutingStatsSingleRouteBroadcastFrames OBJECT-TYPE

```
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
```



```
        "The total number of good frames received that  
        were Single Route Broadcast."  
 ::= { sourceRoutingStatsEntry 7 }
```

sourceRoutingStatsInOctets OBJECT-TYPE

```
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
    "The count of octets in good frames sent into this  
    ring from another ring."  
 ::= { sourceRoutingStatsEntry 8 }
```

sourceRoutingStatsOutOctets OBJECT-TYPE

```
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
    "The count of octets in good frames sent from this  
    ring to another ring."  
 ::= { sourceRoutingStatsEntry 9 }
```

sourceRoutingStatsThroughOctets OBJECT-TYPE

```
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
    "The count of octets in good frames sent another  
    ring, through this ring, to another ring."  
 ::= { sourceRoutingStatsEntry 10 }
```

sourceRoutingStatsAllRoutesBroadcastOctets OBJECT-TYPE

```
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
    "The total number of octets in good frames  
    received that were All Routes Broadcast."  
 ::= { sourceRoutingStatsEntry 11 }
```

sourceRoutingStatsSingleRoutesBroadcastOctets OBJECT-TYPE

```
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION
```


"The total number of octets in good frames
 received that were Single Route Broadcast."
 ::= { sourceRoutingStatsEntry 12 }

sourceRoutingStatsLocalLLCFrames OBJECT-TYPE

 SYNTAX Counter

 ACCESS read-only

 STATUS mandatory

 DESCRIPTION

 "The total number of frames received who had no
 routing information and were not All Route
 Broadcast Frames."

::= { sourceRoutingStatsEntry 13 }

sourceRoutingStats1HopFrames OBJECT-TYPE

 SYNTAX Counter

 ACCESS read-only

 STATUS mandatory

 DESCRIPTION

 "The total number of frames received whose route
 had 1 hop, were not All Route Broadcast Frames,
 and whose source or destination were on this ring
 (i.e. frames that had a RIF field and had this
 ring number in the first or last entry of the RIF
 field)."

::= { sourceRoutingStatsEntry 14 }

sourceRoutingStats2HopsFrames OBJECT-TYPE

 SYNTAX Counter

 ACCESS read-only

 STATUS mandatory

 DESCRIPTION

 "The total number of frames received whose route
 had 2 hops, were not All Route Broadcast Frames,
 and whose source or destination were on this ring
 (i.e. frames that had a RIF field and had this
 ring number in the first or last entry of the RIF
 field)."

::= { sourceRoutingStatsEntry 15 }

sourceRoutingStats3HopsFrames OBJECT-TYPE

 SYNTAX Counter

 ACCESS read-only

 STATUS mandatory

 DESCRIPTION

"The total number of frames received whose route had 3 hops, were not All Route Broadcast Frames, and whose source or destination were on this ring (i.e. frames that had a RIF field and had this ring number in the first or last entry of the RIF field)."

::= { sourceRoutingStatsEntry 16 }

sourceRoutingStats4HopsFrames OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of frames received whose route had 4 hops, were not All Route Broadcast Frames, and whose source or destination were on this ring (i.e. frames that had a RIF field and had this ring number in the first or last entry of the RIF field)."

::= { sourceRoutingStatsEntry 17 }

sourceRoutingStats5HopsFrames OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of frames received whose route had 5 hops, were not All Route Broadcast Frames, and whose source or destination were on this ring (i.e. frames that had a RIF field and had this ring number in the first or last entry of the RIF field)."

::= { sourceRoutingStatsEntry 18 }

sourceRoutingStats6HopsFrames OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

DESCRIPTION

"The total number of frames received whose route had 6 hops, were not All Route Broadcast Frames, and whose source or destination were on this ring (i.e. frames that had a RIF field and had this ring number in the first or last entry of the RIF field)."


```
::= { sourceRoutingStatsEntry 19 }
```

```
sourceRoutingStats7HopsFrames OBJECT-TYPE
```

```
SYNTAX Counter
```

```
ACCESS read-only
```

```
STATUS mandatory
```

```
DESCRIPTION
```

```
    "The total number of frames received whose route  
    had 7 hops, were not All Route Broadcast Frames,  
    and whose source or destination were on this ring  
    (i.e. frames that had a RIF field and had this  
    ring number in the first or last entry of the RIF  
    field)."
```

```
::= { sourceRoutingStatsEntry 20 }
```

```
sourceRoutingStats8HopsFrames OBJECT-TYPE
```

```
SYNTAX Counter
```

```
ACCESS read-only
```

```
STATUS mandatory
```

```
DESCRIPTION
```

```
    "The total number of frames received whose route  
    had 8 hops, were not All Route Broadcast Frames,  
    and whose source or destination were on this ring  
    (i.e. frames that had a RIF field and had this  
    ring number in the first or last entry of the RIF  
    field)."
```

```
::= { sourceRoutingStatsEntry 21 }
```

```
sourceRoutingStatsMoreThan8HopsFrames OBJECT-TYPE
```

```
SYNTAX Counter
```

```
ACCESS read-only
```

```
STATUS mandatory
```

```
DESCRIPTION
```

```
    "The total number of frames received whose route  
    had more than 8 hops, were not All Route Broadcast  
    Frames, and whose source or destination were on  
    this ring (i.e. frames that had a RIF field and  
    had this ring number in the first or last entry of  
    the RIF field)."
```

```
::= { sourceRoutingStatsEntry 22 }
```

```
sourceRoutingStatsOwner OBJECT-TYPE
```

```
SYNTAX OwnerString
```

```
ACCESS read-write
```

```
STATUS mandatory
```


DESCRIPTION

"The entity that configured this entry and is
therefore using the resources assigned to it."

::= { sourceRoutingStatsEntry 23 }

sourceRoutingStatsStatus OBJECT-TYPE

SYNTAX EntryStatus

ACCESS read-write

STATUS mandatory

DESCRIPTION

"The status of this sourceRoutingStats entry."

::= { sourceRoutingStatsEntry 24 }

END

7. References

- [1] M.T. Rose and K. McCloghrie, Structure and Identification of Management Information for TCP/IP-based internets. Request for Comments 1155, (May, 1990).
- [2] M.T. Rose and K. McCloghrie, Concise MIB Definitions. Request for Comments 1212, (March, 1991).
- [3] K. McCloghrie and M.T. Rose, Management Information Base for Network Management of TCP/IP-based internets: MIB-II. Request for Comments 1213, (March, 1991).
- [4] J.D. Case, M.S. Fedor, M.L. Schoffstall, and J.R. Davin, Simple Network Management Protocol. Request for Comments 1157, (May, 1990).
- [5] Information processing systems - Open Systems Interconnection - Specification of Abstract Syntax Notation One (ASN.1), International Organization for Standardization. International Standard 8824, (December, 1987).
- [6] Steven Waldbusser, Remote Network Monitoring Management Information Base Request for Comments 1271, (November, 1991).

Table of Contents

1	Status of this Memo	1
2	Abstract	1
3	The Network Management Framework	2
4	Guidelines for implementing RFC1271 objects on a Token Ring network	3
4.1	Host Group	3
4.2	Matrix Group	3
4.3	Filter Group	3
4.4	Other comments	4
5	Overview of the RMON Token Ring Extensions MIB	5
5.1	The Token Ring Statistics Groups	5
5.2	The Token Ring History Groups	5
5.3	The Token Ring Ring Station Group	6
5.4	The Token Ring Ring Station Order Group	6
5.5	The Token Ring Ring Station Config Group	6
5.6	The Source Routing Group	6
6	Definitions	7
6.1	The Token Ring Mac-Layer Statistics Group	8
6.2	The Token Ring Promiscuous Statistics Group	16
6.3	The Token Ring Mac-Layer History Group	22
6.4	The Token Ring Promiscuous History Group	30
6.5	The Token Ring Ring Station Group	36
6.6	The Token Ring Ring Station Order Group	46
6.7	The Token Ring Ring Station Config Group	48
6.8	The Source Routing Group	53
7	References	61

