

ROLL  
Internet-Draft  
Intended status: Standards Track  
Expires: October 16, 2014

J. Hui  
Cisco  
R. Kelsey  
Silicon Labs  
April 14, 2014

**Multicast Protocol for Low power and Lossy Networks (MPL)**  
**draft-ietf-roll-trickle-mcast-09**

Abstract

This document specifies the Multicast Protocol for Low power and Lossy Networks (MPL) that provides IPv6 multicast forwarding in constrained networks. MPL avoids the need to construct or maintain any multicast forwarding topology, disseminating messages to all MPL Forwarders in an MPL Domain. MPL uses the Trickle algorithm to manage message transmissions for both control and data-plane messages. Different Trickle parameter configurations allow MPL to trade between dissemination latency and transmission efficiency.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on October 16, 2014.

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	<a href="#">Introduction</a>	<a href="#">3</a>
<a href="#">2.</a>	<a href="#">Terminology</a>	<a href="#">3</a>
<a href="#">3.</a>	<a href="#">Applicability Statement</a>	<a href="#">4</a>
<a href="#">4.</a>	<a href="#">Protocol Overview</a>	<a href="#">5</a>
<a href="#">4.1.</a>	<a href="#">MPL Domains</a>	<a href="#">5</a>
<a href="#">4.2.</a>	<a href="#">Information Base Overview</a>	<a href="#">6</a>
<a href="#">4.3.</a>	<a href="#">Protocol Overview</a>	<a href="#">6</a>
<a href="#">4.4.</a>	<a href="#">Signaling Overview</a>	<a href="#">8</a>
<a href="#">5.</a>	<a href="#">MPL Parameters and Constants</a>	<a href="#">8</a>
<a href="#">5.1.</a>	<a href="#">MPL Multicast Addresses</a>	<a href="#">8</a>
<a href="#">5.2.</a>	<a href="#">MPL Message Types</a>	<a href="#">9</a>
<a href="#">5.3.</a>	<a href="#">MPL Seed Identifiers</a>	<a href="#">9</a>
<a href="#">5.4.</a>	<a href="#">MPL Parameters</a>	<a href="#">9</a>
<a href="#">6.</a>	<a href="#">Protocol Message Formats</a>	<a href="#">11</a>
<a href="#">6.1.</a>	<a href="#">MPL Option</a>	<a href="#">11</a>
<a href="#">6.2.</a>	<a href="#">MPL Control Message</a>	<a href="#">12</a>
<a href="#">6.3.</a>	<a href="#">MPL Seed Info</a>	<a href="#">13</a>
<a href="#">7.</a>	<a href="#">Information Base</a>	<a href="#">14</a>
<a href="#">7.1.</a>	<a href="#">Local Interface Set</a>	<a href="#">14</a>
<a href="#">7.2.</a>	<a href="#">Domain Set</a>	<a href="#">15</a>
<a href="#">7.3.</a>	<a href="#">Seed Set</a>	<a href="#">15</a>
<a href="#">7.4.</a>	<a href="#">Buffered Message Set</a>	<a href="#">15</a>
<a href="#">8.</a>	<a href="#">MPL Seed Sequence Numbers</a>	<a href="#">16</a>
<a href="#">9.</a>	<a href="#">MPL Data Messages</a>	<a href="#">16</a>
<a href="#">9.1.</a>	<a href="#">MPL Data Message Generation</a>	<a href="#">16</a>
<a href="#">9.2.</a>	<a href="#">MPL Data Message Transmission</a>	<a href="#">17</a>
<a href="#">9.3.</a>	<a href="#">MPL Data Message Processing</a>	<a href="#">18</a>
<a href="#">10.</a>	<a href="#">MPL Control Messages</a>	<a href="#">19</a>
<a href="#">10.1.</a>	<a href="#">MPL Control Message Generation</a>	<a href="#">19</a>
<a href="#">10.2.</a>	<a href="#">MPL Control Message Transmission</a>	<a href="#">19</a>
<a href="#">10.3.</a>	<a href="#">MPL Control Message Processing</a>	<a href="#">20</a>
<a href="#">11.</a>	<a href="#">Acknowledgements</a>	<a href="#">21</a>
<a href="#">12.</a>	<a href="#">IANA Considerations</a>	<a href="#">21</a>
<a href="#">12.1.</a>	<a href="#">MPL Option Type</a>	<a href="#">21</a>
<a href="#">12.2.</a>	<a href="#">MPL ICMPv6 Type</a>	<a href="#">22</a>
<a href="#">12.3.</a>	<a href="#">Well-known Multicast Addresses</a>	<a href="#">22</a>
<a href="#">13.</a>	<a href="#">Security Considerations</a>	<a href="#">22</a>
<a href="#">14.</a>	<a href="#">References</a>	<a href="#">23</a>
<a href="#">14.1.</a>	<a href="#">Normative References</a>	<a href="#">23</a>
<a href="#">14.2.</a>	<a href="#">Informative References</a>	<a href="#">24</a>
	<a href="#">Authors' Addresses</a>	<a href="#">24</a>



## **1. Introduction**

Low power and Lossy Networks typically operate with strict resource constraints in communication, computation, memory, and energy. Such resource constraints may preclude the use of existing IPv6 multicast routing and forwarding mechanisms. Traditional IP multicast delivery typically relies on topology maintenance mechanisms to discover and maintain routes to all subscribers of a multicast group (e.g. [\[RFC3973\]](#) [\[RFC4601\]](#)). However, maintaining such topologies in Low power and Lossy Networks (LLNs) is costly and may not be feasible given the available resources.

Memory constraints may limit devices to maintaining links/routes to one or a few neighbors. For this reason, the Routing Protocol for LLNs (RPL) specifies both storing and non-storing modes [\[RFC6550\]](#). The latter allows RPL routers to maintain only one or a few default routes towards a LLN Border Router (LBR) and use source routing to forward messages away from the LBR. For the same reasons, a LLN device may not be able to maintain a multicast routing topology when operating with limited memory.

Furthermore, the dynamic properties of wireless networks can make the cost of maintaining a multicast routing topology prohibitively expensive. In wireless environments, topology maintenance may involve selecting a connected dominating set used to forward multicast messages to all nodes in an administrative domain. However, existing mechanisms often require two-hop topology information and the cost of maintaining such information grows polynomially with network density.

This document specifies the Multicast Protocol for Low power and Lossy Networks (MPL), which provides IPv6 multicast forwarding in constrained networks. MPL avoids the need to construct or maintain any multicast routing topology, disseminating multicast messages to all MPL Forwarders in an MPL Domain. By using the Trickle algorithm [\[RFC6206\]](#), MPL requires only small, constant state for each MPL device that initiates disseminations. The Trickle algorithm also allows MPL to be density-aware, allowing the communication rate to scale logarithmically with density.

## **2. Terminology**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [\[RFC2119\]](#).

The following terms are used throughout this document:



MPL Forwarder	- A router that implements MPL. An MPL Forwarder is equipped with at least one MPL Interface.
MPL Interface	- An MPL Forwarder's attachment to a communications medium, over which it transmits and receives MPL Data Messages and MPL Control Messages according to this specification. An MPL Interface is assigned one or more unicast addresses and is subscribed to one or more MPL Domain Addresses.
MPL Domain Address	- A multicast address that identifies the set of MPL Interfaces within an MPL Domain. MPL Data Messages disseminated in an MPL Domain have the associated MPL Domain Address as their destination address.
MPL Domain	- A scope zone, as defined in [ <a href="#">RFC4007</a> ], in which MPL Interfaces subscribe to the same MPL Domain Address and participate in disseminating MPL Data Messages.
MPL Data Message	- A multicast message that is used to communicate a multicast payload between MPL Forwarders within an MPL domain. An MPL Data Message contains an MPL Option in the IPv6 header and has as its destination address the MPL Domain Address corresponding to the MPL Domain.
MPL Control Message	- A link-local multicast message that is used to communicate information about recently received MPL Data Messages to neighboring MPL Forwarders.
MPL Seed	- An MPL Forwarder that generates MPL Data Messages and serves as an entry point into an MPL Domain.
MPL Seed Identifier	- An unsigned integer that uniquely identifies an MPL Seed within an MPL Domain.

### 3. Applicability Statement

MPL is an IPv6 multicast forwarding protocol designed for the communication characteristics and resource constraints of Low-Power and Lossy Networks. By implementing controlled disseminations of multicast messages using the Trickle algorithm, MPL is designed for networks that communicate using low-power and lossy links with widely varying topologies in both the space and time dimensions.



While designed specifically for Low-Power and Lossy Networks, MPL is not limited to use over such networks. MPL may be applicable to any network where no multicast routing state is desired. MPL may also be used in environments where only a subset of links are considered Low-Power and Lossy links.

A host need not be aware that their multicast is supported by MPL as long as its attachment router forwards multicast messages between the MPL Domain and the host. However, a host may choose to implement MPL so that it can take advantage of the broadcast medium inherent in many Low-Power and Lossy Networks and receive multicast messages carried by MPL directly.

## **4. Protocol Overview**

The goal of MPL is to deliver multicast messages to all interfaces that subscribe to the multicast messages' destination address within an MPL Domain.

### **4.1. MPL Domains**

An MPL Domain is a scope zone, as defined in [[RFC4007](#)], in which MPL Interfaces subscribe to the same MPL Domain Address and participate in disseminating MPL Data Messages.

By default, an MPL Forwarder SHOULD participate in an MPL Domain identified by the ALL\_MPL\_FORWARDERS multicast address with a scope value of 3 (Realm-Local) [[I-D.ietf-6man-multicast-scopes](#)].

When MPL is used in deployments that use administratively defined scopes that cover, for example, multiple subnets based on different underlying network technologies, Admin-Local scope (scop value 4) or Site-Local scope (scop value 5) SHOULD be used.

An MPL Forwarder MAY participate in additional MPL Domains identified by other multicast addresses. An MPL Interface MUST subscribe to the MPL Domain Addresses for the MPL Domains that it participates in. The assignment of other multicast addresses is out of scope.

For each MPL Domain Address that an MPL Interface subscribes to, the MPL Interface MUST also subscribe to the same MPL Domain Address with a scope value of 2 (link-local) when reactive forwarding is in use (i.e. when communicating MPL Control Messages).





#### **4.2. Information Base Overview**

A node records necessary protocol state in the following information sets:

- o The Local Interface Set records the set of local MPL Interfaces and the unicast addresses assigned to those MPL Interfaces.
- o The Domain Set records the set of MPL Domain Addresses and the local MPL Interfaces that subscribe to those addresses.
- o A Seed Set records information about received MPL Data Messages received from an MPL Seed within an MPL Domain. Each MPL Domain has an associated Seed Set. A Seed Set maintains the minimum sequence number for MPL Data Messages that the MPL Forwarder is willing to receive or has buffered in its Buffered Message Set from an MPL Seed. MPL uses Seed Sets and Buffered Message Sets to determine when to accept an MPL Data Message, process its payload, and retransmit it.
- o A Buffered Message Set records recently received MPL Data Messages from an MPL Seed within an MPL Domain. Each MPL Domain has an associated Buffered Message Set. MPL Data Messages resident in a Buffered Message Set have sequence numbers that are greater than or equal to the minimum threshold maintained in the corresponding Seed Set. MPL uses Buffered Message Sets to store MPL Data Messages that may be transmitted by the MPL Forwarder for forwarding.

#### **4.3. Protocol Overview**

MPL achieves its goal by implementing a controlled flood that attempts to disseminate the multicast data message to all interfaces within an MPL Domain. MPL performs the following tasks to disseminate a multicast message:

- o When having a multicast message to forward into an MPL Domain, the MPL Seed generates an MPL Data Message that includes the MPL Domain Address as the IPv6 Destination Address, the MPL Seed Identifier, a newly generated sequence number, and the multicast message. If the multicast destination address is not the MPL Domain Address, IP-in-IP [[RFC2473](#)] is used to encapsulate the multicast message in an MPL Data Message, preserving the original IPv6 Destination Address.
- o Upon receiving an MPL Data Message, the MPL Forwarder extracts the MPL Seed and sequence number and determines whether or not the MPL



Data Message was previously received using the MPL Domain's Seed Set and Buffered Message Set.

- \* If the sequence number is less than the lower-bound sequence number maintained in the Seed Set or a message with the same sequence number exists within the Buffered Message Set, the MPL Forwarder marks the MPL Data Message as old.
  - \* Otherwise, the MPL Forwarder marks the MPL Data Message as new.
- o For each newly received MPL Data Message, an MPL Forwarder updates the Seed Set, adds the MPL Data Message into the Buffered Message Set, processes its payload, and multicasts the MPL Data Message a number of times on all MPL Interfaces participating in the same MPL Domain to forward the message.
  - o Each MPL Forwarder may periodically link-local multicast MPL Control Messages on MPL Interfaces to communicate information contained in an MPL Domain's Seed Set and Buffered Message Set.
  - o Upon receiving an MPL Control Message, an MPL Forwarder determines whether there are any new MPL Data Messages that have yet to be received by the MPL Control Message's source and multicasts those MPL Data Messages.

MPL's configuration parameters allow two forwarding strategies for disseminating MPL Data Messages via MPL Interfaces.

**Proactive Forwarding** - With proactive forwarding, an MPL Forwarder schedules transmissions of MPL Data Messages using the Trickle algorithm, without any prior indication that neighboring nodes have yet to receive the message. After transmitting the MPL Data Message a limited number of times, the MPL Forwarder may terminate proactive forwarding for the MPL Data Message.

**Reactive Forwarding** - With reactive forwarding, an MPL Forwarder link-local multicasts MPL Control Messages using the Trickle algorithm [[RFC6206](#)]. MPL Forwarders use MPL Control Messages to discover new MPL Data Messages that have not yet been received. When discovering that a neighboring MPL Forwarder has not yet received an MPL Data Message, the MPL Forwarder schedules those MPL Data Messages for transmission using the Trickle algorithm.

Note that the use of proactive and reactive forwarding strategies within the same MPL Domain are not mutually exclusive and may be used simultaneously. For example, upon receiving a new MPL Data Message when both proactive and reactive forwarding techniques are enabled, an MPL Forwarder will proactively retransmit the MPL Data Message a



limited number of times and schedule further transmissions upon receiving MPL Control Messages.

#### **4.4. Signaling Overview**

MPL generates and processes the following messages:

MPL Data Message - Generated by an MPL Seed to deliver a multicast message across an MPL Domain. The MPL Data Message's source is an address in the Local Interface Set of the MPL Seed that generated the message and is valid within the MPL Domain. The MPL Data Message's destination is the MPL Domain Address corresponding to the MPL Domain. An MPL Data Message contains:

- \* The Seed Identifier of the MPL Seed that generated the MPL Data Message.
- \* The sequence number of the MPL Seed that generated the MPL Data Message.
- \* The original multicast message.

MPL Control Message - Generated by an MPL Forwarder to communicate information contained in an MPL Domain's Seed Set and Buffered Message Set to neighboring MPL Forwarders. An MPL Control Message contains a list of tuples for each entry in the Seed Set. Each tuple contains:

- \* The minimum sequence number maintained in the Seed Set for the MPL Seed.
- \* A bit-vector indicating the sequence numbers of MPL Data Messages resident in the Buffered Message Set for the MPL Seed, where the first bit represents a sequence number equal to the minimum threshold maintained in the Seed Set.
- \* The length of the bit-vector.

### **5. MPL Parameters and Constants**

This section describes various program and networking parameters and constants used by MPL.

#### **5.1. MPL Multicast Addresses**

MPL makes use of MPL Domain Addresses to identify MPL Interfaces of an MPL Domain. By default, MPL Forwarders subscribe to the



ALL\_MPL\_FORWARDERS multicast address with a scope value of 3 [[I-D.ietf-6man-multicast-scopes](#)].

For each MPL Domain Address that an MPL Interface subscribes to, the MPL Interface MUST also subscribe to the MPL Domain Address with a scope value of 2 (link-local) when reactive forwarding is in use. MPL Forwarders use the link-scoped MPL Domain Address to communicate MPL Control Messages to neighboring (i.e. on-link) MPL Forwarders.

## 5.2. MPL Message Types

MPL defines an IPv6 Option for carrying an MPL Seed Identifier and a sequence number within an MPL Data Message. The IPv6 Option Type has value 0x6D.

MPL defines an ICMPv6 Message (MPL Control Message) for communicating information contained in an MPL Domain's Seed Set and Buffered Message Set to neighboring MPL Forwarders. The MPL Control Message has ICMPv6 Type MPL\_ICMP\_TYPE.

## 5.3. MPL Seed Identifiers

MPL uses MPL Seed Identifiers to uniquely identify MPL Seeds within an MPL Domain. For each MPL Domain that the MPL Forwarder serves as an MPL Seed, the MPL Forwarder MUST have an associated MPL Seed Identifier. An MPL Forwarder MAY use the same MPL Seed Identifier across multiple MPL Domains, but the MPL Seed Identifier MUST be unique within each MPL Domain. The mechanism for assigning and verifying uniqueness of MPL Seed Identifiers is not specified in this document.

## 5.4. MPL Parameters

**PROACTIVE\_FORWARDING** A boolean value that indicates whether the MPL Forwarder schedules MPL Data Message transmissions after receiving them for the first time. PROACTIVE\_FORWARDING has a default value of TRUE. The mechanism for setting PROACTIVE\_FORWARDING is not specified within this document.

**SEED\_SET\_ENTRY\_LIFETIME** The minimum lifetime for an entry in the Seed Set. SEED\_SET\_ENTRY\_LIFETIME has a default value of 30 minutes. It is RECOMMENDED that all MPL Forwarders use the same value for SEED\_SET\_ENTRY\_LIFETIME for a given MPL Domain and use a default value of 30 minutes. The mechanism for setting SEED\_SET\_ENTRY\_LIFETIME is not specified within this document.

As specified in [[RFC6206](#)], a Trickle timer runs for a defined interval and has three configuration parameters: the minimum interval





size  $I_{min}$ , the maximum interval size  $I_{max}$ , and a redundancy constant  $k$ .

This specification defines a fourth Trickle configuration parameter, `TimerExpirations`, which indicates the number of Trickle timer expiration events that occur before terminating the Trickle algorithm for a given MPL Data Message or MPL Control Message.

Each MPL Interface uses the following Trickle parameters for MPL Data Message and MPL Control Message transmissions.

`DATA_MESSAGE_IMIN` The minimum Trickle timer interval, as defined in [\[RFC6206\]](#), for MPL Data Message transmissions. `DATA_MESSAGE_IMIN` has a default value of 10 times the expected link-layer latency.

`DATA_MESSAGE_IMAX` The maximum Trickle timer interval, as defined in [\[RFC6206\]](#), for MPL Data Message transmissions. `DATA_MESSAGE_IMAX` has a default value equal to `DATA_MESSAGE_IMIN`.

`DATA_MESSAGE_K` The redundancy constant, as defined in [\[RFC6206\]](#), for MPL Data Message transmissions. `DATA_MESSAGE_K` has a default value of 1.

`DATA_MESSAGE_TIMER_EXPIRATIONS` The number of Trickle timer expirations that occur before terminating the Trickle algorithm's retransmission of a given MPL Data Message. `DATA_MESSAGE_TIMER_EXPIRATIONS` has a default value of 3.

`CONTROL_MESSAGE_IMIN` The minimum Trickle timer interval, as defined in [\[RFC6206\]](#), for MPL Control Message transmissions. `CONTROL_MESSAGE_IMIN` has a default value of 10 times the worst-case link-layer latency.

`CONTROL_MESSAGE_IMAX` The maximum Trickle timer interval, as defined in [\[RFC6206\]](#), for MPL Control Message transmissions. `CONTROL_MESSAGE_IMAX` has a default value of 5 minutes.

`CONTROL_MESSAGE_K` The redundancy constant, as defined in [\[RFC6206\]](#), for MPL Control Message transmissions. `CONTROL_MESSAGE_K` has a default value of 1.

`CONTROL_MESSAGE_TIMER_EXPIRATIONS` The number of Trickle timer expirations that occur before terminating the Trickle algorithm for MPL Control Message transmissions. `CONTROL_MESSAGE_TIMER_EXPIRATIONS` has a default value of 10.

As described in [\[RFC6206\]](#), if different nodes have different configuration parameters, Trickle may have unintended behaviors.



Therefore, it is RECOMMENDED that all MPL Interfaces attached to the same link of a given MPL Domain use the same values for the Trickle Parameters above for a given MPL Domain. The mechanism for setting the Trickle Parameters is not specified within this document.

The default MPL parameters specify a forwarding strategy that utilizes both proactive and reactive techniques. Using these default values, an MPL Forwarder proactively transmits any new MPL Data Messages it receives then uses MPL Control Messages to trigger additional MPL Data Message retransmissions where message drops are detected. Setting DATA\_MESSAGE\_IMAX to the same as DATA\_MESSAGE\_IMIN in this case is acceptable since subsequent MPL Data Message retransmissions are triggered by MPL Control Messages, where CONTROL\_MESSAGE\_IMAX is greater than CONTROL\_MESSAGE\_IMIN.

## 6. Protocol Message Formats

The protocol messages generated and processed by an MPL Forwarder are described in this section.

### 6.1. MPL Option

The MPL Option is carried in MPL Data Messages in an IPv6 Hop-by-Hop Options header, immediately following the IPv6 header. The MPL Option has the following format:

```

0                                     1                                     2                                     3
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
                                     +-+-+-+-+-+-+-+-+
                                     | Option Type | Opt Data Len |
+-+-+-+-+-+-+-+-+
| S |M|V|  rsv  |  sequence  |      seed-id (optional)      |
+-+-+-+-+-+-+-+-+

```

```
Option Type      0x6D.
```

Opt Data Len	Length of the Option Data field in octets.
--------------	--

S                    2-bit unsigned integer. Identifies the length of seed-id. 0 indicates that the seed-id is the IPv6 Source Address and not included in the MPL Option. 1 indicates that the seed-id is a 16-bit unsigned integer. 2 indicates that the seed-id is a 64-bit unsigned integer. 3 indicates that the seed-id is a 128-bit unsigned integer.



M	1-bit flag. 1 indicates that the value in sequence is known to be the largest sequence number that was received from the MPL Seed.
V	1-bit flag. 0 indicates that the MPL Option conforms to this specification. MPL Data Messages with an MPL Option in which this flag is 1 MUST be dropped.
rsv	4-bit reserved field. MUST be set to 0 on transmission and ignored on reception.
sequence	8-bit unsigned integer. Identifies relative ordering of MPL Data Messages from the MPL Seed identified by seed-id.
seed-id	Uniquely identifies the MPL Seed that initiated dissemination of the MPL Data Message. The size of seed-id is indicated by the S field.

The Option Data (in particular the M flag) of the MPL Option is updated by MPL Forwarders as the MPL Data Message is forwarded. Nodes that do not understand the MPL Option MUST discard the MPL Data Message. Thus, according to [\[RFC2460\]](#) the three high order bits of the Option Type are set to '011'. The Option Data length is variable.

The seed-id uniquely identifies an MPL Seed. When seed-id is 128 bits (S=3), the MPL seed MAY use an IPv6 address assigned to one of its interfaces that is unique within the MPL Domain. Managing MPL Seed Identifiers is not within scope of this document.

The sequence field establishes a total ordering of MPL Data Messages generated by an MPL Seed for an MPL Domain. The MPL Seed MUST increment the sequence field's value on each new MPL Data Message that it generates for an MPL Domain. Implementations MUST follow the Serial Number Arithmetic as defined in [\[RFC1982\]](#) when incrementing a sequence value or comparing two sequence values.

Future updates to this specification may define additional fields following the seed-id field.

## [6.2.](#) MPL Control Message

An MPL Forwarder uses ICMPv6 messages to communicate information contained in an MPL Domain's Seed Set and Buffered Message Set to neighboring MPL Forwarders. The MPL Control Message has the following format:













AddressSet - a set of unicast addresses assigned to the MPL Interface.

### **7.2. Domain Set**

The Domain Set records the MPL Interfaces that subscribe to each MPL Domain Address. The Domain Set consists of MPL Domain Tuples, one per MPL Domain: (MPLInterfaceSet).

MPLInterfaceSet - a set of MPL Interfaces that subscribe to the MPL Domain Address that identifies the MPL Domain.

### **7.3. Seed Set**

A Seed Set records a sliding window used to determine the sequence numbers of MPL Data Messages that an MPL Forwarder is willing to accept generated by the MPL Seed. An MPL Forwarder maintains a Seed Set for each MPL Domain that it participates in. A Seed Set consists of MPL Seed Tuples: (SeedID, MinSequence, Lifetime).

SeedID - the identifier for the MPL Seed.

MinSequence - a lower-bound sequence number that represents the sequence number of the oldest MPL Data Message the MPL Forwarder is willing to receive or transmit. An MPL Forwarder MUST ignore any MPL Data Message that has sequence value less than than MinSequence.

Lifetime - indicates the minimum remaining lifetime of the Seed Set entry. An MPL Forwarder MUST NOT free a Seed Set entry before the remaining lifetime expires.

### **7.4. Buffered Message Set**

A Buffered Message Set records recently received MPL Data Messages from an MPL Seed within an MPL Domain. An MPL Forwarder uses a Buffered Message Set to buffer MPL Data Messages while the MPL Forwarder is forwarding the MPL Data Messages. An MPL Forwarder maintains a Buffered Message Set for each MPL Domain that it participates in. A Buffered Message Set consists of Buffered Message Tuples: (SeedID, SequenceNumber, DataMessage).

SeedID - the identifier for the MPL Seed that generated the MPL Data Message.

SequenceNumber - the sequence number for the MPL Data Message.

DataMessage - the MPL Data Message.



All MPL Data Messages within a Buffered Message Set MUST have a sequence number greater than or equal to MinSequence for the corresponding SeedID. When increasing MinSequence for an MPL Seed, the MPL Forwarder MUST delete any MPL Data Messages from the corresponding Buffered Message Set that have sequence numbers less than MinSequence.

## **8. MPL Seed Sequence Numbers**

Each MPL Seed maintains a sequence number for each MPL Domain that it serves. The sequence numbers are included in MPL Data Messages generated by the MPL Seed. The MPL Seed MUST increment the sequence number for each MPL Data Message that it generates for an MPL Domain. Implementations MUST follow the Serial Number Arithmetic as defined in [[RFC1982](#)] when incrementing a sequence value or comparing two sequence values. This sequence number is used to establish a total ordering of MPL Data Messages generated by an MPL Seed for an MPL Domain.

## **9. MPL Data Messages**

### **9.1. MPL Data Message Generation**

MPL Data Messages are generated by MPL Seeds when these messages enter the MPL Domain. All MPL Data messages have the following properties:

- o The IPv6 Source Address MUST be an address in the AddressSet of a corresponding MPL Interface and MUST be valid within the MPL Domain.
- o The IPv6 Destination Address MUST be set to the MPL Domain Address corresponding to the MPL Domain.
- o An MPL Data Message MUST contain an MPL Option in its IPv6 Header to identify the MPL Seed that generated the message and the ordering relative to other MPL Data Messages generated by the MPL Seed.

When the destination address is an MPL Domain Address and the source address is in the AddressList of an MPL Interface that belongs to that MPL Domain Address, the application message and the MPL Data Message MAY be identical. In other words, the MPL Data Message may contain a single IPv6 header that includes the MPL Option.

Otherwise, IPv6-in-IPv6 encapsulation MUST be used to satisfy the MPL Data Message requirements listed above [[RFC2473](#)]. The complete IPv6-in-IPv6 message forms an MPL Data Message. The outer IPv6 header



conforms to the MPL Data Message requirements listed above. The encapsulated IPv6 datagram encodes the multicast data message that is communicated beyond the MPL Domain.

## 9.2. MPL Data Message Transmission

An MPL Forwarder manages transmission of MPL Data Messages in its Buffered Message Sets using the Trickle algorithm [RFC6206]. An MPL Forwarder MUST use a separate Trickle timer for each MPL Data Message that it is actively forwarding. In accordance with Section 5 of RFC 6206 [RFC6206], this document defines the following:

- o This document defines a "consistent" transmission as receiving an MPL Data Message that has the same MPL Domain Address, seed-id, and sequence value as the MPL Data Message managed by the Trickle timer.
- o This document defines an "inconsistent" transmission as receiving an MPL Data Message that has the same MPL Domain Address, seed-id value, and the M flag set, but has a sequence value less than MPL Data Message managed by the Trickle timer.
- o This document does not define any external "events".
- o This document defines MPL Data Messages as Trickle messages.
- o The actions outside the Trickle algorithm that the protocol takes involve managing the MPL Domain's Seed Set and Buffered Message Set.

As specified in [RFC6206], a Trickle timer has three variables: the current interval size *I*, a time within the current interval *t*, and a counter *c*. MPL defines a fourth variable, *e*, which counts the number of Trickle timer expiration events since the Trickle timer was last reset.

After DATA\_MESSAGE\_TIMER\_EXPIRATIONS Trickle timer events, the MPL Forwarder MUST disable the Trickle timer. When a buffered MPL Data Message does not have an associated Trickle timer, the MPL Forwarder MAY delete the message from the Buffered Message Set by advancing MinSequence of the corresponding MPL Seed in the Seed Set. When the MPL Forwarder no longer buffers any messages for an MPL Seed, the MPL Forwarder MUST NOT increment MinSequence for that MPL Seed.

When transmitting an MPL Data Message, the MPL Forwarder MUST either set the M flag to zero or set it to a level that indicates whether or not the message's sequence number is the largest value that has been received from the MPL Seed.





### **9.3. MPL Data Message Processing**

Upon receiving an MPL Data Message, the MPL Forwarder first processes the MPL Option and updates the Trickle timer associated with the MPL Data Message if one exists.

Upon receiving an MPL Data Message, an MPL Forwarder **MUST** perform one of the following actions:

- o Accept the message and enter the MPL Data Message in the MPL Domain's Buffered Message Set.
- o Accept the message and update the corresponding MinSequence in the MPL Domain's Seed Set to 1 greater than the message's sequence number.
- o Discard the message without any change to the MPL Information Base.

If a Seed Set entry exists for the MPL Seed, the MPL Forwarder **MUST** discard the MPL Data Message if its sequence number is less than MinSequence or exists in the Buffered Message Set.

If a Seed Set entry does not exist for the MPL Seed, the MPL Forwarder **MUST** create a new entry for the MPL Seed before accepting the MPL Data Message.

If memory is limited, an MPL Forwarder **SHOULD** reclaim memory resources by:

- o Incrementing MinSequence entries in a Seed Set and deleting MPL Data Messages in the corresponding Buffered Message Set that fall below the MinSequence value.
- o Deleting other Seed Set entries that have expired and the corresponding MPL Data Messages in the Buffered Message Set.

If the MPL Forwarder accepts the MPL Data Message, the MPL Forwarder **MUST** perform the following actions:

- o Reset the Lifetime of the corresponding Seed Set entry to SEED\_SET\_ENTRY\_LIFETIME.
- o If PROACTIVE\_FORWARDING is true, the MPL Forwarder **MUST** initialize and start a Trickle timer for the MPL Data Message.



- o If the MPL Control Message Trickle timer is not running and `CONTROL_MESSAGE_TIMER_EXPIRATIONS` is non-zero, the MPL Forwarder MUST initialize and start the MPL Control Message Trickle timer.
- o If the MPL Control Message Trickle timer is running, the MPL Forwarder MUST reset the MPL Control Message Trickle timer.

## **10. MPL Control Messages**

### **10.1. MPL Control Message Generation**

An MPL Forwarder generates MPL Control Messages to communicate an MPL Domain's Seed Set and Buffered Message Set to neighboring MPL Forwarders. Each MPL Control Message is generated according to [Section 6.2](#), with an MPL Seed Info for each entry in the MPL Domain's Seed Set. Each MPL Seed Info entry has the following content:

- o `S` set to the size of the seed-id field in the MPL Seed Info entry.
- o `min-seqno` set to `MinSequence` of the MPL Seed.
- o `bm-len` set to the size of buffered-mpl-messages in octets.
- o `seed-id` set to the MPL seed identifier.
- o buffered-mpl-messages with each bit representing whether or not an MPL Data Message with the corresponding sequence number exists in the Buffered Message Set. The  $i$ 'th bit represents a sequence number of `min-seqno + i`. '0' indicates that the corresponding MPL Data Message does not exist in the Buffered Message Set. '1' indicates that the corresponding MPL Data Message does exist in the Buffered Message Set.

### **10.2. MPL Control Message Transmission**

An MPL Forwarder transmits MPL Control Messages using the Trickle algorithm. An MPL Forwarder maintains a single Trickle timer for each MPL Domain. When `CONTROL_MESSAGE_TIMER_EXPIRATIONS` is 0, the MPL Forwarder does not execute the Trickle algorithm and does not transmit MPL Control Messages. In accordance with Section 5 of [RFC 6206](#) [RFC6206], this document defines the following:

- o This document defines a "consistent" transmission as receiving an MPL Control Message that results in a determination that neither the receiving nor transmitting node has any new MPL Data Messages to offer.



- o This document defines an "inconsistent" transmission as receiving an MPL Control Message that results in a determination that either the receiving or transmitting node has at least one new MPL Data Message to offer.
- o The Trickle timer is reset in response to external "events." This document defines an "event" as increasing MinSequence of any entry in the corresponding Seed Set or adding a message to the corresponding Buffered Message Set.
- o This document defines an MPL Control Message as a Trickle message.

As specified in [[RFC6206](#)], a Trickle timer has three variables: the current interval size  $I$ , a time within the current interval  $t$ , and a counter  $c$ . MPL defines a fourth variable,  $e$ , which counts the number of Trickle timer expiration events since the Trickle timer was last reset. After CONTROL\_MESSAGE\_TIMER\_EXPIRATIONS Trickle timer events, the MPL Forwarder MUST disable the Trickle timer.

### **10.3. MPL Control Message Processing**

An MPL Forwarder processes each MPL Control Message that it receives to determine if it has any new MPL Data Messages to receive or offer.

An MPL Forwarder determines if a new MPL Data Message has not been received from a neighboring node if any of the following conditions hold true:

- o The MPL Control Message includes an MPL Seed that does not exist in the MPL Domain's Seed Set.
- o The MPL Control Message indicates that the neighbor has an MPL Data Message in its Buffered Message Set with sequence number greater than MinSequence (i.e. the  $i$ -th bit is set to 1 and  $\text{min-seqno} + i > \text{MinSequence}$ ) and is not included in the MPL Domain's Buffered Message Set.

When an MPL Forwarder determines that it has not yet received an MPL Data Message buffered by a neighboring device, the MPL Forwarder MUST reset its Trickle timer associated with MPL Control Message transmissions. If an MPL Control Message Trickle timer is not running, the MPL Forwarder MUST initialize and start a new Trickle timer.

An MPL Forwarder determines if an MPL Data Message in the Buffered Message Set has not yet been received by a neighboring MPL Forwarder if any of the following conditions hold true:



- o The MPL Control Message does not include an MPL Seed for the MPL Data Message.
- o The MPL Data Message's sequence number is greater than or equal to min-seqno and not included in the neighbor's corresponding Buffered Message Set (i.e. the MPL Data Message's sequence number does not have a corresponding bit in buffered-mpl-messages set to 1).

When an MPL Forwarder determines that it has at least one MPL Data Message in its corresponding Buffered Message Set that has not yet been received by a neighbor, the MPL Forwarder MUST reset the MPL Control Message Trickle timer. Additionally, for each of those entries in the Buffered Message Set, the MPL Forwarder MUST reset the Trickle timer and reset *e* to 0. If a Trickle timer is not associated with the MPL Data Message, the MPL Forwarder MUST initialize and start a new Trickle timer.

## **11. Acknowledgements**

The authors would like to acknowledge the helpful comments of Robert Cragie, Esko Dijk, Ralph Droms, Paul Duffy, Adrian Farrel, Ulrich Herberg, Owen Kirby, Kerry Lynn, Joseph Reddy, Michael Richardson, Ines Robles, Don Sturek, Dario Tedeschi, and Peter van der Stok, which greatly improved the document.

## **12. IANA Considerations**

This document defines one IPv6 Option, a type that must be allocated from the IPv6 "Destination Options and Hop-by-Hop Options" registry of [[RFC2780](#)].

This document defines one ICMPv6 Message, a type that must be allocated from the "ICMPv6 "type" Numbers" registry of [[RFC4443](#)].

This document registers a well-known multicast address from the Variable Scope Multicast Address registry.

### **12.1. MPL Option Type**

IANA is requested to allocate an IPv6 Option Type from the IPv6 "Destination Options and Hop-by-Hop Options" registry of [[RFC2780](#)], as specified in Table 1 below:





Hex Value	act	chg	rest	Description	Reference
0x6D	01	1	01101	MPL Option	This Document

Table 1: IPv6 Option Type Allocation

## 12.2. MPL ICMPv6 Type

IANA is requested to allocate an ICMPv6 Type from the "ICMPv6 "type" Numbers" registry of [\[RFC4443\]](#), as specified in Table 2 below:

Type	Name	Reference
TBD	MPL Control Message	This Document

Table 2: IPv6 Option Type Allocation

In this document, the mnemonic MPL\_ICMP\_TYPE was used to refer to the ICMPv6 Type above, which is TBD by IANA.

## 12.3. Well-known Multicast Addresses

IANA is requested to allocate an IPv6 multicast address, with Group ID in the range [0x01,0xFF] for 6LoWPAN compression [\[RFC6282\]](#), "ALL\_MPL\_FORWARDERS" from the "Variable Scope Multicast Addresses" sub-registry of the "IPv6 Multicast Address Space" registry [\[RFC3307\]](#) as specified in Table 3 below:

Address(s)	Description	Reference	Date
			Registered
FF0X:0:0:0:0:0:0:FC	ALL_MPL_FORWARDERS	This Document	2013-04-10

Table 3: Variable Scope Multicast Address Allocation

## 13. Security Considerations

MPL uses sequence numbers to maintain a total ordering of MPL Data Messages from an MPL Seed. The use of sequence numbers allows a denial-of-service attack where an attacker can spoof a message with a sufficiently large sequence number to: (i) flush messages from the



Buffered Message List and (ii) increase the MinSequence value for an MPL Seed in the corresponding Seed Set. The former side effect allows an attacker to halt the forwarding process of any MPL Data Messages being disseminated. The latter side effect allows an attacker to prevent MPL Forwarders from accepting new MPL Data Messages that an MPL Seed generates while the sequence number is less than MinSequence.

More generally, the basic ability to inject messages into a Low-power and Lossy Network can be used as a denial-of-service attack regardless of what forwarding protocol is used. For these reasons, Low-power and Lossy Networks typically employ link-layer security mechanisms to disable an attacker's ability to inject messages.

To prevent attackers from injecting packets through an MPL Forwarder, the MPL Forwarder MUST NOT accept or forward MPL Data Messages from a communication interface that does not subscribe to the MPL Domain Address identified in message's destination address.

MPL uses the Trickle algorithm to manage message transmissions and the security considerations described in [\[RFC6206\]](#) apply.

## **14. References**

### **14.1. Normative References**

- [I-D.ietf-6man-multicast-scopes] Droms, R., "IPv6 Multicast Address Scopes", [draft-ietf-6man-multicast-scopes-04](#) (work in progress), March 2014.
- [RFC1982] Elz, R. and R. Bush, "Serial Number Arithmetic", [RFC 1982](#), August 1996.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2460] Deering, S. and R. Hinden, "Internet Protocol, Version 6 (IPv6) Specification", [RFC 2460](#), December 1998.
- [RFC2473] Conta, A. and S. Deering, "Generic Packet Tunneling in IPv6 Specification", [RFC 2473](#), December 1998.
- [RFC2780] Bradner, S. and V. Paxson, "IANA Allocation Guidelines For Values In the Internet Protocol and Related Headers", [BCP 37](#), [RFC 2780](#), March 2000.
- [RFC3307] Haberman, B., "Allocation Guidelines for IPv6 Multicast Addresses", [RFC 3307](#), August 2002.



- [RFC4007] Deering, S., Haberman, B., Jinmei, T., Nordmark, E., and B. Zill, "IPv6 Scoped Address Architecture", [RFC 4007](#), March 2005.
- [RFC4443] Conta, A., Deering, S., and M. Gupta, "Internet Control Message Protocol (ICMPv6) for the Internet Protocol Version 6 (IPv6) Specification", [RFC 4443](#), March 2006.
- [RFC6206] Levis, P., Clausen, T., Hui, J., Gnawali, O., and J. Ko, "The Trickle Algorithm", [RFC 6206](#), March 2011.
- [RFC6282] Hui, J. and P. Thubert, "Compression Format for IPv6 Datagrams over IEEE 802.15.4-Based Networks", [RFC 6282](#), September 2011.
- [RFC6550] Winter, T., Thubert, P., Brandt, A., Hui, J., Kelsey, R., Levis, P., Pister, K., Struik, R., Vasseur, JP., and R. Alexander, "RPL: IPv6 Routing Protocol for Low-Power and Lossy Networks", [RFC 6550](#), March 2012.

#### **[14.2.](#) Informative References**

- [RFC3973] Adams, A., Nicholas, J., and W. Siadak, "Protocol Independent Multicast - Dense Mode (PIM-DM): Protocol Specification (Revised)", [RFC 3973](#), January 2005.
- [RFC4601] Fenner, B., Handley, M., Holbrook, H., and I. Kouvelas, "Protocol Independent Multicast - Sparse Mode (PIM-SM): Protocol Specification (Revised)", [RFC 4601](#), August 2006.

#### **Authors' Addresses**

Jonathan W. Hui  
Cisco  
170 West Tasman Drive  
San Jose, California 95134  
USA

Phone: +408 424 1547  
Email: [jonhui@cisco.com](mailto:jonhui@cisco.com)



Richard Kelsey  
Silicon Labs  
25 Thomson Place  
Boston, Massachusetts 02210  
USA

Phone: +617 951 1225

Email: [richard.kelsey@silabs.com](mailto:richard.kelsey@silabs.com)