

RTCWEB Working Group  
Internet-Draft  
Intended status: Informational  
Expires: June 22, 2013

C. Holmberg  
S. Hakansson  
G. Eriksson  
Ericsson  
December 19, 2012

**Web Real-Time Communication Use-cases and Requirements**  
**draft-ietf-rtcweb-use-cases-and-requirements-10.txt**

Abstract

This document describes web based real-time communication use-cases. Based on the use-cases, the document also derives requirements related to the browser, and the API used by web applications to request and control media stream and data exchange services provided by the browser.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on June 22, 2013.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as

described in the Simplified BSD License.

## Table of Contents

|                         |   |                    |
|-------------------------|---|--------------------|
| <a href="#">1.</a>      | Introduction . . . . .  | <a href="#">4</a>  |
| <a href="#">2.</a>      | Conventions . . . . .   | <a href="#">4</a>  |
| <a href="#">3.</a>      | Definitions . . . . .   | <a href="#">4</a>  |
| <a href="#">4.</a>      | Use-cases . . . . .   | <a href="#">4</a>  |
| <a href="#">4.1.</a>    | Introduction . . . . .  | <a href="#">4</a>  |
| <a href="#">4.2.</a>    | Browser-to-browser use-cases . . . . .                                      | <a href="#">5</a>  |
| <a href="#">4.2.1.</a>  | Simple Video Communication Service . . . . .                                | <a href="#">5</a>  |
| <a href="#">4.2.2.</a>  | Simple Video Communication Service, NAT/FW that<br>blocks UDP . . . . .     | <a href="#">6</a>  |
| <a href="#">4.2.3.</a>  | Simple Video Communication Service, FW that only<br>allows http . . . . .   | <a href="#">6</a>  |
| <a href="#">4.2.4.</a>  | Simple Video Communication Service, global service<br>provider . . . . .    | <a href="#">6</a>  |
| <a href="#">4.2.5.</a>  | Simple Video Communication Service, enterprise<br>aspects . . . . .         | <a href="#">7</a>  |
| <a href="#">4.2.6.</a>  | Simple Video Communication Service, access change . .                       | <a href="#">8</a>  |
| <a href="#">4.2.7.</a>  | Simple Video Communication Service, QoS . . . . .                           | <a href="#">8</a>  |
| <a href="#">4.2.8.</a>  | Simple Video Communication Service with sharing . . .                       | <a href="#">9</a>  |
| <a href="#">4.2.9.</a>  | Simple Video Communication Service with file<br>exchange . . . . .          | <a href="#">9</a>  |
| <a href="#">4.2.10.</a> | Simple video communication service with<br>inter-operator calling . . . . . | <a href="#">9</a>  |
| <a href="#">4.2.11.</a> | Hockey Game Viewer . . . . .  | <a href="#">10</a> |
| <a href="#">4.2.12.</a> | Multiparty video communication . . . . .                                    | <a href="#">11</a> |
| <a href="#">4.2.13.</a> | Multiparty on-line game with voice communication . . .                      | <a href="#">12</a> |
| <a href="#">4.2.14.</a> | Distributed Music Band . . . . .  | <a href="#">12</a> |
| <a href="#">4.3.</a>    | Browser - GW/Server use cases . . . . .                                     | <a href="#">13</a> |
| <a href="#">4.3.1.</a>  | Telephony terminal . . . . .  | <a href="#">13</a> |
| <a href="#">4.3.2.</a>  | Fedex Call . . . . .  | <a href="#">14</a> |
| <a href="#">4.3.3.</a>  | Video conferencing system with central server . . . .                       | <a href="#">14</a> |
| <a href="#">5.</a>      | Requirements . . . . .  | <a href="#">15</a> |
| <a href="#">5.1.</a>    | General . . . . .   | <a href="#">15</a> |
| <a href="#">5.2.</a>    | Browser requirements . . . . .  | <a href="#">15</a> |
| <a href="#">5.3.</a>    | API requirements . . . . .  | <a href="#">19</a> |
| <a href="#">6.</a>      | IANA Considerations . . . . .   | <a href="#">21</a> |
| <a href="#">7.</a>      | Security Considerations . . . . .   | <a href="#">21</a> |
| <a href="#">7.1.</a>    | Introduction . . . . .  | <a href="#">21</a> |
| <a href="#">7.2.</a>    | Browser Considerations . . . . .  | <a href="#">22</a> |
| <a href="#">7.3.</a>    | Web Application Considerations . . . . .                                    | <a href="#">22</a> |
| <a href="#">8.</a>      | Additional use-cases . . . . .  | <a href="#">22</a> |
| <a href="#">9.</a>      | Acknowledgements . . . . .  | <a href="#">23</a> |
| <a href="#">10.</a>     | Change Log . . . . .  | <a href="#">24</a> |
| <a href="#">11.</a>     | References . . . . .  | <a href="#">27</a> |



|                       |                                  |                    |
|-----------------------|----------------------------------|--------------------|
| <a href="#">11.1.</a> | Normative References . . . . .   | <a href="#">27</a> |
| <a href="#">11.2.</a> | Informative References . . . . . | <a href="#">27</a> |
| Authors'              | Addresses . . . . .              | <a href="#">27</a> |

## **1. Introduction**

This document presents a few use-cases of web applications that are executed in a browser and use real-time communication capabilities. Based on the use-cases, the document derives requirements related to the browser and the API used by web applications in the browser.

The requirements related to the browser are named "Fn" and are described in [Section 5.2](#)

The requirements related to the API are named "An" and are described in [Section 5.3](#)

The document focuses on requirements related to real-time media streams and data exchange. Requirements related to privacy, signalling between the browser and web server etc. are currently not considered.

## **2. Conventions**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#), [RFC 2119](#) [[RFC2119](#)].

## **3. Definitions**

TBD

## **4. Use-cases**

### **4.1. Introduction**

This section describes web based real-time communication use-cases, from which requirements are derived.

The following considerations are applicable to all use cases:

- o Clients can be on IPv4-only
- o Clients can be on IPv6-only
- o Clients can be on dual-stack
- o Clients can be on wideband (10s of Mbits/sec)
- o Clients can be on narrowband (10s to 100s of Kbits/sec)
- o Clients can be on variable-media-quality networks (wireless)



- o Clients can be on congested networks
- o Clients can be on firewalled networks with no UDP allowed
- o Clients can be on networks with any type (as described in [RFC4787](#)) of NAT.

## **[4.2.](#) Browser-to-browser use-cases**

### **[4.2.1.](#) Simple Video Communication Service**

#### **[4.2.1.1.](#) Description**

Two or more users have loaded a video communication web application into their browsers, provided by the same service provider, and logged into the service it provides. The web service publishes information about user login status by pushing updates to the web application in the browsers. When one online user selects a peer online user, a 1-1 audiovisual communication session between the browsers of the two peers is initiated. The invited user might accept or reject the session.

During session establishment a self-view is displayed, and once the session has been established the video sent from the remote peer is displayed in addition to the self-view. During the session, each user can select to remove and re-insert the self-view as often as desired. Each user can also change the sizes of his/her two video displays during the session. Each user can also pause sending of media (audio, video, or both) and mute incoming media

It is essential that the communication cannot be wiretapped [[RFC2804](#)].

The users are provided with means that allow them to (through a separate, trusted communication channel) verify that the media origins from the other user and has not been manipulated.

The user's browsers will reject all incoming media that has been created, injected or in any way modified by any entity not trusted by the service provider.

The application gives the users the opportunity to stop it from exposing the IP address to the application of the other user.

Any session participant can end the session at any time.

The two users may be using communication devices of different makes, with different operating systems and browsers from different vendors.

One user has an unreliable Internet connection. It sometimes loses





packets, and sometimes goes down completely.

One user is located behind a Network Address Translator (NAT).

The web service monitors the quality of the service (focus on quality of audio and video) the end-users experience.

#### **4.2.1.2. Derived Requirements**

F1, F2, F3, F4, F5, F6, F8, F9, F10, F20, F25, F28, F35, F36, F38

A1, A2, A3, A4, A5, A6, A7, A8, A9, A10, A11, A12, A25, A26

#### **4.2.2. Simple Video Communication Service, NAT/FW that blocks UDP**

##### **4.2.2.1. Description**

This use-case is almost identical to the Simple Video Communication Service use-case ([Section 4.2.1](#)). The difference is that one of the users is behind a NAT that blocks UDP traffic.

##### **4.2.2.2. Derived Requirements**

F1, F2, F3, F4, F5, F6, F8, F9, F10, F20, F25, F28, F29

A1, A2, A3, A4, A5, A6, A7, A8, A9, A10, A11, A12

#### **4.2.3. Simple Video Communication Service, FW that only allows http**

##### **4.2.3.1. Description**

This use-case is almost identical to the Simple Video Communication Service use-case ([Section 4.2.1](#)). The difference is that one of the users is behind a FW that only allows http traffic.

Note: What about WS? Could it be a viable back-off mechanism?

##### **4.2.3.2. Derived Requirements**

F1, F2, F3, F4, F5, F6, F8, F9, F10, F20, F25, F28, F37

A1, A2, A3, A4, A5, A6, A7, A8, A9, A10, A11, A12

#### **4.2.4. Simple Video Communication Service, global service provider**



#### **4.2.4.1. Description**

This use-case is almost identical to the Simple Video Communication Service use-case ([Section 4.2.1](#)).

What is added is that the service provider is operating over large geographical areas (or even globally).

Assuming that ICE will be used, this means that the service provider would like to be able to provide several STUN and TURN servers (via the app) to the browser; selection of which one(s) to use is part of the ICE processing. Other reasons for wanting to provide several STUN and TURN servers include support for IPv4 and IPv6, load balancing and redundancy.

#### **4.2.4.2. Derived Requirements**

F1, F2, F3, F4, F5, F6, F8, F9, F10, F20, F25, F28, F31

A1, A2, A3, A4, A5, A6, A7, A8, A9, A10, A11, A12, A22

#### **4.2.5. Simple Video Communication Service, enterprise aspects**

##### **4.2.5.1. Description**

This use-case is similar to the Simple Video Communication Service use-case ([Section 4.2.1](#)).

What is added is aspects when using the service in enterprises. ICE is assumed in the further description of this use-case.

An enterprise that uses a RTCWEB based web application for communication desires to audit all RTCWEB based application session used from inside the company towards any external peer. To be able to do this they deploy a TURN server that straddle the boundary between the internal network and the external.

The firewall will block all attempts to use STUN with an external destination unless they go to the enterprise auditing TURN server. In cases where employees are using RTCWEB applications provided by an external service provider they still want to have the traffic to stay inside their internal network and in addition not load the straddling TURN server, thus they deploy a STUN server allowing the RTCWEB client to determine its server reflexive address on the internal side. Thus enabling cases where peers are both on the internal side to connect without the traffic leaving the internal network. It must be possible to configure the browsers used in the enterprise with network specific STUN and TURN servers. This should be possible to



achieve by autoconfiguration methods. The RTCWEB functionality will need to utilize both network specific STUN and TURN resources and STUN and TURN servers provisioned by the web application.

#### **4.2.5.2. Derived Requirements**

F1, F2, F3, F4, F5, F6, F8, F9, F10, F20, F25, F28, F32

A1, A2, A3, A4, A5, A6, A7, A8, A9, A10, A11, A12

#### **4.2.6. Simple Video Communication Service, access change**

##### **4.2.6.1. Description**

This use-case is almost identical to the Simple Video Communication Service use-case ([Section 4.2.1](#)). The difference is that the user changes network access during the session:

The communication device used by one of the users have several network adapters (Ethernet, WiFi, Cellular). The communication device is accessing the Internet using Ethernet, but the user has to start a trip during the session. The communication device automatically changes to use WiFi when the Ethernet cable is removed and then moves to cellular access to the Internet when moving out of WiFi coverage. The session continues even though the access method changes.

##### **4.2.6.2. Derived Requirements**

F1, F2, F3, F4, F5, F6, F8, F9, F10, F20, F25, F26, F28

A1, A2, A3, A4, A5, A6, A7, A8, A9, A10, A11, A12

#### **4.2.7. Simple Video Communication Service, QoS**

##### **4.2.7.1. Description**

This use-case is almost identical to the Simple Video Communication Service, access change use-case ([Section 4.2.6](#)). The use of Quality of Service (QoS) capabilities is added:

The user in the previous use case that starts a trip is behind a common residential router that supports prioritization of traffic. In addition, the user's provider of cellular access has QoS support enabled. The user is able to take advantage of the QoS support both when accessing via the residential router and when using cellular.



#### **4.2.7.2. Derived Requirements**

F1, F2, F3, F4, F5, F6, F8, F9, F10, F20, F24, F25, F26, F28

A1, A2, A3, A4, A5, A6, A7, A8, A9, A10, A11, A12

#### **4.2.8. Simple Video Communication Service with sharing**

##### **4.2.8.1. Description**

This use-case has the audio and video communication of the Simple Video Communication Service use-case ([Section 4.2.1](#)).

But in addition to this, one of the users can share what is being displayed on her/his screen with a peer. The user can choose to share the entire screen, part of the screen (part selected by the user) or what a selected application displays with the peer.

##### **4.2.8.2. Derived Requirements**

F1, F2, F3, F4, F5, F6, F8, F9, F10, F20, F25, F28, F30

A1, A2, A3, A4, A5, A6, A7, A8, A9, A10, A11, A12, A21

#### **4.2.9. Simple Video Communication Service with file exchange**

##### **4.2.9.1. Description**

This use-case has the audio and video communication of the Simple Video Communication Service use-case ([Section 4.2.1](#)).

But in addition to this, the users can send and receive files stored in the file system of the device used.

##### **4.2.9.2. Derived Requirements**

F1, F2, F3, F4, F5, F6, F8, F9, F10, F20, F25, F28, F30, F33

A1, A2, A3, A4, A5, A6, A7, A8, A9, A10, A11, A12, A21, A24

#### **4.2.10. Simple video communication service with inter-operator calling**

##### **4.2.10.1. Description**

Two users have logged into two different web applications, provided by different service providers.

The service providers are interconnected by some means, but exchange





no more information about the users than what can be carried using SIP.

NOTE: More profiling of what this means may be needed.

For each user Alice who has authorized another user Bob to receive login status information, Alice's service publishes Alice's login status information to Bob. How this authorization is defined and established is out of scope.

The same functionality as in the the Simple Video Communication Service use-case ([Section 4.2.1](#)) is available.

The same issues with connectivity apply.

#### **[4.2.10.2](#). Derived requirements**

F1, F2, F3, F4, F5, F6, F8, F9, F10, F20, F25, F27, F28

A1, A2, A3, A4, A5, A6, A7, A8, A9, A10, A11, A12, A20

#### **[4.2.11](#). Hockey Game Viewer**

##### **[4.2.11.1](#). Description**

An ice-hockey club uses an application that enables talent scouts to, in real-time, show and discuss games and players with the club manager. The talent scouts use a mobile phone with two cameras, one front facing and one rear facing.

The club manager uses a desktop, equipped with one camera, for viewing the game and discussing with the talent scout.

Before the game starts, and during game breaks, the talent scout and the manager have a 1-1 audiovisual communication session. Only the rear facing camera of the mobile phone is used. On the display of the mobile phone, the video of the club manager is shown with a picture-in-picture thumbnail of the rear facing camera (self-view). On the display of the desktop, the video of the talent scout is shown with a picture-in-picture thumbnail of the desktop camera (self-view).

When the game is on-going, the talent scout activates the use of the front facing camera, and that stream is sent to the desktop (the stream from the rear facing camera continues to be sent all the time). The video stream captured by the front facing camera (that is capturing the game) of the mobile phone is shown in a big window on the desktop screen, with picture-in-picture thumbnails of the rear



facing camera and the desktop camera (self-view). On the display of the mobile phone the game is shown (front facing camera) with picture-in-picture thumbnails of the rear facing camera (self-view) and the desktop camera. As the most important stream in this phase is the video showing the game, the application used in the talent scout's mobile sets higher priority for that stream.

It is essential that the communication cannot be wiretapped [[RFC2804](#)].

#### **4.2.11.2. Derived Requirements**

F1, F2, F3, F4, F5, F6, F8, F9, F10, F17, F20, F34

A1, A2, A3, A4, A5, A7, A8, A9, A10, A11, A12, A17, A23

#### **4.2.12. Multiparty video communication**

##### **4.2.12.1. Description**

In this use-case is the Simple Video Communication Service use-case ([Section 4.2.1](#)) is extended by allowing multiparty sessions. No central server is involved - the browser of each participant sends and receives streams to and from all other session participants. The web application in the browser of each user is responsible for setting up streams to all receivers.

In order to enhance intelligibility, the web application pans the audio from different participants differently when rendering the audio. This is done automatically, but users can change how the different participants are placed in the (virtual) room. In addition the levels in the audio signals are adjusted before mixing.

Another feature intended to enhance the use experience is that the video window that displays the video of the currently speaking peer is highlighted.

Each video stream received is by default displayed in a thumbnail frame within the browser, but users can change the display size.

It is essential that the communication cannot be wiretapped [[RFC2804](#)].

Note: What this use-case adds in terms of requirements is capabilities to send streams to and receive streams from several peers concurrently, as well as the capabilities to render the video from all received streams and be able to spatialize, level adjust and mix the audio from all received streams locally in the browser. It



also adds the capability to measure the audio level/activity.

#### **4.2.12.2. Derived Requirements**

F1, F2, F3, F4, F5, F6, F8, F9, F10, F11, F12, F13, F14, F15, F16, F17, F20, F25

A1, A2, A3, A4, A5, A6, A7, A8, A9, A10, A11, A12, A13, A14, A15, A16, A17

#### **4.2.13. Multiparty on-line game with voice communication**

##### **4.2.13.1. Description**

This use case is based on the previous one. In this use-case, the voice part of the multiparty video communication use case is used in the context of an on-line game. The received voice audio media is rendered together with game sound objects. For example, the sound of a tank moving from left to right over the screen must be rendered and played to the user together with the voice media.

Quick updates of the game state is required, and have higher priority than the voice.

It is essential that the communication cannot be wiretapped [[RFC2804](#)].

Note: the difference regarding local audio processing compared to the "Multiparty video communication" use-case is that other sound objects than the streams must be possible to be included in the spatialization and mixing. "Other sound objects" could for example be a file with the sound of the tank; that file could be stored locally or remotely.

##### **4.2.13.2. Derived Requirements**

F1, F2, F3, F4, F5, F6, F8, F9, F11, F12, F13, F14, F15, F16, F18, F20, F23, F34

A1, A2, A3, A4, A5, A7, A8, A9, A10, A11, A12, A13, A14, A15, A16, A17, A18, A23

#### **4.2.14. Distributed Music Band**

##### **4.2.14.1. Description**

In this use-case, a music band is playing music while the members are at different physical locations. No central server is used, instead



all streams are set up in a mesh fashion.

Discussion: This use-case was briefly discussed at the Quebec webrtc meeting and it got support. So far the only concrete requirement (A17) derived is that the application must be able to ask the browser to treat the audio signal as audio (in contrast to speech). However, the use case should be further analysed to determine other requirements (could be e.g. on delay mic->speaker, level control of audio signals, etc.).

#### **4.2.14.2. Derived Requirements**

F1, F2, F3, F4, F5, F6, F8, F9, F11, F12, F13, F14, F15, F16

A1, A2, A3, A4, A5, A7, A8, A9, A10, A11, A12, A13, A14, A15, A16, A19

### **4.3. Browser - GW/Server use cases**

#### **4.3.1. Telephony terminal**

##### **4.3.1.1. Description**

A mobile telephony operator allows its customers to use a web browser to access their services. After a simple log in the user can place and receive calls in the same way as when using a normal mobile phone. When a call is received or placed, the identity is shown in the same manner as when a mobile phone is used.

It is essential that the communication cannot be wiretapped [[RFC2804](#)].

Note: With "place and receive calls in the same way as when using a normal mobile phone" it is meant that you can dial a number, and that your mobile telephony operator has made available your phone contacts on line, so they are available and can be clicked to call, and be used to present the identity of an incoming call. If the callee is not in your phone contacts the number is displayed. Furthermore, your call logs are available, and updated with the calls made/received from the browser. And for people receiving calls made from the web browser the usual identity (i.e. the phone number of the mobile phone) will be presented.

##### **4.3.1.2. Derived Requirements**

F1, F2, F3, F4, F5, F6, F8, F9, F10, F20, F21

A1, A2, A3, A4, A7, A8, A9, A10, A11, A12





### **4.3.2. Fedex Call**

#### **4.3.2.1. Description**

Alice uses her web browser with a service something like Skype to be able to phone PSTN numbers. Alice calls 1-800-gofedex. Alice should be able to hear the initial prompts from the fedex IVR and when the IVR says press 1, there should be a way for Alice to navigate the IVR.

#### **4.3.2.2. Derived Requirements**

F1, F2, F3, F4, F5, F6, F8, F9, F10, F21, F22

A1, A2, A3, A4, A7, A8, A9, A10, A11, A12

### **4.3.3. Video conferencing system with central server**

#### **4.3.3.1. Description**

An organization uses a video communication system that supports the establishment of multiparty video sessions using a central conference server.

The browser of each participant send an audio stream (type in terms of mono, stereo, 5.1, ... depending on the equipment of the participant) to the central server. The central server mixes the audio streams (and can in the mixing process naturally add effects such as spatialization) and sends towards each participant a mixed audio stream which is played to the user.

The browser of each participant sends video towards the server. For each participant one high resolution video is displayed in a large window, while a number of low resolution videos are displayed in smaller windows. The server selects what video streams to be forwarded as main- and thumbnail videos respectively, based on speech activity. As the video streams to display can change quite frequently (as the conversation flows) it is important that the delay from when a video stream is selected for display until the video can be displayed is short.

The organization has an internal network set up with an aggressive firewall handling access to the Internet. If users cannot physically access the internal network, they can establish a Virtual Private Network (VPN).

It is essential that the communication cannot be wiretapped [[RFC2804](#)].



All participants are authenticated by the central server, and authorized to connect to the central server. The participants are identified to each other by the central server, and the participants do not have access to each others' credentials such as e-mail addresses or login IDs.

Note: This use-case adds requirements on support for fast stream switches F7, on encryption of media and on ability to traverse very restrictive FWs. There exist several solutions that enable the server to forward one high resolution and several low resolution video streams: a) each browser could send a high resolution, but scalable stream, and the server could send just the base layer for the low resolution streams, b) each browser could in a simulcast fashion send one high resolution and one low resolution stream, and the server just selects or c) each browser sends just a high resolution stream, the server transcodes into low resolution streams as required.

#### **4.3.3.2. Derived Requirements**

F1, F2, F3, F4, F5, F6, F7, F8, F9, F10, F17, F19, F20

A1, A2, A3, A4, A5, A7, A8, A9, A10, A11, A12, A17

## **5. Requirements**

### **5.1. General**

This section contains the requirements derived from the use-cases in [section 4](#).

NOTE: It is assumed that the user applications are executed on a browser. Whether the capabilities to implement specific browser requirements are implemented by the browser application, or are provided to the browser application by the underlying operating system, is outside the scope of this document.

### **5.2. Browser requirements**

| REQ-ID | DESCRIPTION   |
|--------|---|
| F1     | The browser MUST be able to use microphones and cameras as input devices to generate streams. |
| F2     | The browser MUST be able to send streams and data to a peer in the presence of NATs.          |



- 
- F3 Transmitted streams and data MUST be rate controlled.
- 
- F4 The browser MUST be able to receive, process and render streams and data ("render" does not apply for data) from peers.
- 
- F5 The browser MUST be able to render good quality audio and video even in the presence of reasonable levels of jitter and packet losses.
- TBD: What is a reasonable level?
- 
- F6 The browser MUST be able to handle high loss and jitter levels in a graceful way.
- 
- F7 The browser MUST support fast stream switches.
- 
- F8 The browser MUST detect when a stream from a peer is not received anymore
- 
- F9 When there are both incoming and outgoing audio streams, echo cancellation MUST be made available to avoid disturbing echo during conversation.
- QUESTION: How much control should be left to the web application?
- 
- F10 The browser MUST support synchronization of audio and video.
- QUESTION: How much control should be left to the web application?
- 
- F11 The browser MUST be able to transmit streams and data to several peers concurrently.
- 
- F12 The browser MUST be able to receive streams and data from multiple peers concurrently.
- 
- F13 The browser MUST be able to apply spatialization effects to audio streams.
- 
- F14 The browser MUST be able to measure the level in audio streams.



- 
- F15                The browser MUST be able to change the level  
                    in audio streams.
- 
- F16                The browser MUST be able to render several  
                    concurrent video streams
- 
- F17                The browser MUST be able to mix several  
                    audio streams.
- 
- F18                The browser MUST be able to process and mix  
                    sound objects (media that is retrieved from  
                    another source than the established media  
                    stream(s) with the peer(s) with audio streams.
- 
- F19                Streams and data MUST be able to pass through  
                    restrictive firewalls.
- 
- F20                It MUST be possible to protect streams and data  
                    from wiretapping.
- 
- F21                The browser MUST support an audio media format  
                    (codec) that is commonly supported by existing  
                    telephony services.
- QUESTION: G.711?
- 
- F22                There should be a way to navigate  
                    a DTMF based IVR
- 
- F23                The browser must be able to send short  
                    latency unreliable datagram traffic to a  
                    peer browser.
- 
- F24                The browser SHOULD be able to take advantage  
                    of available capabilities (supplied by network  
                    nodes) to prioritize voice, video and data  
                    appropriately.
- 
- F25                The browser SHOULD use encoding of streams  
                    suitable for the current rendering (e.g.  
                    video display size) and SHOULD change parameters  
                    if the rendering changes during the session
- 
- F26                It MUST be possible to move from one network  
                    interface to another one
- 
- F27                The browser MUST be able to initiate and





accept a media session where the data needed for establishment can be carried in SIP.

- 
- F28            The browser MUST support a baseline audio and video codec
- 
- F29            The browser MUST be able to send streams and data to a peer in the presence of NATs that block UDP traffic.
- 
- F30            The browser MUST be able to use the screen (or a specific area of the screen) or what a certain application displays on the screen to generate streams.
- 
- F31            The browser MUST be able to use several STUN and TURN servers
- 
- F32            There browser MUST support that STUN and TURN servers to use are supplied by other entities than the service provided (i.e. the network provider).
- 
- F33            The browser must be able to send reliable data traffic to a peer browser.
- 
- F34            The browser MUST support priortization of streams and data.
- 
- F35            The browser MUST enable verification, given the right circumstances and by use of other trusted communication, of that streams and data received have not been manipulated by any party.
- 
- F36            The browser MUST reject incoming media and data, either modified, created or injected, by any entity not trusted            by the site.
- 
- F37            The browser MUST be able to send streams and data to a peer in the presence of FWs that only allows http(s) traffic.
- 
- F38            The browser MUST be able to collect statistics, related to the transport of audio and video between peers, needed to estimate quality of service.
-



### 5.3. API requirements

| REQ-ID | DESCRIPTION   |
|--------|---|
| A1     | The Web API MUST provide means for the application to ask the browser for permission to use cameras and microphones as input devices.   |
| A2     | The Web API MUST provide means for the web application to control how streams generated by input devices are used.  |
| A3     | The Web API MUST provide means for the web application to control the local rendering of streams (locally generated streams and streams received from a peer).  |
| A4     | The Web API MUST provide means for the web application to initiate sending of stream/stream components to a peer.   |
| A5     | <p>The Web API MUST provide means for the web application to control the media format (codec) to be used for the streams sent to a peer.</p> <p>NOTE: The level of control depends on whether the codec negotiation is handled by the browser or the web application.</p> |
| A6     | The Web API MUST provide means for the web application to modify the media format for streams sent to a peer after a media stream has been established.   |
| A7     | The Web API MUST provide means for informing the web application of whether the establishment of a stream with a peer was successful or not.  |
| A8     | The Web API MUST provide means for the web application to mute/unmute a stream or stream component(s). When a stream is sent to a peer mute status must be preserved in the stream received by the peer.  |
| A9     | The Web API MUST provide means for the web application to cease the sending of a stream   |



to a peer.

- 
- A10            The Web API MUST provide means for the web application to cease processing and rendering of a stream received from a peer.
- 
- A11            The Web API MUST provide means for informing the web application when a stream from a peer is no longer received.
- 
- A12            The Web API MUST provide means for informing the web application when high loss rates occur.
- 
- A13            The Web API MUST provide means for the web application to apply spatialization effects to audio streams.
- 
- A14            The Web API MUST provide means for the web application to detect the level in audio streams.
- 
- A15            The Web API MUST provide means for the web application to adjust the level in audio streams.
- 
- A16            The Web API MUST provide means for the web application to mix audio streams.
- 
- A17            For each stream generated, the Web API MUST provide an identifier that is accessible by the application. The identifier MUST be accessible also for a peer receiving that stream and MUST be unique relative to all other stream identifiers in use by either party.
- 
- A18            The Web API MUST provide a mechanism for sending and receiving isolated discrete chunks of data.
- 
- A19            The Web API MUST provide means for the web application indicate the type of audio signal (speech, audio)for audio stream(s)/stream component(s).
- 
- A20            It must be possible for an initiator or a responder Web application to indicate the types of media he's willing to accept incoming streams for when setting up a connection (audio,



video, other). The types of media he's willing to accept can be a subset of the types of media the browser is able to accept.

- 
- A21            The Web API MUST provide means for the application to ask the browser for permission to the screen, a certain area on the screen or what a certain application displays on the screen as input to streams.
- 
- A22            The Web API MUST provide means for the application to specify several STUN and/or TURN servers to use.
- 
- A23            The Web API MUST provide means for the application to specify the priority to apply for outgoing streams and data.
- 
- A24            The Web API MUST provide a mechanism for sending and receiving files.
- 
- A25            It must be possible for the application to refrain from exposing the IP address
- 
- A26            The Web API MUST provide means for the application to obtain the statistics (related to transport, and collected by the browser) needed to estimate quality of service.
- 

## **6. IANA Considerations**

TBD

## **7. Security Considerations**

### **7.1. Introduction**

A malicious web application might use the browser to perform Denial Of Service (DOS) attacks on NAT infrastructure, or on peer devices. Also, a malicious web application might silently establish outgoing, and accept incoming, streams on an already established connection.

Based on the identified security risks, this section will describe security considerations for the browser and web application.





## **7.2. Browser Considerations**

The browser is expected to provide mechanisms for getting user consent to use device resources such as camera and microphone.

The browser is expected to provide mechanisms for informing the user that device resources such as camera and microphone are in use ("hot").

The browser is expected to provide mechanisms for users to revise and even completely revoke consent to use device resources such as camera and microphone.

The browser is expected to provide mechanisms for getting user consent to use the screen (or a certain part of it) or what a certain application displays on the screen as source for streams.

The browser is expected to provide mechanisms for informing the user that the screen, part thereof or an application is serving as a stream source ("hot").

The browser is expected to provide mechanisms for users to revise and even completely revoke consent to use the screen, part thereof or an application is serving as a stream source.

The browser is expected to provide mechanisms in order to assure that streams are the ones the recipient intended to receive.

The browser is expected to provide mechanisms that allows the users to verify that the streams received have not be manipulated (F35).

The browser needs to ensure that media is not sent, and that received media is not rendered, until the associated stream establishment and handshake procedures with the remote peer have been successfully finished.

The browser needs to ensure that the stream negotiation procedures are not seen as Denial Of Service (DOS) by other entities.

## **7.3. Web Application Considerations**

The web application is expected to ensure user consent in sending and receiving media streams.

## **8. Additional use-cases**

Several additional use-cases have been discussed. At this point



these use-cases are not included as requirement deriving use-cases for different reasons (lack of documentation, overlap with existing use-cases, lack of consensus). For completeness these additional use-cases are listed below:

1. Use-cases regarding different situations when being invited to a "session", e.g. browser open, browser open but another tab active, browser open but active in session, browser closed, .... (Matthew Kaufman); discussed at webrtc meeting
2. E911 (Paul Beaumont) <http://www.ietf.org/mail-archive/web/rtcweb/current/msg00525.html>, followed up by Stephan Wenger
3. Local Recording and Remote recording (John): Discussed a \_lot\_ on the mail lists (rtcweb as well as public-webrtc) 1August and September 2011. Concrete proposal: <http://www.ietf.org/mail-archive/web/rtcweb/current/msg01006.html> (remote) and <http://www.ietf.org/mail-archive/web/rtcweb/current/msg00734.html> (local)
4. Emergency access for disabled (Bernard Aboba) <http://www.ietf.org/mail-archive/web/rtcweb/current/msg00478.html>
5. Clue use-cases (Roni Even) <http://tools.ietf.org/html/draft-ietf-clue-telepresence-use-cases-01>
6. Rohan red cross (Cullen Jennings); <http://www.ietf.org/mail-archive/web/rtcweb/current/msg00323.html>
7. Security camera/baby monitor usage <http://www.ietf.org/mail-archive/web/rtcweb/current/msg00543.html>
8. Large multiparty session <http://www.ietf.org/mail-archive/web/rtcweb/current/msg00530.html>
9. Call center <http://www.ietf.org/mail-archive/web/rtcweb/current/msg04203.html>
10. Enterprise policies <http://www.ietf.org/mail-archive/web/rtcweb/current/msg04271.html>
11. Low-complex multiparty central node <http://www.ietf.org/mail-archive/web/rtcweb/current/msg04430.html>
12. Multiparty central node that is not allowed to decipher <http://www.ietf.org/mail-archive/web/rtcweb/current/msg04457.html>
13. Enable company coop without being able to decipher <http://www.ietf.org/mail-archive/web/rtcweb/current/msg04461.html>

## 9. Acknowledgements

Dan Burnett has reviewed and proposed a lot of things that enhances the document. Most of this has been incorporated in rev -05.

Stephan Wenger has provided a lot of useful input and feedback, as well as editorial comments.

Harald Alvestrand and Ted Hardie have provided comments and feedback on the draft.



Harald Alvestrand and Cullen Jennings have provided additional use-cases.

Thank You to everyone in the RTCWEB community that have provided comments, feedback and improvement proposals on the draft content.

## **10. Change Log**

[RFC EDITOR NOTE: Please remove this section when publishing]

Changes from [draft-ietf-rtcweb-use-cases-and-requirements-09](#)

- o Changed "video communication session" to "audiovisual communication session".

Changes from [draft-ietf-rtcweb-use-cases-and-requirements-08](#)

- o Changed "eavesdropping" to "wiretapping" and referenced [RFC2804](#).
- o Removed informal ref webrtc\_req; that document has been abandoned by the W3C webrtc WG.
- o Added use-case where one user is behind a FW that only allows http; derived req. F37.
- o Changed F24 slightly; MUST-> SHOULD, inserted "available".
- o Added a clause to "Simple video communication service" saying that the service provider monitors the quality of service, and derived reqs F38 and A26.

Changes from [draft-ietf-rtcweb-use-cases-and-requirements-07](#)

- o Added "and data exchange" to 1. Introduction.
- o Removed cone and symmetric NAT from 4.1 Introduction, refers to [RFC4787](#) instead.
- o Added text on enabling verification of that the media has not been manipulated by anyone to use-case "Simple Video Communication Service", derived req. F35
- o Added text on that the browser should reject media (data) that has been created/injected/modified by non-trusted party, derived req. F36
- o Added text on enabling the app to refrain from revealing IP address to use-case "Simple Video Communication Service", derived req. A25
- o Added use-case "Simple Video Communication Service with file exchange", derived reqs F33 and A24
- o Added priority of video streams to "Hockey game viewer" use case, added priority of data to "on-line game use-case", derived reqs F34 and A23



- o In F22, "the IVR" -> "a DTMF based IVR".
- o Updated req F23 to clarify that requirements such as NAT traversal, protection from eavesdropping, rate control applies also to datagram.

Changes from [draft-ietf-rtcweb-use-cases-and-requirements-06](#)

- o Renaming of requirements (FaI1 -> F31), (FaI2 -> F32) and (AaI1 -> A22)

Changes from [draft-ietf-rtcweb-use-cases-and-requirements-05](#)

- o Added use-case "global service provider", derived reqs associated with several STUN/TURN servers
- o Added use-case "enterprise aspects", derived req associated with enabling the network provider to supply STUN and TURN servers
- o The requirements from the above are ICE specific and labeled accordingly
- o Separated the requirements phrased like "processing such as pan, mix and render" for audio to be specific reqs on spatialization, level measurement, level adjustment and mixing (discussed on the lists in <http://www.ietf.org/mail-archive/web/rtcweb/current/msg01648.html> and <http://lists.w3.org/Archives/Public/public-webrtc/2011Sep/0102.html>)
- o Added use-case on sharing as decided in <http://www.ietf.org/mail-archive/web/rtcweb/current/msg01700.html>, derived reqs F30 and A21
- o Added the list of common considerations proposed in mail <http://www.ietf.org/mail-archive/web/rtcweb/current/msg01562.html> to the Introduction of the use-case section

Changes from [draft-ietf-rtcweb-use-cases-and-requirements-04](#)

- o Most changes based on the input from Dan Burnett <http://www.ietf.org/mail-archive/web/rtcweb/current/msg00948.html>
- o Many editorial changes
- o 4.2.1.1 Clarified
- o Some clarification added to 4.3.1.1 as a note
- o F-requirements updated (see reply to Dan's mail).
- o Almost all A-requirements updated to start "The Web API MUST provide ..."
- o A8 removed, A9 rephrased to cover A8 and old A9
- o A15 rephrased
- o For more details, and discussion, look att the response to Dan's mail <http://www.ietf.org/mail-archive/web/rtcweb/current/msg01177.html>





Changes from [draft-ietf-rtcweb-use-cases-and-requirements-03](#)

- o Editorials
- o Changed when the self-view is displayed in 4.2.1.1, and added words about allowing users to remove and re-insert it.
- o Clarified 4.2.6.1
- o Removed the "mono" stuff from 4.2.7.1
- o Added that communication should not be possible to eavesdrop to most use cases - and req. F17
- o Re-phrased 4.3.3.1 to not describe the technical solution so much, and removed "stereo" stuff. Solution possibilities are now in a note.
- o Re-inserted API requirements after discussion in the W3C webrtc WG. (Re-phrased A15 and added A18 compared to version -02).

Changes from [draft-ietf-rtcweb-use-cases-and-requirements-02](#)

- o Removed description/list of API requirements, instead
- o Reference to W3C webrtc\_reqs document for API requirements

Changes from [draft-ietf-rtcweb-ucreqs-01](#)

- o Changed Intended status to Information
- o Changed "Ipr" to "trust200902"
- o Added use case "Simple video communication service, NAT/FW that blocks UDP", and derived new req F26
- o Added use case "Distributed Music Band" and derived new req A17
- o Added F24 as requirement derived from use case "Simple video communication service with inter-operator calling"
- o Added section "Additional use cases"
- o Added text about ID handling to multiparty with central server use case
- o Re-phrased A1 slightly

Changes from [draft-ietf-rtcweb-ucreqs-00](#)

- o - Reshuffled: Just two main groups of use cases (b2b and b2GW/Server); removed some specific use cases and added them instead as flavors to the base use case (Simple video communication)
- o - Changed the formulation of F19
- o - Removed the requirement on an API for DTMF
- o - Removed "FX3: There SHOULD be a mapping of the minimum needed data for setting up connections into SIP, so that the restriction to SIP-carriable data can be verified. Not a rev on the browser but rather on a document"
- o - (see <http://www.ietf.org/mail-archive/web/rtcweb/current/msg00227.html> for more details)



- o -Added text on informing user of that mic/cam is being used and that it must be possible to revoke permission to use them in [section 7](#).

Changes from [draft-holmberg-rtcweb-ucreqs-01](#)

- o - Draft name changed to [draft-ietf-rtcweb-ucreqs](#)
- o - Use-case grouping introduced
- o - Additional use-cases added
- o - Additional reqs added (derived from use cases): F19-F25, A16-A17

Changes from [draft-holmberg-rtcweb-ucreqs-00](#)

- o - Mapping between use-cases and requirements added (Harald Alvestrand, 090311)
- o - Additional security considerations text (Harald Alvestrand, 090311)
- o - Clarification that user applications are assumed to be executed by a browser (Ted Hardie, 080311)
- o - Editorial corrections and clarifications

## **[11.](#) References**

### **[11.1.](#) Normative References**

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2804] IAB and IESG, "IETF Policy on Wiretapping", [RFC 2804](#), May 2000.

### **[11.2.](#) Informative References**

#### Authors' Addresses

Christer Holmberg  
Ericsson  
Hirsalantie 11  
Jorvas 02420  
Finland

Email: [christer.holmberg@ericsson.com](mailto:christer.holmberg@ericsson.com)



Stefan Hakansson  
Ericsson  
Laboratoriegrand 11  
Lulea 97128  
Sweden

Email: stefan.lk.hakansson@ericsson.com

Goran AP Eriksson  
Ericsson  
Farogatan 6  
Stockholm 16480  
Sweden

Email: goran.ap.eriksson@ericsson.com

