

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: April 30, 2015

A.B. Roach
Mozilla
October 27, 2014

WebRTC Video Processing and Codec Requirements
draft-ietf-rtcweb-video-01

Abstract

This specification provides the requirements and considerations for WebRTC applications to send and receive video across a network. It specifies the video processing that is required, as well as video codecs and their parameters.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 30, 2015.

Copyright Notice

Copyright (c) 2014 IETFTrust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
2.	Terminology	2
3.	Pre and Post Processing	2
3.1.	Camera Source Video	3
3.2.	Screen Source Video	3
4.	Stream Orientation	4
5.	Codec-Specific Considerations	4
5.1.	VP8	5
5.2.	H.264	5
6.	Mandatory to Implement Video Codec	6
6.1.	Temperature of Working Group	6
7.	Security Considerations	7
8.	IANA Considerations	7
9.	Acknowledgements	7
10.	References	7
10.1.	Normative References	7
10.2.	Informative References	9
	Author's Address	9

[1.](#) Introduction

One of the major functions of WebRTC endpoints is the ability to send and receive interactive video. The video might come from a camera, a screen recording, a stored file, or some other source. This specification defines how the video is used and discusses special considerations for processing the video. It also covers the video-related algorithms WebRTC devices need to support.

Note that this document only discusses those issues dealing with video codec handling. Issues that are related to transport of media streams across the network are specified in [[I-D.ietf-rtcweb-rtp-usage](#)].

[2.](#) Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

[3.](#) Pre and Post Processing

This section provides guidance on pre- or post-processing of video streams.

Unless specified otherwise by the SDP or codec, the color space SHOULD be sRGB [[SRGB](#)].

Roach

Expires April 30, 2015

[Page 2]

Internet-Draft

WebRTC Video

October 2014

TODO: I'm just throwing this out there to see if a specific proposal, even if wrong, might draw more comment than "TBD". If you don't like sRGB for this purpose, comment on the rtcweb@ietf.org mailing list. It has been suggested that the MPEG "Coding independent media description code points" specification [[IEC23001-8](#)] may have applicability here.

[3.1.](#) Camera Source Video

This document imposes no normative requirements on camera capture; however, implementors are encouraged to take advantage of the following features, if feasible for their platform:

- o Automatic focus, if applicable for the camera in use
- o Automatic white balance
- o Automatic light level control

[3.2.](#) Screen Source Video

If the video source is some portion of a computer screen (e.g., desktop or application sharing), then the considerations in this section also apply.

Because screen-sourced video can change resolution (due to, e.g., window resizing and similar operations), WebRTC video recipients MUST be prepared to handle mid-stream resolution changes in a way that preserves their utility. Precise handling (e.g., resizing the element a video is rendered in versus scaling down the received stream; decisions around letter/pillarboxing) is left to the discretion of the application.

Additionally, attention is drawn to the requirements in [[I-D.ietf-rtcweb-security-arch](#)] [section 5.2](#) and the considerations in [[I-D.ietf-rtcweb-security](#)] [section 4.1.1](#).

TODO: Do we want to define additional metadata to indicate whether a stream is sourced from a camera versus a screen capture? This would allow the receiving party to tune, e.g., output filters. It would appear that H.263 has this kind of indicator built into its bitstream, but I found no analog in H.264 or VP8.

[4.](#) Stream Orientation

In some circumstances - and notably those involving mobile devices - the orientation of the camera may not match the orientation used by the encoder. Of more importance, the orientation may change over the course of a call, requiring the receiver to change the orientation in which it renders the stream.

While the sender may elect to simply change the pre-encoding orientation of frames, this may not be practical or efficient (in particular, in cases where the interface to the camera returns pre-compressed video frames). Note that the potential for this behavior adds another set of circumstances under which the resolution of a screen might change in the middle of a video stream, in addition to those mentioned under "Screen Sourced Video," above.

To accommodate these circumstances, RTCWEB implementations SHOULD support generating and receiving the R0 and R1 bits of the Coordination of Video Orientation (CVO) mechanism described in section 7.4.5 of [[TS26.114](#)]. (TODO: Is "SHOULD support" the right level here?) They MAY support the other bits in the CVO extension, including the higher-resolution rotation bits.

Further, some codecs support in-band signaling of orientation (for example, the SEI "Display Orientation" messages in H.264 and H.265). If CVO has been negotiated, then the sender MUST NOT make use of such codec-specific mechanisms. However, when support for CVO is not signaled in the SDP, then such implementations MAY make use of the codec-specific mechanisms instead.

[5.](#) Codec-Specific Considerations

WebRTC endpoints are not required to support the codecs mentioned in this section.

However, to foster interoperability between endpoints that have codecs in common, if they do support one of the listed codecs, then they need to meet the requirements specified in the subsection for that codec.

SDP allows for codec-independent indication of preferred video resolutions using the mechanism described in [[RFC6236](#)]. If a recipient of video indicates a receiving resolution, the sender SHOULD accommodate this resolution, as the receiver may not be capable of handling higher resolutions.

Roach

Expires April 30, 2015

[Page 4]

Internet-Draft

WebRTC Video

October 2014

Additionally, codecs may include codec-specific means of signaling maximum receiver abilities with regards to resolution, frame rate, and bitrate.

Unless otherwise signaled in SDP, recipients of video streams are MUST be able to decode video at a rate of at least 20 fps at a resolution of at least 320x240. These values are selected based on the recommendations in [[HSUP1](#)].

Encoders are encouraged to support encoding media with at least the same resolution and frame rates cited above.

[5.1.](#) VP8

If VP8, defined in [[RFC6386](#)], is supported, then the endpoint MUST support the payload formats defined in [[I-D.ietf-payload-vp8](#)]. In addition it MUST support the 'bilinear' and 'none' reconstruction filters.

In addition to the [[RFC6236](#)] mechanism, H.264 encoders MUST limit the streams they send to conform to the values indicated by receivers in the corresponding max-fr and max-fs SDP attributes.

TODO: There have been claims that VP8 already requires supporting both filters; if true, these do not need to be reiterated here.

[5.2.](#) H.264

If [\[H264\]](#) is supported, then the device MUST support the payload formats defined in [\[RFC6184\]](#). In addition, they MUST support Constrained Baseline Profile Level 1.2, and they SHOULD support H.264 Constrained High Profile Level 1.3.

Implementations of the H.264 codec have utilized a wide variety of optional parameters. To improve interoperability the following parameter settings are specified:

packetization-mode: Packetization-mode 1 MUST be supported. Other modes MAY be negotiated and used.

profile-level-id: Implementations MUST include this parameter within SDP and SHOULD interpret it when receiving it.

max-mbps, max-smbps, max-fs, max-cpb, max-dpb, and max-br: These parameters allow the implementation to specify that they can support certain features of H.264 at higher rates and values than those signalled by their level (set with profile-level-id). Implementations MAY include these parameters in their SDP, but

SHOULD interpret them when receiving them, allowing them to send the highest quality of video possible.

sprop-parameter-sets: H.264 allows sequence and picture information to be sent both in-band, and out-of-band. WebRTC implementations MUST signal this information in-band; as a result, this parameter will not be present in SDP.

TODO: Do we need to require the handling of specific SEI messages? One example that has been raised is freeze-frame messages.

[6.](#) Mandatory to Implement Video Codec

Note: This section is here purely as a placeholder, as there is not yet WG Consensus on Mandatory to Implement video codecs. The issue

is more complicated than may be immediately apparent to newcomers, who are strongly encouraged to familiarize themselves with the previous discussions on the topic before engaging on this issue.

The currently recorded working group consensus is that all implementations MUST support a single, specified mandatory-to-implement codec. The remaining decision point is a selection of this single codec.

[6.1.](#) Temperature of Working Group

To capture the conversation so far, this section summarizes the result of a straw poll that the working group undertook in December 2013 and January 2014. Respondents were asked to answer "Yes," "Acceptable," or "No" for each option. The options were collected from the working group at large prior to the initiation of the straw poll.

	Yes	Acc	No
	---	---	---
1. All entities MUST support H.264	48%	11%	41%
2. All entities MUST support VP8	41%	17%	42%
3. All entities MUST support both H.264 and VP8	9%	38%	53%
4. Browsers MUST support both H.264 and VP8, other entities MUST support at least one of H.264 and VP8	11%	34%	55%
5. All entities MUST support at least one of H.264 and VP8	10%	16%	74%
6. All entities MUST support H.261	5%	23%	72%
7. There is no MTI video codec	12%	30%	58%
8. All entities MUST support H.261 and all entities MUST support at least one of H.264 and VP8	4%	28%	68%
9. All entities MUST support Theora	7%	26%	67%

10. All entities MUST implement at least two of {VP8, H.264, H.261}	5%	30%	65%
11. All entities MUST implement at least two of {VP8, H.264, H.263}	5%	25%	70%
12. All entities MUST support decoding using both H.264 and VP8, and MUST support encoding using at least one of H.264 or VP8	7%	20%	73%
13. All entities MUST support H.263	6%	19%	75%

14. All entities MUST implement at least two of {VP8, H.264, Theora}	6%	27%	67%
15. All entities MUST support decoding using Theora	1%	15%	84%
16. All entities MUST support Motion JPEG	1%	25%	74%

7. Security Considerations

This specification does not introduce any new mechanisms or security concerns beyond what the other documents it references. In WebRTC, video is protected using DTLS/SRTP. A complete discussion of the security can be found in [[I-D.ietf-rtcweb-security](#)] and [[I-D.ietf-rtcweb-security-arch](#)]. Implementers should consider whether the use of variable bit rate video codecs are appropriate for their application based on [[RFC6562](#)].

8. IANA Considerations

This document requires no actions from IANA.

9. Acknowledgements

The authors would like to thank Gaelle Martin-Cocher, Stephan Wenger, and Bernard Aboba for their detailed feedback and assistance with this document. Thanks to Cullen Jennings for providing text and review. This draft includes text from [draft-cbran-rtcweb-codec](#).

10. References

10.1. Normative References

- [H264] ITU-T Recommendation H.264, "Advanced video coding for generic audiovisual services", April 2013.
- [HSUP1] ITU-T Recommendation H.Supp1, "Application profile - Sign language and lip-reading real-time conversation using low bit rate video communication", May 1999.
- [I-D.ietf-payload-vp8]

Galligan, "RTP Payload Format for VP8 Video", [draft-ietf-payload-vp8-11](#) (work in progress), February 2014.

[IEC23001-8]

ISO/IEC 23001-8:2013/DCOR1, "Coding independent media description code points", 2013.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

[RFC4175] Gharai, L. and C. Perkins, "RTP Payload Format for Uncompressed Video", [RFC 4175](#), September 2005.

[RFC4421] Perkins, C., "RTP Payload Format for Uncompressed Video: Additional Colour Sampling Modes", [RFC 4421](#), February 2006.

[RFC5104] Wenger, S., Chandra, U., Westerlund, M., and B. Burman, "Codec Control Messages in the RTP Audio-Visual Profile with Feedback (AVPF)", [RFC 5104](#), February 2008.

[RFC6184] Wang, Y.-K., Even, R., Kristensen, T., and R. Jesup, "RTP Payload Format for H.264 Video", [RFC 6184](#), May 2011.

[RFC6236] Johansson, I. and K. Jung, "Negotiation of Generic Image Attributes in the Session Description Protocol (SDP)", [RFC 6236](#), May 2011.

[RFC6386] Bankoski, J., Koleszar, J., Quillio, L., Salonen, J., Wilkins, P., and Y. Xu, "VP8 Data Format and Decoding Guide", [RFC 6386](#), November 2011.

[RFC6562] Perkins, C. and JM. Valin, "Guidelines for the Use of Variable Bit Rate Audio with Secure RTP", [RFC 6562](#), March 2012.

[SRGB] IEC 61966-2-1, "Multimedia systems and equipment - Colour measurement and management - Part 2-1: Colour management - Default RGB colour space - sRGB.", October 1999.

[TS26.114]

3GPP TS 26.114 V12.7.0, "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; IP Multimedia Subsystem (IMS); Multimedia Telephony; Media handling and interaction (Release 12)", September 2014.

[10.2](#). Informative References

[I-D.ietf-rtcweb-rtp-usage]

Perkins, C., Westerlund, M., and J. Ott, "Web Real-Time Communication (WebRTC): Media Transport and Use of RTP", [draft-ietf-rtcweb-rtp-usage-06](#) (work in progress), February 2013.

[I-D.ietf-rtcweb-security-arch]

Rescorla, E., "WebRTC Security Architecture", [draft-ietf-rtcweb-security-arch-09](#) (work in progress), February 2014.

[I-D.ietf-rtcweb-security]

Rescorla, E., "Security Considerations for WebRTC", [draft-ietf-rtcweb-security-06](#) (work in progress), January 2014.

Author's Address

Adam Roach
Mozilla
\
Dallas
US

Phone: +1 650 903 0800 x863
Email: adam@nostrum.com

