

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: January 18, 2017

X. Liu
P. Sarda
Ericsson
V. Choudhary
Huawei Technologies
July 18, 2016

A YANG Data Model for Routing Information Protocol (RIP)
draft-ietf-rtgwg-yang-rip-02.txt

Abstract

This document describes a data model for the Routing Information Protocol (RIP). Both RIP version 2 and RIPng are covered.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>

This Internet-Draft will expire on January 18, 2017.

Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents

Internet-Draft [draft-ietf-rtgwg-yang-rip-02.txt](#)

July 2016

(<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

| | | |
|----------------------|--|--------------------|
| 1. | Introduction..... | 2 |
| 1.1. | Terminology..... | 2 |
| 1.2. | Tree Diagrams..... | 3 |
| 2. | RIP YANG model overview..... | 3 |
| 3. | RIP YANG module..... | 9 |
| 4. | IANA Considerations..... | 36 |
| 5. | Security Considerations..... | 37 |
| 6. | References..... | 37 |
| 6.1. | Normative References..... | 37 |
| 6.2. | Informative References..... | 37 |

[1.](#) Introduction

This document introduces a YANG [[RFC6020](#)] data model for the Routing Information Protocol (RIP) [[RFC2453](#)][[RFC2080](#)]. RIP was designed to work as an Interior Gateway Protocol (IGP) in moderate-size Autonomous Systems (AS).

This YANG model supports both RIP version 2 and RIPng. RIP version 2 (defined in [[RFC2453](#)]) supports IPv4. RIPng (defined in [[RFC2080](#)]) supports IPv6.

[1.1.](#) Terminology

The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#), [[RFC2119](#)].

The following terms are defined in [[RFC6020](#)] and are not redefined here:

- o augment
- o data model

- o data node

[1.2.](#) Tree Diagrams

A simplified graphical representation of the data model is used in this document. The meaning of the symbols in these diagrams is as follows:

- o Brackets "[" and "]" enclose list keys.
- o Curly braces "{" and "}" contain names of optional features that make the corresponding node conditional.
- o Abbreviations before data node names: "rw" means configuration (read-write), and "ro" means state data (read-only).
- o Symbols after data node names: "?" means an optional node, "!" means a presence container, and "*" denotes a list and leaf-list.
- o Parentheses enclose choice and case nodes, and case nodes are also marked with a colon (":").
- o Ellipsis ("...") stands for contents of subtrees that are not shown.

[2.](#) RIP YANG model overview

This document defines the YANG module "ietf-rip", which has the following structure:

```
module: ietf-rip
augment /rt:routing/rt:control-plane-protocols/rt:control-plane-
protocol:
  +--rw rip
    +--rw originate-default-route!
      | +--rw route-policy?   route-policy-ref
    +--rw default-metric?      uint8
```

```

+--rw distance?                               uint8
+--rw triggered-update-threshold?             uint8
+--rw maximum-paths?                          uint8
+--rw output-delay?                          uint8
+--rw distribute-list* [prefix-set-name direction]
|  +--rw prefix-set-name                      prefix-set-ref
|  +--rw direction                          enumeration

```

```

|  +--rw if-name?                             if:interface-ref
+--rw redistribute
|  +--rw bgp* [asn]
|  |  +--rw asn                               inet:as-number
|  |  +--rw metric?                          uint8
|  |  +--rw route-policy?                   route-policy-ref
|  +--rw cg-nat!
|  |  +--rw metric?                          uint8
|  |  +--rw route-policy?                   route-policy-ref
|  +--rw connected!
|  |  +--rw metric?                          uint8
|  |  +--rw route-policy?                   route-policy-ref
|  +--rw ipsec!
|  |  +--rw metric?                          uint8
|  |  +--rw route-policy?                   route-policy-ref
|  +--rw isis* [instance]
|  |  +--rw instance                         leafref
|  |  +--rw level?                          enumeration
|  |  +--rw metric?                          uint8
|  |  +--rw route-policy?                   route-policy-ref
|  +--rw nat!
|  |  +--rw metric?                          uint8
|  |  +--rw route-policy?                   route-policy-ref
|  +--rw ospfv2* [instance]
|  |  +--rw instance                         leafref
|  |  +--rw route-type?                     ospf:route-type
|  |  +--rw metric?                          uint8
|  |  +--rw route-policy?                   route-policy-ref
|  +--rw ospfv3* [instance]
|  |  +--rw instance                         leafref
|  |  +--rw route-type?                     ospf:route-type
|  |  +--rw metric?                          uint8
|  |  +--rw route-policy?                   route-policy-ref
|  +--rw ripv2* [instance]
|  |  +--rw instance                         leafref

```

```

| | +--rw metric?          uint8
| | +--rw route-policy?  route-policy-ref
| +--rw ripng* [instance]
| | +--rw instance       leafref
| | +--rw metric?        uint8
| | +--rw route-policy?  route-policy-ref

```

```

| +--rw static!
|   +--rw metric?          uint8
|   +--rw route-policy?  route-policy-ref
+--rw timers
| +--rw update-interval?  uint16
| +--rw invalid-interval? uint16
| +--rw holddown-interval? uint16
| +--rw flush-interval?   uint16
+--rw interface* [interface]
  +--rw interface          if:interface-ref
  +--rw authentication
  | +--rw (auth-type-selection)?
  |   +--:(auth-key-chain)
  |   | +--rw key-chain?      key-chain:key-chain-ref
  |   +--:(auth-key)
  |   +--rw key?              string
  |   +--rw crypto-algorithm
  |   +--rw (algorithm)?
  |   +--:(hmac-sha-1-12) {crypto-hmac-sha-1-12}?
  |   | +--rw hmac-sha1-12?   empty
  |   +--:(aes-cmac-prf-128) {aes-cmac-prf-128}?
  |   | +--rw aes-cmac-prf-128? empty
  |   +--:(md5)
  |   | +--rw md5?            empty
  |   +--:(sha-1)
  |   | +--rw sha-1?          empty
  |   +--:(hmac-sha-1)
  |   | +--rw hmac-sha-1?     empty
  |   +--:(hmac-sha-256)
  |   | +--rw hmac-sha-256?   empty
  |   +--:(hmac-sha-384)
  |   | +--rw hmac-sha-384?   empty
  |   +--:(hmac-sha-512)
  |   | +--rw hmac-sha-512?   empty
  |   +--:(clear-text) {clear-text}?
  |   | +--rw clear-text?     empty

```

```

|           +---:(replay-protection-only) {replay-
protection-only}?
|           +---rw replay-protection-only?   empty
+---rw bfd {bfd}?
|   +---rw enabled?                           boolean

```

Liu

Expires January 18, 2017

[Page 5]

Internet-Draft

[draft-ietf-rtgwg-yang-rip-02.txt](#)

July 2016

```

|   +---rw local-multiplier?                   bfd-multiplier
|   +---rw (interval-config-type)?
|       +---:(tx-rx-intervals)
|           |   +---rw desired-min-tx-interval   uint32
|           |   +---rw required-min-rx-interval  uint32
|       +---:(single-interval)
|           +---rw min-interval                   uint32
+---rw cost?                                     uint8
+---rw neighbors {neighbor-configuration}?
|   +---rw neighbor* [address]
|       +---rw address   inet:ip-address
+---rw no-listen?                               empty
+---rw no-supply?                               empty
+---rw originate-default-route!
|   +---rw route-policy?   route-policy-ref
+---rw split-horizon?                           enumeration
+---rw summary-address
|   +---rw address?   inet:ip-prefix
|   +---rw metric?   uint8
+---rw timers
|   +---rw update-interval?   uint16
|   +---rw invalid-interval?  uint16
|   +---rw holddown-interval?  uint16
|   +---rw flush-interval?    uint16

```

augment /rt:routing-state/rt:control-plane-protocols/rt:control-plane-protocol:

```

+---ro rip
|   +---ro originate-default-route!
|       |   +---ro route-policy?   route-policy-ref
+---ro default-metric?   uint8
+---ro distance?         uint8
+---ro triggered-update-threshold?  uint8
+---ro maximum-paths?   uint8
+---ro output-delay?    uint8
+---ro distribute-list* [prefix-set-name direction]
|   +---ro prefix-set-name   prefix-set-ref
|   +---ro direction         enumeration

```

```
| +--ro if-name?          if:interface-ref
+--ro next-triggered-update?  uint32
+--ro num-of-routes?        uint32
+--ro timers
```

Liu

Expires January 18, 2017

[Page 6]

Internet-Draft [draft-ietf-rtgwg-yang-rip-02.txt](#)

July 2016

```
| +--ro update-interval?    uint16
| +--ro invalid-interval?  uint16
| +--ro holddown-interval?  uint16
| +--ro flush-interval?    uint16
+--ro interface* [interface]
| +--ro interface          if:interface-ref
| +--ro oper-status?      enumeration
| +--ro cost?             uint8
| +--ro listen?           boolean
| +--ro next-full-update?  uint32
| +--ro originate-default-route? boolean
| +--ro poison-reverse?   boolean
| +--ro split-horizon?    boolean
| +--ro supply?           boolean
| +--ro valid-address?    boolean
| +--ro timers
| | +--ro update-interval?  uint16
| | +--ro invalid-interval?  uint16
| | +--ro holddown-interval?  uint16
| | +--ro flush-interval?    uint16
| +--ro statistics {interface-statistics}?
| | +--ro discontinuity-time? yang:date-and-time
| | +--ro bad-packets-rcvd?   yang:counter32
| | +--ro bad-routes-rcvd?   yang:counter32
| | +--ro updates-sent?      yang:counter32
+--ro ipv4
| +--ro neighbors
| | +--ro neighbor* [ipv4-address]
| | | +--ro ipv4-address    inet:ipv4-address
| | | +--ro last-update?    yang:date-and-time
| | | +--ro bad-packets-rcvd? yang:counter32
| | | +--ro bad-routes-rcvd? yang:counter32
| +--ro routes
| | +--ro route* [ipv4-prefix]
| | | +--ro ipv4-prefix     inet:ipv4-prefix
| | | +--ro next-hop?      inet:ipv4-
address
| | +--ro interface?      if:interface-ref
```

| | | |
|--|----------------------|-------------|
| | +++ro redistributed? | boolean |
| | +++ro route-type? | enumeration |
| | +++ro metric? | uint8 |

Internet-Draft [draft-ietf-rtgwg-yang-rip-02.txt](#)

July 2016

| | | |
|---------------------------------------|-------------------------------------|--|
| | +++ro expire-time? | uint16 |
| | +++ro deleted? | boolean |
| | +++ro holddown? | boolean |
| | +++ro need-triggered-update? | boolean |
| | +++ro inactive? | boolean |
| | +++ro flush-expire-before-holddown? | boolean |
| +++ro ipv6 | | |
| | +++ro neighbors | |
| | | +++ro neighbor* [ipv6-address] |
| | | +++ro ipv6-address inet:ipv6-address |
| | | +++ro last-update? yang:date-and-time |
| | | +++ro bad-packets-rcvd? yang:counter32 |
| | | +++ro bad-routes-rcvd? yang:counter32 |
| | +++ro routes | |
| | +++ro route* [ipv6-prefix] | |
| | +++ro ipv6-prefix | inet:ipv6-prefix |
| | +++ro next-hop? | inet:ipv6- |
| address | | |
| | +++ro interface? | if:interface-ref |
| | +++ro redistributed? | boolean |
| | +++ro route-type? | enumeration |
| | +++ro metric? | uint8 |
| | +++ro expire-time? | uint16 |
| | +++ro deleted? | boolean |
| | +++ro holddown? | boolean |
| | +++ro need-triggered-update? | boolean |
| | +++ro inactive? | boolean |
| | +++ro flush-expire-before-holddown? | boolean |
| +++ro statistics {global-statistics}? | | |
| | +++ro discontinuity-time? | yang:date-and-time |
| | +++ro requests-rcvd? | yang:counter32 |
| | +++ro requests-sent? | yang:counter32 |
| | +++ro responses-rcvd? | yang:counter32 |
| | +++ro responses-sent? | yang:counter32 |
| rpcs: | | |
| ++++x clear-rip-route | | |
| ++++w input | | |
| ++++w rip-instance? | Leafref | |

3. RIP YANG module

```
<CODE BEGINS> file "ietf-rip@2016-07-08.yang"
module ietf-rip {
  namespace "urn:ietf:params:xml:ns:yang:ietf-rip";
  // replace with IANA namespace when assigned
  prefix rip;

  import ietf-inet-types {
    prefix "inet";
  }

  import ietf-yang-types {
    prefix "yang";
  }

  import ietf-interfaces {
    prefix "if";
  }

  import ietf-ip {
    prefix "ip";
  }

  import ietf-routing {
    prefix "rt";
  }

  import ietf-key-chain {
    prefix "key-chain";
  }

  import ietf-bfd {
    prefix "bfd";
  }

  import ietf-ospf {
    prefix "ospf";
  }
}
```

organization "TBD";

```
contact "TBD";
description
  "This YANG module defines a model for managing Routing
  Information Protocol (RIP), including RIP version 2 and RIPng.";

revision 2016-07-08 {
  description
    "Initial revision.";
  reference
    "RFC 2453: RIP Version 2.
     RFC 2080: RIPng for IPv6.
     RFC 1724: RIP Version 2 MIB Extension.";
}

/*
 * Features
 */
feature bfd {
  description
    "This feature indicates that the system supports BFD.";
}

feature bfd-protocol-params {
  description
    "BFD protocol specific parameters support.";
}

feature global-statistics {
  description
    "This feature indicates that the system supports collecting
    global statistic data.";
}

feature interface-statistics {
  description
    "This feature indicates that the system supports collecting
    per-interface statistic data.";
}
```

```
feature neighbor-configuration {
  description
```

Liu

Expires January 18, 2017

[Page 10]

Internet-Draft

[draft-ietf-rtgwg-yang-rip-02.txt](#)

July 2016

```
    "This feature indicates that the system supports
    neighbor configuration.";
}

/*
 * Typedefs
 */

typedef prefix-set-ref {
  type string;
  description
    "A type for a reference to a prefix list.";
}

typedef route-policy-ref {
  type string;
  description
    "A type for a reference to a route policy.";
}

/*
 * Identities
 */

identity rip {
  base "rt:routing-protocol";
  description "Identity for the RIP routing protocol.";
}

identity ripv2 {
  base "rip:rip";
  description "RIPv2";
}

identity ripng {
  base "rip:rip";
  description "RIPng";
}

/*
```

* Groupings

Liu

Expires January 18, 2017

[Page 11]

Internet-Draft

[draft-ietf-rtgwg-yang-rip-02.txt](#)

July 2016

```
*/

grouping originate-default-route-container {
  description
    "Container for setting of originating default route.";
  container originate-default-route {
    presence "Present if originating default route is enabled.";
    description
      "Injects the default route into the RIP or RIPng
      instance.";
    leaf route-policy {
      type route-policy-ref;
      description
        "The conditions of the route policy are applied to the
        default route.";
    }
  }
}

grouping redistribute-container {
  description
    "Container of redistribute attributes.";

  container redistribute {
    description
      "Redistributes routes learned from other routing protocols
      into the RIP routing instance.";
    list bgp {
      key "asn";
      description
        "Redistributes routes from the specified BGP autonomous
        system (AS) into the RIP routing instance.";
      leaf asn {
        type inet:as-number;
        description
          "BFP autonomous system (AS) number.";
      }
      uses redistribute-route-policy-attributes;
    }
    container cg-nat {
      presence
```

```
        "Present if Carrier Grade Network Address Translation
        (CGNAT) routes are redistributed.";
    description
        "Carrier Grade Network Address Translation (CGNAT)
        routes.";
    uses redistribute-route-policy-attributes;
}
container connected {
    presence
        "Present if directly attached network routes are
        redistributed.";
    description
        "Redistributes directly attached networks into the RIP
        routing instance.";
    uses redistribute-route-policy-attributes;
}
container ipsec {
    presence
        "Present if IP security routing instance routes
        are redistributed.";
    description
        "Redistributes routes from the IP security routing
        instance into the RIP routing instance.";
    uses redistribute-route-policy-attributes;
}
list isis {
    key "instance";
    description
        "Redistributes ISIS routes.";
    leaf instance {
        type leafref {
            path "../..../..../rt:control-plane-protocol/rt:name";
        }
        must "../..../..../rt:control-plane-protocol"
            + "[rt:name = current()]/type = 'isis' " {
            description
                "The type of the routing protocol must be 'isis'";
        }
    }
    description
        "Redistributes routes from the specified IS-IS routing
        instance into the RIP routing instance.";
```



```
    }
  leaf level {
    type enumeration {
      enum 1 {
        description "ISIS level 1 routes.";
      }
      enum 2 {
        description "ISIS level 1 routes.";
      }
      enum 1-2 {
        description "ISIS level 1-2 routes.";
      }
    }
    description
      "ISIS level.";
  }
  uses redistribute-route-policy-attributes;
}
container nat {
  presence
    "Present if Network Address Translation (NAT) routes
    are redistributed.";
  description
    "Redistributes Network Address Translation (NAT)
    routes into the RIP routing instance.";
  uses redistribute-route-policy-attributes;
}
list ospfv2 {
  when "../..../rt:type = 'rip:ripv2'" {
    description
      "Applicable to RIPv2.";
  }
  key "instance";
  description
    "Redistributes routes from the specified OSPF routing
    instance into the RIP routing instance.";
  leaf instance {
    type leafref {
      path "../..../..../rt:control-plane-protocol/rt:name";
    }
    must "../..../..../rt:control-plane-protocol"
```

```
    + "[rt:name = current()]/type = 'ospfv2'" {
      description
        "The type of the routing protocol must be 'ospfv2'";
    }
  description
    "OSPF instance ID. Redistributes routes from the
    specified OSPF routing instance into the RIP routing
    instance. ";
}
leaf route-type {
  type ospf:route-type;
  description
    "Redistributes only those OSPF routes matching the
    specified route type into the RIP routing instance.";
}
uses redistribute-route-policy-attributes;
}
list ospfv3 {
  when "../..../rt:type = 'rip:ripng'" {
    description
      "Applicable to RIPng.";
  }
  key "instance";
  description
    "Redistributes routes from the specified OSPF routing
    instance into the RIP routing instance.";
  leaf instance {
    type leafref {
      path "../..../..../rt:control-plane-protocol/rt:name";
    }
    must "../..../..../rt:control-plane-protocol"
      + "[rt:name = current()]/type = 'ospfv3'" {
      description
        "The type of the routing protocol must be 'ospfv3'";
    }
  }
  description
    "OSPF instance ID. Redistributes routes from the
    specified OSPF routing instance into the RIP routing
    instance. ";
}
leaf route-type {
```

```
    type ospf:route-type;
    description
      "Redistributes only those OSPF routes matching the
       specified route type into the RIP routing instance.";
  }
  uses redistribute-route-policy-attributes;
}
list ripv2 {
  when "../..../rt:type = 'rip:ripv2'" {
    description
      "Applicable to RIPv2.";
  }
  key "instance";
  description
    "Redistributes routes from another RIP routing instance
     into the current RIP routing instance.";
  leaf instance {
    type leafref {
      path "../..../..../rt:control-plane-protocol/rt:name";
    }
    must "../..../..../rt:control-plane-protocol"
      + "[rt:name = current()]/type = 'ripv2'" {
      description
        "The type of the routing protocol must be 'ripv2'";
    }
    description
      "Redistributes routes from the specified RIP routing
       instance into the RIP routing instance.";
  }
  uses redistribute-route-policy-attributes;
}
list ripng {
  when "../..../rt:type = 'rip:ripng'" {
    description
      "Applicable to RIPng.";
  }
  key "instance";
  description
    "Redistributes routes from another RIPng routing instance
     into the current RIPng routing instance.";
  leaf instance {
```

```
    type leafref {
      path "../..../..../rt:control-plane-protocol/rt:name";
    }
    must "../..../..../rt:control-plane-protocol"
      + "[rt:name = current()]/type = 'ripng'" {
      description
        "The type of the routing protocol must be 'ripng'";
    }
    description
      "Redistributes routes from the specified RIPng routing
        instance into the RIPng routing instance.";
  }
  uses redistribute-route-policy-attributes;
}
container static {
  presence "Present if redistributing static routes.";
  description
    "Redistributes static routes into the RIP routing
      instance.";
  uses redistribute-route-policy-attributes;
}
} // redistribute
} // redistribute-container

grouping redistribute-route-policy-attributes {
  description
    "Attributes for redistributing a route policy.";
  leaf metric {
    type uint8 {
      range 0..16;
    }
    description
      "Metric used for the redistributed route. If a metric is
        not specified, the metric configured with the
        default-metric attribute in RIP router configuration is
        used. If the default-metric attribute has not been
        configured, the default metric for redistributed routes
        is 0.";
  }
  leaf route-policy {
    type route-policy-ref;
  }
}
```

```
    description
      "Applies the conditions of the specified route policy to
       routes that are redistributed into the RIP routing
       instance.";
  }
} // redistribute-route-policy-attributes

grouping timers-container {
  description
    "Container for settings of basic timers";
  container timers {
    must "invalid-interval >= (update-interval * 3)" {
      description
        "invalid-interval must be at least three times the value
         for the update-interval argument.";
    }
    must "flush-interval > invalid-interval" {
      description
        "flush-interval must be larger than the value for the
         invalid-interval argument";
    }
  }
  description
    "Timers for the specified RIP or RIPng instance or
     interface.";
  leaf update-interval {
    type uint16 {
      range 1..32767;
    }
    units seconds;
    default 30;
    description
      "Interval at which RIP or RIPng updates are sent.";
  }
  leaf invalid-interval {
    type uint16 {
      range 1..32767;
    }
    units seconds;
    default 180;
    description
      "Interval before a route is declared invalid after no
```

```
        updates are received. This value is at least three times
        the value for the update-interval argument.";
    }
    leaf holddown-interval {
        type uint16 {
            range 1..32767;
        }
        units seconds;
        default 180;
        description
            "Interval before better routes are released.";
    }
    leaf flush-interval {
        type uint16 {
            range 1..32767;
        }
        units seconds;
        default 240;
        description
            "Interval before a route is flushed from the routing
            table. This value must be larger than the value for the
            invalid-interval argument.";
    }
} // timers
}

grouping global-attributes {
    description
        "Global configuration and state attributes.";
    uses originate-default-route-container;

    leaf default-metric {
        type uint8 {
            range 0..16;
        }
        default 0;
        description
            "Set the default metric.";
    }

    leaf distance {
```

```
    type uint8 {
      range 1..255;
    }
    default 120;
    description
      "The administrative distance of the RIP or RIPng for the
       current RIP or RIPng instance.";
  }

  leaf triggered-update-threshold {
    type uint8 {
      range 1..30;
    }
    units seconds;
    default 5;
    description
      "This attribute is used to suppress triggered updates.
       When the arrival of a regularly scheduled update matches the
       number of seconds or is less than the number seconds
       configured with this attribute, the triggered update is
       suppressed.";
  }

  leaf maximum-paths {
    type uint8 {
      range 1..16;
    }
    default 8;
    description
      "The number of multiple equal-cost RIP or RIPng routes
       that can be used as the best paths for balancing the load
       of outgoing traffic packets.";
  }

  leaf output-delay {
    type uint8 {
      range 1..50;
    }
    units milliseconds;
    description
      "A delay time between packets sent in multipacket
```

```
        RIP or RIPng updates.";
    }
} // global-attributes

grouping distribute-lists {
  description
    "Grouping for distribute lists.";
  list distribute-list {
    key "prefix-set-name direction";
    description
      "List of distribute-lists, which are used to filter in-coming
      or out-going routing updates.";

    leaf prefix-set-name {
      type prefix-set-ref;
      description
        "Reference to a prefix list to be applied to RIP or
        RIPng packets.";
    }

    leaf direction {
      type enumeration {
        enum "in" {
          description
            "Apply the distribute-list to in-coming routes.";
        }
        enum "out" {
          description
            "Apply the distribute-list to out-going routes.";
        }
      }
      description
        "Direction of the routing updates.";
    }
  }

  leaf if-name {
    type if:interface-ref;
    description
      "Reference to an interface to which the prefix list is
      applied.";
  }
}
```

```
    }
  } // distribute-lists

  grouping route-attributes {
    description
      "Grouping for route attributes.";
    leaf redistributed {
      type boolean;
      description
        "Redistributed routes";
    }

    leaf route-type {
      type enumeration {
        enum connected {
          description "Connected route.";
        }
        enum external {
          description "External route.";
        }
        enum external-backup {
          description "External backup route.";
        }
        enum rip {
          description "RIP route.";
        }
      }
      description
        "Route type.";
    }
    leaf metric {
      type uint8 {
        range 0..16;
      }
      description "Route metric.";
    }
    leaf expire-time {
      type uint16;
      description "Expiration time.";
    }
    leaf deleted {
```

```
    type boolean;
    description "Deleted route.";
}
leaf holddown {
    type boolean;
    description "Holddown route.";
}
leaf need-triggered-update {
    type boolean;
    description "The route needs triggered update.";
}
leaf inactive {
    type boolean;
    description "The route is inactive.";
}
leaf flush-expire-before-holddown {
    type boolean;
    description
        "The flush timer expired before holddown time.";
}
} // route-attribute

/*
 * Configuration data nodes
 */

augment "/rt:routing/rt:control-plane-protocols/"
+ "rt:control-plane-protocol" {
    when "rt:type = 'rip:ripv2' or rt:type = 'rip:ripng'" {
        description
            "This augment is only valid for a routing protocol instance
            of RIP (type 'ripv2' or 'ripng').";
    }
    description "RIP augmentation.";

    container rip {
        description
            "RIP configuration data.";

        uses global-attributes;
        uses distribute-lists;
    }
}
```

```
uses redistribute-container;
uses timers-container;

list interface {
  key "interface";
  description
    "List of RIP interfaces.";
  leaf interface {
    type if:interface-ref;
    must "(../../rt:type = 'rip:ripv2' and "
      + "/if:interfaces/if:interface[name=current()]/"
      + "ip:ipv4) or "
      + "(../../rt:type = 'rip:ripng' and "
      + "/if:interfaces/if:interface[name=current()]/"
      + "ip:ipv6)" {
      error-message "Invalid interface type.";
      description
        "RIPv2 can be enabled on IPv4 interfae, and
        RIPng can be enabled on IPv6 interface.";
    }
    description
      "Enable RIP on this interface.";
  }
}

container authentication {
  when "../../rt:type = 'rip:ripv2'" {
    description "Only applicable to RIPv2.";
  }
  description
    "Enables authentication and specifies the authentication
    scheme for the RIP interface";
  choice auth-type-selection {
    description
      "Specify the authentication scheme.
      The use of the key-chain reference here is:
      1) Designed to align with other proposed protocol
      models.
      2) Not finalized, pending resolution of alignment with
      the RFC published KeyTables information model.";
    case auth-key-chain {
      leaf key-chain {
```

```
        type key-chain:key-chain-ref;
        description
            "key-chain name";
    }
}
case auth-key {
    leaf key {
        type string;
        description
            "Key string in ASCII format.";
    }
    container crypto-algorithm {
        uses key-chain:crypto-algorithm-types;
        description
            "Cryptographic algorithm associated with key.";
    }
}
}
}

container bfd {
    if-feature bfd;
    description "BFD operation.";
    leaf enabled {
        type boolean;
        description
            "True if BFD is enabled for the interface.";
    }
    uses bfd:bfd-grouping-base-cfg-parms {
        if-feature bfd-protocol-parms;
    }
}

leaf cost {
    type uint8 {
        range 1..16;
    }
    default 1;
    description
        "Interface cost.";
}
}
```

```
container neighbors {
  if-feature neighbor-configuration;
  description
    "Specifies the RIP neighbors. Useful for a non-broadcast
    multiple access (NBMA) network.";
  list neighbor {
    key "address";
    description
      "Specify a RIP neighbor on a non-broadcast network.";
    leaf address {
      type inet:ip-address;
      description "Neighbor IP address.";
    }
  }
}

leaf no-listen {
  type empty;
  description
    "Disable the specified interface to receive (listen to)
    and process RIP or RIPng packets.";
}

leaf no-supply {
  type empty;
  description
    "Disables sending of RIP or RIPng packets on the
    specified interface.";
}

uses originate-default-route-container;

leaf split-horizon {
  type enumeration {
    enum simple {
      description
        "Enables simple split-horizon processing.";
    }
    enum poison {
      description

```

```
        "Enables split-horizon processing with poison
          reverse.";
      }
    }
    default simple;
    description
      "Enables RIP or RIPng split-horizon processing on the
        specified interface.";
  }

  container summary-address {
    description
      "Summarizes information about RIP or RIPng routes sent
        over the specified interface in RIP or RIPng update
        packets.";
    leaf address {
      type inet:ip-prefix;
      description
        "IPv4 address, in the form A.B.C.D, and the prefix
          length, separated by the slash (/) character;
          or IPv6 address, in the form A:B:C:D:E:F:G:H, and the
          prefix length, separated by the slash (/) character.";
    }
    leaf metric {
      type uint8 {
        range 0..16;
      }
      description
        "Metric used for the route. If this attribute is not
          used, the value set through the default-metric
          attribute in RIP or RIPng router configuration is
          used for the route. ";
    }
  }
}

uses timers-container;
} // interface
} // container rip
}

/*
```

```
* Operational state data nodes
*/

augment "/rt:routing-state/rt:control-plane-protocols/"
+ "rt:control-plane-protocol" {
  when "rt:type = 'rip:ripv2' or rt:type = 'rip:ripng'" {
    description
      "This augment is only valid for a routing protocol instance
      of type 'ripv2' or 'ripng'.";
  }
  description
    "RIP state.";
  container rip {
    description "RIP operational state.";

    uses global-attributes;
    uses distribute-lists;

    leaf next-triggered-update {
      type uint32;
      description
        "Next triggered update.";
    }
    leaf num-of-routes {
      type uint32;
      description
        "The number of routes.";
    }
  }

  uses timers-container;

  list interface {
    key "interface";
    description
      "List of RIP interfaces.";
    leaf interface {
      type if:interface-ref;
      description
        "Enable RIP on this interface.";
    }
    leaf oper-status {
```

```
type enumeration {
  enum up {
    description
      "RIPv2 or RIPng is operational on this interface.";
  }
  enum down {
    description
      "RIPv2 or RIPng is not operational on this
      interface.";
  }
}
description
  "Operational state.";
}
leaf cost {
  type uint8 {
    range 1..16;
  }
  default 1;
  description
    "Interface cost.";
}
leaf listen {
  type boolean;
  description
    "The interface is enabled to receive (listen to)
    and process RIP or RIPng packets.";
}
leaf next-full-update {
  type uint32;
  description
    "Next full update time.";
}
leaf originate-default-route {
  type boolean;
  description
    "'true' if originating default route is enabled.";
}
leaf poison-reverse {
  type boolean;
  description
```

```
        "'true' if Split Horizon with Poisoned Reverse is
        enabled.";
    }
    leaf split-horizon {
        type boolean;
        description
            "'true' if Split Horizon processing is enabled.";
    }
    leaf supply {
        type boolean;
        description
            "The interface is enabled to supply (send) RIP or RIPng
            packets.";
    }
    leaf valid-address {
        type boolean;
        description
            "The interface has a valid address.";
    }
    uses timers-container;

    container statistics {
        if-feature interface-statistics;
        description
            "Interface statistic counters.";
        leaf discontinuity-time {
            type yang:date-and-time;
            description
                "The time on the most recent occasion at which any one
                or more of the statistic counters suffered a
                discontinuity. If no such discontinuities have
                occurred since the last re-initialization of the local
                management subsystem, then this node contains the time
                the local management subsystem re-initialized
                itself.";
        }
        leaf bad-packets-rcvd {
            type yang:counter32;
            description
                "The number of RIP invalid packets received by
                the RIP process which were subsequently discarded
```

```
        for any reason (e.g. a version 0 packet, or an
        unknown command type).";
    }
    leaf bad-routes-rcvd {
        type yang:counter32;
        description
            "The number of routes, in valid RIP packets,
            which were ignored for any reason (e.g. unknown
            address family, or invalid metric).";
    }
    leaf updates-sent {
        type yang:counter32;
        description
            "The number of triggered RIP updates actually
            sent on this interface. This explicitly does
            NOT include full updates sent containing new
            information.";
    }
}
} // interface

container ipv4 {
    when "../..//rt:type = 'rip:ripv2'" {
        description
            "IPv4 address family is supported by RIPv2.";
    }
    description
        "IPv4 address family information.";
    container neighbors {
        description
            "IPv4 neighbor information.";
        list neighbor {
            key "ipv4-address";
            description
                "A RIPv2 RIP neighbor.";

            leaf ipv4-address {
                type inet:ipv4-address;
                description
                    "IP address that a RIP neighbor is using as its
                    source address.";
            }
        }
    }
}
```

```
    }
    leaf last-update {
      type yang:date-and-time;
      description
        "The time when the most recent RIP update was
        received from this neighbor.";
    }
    leaf bad-packets-rcvd {
      type yang:counter32;
      description
        "The number of RIP invalid packets received from
        this neighbor which were subsequently discarded
        for any reason (e.g. a version 0 packet, or an
        unknown command type).";
    }
    leaf bad-routes-rcvd {
      type yang:counter32;
      description
        "The number of routes received from this neighbor,
        in valid RIP packets, which were ignored for any
        reason (e.g. unknown address family, or invalid
        metric).";
    }
  } // neighbor
} // neighbors
container routes {
  description
    "IPv4 route information.";
  list route {
    key "ipv4-prefix";
    description
      "A RIPv2 IPv4 route.";

    leaf ipv4-prefix {
      type inet:ipv4-prefix;
      description
        "IP address (in the form A.B.C.D) and prefix length,
        separated by the slash (/) character. The range of
        values for the prefix-length is 0 to 32.";
    }
  }
  leaf next-hop {
```

```
        type inet:ipv4-address;
        description
            "Next hop IPv4 address.";
    }
    leaf interface {
        type if:interface-ref;
        description
            "The interface that the route uses.";
    }
    uses route-attributes;
} // route
} // routes
} // ipv4
container ipv6 {
    when "../..//rt:type = 'rip:ripng'" {
        description
            "IPv6 address family is supported by RIPng.";
    }
    description
        "IPv6 address family information.";
    container neighbors {
        description
            "IPv6 neighbor information.";
        list neighbor {
            key "ipv6-address";
            description
                "A RIPv2 RIP neighbor.";

            leaf ipv6-address {
                type inet:ipv6-address;
                description
                    "IP address that a RIP neighbor is using as its
                    source address.";
            }
            leaf last-update {
                type yang:date-and-time;
                description
                    "The time when the most recent RIP update was
                    received from this neighbor.";
            }
            leaf bad-packets-rcvd {
```

```
    type yang:counter32;
    description
      "The number of RIP invalid packets received from
      this neighbor which were subsequently discarded
      for any reason (e.g. a version 0 packet, or an
      unknown command type).";
  }
  leaf bad-routes-rcvd {
    type yang:counter32;
    description
      "The number of routes received from this neighbor,
      in valid RIP packets, which were ignored for any
      reason (e.g. unknown address family, or invalid
      metric).";
  }
} // neighbor
} // neighbors
container routes {
  description
    "IPv6 route information.";
  list route {
    key "ipv6-prefix";
    description
      "A RIPng IPv6 route.";

    leaf ipv6-prefix {
      type inet:ipv6-prefix;
      description
        "IP address (in the canonical format defined in
        RFC5952) and prefix length, separated by the slash
        (/) character. The range of values for the
        prefix-length is 0 to 128.";
    }
    leaf next-hop {
      type inet:ipv6-address;
      description
        "Next hop IPv6 address.";
    }
  }
  leaf interface {
    type if:interface-ref;
    description
```

```
        "The interface that the route uses.";
    }
    uses route-attributes;
} // route
} // routes
} // ipv6

container statistics {
  if-feature global-statistics;
  description
    "Global statistic counters.";
  leaf discontinuity-time {
    type yang:date-and-time;
    description
      "The time on the most recent occasion at which any one
      or more of the statistic counters suffered a
      discontinuity. If no such discontinuities have occurred
      since the last re-initialization of the local
      management subsystem, then this node contains the time
      the local management subsystem re-initialized itself.";
  }
  leaf requests-rcvd {
    type yang:counter32;
    description
      "The number of requests received by RIP.";
  }
  leaf requests-sent {
    type yang:counter32;
    description
      "The number of requests sent by RIP.";
  }
  leaf responses-rcvd {
    type yang:counter32;
    description
      "The number of responses received by RIP.";
  }
  leaf responses-sent {
    type yang:counter32;
    description
      "The number of responses sent by RIP.";
  }
}
```

```
    }
  } // rip
} // augment

/*
 * RPCs
 */

rpc clear-rip-route {
  description
    "Clears RIP routes from the IP routing table and routes
    redistributed into the RIP protocol for the specified RIP
    instance or for all RIP instances in the current context.";

  input {
    leaf rip-instance {
      type leafref {
        path "/rt:routing/rt:control-plane-protocols/"
          + "rt:control-plane-protocol/rt:name";
      }
      description
        "Instance name identifying a specific RIP instance.
        This leaf is optional for the rpc.
        If it is specified, the rpc will clear all routes in the
        specified RIP instance;
        if it is not specified, the rpc will clear all routes in
        all RIP instances.";
    }
  }
} // rcp clear-rip-route
}
<CODE ENDS>
```

[4.](#) IANA Considerations

RFC Ed.: In this section, replace all occurrences of 'XXXX' with the actual RFC number (and remove this note).

This document registers the following namespace URIs in the IETF XML registry [[RFC3688](#)]:

```
-----  
name:          ietf-rip  
namespace:     urn:ietf:params:xml:ns:yang:ietf-rip  
prefix:        rip  
reference:     RFC XXXX  
-----
```

[5.](#) Security Considerations

The configuration, state, and action data defined in this document are designed to be accessed via the NETCONF protocol [[RFC6241](#)]. The data-model by itself does not create any security implications. The security considerations for the NETCONF protocol are applicable. The NETCONF protocol used for sending the data supports authentication and encryption.

[6.](#) References

[6.1.](#) Normative References

- [RFC6020] Bjorklund, M., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), October 2010.
- [RFC6991] Schoenwaelder, J., "Common YANG Data Types", [RFC 6991](#), July 2013.
- [RFC6241] Enns, R., Bjorklund, M., Schoenwaelder, J., and A. Bierman, "Network Configuration Protocol (NETCONF)", [RFC 6241](#), June 2011.
- [RFC2453] G. Malkin, "RIP Version 2", [RFC2453](#), November 1998.
- [RFC2080] G. Malkin and R. Minnear, "RIPng for IPv6", [RFC2080](#), January 1997.
- [RFC1724] G. Malkin and F. Baker, "RIP Version 2 MIB Extension", [RFC1724](#), November 1994.

[6.2.](#) Informative References

- [RFC6087] Bierman, A., "Guidelines for Authors and Reviewers of YANG Data Model Documents", [RFC 6087](#), January 2011.

Internet-Draft

[draft-ietf-rtgwg-yang-rip-02.txt](#)

July 2016

Authors' Addresses

Xufeng Liu
Ericsson / Kuarto Technologies Inc.
8281 Greensboro Drive, Suite 200
McLean, VA 22102
USA

Email: xliu@kuatrotech.com

Prateek Sarma
Ericsson India Global Services Pvt. Ltd.
Fern Icon, Survey No 28 and 36/5, Doddanakundi Village
Bangalore, Karnataka 560037
India

Email: prateek.sarda@ericsson.com

Vikram Choudhary
Huawei Technologies
Divyashree Techno Park, Whitefield
Bangalore, Karnataka 560037
India

Email: vikram.choudhary@huawei.com

Liu

Expires January 18, 2017

[Page 38]