

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: August 4, 2018

X. Liu
Jabil
P. Sarda
Ericsson
V. Choudhary
Individual
January 31, 2018

**A YANG Data Model for Routing Information Protocol (RIP)
draft-ietf-rtgwg-yang-rip-09**

Abstract

This document describes a data model for the management of the Routing Information Protocol (RIP). Both RIP version 2 and RIPng are covered. The data model includes definitions for configuration, operational state, and Remote Procedure Calls (RPCs).

The YANG model in this document conforms to the Network Management Datastore Architecture (NMDA).

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 4, 2018.

Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents

carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Terminology	2
1.2.	Tree Diagrams	3
1.3.	Prefixes in Data Node Names	3
2.	Design of the Data Model	3
2.1.	Scope of the Model	3
2.2.	Relation with Core Routing Framework	4
2.3.	Protocol Configuration	4
2.4.	Protocol States	5
2.5.	RPC Operations	6
2.6.	Notifications	6
2.7.	Optional Features	6
3.	Tree Structure	6
4.	YANG Module	10
5.	IANA Considerations	34
6.	Security Considerations	34
7.	References	35
7.1.	Normative References	35
7.2.	Informative References	37
Appendix A.	Data Tree Example	39
	Authors' Addresses	43

[1.](#) Introduction

This document introduces a YANG [[RFC7950](#)] data model for the Routing Information Protocol (RIP) [[RFC2453](#)][[RFC2080](#)]. RIP was designed to work as an Interior Gateway Protocol (IGP) in moderate-size Autonomous Systems (AS).

This YANG model supports both RIP version 2 and RIPng. RIP version 2 (defined in [[RFC2453](#)]) supports IPv4. RIPng (defined in [[RFC2080](#)]) supports IPv6.

[1.1.](#) Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

The following terms are defined in [[RFC7950](#)] and are not redefined here:

- o augment
- o data model
- o data node

1.2. Tree Diagrams

A simplified graphical representation of the data model is used in this document. The meaning of the symbols in these diagrams is defined in [[I-D.ietf-netmod-yang-tree-diagrams](#)].

1.3. Prefixes in Data Node Names

In this document, names of data nodes, actions, and other data model objects are often used without a prefix, as long as it is clear from the context in which YANG module each name is defined. Otherwise, names are prefixed using the standard prefix associated with the corresponding YANG module, as shown in Table 1.

Prefix	YANG module	Reference
yang	ietf-yang-types	[RFC6991]
inet	ietf-inet-types	[RFC6991]
if	ietf-interfaces	[I-D.ietf-netmod-rfc7223bis]
ip	ietf-ip	[I-D.ietf-netmod-rfc7277bis]
rt	ietf-routing	[I-D.ietf-netmod-rfc8022bis]
bfd-types	ietf-bfd-types	[I-D.ietf-bfd-yang]
isis	ietf-isis	[I-D.ietf-isis-yang-isis-cfg]
key-chain	ietf-key-chain	[RFC8177]
ospf	ietf-ospf	[I-D.ietf-ospf-yang]

Table 1: Prefixes and Corresponding YANG Modules

2. Design of the Data Model

2.1. Scope of the Model

The model covers RIP version 2 [[RFC2453](#)] and RIPng [[RFC2080](#)] protocols. The model is designed to be implemented on a device where RIP version 2 or RIPng is implemented, and can be used to:

- o Configure the RIP version 2 or RIPng protocol.

- o Manage the protocol operational behaviors.
- o Retrieve the protocol operational status.

The capabilities describe in [[RFC1724](#)] are covered.

2.2. Relation with Core Routing Framework

This model augments the core routing data model "ietf-routing" specified in [[I-D.ietf-netmod-rfc8022bis](#)].

```

+--rw routing
  +--rw router-id?
  +--rw control-plane-protocols
  |   +--rw control-plane-protocol* [type name]
  |       +--rw type
  |       +--rw name
  |       +--rw rip      <= Augmented by this Model
  |       ...

```

The "rip" container instantiates a RIP protocol entity that supports RIP version 2 or RIPng. Depending on the implementation of "ietf-routing", a RIP instance MAY belong to a logical router or network instance.

2.3. Protocol Configuration

The model structure for the protocol configuration is as shown below:

```

augment /rt:routing/rt:control-plane-protocols/
rt:control-plane-protocol:
  +--rw rip
    +--rw <per instance configuration>
    +--rw interface* [interface]
      +--rw interface          if:interface-ref
      +--rw <per interface configuration>
      +--rw neighbors {explicit-neighbors}?
      |   +--rw neighbor* [address]
      |       +--rw address    inet:ip-address
      |       +--rw <per neighbor configuration>

```

The model allows to configure the following protocol entities:

- o Protocol instance (RIP version 2 or RIPng)

- o Interface
- o Neighbor

2.4. Protocol States

The model structure for the protocol states is as shown below:

```
augment /rt:routing/rt:control-plane-protocols/
rt:control-plane-protocol:
  +--rw rip
    +--ro <per instance operational states>
    +--rw interface* [interface]
      | +--rw interface                               if:interface-ref
      | +--ro <per instance operational states>
      | +--ro statistics {interface-statistics}?
      |   +--ro <per instance statistics>
    +--ro ipv4
      | +--ro neighbors
      | | +--ro neighbor* [ipv4-address]
      | |   +--ro <per neighbor IPv4 operational states>
      | +--ro routes
      |   +--ro route* [ipv4-prefix]
      |   +--ro <IPv4 RIP route states>
    +--ro ipv6
      | +--ro neighbors
      | | +--ro neighbor* [ipv6-address]
      | |   +--ro <per neighbor IPv6 operational states>
      | +--ro routes
      |   +--ro route* [ipv6-prefix]
      |   +--ro ipv6-prefix                               inet:ipv6-prefix
      |   +--ro <IPv4 RIP route states>
    +--ro statistics {global-statistics}?
      +--ro <per instance statistics>
```

This model conforms to the Network Management Datastore Architecture (NMDA) [[I-D.ietf-netmod-revised-datastores](#)]. The operational state data is combined with the associated configuration data in the same hierarchy [[I-D.ietf-netmod-rfc6087bis](#)]. When protocol states are retrieved from the NMDA operational state datastore, the returned states cover all "config true" (rw) and "config false" (ro) nodes defined in the schema.

The model allows to retrieve protocol states at the following levels:

- o Protocol instance (RIP version 2 or RIPng)

- o Interface
- o Neighbor
- o Route

2.5. RPC Operations

This model defines one RPC "clear-rip-route" that can be used to clear RIP routes from the routing table.

2.6. Notifications

This model does not define RIP specific notifications. To enable notifications, the mechanism defined in [\[I-D.ietf-netconf-subscribed-notifications\]](#) and [\[I-D.ietf-netconf-yang-push\]](#) can be used. This mechanism currently allows the user to:

- o Subscribe notifications on a per client basis.
- o Specify subtree filters or xpath filters so that only interested contents will be sent.
- o Specify either periodic or on-demand notifications.

2.7. Optional Features

This model defines several features are beyond the basic RIP configuration and it is the responsibility of each vendor to decide whether to support a given feature on a device.

3. Tree Structure

This document defines the YANG module "ietf-rip", which has the following tree structure:

```
module: ietf-rip
  augment /rt:routing/rt:control-plane-protocols
  /rt:control-plane-protocol:
    +--rw rip
      +--rw originate-default-route
        |   +--rw enabled?          boolean
        |   +--rw route-policy?    route-policy-ref
      +--rw default-metric?         uint8
      +--rw distance?               uint8
      +--rw triggered-update-threshold? uint8
      +--rw maximum-paths?          uint8
```



```

+--rw output-delay?                uint8
+--rw distribute-list* [prefix-set-name direction]
|  +--rw prefix-set-name            prefix-set-ref
|  +--rw direction                  enumeration
|  +--rw if-name?                   if:interface-ref
+--rw redistribute
|  +--rw bgp* [asn]
|  |  +--rw asn                     inet:as-number
|  |  +--rw metric?                 uint8
|  |  +--rw route-policy?           route-policy-ref
|  +--rw cg-nat!
|  |  +--rw metric?                 uint8
|  |  +--rw route-policy?           route-policy-ref
|  +--rw connected!
|  |  +--rw metric?                 uint8
|  |  +--rw route-policy?           route-policy-ref
|  +--rw ipsec!
|  |  +--rw metric?                 uint8
|  |  +--rw route-policy?           route-policy-ref
|  +--rw isis* [instance]
|  |  +--rw instance
|  |  |  -> ../../../../../../rt:control-plane-protocol/name
|  |  +--rw level?                  enumeration
|  |  +--rw metric?                 uint8
|  |  +--rw route-policy?           route-policy-ref
|  +--rw nat!
|  |  +--rw metric?                 uint8
|  |  +--rw route-policy?           route-policy-ref
|  +--rw ospfv2* [instance]
|  |  +--rw instance
|  |  |  -> ../../../../../../rt:control-plane-protocol/name
|  |  +--rw route-type?             ospf:route-type
|  |  +--rw metric?                 uint8
|  |  +--rw route-policy?           route-policy-ref
|  +--rw ospfv3* [instance]
|  |  +--rw instance
|  |  |  -> ../../../../../../rt:control-plane-protocol/name
|  |  +--rw route-type?             ospf:route-type
|  |  +--rw metric?                 uint8
|  |  +--rw route-policy?           route-policy-ref
|  +--rw ripv2* [instance]
|  |  +--rw instance
|  |  |  -> ../../../../../../rt:control-plane-protocol/name
|  |  +--rw metric?                 uint8
|  |  +--rw route-policy?           route-policy-ref
|  +--rw ripng* [instance]
|  |  +--rw instance
|  |  |  -> ../../../../../../rt:control-plane-protocol/name

```



```

| | +--rw metric?          uint8
| | +--rw route-policy?    route-policy-ref
| +--rw static!
|   +--rw metric?          uint8
|   +--rw route-policy?    route-policy-ref
+--rw timers
| +--rw update-interval?    uint16
| +--rw invalid-interval?   uint16
| +--rw holddown-interval?  uint16
| +--rw flush-interval?     uint16
+--rw interfaces
| +--rw interface* [interface]
|   +--rw interface          if:interface-ref
|   +--rw authentication
|     +--rw (auth-type-selection)?
|       +--:(auth-key-chain)
|         +--rw key-chain?
key-chain:key-chain-ref
|       +--:(auth-key)
|         +--rw key?          string
|         +--rw crypto-algorithm? identityref
+--rw bfd {bfd}?
|   +--rw enable?            boolean
|   +--rw local-multiplier?   multiplier
|   +--rw (interval-config-type)?
|     +--:(tx-rx-intervals)
|       +--rw desired-min-tx-interval?  uint32
|       +--rw required-min-rx-interval?  uint32
|       +--:(single-interval)
|         +--rw min-interval?            uint32
+--rw cost?                    uint8
+--rw neighbors {explicit-neighbors}?
|   +--rw neighbor* [address]
|     +--rw address      inet:ip-address
+--rw no-listen?              empty
+--rw originate-default-route
|   +--rw enabled?          boolean
|   +--rw route-policy?     route-policy-ref
+--rw passive?                empty
+--rw split-horizon?          enumeration
+--rw summary-address
|   +--rw address?          inet:ip-prefix
|   +--rw metric?           uint8
+--rw timers
|   +--rw update-interval?    uint16
|   +--rw invalid-interval?   uint16
|   +--rw holddown-interval?  uint16
|   +--rw flush-interval?     uint16

```



```

|      +--ro oper-status?          enumeration
|      +--ro next-full-update?     uint32
|      +--ro valid-address?        boolean
|      +--ro statistics {interface-statistics}?
|          +--ro discontinuity-time? yang:date-and-time
|          +--ro bad-packets-rcvd?  yang:counter32
|          +--ro bad-routes-rcvd?   yang:counter32
|          +--ro updates-sent?      yang:counter32
+--ro next-triggered-update?       uint32
+--ro num-of-routes?              uint32
+--ro ipv4
|   +--ro neighbors
|   |   +--ro neighbor* [ipv4-address]
|   |       +--ro ipv4-address      inet:ipv4-address
|   |       +--ro last-update?     yang:date-and-time
|   |       +--ro bad-packets-rcvd? yang:counter32
|   |       +--ro bad-routes-rcvd? yang:counter32
|   +--ro routes
|       +--ro route* [ipv4-prefix]
|       +--ro ipv4-prefix
inet:ipv4-prefix
|   +--ro next-hop?
inet:ipv4-address
|   +--ro interface?
if:interface-ref
|       +--ro redistributed?        boolean
|       +--ro route-type?          enumeration
|       +--ro metric?              uint8
|       +--ro expire-time?         uint16
|       +--ro deleted?             boolean
|       +--ro holddown?            boolean
|       +--ro need-triggered-update? boolean
|       +--ro inactive?            boolean
|       +--ro flush-expire-before-holddown? boolean
+--ro ipv6
|   +--ro neighbors
|   |   +--ro neighbor* [ipv6-address]
|   |       +--ro ipv6-address      inet:ipv6-address
|   |       +--ro last-update?     yang:date-and-time
|   |       +--ro bad-packets-rcvd? yang:counter32
|   |       +--ro bad-routes-rcvd? yang:counter32
|   +--ro routes
|       +--ro route* [ipv6-prefix]
|       +--ro ipv6-prefix
inet:ipv6-prefix
|   +--ro next-hop?
inet:ipv6-address
|   +--ro interface?

```



```
if:interface-ref
|      +--ro redistributed?          boolean
|      +--ro route-type?            enumeration
|      +--ro metric?                uint8
|      +--ro expire-time?           uint16
|      +--ro deleted?               boolean
|      +--ro holddown?              boolean
|      +--ro need-triggered-update?  boolean
|      +--ro inactive?              boolean
|      +--ro flush-expire-before-holddown?  boolean
+--ro statistics {global-statistics}?
  +--ro discontinuity-time?  yang:date-and-time
  +--ro requests-rcvd?      yang:counter32
  +--ro requests-sent?      yang:counter32
  +--ro responses-rcvd?     yang:counter32
  +--ro responses-sent?     yang:counter32

rpcs:
+---x clear-rip-route
+---w input
+---w rip-instance?  leafref
```

4. YANG Module

```
<CODE BEGINS> file "ietf-rip@2018-01-17.yang"
module ietf-rip {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-rip";

  prefix rip;

  import ietf-inet-types {
    prefix "inet";
  }

  import ietf-yang-types {
    prefix "yang";
  }

  import ietf-interfaces {
    prefix "if";
  }

  import ietf-ip {
    prefix "ip";
  }
}
```



```
import ietf-routing {
  prefix "rt";
}

import ietf-key-chain {
  prefix "key-chain";
}

import ietf-bfd-types {
  prefix "bfd-types";
}

import ietf-ospf {
  prefix "ospf";
}

import ietf-isis {
  prefix "isis";
}

organization "IETF Routing Area Working Group (rtgwg)";

contact
  "WG Web:   <http://tools.ietf.org/wg/rgtwg/>
  WG List:  <mailto:rgtwg@ietf.org>

  Editor:   Xufeng Liu
            <mailto:xufeng\_liu@jabil.com>

  Editor:   Prateek Sarda
            <mailto:prateek.sarda@ericsson.com>

  Editor:   Vikram Choudhary
            <mailto:vikschw@gmail.com>;
```

description

"This YANG module defines a model for managing Routing Information Protocol (RIP), including RIP version 2 and RIPng.

Copyright (c) 2018 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.";

```
revision 2018-01-17 {
  description
    "Initial revision.";
  reference
    "RFC XXXX: A YANG Data Model for Routing Information Protocol
    (RIP).
    RFC 2453: RIP Version 2.
    RFC 2080: RIPng for IPv6.
    RFC 1724: RIP Version 2 MIB Extension.";
}

/*
 * Features
 */
feature bfd {
  description
    "This feature indicates that the RIP implementation on the
    system supports BFD (Bidirectional Forwarding Detection).";
}

feature explicit-neighbors {
  description
    "This feature indicates that the system supports explicit
    neighbor configuration on a RIP interface.";
}

feature global-statistics {
  description
    "This feature indicates that the system supports collecting
    global statistic data related to RIP.";
}

feature interface-statistics {
  description
    "This feature indicates that the system supports collecting
    per-interface statistic data related to RIP.";
}

/*
 * Typedefs
 */

typedef prefix-set-ref {
  type string;
  description
```



```
"A type for a reference to a prefix set.
The string value is the name identifier for uniquely
identifying the referenced prefix set, which contains a list
of prefixes that a routing policy can applied. The definition
of such a prefix set is outside the scope of this document.";
}

typedef route-policy-ref {
  type string;
  description
    "A type for a reference to a route policy.
    The string value is the name identifier for uniquely
    identifying the referenced routing policy, which contains one
    or more policy rules that can be used for a routing decision.
    The definition of such a routing policy is outside the scope
    of this document.";
}

/*
 * Identities
 */

identity rip {
  base rt:routing-protocol;
  description "Identity for the RIP routing protocol.";
}

identity ripv2 {
  base rip:rip;
  description "Identity for RIPv2 (RIP version 2).";
}

identity ripng {
  base rip:rip;
  description "Identity for RIPng.";
}

/*
 * Groupings
 */

grouping originate-default-route-container {
  description
    "Containing settings whether to originate the default route
    in RIP routing instance.";
  container originate-default-route {
    description
      "Injects the default route into the RIP (RIPv2 or RIPng)
```



```
        routing instance.";
    leaf enabled {
        type boolean;
        default false;
        description
            "'true' if originating default route is enabled.";
    }
    leaf route-policy {
        type route-policy-ref;
        description
            "The conditions of the route policy are applied to the
            default route.";
    }
}
}

grouping redistribute-container {
    description
        "Container of redistribute attributes.";

    container redistribute {
        description
            "Redistributes routes learned from other routing protocols
            into the RIP routing instance.";
        list bgp {
            key "asn";
            description
                "Redistributes routes from the specified BGP (Border
                Gateway Protocol) autonomous system (AS) into the RIP
                routing instance.";
            leaf asn {
                type inet:as-number;
                description
                    "BGP autonomous system (AS) number.";
            }
            uses redistribute-route-policy-attributes;
        }
        container cg-nat {
            presence
                "Present if Carrier Grade Network Address Translation
                (CGNAT) routes are redistributed.";
            description
                "Carrier Grade Network Address Translation (CGNAT)
                routes.";
            uses redistribute-route-policy-attributes;
        }
        container connected {
            presence
```



```
    "Present if directly attached network routes are
    redistributed.";
  description
    "Redistributes directly attached networks into the RIP
    routing instance.";
  uses redistribute-route-policy-attributes;
}
container ipsec {
  presence
    "Present if IP security routing instance routes
    are redistributed.";
  description
    "Redistributes routes from the IP security routing
    instance into the RIP routing instance.";
  uses redistribute-route-policy-attributes;
}
list isis {
  key "instance";
  description
    "Redistributes IS-IS routes.";
  leaf instance {
    type leafref {
      path "../../../../../rt:control-plane-protocol/rt:name";
    }
    must "derived-from-or-self("
      + "../../../../../rt:control-plane-protocol"
      + "[rt:name = current()]/rt:type, 'isis:isis')" {
      description
        "The type of the routing protocol must be 'isis'";
    }
  }
  description
    "Redistributes routes from the specified IS-IS routing
    instance into the RIP routing instance.";
}
leaf level {
  type enumeration {
    enum 1 {
      description "IS-IS level 1 routes.";
    }
    enum 2 {
      description "IS-IS level 2 routes.";
    }
    enum 1-2 {
      description "IS-IS level 1-2 routes.";
    }
  }
}
description
  "IS-IS level.";
```



```
    }
    uses redistribute-route-policy-attributes;
  }
  container nat {
    presence
      "Present if Network Address Translation (NAT) routes
       are redistributed.";
    description
      "Redistributes Network Address Translation (NAT)
       routes into the RIP routing instance.";
    uses redistribute-route-policy-attributes;
  }
  list ospfv2 {
    when "derived-from-or-self(..../rt:type, 'rip:ripv2')" {
      description
        "Applicable to RIPv2.";
    }
    key "instance";
    description
      "Redistributes routes from the specified OSPFv2 routing
       instance into the RIPv2 routing instance.";
    leaf instance {
      type leafref {
        path "../..../rt:control-plane-protocol/rt:name";
      }
      must "derived-from-or-self("
        + "../..../rt:control-plane-protocol"
        + "[rt:name = current()]/rt:type, 'ospf:ospfv2')" {
        description
          "The type of the routing protocol must be 'ospfv2'";
      }
      description
        "OSPFv2 instance ID. Redistributes routes from the
         specified OSPFv2 routing instance into the RIPv2 routing
         instance. ";
    }
    leaf route-type {
      type ospf:route-type;
      description
        "Redistributes only those OSPFv2 routes matching the
         specified route type into the RIPv2 routing instance.";
    }
    uses redistribute-route-policy-attributes;
  }
  list ospfv3 {
    when "derived-from-or-self(..../rt:type, 'rip:ripng')" {
      description
        "Applicable to RIPng.";
```



```
}
key "instance";
description
  "Redistributes routes from the specified OSPFv3 routing
   instance into the RIPng routing instance.";
leaf instance {
  type leafref {
    path "../../../../../rt:control-plane-protocol/rt:name";
  }
  must "derived-from-or-self("
    + "../../../../../rt:control-plane-protocol"
    + "[rt:name = current()]/rt:type, 'ospf:ospfv3')\" {
    description
      "The type of the routing protocol must be 'ospfv3'";
  }
  description
    "OSPFv3 instance ID. Redistributes routes from the
     specified OSPFv3 routing instance into the RIPng routing
     instance. ";
}
leaf route-type {
  type ospf:route-type;
  description
    "Redistributes only those OSPFv3 routes matching the
     specified route type into the RIPng routing instance.";
}
uses redistribute-route-policy-attributes;
}
list ripv2 {
  when "derived-from-or-self(../../../../../rt:type, 'rip:ripv2')\" {
    description
      "Applicable to RIPv2.";
  }
  key "instance";
  description
    "Redistributes routes from another RIPv2 routing instance
     into the current RIPv2 routing instance.";
  leaf instance {
    type leafref {
      path "../../../../../rt:control-plane-protocol/rt:name";
    }
    must "derived-from-or-self("
      + "../../../../../rt:control-plane-protocol"
      + "[rt:name = current()]/rt:type, 'rip:ripv2')\" {
      description
        "The type of the routing protocol must be 'ripv2'";
    }
  }
  description
```



```
        "Redistributes routes from the specified RIPv2 routing
        instance into the RIPv2 routing instance.";
    }
    uses redistribute-route-policy-attributes;
}
list ripng {
    when "derived-from-or-self(..../rt:type, 'rip:ripng')" {
        description
            "Applicable to RIPng.";
    }
    key "instance";
    description
        "Redistributes routes from another RIPng routing instance
        into the current RIPng routing instance.";
    leaf instance {
        type leafref {
            path "..../rt:control-plane-protocol/rt:name";
        }
        must "derived-from-or-self("
            + "..../rt:control-plane-protocol"
            + "[rt:name = current()]/rt:type, 'rip:ripng')";
        description
            "The type of the routing protocol must be 'ripng'";
    }
    description
        "Redistributes routes from the specified RIPng routing
        instance into the RIPng routing instance.";
    }
    uses redistribute-route-policy-attributes;
}
container static {
    presence "Present if redistributing static routes.";
    description
        "Redistributes static routes into the RIP routing
        instance.";
    uses redistribute-route-policy-attributes;
}
} // redistribute
} // redistribute-container

grouping redistribute-route-policy-attributes {
    description
        "Attributes for redistributing a route policy.";
    leaf metric {
        type uint8 {
            range 0..16;
        }
    }
    description
```



```
        "Metric used for the redistributed route. If a metric is
        not specified, the metric configured with the
        default-metric attribute in RIP router configuration is
        used. If the default-metric attribute has not been
        configured, the default metric for redistributed routes
        is 1.";
    }
    leaf route-policy {
        type route-policy-ref;
        description
            "Applies the conditions of the specified route policy to
            routes that are redistributed into the RIP routing
            instance.";
    }
} // redistribute-route-policy-attributes

grouping timers-container {
    description
        "Container for settings of basic timers";
    container timers {
        must "invalid-interval >= (update-interval * 3)" {
            description
                "invalid-interval must be at least three times the value
                for the update-interval argument.";
        }
        must "flush-interval > invalid-interval" {
            description
                "flush-interval must be larger than the value for the
                invalid-interval argument";
        }
    }
    description
        "Timers for the specified RIPv2 or RIPv6 instance or
        interface.";
    leaf update-interval {
        type uint16 {
            range 1..32767;
        }
        units seconds;
        default 30;
        description
            "Interval at which RIPv2 or RIPv6 updates are sent.";
    }
    leaf invalid-interval {
        type uint16 {
            range 1..32767;
        }
        units seconds;
        default 180;
```



```
        description
            "Interval before a route is declared invalid after no
            updates are received. This value is at least three times
            the value for the update-interval argument.";
    }
    leaf holddown-interval {
        type uint16 {
            range 1..32767;
        }
        units seconds;
        default 180;
        description
            "Interval before better routes are released.";
    }
    leaf flush-interval {
        type uint16 {
            range 1..32767;
        }
        units seconds;
        default 240;
        description
            "Interval before a route is flushed from the routing
            table. This value must be larger than the value for the
            invalid-interval argument.";
    }
} // timers
}

grouping global-attributes {
    description
        "Global configuration and state attributes.";
    uses originate-default-route-container;

    leaf default-metric {
        type uint8 {
            range 0..16;
        }
        default 1;
        description
            "Set the default metric.";
    }
}

leaf distance {
    type uint8 {
        range 1..255;
    }
    default 120;
    description
```



```
        "The administrative distance of the RIPv2 or RIPv6 for the
        current RIPv2 or RIPv6 instance.";
    }

    leaf triggered-update-threshold {
        type uint8 {
            range 1..30;
        }
        units seconds;
        default 5;
        description
            "This attribute is used to suppress triggered updates.
            When the arrival of a regularly scheduled update matches the
            number of seconds or is less than the number seconds
            configured with this attribute, the triggered update is
            suppressed.";
    }

    leaf maximum-paths {
        type uint8 {
            range 1..16;
        }
        default 8;
        description
            "The number of multiple equal-cost RIPv2 or RIPv6 routes
            that can be used as the best paths for balancing the load
            of outgoing traffic packets.";
    }

    leaf output-delay {
        type uint8 {
            range 1..50;
        }
        units milliseconds;
        description
            "A delay time between packets sent in multipacket
            RIPv2 or RIPv6 updates.";
    }
} // global-attributes

grouping distribute-lists {
    description
        "Grouping for distribute lists.";
    list distribute-list {
        key "prefix-set-name direction";
        description
            "List of distribute-lists, which are used to filter in-coming
            or out-going routing updates.";
    }
}
```



```
    leaf prefix-set-name {
      type prefix-set-ref;
      description
        "Reference to a prefix list to be applied to RIPv2 or
        RIPv6 packets.";
    }

    leaf direction {
      type enumeration {
        enum "in" {
          description
            "Apply the distribute-list to in-coming routes.";
        }
        enum "out" {
          description
            "Apply the distribute-list to out-going routes.";
        }
      }
      description
        "Direction of the routing updates.";
    }

    leaf if-name {
      type if:interface-ref;
      description
        "Reference to an interface to which the prefix list is
        applied.";
    }
  }
} // distribute-lists

grouping route-attributes {
  description
    "Grouping for route attributes.";
  leaf redistributed {
    type boolean;
    description
      "Redistributed routes";
  }
}

leaf route-type {
  type enumeration {
    enum connected {
      description "Connected route.";
    }
    enum external {
      description "External route.";
    }
  }
}
```



```
        enum external-backup {
            description "External backup route.";
        }
        enum rip {
            description "RIP route.";
        }
    }
    description
        "Route type.";
}
leaf metric {
    type uint8 {
        range 0..16;
    }
    description "Route metric.";
}
leaf expire-time {
    type uint16;
    description "Expiration time.";
}
leaf deleted {
    type boolean;
    description "Deleted route.";
}
leaf holddown {
    type boolean;
    description "Holddown route.";
}
leaf need-triggered-update {
    type boolean;
    description "The route needs triggered update.";
}
leaf inactive {
    type boolean;
    description "The route is inactive.";
}
leaf flush-expire-before-holddown {
    type boolean;
    description
        "The flush timer expired before holddown time.";
}
} // route-attribute

/*
 * Configuration data and operational state data nodes
 */

augment "/rt:routing/rt:control-plane-protocols/"
```



```
+ "rt:control-plane-protocol" {
when "derived-from(rt:type, 'rip:rip')" {
  description
    "This augment is only valid for a routing protocol instance
    of RIP (type 'ripv2' or 'ripng').";
}
description "RIP augmentation.";

container rip {
  description
    "RIP data.";

  uses global-attributes;
  uses distribute-lists;
  uses redistribute-container;
  uses timers-container;

  container interfaces {
    description
      "Containing a list of RIP interfaces.";
    list interface {
      key "interface";
      description
        "List of RIP interfaces.";
      leaf interface {
        type if:interface-ref;
        must "(derived-from-or-self("
          + "../...../rt:type, 'rip:ripv2') and "
          + "/if:interfaces/if:interface[if:name=current()]/"
          + "ip:ipv4) or "
          + "(derived-from-or-self("
          + "../...../rt:type, 'rip:ripng') and "
          + "/if:interfaces/if:interface[if:name=current()]/"
          + "ip:ipv6)" {
          error-message "Invalid interface type.";
          description
            "RIPv2 can be enabled on IPv4 interfae, and
            RIPvng can be enabled on IPv6 interface.";
        }
      }
      description
        "Enable RIP on this interface.";
    }
  }

  container authentication {
    when "derived-from-or-self("
      + "../...../rt:type, 'rip:ripv2')" {
      description "Only applicable to RIPv2.";
    }
  }
}
```



```
description
  "Enables authentication and specifies the
  authentication scheme for the RIP interface";
choice auth-type-selection {
  description
    "Specify the authentication scheme.";
  reference
    "RFC8177: YANG Data Model for Key Chains.";
  case auth-key-chain {
    leaf key-chain {
      type key-chain:key-chain-ref;
      description
        "key-chain name.";
    }
  }
  case auth-key {
    leaf key {
      type string;
      description
        "Key string in ASCII format.";
    }
    leaf crypto-algorithm {
      type identityref {
        base key-chain:crypto-algorithm;
      }
      description
        "Cryptographic algorithm associated with key.";
    }
  }
}

container bfd {
  if-feature bfd;
  description "BFD configuration.";
  uses bfd-types:client-cfg-parms;
}

leaf cost {
  type uint8 {
    range 1..16;
  }
  default 1;
  description
    "Interface cost.";
}

container neighbors {
```



```
if-feature explicit-neighbors;
description
  "Specifies the RIP neighbors. Useful for a
   non-broadcast multiple access (NBMA) network.";
list neighbor {
  key "address";
  description
    "Specify a RIP neighbor on a non-broadcast network.";
  leaf address {
    type inet:ip-address;
    description "Neighbor IP address.";
  }
}

leaf no-listen {
  type empty;
  description
    "Disables listening to and processing of RIPv2 or RIPv2
    packets on the specified interface.";
}

uses originate-default-route-container;

leaf passive {
  type empty;
  description
    "Disables sending of RIPv2 or RIPv2 packets on the
    specified interface.";
}

leaf split-horizon {
  type enumeration {
    enum disabled {
      description
        "Disables split-horizon processing.";
    }
    enum simple {
      description
        "Enables simple split-horizon processing.";
    }
    enum poison-reverse {
      description
        "Enables split-horizon processing with poison
        reverse.";
    }
  }
  default simple;
}
```



```
    description
      "Controls RIPv2 or RIPv6 split-horizon processing on
       the specified interface.";
  }

  container summary-address {
    description
      "Summarizes information about RIPv2 or RIPv6 routes
       sent over the specified interface in RIPv2 or RIPv6
       update packets.";
    leaf address {
      type inet:ip-prefix;
      description
        "Specifies the IP address and the prefix length that
         identify the routes to be summarized. The IP address
         can be specified in either IPv4 or IPv6 format, as
         specified in RFC6991.";
    }
    leaf metric {
      type uint8 {
        range 0..16;
      }
      description
        "Metric used for the route. If this attribute is not
         used, the value set through the default-metric
         attribute in RIPv2 or RIPv6 router configuration is
         used for the route. ";
    }
  }
}

uses timers-container;

/* Operational state */
leaf oper-status {
  type enumeration {
    enum up {
      description
        "RIPv2 or RIPv6 is operational on this interface.";
    }
    enum down {
      description
        "RIPv2 or RIPv6 is not operational on this
         interface.";
    }
  }
}
config false;
description
  "Operational state.";
```



```
}
leaf next-full-update {
  type uint32;
  config false;
  description
    "Next full update time.";
}
leaf valid-address {
  type boolean;
  config false;
  description
    "The interface has a valid address.";
}

container statistics {
  if-feature interface-statistics;
  config false;
  description
    "Interface statistic counters.";
  leaf discontinuity-time {
    type yang:date-and-time;
    description
      "The time on the most recent occasion at which any
       one or more of the statistic counters suffered a
       discontinuity. If no such discontinuities have
       occurred since the last re-initialization of the
       local management subsystem, then this node contains
       the time the local management subsystem
       re-initialized itself.";
  }
  leaf bad-packets-rcvd {
    type yang:counter32;
    description
      "The number of RIP invalid packets received by
       the RIP process which were subsequently discarded
       for any reason (e.g. a version 0 packet, or an
       unknown command type).";
  }
  leaf bad-routes-rcvd {
    type yang:counter32;
    description
      "The number of routes, in valid RIP packets,
       which were ignored for any reason (e.g. unknown
       address family, or invalid metric).";
  }
  leaf updates-sent {
    type yang:counter32;
    description
```



```
        "The number of triggered RIP updates actually
        sent on this interface. This explicitly does
        NOT include full updates sent containing new
        information.";
    }
}
} // interface
} // interfaces

/* Operational state */
leaf next-triggered-update {
    type uint32;
    config false;
    description
        "Next triggered update.";
}
leaf num-of-routes {
    type uint32;
    config false;
    description
        "The number of routes.";
}

container ipv4 {
    when "derived-from-or-self(..../rt:type, 'rip:ripv2')" {
        description
            "IPv4 address family is supported by RIPv2.";
    }
    config false;
    description
        "IPv4 address family information.";
    container neighbors {
        description
            "IPv4 neighbor information.";
        list neighbor {
            key "ipv4-address";
            description
                "A RIPv2 neighbor.";

            leaf ipv4-address {
                type inet:ipv4-address;
                description
                    "IP address that a RIP neighbor is using as its
                    source address.";
            }
        }
        leaf last-update {
            type yang:date-and-time;
            description
```



```
        "The time when the most recent RIP update was
          received from this neighbor.";
    }
    leaf bad-packets-rcvd {
        type yang:counter32;
        description
            "The number of RIP invalid packets received from
             this neighbor which were subsequently discarded
             for any reason (e.g. a version 0 packet, or an
             unknown command type).";
    }
    leaf bad-routes-rcvd {
        type yang:counter32;
        description
            "The number of routes received from this neighbor,
             in valid RIP packets, which were ignored for any
             reason (e.g. unknown address family, or invalid
             metric).";
    }
} // neighbor
} // neighbors
container routes {
    description
        "IPv4 route information.";
    list route {
        key "ipv4-prefix";
        description
            "A RIPv2 IPv4 route.";

        leaf ipv4-prefix {
            type inet:ipv4-prefix;
            description
                "IP address (in the form A.B.C.D) and prefix length,
                 separated by the slash (/) character. The range of
                 values for the prefix-length is 0 to 32.";
        }
        leaf next-hop {
            type inet:ipv4-address;
            description
                "Next hop IPv4 address.";
        }
        leaf interface {
            type if:interface-ref;
            description
                "The interface that the route uses.";
        }
        uses route-attributes;
    } // route
}
```



```
    } // routes
  } // ipv4
  container ipv6 {
    when "derived-from-or-self(..../rt:type, 'rip:ripng')" {
      description
        "IPv6 address family is supported by RIPng.";
    }
    config false;
    description
      "IPv6 address family information.";
    container neighbors {
      description
        "IPv6 neighbor information.";
      list neighbor {
        key "ipv6-address";
        description
          "A RIPng neighbor.";

        leaf ipv6-address {
          type inet:ipv6-address;
          description
            "IP address that a RIP neighbor is using as its
             source address.";
        }
        leaf last-update {
          type yang:date-and-time;
          description
            "The time when the most recent RIP update was
             received from this neighbor.";
        }
        leaf bad-packets-rcvd {
          type yang:counter32;
          description
            "The number of RIP invalid packets received from
             this neighbor which were subsequently discarded
             for any reason (e.g. a version 0 packet, or an
             unknown command type).";
        }
        leaf bad-routes-rcvd {
          type yang:counter32;
          description
            "The number of routes received from this neighbor,
             in valid RIP packets, which were ignored for any
             reason (e.g. unknown address family, or invalid
             metric).";
        }
      }
    } // neighbor
  } // neighbors
```



```
container routes {
  description
    "IPv6 route information.";
  list route {
    key "ipv6-prefix";
    description
      "A RIPng IPv6 route.";

    leaf ipv6-prefix {
      type inet:ipv6-prefix;
      description
        "IP address (in the canonical format defined in
        RFC5952) and prefix length, separated by the slash
        (/) character. The range of values for the
        prefix-length is 0 to 128.";
    }
    leaf next-hop {
      type inet:ipv6-address;
      description
        "Next hop IPv6 address.";
    }
    leaf interface {
      type if:interface-ref;
      description
        "The interface that the route uses.";
    }
    uses route-attributes;
  } // route
} // routes
} // ipv6

container statistics {
  if-feature global-statistics;
  config false;
  description
    "Global statistic counters.";
  leaf discontinuity-time {
    type yang:date-and-time;
    description
      "The time on the most recent occasion at which any one
      or more of the statistic counters suffered a
      discontinuity. If no such discontinuities have occurred
      since the last re-initialization of the local
      management subsystem, then this node contains the time
      the local management subsystem re-initialized itself.";
  }
  leaf requests-rcvd {
    type yang:counter32;
```



```
        description
            "The number of requests received by RIP.";
    }
    leaf requests-sent {
        type yang:counter32;
        description
            "The number of requests sent by RIP.";
    }
    leaf responses-rcvd {
        type yang:counter32;
        description
            "The number of responses received by RIP.";
    }
    leaf responses-sent {
        type yang:counter32;
        description
            "The number of responses sent by RIP.";
    }
} // statistics
} // container rip
}

/*
 * RPCs
 */

rpc clear-rip-route {
    description
        "Clears RIP routes from the IP routing table and routes
        redistributed into the RIP protocol for the specified RIP
        instance or for all RIP instances in the current context.";

    input {
        leaf rip-instance {
            type leafref {
                path "/rt:routing/rt:control-plane-protocols/"
                    + "rt:control-plane-protocol/rt:name";
            }
            description
                "Instance name identifying a specific RIP instance.
                This leaf is optional for the rpc.
                If it is specified, the rpc will clear all routes in the
                specified RIP instance;
                if it is not specified, the rpc will clear all routes in
                all RIP instances.";
        }
    }
}
} // rpc clear-rip-route
```



```
}  
<CODE ENDS>
```

5. IANA Considerations

RFC Ed.: In this section, replace all occurrences of 'XXXX' with the actual RFC number (and remove this note).

This document registers the following namespace URIs in the IETF XML registry [[RFC3688](#)]:

```
-----  
URI: urn:ietf:params:xml:ns:yang:ietf-rip  
Registrant Contact: The IESG.  
XML: N/A, the requested URI is an XML namespace.  
-----
```

This document registers the following YANG modules in the YANG Module Names registry [[RFC7950](#)]:

```
-----  
name:      ietf-rip  
namespace: urn:ietf:params:xml:ns:yang:ietf-rip  
prefix:    rip  
reference:  RFC XXXX  
-----
```

6. Security Considerations

The YANG module specified in this document defines a schema for data that is designed to be accessed via network management protocols such as NETCONF [[RFC6241](#)] or RESTCONF [[RFC8040](#)]. The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure transport is Secure Shell (SSH) [[RFC6242](#)]. The lowest RESTCONF layer is HTTPS, and the mandatory-to-implement secure transport is TLS [[RFC5246](#)].

The NETCONF access control model [[RFC6536](#)] provides the means to restrict access for particular NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

There are a number of data nodes defined in this YANG module that are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative

effect on network operations. These are the subtrees and data nodes and their sensitivity/vulnerability:

```
/rt:routing/rt:control-plane-protocols/rt:control-plane-protocol/  
rip:rip
```

Unauthorized access to any data node of these subtrees can adversely affect the routing subsystem of both the local device and the network. This may lead to network malfunctions, delivery of packets to inappropriate destinations, and other problems.

Some of the readable data nodes in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes. These are the subtrees and data nodes and their sensitivity/vulnerability:

```
/rt:routing/rt:control-plane-protocols/rt:control-plane-protocol/  
rip:rip
```

Unauthorized access to any data node of these subtrees can disclose the operational state information of RIP on this device.

Some of the RPC operations in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control access to these operations. These are the operations and their sensitivity/vulnerability:

RPC clear-rip-route:

Unauthorized access to the RPC above can adversely affect the routing subsystem of both the local device and the network. This may lead to network malfunctions, delivery of packets to inappropriate destinations, and other problems.

7. References

7.1. Normative References

- [RFC1724] Malkin, G. and F. Baker, "RIP Version 2 MIB Extension", [RFC 1724](#), DOI 10.17487/RFC1724, November 1994, <<https://www.rfc-editor.org/info/rfc1724>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

- [RFC2453] Malkin, G., "RIP Version 2", STD 56, [RFC 2453](#), DOI 10.17487/RFC2453, November 1998, <<https://www.rfc-editor.org/info/rfc2453>>.
- [RFC2080] Malkin, G. and R. Minnear, "RIPng for IPv6", [RFC 2080](#), DOI 10.17487/RFC2080, January 1997, <<https://www.rfc-editor.org/info/rfc2080>>.
- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.
- [RFC5246] Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2", [RFC 5246](#), DOI 10.17487/RFC5246, August 2008, <<https://www.rfc-editor.org/info/rfc5246>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", [RFC 6242](#), DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC6536] Bierman, A. and M. Bjorklund, "Network Configuration Protocol (NETCONF) Access Control Model", [RFC 6536](#), DOI 10.17487/RFC6536, March 2012, <<https://www.rfc-editor.org/info/rfc6536>>.
- [RFC6991] Schoenwaelder, J., Ed., "Common YANG Data Types", [RFC 6991](#), DOI 10.17487/RFC6991, July 2013, <<https://www.rfc-editor.org/info/rfc6991>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", [RFC 8040](#), DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.
- [RFC8177] Lindem, A., Ed., Qu, Y., Yeung, D., Chen, I., and J. Zhang, "YANG Data Model for Key Chains", [RFC 8177](#), DOI 10.17487/RFC8177, June 2017, <<https://www.rfc-editor.org/info/rfc8177>>.

[I-D.ietf-netmod-rfc7223bis]

Bjorklund, M., "A YANG Data Model for Interface Management", [draft-ietf-netmod-rfc7223bis-03](#) (work in progress), January 2018.

[I-D.ietf-netmod-rfc7277bis]

Bjorklund, M., "A YANG Data Model for IP Management", [draft-ietf-netmod-rfc7277bis-03](#) (work in progress), January 2018.

[I-D.ietf-netmod-rfc8022bis]

Lhotka, L., Lindem, A., and Y. Qu, "A YANG Data Model for Routing Management (NMDA Version)", [draft-ietf-netmod-rfc8022bis-11](#) (work in progress), January 2018.

[I-D.ietf-bfd-yang]

Rahman, R., Zheng, L., Jethanandani, M., Networks, J., and G. Mirsky, "YANG Data Model for Bidirectional Forwarding Detection (BFD)", [draft-ietf-bfd-yang-09](#) (work in progress), January 2018.

[I-D.ietf-isis-yang-isis-cfg]

Litkowski, S., Yeung, D., Lindem, A., Zhang, Z., and L. Lhotka, "YANG Data Model for IS-IS protocol", [draft-ietf-isis-yang-isis-cfg-19](#) (work in progress), November 2017.

[I-D.ietf-ospf-yang]

Yeung, D., Qu, Y., Zhang, Z., Chen, I., and A. Lindem, "Yang Data Model for OSPF Protocol", [draft-ietf-ospf-yang-09](#) (work in progress), October 2017.

[I-D.ietf-netmod-revised-datastores]

Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture", [draft-ietf-netmod-revised-datastores-10](#) (work in progress), January 2018.

7.2. Informative References

[RFC7951] Lhotka, L., "JSON Encoding of Data Modeled with YANG", [RFC 7951](#), DOI 10.17487/RFC7951, August 2016, <<https://www.rfc-editor.org/info/rfc7951>>.

[I-D.ietf-netconf-subscribed-notifications]

Voit, E., Clemm, A., Prieto, A., Nilsen-Nygaard, E., and A. Tripathy, "Custom Subscription to Event Streams", [draft-ietf-netconf-subscribed-notifications-08](#) (work in progress), December 2017.

[I-D.ietf-netconf-yang-push]

Clemm, A., Voit, E., Prieto, A., Tripathy, A., Nilsen-Nygaard, E., Bierman, A., and B. Lengyel, "YANG Datastore Subscription", [draft-ietf-netconf-yang-push-12](#) (work in progress), December 2017.

[I-D.ietf-netmod-rfc6087bis]

Bierman, A., "Guidelines for Authors and Reviewers of YANG Data Model Documents", [draft-ietf-netmod-rfc6087bis-16](#) (work in progress), January 2018.

[I-D.ietf-netmod-yang-tree-diagrams]

Bjorklund, M. and L. Berger, "YANG Tree Diagrams", [draft-ietf-netmod-yang-tree-diagrams-05](#) (work in progress), January 2018.

Appendix A. Data Tree Example

This section contains an example of an instance data tree in the JSON encoding [[RFC7951](#)], containing both configuration and state data.

```

+-----+
| Router 203.0.113.1 |
+-----+
| eth1
| 2001:db8:0:1::1/64
|
| 2001:db8:0:1::2/64
+-----+
| Another Router | +-----+ 2001:db8:0:2::/64
+-----+

```

The configuration instance data tree for Router 203.0.113.1 in the above figure could be as follows:


```
{
  "ietf-interfaces:interfaces": {
    "interface": [
      {
        "name": "eth1",
        "description": "An interface with RIPng enabled.",
        "type": "iana-if-type:ethernetCsmacd",
        "ietf-ip:ipv6": {
          "address": [
            {
              "ip": "2001:db8:0:1::1",
              "prefix-length": 64
            }
          ],
          "forwarding": true
        }
      ]
    ],
    "ietf-routing:routing": {
      "router-id": "203.0.113.1",
      "control-plane-protocols": {
        "control-plane-protocol": [
          {
            "type": "ietf-rip:ripng",
            "name": "ripng-1",
            "description": "RIPng instance ripng-1.",
            "ietf-rip:rip": {
              "redistribute": {
                "connected": {
                }
              }
            },
            "interfaces": {
              "interface": [
                {
                  "interface": "eth1",
                  "split-horizon": "poison-reverse"
                }
              ]
            }
          ]
        ]
      }
    }
  }
}
```


The cooresponding operational state data for Router 203.0.113.1 could be as follows:

```
{
  "ietf-interfaces:interfaces": {
    "interface": [
      {
        "name": "eth1",
        "description": "An interface with RIPng enabled.",
        "type": "iana-if-type:ethernetCsmacd",
        "phys-address": "00:00:5e:00:53:01",
        "oper-status": "up",
        "statistics": {
          "discontinuity-time": "2016-10-24T17:11:27+02:00"
        },
        "ietf-ip:ipv6": {
          "forwarding": true,
          "mtu": 1500,
          "address": [
            {
              "ip": "2001:db8:0:1::1",
              "prefix-length": 64,
              "origin": "static",
              "status": "preferred"
            },
            {
              "ip": "fe80::200:5eff:fe00:5301",
              "prefix-length": 64,
              "origin": "link-layer",
              "status": "preferred"
            }
          ],
          "neighbor": [
            {
              "ip": "2001:db8:0:1::2",
              "link-layer-address": "00:00:5e:00:53:02",
              "origin": "dynamic",
              "is-router": [null],
              "state": "reachable"
            },
            {
              "ip": "fe80::200:5eff:fe00:5302",
              "link-layer-address": "00:00:5e:00:53:02",
              "origin": "dynamic",
              "is-router": [null],
              "state": "reachable"
            }
          ]
        }
      ]
    }
  }
}
```



```
    }
  }
]
},
"ietf-routing:routing": {
  "router-id": "203.0.113.1",
  "interfaces": {
    "interface": [
      "eth1"
    ]
  },
},
"control-plane-protocols": {
  "control-plane-protocol": [
    {
      "type": "ietf-rip:ripng",
      "name": "ripng-1",
      "description": "RIPng instance ripng-1.",
      "ietf-rip:rip": {
        "default-metric": 1,
        "next-triggered-update": 5
        "interfaces": {
          "interface": [
            {
              "interface": "eth1",
              "oper-status": "up",
              "cost": 1,
              "split-horizon": "poison-reverse",
              "valid-address": true
            }
          ]
        },
      },
      "ipv6" {
        "neighbors": {
          "neighbor": [
            {
              "address": "fe80::200:5eff:fe00:5302",
              "last-update": "2017-01-02T10:34:55+02:00"
            }
          ]
        }
      }
    }
  ],
  "routes": {
    "route": [
      {
        "ipv6-prefix": "2001:db8:0:1::/64",
        "interface": "eth1",
        "redistributed": true,
        "route-type": "connected",
        "metric": 1,
      }
    ]
  }
}
```



```
        "expire-time": 22
      },
      {
        "ipv6-prefix": "2001:db8:0:2::/64",
        "next-hop": "fe80::200:5eff:fe00:5302",
        "interface": "eth1",
        "redistributed": false,
        "route-type": "rip",
        "metric": 2,
        "expire-time": 82
      }
    ]
  }
},
"statistics": {
  "discontinuity-time": "2016-10-24T17:11:27+02:00",
  "requests-rcvd": 523,
  "requests-sent": 262,
  "responses-rcvd": 261,
  "responses-sent": 523
}
}
}
]
}
}
```

Authors' Addresses

Xufeng Liu
Jabil
8281 Greensboro Drive, Suite 200
McLean VA 22102
USA

EMail: Xufeng_Liu@jabil.com

Prateek Sarda
Ericsson
Fern Icon, Survey No 28 and 36/5, Doddanakundi Village
Bangalore Karnataka 560037
India

EMail: prateek.sarda@ericsson.com

Vikram Choudhary
Individual
Bangalore 560066
India

EMail: vikschw@gmail.com