

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: May 22, 2020

A. Backman, Ed.
Amazon
M. Jones, Ed.
Microsoft
M. Scurtescu
Coinbase
M. Ansari
Cisco
A. Nadalin
Microsoft
November 19, 2019

Poll-Based Security Event Token (SET) Delivery Using HTTP draft-ietf-secevent-http-poll-06

Abstract

This specification defines how a series of Security Event Tokens (SETs) may be delivered to an intended recipient using HTTP POST over TLS initiated as a poll by the recipient. The specification also defines how delivery can be assured, subject to the SET Recipient's need for assurance.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 22, 2020.

Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents

(<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction and Overview	2
1.1.	Notational Conventions	3
1.2.	Definitions	3
2.	SET Delivery	3
2.1.	Polling Delivery using HTTP	4
2.2.	Polling HTTP Request	4
2.3.	Polling HTTP Response	5
2.4.	Poll Request	6
2.4.1.	Poll Only Request	6
2.4.2.	Acknowledge Only Request	7
2.4.3.	Poll with Acknowledgement	8
2.4.4.	Poll with Acknowledgement and Errors	9
2.5.	Poll Response	9
2.5.1.	Poll Error Response	11
2.6.	Error Response Handling	11
3.	Authentication and Authorization	12
4.	Security Considerations	12
4.1.	Authentication Using Signed SETs	12
4.2.	HTTP Considerations	13
4.3.	Confidentiality of SETs	13
4.4.	Access Token Considerations	13
4.4.1.	Bearer Token Considerations	13
5.	Privacy Considerations	14
6.	IANA Considerations	14
7.	References	14
7.1.	Normative References	14
7.2.	Informative References	16
Appendix A.	Acknowledgments	16
Appendix B.	Change Log	17
	Authors' Addresses	18

1. Introduction and Overview

This specification defines how a stream of Security Event Tokens (SETs) [[RFC8417](#)] can be transmitted to an intended SET Recipient using HTTP [[RFC7231](#)] over TLS. The specification defines a method to poll for SETs using HTTP POST. This is an alternative SET delivery method to the one defined in [[I-D.ietf-secevent-http-push](#)].

A mechanism for exchanging configuration metadata such as endpoint URLs and cryptographic key parameters between the transmitter and recipient is out of scope for this specification. How SETs are defined and the process by which security events are identified for SET Recipients are specified in [[RFC8417](#)].

[1.1.](#) Notational Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

Throughout this document, all figures MAY contain spaces and extra line wrapping for readability and due to space limitations.

[1.2.](#) Definitions

This specification utilizes terminology defined in [[RFC8417](#)] and [[I-D.ietf-secevent-http-push](#)].

[2.](#) SET Delivery

When a SET is available for a SET Recipient, the SET Transmitter attempts to deliver the SET by queueing the SET in a buffer so that a SET Recipient can poll for SETs using HTTP/1.1 POST.

In Poll-Based SET Delivery Using HTTP, zero or more SETs are delivered in a JSON [[RFC8259](#)] document to a SET Recipient in response to an HTTP POST request to the SET Transmitter. Then in a following request, the SET Recipient acknowledges received SETs and can poll for more. All requests and responses are JSON documents and use a "Content-Type" of "application/json", as described in [Section 2.1](#).

After successful (acknowledged) SET delivery, SET Transmitters are not required to retain or record SETs for retransmission. Once a SET is acknowledged, the SET Recipient SHALL be responsible for retention, if needed.

Upon receiving a SET, the SET Recipient reads the SET and validates it in the manner described in Section 2 of [[I-D.ietf-secevent-http-push](#)]. The SET Recipient MUST acknowledge receipt to the SET Transmitter. The SET Recipient SHALL NOT use the event acknowledgement mechanism to report event errors other than those relating to the parsing and validation of the SET.

2.1. Polling Delivery using HTTP

This method allows a SET Recipient to use HTTP POST ([Section 4.3.3 of \[RFC7231\]](#)) to acknowledge SETs and to check for and receive zero or more SETs. Requests MAY be made at a periodic interval (short polling) or requests MAY wait, pending availability of new SETs using long polling, per [Section 2 of \[RFC6202\]](#).

The delivery of SETs in this method is facilitated by HTTP POST requests initiated by the SET Recipient in which:

- o The SET Recipient makes a request for available SETs using an HTTP POST to a pre-arranged endpoint provided by the SET Transmitter or,
- o after validating previously received SETs, the SET Recipient initiates another poll request using HTTP POST that includes acknowledgement of previous SETs and waits for the next batch of SETs.

The purpose of the acknowledgement is to inform the SET Transmitter that delivery has succeeded and redelivery is no longer required. Before acknowledgement, SET Recipients SHOULD ensure that received SETs have been validated and retained in a manner appropriate to the recipient's requirements. The level and method of retention of SETs by SET Recipients is out of scope of this specification.

2.2. Polling HTTP Request

When initiating a poll request, the SET Recipient constructs a JSON document that consists of polling request parameters and SET acknowledgement parameters in the form of JSON objects. The request payloads are delivered in a JSON document, as described in [Section 2.4](#) and [Section 2.5](#).

When making a request, the HTTP header "Content-Type" is set to "application/json".

The following JSON object members are used in a polling request:

Request Processing Parameters

maxEvents

An OPTIONAL JSON integer value indicating the maximum number of unacknowledged SETs that SHOULD be returned. If more than the maximum number of SETs are available, the oldest SETs available SHOULD be returned first. A value of "0" MAY be used by SET Recipients that would like to perform an acknowledge only

request. This enables the Recipient to use separate HTTP requests for acknowledgement and reception of SETs. If this parameter is omitted, no limit is placed on the number of SETs to be returned.

returnImmediately

An OPTIONAL JSON boolean value that indicates the SET Transmitter SHOULD return an immediate response even if no results are available (short polling). The default value is "false", which indicates the request is to be treated as an HTTP Long Poll, per [Section 2 of \[RFC6202\]](#). The timeout for the request is part of the configuration between the participants, which is out of scope of this specification.

SET Acknowledgment Parameters

ack

A JSON array of strings whose values are the "jti" values of successfully received SETs that are being acknowledged. If there are no outstanding SETs to acknowledge, this member is omitted. When acknowledging a SET, the SET Transmitter is released from any obligation to retain the SET.

setErrs

A JSON object with one or more members whose keys are the "jti" values of invalid SETs received. The values of these objects are themselves JSON objects that describe the errors detected using the "err" and "description" values specified in [Section 2.6](#). If there are no outstanding SETs with errors to return, this member is omitted.

[2.3. Polling HTTP Response](#)

In response to a poll request, the SET Transmitter checks for available SETs and responds with a JSON document containing the following JSON object members:

sets

A JSON object that contains zero or more nested JSON objects. Each nested JSON object's key corresponds to the "jti" of a SET to be delivered, and its value is a JSON string containing the value of the encoded corresponding SET. If there are no outstanding SETs to be transmitted, the JSON object SHALL be empty.

moreAvailable

A JSON boolean value that indicates if more unacknowledged SETs are available to be returned.

When making a response, the HTTP header "Content-Type" is set to "application/json".

2.4. Poll Request

The SET Recipient performs an HTTP POST (see [Section 4.3.4 of \[RFC7231\]](#)) to a pre-arranged polling endpoint URI to check for SETs that are available. Because the SET Recipient has no prior SETs to acknowledge, the "ack" and "setErrs" request parameters are omitted.

After a period of time configured between the SET Transmitter and Recipient, a SET Transmitter MAY redeliver SETs it has previously delivered. The SET Recipient SHOULD accept repeat SETs and acknowledge the SETs regardless of whether the Recipient believes it has already acknowledged the SETs previously. A SET Transmitter MAY limit the number of times it attempts to deliver a SET.

If the SET Recipient has received SETs from the SET Transmitter, the SET Recipient SHOULD parse and validate received SETs to meet its own requirements and SHOULD acknowledge receipt in a timely fashion (e.g., seconds or minutes) so that the SET Transmitter can mark the SETs as received. SET Recipients SHOULD acknowledge receipt before taking any local actions based on the SETs to avoid unnecessary delay in acknowledgement, where possible.

Poll requests have three variations:

Poll Only

In which a SET Recipient asks for the next set of events where no previous SET deliveries are acknowledged (such as in the initial poll request).

Acknowledge Only

In which a SET Recipient sets the "maxEvents" value to "0" along with "ack" and "setErrs" members indicating the SET Recipient is acknowledging previously received SETs and does not want to receive any new SETs in response to the request.

Combined Acknowledge and Poll

In which a SET Recipient is both acknowledging previously received SETs using the "ack" and "setErrs" members and will wait for the next group of SETs in the SET Transmitters response.

2.4.1. Poll Only Request

In the case where no SETs were received in a previous poll (see Figure 7), the SET Recipient simply polls without acknowledgement parameters ("ack" and "setErrs").

The following is an example request made by a SET Recipient that has no outstanding SETs to acknowledge and is polling for available SETs at the endpoint "https://notify.idp.example.com/Events":

```
POST /Events HTTP/1.1
Host: notify.idp.example.com
Content-Type: application/json
```

```
{
  "returnImmediately": true
}
```

Figure 1: Example Initial Poll Request

A SET Recipient can poll using default parameter values by passing an empty JSON object.

The following is a non-normative example default poll request to the endpoint "https://notify.idp.example.com/Events":

```
POST /Events HTTP/1.1
Host: notify.idp.example.com
Content-Type: application/json
```

```
{}
```

Figure 2: Example Default Poll Request

[2.4.2.](#) Acknowledge Only Request

In this variation, the SET Recipient acknowledges previously received SETs and indicates it does not want to receive SETs in response by setting the "maxEvents" value to "0".

This variation might be used, for instance, when a SET Recipient needs to acknowledge received SETs independently (e.g., on separate threads) from the process of receiving SETs.

The following is a non-normative example poll request with acknowledgement of SETs received (for example as shown in Figure 6):

```
POST /Events HTTP/1.1
Host: notify.idp.example.com
Content-Type: application/json

{
  "ack": [
    "4d3559ec67504aaba65d40b0363faad8",
    "3d0c3cf797584bd193bd0fb1bd4e7d30"
  ],
  "maxEvents": 0,
  "returnImmediately": true
}
```

Figure 3: Example Acknowledge Only Request

[2.4.3.](#) Poll with Acknowledgement

This variation allows a recipient thread to simultaneously acknowledge previously received SETs and wait for the next group of SETs in a single request.

The following is a non-normative example poll with acknowledgement of the SETs received in Figure 6:

```
POST /Events HTTP/1.1
Host: notify.idp.example.com
Content-Type: application/json

{
  "ack": [
    "4d3559ec67504aaba65d40b0363faad8",
    "3d0c3cf797584bd193bd0fb1bd4e7d30"
  ],
  "returnImmediately": false
}
```

Figure 4: Example Poll with Acknowledgement and No Errors

In the above acknowledgement, the SET Recipient has acknowledged receipt of two SETs and has indicated it wants to wait until the next SET is available.

[2.4.4.](#) Poll with Acknowledgement and Errors

In the case where errors were detected in previously delivered SETs, the SET Recipient MAY use the "setErrs" member to communicate the errors in the following poll request.

The following is a non-normative example of a response acknowledging one successfully received SET and one SET with an error from the two SETs received in Figure 6:

```
POST /Events HTTP/1.1
Host: notify.idp.example.com
Content-Language: en-US
Content-Type: application/json

{
  "ack": ["3d0c3cf797584bd193bd0fb1bd4e7d30"],
  "setErrs": {
    "4d3559ec67504aaba65d40b0363faad8": {
      "err": "jwtAud",
      "description": "The audience value was invalid."
    }
  },
  "returnImmediately": true
}
```

Figure 5: Example Poll Acknowledgement with Error

[2.5.](#) Poll Response

In response to a valid poll request, the service provider MAY respond immediately if SETs are available to be delivered. If no SETs are available at the time of the request, the SET Transmitter SHALL delay responding until a SET is available or the timeout interval has elapsed unless the poll request parameter "returnImmediately" is "true".

As described in [Section 2.3](#), a JSON document is returned containing a number of members including "sets", which SHALL contain zero or more SETs.

In the above example, two SETs whose "jti" values are "4d3559ec67504aaba65d40b0363faad8" and "3d0c3cf797584bd193bd0fb1bd4e7d30" are delivered.

The following is a non-normative example response to the request shown in [Section 2.4](#), which indicates that no new SETs or unacknowledged SETs are available:

```
HTTP/1.1 200 OK
Content-Type: application/json
```

```
{
  "sets": {}
}
```

Figure 7: Example No SETs Poll Response

Upon receiving the JSON document (e.g., as shown in Figure 6), the SET Recipient parses and verifies the received SETs and notifies the SET Transmitter of successfully received SETs and SETs with errors via the next poll request to the SET Transmitter, as described in [Section 2.4.3](#) or [Section 2.4.4](#).

[2.5.1](#). Poll Error Response

In the event of a general HTTP error condition in the context of processing a poll request, the service provider SHOULD respond with an appropriate HTTP Response Status Code as defined in [Section 6 of \[RFC7231\]](#).

Service providers MAY respond to any invalid poll request with an HTTP Response Status Code of 400 (Bad Request) even when a more specific code might apply, for example if the service provider deemed that a more specific code presented an information disclosure risk. When no more specific code might apply, the service provider SHALL respond to an invalid poll request with an HTTP Status Code of 400.

The response body for responses to invalid poll requests is left undefined.

The following is a non-normative example of a response to an invalid poll request:

```
HTTP/1.1 400 Bad Request
```

Example Poll Error Response

[2.6](#). Error Response Handling

If a SET is invalid, error codes from the IANA "Security Event Token Delivery Error Codes" registry established by [\[I-D.ietf-secevent-http-push\]](#) are used in error responses. As

described in Section 2.3 of [[I-D.ietf-secevent-http-push](#)], an error response is a JSON object providing details about the error that includes the following name/value pairs:

err

A value from the IANA "Security Event Token Delivery Error Codes" registry that identifies the error.

description

A human-readable string that provides additional diagnostic information.

When included as part of a batch of SETs, the above JSON is included as part of the "setErrs" member, as defined in [Section 2.3](#) and [Section 2.4.4](#).

When the SET Recipient includes one or more error responses in a request to the SET Transmitter, it must also include in the request a "Content-Language" header whose value indicates the language of the error descriptions included in the request. The method of language selection in the case when the SET Recipient can provide error messages in multiple languages is out of scope for this specification.

[3. Authentication and Authorization](#)

The SET delivery method described in this specification is based upon HTTP and depends on the use of TLS and/or standard HTTP authentication and authorization schemes, as per [[RFC7235](#)].

As per [Section 4.1 of \[RFC7235\]](#), a SET delivery endpoint SHALL indicate supported HTTP authentication schemes via the "WWW-Authenticate" header.

Authorization for the ability to pick-up or deliver SETs can be determined by using the identity of the SET issuer, or via other employed authentication methods. Among other benefits, authentication can help prevent denial-of-service attacks. Because SETs are not commands, SET Recipients are free to ignore SETs that are not of interest after acknowledging their receipt.

[4. Security Considerations](#)

[4.1. Authentication Using Signed SETs](#)

In scenarios where HTTP authorization or TLS mutual authentication are not used or are considered weak, JWS signed SETs SHOULD be used (see [[RFC7515](#)] and [Section 5 of \[RFC8417\]](#)). This enables the SET

Recipient to validate that the SET issuer is authorized to deliver the SET.

[4.2.](#) HTTP Considerations

SET delivery depends on the use of Hypertext Transfer Protocol and is thus subject to the security considerations of HTTP [Section 9 of \[RFC7230\]](#) and its related specifications.

As stated in [Section 2.7.1 of \[RFC7230\]](#), an HTTP requestor MUST NOT generate the "userinfo" (i.e., username and password) component (and its "@" delimiter) when an "http" URI reference is generated with a message, as they are now disallowed in HTTP.

[4.3.](#) Confidentiality of SETs

SETs may contain sensitive information that is considered Personally Identifiable Information (PII). In such cases, SET Transmitters and SET Recipients MUST protect the confidentiality of the SET contents by encrypting the SET as described in JWE [\[RFC7516\]](#), using a transport-layer security mechanism such as TLS, or both. If an Event delivery endpoint supports TLS, it MUST support at least TLS version 1.2 [\[RFC5246\]](#) and SHOULD support the newest version of TLS that meets its security requirements. When using TLS, the client MUST perform a TLS/SSL server certificate check, per [\[RFC6125\]](#). Implementation security considerations for TLS can be found in "Recommendations for Secure Use of TLS and DTLS" [\[RFC7525\]](#).

[4.4.](#) Access Token Considerations

When using access tokens, such as those issued by OAuth 2.0 [\[RFC6749\]](#), implementers MUST take into account threats and countermeasures documented in [Section 8 of \[RFC7521\]](#).

[4.4.1.](#) Bearer Token Considerations

Due to the possibility of interception, Bearer tokens MUST be exchanged using TLS.

Bearer tokens SHOULD have a limited lifetime that can be determined directly or indirectly (e.g., by checking with a validation service) by the service provider. By expiring tokens, clients are forced to obtain a new token (which usually involves re-authentication) for continued authorized access. For example, in OAuth 2.0, a client MAY use an OAuth refresh token to obtain a new bearer token after authenticating to an authorization server, per [Section 6 of \[RFC6749\]](#).

Implementations supporting OAuth bearer tokens need to factor in security considerations of this authorization method [[RFC7521](#)]. Since security is only as good as the weakest link, implementers also need to consider authentication choices coupled with OAuth bearer tokens. The security considerations of the default authentication method for OAuth bearer tokens, HTTP Basic, are well documented in [[RFC7617](#)], therefore implementers are encouraged to prefer stronger authentication methods. Designating the specific methods of authentication and authorization are out of scope for the delivery of SETs, however this information is provided as a resource to implementers.

5. Privacy Considerations

If a SET needs to be retained for audit purposes, a JWS signature MAY be used to provide verification of its authenticity.

SET Transmitters SHOULD attempt to deliver SETs that are targeted to the specific business and protocol needs of subscribers.

When sharing personally identifiable information or information that is otherwise considered confidential to affected users, SET Transmitters and Recipients MUST have the appropriate legal agreements and user consent or terms of service in place.

The propagation of subject identifiers can be perceived as personally identifiable information. Where possible, SET Transmitters and Recipients SHOULD devise approaches that prevent propagation, for example, the passing of a hash value that requires the subscriber to already know the subject.

6. IANA Considerations

This specification requires no IANA actions.

7. References

7.1. Normative References

[I-D.ietf-secevent-http-push]

Backman, A., Jones, M., Scurtescu, M., Ansari, M., and A. Nadalin, "Push-Based Security Event Token (SET) Delivery Using HTTP", [draft-ietf-secevent-http-push-07](#) (work in progress), July 2019.

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC5246] Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2", [RFC 5246](#), DOI 10.17487/RFC5246, August 2008, <<https://www.rfc-editor.org/info/rfc5246>>.
- [RFC6125] Saint-Andre, P. and J. Hodges, "Representation and Verification of Domain-Based Application Service Identity within Internet Public Key Infrastructure Using X.509 (PKIX) Certificates in the Context of Transport Layer Security (TLS)", [RFC 6125](#), DOI 10.17487/RFC6125, March 2011, <<https://www.rfc-editor.org/info/rfc6125>>.
- [RFC7231] Fielding, R., Ed. and J. Reschke, Ed., "Hypertext Transfer Protocol (HTTP/1.1): Semantics and Content", [RFC 7231](#), DOI 10.17487/RFC7231, June 2014, <<https://www.rfc-editor.org/info/rfc7231>>.
- [RFC7515] Jones, M., Bradley, J., and N. Sakimura, "JSON Web Signature (JWS)", [RFC 7515](#), DOI 10.17487/RFC7515, May 2015, <<https://www.rfc-editor.org/info/rfc7515>>.
- [RFC7516] Jones, M. and J. Hildebrand, "JSON Web Encryption (JWE)", [RFC 7516](#), DOI 10.17487/RFC7516, May 2015, <<https://www.rfc-editor.org/info/rfc7516>>.
- [RFC7525] Sheffer, Y., Holz, R., and P. Saint-Andre, "Recommendations for Secure Use of Transport Layer Security (TLS) and Datagram Transport Layer Security (DTLS)", [BCP 195](#), [RFC 7525](#), DOI 10.17487/RFC7525, May 2015, <<https://www.rfc-editor.org/info/rfc7525>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8259] Bray, T., Ed., "The JavaScript Object Notation (JSON) Data Interchange Format", STD 90, [RFC 8259](#), DOI 10.17487/RFC8259, December 2017, <<https://www.rfc-editor.org/info/rfc8259>>.

- [RFC8417] Hunt, P., Ed., Jones, M., Denniss, W., and M. Ansari, "Security Event Token (SET)", [RFC 8417](#), DOI 10.17487/RFC8417, July 2018, <<https://www.rfc-editor.org/info/rfc8417>>.

[7.2. Informative References](#)

- [RFC6202] Loreto, S., Saint-Andre, P., Salsano, S., and G. Wilkins, "Known Issues and Best Practices for the Use of Long Polling and Streaming in Bidirectional HTTP", [RFC 6202](#), DOI 10.17487/RFC6202, April 2011, <<https://www.rfc-editor.org/info/rfc6202>>.
- [RFC6749] Hardt, D., Ed., "The OAuth 2.0 Authorization Framework", [RFC 6749](#), DOI 10.17487/RFC6749, October 2012, <<https://www.rfc-editor.org/info/rfc6749>>.
- [RFC7230] Fielding, R., Ed. and J. Reschke, Ed., "Hypertext Transfer Protocol (HTTP/1.1): Message Syntax and Routing", [RFC 7230](#), DOI 10.17487/RFC7230, June 2014, <<https://www.rfc-editor.org/info/rfc7230>>.
- [RFC7235] Fielding, R., Ed. and J. Reschke, Ed., "Hypertext Transfer Protocol (HTTP/1.1): Authentication", [RFC 7235](#), DOI 10.17487/RFC7235, June 2014, <<https://www.rfc-editor.org/info/rfc7235>>.
- [RFC7521] Campbell, B., Mortimore, C., Jones, M., and Y. Goland, "Assertion Framework for OAuth 2.0 Client Authentication and Authorization Grants", [RFC 7521](#), DOI 10.17487/RFC7521, May 2015, <<https://www.rfc-editor.org/info/rfc7521>>.
- [RFC7617] Reschke, J., "The 'Basic' HTTP Authentication Scheme", [RFC 7617](#), DOI 10.17487/RFC7617, September 2015, <<https://www.rfc-editor.org/info/rfc7617>>.

[Appendix A. Acknowledgments](#)

The editors would like to thank the members of the SCIM working group, which began discussions of provisioning events starting with [draft-hunt-scim-notify-00](#) in 2015.

The editors would like to thank Phil Hunt and the other the authors of [draft-ietf-secevent-delivery-02](#), on which this specification is based.

The editors would like to thank the participants in the SecEvents working group for their contributions to this specification.

[Appendix B](#). Change Log

[[] to be removed by the RFC Editor before publication as an RFC []]

Draft 00 - AB - Based on [draft-ietf-secevent-delivery-02](#) with the following additions:

- o Renamed to "Poll-Based SET Token Delivery Using HTTP"
- o Removed references to the HTTP Push delivery method.

Draft 01 - mbj:

- o Addressed problems identified in my 18-Jul-18 review message titled "Issues for both the Push and Poll Specs".
- o Changes to align terminology with [RFC 8417](#), for instance, by using the already defined term SET Recipient rather than SET Receiver.
- o Applied editorial and minor normative corrections.
- o Updated Marius' contact information.
- o Begun eliminating redundancies between this specification and "Push-Based Security Event Token (SET) Delivery Using HTTP" [[I-D.ietf-secevent-http-push](#)], referencing, rather than duplicating common normative text.

Draft 02 - mbj:

- o Removed vestigial language remaining from when the push and poll delivery methods were defined in a common specification.
- o Replaced remaining uses of the terms Event Transmitter and Event Recipient with the correct terms SET Transmitter and SET Recipient.
- o Removed uses of the unnecessary term "Event Stream".
- o Removed dependencies between the semantics of "maxEvents" and "returnImmediately".
- o Said that PII in SETs is to be encrypted with TLS, JWE, or both.
- o Corrected grammar and spelling errors.

Draft 03 - mbj:

- o Corrected uses of "attribute" to "member" when describing JSON objects.
- o Further alignment with the push draft.

Draft 04 - AB + mbj

- o Referenced SET Transmitter definition in http-push.
- o Removed incorrect normative text regarding SET construction.
- o Consolidated general out-of-scope items under Introduction.
- o Removed unnecessary HTTP headers in examples and added Content-Type.
- o Added Content-Language requirement for error descriptions, aligning with http-push.
- o Stated that bearer tokens SHOULD have a limited lifetime.
- o Minor editorial fixes.

Draft 05 - AB + mbj

- o Added normative text defining how to respond to invalid poll requests.
- o Addressed shepherd comments by Yaron Sheffer.

Draft 06 - mbj

- o Addressed nits identified by the idnits tool.

Authors' Addresses

Annabelle Backman (editor)
Amazon

Email: richanna@amazon.com

Michael B. Jones (editor)
Microsoft

Email: mbj@microsoft.com

URI: <http://self-issued.info/>

Marius Scurtescu
Coinbase

Email: marius.scurtescu@coinbase.com

Morteza Ansari
Cisco

Email: morteza.ansari@cisco.com

Anthony Nadalin
Microsoft

Email: tonynad@microsoft.com