

Security Events Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: September 10, 2017

P. Hunt, Ed.  
Oracle  
W. Denniss  
Google  
M. Ansari  
Cisco  
M. Jones  
Microsoft  
March 9, 2017

**Security Event Token (SET)**  
**draft-ietf-secevent-token-01**

Abstract

This specification defines the Security Event Token, which may be distributed via a protocol such as HTTP. The Security Event Token (SET) specification profiles the JSON Web Token (JWT), which can be optionally signed and/or encrypted. A SET describes a statement of fact from the perspective of an issuer that it intends to share with one or more receivers.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 10, 2017.

Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of

publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	<a href="#">Introduction and Overview</a>	<a href="#">2</a>
<a href="#">1.1.</a>	<a href="#">Notational Conventions</a>	<a href="#">4</a>
<a href="#">1.2.</a>	<a href="#">Definitions</a>	<a href="#">4</a>
<a href="#">2.</a>	<a href="#">The Security Event Token (SET)</a>	<a href="#">5</a>
<a href="#">2.1.</a>	<a href="#">Core SET Claims</a>	<a href="#">8</a>
<a href="#">2.2.</a>	<a href="#">Security Event Token Construction</a>	<a href="#">9</a>
<a href="#">3.</a>	<a href="#">Security Considerations</a>	<a href="#">11</a>
<a href="#">3.1.</a>	<a href="#">Confidentiality and Integrity</a>	<a href="#">12</a>
<a href="#">3.2.</a>	<a href="#">Delivery</a>	<a href="#">12</a>
<a href="#">3.3.</a>	<a href="#">Sequencing</a>	<a href="#">12</a>
<a href="#">3.4.</a>	<a href="#">Timing Issues</a>	<a href="#">13</a>
<a href="#">3.5.</a>	<a href="#">Distinguishing SETs from Access Tokens</a>	<a href="#">13</a>
<a href="#">4.</a>	<a href="#">Privacy Considerations</a>	<a href="#">14</a>
<a href="#">5.</a>	<a href="#">IANA Considerations</a>	<a href="#">14</a>
<a href="#">5.1.</a>	<a href="#">JSON Web Token Claims Registration</a>	<a href="#">14</a>
<a href="#">5.1.1.</a>	<a href="#">Registry Contents</a>	<a href="#">14</a>
<a href="#">6.</a>	<a href="#">References</a>	<a href="#">14</a>
<a href="#">6.1.</a>	<a href="#">Normative References</a>	<a href="#">14</a>
<a href="#">6.2.</a>	<a href="#">Informative References</a>	<a href="#">15</a>
<a href="#">Appendix A.</a>	<a href="#">Acknowledgments</a>	<a href="#">16</a>
<a href="#">Appendix B.</a>	<a href="#">Change Log</a>	<a href="#">16</a>
	<a href="#">Authors' Addresses</a>	<a href="#">18</a>

## **[1.](#) Introduction and Overview**

This specification defines an extensible Security Event Token (SET) format which may be exchanged using protocols such as HTTP. The specification builds on the JSON Web Token (JWT) format [[RFC7519](#)] in order to provide a self-contained token that can be optionally signed using JSON Web Signature (JWS) [[RFC7515](#)] and/or encrypted using JSON Web Encryption (JWE) [[RFC7516](#)].

This specification profiles the use of JWT for the purpose of issuing security event tokens (SETs). This specification defines a base format upon which profiling specifications define actual events and their meanings. Unless otherwise specified, this specification uses non-normative example events intended to demonstrate how events may be constructed.



This specification is scoped to security and identity related events. While security event tokens may be used for other purposes, the specification only considers security and privacy concerns relevant to identity and personal information.

Security Events are not commands issued between parties. A security event is a statement of fact from the perspective of an issuer about the state of a security subject (e.g., a web resource, token, IP address, the issuer itself) that the issuer controls or is aware of, that has changed in some way (explicitly or implicitly). A security subject MAY be permanent (e.g., a user account) or temporary (e.g., an HTTP session) in nature. A state change could describe a direct change of entity state, an implicit change of state or other higher-level security statements such as:

- o The creation, modification, removal of a resource.
- o The resetting or suspension of an account.
- o The revocation of a security token prior to its expiry.
- o The logout of a user session. Or,
- o A cumulative conclusion such as to indicate that a user has taken over an email identifier that may have been used in the past by another user.

While subject state changes are often triggered by a user-agent or security-subsystem, the issuance and transmission of an event often occurs asynchronously and in a back-channel to the action which caused the change that generated the security event. Subsequently, an Event Receiver having received a SET, validates and interprets the received SET and takes its own independent action, if any. For example, having been informed of a personal identifier being associated with a different security subject (e.g., an email address is being used by someone else), the Event Receiver may choose to ensure that the new user is not granted access to resources associated with the previous user. Or, the Event Receiver may not have any relationship with the subject, and no action is taken.

While Event Receivers will often take actions upon receiving SETs, security events MUST NOT be assumed to be commands or requests. The intent of this specification is to define a way of exchanging statements of fact that subscribers may interpret for their own purposes. As such, SETs have no capability for error signaling other than to ensure the validation of a received SET.



### **[1.1.](#) Notational Conventions**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [\[RFC2119\]](#). These keywords are capitalized when used to unambiguously specify requirements of the protocol or application features and behavior that affect the inter-operability and security of implementations. When these words are not capitalized, they are meant in their natural-language sense.

For purposes of readability, examples are not URL encoded. Implementers MUST percent encode URLs as described in [Section 2.1 of \[RFC3986\]](#).

Throughout this document, all figures MAY contain spaces and extra line-wrapping for readability and space limitations. Similarly, some URIs contained within examples have been shortened for space and readability reasons.

### **[1.2.](#) Definitions**

The following definitions are used with SETs:

#### Security Event Token (SET)

A SET is a JWT [\[RFC7519\]](#) that is distributed to one or more registered Event Receivers.

#### Event Transmitter

A service provider that delivers SETs to other providers known as Event Receivers.

#### Event Receiver

An Event Receiver is an entity that receives SETs through some distribution method.

#### Subject

A SET describes an event or state change that has occurred about a Subject. A Subject may be a principal (e.g., [Section 4.1.2 \[RFC7519\]](#)), a web resource, an entity such as an IP address, or the issuer itself that a SET might reference.

**Profiling Specification** A specification that uses the SET Token specification to define one or more event types and the associated claims included.



## **2. The Security Event Token (SET)**

A SET conveys a statement (in the form of a JWT [[RFC7519](#)]) about a single security event in relation to a Subject.

The schema and structure of a SET follows the JWT [[RFC7519](#)] specification. A SET has the following structure:

- o An outer JSON object that acts as the SET "envelope". The envelope contains a set of name/value pairs called the JWT Claims Set, typically common to every SET or common to a number of different Events within a single Profiling Specification or a related series of specifications. Claims in the envelope (the outer JSON structure) SHOULD be registered in the JWT Token Claims Registry [Section 10.1 \[RFC7519\]](#) or be Public Claims or Private Claims as also defined in [[RFC7519](#)].
- o Envelope claims that are profiled and defined in this specification are used to validate a SET and declare the contents of the event data included in the SET. The claim "events" identifies the event types expressed that are related to the Security Subject and MAY also include event-specific data.
- o Each JSON member of the "events" object is a name and value pair. The JSON attribute name is a URI String value that expresses an event type, and the corresponding value is a JSON object known as the event "payload". The payload JSON object contains claims typically unique to the event's URI type value and are not registered as JWT claims. These claims are defined by their associated Profiling Specification. An event with no payload claims SHALL be represented as the empty JSON object ("{}"). In many cases, one event URI expresses the primary event URI, while other events might be considered extensions that MAY be used to do things such as:
  - \* A categorization event type to provide classification information (e.g., threat type or level).
  - \* An enhancement of an existing specifications the arise over time.
  - \* An extension needed to link a potential series of events.
  - \* Localized specific purpose event URI used between a particular Event Transmitter and Receiver.





The following is a non-normative example showing the JWT Claims Set for a hypothetical SCIM password reset SET. This example shows an additional events value ("https://example.com/scim/event/passwordResetExt") used to convey additional information -- in this case, the current count of reset attempts:

```
{
  "jti": "3d0c3cf797584bd193bd0fb1bd4e7d30",
  "iat": 1458496025,
  "iss": "https://scim.example.com",
  "aud": [
    "https://jhub.example.com/Feeds/98d52461fa5bbc879593b7754",
    "https://jhub.example.com/Feeds/5d7604516b1d08641d7676ee7"
  ],
  "sub": "https://scim.example.com/Users/44f6142df96bd6ab61e7521d9",
  "events": {
    "urn:ietf:params:scim:event:passwordReset":
      { "id": "44f6142df96bd6ab61e7521d9" },
    "https://example.com/scim/event/passwordResetExt":
      { "resetAttempts": 5 }
  }
}
```

Figure 1: Example SCIM Password Reset Event

The event in the figure above expresses hypothetical password reset event for SCIM [[RFC7644](#)]. The JWT consists of:

- o An "events" claim specifying the hypothetical SCIM URN ("urn:ietf:params:scim:event:passwordReset") for a password reset, and a local schema, "https://example.com/scim/event/passwordResetExt", that is used to provide additional event information such as the current count of resets.
- o An "iss" claim, denoting the Event Transmitter.
- o The "sub" claim specifies the SCIM resource URI that was affected.
- o The "aud" claim specifies the intended audiences for the event. The syntax of the "aud" claim is defined in [Section 4.1.3](#) [[RFC7519](#)].

In this example, the SCIM event indicates that a password has been updated and the current password reset count is 5. Notice that the value for "resetAttempts" is actually part of its own JSON object associated with its own event URI attribute.



Here is another example JWT Claims Set for a security event token, this one for a Logout Token:

```
{
  "iss": "https://server.example.com",
  "sub": "248289761001",
  "aud": "s6BhdRkqt3",
  "iat": 1471566154,
  "jti": "bWJq",
  "sid": "08a5019c-17e1-4977-8f42-65a12843ea02",
  "events": {
    "http://schemas.openid.net/event/backchannel-logout": {}
  }
}
```

Figure 2: Example OpenID Back-Channel Logout Event

Note that the above SET has an empty JSON object and uses the JWT registered claims "sub" and "sid" to identify the subject that was logged-out.

In the following example JWT Claims Set, a fictional medical service collects consent for medical actions and notifies other parties. The individual for whom consent is identified was originally authenticated via OpenID Connect. In this case, the issuer of the security event is an application rather than the OpenID provider:

```
{
  "jti": "fb4e75b5411e4e19b6c0fe87950f7749",

  "sub": "248289761001",
  "iat": 1458496025,
  "iss": "https://my.examplemed.com",
  "aud": [
    "https://rp.example.com"
  ],
  "events": {
    "https://openid.net/heart/specs/consent.html": {
      "iss": "https://connect.example.com",
      "consentUri": [
        "https://terms.examplemed.com/labdisclosure.html#Agree"
      ]
    }
  }
}
```

Figure 3: Example Consent Event



In the above example, the attribute "iss" contained within the payload for the event "https://openid.net/heart/specs/consent.html", refers to the issuer of the Security Subject ("sub") rather than the event issuer "https://my.examplemed.com". They are distinct from the top level value of "iss" which always refers to the issuer of the event - a medical consent service that is a relying party to the OpenID Provider.

## **[2.1.](#) Core SET Claims**

The following are claims that are based on [\[RFC7519\]](#) claim definitions and are profiled for use in an event token:

### **jti**

As defined by [Section 4.1.7 \[RFC7519\]](#) contains a unique identifier for an event. The identifier SHOULD be unique within a particular event feed and MAY be used by clients to track whether a particular event has already been received. This claim is REQUIRED.

### **iss**

A single valued String containing the URI of the service provider publishing the SET (the issuer). This claim is REQUIRED. Note that when a SET is expressing an event about a Security Subject for which the SET issuer is not the issuer of the Security Subject, the conflict SHALL be resolved by including the Security Subject "iss" value within the event "payload" (see "events" claim).

### **aud**

The syntax of the claim is as defined in [Section 4.1.3 \[RFC7519\]](#). This claim MAY contains one or more audience identifiers for the SET. This claim is RECOMMENDED.

### **iat**

As defined by [Section 4.1.6 \[RFC7519\]](#), a value containing a NumericDate, which represents when the event was issued. Unless otherwise specified, the value SHOULD be interpreted as equivalent to the actual time of the event. This claim is REQUIRED.

### **nbf**

Defined by [Section 4.1.5 \[RFC7519\]](#), a number whose value is a NumericDate. In the context of the SET token it SHALL be interpreted to mean a date in which the event is believed to have occurred (in the past) or will occur in the future. Note: there MAY be some cases where "nbf" is still smaller than "iat" such as when it took an extended time for a SET to be issued (for example after some analysis). This claim is OPTIONAL.



- sub As defined by [Section 4.1.2 \[RFC7519\]](#), a String or URI value representing the principal or the subject of the SET. This is usually the entity whose "state" was changed. For example, an IP Address was added to a black list. A URI representing a user resource that was modified. A token identifier for a revoked token. If used, the Profile Specification SHOULD define the content and format semantics for the value. This claim is OPTIONAL, as the principal for any given profile may already be identified without the inclusion of a subject claim.
- exp As defined by [\[RFC7519\]](#), this claim is time on which the JWT MUST NOT be accepted for processing. In the context of a SET however, this notion does not apply since a SET reflects something that has already been processed and is historical in nature. While some specifications MAY have a need for this claim, its use in general cases is NOT RECOMMENDED.

The following are new claims defined by this specification:

#### events

The semantics of this claim is to define a set of event statements that each MAY add additional claims to fully describe a single logical event that has occurred (e.g. a state change to a subject). Multiple event statements of the same type SHALL NOT be accepted. The "events" claim SHOULD NOT be used to express multiple logical events.

The value of "events" is a JSON object whose members are a set of JSON name/value pairs whose names are URIs representing the event statements being expressed. Event URI values SHOULD be stable values (e.g. a permanent URL for an event specification). For each name present, the corresponding value SHALL be a JSON object. The JSON object MAY be an empty object ("{}"), or it MAY be a JSON object containing data as described by the Profiling Specification.

#### txn

An OPTIONAL String value that represents a unique transaction identifier. In cases where multiple SETs are issued based on different event URIs, the transaction identifier MAY be used to correlate SETs to the same originating event or stateful change.

## **[2.2. Security Event Token Construction](#)**

A SET is a JWT [\[RFC7519\]](#) that is constructed by building a JSON structure that constitutes an event object which is then used as the body of a JWT.





While this specification uses JWT to convey a SET, implementers SHALL NOT use SETs to convey authentication or authorization assertions.

The following is an example JWT Claims Set for a security event token (which has been formatted for readability):

```
{
  "jti": "4d3559ec67504aaba65d40b0363faad8",
  "iat": 1458496404,
  "iss": "https://scim.example.com",
  "aud": [
    "https://scim.example.com/Feeds/98d52461fa5bbc879593b7754",
    "https://scim.example.com/Feeds/5d7604516b1d08641d7676ee7"
  ],
  "events": {
    "urn:ietf:params:scim:event:create": {
      "ref":
        "https://scim.example.com/Users/44f6142df96bd6ab61e7521d9",
      "attributes": ["id", "name", "userName", "password", "emails"]
    }
  }
}
```

Figure 4: Example Event Claims

When transmitted, the above JSON body must be converted into a JWT as per [\[RFC7519\]](#).

The following is an example of a SCIM Event expressed as an unsecured JWT. The JWT header of:

```
{"alg":"none"}
```

Base64url encoding of the octets of the UTF-8 representation of the header yields:

```
eyJhbGciOiJub25lIn0
```



The example JSON Event Data is encoded as follows:

```
e3sgIAogICJqdGkiOiAiNGQzNTU5ZW2M2NzUwNGFhYmE2NWQ0MGIwMzYzZmFhZDgiLAog
ICJpYXQiOiAxNDU4NDk2NDA0LAogICJpc3MiOiAiaHR0cHM6Ly9zY2ltLmV4YW1wbGUu
Y29tIiwgIAogICJhdWQiOiBbCiAgICJodHRwczovL3Njaw0uZXhhbXBsZS5jb20vRmVl
ZHMvOThkNTI0NjFmYTViYmM4Nzk1OTNiNzc1NCIsCiAgICJodHRwczovL3Njaw0uZXhh
bXBsZS5jb20vRmVlZHMvNWQ3NjA0NTE2YjFkMDg2NDFkNzY3NmVlNyIKICBdLCAgCiAg
CiAgImV2ZW50cyI6IHsKICAgICJ1cm46aWV0ZjpwYXJhbXM6c2NpbTpldmVudDpjcmVh
dGUiOiB7CiAgICAgICJyZWYiOgogICAgICAgICJodHRwczovL3Njaw0uZXhhbXBsZS5j
b20vVXNlcnMvNDRmNjE0MmRmOTZiZDZhYjYxZTc1MjFkOSIsCiAgICAgICJhdHRyaWJ1
dGVzIjpbImlkIiwgIm5hbWUiLCaidXNlck5hbWUiLCaiaGFzc3dvcmQiLCaiaZW1haWxz
Il0KICAgIH0KICB9Cn0
```

The encoded JWS signature is the empty string. Concatenating the parts yields:

```
eyJhbGciOiJub251In0
.
e3sgIAogICJqdGkiOiAiNGQzNTU5ZW2M2NzUwNGFhYmE2NWQ0MGIwMzYzZmFhZDgiLAog
ICJpYXQiOiAxNDU4NDk2NDA0LAogICJpc3MiOiAiaHR0cHM6Ly9zY2ltLmV4YW1wbGUu
Y29tIiwgIAogICJhdWQiOiBbCiAgICJodHRwczovL3Njaw0uZXhhbXBsZS5jb20vRmVl
ZHMvOThkNTI0NjFmYTViYmM4Nzk1OTNiNzc1NCIsCiAgICJodHRwczovL3Njaw0uZXhh
bXBsZS5jb20vRmVlZHMvNWQ3NjA0NTE2YjFkMDg2NDFkNzY3NmVlNyIKICBdLCAgCiAg
CiAgImV2ZW50cyI6IHsKICAgICJ1cm46aWV0ZjpwYXJhbXM6c2NpbTpldmVudDpjcmVh
dGUiOiB7CiAgICAgICJyZWYiOgogICAgICAgICJodHRwczovL3Njaw0uZXhhbXBsZS5j
b20vVXNlcnMvNDRmNjE0MmRmOTZiZDZhYjYxZTc1MjFkOSIsCiAgICAgICJhdHRyaWJ1
dGVzIjpbImlkIiwgIm5hbWUiLCaidXNlck5hbWUiLCaiaGFzc3dvcmQiLCaiaZW1haWxz
Il0KICAgIH0KICB9Cn0
.
```

Figure 5: Example Unsecured Security Event Token

For the purpose of a simpler example in Figure 5, an unencrypted token was shown. When SETs are not signed or encrypted, the Event Receiver MUST depend upon TLS and HTTP to authenticate the sender and the security of the channel to authenticate the SET and its sender.

When validation (i.e. auditing), or additional transmission security is required, JWS Signing and JWS Encryption MAY be used. To create and or validate a signed or encrypted SET, follow the instructions in [section 7 of \[RFC7519\]](#).

### 3. Security Considerations



### **[3.1.](#) Confidentiality and Integrity**

SETs may often contain sensitive information. Therefore, methods for distribution of events SHOULD require the use of a transport-layer security mechanism when distributing events. Parties MUST support TLS 1.2 [[RFC5246](#)] and MAY support additional transport-layer mechanisms meeting its security requirements. When using TLS, the client MUST perform a TLS/SSL server certificate check, per [[RFC6125](#)]. Implementation security considerations for TLS can be found in "Recommendations for Secure Use of TLS and DTLS" [[RFC7525](#)].

Security Events distributed through third-parties or that carry personally identifiable information, SHOULD be encrypted using JWE [[RFC7516](#)] or secured for confidentiality by other means.

Security Events distributed without authentication over the channel, such as via TLS ([[RFC5246](#)] and [[RFC6125](#)]), and/or OAuth2 [[RFC6749](#)], or Basic Authentication [[RFC7617](#)], MUST be signed using JWS [[RFC7515](#)] so that individual events MAY be authenticated and validated by the Event Receiver.

### **[3.2.](#) Delivery**

This specification does not define a delivery mechanism by itself. In addition to confidentiality and integrity (discussed above), implementers and Profile Specifications MUST consider the consequences of delivery mechanisms that are not secure and/or not assured. For example, while a SET may be end-to-end secured using JWE encrypted SETs, without TLS there is no assurance that the correct endpoint received the SET and that it could be successfully processed.

### **[3.3.](#) Sequencing**

As defined in this specification, there is no defined way to order multiple SETs in a sequence. Depending on the type and nature of SET event, order may or may not matter. For example, in provisioning, event order is critical -- an object could not be modified before it was created. In other SET types, such as a token revocation, the order of SETs for revoked tokens does not matter. If however, the event was described as a log-in or logged-out status for a user subject, then order becomes important.

Profiling Specifications and implementers SHOULD take caution when using timestamps such as "iat" to define order. Distributed systems will have some amount of clock-skew and thus time by itself will not guarantee order.



Specifications profiling SET SHOULD define a mechanism for detecting order or sequence of events. For example, the "txn" claim could contain an ordered value (e.g., a counter) that the issuer defines.

### **3.4. Timing Issues**

When SETs are delivered asynchronously and/or out-of-band with respect to the original action that incurred the security event, it is important to consider that a SET might be delivered to a Subscriber in advance or well behind the process that caused the event. For example, a user having been required to logout and then log back in again, may cause a logout SET to be issued that may arrive at the same time as the user-agent accesses a web site having just logged-in. If timing is not handled properly, the effect would be to erroneously treat the new user session as logged out. Profiling Specifications SHOULD be careful to anticipate timing and subject selection information. For example, it might be more appropriate to cancel a "session" rather than a "user". Alternatively, the specification could use timestamps that allows new sessions to be started immediately after a stated logout event time.

### **3.5. Distinguishing SETs from Access Tokens**

Because [[RFC7519](#)] states that "all claims that are not understood by implementations MUST be ignored.", there is a consideration that a SET token might be confused as an access or authorization token in the case where a SET is mistakenly or intentionally intercepted and presented as an access token. To avoid this, it is recommended that implementers consider one or more of the following:

- o Avoid use of the JWT claim "exp" within the envelope.
- o Where possible, use a separate "aud" claim value to distinguish between the SET subscriber and the audience of an access token. For example, a Logout while intended for the same relying party could use a different audience to distinguish between normal access and logout notification.
- o Modify access validation systems to check for the presence of the "events" claim as a means to detect security event tokens. This is particularly useful if the same endpoint may receive both types of tokens.
- o Consider avoiding use of the "sub" claim at the top level.





## **4. Privacy Considerations**

If a SET needs to be retained for audit purposes, JWS MAY be used to provide verification of its authenticity.

Event Transmitters SHOULD attempt to specialize feeds so that the content is targeted to the specific business and protocol needs of subscribers.

When sharing personally identifiable information or information that is otherwise considered confidential to affected users, Event Transmitters and Receivers MUST have the appropriate legal agreements and user consent or terms of service in place.

The propagation of subject identifiers can be perceived as personally identifiable information. Where possible, Event Transmitters and Receivers SHOULD devise approaches that prevent propagation -- for example, the passing of a hash value that requires the subscriber to already know the subject.

## **5. IANA Considerations**

### **5.1. JSON Web Token Claims Registration**

This specification registers the "events" and "txn" claims in the IANA "JSON Web Token Claims" registry [[IANA.JWT.Claims](#)] established by [[RFC7519](#)].

#### **5.1.1. Registry Contents**

- o Claim Name: "events"
- o Claim Description: Security Event Object
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [[ this specification ]]
  
- o Claim Name: "txn"
- o Claim Description: Transaction Identifier
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [[ this specification ]]

## **6. References**

### **6.1. Normative References**

[IANA.JWT.Claims]  
IANA, "JSON Web Token Claims",  
<<http://www.iana.org/assignments/jwt>>.



- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), DOI 10.17487/RFC3986, January 2005, <<http://www.rfc-editor.org/info/rfc3986>>.
- [RFC5246] Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2", [RFC 5246](#), DOI 10.17487/RFC5246, August 2008, <<http://www.rfc-editor.org/info/rfc5246>>.
- [RFC6125] Saint-Andre, P. and J. Hodges, "Representation and Verification of Domain-Based Application Service Identity within Internet Public Key Infrastructure Using X.509 (PKIX) Certificates in the Context of Transport Layer Security (TLS)", [RFC 6125](#), DOI 10.17487/RFC6125, March 2011, <<http://www.rfc-editor.org/info/rfc6125>>.
- [RFC6749] Hardt, D., Ed., "The OAuth 2.0 Authorization Framework", [RFC 6749](#), DOI 10.17487/RFC6749, October 2012, <<http://www.rfc-editor.org/info/rfc6749>>.
- [RFC7519] Jones, M., Bradley, J., and N. Sakimura, "JSON Web Token (JWT)", [RFC 7519](#), DOI 10.17487/RFC7519, May 2015, <<http://www.rfc-editor.org/info/rfc7519>>.
- [RFC7525] Sheffer, Y., Holz, R., and P. Saint-Andre, "Recommendations for Secure Use of Transport Layer Security (TLS) and Datagram Transport Layer Security (DTLS)", [BCP 195](#), [RFC 7525](#), DOI 10.17487/RFC7525, May 2015, <<http://www.rfc-editor.org/info/rfc7525>>.
- [RFC7617] Reschke, J., "The 'Basic' HTTP Authentication Scheme", [RFC 7617](#), DOI 10.17487/RFC7617, September 2015, <<http://www.rfc-editor.org/info/rfc7617>>.

## **6.2. Informative References**

- [openid-connect-core] Sakimura, N., Bradley, J., Jones, M., de Medeiros, B., and C. Mortimore, "OpenID Connect Core 1.0", November 2014, <[http://openid.net/specs/openid-connect-core-1\\_0.html](http://openid.net/specs/openid-connect-core-1_0.html)>.



- [RFC7009] Lodderstedt, T., Ed., Dronia, S., and M. Scurtescu, "OAuth 2.0 Token Revocation", [RFC 7009](#), DOI 10.17487/RFC7009, August 2013, <<http://www.rfc-editor.org/info/rfc7009>>.
- [RFC7515] Jones, M., Bradley, J., and N. Sakimura, "JSON Web Signature (JWS)", [RFC 7515](#), DOI 10.17487/RFC7515, May 2015, <<http://www.rfc-editor.org/info/rfc7515>>.
- [RFC7516] Jones, M. and J. Hildebrand, "JSON Web Encryption (JWE)", [RFC 7516](#), DOI 10.17487/RFC7516, May 2015, <<http://www.rfc-editor.org/info/rfc7516>>.
- [RFC7517] Jones, M., "JSON Web Key (JWK)", [RFC 7517](#), DOI 10.17487/RFC7517, May 2015, <<http://www.rfc-editor.org/info/rfc7517>>.
- [RFC7644] Hunt, P., Ed., Grizzle, K., Ansari, M., Wahlstroem, E., and C. Mortimore, "System for Cross-domain Identity Management: Protocol", [RFC 7644](#), DOI 10.17487/RFC7644, September 2015, <<http://www.rfc-editor.org/info/rfc7644>>.
- [saml-core-2.0]  
Internet2, "Assertions and Protocols for the OASIS Security Assertion Markup Language (SAML) V2.0", March 2005.

## [Appendix A.](#) Acknowledgments

The editors would like to thank the members of the SCIM WG which began discussions of provisioning events starting with: [draft-hunt-scim-notify-00](#) in 2015.

The editors would like to thank the participants in the IETF id-event mailing list and related working groups for their support of this specification.

## [Appendix B.](#) Change Log

From the original [draft-hunt-idevent-token](#):

Draft 01 - PH - Renamed eventUris to events

Draft 00 - PH - First Draft

Draft 01 - PH - Fixed some alignment issues with JWT. Remove event type attribute.



Draft 02 - PH - Renamed to Security Events, removed questions, clarified examples and intro text, and added security and privacy section.

Draft 03 - PH

General edit corrections from Sarah Squire

Changed "event" term to "SET"

Corrected author organization for William Denniss to Google

Changed definition of SET to be 2 parts, an envelope and 1 or more payloads.

Clarified that the intent is to express a single event with optional extensions only.

- mbj - Registered "events" claim, and proof-reading corrections.

Draft 04 - PH -

- o Re-added the "sub" claim with clarifications that any SET type may use it.
- o Added additional clarification on the use of envelope vs. payload attributes
- o Added security consideration for event timing.
- o Switched use of "attribute" to "claim" for consistency.
- o Revised examples to put "sub" claim back in the top level.
- o Added clarification that SETs typically do not use "exp".
- o Added security consideration for distinguishing Access Tokens and SETs.

Draft 05 - PH - Fixed find/replace error that resulted in claim being spelled claimc

Draft 06 - PH -

- o Corrected typos
- o New txn claim
- o New security considerations Sequencing and Timing Issues

Draft 07 -

- o PH - Moved payload objects to be values of event URI attributes, per discussion.
- o mbj - Applied terminology consistency and grammar cleanups.

Draft 08 - PH -

- o Added clarification to status of examples





- o Changed from primary vs. extension to state that multiple events may be expressed, some of which may or may not be considered extensions of others (which is for the subscriber or profiling specifications to determine).

- o Other editorial changes suggested by Yaron

From [draft-ietf-secevent-token](#):

Draft 00 - PH - First WG Draft based on [draft-hunt-idevent-token](#)

Draft 01 - PH - Changes as follows:

- o Changed terminology away from pub-sub to transmitter/receiver based on WG feedback
- o Cleaned up/removed some text about extensions (now only used as example)
- o Clarify purpose of spec vs. future profiling specs that define actual events

#### Authors' Addresses

Phil Hunt (editor)  
Oracle Corporation

Email: [phil.hunt@yahoo.com](mailto:phil.hunt@yahoo.com)

William Denniss  
Google

Email: [wdenniss@google.com](mailto:wdenniss@google.com)

Morteza Ansari  
Cisco

Email: [morteza.ansari@cisco.com](mailto:morteza.ansari@cisco.com)

Michael B. Jones  
Microsoft

Email: [mbj@microsoft.com](mailto:mbj@microsoft.com)

URI: <http://self-issued.info/>

