

Network Working Group  
Internet-Draft  
Expires: May 19, 2005

C. Lonvick, Ed.  
Cisco Systems, Inc.  
November 18, 2004

SSH Protocol Assigned Numbers  
draft-ietf-secsh-assignednumbers-08.txt

Status of this Memo

This document is an Internet-Draft and is subject to all provisions of [section 3 of RFC 3667](#). By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she become aware will be disclosed, in accordance with [RFC 3668](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on May 19, 2005.

Copyright Notice

Copyright (C) The Internet Society (2004).

Abstract

This document defines the instructions to the IANA and the initial state of the IANA assigned numbers for the SSH protocol. It is intended only for the initialization of the IANA registries referenced in the documents.

Internet-Draft

SSH Protocol Assigned Numbers

November 2004

## Table of Contents

<a href="#">1.</a>	Editor's Note . . . . .	<a href="#">4</a>
<a href="#">2.</a>	Introduction . . . . .	<a href="#">4</a>
<a href="#">3.</a>	Conventions Used in This Document . . . . .	<a href="#">4</a>
<a href="#">4.</a>	IANA Considerations . . . . .	<a href="#">5</a>
<a href="#">4.1</a>	Message Numbers . . . . .	<a href="#">5</a>
<a href="#">4.1.1</a>	Conventions . . . . .	<a href="#">5</a>
<a href="#">4.1.2</a>	Initial Assignments . . . . .	<a href="#">6</a>
<a href="#">4.1.3</a>	Future Assignments . . . . .	<a href="#">7</a>
<a href="#">4.2</a>	Disconnection Messages Reason Codes and Descriptions . . . . .	<a href="#">7</a>
<a href="#">4.2.1</a>	Conventions . . . . .	<a href="#">7</a>
<a href="#">4.2.2</a>	Initial Assignments . . . . .	<a href="#">7</a>
<a href="#">4.2.3</a>	Future Assignments . . . . .	<a href="#">8</a>
<a href="#">4.3</a>	Channel Connection Failure Reason Codes and Descriptions . . . . .	<a href="#">8</a>
<a href="#">4.3.1</a>	Conventions . . . . .	<a href="#">8</a>
<a href="#">4.3.2</a>	Initial Assignments . . . . .	<a href="#">8</a>
<a href="#">4.3.3</a>	Future Assignments . . . . .	<a href="#">9</a>
<a href="#">4.3.4</a>	Notes about the PRIVATE USE Range . . . . .	<a href="#">9</a>
<a href="#">4.4</a>	Extended Channel Data Transfer data_type_code and Data . . . . .	<a href="#">9</a>
<a href="#">4.4.1</a>	Conventions . . . . .	<a href="#">9</a>
<a href="#">4.4.2</a>	Initial Assignments . . . . .	<a href="#">10</a>
<a href="#">4.4.3</a>	Future Assignments . . . . .	<a href="#">10</a>
<a href="#">4.5</a>	Pseudo-Terminal Encoded Terminal Modes . . . . .	<a href="#">10</a>
<a href="#">4.5.1</a>	Conventions . . . . .	<a href="#">10</a>
<a href="#">4.5.2</a>	Initial Assignments . . . . .	<a href="#">10</a>
<a href="#">4.5.3</a>	Future Assignments . . . . .	<a href="#">12</a>
<a href="#">4.6</a>	Names . . . . .	<a href="#">12</a>
<a href="#">4.6.1</a>	Conventions for Names . . . . .	<a href="#">12</a>
<a href="#">4.6.2</a>	Future Assignments of Names . . . . .	<a href="#">13</a>
<a href="#">4.7</a>	Service Names . . . . .	<a href="#">13</a>
<a href="#">4.8</a>	Authentication Method Names . . . . .	<a href="#">13</a>
<a href="#">4.9</a>	Connection Protocol Assigned Names . . . . .	<a href="#">14</a>
<a href="#">4.9.1</a>	Connection Protocol Channel Types . . . . .	<a href="#">14</a>
<a href="#">4.9.2</a>	Connection Protocol Global Request Names . . . . .	<a href="#">14</a>
<a href="#">4.9.3</a>	Connection Protocol Channel Request Names . . . . .	<a href="#">14</a>
<a href="#">4.9.4</a>	Initial Assignment of Signal Names . . . . .	<a href="#">14</a>
<a href="#">4.10</a>	Key Exchange Method Names . . . . .	<a href="#">15</a>
<a href="#">4.11</a>	Assigned Algorithm Names . . . . .	<a href="#">15</a>
<a href="#">4.11.1</a>	Encryption Algorithm Names . . . . .	<a href="#">15</a>
<a href="#">4.11.2</a>	MAC Algorithm Names . . . . .	<a href="#">16</a>
<a href="#">4.11.3</a>	Public Key Algorithm Names . . . . .	<a href="#">16</a>

[4.11.4](#) Compression Algorithm Names . . . . . [16](#)  
[5.](#) Security Considerations . . . . . [16](#)  
[6.](#) References . . . . . [17](#)  
[6.1](#) Normative References . . . . . [17](#)  
[6.2](#) Informative References . . . . . [17](#)  
Author's Address . . . . . [18](#)

Intellectual Property and Copyright Statements . . . . . [19](#)

## 1. Editor's Note

The references in this document are statically defined. However, the locations of the referenced materials are dynamic and are changing with the whims of the Working Group. Please do not comment to the editor or the Working Group about inaccuracies along those lines in this document at this time. (This paragraph will be removed before this document is submitted to the RFC Editor.)

## 2. Introduction

This document does not define any new protocols. It is intended only to create the initial state of the IANA databases for the SSH protocol and also contains instructions for future assignments. Except for one HISTORIC algorithm generally regarded as obsolete, this document does not define any new protocols or any number ranges not already defined in: [[SSH-ARCH](#)], [[SSH-TRANS](#)], [[SSH-USERAUTH](#)], [[SSH-CONNECT](#)].

## 3. Conventions Used in This Document

All documents related to the SSH protocols shall use the keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" to describe requirements. These keywords are to be interpreted as described in [[RFC2119](#)].

The keywords "PRIVATE USE", "HIERARCHICAL ALLOCATION", "FIRST COME

FIRST SERVED", "EXPERT REVIEW", "SPECIFICATION REQUIRED", "IESG APPROVAL", "IETF CONSENSUS", and "STANDARDS ACTION" that appear in this document when used to describe namespace allocation are to be interpreted as described in [[RFC2434](#)]. These designations are repeated in this document for clarity.

PRIVATE USE - For private or local use only, with the type and purpose defined by the local site. No attempt is made to prevent multiple sites from using the same value in different (and incompatible) ways. There is no need for IANA to review such assignments and assignments are not generally useful for interoperability.

HIERARCHICAL ALLOCATION - Delegated managers can assign values provided they have been given control over that part of the name space. IANA controls the higher levels of the namespace according to one of the other policies.

FIRST COME FIRST SERVED - Anyone can obtain an assigned number, so long as they provide a point of contact and a brief description of

what the value would be used for. For numbers, the exact value is generally assigned by the IANA; with names, specific names are usually requested.

EXPERT REVIEW - approval by a Designated Expert is required.

SPECIFICATION REQUIRED - Values and their meaning must be documented in an RFC or other permanent and readily available reference, in sufficient detail so that interoperability between independent implementations is possible.

IESG APPROVAL - New assignments must be approved by the IESG, but there is no requirement that the request be documented in an RFC (though the IESG has discretion to request documents or other supporting materials on a case-by-case basis).

IETF CONSENSUS - New values are assigned through the IETF consensus process. Specifically, new assignments are made via RFCs approved by the IESG. Typically, the IESG will seek input on prospective assignments from appropriate persons (e.g., a relevant Working Group if one exists).

STANDARDS ACTION - Values are assigned only for Standards Track RFCs approved by the IESG.

#### [4.](#) IANA Considerations

This entire document is the IANA considerations for the SSH protocol as is defined in [[SSH-ARCH](#)], [[SSH-TRANS](#)], [[SSH-USERAUTH](#)], [[SSH-CONNECT](#)]. This section contains conventions used in naming the namespaces, the initial state of the registry, and instructions for future assignments.

##### [4.1](#) Message Numbers

The Message Number is an 8-bit value, which describes the payload of a packet.

###### [4.1.1](#) Conventions

Protocol packets have message numbers in the range 1 to 255. These numbers are allocated as follows:

Transport layer protocol:

1 to 19      Transport layer generic (e.g. disconnect, ignore, debug, etc.)

20 to 29      Algorithm negotiation

30 to 49      Key exchange method specific (numbers can be reused for different authentication methods)

User authentication protocol:

50 to 59      User authentication generic

60 to 79      User authentication method specific (numbers can be reused for different authentication methods)

Connection protocol:

80 to 89      Connection protocol generic

90 to 127     Channel related messages

Reserved for client protocols:

128 to 191 Reserved

Local extensions:

192 to 255 Local extensions

#### [4.1.2](#) Initial Assignments

Message ID -----	Value -----	Reference -----
SSH_MSG_DISCONNECT	1	[ <a href="#">SSH-TRANS</a> ]
SSH_MSG_IGNORE	2	[ <a href="#">SSH-TRANS</a> ]
SSH_MSG_UNIMPLEMENTED	3	[ <a href="#">SSH-TRANS</a> ]
SSH_MSG_DEBUG	4	[ <a href="#">SSH-TRANS</a> ]
SSH_MSG_SERVICE_REQUEST	5	[ <a href="#">SSH-TRANS</a> ]
SSH_MSG_SERVICE_ACCEPT	6	[ <a href="#">SSH-TRANS</a> ]
SSH_MSG_KEXINIT	20	[ <a href="#">SSH-TRANS</a> ]
SSH_MSG_NEWKEYS	21	[ <a href="#">SSH-TRANS</a> ]
SSH_MSG_KEXDH_INIT	30	[ <a href="#">SSH-TRANS</a> ]
SSH_MSG_KEXDH_REPLY	31	[ <a href="#">SSH-TRANS</a> ]
SSH_MSG_USERAUTH_REQUEST	50	[ <a href="#">SSH-USERAUTH</a> ]
SSH_MSG_USERAUTH_FAILURE	51	[ <a href="#">SSH-USERAUTH</a> ]
SSH_MSG_USERAUTH_SUCCESS	52	[ <a href="#">SSH-USERAUTH</a> ]
SSH_MSG_USERAUTH_BANNER	53	[ <a href="#">SSH-USERAUTH</a> ]
SSH_MSG_USERAUTH_PK_OK	60	[ <a href="#">SSH-USERAUTH</a> ]
SSH_MSG_GLOBAL_REQUEST	80	[ <a href="#">SSH-CONNECT</a> ]
SSH_MSG_REQUEST_SUCCESS	81	[ <a href="#">SSH-CONNECT</a> ]
SSH_MSG_REQUEST_FAILURE	82	[ <a href="#">SSH-CONNECT</a> ]
SSH_MSG_CHANNEL_OPEN	90	[ <a href="#">SSH-CONNECT</a> ]

SSH_MSG_CHANNEL_OPEN_CONFIRMATION	91	[ <a href="#">SSH-CONNECT</a> ]
SSH_MSG_CHANNEL_OPEN_FAILURE	92	[ <a href="#">SSH-CONNECT</a> ]
SSH_MSG_CHANNEL_WINDOW_ADJUST	93	[ <a href="#">SSH-CONNECT</a> ]
SSH_MSG_CHANNEL_DATA	94	[ <a href="#">SSH-CONNECT</a> ]
SSH_MSG_CHANNEL_EXTENDED_DATA	95	[ <a href="#">SSH-CONNECT</a> ]
SSH_MSG_CHANNEL_EOF	96	[ <a href="#">SSH-CONNECT</a> ]
SSH_MSG_CHANNEL_CLOSE	97	[ <a href="#">SSH-CONNECT</a> ]

SSH_MSG_CHANNEL_REQUEST	98	[ <a href="#">SSH-CONNECT</a> ]
SSH_MSG_CHANNEL_SUCCESS	99	[ <a href="#">SSH-CONNECT</a> ]
SSH_MSG_CHANNEL_FAILURE	100	[ <a href="#">SSH-CONNECT</a> ]

### [4.1.3](#) Future Assignments

Requests for assignments of new message numbers in the range of 1 to 127 MUST be done through the STANDARDS ACTION method as described in [[RFC2434](#)].

Requests for assignments of new message numbers in the range of 128 to 191 MUST be done through the IETF CONSENSUS method as described in [[RFC2434](#)].

The IANA will not control the message numbers range of 192 through 255. This range will be left for PRIVATE USE.

## [4.2](#) Disconnection Messages Reason Codes and Descriptions

The Disconnection Message 'reason code' is a uint32 value. The associated Disconnection Message 'description string' is a human-readable message which describes the disconnect reason.

### [4.2.1](#) Conventions

Protocol packets containing the SSH\_MSG\_DISCONNECT message MUST have Disconnection Message 'reason code' values in the range of 0x00000001 to 0xFFFFFFFF. These are described in [[SSH-TRANS](#)].

### [4.2.2](#) Initial Assignments

description string -----	reason code -----
SSH_DISCONNECT_HOST_NOT_ALLOWED_TO_CONNECT	1
SSH_DISCONNECT_PROTOCOL_ERROR	2
SSH_DISCONNECT_KEY_EXCHANGE_FAILED	3
SSH_DISCONNECT_RESERVED	4
SSH_DISCONNECT_MAC_ERROR	5
SSH_DISCONNECT_COMPRESSION_ERROR	6
SSH_DISCONNECT_SERVICE_NOT_AVAILABLE	7



SSH_DISCONNECT_PROTOCOL_VERSION_NOT_SUPPORTED	8
SSH_DISCONNECT_HOST_KEY_NOT_VERIFIABLE	9
SSH_DISCONNECT_CONNECTION_LOST	10
SSH_DISCONNECT_BY_APPLICATION	11
SSH_DISCONNECT_TOO_MANY_CONNECTIONS	12
SSH_DISCONNECT_AUTH_CANCELLED_BY_USER	13
SSH_DISCONNECT_NO_MORE_AUTH_METHODS_AVAILABLE	14
SSH_DISCONNECT_ILLEGAL_USER_NAME	15

### [4.2.3](#) Future Assignments

Disconnection Message 'reason code' values MUST be assigned sequentially. Requests for assignments of new Disconnection Message 'reason code' values, and their associated Disconnection Message 'description string', in the range of 0x00000010 through 0xFDFFFFFF MUST be done through the IETF CONSENSUS method as described in [\[RFC2434\]](#). The IANA will not assign Disconnection Message 'reason code' values in the range of 0xFE000000 through 0xFFFFFFFF. Disconnection Message 'reason code' values in that range are left for PRIVATE USE as described in [\[RFC2434\]](#).

### [4.3](#) Channel Connection Failure Reason Codes and Descriptions

The Channel Connection Failure 'reason code' is a uint32 value. The associated Channel Connection Failure 'description string' is a human-readable message which describes the channel connection failure reason. This is described in [\[SSH-CONNECT\]](#).

#### [4.3.1](#) Conventions

Protocol packets containing the SSH\_MSG\_CHANNEL\_OPEN\_FAILURE message MUST have Channel Connection Failure 'reason code' values in the range of 0x00000001 to 0xFFFFFFFF.

#### [4.3.2](#) Initial Assignments

The initial assignments for the 'reason code' values and 'description string' values are given below. Note that the values for the 'reason code' are given in decimal format for readability but that they are actually uint32 values.

description string -----	reason code -----
SSH_OPEN_ADMINISTRATIVELY_PROHIBITED	1
SSH_OPEN_CONNECT_FAILED	2
SSH_OPEN_UNKNOWN_CHANNEL_TYPE	3
SSH_OPEN_RESOURCE_SHORTAGE	4

### [4.3.3](#) Future Assignments

Channel Connection Failure 'reason code' values MUST be assigned sequentially. Requests for assignments of new Channel Connection Failure 'reason code' values, and their associated Channel Connection Failure 'description string', in the range of 0x00000005 to 0x0xFDFFFFFF MUST be done through the IETF CONSENSUS method as described in [[RFC2434](#)]. The IANA will not assign Channel Connection Failure 'reason code' values in the range of 0xFF000000 to 0xFFFFFFFF. Channel Connection Failure 'reason code' values in that range are left for PRIVATE USE as described in [[RFC2434](#)].

### [4.3.4](#) Notes about the PRIVATE USE Range

While it is understood that the IANA will have no control over the range of 0xFF000000 to 0xFFFFFFFF, this range will be split in two parts and administered by the following conventions.

- o The range of 0xFF000000 to 0xFEFFFFFF is to be used in conjunction with locally assigned channels. For example, if a channel is proposed with a 'channel type' of "example\_session@example.com" but fails, then the server will respond with either a 'reason code' assigned by the IANA (as listed above and in the range of 0x00000001 to 0x0xFDFFFFFF), or with a locally assigned value in the range of 0xFF000000 to 0xFEFFFFFF. Naturally, if the server does not understand the proposed 'channel type', even if it is a locally defined 'channel type', then the 'reason code' MUST be 0x00000003 as described above. If the server does understand the 'channel type' but the channel still fails to open, then the server SHOULD respond with a locally assigned 'reason code' value consistent with the proposed, local 'channel type'. It is assumed that practitioners will first attempt to use the IANA assigned 'reason code' values and then document their locally assigned 'reason code' values.
- o There are no restrictions or suggestions for the range starting with 0xFF. No interoperability is expected for anything used in this range. Essentially it is for experimentation.

## [4.4](#) Extended Channel Data Transfer data\_type\_code and Data

The Extended Channel Data Transfer 'data\_type\_code' is an uint23 value. The associated Extended Channel Data Transfer 'data' is a human-readable message which describes the type of data allowed to be transferred in the channel.

#### [4.4.1](#) Conventions

Protocol packets containing the SSH\_MSG\_CHANNEL\_EXTENDED\_DATA message MUST have Extended Channel Data Transfer 'data\_type\_code' values in

the range of 0x00000001 to 0xFFFFFFFF. This is described in [[SSH-CONNECT](#)].

#### [4.4.2](#) Initial Assignments

The initial assignments for the 'data\_type\_code' values and 'data' values are given below. Note that the value for the 'data\_type\_code' is given in decimal format for readability but that the values are actually uint32 values.

data	data_type_code
----	-----
SSH_EXTENDED_DATA_STDERR	1

#### [4.4.3](#) Future Assignments

Extended Channel Data Transfer 'data\_type\_code' values MUST be assigned sequentially. Requests for assignments of new Extended Channel Data Transfer 'data\_type\_code' values, and their associated Extended Channel Data Transfer 'data' strings, in the range of 0x00000002 to 0xFDFFFFFF MUST be done through the IETF CONSENSUS method as described in [[RFC2434](#)]. The IANA will not assign Extended Channel Data Transfer 'data\_type\_code' values in the range of 0xFE000000 to 0xFFFFFFFF. Extended Channel Data Transfer 'data\_type\_code' values in that range are left for PRIVATE USE as described in [[RFC2434](#)].

#### [4.5](#) Pseudo-Terminal Encoded Terminal Modes

SSH\_MSG\_CHANNEL\_REQUEST messages with a "pty-req" string MUST contain "encoded terminal modes". These "encoded terminal modes" are opcode-argument pairs consisting of an opcode and an argument.

#### [4.5.1](#) Conventions

Protocol packets containing the SSH\_MSG\_CHANNEL\_REQUEST message with a "pty-req" string MUST contain "encoded terminal modes" with an opcode of 1 byte. The opcode values are in the range of 1 to 255. Opcodes 1 to 159 have a single uint32 argument. Opcodes 160 to 255 are not yet defined.

#### 4.5.2 Initial Assignments

opcode	argument	description
-----	-----	-----
0	TTY_OP_END	Indicates end of options.
1	VINTR	Interrupt character; 255 if none. Similarly

2	VQUIT	for the other characters. Not all of these characters are supported on all systems. The quit character (sends SIGQUIT signal on POSIX systems).
3	VERASE	Erase the character to left of the cursor.
4	VKILL	Kill the current input line.
5	VEOF	End-of-file character (sends EOF from the terminal).
6	VEOL	End-of-line character in addition to carriage return and/or linefeed.
7	VEOL2	Additional end-of-line character.
8	VSTART	Continues paused output (normally control-Q).
9	VSTOP	Pauses output (normally control-S).
10	VSUSP	Suspends the current program.
11	VDSUSP	Another suspend character.
12	VREPRINT	Reprints the current input line.
13	VWERASE	Erases a word left of cursor.
14	VLNEXT	Enter the next character typed literally, even if it is a special character
15	VFLUSH	Character to flush output.
16	VSWTCH	Switch to a different shell layer.
17	VSTATUS	Prints system status line (load, command, pid, etc).
18	VDISCARD	Toggles the flushing of terminal output.
30	IGNPAR	The ignore parity flag. The parameter SHOULD be 0 if this flag is FALSE set, and 1 if it is TRUE.
31	PARMRK	Mark parity and framing errors.

32	INPCK	Enable checking of parity errors.
33	ISTRIP	Strip 8th bit off characters.
34	INLCR	Map NL into CR on input.
35	IGNCR	Ignore CR on input.
36	ICRNL	Map CR to NL on input.
37	IUCLC	Translate uppercase characters to lowercase.
38	IXON	Enable output flow control.
39	IXANY	Any char will restart after stop.
40	IXOFF	Enable input flow control.
41	IMAXBEL	Ring bell on input queue full.
50	ISIG	Enable signals INTR, QUIT, [D]SUSP.
51	ICANON	Canonicalize input lines.
52	XCASE	Enable input and output of uppercase characters by preceding their lowercase equivalents with "\".
53	ECHO	Enable echoing.
54	ECHOE	Visually erase chars.
55	ECHOK	Kill character discards current line.

56	ECHONL	Echo NL even if ECHO is off.
57	NOFLSH	Don't flush after interrupt.
58	TOSTOP	Stop background jobs from output.
59	IEXTEN	Enable extensions.
60	ECHOCTL	Echo control characters as ^(Char).
61	ECHOKE	Visual erase for line kill.
62	PENDIN	Retype pending input.
70	OPOST	Enable output processing.
71	OLCUC	Convert lowercase to uppercase.
72	ONLCR	Map NL to CR-NL.
73	OCRNL	Translate carriage return to newline (output).
74	ONOCR	Translate newline to carriage return-newline (output).
75	ONLRET	Newline performs a carriage return (output).
90	CS7	7 bit mode.
91	CS8	8 bit mode.
92	PARENB	Parity enable.
93	PARODD	Odd parity, else even.

128 TTY\_OP\_ISPEED Specifies the input baud rate in

bits per second.  
129 TTY\_OP\_OSPEED Specifies the output baud rate in  
bits per second.

### [4.5.3](#) Future Assignments

Requests for assignments of new opcodes and their associated arguments MUST be done through the IETF CONSENSUS method as described in [[RFC2434](#)].

## [4.6](#) Names

In the following sections, the values for the name spaces are textual. The conventions and instructions to the IANA for future assignments are given in this section. The initial assignments are given in their respective sections.

### [4.6.1](#) Conventions for Names

All names registered by the IANA in the following sections MUST be printable US-ASCII strings, and MUST NOT contain the characters at-sign ("@"), comma (","), or whitespace or control characters (ASCII codes 32 or less). Names are case-sensitive, and MUST NOT be longer than 64 characters.

A provision is made here for locally extensible names. The IANA will not register, and will not control names with the at-sign ("@" in them. Names with the at-sign in them will have the format of "name@domainname" (without the double quotes) where the part preceding the at-sign is the name. The format of the part preceding the at sign is not specified, however these names MUST be printable US-ASCII strings, and MUST NOT contain the comma character (","), or whitespace, or control characters (ASCII codes 32 or less). The part following the at-sign MUST be a valid, fully qualified internet domain name [[RFC1034](#)] controlled by the person or organization defining the name. Names are case-sensitive, and MUST NOT be longer than 64 characters. It is up to each domain how it manages its local namespace. It has been noted that these names resemble STD 11 [[RFC0822](#)] email addresses. This is purely coincidental and actually has nothing to do with STD 11 [[RFC0822](#)]. An example of a locally

defined name is "ourcipher-cbc@example.com" (without the double quotes).

#### [4.6.2](#) Future Assignments of Names

Requests for assignments of new Names MUST be done through the IETF CONSENSUS method as described in [[RFC2434](#)].

#### [4.7](#) Service Names

The Service Name is used to describe a protocol layer.

Service name -----	Reference -----
ssh-userauth	[ <a href="#">SSH-USERAUTH</a> ]
ssh-connection	[ <a href="#">SSH-CONNECT</a> ]

#### [4.8](#) Authentication Method Names

The Authentication Method Name is used to describe an authentication method for the "ssh-userauth" service [[SSH-USERAUTH](#)].

Method name -----	Reference -----
publickey	[ <a href="#">SSH-USERAUTH</a> , <a href="#">Section 4</a> ]
password	[ <a href="#">SSH-USERAUTH</a> , <a href="#">Section 5</a> ]
hostbased	[ <a href="#">SSH-USERAUTH</a> , <a href="#">Section 6</a> ]
none	[ <a href="#">SSH-USERAUTH</a> , <a href="#">Section 2.3</a> ]

#### [4.9](#) Connection Protocol Assigned Names

The following are the Connection Protocol Type and Request names.

##### [4.9.1](#) Connection Protocol Channel Types

Channel type -----	Reference -----
-----------------------	--------------------

session	[SSH-CONNECT, <a href="#">Section 4.1</a> ]
x11	[SSH-CONNECT, <a href="#">Section 4.3.2</a> ]
forwarded-tcpip	[SSH-CONNECT, <a href="#">Section 5.2</a> ]
direct-tcpip	[SSH-CONNECT, <a href="#">Section 5.2</a> ]

#### [4.9.2](#) Connection Protocol Global Request Names

Request type	Reference
-----	-----
tcpip-forward	[SSH-CONNECT, <a href="#">Section 5.1</a> ]
cancel-tcpip-forward	[SSH-CONNECT, <a href="#">Section 5.1</a> ]

#### [4.9.3](#) Connection Protocol Channel Request Names

Request type	Reference
-----	-----
pty-req	[SSH-CONNECT, <a href="#">Section 4.2</a> ]
x11-req	[SSH-CONNECT, <a href="#">Section 4.3.1</a> ]
env	[SSH-CONNECT, <a href="#">Section 4.4</a> ]
shell	[SSH-CONNECT, <a href="#">Section 4.5</a> ]
exec	[SSH-CONNECT, <a href="#">Section 4.5</a> ]
subsystem	[SSH-CONNECT, <a href="#">Section 4.5</a> ]
window-change	[SSH-CONNECT, <a href="#">Section 4.7</a> ]
xon-xoff	[SSH-CONNECT, <a href="#">Section 4.8</a> ]
signal	[SSH-CONNECT, <a href="#">Section 4.9</a> ]
exit-status	[SSH-CONNECT, <a href="#">Section 4.10</a> ]
exit-signal	[SSH-CONNECT, <a href="#">Section 4.10</a> ]

#### [4.9.4](#) Initial Assignment of Signal Names

Signal	Reference
-----	-----
ABRT	[ <a href="#">SSH-CONNECT</a> ]
ALRM	[ <a href="#">SSH-CONNECT</a> ]
FPE	[ <a href="#">SSH-CONNECT</a> ]
HUP	[ <a href="#">SSH-CONNECT</a> ]
ILL	[ <a href="#">SSH-CONNECT</a> ]



KILL	[ <a href="#">SSH-CONNECT</a> ]
PIPE	[ <a href="#">SSH-CONNECT</a> ]
QUIT	[ <a href="#">SSH-CONNECT</a> ]
SEGV	[ <a href="#">SSH-CONNECT</a> ]
TERM	[ <a href="#">SSH-CONNECT</a> ]
USR1	[ <a href="#">SSH-CONNECT</a> ]
USR2	[ <a href="#">SSH-CONNECT</a> ]

#### [4.10](#) Key Exchange Method Names

The Key Exchange Method Name describes a key-exchange method for the protocol [[SSH-TRANS](#)]. Note that, for historical reasons, the name "diffie-hellman-group1-sha1" is used for a key exchange method using Oakley Group 2. This is considered an aberration and should not be repeated. Any future specifications of Diffie Hellman key exchange using Oakley groups defined in [[RFC2412](#)] or its successors should be named using the group numbers assigned by IANA, and names of the form "diffie-hellman-groupN-sha1" should be reserved for this purpose.

Method name	Reference
-----	-----
diffie-hellman-group1-sha1	[SSH-TRANS, <a href="#">Section 8.1</a> ]
diffie-hellman-group14-sha1	[SSH-TRANS, <a href="#">Section 8.2</a> ]

#### [4.11](#) Assigned Algorithm Names

The following names identify the Encryption Algorithm Names.

##### [4.11.1](#) Encryption Algorithm Names

Cipher name	Reference
-----	-----
3des-cbc	[SSH-TRANS, <a href="#">Section 4.3</a> ]
blowfish-cbc	[SSH-TRANS, <a href="#">Section 4.3</a> ]
twofish256-cbc	[SSH-TRANS, <a href="#">Section 4.3</a> ]
twofish-cbc	[SSH-TRANS, <a href="#">Section 4.3</a> ]
twofish192-cbc	[SSH-TRANS, <a href="#">Section 4.3</a> ]
twofish128-cbc	[SSH-TRANS, <a href="#">Section 4.3</a> ]
aes256-cbc	[SSH-TRANS, <a href="#">Section 4.3</a> ]
aes192-cbc	[SSH-TRANS, <a href="#">Section 4.3</a> ]
aes128-cbc	[SSH-TRANS, <a href="#">Section 4.3</a> ]
serpent256-cbc	[SSH-TRANS, <a href="#">Section 4.3</a> ]
serpent192-cbc	[SSH-TRANS, <a href="#">Section 4.3</a> ]
serpent128-cbc	[SSH-TRANS, <a href="#">Section 4.3</a> ]
arcfour	[SSH-TRANS, <a href="#">Section 4.3</a> ]

idea-cbc	[SSH-TRANS, <a href="#">Section 4.3</a> ]
cast128-cbc	[SSH-TRANS, <a href="#">Section 4.3</a> ]
none	[SSH-TRANS, <a href="#">Section 4.3</a> ]
des-cbc	[ <a href="#">FIPS-46-3</a> ] HISTORIC; See page 4 of [ <a href="#">FIPS 46-3</a> ]

#### [4.11.2](#) MAC Algorithm Names

The following names identify the MAC Algorithm Names.

MAC name	Reference
-----	-----
hmac-sha1	[SSH-TRANS, <a href="#">Section 4.4</a> ]
hmac-sha1-96	[SSH-TRANS, <a href="#">Section 4.4</a> ]
hmac-md5	[SSH-TRANS, <a href="#">Section 4.4</a> ]
hmac-md5-96	[SSH-TRANS, <a href="#">Section 4.4</a> ]
none	[SSH-TRANS, <a href="#">Section 4.4</a> ]

#### [4.11.3](#) Public Key Algorithm Names

This table identifies the Public Key Algorithm names.

Algorithm name	Reference
-----	-----
ssh-dss	[SSH-TRANS, <a href="#">Section 4.6</a> ]
ssh-rsa	[SSH-TRANS, <a href="#">Section 4.6</a> ]
spki-sign-rsa	[SSH-TRANS, <a href="#">Section 4.6</a> ]
spki-sign-dss	[SSH-TRANS, <a href="#">Section 4.6</a> ]
pgp-sign-rsa	[SSH-TRANS, <a href="#">Section 4.6</a> ]
pgp-sign-dss	[SSH-TRANS, <a href="#">Section 4.6</a> ]

#### [4.11.4](#) Compression Algorithm Names

The following names identify the Compression Algorithm names.

Algorithm name	Reference
-----	-----
none	[SSH-TRANS, <a href="#">Section 4.2</a> ]
zlib	[SSH-TRANS, <a href="#">Section 4.2</a> ]

## [5.](#) Security Considerations

This protocol provides a secure encrypted channel over an insecure

network.

Full security considerations for this protocol are provided in [\[SSH-ARCH\]](#).

## [6.](#) References

### [6.1](#) Normative References

[SSH-ARCH]

Lonvick, C., "SSH Protocol Architecture", I-D [draft-ietf-architecture-18.txt](#), October 2004.

[SSH-TRANS]

Lonvick, C., "SSH Transport Layer Protocol", I-D [draft-ietf-transport-20.txt](#), October 2004.

[SSH-USERAUTH]

Lonvick, C., "SSH Authentication Protocol", I-D [draft-ietf-userauth-23.txt](#), October 2004.

[SSH-CONNECT]

Lonvick, C., "SSH Connection Protocol", I-D [draft-ietf-connect-21.txt](#), October 2004.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

[RFC2412] Orman, H., "The OAKLEY Key Determination Protocol", [RFC 2412](#), November 1998.

[RFC2434] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 2434](#), October 1998.

### [6.2](#) Informative References

[RFC0822] Crocker, D., "Standard for the format of ARPA Internet text messages", STD 11, [RFC 822](#), August 1982.

[RFC1034] Mockapetris, P., "Domain names - concepts and facilities",  
STD 13, [RFC 1034](#), November 1987.

[FIPS-46-3]

U.S. Dept. of Commerce, "FIPS PUB 46-3, Data Encryption  
Standard (DES)", October 1999.

Lonvick

Expires May 19, 2005

[Page 17]

---

Internet-Draft

SSH Protocol Assigned Numbers

November 2004

#### Author's Address

Chris Lonvick (editor)  
Cisco Systems, Inc.  
12515 Research Blvd.  
Austin 78759  
USA

EMail: [clonvick@cisco.com](mailto:clonvick@cisco.com)

#### Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at [ietf-ipr@ietf.org](mailto:ietf-ipr@ietf.org).

The IETF has been notified of intellectual property rights claimed in

regard to some or all of the specification contained in this document. For more information consult the online list of claimed rights.

#### Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

#### Copyright Statement

Copyright (C) The Internet Society (2004). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Lonvick

Expires May 19, 2005

[Page 19]

---

Internet-Draft

SSH Protocol Assigned Numbers

November 2004

#### Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.

