

Network Working Group  
INTERNET-DRAFT  
Expires September 21, 2005

F. Cusack  
Google, Inc.  
M. Forssen  
Appgate AB  
March 21, 2005

## **Generic Message Exchange Authentication For SSH**

**<[draft-ietf-secsh-auth-kbdinteract-07.txt](#)>**

### Status of this Memo

This document is an Internet-Draft and is subject to all provisions of [Section 3 of RFC 3667](#). By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she become aware will be disclosed, in accordance with [RFC 3668](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at  
<<http://www.ietf.org/1id-abstracts.html>>.

The list of Internet-Draft Shadow Directories can be accessed at  
<<http://www.ietf.org/shadow.html>>.

This Internet-Draft will expire on September 21, 2005.

### Copyright Notice

Copyright (C) The Internet Society (2005).

### Abstract

SSH is a protocol for secure remote login and other secure network services over an insecure network. This document describes a general purpose authentication method for the SSH protocol, suitable for interactive authentications where the authentication data should be entered via a keyboard (or equivalent alphanumeric input device). The major goal of this method is to allow the SSH client to support a whole class of authentication mechanism(s) without knowing the specifics of the actual authentication mechanism(s).



## **1. Introduction**

The SSH authentication protocol [[SSH-USERAUTH](#)] is a general-purpose user authentication protocol. It is intended to be run over the SSH transport layer protocol [[SSH-TRANS](#)]. The authentication protocol assumes that the underlying protocols provide integrity and confidentiality protection.

This document describes a general purpose authentication method for the SSH authentication protocol. This method is suitable for interactive authentication methods which do not need any special software support on the client side. Instead all authentication data should be entered via the keyboard. The major goal of this method is to allow the SSH client to have little or no knowledge of the specifics of the underlying authentication mechanism(s) used by the SSH server. This will allow the server to arbitrarily select or change the underlying authentication mechanism(s) without having to update client code.

The name for this authentication method is "keyboard-interactive".

This document should be read only after reading the SSH architecture document [[SSH-ARCH](#)] and the SSH authentication document [[SSH-USERAUTH](#)]. This document freely uses terminology and notation from both documents without reference or further explanation.

This document also describes some of the client interaction with the user in obtaining the authentication information. While this is somewhat out of the scope of a protocol specification, it is described here anyway since some aspects of the protocol are specifically designed based on user interface issues, and omitting this information may lead to incompatible or awkward implementations.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC-2119](#)].

## **2. Rationale**

Currently defined authentication methods for SSH are tightly coupled with the underlying authentication mechanism. This makes it difficult to add new mechanisms for authentication as all clients must be updated to support the new mechanism. With the generic method defined here, clients will not require code changes to support new authentication mechanisms, and if a separate authentication layer is used, such as [[PAM](#)], then the server may not need any code changes either.



This presents a significant advantage to other methods, such as the "password" method (defined in [[SSH-USERAUTH](#)]), as new (presumably stronger) methods may be added "at will" and system security can be transparently enhanced.

Challenge-response and One Time Password mechanisms are also easily supported with this authentication method.

This authentication method is however limited to authentication mechanisms which do not require any special code, such as hardware drivers or password mangling, on the client.

### **[3. Protocol Exchanges](#)**

The client initiates the authentication with a SSH\_MSG\_USERAUTH\_REQUEST message. The server then requests authentication information from the client with a SSH\_MSG\_USERAUTH\_INFO\_REQUEST message. The client obtains the information from the user and then responds with a SSM\_MSG\_USERAUTH\_INFO\_RESPONSE message. The server **MUST NOT** send another SSH\_MSG\_USERAUTH\_INFO\_REQUEST before it has received the answer from the client.

#### **[3.1 Initial Exchange](#)**

The authentication starts with the client sending the following packet:

byte	SSH_MSG_USERAUTH_REQUEST
string	user name (ISO-10646 UTF-8, as defined in [ <a href="#">RFC-3629</a> ])
string	service name (US-ASCII)
string	"keyboard-interactive" (US-ASCII)
string	language tag (as defined in [ <a href="#">RFC-3066</a> ])
string	submethods (ISO-10646 UTF-8)

The language tag is deprecated and **SHOULD** be the empty string. It may be removed in a future revision of this specification. The server **SHOULD** instead select the language used based on the tags communicated during key exchange [[SSH-TRANS](#)].

If the language tag is not the empty string, the server **SHOULD** use the specified language for any messages sent to the client as part of this protocol. The language tag **SHOULD NOT** be used for language selection for messages outside of this protocol. The language to be used if the server does not support the requested language is implementation-dependent.

The submethods field is included so the user can give a hint of which



actual methods he wants to use. It is a comma-separated list of authentication submethods (software or hardware) which the user prefers. If the client has knowledge of the submethods preferred by the user, presumably through a configuration setting, it MAY use the submethods field to pass this information to the server. Otherwise it MUST send the empty string.

The actual names of the submethods is something which the user and the server need to agree upon.

Server interpretation of the submethods field is implementation-dependent.

One possible implementation strategy of the submethods field on the server is that, unless the user may use multiple different submethods, the server ignores this field. If the user may authenticate using one of several different submethods the server should treat the submethods field as a hint on which submethod the user wants to use this time.

Note that when this message is sent to the server, the client has not yet prompted the user for a password, and so that information is NOT included with this initial message (unlike the "password" method).

The server MUST reply with either a SSH\_MSG\_USERAUTH\_SUCCESS, SSH\_MSG\_USERAUTH\_FAILURE, or SSH\_MSG\_USERAUTH\_INFO\_REQUEST message.

The server SHOULD NOT reply with the SSH\_MSG\_USERAUTH\_FAILURE message if the failure is based on the user name or service name; instead it SHOULD send SSH\_MSG\_USERAUTH\_INFO\_REQUEST message(s) which look just like the one(s) which would have been sent in cases where authentication should proceed, and then send the failure message (after a suitable delay, as described below). The goal is to make it impossible to find valid usernames by just comparing the results when authenticating as different users.

The server MAY reply with a SSH\_MSG\_USERAUTH\_SUCCESS message if no authentication is required for the user in question, however a better approach, for reasons discussed above, might be to reply with a SSH\_MSG\_USERAUTH\_INFO\_REQUEST message and ignore (don't validate) the response.

### **3.2 Information Requests**

Requests are generated from the server using the SSH\_MSG\_USERAUTH\_INFO\_REQUEST message.

The server may send as many requests as are necessary to authenticate





the client; the client MUST be prepared to handle multiple exchanges. However the server MUST NOT ever have more than one SSH\_MSG\_USERAUTH\_INFO\_REQUEST message outstanding. That is, it may not send another request before the client has answered.

The SSH\_MSG\_USERAUTH\_INFO\_REQUEST message is defined as follows:

```
byte      SSH_MSG_USERAUTH_INFO_REQUEST
string    name (ISO-10646 UTF-8)
string    instruction (ISO-10646 UTF-8)
string    language tag (as defined in [RFC-3066])
int       num-prompts
string    prompt[1] (ISO-10646 UTF-8)
boolean   echo[1]
...
string    prompt[num-prompts] (ISO-10646 UTF-8)
boolean   echo[num-prompts]
```

The language tag is deprecated and SHOULD be the empty string. It may be removed in a future revision of this specification. The server SHOULD instead select the language used based on the tags communicated during key exchange [[SSH-TRANS](#)].

If the language tag is not the empty string, the server SHOULD use the specified language for any messages sent to the client as part of this protocol. The language tag SHOULD NOT be used for language selection for messages outside of this protocol. The language to be used if the server does not support the requested language is implementation-dependent.

The server SHOULD take into consideration that some clients may not be able to properly display a long name or prompt field (see next section), and limit the lengths of those fields if possible. For example, instead of an instruction field of "Enter Password" and a prompt field of "Password for user23@host.domain: ", a better choice might be an instruction field of "Password authentication for user23@host.domain" and a prompt field of "Password: ". It is expected that this authentication method would typically be backended by [[PAM](#)] and so such choices would not be possible.

The name and instruction fields MAY be empty strings, the client MUST be prepared to handle this correctly. The prompt field(s) MUST NOT be empty strings.

The num-prompts field may be '0', in which case there will be no prompt/echo fields in the message, but the client SHOULD still display the name and instruction fields (as described below).



### **3.3 User Interface**

Upon receiving a request message, the client SHOULD prompt the user as follows:

A command line interface (CLI) client SHOULD print the name and instruction (if non-empty), adding newlines. Then for each prompt in turn, the client SHOULD display the prompt and read the user input.

A graphical user interface (GUI) client has many choices on how to prompt the user. One possibility is to use the name field (possibly prefixed with the application's name) as the title of a dialog window in which the prompt(s) are presented. In that dialog window, the instruction field would be a text message, and the prompts would be labels for text entry fields. All fields SHOULD be presented to the user, for example an implementation SHOULD NOT discard the name field because its windows lack titles; it SHOULD instead find another way to display this information. If prompts are presented in a dialog window, then the client SHOULD NOT present each prompt in a separate window.

All clients MUST properly handle an instruction field with embedded newlines. They SHOULD also be able to display at least 30 characters for the name and prompts. If the server presents names or prompts longer than 30 characters, the client MAY truncate these fields to the length it can display. If the client does truncate any fields, there MUST be an obvious indication that such truncation has occurred. The instruction field SHOULD NOT be truncated.

Clients SHOULD use control character filtering as discussed in [[SSH-ARCH](#)] to avoid attacks by including terminal control characters in the fields to be displayed.

For each prompt, the corresponding echo field indicates whether or not the user input should be echoed as characters are typed. Clients SHOULD correctly echo/mask user input for each prompt independently of other prompts in the request message. If a client does not honor the echo field for whatever reason, then the client MUST err on the side of masking input. A GUI client might like to have a checkbox toggling echo/mask. Clients SHOULD NOT add any additional characters to the prompt such as ": " (colon-space); the server is responsible for supplying all text to be displayed to the user. Clients MUST also accept empty responses from the user and pass them on as empty strings.

### **3.4 Information Responses**

After obtaining the requested information from the user, the client



MUST respond with a SSH\_MSG\_USERAUTH\_INFO\_RESPONSE message.

The format of the SSH\_MSG\_USERAUTH\_INFO\_RESPONSE message is as follows:

```
byte      SSH_MSG_USERAUTH_INFO_RESPONSE
int       num-responses
string    response[1] (ISO-10646 UTF-8)
...
string    response[num-responses] (ISO-10646 UTF-8)
```

Note that the responses are encoded in ISO-10646 UTF-8. It is up to the server how it interprets the responses and validates them. However, if the client reads the responses in some other encoding (e.g., ISO 8859-1), it MUST convert the responses to ISO-10646 UTF-8 before transmitting.

From an internationalization standpoint, it is desired that if a user enters responses the authentication process will work regardless of what OS and client software they are using. Doing so requires normalization. Systems supporting non-ASCII passwords SHOULD always normalize passwords and usernames whenever they are added to the database, or compared (with or without hashing) to existing entries in the database. SSH implementations that both store the passwords and compare them SHOULD use [[SASLPREP](#)] for normalization.

If the num-responses field does not match the num-prompts field in the request message, the server MUST send a failure message.

In the case that the server sends a '0' num-prompts field in the request message, the client MUST send a response message with a '0' num-responses field to complete the exchange.

The responses MUST be ordered as the prompts were ordered. That is, response[n] MUST be the answer to prompt[n].

After receiving the response, the server MUST send either a SSH\_MSG\_USERAUTH\_SUCCESS, SSH\_MSG\_USERAUTH\_FAILURE, or another SSH\_MSG\_USERAUTH\_INFO\_REQUEST message.

If the server fails to authenticate the user (through the underlying authentication mechanism(s)), it SHOULD NOT send another request message(s) in an attempt to obtain new authentication data, instead it SHOULD send a failure message. The only time the server should send multiple request messages is if additional authentication data is needed (i.e., because there are multiple underlying authentication mechanisms that must be used to authenticate the user).



If the server intends to respond with a failure message, it MAY delay for an implementation-dependent time before sending to the client. It is suspected that implementations are likely to make the time delay configurable; a suggested default is 2 seconds.

#### **4. Authentication Examples**

Here are two example exchanges between a client and server. The first is an example of challenge/response with a handheld token. This is an authentication that is not otherwise possible with other authentication methods.

```
C:  byte      SSH_MSG_USERAUTH_REQUEST
C:  string    "user23"
C:  string    "ssh-userauth"
C:  string    "keyboard-interactive"
C:  string    ""
C:  string    ""

S:  byte      SSH_MSG_USERAUTH_INFO_REQUEST
S:  string    "CRYPTOCard Authentication"
S:  string    "The challenge is '14315716'"
S:  string    "en-US"
S:  int       1
S:  string    "Response: "
S:  boolean   TRUE
```

[Client prompts user for password]

```
C:  byte      SSH_MSG_USERAUTH_INFO_RESPONSE
C:  int       1
C:  string    "6d757575"

S:  byte      SSH_MSG_USERAUTH_SUCCESS
```

The second example is of a standard password authentication, in this case the user's password is expired.

```
C:  byte      SSH_MSG_USERAUTH_REQUEST
C:  string    "user23"
C:  string    "ssh-userauth"
C:  string    "keyboard-interactive"
C:  string    "en-US"
C:  string    ""
```





S:    byte        SSH\_MSG\_USERAUTH\_INFO\_REQUEST  
S:    string     "Password Authentication"  
S:    string     ""  
S:    string     "en-US"  
S:    int        1  
S:    string     "Password: "  
S:    boolean    FALSE

[Client prompts user for password]

C:    byte        SSH\_MSG\_USERAUTH\_INFO\_RESPONSE  
C:    int        1  
C:    string     "password"

S:    byte        SSH\_MSG\_USERAUTH\_INFO\_REQUEST  
S:    string     "Password Expired"  
S:    string     "Your password has expired."  
S:    string     "en-US"  
S:    int        2  
S:    string     "Enter new password: "  
S:    boolean    FALSE  
S:    string     "Enter it again: "  
S:    boolean    FALSE

[Client prompts user for new password]

C:    byte        SSH\_MSG\_USERAUTH\_INFO\_RESPONSE  
C:    int        2  
C:    string     "newpass"  
C:    string     "newpass"

S:    byte        SSH\_MSG\_USERAUTH\_INFO\_REQUEST  
S:    string     "Password changed"  
S:    string     "Password successfully changed for user23."  
S:    string     "en-US"  
S:    int        0

[Client displays message to user]

C:    byte        SSH\_MSG\_USERAUTH\_INFO\_RESPONSE  
C:    int        0  
  
S:    byte        SSH\_MSG\_USERAUTH\_SUCCESS



## **5. IANA Considerations**

The userauth type "keyboard-interactive" is used for this authentication method.

The following method-specific constants are used with this authentication method:

SSH_MSG_USERAUTH_INFO_REQUEST	60
SSH_MSG_USERAUTH_INFO_RESPONSE	61

## **6. Security Considerations**

The authentication protocol, and this authentication method, depend on the security of the underlying SSH transport layer. Without the confidentiality provided therein, any authentication data passed with this method is subject to interception.

The number of client-server exchanges required to complete an authentication using this method may be variable. It is possible that an observer may gain valuable information simply by counting that number. For example, an observer may guess that a user's password has expired, and with further observation may be able to determine the password lifetime imposed by a site's password expiration policy.

## **7. References**

### **7.1 Normative References**

- [RFC-2119]      Bradner, S., "Key words for use in RFCs to Indicate Requirement Level", [BCP 14](#), [RFC 2119](#), March 1997.
  
- [RFC-3629]      Yergeau, F., "UTF-8, a transformation format of Unicode and ISO 10646", [RFC 3629](#), November 2003.
  
- [RFC-3066]      Alvestrand, H., "Tags for the Identification of Languages", [BCP 47](#), [RFC 3066](#), January 2001.
  
- [SSH-ARCH]      Lonvick, C., "SSH Protocol Architecture", work in progress, [draft-ietf-secsh-architecture-22.txt](#), March 2005.



- [SSH-CONNECT]    Lonvick, C., "SSH Connection Protocol", work in progress, [draft-ietf-secsh-connect-25.txt](#), March 2005.
- [SSH-TRANS]    Lonvick, C., "SSH Transport Layer Protocol", work in progress, [draft-ietf-secsh-transport-24.txt](#), March 2005.
- [SSH-USERAUTH]    Lonvick, C., "SSH Authentication Protocol", work in progress, [draft-ietf-secsh-userauth-27.txt](#), March 2005.
- [SASLPREP]    Zeilenga, K., "SASLprep: Stringprep profile for user names and passwords", work in progress, [draft-ietf-sasl-saslprep-10](#), July 2004.

## **7.2 Informative References**

- [PAM]    Samar, V., Schemers, R., "Unified Login With Pluggable Authentication Modules (PAM)", OSF [RFC 86.0](#), October 1995

## **8. Authors' Addresses**

Frank Cusack  
Google, Inc.  
1600 Amphitheatre Parkway  
Mountain View, CA 94043  
Email: frank@google.com

Martin Forssen  
Appgate AB  
Stora Badhusgatan 18-20  
SE-411 21 Gothenburg  
SWEDEN  
Email: maf@appgate.com

## **9. Intellectual Property and Copyright Statements**

### **9.1 IPR Disclosure Acknowledgement**

By submitting this Internet-Draft, I certify that any applicable patent or other IPR claims of which I am aware have been disclosed, and any of which I become aware will be disclosed, in accordance with [RFC 3668](#).



## **9.2 Full Copyright Statement**

**Copyright (C) The Internet Society (2005).** This document is subject to the rights, licenses and restrictions contained in [BCP 78](#) and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

### Intellectual Property

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at [<http://www.ietf.org/ipr>](http://www.ietf.org/ipr).

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at [<ietf-ipr@ietf.org>](mailto:ietf-ipr@ietf.org).

The IETF has been notified of intellectual property rights claimed in regard to some or all of the specification contained in this document. For more information consult the online list of claimed rights.

### Acknowledgement

Funding for the RFC Editor function is currently provided by the Internet Society.

