Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: June 1, 2013

R. Bush
Internet Initiative Japan
B. Wijnen
RIPE NCC
K. Patel
Cisco Systems
M. Baer
SPARTA

November 28, 2012

Definitions of Managed Objects for the RPKI-Router Protocol draft-ietf-sidr-rpki-rtr-protocol-mib-03

Abstract

This document defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes objects used for monitoring the RPKI Router protocol.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at http://datatracker.ietf.org/drafts/current/.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on June 1, 2013.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (http://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction 3
1.1. Requirements Language 3
2. Internet-Standard Management Framework 3
3. Overview 3
4. Definitions 4
5. IANA Considerations 20
6. Security Considerations 21
7. References 21
7.1. Normative References 21
7.2. Informative References 22
Authors' Addresses 22

1. Introduction

This document defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it defines objects used for monitoring the RPKI Router protocol [I-D.ietf-sidr-rpki-rtr].

1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

2. Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of [RFC3410]. Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This document specifies a MIB module that is compliant to the SMIv2, which is described in STD 58, [RFC2578], STD 58, [RFC2579] and STD 58, [RFC2580].

3. Overview

The objects defined in this document are used to monitor the RPKI Router protocol [I-D.ietf-sidr-rpki-rtr]. The MIB module defined in this draft is broken into these tables: the RPKI Router Cache Server (connection) Table, the RPKI Router Cache Server Errors Table, and the RPKI Router Prefix Origin Table.

The RPKI Router Cache Server Table contains information about state and current activity of connections with the RPKI Router Cache Servers. It also contains counters for the number of messages received and sent plus the number of announcements, withdrawals and active records. The RPKI Router Cache Server Errors Table contains counters of occurrences of errors on the connections (if any). The RPKI Router Prefix Origin Table contains IP prefixes with their minimum and maximum prefix lengths and the Origin AS. This data is the collective set of information received from all RPKI Cache Servers that the router is connected with. The Cache Servers are running the RPKI Router protocol.

Two Notification have been defined to inform a Network Management Station (NMS) or operators about changes in the connection state of the connections listed in the RPKI Cache Server (Connection) Table.

4. Definitions

The Following MIB module imports definitions from [RFC2578], STD 58, [RFC2579] STD 58, [RFC2580], [RFC4001], [RFC2287]. That means we have a normative reference to those documents.

The MIB module also has a normative reference to the RPKI Router protocol [I-D.ietf-sidr-rpki-rtr]. Furthermore, for background and informative information, the MIB module refers to [RFC1982], [RFC5925], [RFC4252], [RFC5246], [RFC5925].

```
RPKI-RTR-MIB DEFINITIONS ::= BEGIN

IMPORTS

    MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE,
    Integer32, Unsigned32, mib-2, Gauge32, Counter32
            FROM SNMPv2-SMI                          -- RFC2578

    InetAddressType, InetAddress, InetPortNumber,
    InetAddressPrefixLength, InetAutonomousSystemNumber
            FROM INET-ADDRESS-MIB                    -- RFC4001

    TEXTUAL-CONVENTION, TimeStamp
            FROM SNMPv2-TC                           -- RFC2579

    MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
            FROM SNMPv2-CONF                         -- RFC2580

    LongUtf8String FROM SYSAPPL-MIB                  -- RFC2287

    ;

rpkiRtrMIB  MODULE-IDENTITY
    LAST-UPDATED "201110140000Z"
    ORGANIZATION "IETF Secure Inter-Domain Routing (SIDR)
                  Working Group
                 "
    CONTACT-INFO "Working Group Email: sidr@ietf.org

                  Randy Bush
```

Internet Initiative Japan
5147 Crystal Springs
Bainbridge Island, Washington, 98110
USA
Email: randy@psg.com

Bert Wijnen
RIPE NCC
Schagen 33
3461 GL Linschoten
Netherlands
Email: bertietf@bwijnen.net

Keyur Patel
Cisco Systems
170 W. Tasman Drive
San Jose, CA 95134
USA
Email: keyupate@cisco.com

Michael Baer
SPARTA
P.O. Box 72682
Davis, CA 95617
USA
Email: michael.baer@sparta.com
"

DESCRIPTION "This MIB module contains management objects to
support monitoring of the Resource Public Key
Infrastructure (RPKI) protocol on routers.

Copyright (c) 2011 IETF Trust and the persons
identified as authors of the code. All rights
reserved.

Redistribution and use in source and binary
forms, with or without modification, is
permitted pursuant to, and subject to the
license terms contained in, the Simplified BSD
License set forth in Section 4.c of the IETF
Trust's Legal Provisions Relating to IETF
Documents (http://trustee.ietf.org/license-info).

This version of this MIB module is part of
RFCxxxx; see the RFC itself for full legal
notices.
"

```
        REVISION     "201110140000Z"
        DESCRIPTION  "Initial version, published as RFCxxxx."
        -- Note to RFC Editor: pls fill in above (2 times) RFC
        --  number for xxxx and delete these 2 lines.
        ::= { mib-2 XXX }  -- XXX to be assigned by IANA

    rpkiRtrNotifications  OBJECT IDENTIFIER ::= { rpkiRtrMIB 0 }
    rpkiRtrObjects        OBJECT IDENTIFIER ::= { rpkiRtrMIB 1 }
    rpkiRtrConformance    OBJECT IDENTIFIER ::= { rpkiRtrMIB 2 }

    -- ================================================================
    -- Textual Conventions used in this MIB module
    -- ================================================================

    RpkiRtrConnectionType ::= TEXTUAL-CONVENTION
        STATUS      current
        DESCRIPTION "The connection type or transport security suite
                     (transport plus security mechanism) used between
                     a router (as a client) and a cache server.

                     The following types have been defined in RFCnnnn:
    --  RFC Editor: pls fill out RFCnnnn number that will be or has
    --              been assigned to draft-ietf-sidr-rpki-rtr-nn.txt
                       ssh(1)    - sect 7.1, see also RFC4252.
                       tls(2)    - sect 7.2, see also RFC5246.
                       tcpMD5(3) - sect 7.3, see also RFC2385.
                       tcpAO(4)  - sect 7.4, see also RFC5925.
                       tcp(5)    - sect 7.
                       ipsec(6)  - sect 7, see also RFC4301.
                       other(7)  - non of the above
                    "
        REFERENCE   "The RPKI/Rtr Protocol, RFCnnnn - section 7"
    --  RFC Editor: pls fill out RFCnnnn number that will be or has been
    --              assigned to draft-ietf-sidr-rpki-rtr-nn.txt
        SYNTAX       INTEGER {
                               ssh(1),
                               tls(2),
                               tcpMD5(3),
                               tcpAO(4),
                               tcp(5),
                               ipsec(6),
                               other(7)
                     }

    -- ================================================================
    -- Scalar objects
    -- ================================================================
    rpkiRtrDiscontinuityTimer OBJECT-TYPE
```

```
        SYNTAX       TimeStamp
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "This timer represents the timestamp (value
                     of sysUpTime) at which time any of the
                     Counter32 ojects in this MIB module
                     encountered a discontinuity.

                     In principle that should only happen if the
                     SNMP agent or the instrumentation for this
                     MIB module (re-)starts."
        ::= { rpkiRtrObjects 1 }

    -- ============================================================
    -- RPKI Router Cache Server Connection Table
    -- ============================================================

    rpkiRtrCacheServerTable OBJECT-TYPE
        SYNTAX       SEQUENCE OF RpkiRtrCacheServerTableEntry
        MAX-ACCESS   not-accessible
        STATUS       current
        DESCRIPTION "This table lists the RPKI cache servers
                     known to this router/system."
        ::= { rpkiRtrObjects 2 }

    rpkiRtrCacheServerTableEntry OBJECT-TYPE
        SYNTAX       RpkiRtrCacheServerTableEntry
        MAX-ACCESS   not-accessible
        STATUS       current
        DESCRIPTION "An entry in the rpkiRtrCacheServerTable.
                     It holds management attributes associated
                     with one connection to a RPKI cache server."
        INDEX        { rpkiRtrCacheServerAddressType,
                       rpkiRtrCacheServerRemoteAddress,
                       rpkiRtrCacheServerRemotePort
                     }
        ::= { rpkiRtrCacheServerTable 1 }

    RpkiRtrCacheServerTableEntry ::= SEQUENCE {
        rpkiRtrCacheServerAddressType          InetAddressType,
        rpkiRtrCacheServerRemoteAddress        InetAddress,
        rpkiRtrCacheServerRemotePort           InetPortNumber,
        rpkiRtrCacheServerLocalAddress         InetAddress,
        rpkiRtrCacheServerLocalPort            InetPortNumber,
        rpkiRtrCacheServerPreference           Unsigned32,
        rpkiRtrCacheServerConnectionType       RpkiRtrConnectionType,
        rpkiRtrCacheServerConnectionStatus     INTEGER,
        rpkiRtrCacheServerDescription          LongUtf8String,
```

```
        rpkiRtrCacheServerMsgsReceived         Counter32,
        rpkiRtrCacheServerMsgsSent             Counter32,
        rpkiRtrCacheServerV4ActiveRecords      Gauge32,
        rpkiRtrCacheServerV4Announcements      Counter32,
        rpkiRtrCacheServerV4Withdrawals        Counter32,
        rpkiRtrCacheServerV6ActiveRecords      Gauge32,
        rpkiRtrCacheServerV6Announcements      Counter32,
        rpkiRtrCacheServerV6Withdrawals        Counter32,
        rpkiRtrCacheServerLatestSerial         Unsigned32,
        rpkiRtrCacheServerNonce                Unsigned32,
        rpkiRtrCacheServerRefreshTimer         Unsigned32,
        rpkiRtrCacheServerTimeToRefresh        Integer32,
        rpkiRtrCacheServerId                   Unsigned32
    }

    rpkiRtrCacheServerAddressType OBJECT-TYPE
        SYNTAX       InetAddressType { ipv4(1), ipv6 (2) }
        MAX-ACCESS   not-accessible
        STATUS       current
        DESCRIPTION "The network address type of the connection
                     to this RPKI cache server.

                     Only IPv4 and IPv6 are supported."
        ::= { rpkiRtrCacheServerTableEntry 1 }

    rpkiRtrCacheServerRemoteAddress OBJECT-TYPE
        SYNTAX       InetAddress (SIZE(4|16))
        MAX-ACCESS   not-accessible
        STATUS       current
        DESCRIPTION "The remote network address for this connection
                     to this RPKI cache server.

                     The format of the address is defined by the
                     value of the corresponding instance of
                     rpkiRtrCacheServerAddressType."
        ::= { rpkiRtrCacheServerTableEntry 2 }

    rpkiRtrCacheServerRemotePort OBJECT-TYPE
        SYNTAX       InetPortNumber (1..65535)
        MAX-ACCESS   not-accessible
        STATUS       current
        DESCRIPTION "The remote port number for this connection
                     to this RPKI cache server."
        ::= { rpkiRtrCacheServerTableEntry 3 }

    rpkiRtrCacheServerLocalAddress OBJECT-TYPE
        SYNTAX       InetAddress (SIZE(4|16))
        MAX-ACCESS   read-only
```

```
        STATUS       current
        DESCRIPTION "The local network address for this connection
                     to this RPKI cache server.

                     The format of the address is defined by the
                     value of the corresponding instance of
                     rpkiRtrCacheServerAddressType."
        ::= { rpkiRtrCacheServerTableEntry 4 }

    rpkiRtrCacheServerLocalPort OBJECT-TYPE
        SYNTAX       InetPortNumber (1..65535)
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The local port number for this connection
                     to this RPKI cache server."
        ::= { rpkiRtrCacheServerTableEntry 5 }

    rpkiRtrCacheServerPreference OBJECT-TYPE
        SYNTAX       Unsigned32 (0..255)
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The routers' preference for this
                     RPKI cache server.

                     A lower value means more preferred. If two
                     entries have the same preference, then the
                     order is arbitrary.

                     If no order is specified in the configuration
                     then this value is set to 255."
        REFERENCE    "The RPKI/Rtr Protocol, RFCnnnn - section 8."
    --  RFC-Editor: pls update RFCnnnn with the actual RFC number
    --              assigned to draft-ietf-sidr-rpki-rtr-nn.txt
        ::= { rpkiRtrCacheServerTableEntry 6 }

    rpkiRtrCacheServerConnectionType OBJECT-TYPE
        SYNTAX       RpkiRtrConnectionType
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The connection type or transport security suite
                     in use for this RPKI cache server."
        ::= { rpkiRtrCacheServerTableEntry 7 }

    rpkiRtrCacheServerConnectionStatus OBJECT-TYPE
        SYNTAX       INTEGER { up(1), down(2) }
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The connection status for this entry
```

```
                    (connection to this RPKI cache server)."
        ::= { rpkiRtrCacheServerTableEntry 8 }

    rpkiRtrCacheServerDescription OBJECT-TYPE
        SYNTAX       LongUtf8String
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "Free form description/information for this
                    connection to this RPKI cache server."
        ::= { rpkiRtrCacheServerTableEntry 9 }

    rpkiRtrCacheServerMsgsReceived OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "Number of messages received from this
                    RPKI cache server via this connection.

                    Discontinuities are indicated by the value
                    of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerTableEntry 10 }

    rpkiRtrCacheServerMsgsSent OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "Number of messages sent to this
                    RPKI cache server via this connection.

                    Discontinuities are indicated by the value
                    of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerTableEntry 11 }

    rpkiRtrCacheServerV4ActiveRecords OBJECT-TYPE
        SYNTAX       Gauge32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "Number of active IPv4 records received from
                    this RPKI cache server via this connection."
        ::= { rpkiRtrCacheServerTableEntry 12 }

    rpkiRtrCacheServerV4Announcements OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The number of IPv4 records announced by the
                    RPKI cache Server via this connection.
```

```
                    Discontinuities are indicated by the value
                    of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerTableEntry 13 }

    rpkiRtrCacheServerV4Withdrawals OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "The number of IPv4 records withdrawn by the
                     RPKI cache Server via this connection.

                     Discontinuities are indicated by the value
                     of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerTableEntry 14 }

    rpkiRtrCacheServerV6ActiveRecords OBJECT-TYPE
        SYNTAX       Gauge32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "Number of active IPv6 records received from
                     this RPKI cache server via this connection."
        ::= { rpkiRtrCacheServerTableEntry 15 }

    rpkiRtrCacheServerV6Announcements OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The number of IPv6 records announced by the
                     RPKI cache Server via this connection.

                     Discontinuities are indicated by the value
                     of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerTableEntry 16 }

    rpkiRtrCacheServerV6Withdrawals OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The number of IPv6 records withdrawn by the
                     RPKI cache Server via this connection.

                     Discontinuities are indicated by the value
                     of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerTableEntry 17 }

    rpkiRtrCacheServerLatestSerial OBJECT-TYPE
        SYNTAX       Unsigned32
        MAX-ACCESS   read-only
```

```
        STATUS       current
        DESCRIPTION "The latest serial number of data received from
                     this RPKI server on this connection.

                     Note: this value wraps back to zero when it
                     reaches its maximum value."
        REFERENCE   "RFCnnnn section 2 and RFC1982"
    --  RFC-Editor: please fill out nnnn with the RFC number assigned
    --              to draft-ietf-sidr-rpki-rtr-nn.txt
        ::= { rpkiRtrCacheServerTableEntry 18 }

    rpkiRtrCacheServerNonce OBJECT-TYPE
        SYNTAX      Unsigned32 (0..65535)
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "The nonce associated with the RPKI cache server
                     at the other end of this connection."
        REFERENCE   "RFCnnnn section 2"
        ::= { rpkiRtrCacheServerTableEntry 19 }

    rpkiRtrCacheServerRefreshTimer OBJECT-TYPE
        SYNTAX       Unsigned32 (60..7200)
        UNITS       "seconds"
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The number of seconds configured for the refresh
                     timer for this connection to this RPKI cache
                     server."
        ::= { rpkiRtrCacheServerTableEntry 20 }

    rpkiRtrCacheServerTimeToRefresh OBJECT-TYPE
        SYNTAX       Integer32
        UNITS       "seconds"
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The number of seconds remaining before a new
                     refresh is performed via a Serial Query to
                     this cache server over this connection.

                     A negative value means that the refresh time
                     has passed this many seconds and the refresh
                     has not yet been completed.

                     Upon a completed refresh (i.e. a successful
                     and complete response to a Serial Query) the
                     value of this attribute will be re-initialized
                     with the value of the corresponding
                     rpkiRtrCacheServerRefreshTimer attribute."
```

```
        ::= { rpkiRtrCacheServerTableEntry 21 }

    rpkiRtrCacheServerId OBJECT-TYPE
        SYNTAX       Unsigned32 (1..4294967295)
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The unique ID for this connection.

                     An implementation must make sure this ID is unique
                     within this table. It is this ID that can be used
                     to find entries in the rpkiRtrPrefixOriginTable
                     that were created by announcements received on this
                     connection from this cache server."
        ::= { rpkiRtrCacheServerTableEntry 22 }

    -- ================================================================
    -- Errors Table
    -- ================================================================

    rpkiRtrCacheServerErrorsTable OBJECT-TYPE
        SYNTAX       SEQUENCE OF RpkiRtrCacheServerErrorsTableEntry
        MAX-ACCESS   not-accessible
        STATUS       current
        DESCRIPTION "This table provides statistics on errors per
                     RPKI peer connection. These can be used for
                     debuging."
        ::= { rpkiRtrObjects 3 }

    rpkiRtrCacheServerErrorsTableEntry OBJECT-TYPE
        SYNTAX       RpkiRtrCacheServerErrorsTableEntry
        MAX-ACCESS   not-accessible
        STATUS       current
        DESCRIPTION "An entry in the rpkiCacheServerErrorTable.  It holds
                     management objects associated with errors that
                     were detected for the specified connection to
                     a specific cache server."
        AUGMENTS    { rpkiRtrCacheServerTableEntry }
        ::= { rpkiRtrCacheServerErrorsTable 1 }

    RpkiRtrCacheServerErrorsTableEntry ::= SEQUENCE {
        rpkiRtrCacheServerErrorsCorruptData        Counter32,
        rpkiRtrCacheServerErrorsInternalError      Counter32,
        rpkiRtrCacheServerErrorsNoData             Counter32,
        rpkiRtrCacheServerErrorsInvalidRequest     Counter32,
        rpkiRtrCacheServerErrorsUnsupportedVersion Counter32,
        rpkiRtrCacheServerErrorsUnsupportedPdu     Counter32,
        rpkiRtrCacheServerErrorsWithdrawalUnknown  Counter32,
        rpkiRtrCacheServerErrorsDuplicateAnnounce  Counter32
```

```
        }

    rpkiRtrCacheServerErrorsCorruptData OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The number of 'Corrupt Data' errors received
                     from the RPKI cache server at the other end
                     of this connection.

                     Discontinuities are indicated by the value
                     of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerErrorsTableEntry 1 }

    rpkiRtrCacheServerErrorsInternalError OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The number of 'Internal Error' errors received
                     from the RPKI cache server at the other end
                     of this connection.

                     Discontinuities are indicated by the value
                     of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerErrorsTableEntry 2 }

    rpkiRtrCacheServerErrorsNoData OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The number of 'No Data Available' errors received
                     from the RPKI cache server at the other end
                     of this connection.

                     Discontinuities are indicated by the value
                     of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerErrorsTableEntry 3 }

    rpkiRtrCacheServerErrorsInvalidRequest OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The number of 'Invalid Request' errors received
                     from the RPKI cache server at the other end
                     of this connection.

                     Discontinuities are indicated by the value
                     of rpkiRtrDiscontinuityTimer."
```

```
        ::= { rpkiRtrCacheServerErrorsTableEntry 4 }

    rpkiRtrCacheServerErrorsUnsupportedVersion OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The number of 'Unsupported Protocol Version'
                     errors received from the RPKI cache server at
                     the other end of this connection.

                     Discontinuities are indicated by the value
                     of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerErrorsTableEntry 5 }

    rpkiRtrCacheServerErrorsUnsupportedPdu OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The number of 'Unsupported PDU Type' errors
                     received from the RPKI cache server at the
                     other end of this connection.

                     Discontinuities are indicated by the value
                     of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerErrorsTableEntry 6 }

    rpkiRtrCacheServerErrorsWithdrawalUnknown OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The number of 'Withdrawal of Unknown Record'
                     errors received from the RPKI cache server at
                     the other end of this connection.

                     Discontinuities are indicated by the value
                     of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerErrorsTableEntry 7 }

    rpkiRtrCacheServerErrorsDuplicateAnnounce OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The number of 'Duplicate Announcement Received'
                     errors received from the RPKI cache server at
                     the other end of this connection.

                     Discontinuities are indicated by the value
                     of rpkiRtrDiscontinuityTimer."
```

```
        ::= { rpkiRtrCacheServerErrorsTableEntry 8 }

    -- ================================================================
    -- The rpkiRtrPrefixOriginTable (was refered to as ROATable in an
    -- earlier version of this table)
    -- ================================================================

    rpkiRtrPrefixOriginTable OBJECT-TYPE
        SYNTAX       SEQUENCE OF RpkiRtrPrefixOriginTableEntry
        MAX-ACCESS   not-accessible
        STATUS       current
        DESCRIPTION "This table lists the prefixes that were
                     announced by RPKI cache servers to this system.
                     That is the prefixes and their Origin ASN
                     as recieved by announcements via the
                     rpki-rtr protocol."
        ::= { rpkiRtrObjects 4 }

    rpkiRtrPrefixOriginTableEntry OBJECT-TYPE
        SYNTAX       RpkiRtrPrefixOriginTableEntry
        MAX-ACCESS   not-accessible
        STATUS       current
        DESCRIPTION "An entry in the rpkiRtrPrefixOriginTable.
                     This represents one announced prefix."
        INDEX       { rpkiRtrPrefixOriginAddressType,
                      rpkiRtrPrefixOriginAddress,
                      rpkiRtrPrefixOriginMinLength
                    }
        ::= { rpkiRtrPrefixOriginTable 1 }

    RpkiRtrPrefixOriginTableEntry ::= SEQUENCE {
        rpkiRtrPrefixOriginAddressType    InetAddressType,
        rpkiRtrPrefixOriginAddress        InetAddress,
        rpkiRtrPrefixOriginMinLength      InetAddressPrefixLength,
        rpkiRtrPrefixOriginMaxLength      InetAddressPrefixLength,
        rpkiRtrPrefixOriginASN            InetAutonomousSystemNumber,
        rpkiRtrPrefixOriginCacheServerId  Unsigned32
    }

    rpkiRtrPrefixOriginAddressType OBJECT-TYPE
        SYNTAX       InetAddressType { ipv4(1), ipv6(2) }
        MAX-ACCESS   not-accessible
        STATUS       current
        DESCRIPTION "The network Address Type for this prefix.

                     Only IPv4 and IPv6 are supported."
        ::= { rpkiRtrPrefixOriginTableEntry 1 }
```

```
   rpkiRtrPrefixOriginAddress OBJECT-TYPE
       SYNTAX       InetAddress (SIZE(4|16))
       MAX-ACCESS   not-accessible
       STATUS       current
       DESCRIPTION "The network Address for this prefix.

                    The format of the address is defined by the
                    value of the corresponding instance of
                    rpkiRtrCacheServerAddressType."
       ::= { rpkiRtrPrefixOriginTableEntry 2 }

   rpkiRtrPrefixOriginMinLength OBJECT-TYPE
       SYNTAX       InetAddressPrefixLength
       MAX-ACCESS   not-accessible
       STATUS       current
       DESCRIPTION "The minimum prefix length allowed for this prefix."
       ::= { rpkiRtrPrefixOriginTableEntry 3 }

   rpkiRtrPrefixOriginMaxLength OBJECT-TYPE
       SYNTAX       InetAddressPrefixLength
       MAX-ACCESS   read-only
       STATUS       current
       DESCRIPTION "The maximum prefix length allowed for this prefix.

                    Note, this value must be greater or equal to the
                    value of rpkiRtrPrefixOriginMinLength."
       ::= { rpkiRtrPrefixOriginTableEntry 4 }

   rpkiRtrPrefixOriginASN OBJECT-TYPE
       SYNTAX       InetAutonomousSystemNumber
       MAX-ACCESS   read-only
       STATUS       current
       DESCRIPTION "The ASN that is authorized to announce the
                    prefix or sub-prefixes covered by this entry."
       ::= { rpkiRtrPrefixOriginTableEntry 5 }

   rpkiRtrPrefixOriginCacheServerId OBJECT-TYPE
       SYNTAX       Unsigned32 (1..4294967295)
       MAX-ACCESS   read-only
       STATUS       current
       DESCRIPTION "The unique ID of the connection to the cache
                    server from which this announcement was received.
                    That connection is identified/found by a matching
                    value in attribute rpkiRtrCacheServerId."
       ::= { rpkiRtrPrefixOriginTableEntry 6 }

   -- ================================================================
   -- Notifications
```

```
   -- ============================================================

   rpkiRtrCacheServerConnectionStateChange NOTIFICATION-TYPE
       OBJECTS     { rpkiRtrCacheServerConnectionStatus,
                     rpkiRtrCacheServerLatestSerial,
                     rpkiRtrCacheServerNonce
                   }
       STATUS      current
       DESCRIPTION "This notification signals a change in the status
                    of an rpkiRtrCacheServerConnection.

                    The SNMP agent MUST throttle the generation of
                    consecutive rpkiRtrCacheServerConnectionStateChange
                    notifications such that there is at least a
                    5 second gap between them.
                   "
       ::= { rpkiRtrNotifications 1 }

   rpkiRtrCacheServerConnectionToGoStale NOTIFICATION-TYPE
       OBJECTS     { rpkiRtrCacheServerV4ActiveRecords,
                     rpkiRtrCacheServerV6ActiveRecords,
                     rpkiRtrCacheServerLatestSerial,
                     rpkiRtrCacheServerNonce,
                     rpkiRtrCacheServerRefreshTimer,
                     rpkiRtrCacheServerTimeToRefresh
                   }
       STATUS      current
       DESCRIPTION "This notification signals that an RPKI cache
                    server connection is about to go stale.
                    It is suggested that this notifiation is
                    generated when the value of the
                    rpkiRtrCacheServerTimeToRefresh attribute
                    goes below 60 seconds.

                    The SNMP agent MUST throttle the generation of
                    consecutive rpkiRtrCacheServerConnectionToGoStale
                    notifications such that there is at least a
                    5 second gap between them.
                   "
       ::= { rpkiRtrNotifications 2 }

   -- ============================================================
   -- Module Compliance information
   -- ============================================================

   rpkiRtrCompliances OBJECT IDENTIFIER ::=
                                          {rpkiRtrConformance 1}
   rpkiRtrGroups      OBJECT IDENTIFIER ::=
```

```
                                        {rpkiRtrConformance 2}

   rpkiRtrReadOnlyCompliance MODULE-COMPLIANCE
       STATUS       current
       DESCRIPTION "The compliance statement for the rpkiRtrMIB
                    module. There are only read-only objects in this
                    MIB module, so the 'ReadOnly' in the name of this
                    compliance statement is there only for clarity
                    and truth in advertising.
                   "
       MODULE      -- This module
       MANDATORY-GROUPS { rpkiRtrCacheServerGroup,
                          rpkiRtrPrefixOriginGroup,
                          rpkiRtrNotificationsGroup
                        }
       GROUP       rpkiRtrCacheServerErrorsGroup
       DESCRIPTION "Implemntation of this group is optional and
                    would be useful for debugging."
       ::= { rpkiRtrCompliances 1 }

   rpkiRtrCacheServerGroup OBJECT-GROUP
       OBJECTS     { rpkiRtrDiscontinuityTimer,
                     rpkiRtrCacheServerLocalAddress,
                     rpkiRtrCacheServerLocalPort,
                     rpkiRtrCacheServerPreference,
                     rpkiRtrCacheServerConnectionType,
                     rpkiRtrCacheServerConnectionStatus,
                     rpkiRtrCacheServerDescription,
                     rpkiRtrCacheServerMsgsReceived,
                     rpkiRtrCacheServerMsgsSent,
                     rpkiRtrCacheServerV4ActiveRecords,
                     rpkiRtrCacheServerV4Announcements,
                     rpkiRtrCacheServerV4Withdrawals,
                     rpkiRtrCacheServerV6ActiveRecords,
                     rpkiRtrCacheServerV6Announcements,
                     rpkiRtrCacheServerV6Withdrawals,
                     rpkiRtrCacheServerLatestSerial,
                     rpkiRtrCacheServerNonce,
                     rpkiRtrCacheServerRefreshTimer,
                     rpkiRtrCacheServerTimeToRefresh,
                     rpkiRtrCacheServerId
                   }
       STATUS      current
       DESCRIPTION "The collection of objects to monitor the RPKI peer
                    connections."
       ::= { rpkiRtrGroups 1 }

   rpkiRtrCacheServerErrorsGroup OBJECT-GROUP
```

```
        OBJECTS     { rpkiRtrCacheServerErrorsCorruptData,
                      rpkiRtrCacheServerErrorsInternalError,
                      rpkiRtrCacheServerErrorsNoData,
                      rpkiRtrCacheServerErrorsInvalidRequest,
                      rpkiRtrCacheServerErrorsUnsupportedVersion,
                      rpkiRtrCacheServerErrorsUnsupportedPdu,
                      rpkiRtrCacheServerErrorsWithdrawalUnknown,
                      rpkiRtrCacheServerErrorsDuplicateAnnounce
                    }
        STATUS      current
        DESCRIPTION "The collection of objects that may help in
                     debugging the communication between rpki
                     clients and cache servers."
        ::= { rpkiRtrGroups 2 }

    rpkiRtrPrefixOriginGroup OBJECT-GROUP
        OBJECTS     { rpkiRtrPrefixOriginMaxLength,
                      rpkiRtrPrefixOriginASN,
                      rpkiRtrPrefixOriginCacheServerId
                    }
        STATUS      current
        DESCRIPTION "The collection of objects that represent
                     the prefix(es) and their validated origin
                     ASes."
        ::= { rpkiRtrGroups 3 }

    rpkiRtrNotificationsGroup NOTIFICATION-GROUP
        NOTIFICATIONS { rpkiRtrCacheServerConnectionStateChange,
                        rpkiRtrCacheServerConnectionToGoStale
                      }
        STATUS      current
        DESCRIPTION "The set of notifications to alert an NMS of change
                     in connections to RPKI cache servers."
        ::= { rpkiRtrGroups 4 }

    END
```

5. IANA Considerations

The MIB module in this document will required an IANA assigned OBJECT IDENTIFIER within the SMI Numbers registry. For example, replacing XXX below:

Descriptor	OBJECT IDENTIFIER value

```
        rpkiRouter            { mib-2 XXX }
```

6. Security Considerations

There are no management objects defined in this MIB module that have a MAX-ACCESS clause of read-write and/or read-create. So, if this MIB module is implemented correctly, then there is no risk that an intruder can alter or create any management objects of this MIB module via direct SNMP SET operations.

Most of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. They are vulnerable in the sense that when an intruder sees the information in this MIB module, then it might help him/her to setup a an attack on the router or cache server. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPSec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [RFC3410], section 8), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

7. References

7.1. Normative References

[I-D.ietf-sidr-rpki-rtr]
Bush, R. and R. Austein, "The RPKI/Router Protocol", draft-ietf-sidr-rpki-rtr-26 (work in progress), February 2012.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.

[RFC2287] Krupczak, C. and J. Saperia, "Definitions of System-Level Managed Objects for Applications", RFC 2287, February 1998.

[RFC2578] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Structure of Management Information Version 2 (SMIv2)", STD 58, RFC 2578, April 1999.

[RFC2579] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Textual Conventions for SMIv2", STD 58, RFC 2579, April 1999.

[RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIv2", STD 58, RFC 2580, April 1999.

[RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", RFC 4001, February 2005.

7.2. Informative References

[RFC1982] Elz, R. and R. Bush, "Serial Number Arithmetic", RFC 1982, August 1996.

[RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", RFC 3410, December 2002.

[RFC4252] Ylonen, T. and C. Lonvick, "The Secure Shell (SSH) Authentication Protocol", RFC 4252, January 2006.

[RFC5246] Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2", RFC 5246, August 2008.

[RFC5925] Touch, J., Mankin, A., and R. Bonica, "The TCP Authentication Option", RFC 5925, June 2010.

Authors' Addresses

Randy Bush
Internet Initiative Japan
5147 Crystal Springs
Bainbridge Island, Washington 98110
US

Email: randy@psg.com

Bert Wijnen
RIPE NCC
Schagen 33
3461 GL Linschoten
Netherlands

Email: bertietf@bwijnen.net

Keyur Patel
Cisco Systems
170 W. Tasman Drive
San Jose, CA 95134
USA

Email: keyupate@cisco.com

Michael Baer
SPARTA
P.O. Box 72682
Davis, CA 95617
USA

Email: michael.baer@sparta.com