

SIDR Working Group
Internet-Draft
Intended status: BCP
Expires: October 31, 2014

S. Turner
IECA, Inc.
K. Patel
Cisco Systems
R. Bush
Internet Initiative Japan, Inc.
April 29, 2014

Router Keying for BGPsec
draft-ietf-sidr-rtr-keying-05

Abstract

BGPsec-speaking routers are provisioned with private keys to sign BGP messages; the corresponding public keys are published in the global RPKI (Resource Public Key Infrastructure) thereby enabling verification of BGPsec messages. This document describes two ways of provisioning the public-private key-pairs: router-driven and operator-driven.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 27, 2013.

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect

Internet-Draft

Router Keying for BGPsec

April 29, 2014

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

1. Introduction

BGPsec-speaking routers are provisioned with private keys, which allow them to digitally sign BGP messages. To verify the signature, the public key, in the form of a certificate [I-D.ietf-sidr-bgpsec-pki-profiles], is published in the RPKI (Resource Public Key Infrastructure). This document describes two methods for provisioning the necessary public-private key-pairs: router-driven and operator-driven.

The difference between the two methods is where the keys are generated: on the router in the router-driven method and elsewhere in the operator-driven method. Routers are expected to support either one, the other, or both methods to work in various deployment environments. Some routers may not allow the private key to be off-loaded while other routers may. Off-loading of private keys would support swapping of routing engines which could then have the same private key installed in the soon-to-be online engine that had previously been installed in the soon-to-be removed card.

The remainder of this document describes how operators can use the two methods to provision new and existing routers.

Note: [I-D.ietf-sidr-bgpsec-pki-profiles] specifies the format for the PKCS #10 request and [I-D.ietf-sidr-bgpsec-algs] specifies the algorithms used to generate the signature.

2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" are to be interpreted as described in [RFC 2119](#) [RFC2119] only when they appear in all upper case. They may also appear in lower or mixed case as English words, without normative meaning.

Readers are assumed to be familiar with the BGPsec protocol [I-D.ietf-sidr-bgpsec-overview] [I-D.ietf-sidr-bgpsec-protocol] and the RPKI [RFC6480] as well as the BGPsec-specific PKI (Public Key

Infrastructure) specifications [[I-D.ietf-sidr-bgpsec-pki-profiles](#)] [[I-D.ietf-sidr-bgpsec-algs](#)].

[3.](#) Provisioning a New Router

Turner, et al.

Expires October 31, 2014

[Page 2]

Internet-Draft

Router Keying for BGPsec

April 29, 2014

Depending on the options supported by the new router, operators are free to use either the router-driven or operator-drive methods. Regardless of the method chosen, operators first establish a secure communication channel (e.g., via SSH (Secure Shell)) between the operator's management platform and the router to allow the operator to securely use the Command Line Interface (CLI). How this channel is established is router-specific and is not in scope of this document. Though other configuration mechanisms might be used, e.g. NetConf (see [[RFC6470](#)]), in the remainder of this document, the secure communication channel between the server and the router is assumed to be an SSH-protected CLI.

Encryption, integrity, authentication, and key exchange algorithms used by the secure communication channel SHOULD be of comparable strength to BGPsec keys, which currently is 128-bit, or stronger than BGPsec keys. In other words for the encryption algorithm, do not use export grade crypto (40-56 bits of security), do not use Triple DES (112 bits of security), do use something like or better than AES-128: aes128-cbc [[RFC4253](#)] and AEAD_AES_128_GCM [[RFC5647](#)]; for integrity use something like hmac-sha2-256 [[RFC6668](#)] or AESAD_AES_128_GCM [[RFC5647](#)]; for authentication use something like ecdsa-sha2-nistp256 [[RFC5656](#)], and; for key exchange use something like ecdh-sha2-nistp256 [[RFC5656](#)].

Note that some routers support the use of public key certificates and SSH. The certificates used for the SSH session are different than the certificates used for BGPsec. The certificates used with SSH should also enable a level of security commensurate with BGPsec keys; x509v3-ecdsa-sha2-nistp256 [[RFC6187](#)] could be used for authentication.

[3.1.](#) Router-Generated Keys

In the router-driven method, once the SSH-protected CLI session is established between the operator and the router, the operator issues a command, or commands, for the router to generate the public/private

key pair, to generate the PKCS#10 request, and to sign the PKCS#10 with the private key. Once generated, the PKCS#10, which includes the public key the router wants certified, is transmitted to the RPKI CA for the CA to certify. This can be via a number of means, two of which might be as follows:

- o Through the SSH-protected CLI session with the operator's RPKI management platform: The operator off-loads the PKCS#10 and uploads the request to the CA. If the CA is operated by an external entity, external network connectivity likely is required.

- o Between the router and the CA: The operator, through a command or commands, prompts the router to send/transfer the PKCS#10 request to the CA over the network. Obviously for this to work, the router requires network connectivity with the CA and if the CA is operated by an external entity external network connectivity may be required.

After the CA certifies the key, it does two things:

- o Publishes the certificate in the Global RPKI. The CA must have connectivity to the relevant publication point, which in turn must have external network connectivity as it is part of the Global RPKI.
- o Returns the certificate to the operator's management station or to the router, normally packaged in a PKCS#7, using the corresponding method by which it received the certificate request.

With network connectivity, the router and CA can exchange the certificate request and the certificate using the application/pkcs10 media type [[RFC5967](#)] and application/pkcs7-mime [[RFC5751](#)], respectively, with the FTP [[RFC2585](#)], the HTTP [[RFC2585](#)], or the EST (Enrollment over Secure Transport) [I-D.ietf-pkix-est].

The router SHOULD extract the certificate from the PCKCS#7 and verify that the private key it holds corresponds to the returned public key. The router SHOULD inform the operator that the certificate was received; by some mechanism which is out of scope of this document.

The router SHOULD inform the operator whether or not the keys correspond, again by a mechanism which is out of scope for this document.

The router SHOULD also verify that the returned certificate validates back to a trust anchor. To perform this verification either the CA's certificate needs to be installed on the router via the CLI or the CA's certificate needs to be returned along with the router's certificate in the PKCS#7. The router SHOULD inform the operator whether or not the signature validates to a trust anchor; this notification mechanism is out of scope. After performing these checks, the router need not retain the CA's certificate because the certificate is not transmitted as part of BGPsec messages.

Note that even if the operator cannot extract the private key from the router, this signature still provides a linkage between a private key and a router. That is the server can verify the proof of possession (POP), as required by [[RFC6484](#)].

[3.2](#). Operator-Generated Keys

In the operator-driven method, the operator generates the public/private key pair and installs the private key into the router over the SSH-protected CLI session. Note that cut/copy and paste operations for keys over a certain sizes is error-prone.

The operator uses RPKI management tools to generate the keys, the PKCS#10 certification request, the certificate, and the PKCS#7 certification response, as well as publishing the certificate in the Global RPKI. External network connectivity may be needed if the certificate is to be published in the Global RPKI.

Along with the PKCS#7, the operator returns the private key. The private key is encapsulated in a PKCS #8 [[RFC5958](#)], the PKCS#8 is further encapsulated in CMS (Cryptographic Message Syntax) SignedData [[RFC5652](#)], and signed by the AS's EE (End Entity) certificate.

The router SHOULD verify the signature of the encapsulated PKCS#8 to ensure the returned private key did in fact come from the operator, but this requires that the operator also provision via the CLI or include in the SignedData the RPKI CA certificate and relevant AS's

EE certificate(s). The router SHOULD inform the operator whether or not the signature validates to a trust anchor; this notification mechanism is out of scope.

The router SHOULD extract the certificate from the PKCS#7 and verify that the private key corresponds to the returned public key. The router SHOULD inform the operator whether it successfully received the certificate; this mechanism is out of scope. The router should inform the operator whether or not the keys correspond; this mechanism is out of scope. The router SHOULD also verify the returned certificate back to a trust anchor, but to perform this verification either the CA's certificate needs to be installed on the router via the CLI or the CA's certificate needs to be returned along with the router's certificate in the PKCS#7. The router SHOULD inform the operator whether or not the signature validates to a trust anchor; this notification mechanism is out of scope. After performing these checks, the router need not retain the CA certificate.

Note: The signature on the PKCS#8 and Certificate need not be made by the same entity. Signing the PKCS#8, permits more advanced configurations where the entity that generates the keys is not CA.

[4.](#) Key Management

An operator's responsibilities do not end after key generation, key

provisioning, certificate issuance, and certificate distribution. They persist for as long as the operator wishes to operate the BGPsec-speaking router.

Paramount to maintaining a router that can be a continuous BGPsec speaker is ensuring that the router has a valid certificate at all times. To ensure this, the operator needs to ensure the router always has a non-expired certificate. That is the key used when BGP-speaking always has an associated certificate whose expiry time is after the current time.

Ensuring this is not terribly difficult but requires that either:

- o The router has a mechanism to notify the operator that the certificate has an impending expiration, and/or

- o The operator notes the expiry time of the certificate and uses a calendaring program to remind them of the expiry time. It is advisable that the expiration warning happen well in advance of the actual expiry time, and/or
- o The RPKI CA warns the operator of pending expiration, and/or
- o Use some other kind of automated process to search for and track the expiry times of router certificates.

Regardless of the technique used to track router certificate expiry times, it is advisable to notify additional operators in the same organization as the expiry time approaches thereby ensuring that the forgetfulness of one operator does not affect the entire organization.

Depending on inter-operator relationship, it may be appropriate to notify a peer operator that one or more of their certificates are about to expire.

Routers that support multiple private keys also greatly increase the chance that routers can continuously speak BGPsec because the new private key and certificate can be obtained prior to expiration of the operational key. Obviously, the router needs to know when to start using the new key. Once the new key is being used, having the already distributed certificate ensures continuous operation.

Whether the certificate is rekeyed (i.e., different key in the certificate with a new expiry time) or renewed (i.e., the same key in the certificate with a new expiry time) depends on the key's lifetime and operational use. Arguably, rekeying the router's BGPsec certificate every time the certificate expires is more secure than

renewal because it limits the private key's exposure. However, if the key is not compromised the certificate could be renewed as many times as allowed by the operator's security policy. Routers that support only one key can use renewal to ensure continuous operation, assuming the certificate is renewed and distributed prior to the operational's certificate expiry time.

Certain unfortunate circumstances exist when the operator will need

to revoke the router's BGPsec certificate. When this occurs, the operator needs to use the RPKI CA system to revoke the certificate by placing the router's BGPsec certificate on the CRL (Certificate Revocation List) as well as rekeying the router's certificate.

5. Other Use Cases

Current router code generates private keys for uses such as SSH, but the private keys may not be seen or off-loaded via the SSH-protected CLI session or any other means. While this is good security, it creates difficulties when a routing engine or whole router must be replaced in the field and all software which accesses the router must be updated with the new keys. Also, any network based initial contact with a new routing engine requires trust in the public key presented on first contact.

To allow operators to quickly replace routers without requiring update and distribution of the corresponding public keys in the RPKI, routers SHOULD allow the private BGPsec key to be off-loaded via the SSH-protected CLI, NetConf (see [\[RFC6470\]](#)), SNMP, etc. This lets the operator upload the old private key via the mechanism used for operator-generated keys, see [Section 3.2](#).

6. Security Considerations

Operator-generated keys could be intercepted in transport and the recipient router would have no way of knowing a substitution had been made or that the key had been disclosed by a monkey in the middle. Hence transport security is strongly RECOMMENDED. As noted in [Section 3](#), the level of security provided by the transport security SHOULD be commensurate with the BGPsec key. Additionally, operators SHOULD ensure the transport security implementation is up to date and addresses all known implementation bugs.

All generated key pairs MUST be generated from a good source of non-deterministic random input [\[RFC4086\]](#) and the private key MUST be protected in a secure fashion. Disclosure of the private key leads to masquerade [\[RFC4949\]](#). The local storage format for the private key is a local matter.

verify the returned certificate is in fact signed by the CA, the revocation status of the CA's certificate is not checked. The operator MUST ensure that installed CA certificate is valid.

Operators need to manage their SSH keys to ensure only those authorized to access the router may do so. As employees no longer need access to the router, their keys SHOULD be removed from the router.

7. IANA Considerations

This document has no IANA Considerations.

8. References

8.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC4086] Eastlake 3rd, D., Schiller, J., and S. Crocker, "Randomness Requirements for Security", [BCP 106](#), [RFC 4086](#), June 2005.
- [RFC4253] Ylonen, T. and C. Lonvick, Ed., "The Secure Shell (SSH) Transport Layer Protocol", [RFC 4253](#), January 2006.
- [RFC5652] Housley, R., "Cryptographic Message Syntax (CMS)", STD 70, [RFC 5652](#), September 2009.
- [RFC5915] Turner, S. and D. Brown, "Elliptic Curve Private Key Structure", [RFC 5915](#), June 2010.
- [RFC5958] Turner, S., "Asymmetric Key Packages", [RFC 5958](#), August 2010.
- [I-D.ietf-sidr-bgpsec-algs]
Turner, S., "BGP Algorithms, Key Formats, & Signature Formats", [draft-ietf-sidr-bgpsec-algs](#) (work in progress).
- [I-D.ietf-sidr-bgpsec-pki-profiles]
Reynolds, M., Turner, S., and S. Kent, "A Profile for BGPSEC Router Certificates, Certificate Revocation Lists, and Certification Requests", [draft-ietf-sidr-bgpsec-pki-profiles](#) (work in progress).

8.2. Informative References

- [I-D.ietf-sidr-bgpsec-overview]
Lepinski, M. and S. Turner, "An Overview of BGPSEC",
[draft-ietf-sidr-bgpsec-overview](#) (work in progress).
- [I-D.ietf-sidr-bgpsec-protocol]
Lepinski, M., "BGPSEC Protocol Specification",
[draft-ietf-sidr-bgpsec-protocol](#) (work in progress).
- [IEEE-802.3]
ISO/IEC 8802-3 Information technology -
Telecommunications and information exchange between
systems - Local and metropolitan area networks -
Common specifications - Part 3: Carrier Sense
Multiple Access with Collision Detection (CSMA/CD)
Access Method and Physical Layer Specifications, 2008.
- [RFC2585] Housley, R. and P. Hoffman, "Internet X.509 Public Key
Infrastructure Operational Protocols: FTP and HTTP",
[RFC 2585](#), May 1999.
- [RFC4253] Ylonen, T. and C. Lonvick, Ed., "The Secure Shell (SSH)
Transport Layer Protocol", [RFC 4253](#), January 2006.
- [RFC4949] Shirey, R., "Internet Security Glossary, Version 2", FYI
36, [RFC 4949](#), August 2007.
- [RFC5647] Igoe, K. and J. Solinas, "AES Galois Counter Mode for the
Secure Shell Transport Layer Protocol", [RFC 5647](#), August
2009.
- [RFC5656] Stebila, D. and J. Green, "Elliptic Curve Algorithm
Integration in the Secure Shell Transport Layer",
[RFC 5656](#), December 2009.
- [RFC5751] Ramsdell, B. and S. Turner, "Secure/Multipurpose Internet
Mail Extensions (S/MIME) Version 3.2 Message
Specification", [RFC 5751](#), January 2010.
- [RFC5967] Turner, S., "The application/pkcs10 Media Type", [RFC 5967](#),
August 2010.
- [RFC6187] Igoe, K. and D. Stebila, "X.509v3 Certificates for Secure
Shell Authentication", [RFC 6187](#), March 2011.
- [RFC6470] Bierman, A., "Network Configuration Protocol (NETCONF)
Base Notifications", [RFC 6470](#), February 2012.

Internet-Draft

Router Keying for BGPsec

April 29, 2014

Secure Internet Routing", [RFC 6480](#), February 2012.

[RFC6668] Bider, D. and M. Baushke, "SHA-2 Data Integrity Verification for the Secure Shell (SSH) Transport Layer Protocol", [RFC 6668](#), July 2012.

[RFC7030] Pritikin, M., Ed., Yee, P., Ed., and D. Harkins, Ed., "Enrollment over Secure Transport", [RFC 7030](#), October 2013.

Authors' Addresses

Sean Turner
IECA, Inc.
3057 Nutley Street, Suite 106
Fairfax, Virginia 22031
US

Email: turners@ieca.com

Keyur Patel
Cisco Systems
170 West Tasman Drive
San Jose, CA 95134
US

Email: keyupate@cisco.com

Randy Bush
Internet Initiative Japan, Inc.
5147 Crystal Springs
Bainbridge Island, Washington 98110
US

Phone: +1 206 780 0431 x1
Email: randy@psg.com

Turner, et al.

Expires October 31, 2014

[Page 10]