

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: January 9, 2020

A. Azimov
Yandex
E. Bogomazov
Qrator Labs
K. Patel
Arrcus, Inc.
J. Snijders
NTT
July 8, 2019

**Verification of AS_PATH Using the Resource Certificate Public Key
Infrastructure and Autonomous System Provider Authorization
draft-ietf-sidrops-aspa-verification-01**

Abstract

This document defines the semantics of an Autonomous System Provider Authorization object in the Resource Public Key Infrastructure to verify the AS_PATH attribute of routes advertised in the Border Gateway Protocol.

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 9, 2020.

Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](https://trustee.ietf.org/license-info) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
2.	Anomaly Propagation	3
3.	Autonomous System Provider Authorization	4
4.	Customer-Provider Verification Procedure	4
5.	AS_PATH Verification	5
5.1.	Upstream Paths	5
5.2.	Downstream Paths	6
5.3.	Mitigation	6
6.	Disavowal of Provider Authorizaion	7
7.	Siblings (Complex Relations)	7
8.	Security Considerations	7
9.	Acknowledgments	8
10.	References	8
10.1.	Normative References	8
10.2.	Informative References	8
	Authors' Addresses	10

[1.](#) Introduction

The Border Gateway Protocol (BGP) was designed without mechanisms to validate BGP attributes. Two consequences are BGP Hijacks and BGP Route Leaks [[RFC7908](#)]. BGP extensions are able to partially solve these problems. For example, ROA-based Origin Validation [[RFC6483](#)] can be used to detect and filter accidental mis-originations, and [[I-D.ietf-grow-route-leak-detection-mitigation](#)] can be used to detect accidental route leaks. While these upgrades to BGP are quite useful, they still rely on transitive BGP attributes, i.e. AS_PATH, that can be manipulated by attackers.

BGPsec [[RFC8205](#)] was designed to solve the problem of AS_PATH validation. Unfortunately, strict cryptographic validation brought

expensive computational overhead for BGP routers. BGPsec also proved vulnerable to downgrade attacks that nullify the benefits of AS_PATH signing. As a result, to abuse the AS_PATH or any other signed transit attribute, an attacker merely needs to downgrade to 'old' BGP-4.

An alternative approach was introduced with soBGP [[I-D.white-sobgp-architecture](#)]. Instead of strong cryptographic AS_PATH validation, it created an AS_PATH security function based on a shared database of ASN adjacencies. While such an approach has reasonable computational cost, the two side adjacencies don't provide a way to automate anomaly detection without high adoption rate - an attacker can easily create a one-way adjacency. SO-BGP transported data about adjacencies in new additional BGP messages, which was recursively complex thus significantly increasing adoption complexity and risk. In addition, the general goal to verify all AS_PATHs was not achievable given the indirect adjacencies at internet exchange points.

Instead of checking AS_PATH correctness, this document focuses on solving real-world operational problems - automatic detection of malicious hijacks and route leaks. To achieve this a new AS_PATH verification procedure is defined which is able to automatically detect invalid (malformed) AS_PATHs in announcements that are received from customers and peers. This procedure uses a shared signed database of customer-to-provider relationships using a new RPKI object - Autonomous System Provider Authorization (ASPA). This technique provides benefits for participants even during early and incremental adoption.

2. Anomaly Propagation

Both route leaks and hijacks have similar effects on ISP operations - they redirect traffic, resulting in increased latency, packet loss, or possible MiTM attacks. But the level of risk depends significantly on the propagation of the anomalies. For example, a hijack that is propagated only to customers may concentrate traffic in a particular ISP's customer cone; while if the anomaly is propagated through peers, upstreams, or reaches Tier-1 networks, thus distributing globally, traffic may be redirected at the level of entire countries and/or global providers.

The ability to constrain propagation of BGP anomalies to upstreams and peers, without requiring support from the source of the anomaly (which is critical if source has malicious intent), should significantly improve the security of inter-domain routing and solve the majority of problems.

3. Autonomous System Provider Authorization

As described in [[RFC6480](#)], the RPKI is based on a hierarchy of resource certificates that are aligned to the Internet Number Resource allocation structure. Resource certificates are X.509 certificates that conform to the PKIX profile [[RFC5280](#)], and to the extensions for IP addresses and AS identifiers [[RFC3779](#)]. A resource certificate is a binding by an issuer of IP address blocks and Autonomous System (AS) numbers to the subject of a certificate, identified by the unique association of the subject's private key with the public key contained in the resource certificate. The RPKI is structured so that each current resource certificate matches a current resource allocation or assignment.

ASPAs are digitally signed objects that bind a selected AFI Provider AS number to a Customer AS number (in terms of BGP announcements not business), and are signed by the holder of the Customer AS. An ASPA attests that a Customer AS holder (CAS) has authorized a particular Provider AS (PAS) to propagate the Customer's IPv4/IPv6 announcements onward, e.g. to the Provider's upstream providers or peers. The ASPA record profile is described in [[I-D.ietf-sidrops-aspa-profile](#)].

4. Customer-Provider Verification Procedure

This section describes an abstract procedure that checks that pair of ASNs (AS1, AS2) is included in the set of signed ASPAs. The semantics of its usage is defined in next section. The procedure takes (AS1, AS2, ROUTE_AFI) as input parameters and returns three types of results: "valid", "invalid" and "unknown".

A relying party (RP) must have access to a local cache of the complete set of cryptographically valid ASPAs when performing customer-provider verification procedure.

1. Retrieve all cryptographically valid ASPAs in a selected AFI with a customer value of AS1. This selection forms the set of "candidate ASPAs."
2. If the set of candidate ASPAs is empty, then the procedure exits with an outcome of "unknown."
3. If there is at least one candidate ASPA where the provider field is AS2, then the procedure exits with an outcome of "valid."
4. Otherwise, the procedure exits with an outcome of "invalid."

Since an AS1 may have different set providers in different AFI, it should also have different set of corresponding ASPAs. In this case,

the output of this procedure with input (AS1, AS2, ROUTE_AFI) may have different output for different ROUTE_AFI values.

5. AS_PATH Verification

The AS_PATH attribute identifies the autonomous systems through which an UPDATE message has passed. AS_PATH may contain two types of components: ordered AS_SEQs and unordered AS_SETs, as defined in [[RFC4271](#)].

The value of each concatenated value of AS_SEQ components can be described as set of pairs {(AS(I), prepend(I)), (AS(I-1), prepend(I-1))...}. In this case, the sequence {AS(I), AS(I-1),...} represents different ASNs, that packet should pass towards the destination.

The bellow procedure is applicable only for 32-bit AS number compatible BGP speakers.

5.1. Upstream Paths

When a route is received from a customer, literal peer or by RS at IX, each pair (AS(I-1), AS(I)) MUST belong to customer-provider or sibling relationship. If there are other types of relationships, it means that the route was leaked or the AS_PATH attribute was malformed. The goal of the described bellow procedure is to check the correctness of this statement.

If a route from ROUTE_AFI address family is received from a customer, peer or RS-client, its AS_PATH MUST be verified as follows:

1. If the closest AS in the AS_PATH is not the receiver's neighbor ASN then procedure halts with the outcome "invalid";
2. If there is a pair (AS(I-1), AS(I)), and customer-provider verification procedure ([Section 4](#)) with parameters (AS(I-1), AS(I), ROUTE_AFI) returns "invalid" then the procedure also halts with the outcome "invalid";
3. If the AS_PATH has at least one AS_SET segment then procedure halts with the outcome "unverifiable";
4. Otherwise, the procedure halts with an outcome of "valid".

5.2. Downstream Paths

When route is received from provider or RS it may have both Upstream and Downstream paths. The first pair (AS(I-1), AS(I)) that has "invalid" outcome of customer-provider verification procedure indicates the end of Upstream path. All subsequent reverse pairs (AS(J), AS(J-1)) MUST belong to customer-provider or sibling relationship, thus can be also verified with ASPA objects. If there are other types of relationships, it means that the route was leaked.

Additional caution should be done while processing prefixes that are received from transparent IXes since they don't add their ASN in the ASPATH.

If a route from ROUTE_AFI address family is received from a customer or RS, its AS_PATH MUST be verified as follows:

1. If route is received from provider and the closest AS in the AS_PATH is not the receiver's neighbor ASN then procedure halts with the outcome "invalid";
2. If there are two pairs (AS(I-1), AS(I)), (AS(J-1), AS(J)) where $J > I$, and customer-provider verification procedure ([Section 4](#)) returns "invalid" for both (AS(I-1), AS(I), ROUTE_AFI) and (AS(J), AS(J-1), ROUTE_AFI), then the procedure also halts with the outcome "invalid";
3. If the AS_PATH has at least one AS_SET segment then procedure halts with the outcome "unverifiable";
4. Otherwise, the procedure halts with an outcome of "valid".

5.3. Mitigation

If the output of the AS_PATH verification procedure is "invalid" the route MUST be rejected.

If the output of the AS_PATH verification procedure is 'unverifiable' it means that AS_PATH can't be fully checked. Such routes should be treated with caution and SHOULD be processed the same way as "invalid" routes. This policy goes with full correspondence to [\[I-D.kumari-deprecate-as-set-confed-set\]](#).

The above AS_PATH verification procedure is able to check routes received from customers and peers. The ASPA mechanism combined with BGP Roles [\[I-D.ietf-idr-bgp-open-policy\]](#) and ROA-based Origin Validation [\[RFC6483\]](#) provide a fully automated solution to detect and filter hijacks and route leaks, including malicious ones.

6. Disavowal of Provider Authorizaion

An ASPA is a positive attestation that an AS holder has authorized its provider to redistribute received routes to the provider's providers and peers. This does not preclude the provider AS from redistribution to its other customers. By creating an ASPA where the provider AS is 0, the customer indicates that no provider should further announce its routes. Specifically, AS 0 is reserved to identify provider-free networks, Internet exchange meshes, etc.

An ASPA with a provider AS of 0 is a statement by the customer AS that the its routes should not be received by any relying party AS from any of its customers or peers.

By convention, an ASPA with a provider AS of 0 should be the only ASPA issued by a given AS holder; although this is not a strict requirement. A provider 0 ASPA may coexist with ASPAs that have different provider AS values; though in such cases, the presence or absence of the provider AS 0 ASPA does not alter the AS_PATH verification procedure.

7. Siblings (Complex Relations)

There are peering relationships which can not be described as strictly simple peer-peer or customer-provider; e.g. when both parties are intentionally sending prefixes received from each other to their peers and/or upstreams.

In this case, two symmetric ASPAs records {(AS1, AS2), (AS2, AS1)} must be created by AS1 and AS2 respectively.

8. Security Considerations

The proposed mechanism is compatible only with BGP implementations that can process 32-bit ASNs in the ASPATH. This limitation should not have a real effect on operations - such legacy BGP routers are rare and it's highly unlikely that they do support integration with RPKI.

ASPA issuers should be aware of the verification implication in issuing an ASPA - an ASPA implicitly invalidates all routes passed to upstream providers other than the provider ASs listed in the collection of ASPAs. It is the Customer AS's duty to maintain a correct set of ASPAs.

While the ASPA is capable to detect both mistake and malicious activity for routes received from customers, RS-clients or peers, it provides only detection of mistakes for routes that are received from upstream providers and RS(s).

Since upstream provider becomes a trusted point, it will be able to send hijacked prefixes of its customers or send hijacked prefixes with malformed AS_PATHs back. While it may happen in theory, it's doesn't seem to be a real scenario: normally customer and provider have a signed agreement and such policy violation should have legal consequences or customer can just drop relation with such provider and remove corresponding ASPA record.

9. Acknowledgments

The authors wish to thank authors of [RFC6483] since its text was used as an example while writing this document. The also authors wish to thank Iljitsch van Beijnum for giving a hint about Downstream paths.

10. References

10.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

10.2. Informative References

- [I-D.ietf-grow-route-leak-detection-mitigation]
Sriram, K. and A. Azimov, "Methods for Detection and Mitigation of BGP Route Leaks", [draft-ietf-grow-route-leak-detection-mitigation-00](#) (work in progress), April 2019.
- [I-D.ietf-idr-bgp-open-policy]
Azimov, A., Bogomazov, E., Bush, R., Patel, K., and K. Sriram, "Route Leak Prevention using Roles in Update and Open messages", [draft-ietf-idr-bgp-open-policy-05](#) (work in progress), February 2019.
- [I-D.ietf-sidrops-aspa-profile]
Azimov, A., Uskov, E., Bush, R., Patel, K., Snijders, J., and R. Housley, "A Profile for Autonomous System Provider Authorization", [draft-ietf-sidrops-aspa-profile-00](#) (work in progress), May 2019.

- [I-D.kumari-deprecate-as-set-confed-set]
Kumari, W. and K. Sriram, "Deprecation of AS_SET and AS_CONFED_SET in BGP", [draft-kumari-deprecate-as-set-confed-set-12](#) (work in progress), July 2018.
- [I-D.white-sobgp-architecture]
White, R., "Architecture and Deployment Considerations for Secure Origin BGP (soBGP)", [draft-white-sobgp-architecture-02](#) (work in progress), June 2006.
- [RFC3779] Lynn, C., Kent, S., and K. Seo, "X.509 Extensions for IP Addresses and AS Identifiers", [RFC 3779](#), DOI 10.17487/RFC3779, June 2004, <<https://www.rfc-editor.org/info/rfc3779>>.
- [RFC4271] Rekhter, Y., Ed., Li, T., Ed., and S. Hares, Ed., "A Border Gateway Protocol 4 (BGP-4)", [RFC 4271](#), DOI 10.17487/RFC4271, January 2006, <<https://www.rfc-editor.org/info/rfc4271>>.
- [RFC5280] Cooper, D., Santesson, S., Farrell, S., Boeyen, S., Housley, R., and W. Polk, "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", [RFC 5280](#), DOI 10.17487/RFC5280, May 2008, <<https://www.rfc-editor.org/info/rfc5280>>.
- [RFC6480] Lepinski, M. and S. Kent, "An Infrastructure to Support Secure Internet Routing", [RFC 6480](#), DOI 10.17487/RFC6480, February 2012, <<https://www.rfc-editor.org/info/rfc6480>>.
- [RFC6483] Huston, G. and G. Michaelson, "Validation of Route Origination Using the Resource Certificate Public Key Infrastructure (PKI) and Route Origin Authorizations (ROAs)", [RFC 6483](#), DOI 10.17487/RFC6483, February 2012, <<https://www.rfc-editor.org/info/rfc6483>>.
- [RFC7908] Sriram, K., Montgomery, D., McPherson, D., Osterweil, E., and B. Dickson, "Problem Definition and Classification of BGP Route Leaks", [RFC 7908](#), DOI 10.17487/RFC7908, June 2016, <<https://www.rfc-editor.org/info/rfc7908>>.
- [RFC8205] Lepinski, M., Ed. and K. Sriram, Ed., "BGPsec Protocol Specification", [RFC 8205](#), DOI 10.17487/RFC8205, September 2017, <<https://www.rfc-editor.org/info/rfc8205>>.

Authors' Addresses

Alexander Azimov
Yandex

Email: a.e.azimov@gmail.com

Eugene Bogomazov
Qrator Labs

Email: eb@qrator.net

Keyur Patel
Arrcus, Inc.

Email: keyur@arrcus.com

Job Snijders
NTT Communications
Theodorus Majofskistraat 100
Amsterdam 1065 SZ
The Netherlands

Email: job@ntt.net

