Network Working Group R. Bush

Internet-Draft Internet Initiative Japan & Arrcus

Updates: 6811 (if approved) R. Volk

Intended status: Standards Track Deutsche Telekom Expires: September 5, 2020

J. Heitz

Cisco March 4, 2020

**BGP RPKI-Based Origin Validation on Export** draft-ietf-sidrops-ov-egress-01

#### Abstract

A BGP speaker may perform RPKI origin validation not only on routes received from BGP neighbors and routes that are redistributed from other routing protocols, but also on routes it sends to BGP neighbors. For egress policy, it is important that the classification uses the effective origin AS of the processed route, which may specifically be altered by the commonly available knobs such as removing private ASs, confederation handling, and other modifications of the origin AS.

## Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at https://datatracker.ietf.org/drafts/current/.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 5, 2020.

## Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to <u>BCP 78</u> and the IETF Trust's Legal Provisions Relating to IETF Documents (<a href="https://trustee.ietf.org/license-info">https://trustee.ietf.org/license-info</a>) in effect on the date of publication of this document. Please review these documents

carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

### Table of Contents

<u>1</u> .	Introduction	2
<u>2</u> .	Suggested Reading	3
<u>3</u> .	Egress Processing	<u>3</u>
<u>4</u> .	Operational Considerations	<u>3</u>
<u>5</u> .	Security Considerations	<u>3</u>
<u>6</u> .	IANA Considerations	<u>4</u>
	References	
<u>7.</u>	<u>.1</u> . Normative References	<u>4</u>
<u>7.</u>	<u>.2</u> . Informative References	<u>4</u>
Auth	hors' Addresses	4

### 1. Introduction

This document does not change the protocol or semantics of [RFC6811] of RPKI-based origin validation. It highlights an important use case of origin validation in eBGP egress policies, explaining specifics of correct implementation in this context.

As the origin AS may be modified by outbound policy, policy semantics based on RPKI Origin Validation state MUST be able to be applied separately on distribution into BGP and on egress.

When applied to egress policy, the effective origin AS MUST be used to determine the Origin Validation state. The effective origin AS is that which will actually be the origin AS in the announcement. It might be affected by removal of private AS(s), confederation, AS migration, etc. If there are any AS\_PATH modifications resulting in origin AS change, then these MUST be taken into account.

This document updates [RFC6811] by clarifying that implementations must use the effective origin AS to determine the Origin Validation state when applying egress policy.

## 2. Suggested Reading

It is assumed that the reader understands BGP, [RFC4271], the RPKI, [RFC6480], Route Origin Authorizations (ROAs), [RFC6482], RPKI-based Prefix Validation, [RFC6811], and Origin Validation Clarifications, [RFC8481].

# 3. Egress Processing

BGP implementations supporting RPKI-based origin validation SHOULD provide the same policy configuration primitives for decisions based on validation state available for use in ingress, redistribution, and egress policies. When applied to egress policy, validation state MUST be determined using the effective origin AS of the route as it will (or would) be announced to the peer. The effective origin AS may differ from that of the route in the RIB due to commonly available knobs such as: removal of private ASs, AS path manipulation, confederation handling, etc.

Egress policy handling can provide more robust protection for outbound eBGP than relying solely on ingress (iBGP, eBGP, connected, static, etc.) redistribution being configured and working correctly better support for the robustness principle.

### 4. Operational Considerations

Configurations may have complex policy where the final announced origin AS may not be easily predicted before all policies have been run. Therefore it SHOULD be possible to specify an origin validation policy which MUST BE run after such non-deterministic policies.

An operator SHOULD be able to list what announcements are not sent to a peer because they were marked Invalid, as long as the router still has them in memory.

## **5**. Security Considerations

This document does not create security considerations beyond those of [RFC6811] and [RFC8481].

### 6. IANA Considerations

This document has no IANA Considerations.

### 7. References

#### 7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate
  Requirement Levels", BCP 14, RFC 2119,
  DOI 10.17487/RFC2119, March 1997,
  <a href="http://www.rfc-editor.org/info/rfc2119">http://www.rfc-editor.org/info/rfc2119</a>.
- [RFC6482] Lepinski, M., Kent, S., and D. Kong, "A Profile for Route
   Origin Authorizations (ROAs)", RFC 6482,
   DOI 10.17487/RFC6482, February 2012,
   <a href="http://www.rfc-editor.org/info/rfc6482">http://www.rfc-editor.org/info/rfc6482</a>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <a href="http://www.rfc-editor.org/info/rfc8174">http://www.rfc-editor.org/info/rfc8174</a>.
- [RFC8481] Bush, R., "Clarifications to BGP Origin Validation Based
   on Resource Public Key Infrastructure (RPKI)", RFC 8481,
   DOI 10.17487/RFC8481, September 2018,
   <a href="https://www.rfc-editor.org/info/rfc8481">https://www.rfc-editor.org/info/rfc8481</a>>.

### 7.2. Informative References

- [RFC6480] Lepinski, M. and S. Kent, "An Infrastructure to Support Secure Internet Routing", <u>RFC 6480</u>, DOI 10.17487/RFC6480, February 2012, <a href="http://www.rfc-editor.org/info/rfc6480">http://www.rfc-editor.org/info/rfc6480</a>.

Authors' Addresses

Randy Bush Internet Initiative Japan & Arrcus 5147 Crystal Springs Bainbridge Island, Washington 98110 US

Email: randy@psg.com

Ruediger Volk Deutsche Telekom

Email: rv@nic.dtag.de

Jakob Heitz Cisco 170 West Tasman Drive San Jose, CA 95134 USA

Email: jheitz@cisco.com