

INTERNET-DRAFT
Internet Engineering Task Force

Ranjith Mukundan
Wipro Technologies
Ken Morneault
Cisco Systems
N Mangalpally
Nortel Networks
Issued: Sept 2004

Expires: March 2005

DPNSS/DASS 2 extensions to the IUA protocol
<[draft-ietf-sigtran-dua-08.txt](#)>

Status of this Memo

By submitting this Internet-Draft, I certify that any applicable patent or other IPR claims of which I am aware have been disclosed, or will be disclosed, and any of which I become aware will be disclosed, in accordance with [RFC 3668](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at
<http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at
<http://www.ietf.org/shadow.html>.

Abstract

This document defines a mechanism for backhauling Digital Private Network Signaling System 1 (DPNSS 1) and Digital Access Signaling System 2 (DASS 2) messages over IP by extending the ISDN User Adaptation (IUA) Layer Protocol defined in [RFC 3057](#). DPNSS 1, specified in ND1301:2001/03 (formerly BTNR 188), is used to interconnect Private Branch Exchanges (PBX) in a private network and DASS 2, specified in BTNR 190, is used to connect PBXs to the PSTN. This document aims to become an Appendix to IUA and to be the base for a DPNSS 1/DASS 2 User Adaptation (DUA) implementation.

Table of Contents

1.0	Introduction	2
1.1	Scope	2
1.2	Terminology	3
1.3	DPNSS Overview	3
1.4	Proposed DPNSS Backhaul Architecture	4
2.0	Changes from IUA.....	4
2.1	New Message Class for DUA.....	4
2.2	Message Header.....	5
2.3	Unit Data Message.....	6
2.4	DLS Status Message.....	6
2.5	Management (MGMT) Messages.....	7
3.0	IANA Considerations.....	8
4.0	Use of SCTP Payload Protocol ID.....	9
5.0	Message Sequence in DUA.....	9
5.1	Resetting of single DLC.....	9
5.2	Resetting all DLCs in a link.....	10
5.3	Information Transfer on a DLC.....	10
5.4	Link Takedown(Single DLC).....	10
5.5	Link Takedown(All DLCs).....	10
5.6	Getting link Status.....	11
5.7	Error conditions.....	11
6.0	Security Considerations.....	11
7.0	References.....	11
8.0	Acknowledgements.....	11
9.0	Author's Addresses.....	12
10.0	Full Copyright Statement.....	12

[1.0](#) Introduction

This document describes a method of implementing Digital Private Network Signaling System 1 (DPNSS 1) [[2](#)] - henceforth just referred to as just DPNSS, and Digital Access Signaling System 2 (DASS 2)[[3](#)], backhaul messaging over IP using a modified version of the ISDN User Adaptation Protocol (IUAP) [[1](#)]. The DPNSS/DASS 2 User Adaptation (DUA) builds on top of IUA by defining the necessary extensions to IUA for a DPNSS/DASS2 implementation.

[1.1](#) Scope

There is a need for Switched Circuit Network (SCN) signaling protocol delivery from a DPNSS Signaling Gateway (SG) to a Media Gateway Controller (MGC). The delivery mechanism should support the following protocols:

- DPNSS (Digital Private Network Signaling System) [[2](#)]
- DASS 2 (Digital Access Signaling System Number 2) [[3](#)]

Unless specifically mentioned, the details in this document are applicable to both DPNSS and DASS 2.

1.2 Terminology

Data channel (D-channel) - A 64 kbit/s time slot which functions as a common signaling channel on a 2048 kbits/s interface or a 1544 kbits/s interface which is provisioned to carry DPNSS signaling.

DPNSS channel - Time slots 1 to 15 and 17 to 31 on a 2048 kbits/s interface or Time slots 1 to 23 on a 1544 kbits/s interface are termed as DPNSS channels. These are the traffic channels which carry voice or data traffic.

- DPNSS supports 60 Channels (30 Real and 30 Virtual)
- DASS2 supports 30 Channels (All Real)

Data Link Connection(DLC) - A DLC is the level 2 process that controls the transfer of level 3 messages on behalf of one DPNSS channel. A DLC uniquely identifies one DPNSS channel.

- DPNSS supports 60 DLCs (30 Real and 30 Virtual)
- DASSII supports 30 DLCs (All Real)

DPNSS Link - A logical collection of the D-channel and the associated DPNSS channels in a 2048 kbits/s interface or a 1544 kbits/s interface is called a "DPNSS Link".

Real channel - A signalling channel with associated traffic channel (TS).

Virtual channel - A signalling channel with no associated traffic channel.

NT1 - The DPNSS minimum retransmission period.

NT2 - The DPNSS minimum post retransmission acknowledgement delay.

1.3 DPNSS Overview

DPNSS is an industry standard interface (ref. ND1301:2001/03) [2] defined between a PBX and an Access Network (AN). DPNSS extends facilities normally only available between extensions on a single PBX to all extensions on PBXs that are connected together in a private network. DPNSS was originally derived from BT's Digital Access Signaling System I (DASS I) enhanced where necessary to meet the private network requirements. Some of these enhancements were incorporated in DASS 2 [3]. DPNSS uses a 2048 kbits/s or 1544 kbits/s Digital Transmission System Interface as shown in Figure 1 below.




Figure 1

Channel 16 on a 2048 kbits/s (E1) interface and channel 24 on a 1544 kbits/s (T1) interface is reserved for data communication between LE and AN. The channels reserved for data are called "Data Channels" or "D-Channels."

The D-Channels are the physical media to exchange data between the DPNSS protocol peer entities. A logical collection of the D-channel and the associated DPNSS channels is called a "DPNSS Link".

[1.4 Proposed DPNSS Backhaul Architecture](#)



NIF - Nodal Interworking function

SCTP - Stream Control Transmission Protocol

DUA - DPNSS User Adaptation Layer Protocol

[2.0 Changes from IUA](#)

This section outlines the differences between DUA and IUA.

[2.1 New Message Class for DUA](#)

The DPNSS/DASS2 Layer 2 to Layer 3 primitives [\[2\]](#) [\[3\]](#) need to be identifiable from IUA boundary primitive transport messages and the boundary primitive transport messages of other IUA extensions (i.e. V5 or GR-303). Therefore, it is necessary to use a different

message class parameter for DUA messages.

Mukundan, et. al.

[Page 4]

For all DPNSS/DASS2 interface boundary primitives, a new Message Class is introduced:

- 13 DPNSS/DASS2 Boundary Primitives Transport Messages
 (DPTM)

Similar to IUA, other valid message classes for DUA are:

- 0 Management (MGMT) Message
3 ASP State Maintenance (ASPSM) Messages
4 ASP Traffic Maintenance (ASPTM) Messages

2.2 Message Header

The IUA Message Header [1] MUST be used with the DPTM messages, but the DLCI field in the DLCI parameter is formatted differently. Figure 2 below shows the IUA Message Header with integer-based Interface Identifier.





Figure 2 IUA Message Header (integer-based Interface Identifier)

In DUA, the DLCI field has a different format in accordance with the ND1301:2001/03 (formerly BTNR 188) [2].



Reserved: 7 bits

Should be set to all '0's and ignored by the receiver.

V-bit: 1 bit

Mukundan, et. al.

[Page 5]

The V-bit is used to determine whether the message is for a particular DLC or it is applicable for all the DLCs in the carrier. The possible values of the V-bit are listed below:

Value	Description
0	Action is to be performed on all DLCs Channel number parameter is ignored.
1	Action is to be performed on a single DLC specified by channel number.

This V-bit value is used only by the Establish and Release messages. Data messages should ignore this value. This indicator is provided so that a single command can be issued to establish or release all the DLCs in one DPNSS Link.

For Channel Number (Channel No.), the valid values are 0 to 63 for DPNSS and 0 to 31 for DASS 2. This is because DASS 2 does not support virtual DLCs and hence has only 32 DLCs.

[2.3](#) Unit Data Message

DPNSS layer 2 does not have a unit data primitive and hence the Unit Data Messages (Request, Indication) are invalid for a DUA application. The Data Request and Indication messages (message types 1 and 2 respectively) will be used with DUA.

[2.4](#) DLC Status Message

For DUA, a new message is necessary to carry the status of the DLCs. This message will be a Management message (i.e. its message class will be a value of 0 for Management). The following message types will be used for these messages:

5	DLC Status Request
6	DLC Status Confirm
7	DLC Status Indication

The DLC Status messages are exchanged between IUA layer peers to request, confirm and indicate the status of the DLCs. The DLC Status messages contain the common message header followed by IUA message header as described in [section 2.1](#).

In addition, the DLC Status Confirm and Indication messages will contain the new parameter called the DLC Status parameter. This parameter will have the following format for an E1 interface:


```

      0               1               2               3
    0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|           Tag (0x12)           |           Length           |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| NA| D1| D2| D3| D4| D5| D6| D7| D8| D9|D10|D11|D12|D13|D14|D15|
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| NA|D17|D18|D19|D20|D21|D22|D23|D24|D25|D26|D27|D28|D29|D30|D31|
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| NA|D33|D34|D35|D36|D37|D38|D39|D40|D41|D42|D43|D44|D45|D46|D47|
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| NA|D49|D50|D51|D52|D53|D54|D55|D56|D57|D58|D59|D60|D61|D62|D63|
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

NA stands for Not Applicable. D0 and D16 are not applicable for an E1 interface because timeslot 0 is used for E1 framing and synchronization bits and timeslot 16 is used for signaling. For DPNSS, there would be a total of max 60 DLCs (30 real + 30 virtual) and in case of DASS2 there would be a total of 30 DLCs (no virtuals).

This parameter will have the following format for a T1 interface:

```

      0               1               2               3
    0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|           Tag (0x12)           |           Length           |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| D0| D1| D2| D3| D4| D5| D6| D7| D8| D9|D10|D11|D12|D13|D14|D15|
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|D16|D17|D18|D19|D20|D21|D22| NA|D24|D25|D26|D27|D28|D29|D30|D31|
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| NA|D33|D34|D35|D36|D37|D38|D39|D40|D41|D42|D43|D44|D45|D46| NA|
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

D23 is not applicable for a T1 interface because timeslot 23 is used for signaling. For DPNSS, there would be a total of max 46 DLCs (23 real + 23 virtual) and in case of DASS2 there would be a total of 23 DLCs (no virtuals).

The parameter carries the status of DLCs using two bits for each DLC. The possible values for the two bits are shown below:

Value	Description
00	Out Of Service
01	Reset Attempted
10	Reset Completed
11	Information Transfer

For DASS 2 the value 00 (Out Of Service) is invalid since the DASS 2

DLC does not have this state. In addition, the Idle state is a transient state local to the DLC so a value is not allocated for it.

For DASS 2 there are no virtual DLCs and hence information about only 32 DLCs need to be carried. Therefore the status message will have a length of 12 for a DASS 2 DLC Status message.

2.5 Management (MGMT) Messages

Only the Notify and Error messages are valid for DUA. The TEI Status messages are not used.

2.5.1 Error Message

The ERR message is sent when an invalid value or unrecognized message is found in an incoming message.

The Error Code parameter indicates the reason for the Error Message. These are the supported values in IUA.

Invalid Version	0x01
Invalid Interface Identifier	0x02
Unsupported Message Class	0x03
Unsupported Message Type	0x04
Unsupported Traffic Handling Mode	0x05
Unexpected Message	0x06
Protocol Error	0x07
Unsupported Interface Identifier Type	0x08
Invalid Stream Identifier	0x09
Unassigned TEI	0x0a
Unrecognized SAPI	0x0b
Invalid TEI, SAPI combination	0x0c
Refused - Management Blocking	0x0d
ASP Identifier Required	0x0e
Invalid ASP Identifier	0x0f

In DUA, the error codes 0x0a, 0x0b and 0x0c are invalid as they are specific to ISDN.

The following additional error codes are supported in DUA:

Channel Number out of range	0x1c
Channel Number not configured	0x1d

The "Channel Number out of range" error is sent if a message is received with a channel number greater than 63 for DPNSS or 31 for DASS 2.

The "Channel Number not configured" error is sent if a message is received with a channel number that is not configured.

3.0 IANA Considerations

IANA has assigned a DUA value for the SCTP Payload Protocol
Identifier field used in SCTP Payload Data chunks. The following

Mukundan, et. al.

[Page 8]

value for the SCTP Payload Protocol Identifier field SHOULD be used for DUA:

SCTP Payload Protocol ID = "10"

4.0 Use of SCTP Payload Protocol ID

As an option, IUA value for SCTP Payload Protocol ID MAY also be used for DUA, for instance, if one wanted to backhaul ISDN and DPNSS over the same SCTP association. However, use of separate SCTP Payload Protocol IDs (10 for DUA and 1 for IUA) is recommended as the primary option even in scenarios where ISDN and DPNSS are backhauled over the same SCTP association.

SCTP Payload Protocol ID of "10" SHOULD be used for DUA if only DPNSS is backhauled over a SCTP association - i.e., in scenarios where simultaneous backhauling of ISDN and DPNSS over the same association is NOT required

The SCTP Payload Protocol Identifier is included in each SCTP Data chunk, to indicate which protocol the SCTP is carrying. This Payload Protocol Identifier is not directly used by SCTP but MAY be used by certain network entities to identify the type of information being carried in a Data chunk.

The User Adaptation peer MAY use the Payload Protocol Identifier as a way of determining whether the message is for IUA or DUA.

5.0 Message Sequence in DUA

An example of the message flows for establishing a data link on a signaling channel, passing PDUs and releasing a data link on a DPNSS channel is shown below. An active association between MGC and SG is established prior to the following message flows.

5.1 Resetting of single DLC

i) Successful

PBX		SG		MGC
	<-----	SABMR		<-----
UA				Est Req(Ind=1)
	----->	Est Cfm	----->	(DLC in RC State)
		Ind=1)		

ii) Unsuccessful(Link Failure)

PBX		SG		MGC
	<-----	SABMR		<-----
				Est Req(Ind=1)
		Retransmissions over		
		NT1 and NT2 expired		
				Rel Ind -----> (DLC in RA state)
				(RELEASE_OTHER, Ind=1)

5.2 Resetting all DLCs in a link

```

PBX                                SG                                MGC
<----- SABMR(1)    <----- Est Req(Ind=0)
<----- SABMR(2)
<----- SABMR(3)
.....
<----- SABMR(N)
In each DLC either
UA is received or
NT1/NT2 is expired

                                Est Cfm -----> (Status of DLCs
                                (Ind=0)           are not updated)
                                <----- Status Req
Status cfm -----> (Mark DLC status
                                based on
                                status bits)

```

If one of more DLCs remains out-of-service after this procedure (e.g. due to layer 2 management), the MGC can either retry this DLC with an Est Req(Ind=1) indicating the specific DLC or with a Est Req(Ind=0) and the SG will retry the appropriate DLC that is out-of-service.

5.3 Information Transfer on a DLC

```

PBX                                SG                                MGC
<----- UI(C)                                <----- Data Req
UI(R)----->                                Data Ind ----->

```

5.4 Link Takedown(Single DLC)

```

PBX                                SG                                MGC
(For DPNSS, mark DLC as OOS)    <----- Rel Req
(For DASSII, mark DLC as RA)                                (RELEASE_MGMT,
                                                                Ind=1)
                                Rel Cfm ----->
                                (Ind=1)

```

5.5 Link Takedown(All DLCs)

```

PBX                                SG                                MGC
(For DPNSS, mark all DLCs as OOS) <----- Rel Req
(For DASSII, mark DLC as RA)                                (RELEASE_MGMT,
                                                                Ind=0)
                                Rel Cfm ----->

```


5.6 Getting link Status

PBX	SG	MGC
	<-----	Stat Req
	Stat Cfm ----->	(Mark DLC status based on status bits)

5.7 Error conditions

PBX	SG	MGC
	Invalid Message <-----	Est/Rel/Data/- Stat Req
	Error Ind ----->	
	(Error Code)	

6.0 Security Considerations

The security considerations discussed for the ISDN User Adaptation Protocol (IUAP) [1] [Section 6.0](#) and the Security Considerations for SIGTRAN Protocols document [4] apply to this document as well.

7.0 References

7.1 Normative References

- [1] Morneault, et al., ISDN Q.921-User Adaptation Layer [RFC3057](#)) February 2001
- [2] Ofcom/NICC ND1301:2001/03, DPNSS [188], Digital Private Signalling System No 1 (DPNSS 1) (Formerly BTNR 188).
- [3] BTNR (British Telecom Network Requirements) 190 Issue 2 Digital Access Signaling System No 2
- [4] Loughney, et al., Security Considerations for Signaling Transport (SIGTRAN) Protocols, [RFC 3788](#), June 2004

7.2 Informative References

- [5] ETS 300 167 (08/1993) : Transmission and Multiplexing; Functional characteristic of 2048 kbits/s interfaces (Standard is based on G.704, G.706).

8.0 Acknowledgments

The authors would like to thank Shashi Kumar and Venkatesh Seshasayee of Wipro Technologies for their useful suggestions and comments.

9.0 Author's Addresses

All correspondence regarding this draft should be sent to the following addresses:

Ranjith Mukundan	Phone: +91-80-51195893
Wipro Technologies	Email: ranjith.mukundan@wipro.com
72, Electronics City	
Hosur Main Road	
Bangalore 560100	
India	

Ken Morneault	Phone: +1-703-484-3323
Cisco Systems Inc.	Email: kmorneau@cisco.com
13615 Dulles Technology Drive	
Herndon, VA. 20171	
USA	

Narsimuloo Mangalpally	Phone: +1-613-967-5034
Nortel Networks	Email: narsim@nortelnetworks.com
250 Sidney Street	
Belleville, Ontario K8P 3Z3	
Canada	

10.0 Full Copyright Statement

"Copyright (C) The Internet Society (2004). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights."

"This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE."