

SIMPLE  
Internet-Draft  
Expires: September 16, 2005

H. Khartabil  
Telio  
E. Leppanen  
M. Lonnfors  
J. Costa-Requena  
Nokia  
March 15, 2005

An Extensible Markup Language (XML) Based Format for Event  
Notification Filtering  
draft-ietf-simple-filter-format-05

Status of this Memo

This document is an Internet-Draft and is subject to all provisions of [Section 3 of RFC 3667](#). By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she become aware will be disclosed, in accordance with [RFC 3668](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on September 16, 2005.

Copyright Notice

Copyright (C) The Internet Society (2005).

Abstract

The SIP event notification framework describes the usage of the Session Initiation Protocol (SIP) for subscriptions and notifications

of changes to a state of a resource. The document does not describe a mechanism of how filtering of event notification information can be achieved. Filtering is a mechanism for defining the preferred notification information to be delivered and for specifying triggers that cause that information to be delivered. In order to enable this, a format is needed to enable the subscriber to describe the state changes of a resource that cause notifications to be sent to it and what those notifications are to contain. This document presents a format in the form of an XML document.

## Table of Contents

<a href="#">1.</a>	<a href="#">Introduction . . . . .</a>	<a href="#">4</a>
<a href="#">2.</a>	<a href="#">Conventions . . . . .</a>	<a href="#">4</a>
<a href="#">3.</a>	<a href="#">Structure of XML-Encoded simple-filter . . . . .</a>	<a href="#">5</a>
<a href="#">3.1</a>	<a href="#">MIME Type for simple-filter Document . . . . .</a>	<a href="#">5</a>
<a href="#">3.2</a>	<a href="#">The &lt;filter-set&gt; Root Element . . . . .</a>	<a href="#">5</a>
<a href="#">3.3</a>	<a href="#">The &lt;ns-bindings&gt; Element . . . . .</a>	<a href="#">5</a>
<a href="#">3.4</a>	<a href="#">The &lt;filter&gt; Element . . . . .</a>	<a href="#">6</a>
<a href="#">3.5</a>	<a href="#">The &lt;what&gt; Element . . . . .</a>	<a href="#">7</a>
<a href="#">3.5.1</a>	<a href="#">The &lt;include&gt; Element . . . . .</a>	<a href="#">7</a>
<a href="#">3.5.2</a>	<a href="#">The &lt;exclude&gt; Element . . . . .</a>	<a href="#">8</a>
<a href="#">3.5.3</a>	<a href="#">The 'type' Attribute . . . . .</a>	<a href="#">8</a>
<a href="#">3.6</a>	<a href="#">The &lt;trigger&gt; Element . . . . .</a>	<a href="#">8</a>
<a href="#">3.6.1</a>	<a href="#">The &lt;changed&gt; Element . . . . .</a>	<a href="#">9</a>
<a href="#">3.6.1.1</a>	<a href="#">The 'from' Attribute . . . . .</a>	<a href="#">9</a>
<a href="#">3.6.1.2</a>	<a href="#">The 'to' Attribute . . . . .</a>	<a href="#">9</a>
<a href="#">3.6.1.3</a>	<a href="#">The 'by' Attribute . . . . .</a>	<a href="#">9</a>
<a href="#">3.6.1.4</a>	<a href="#">Combination of Attributes . . . . .</a>	<a href="#">10</a>
<a href="#">3.6.2</a>	<a href="#">The &lt;added&gt; Element . . . . .</a>	<a href="#">10</a>
<a href="#">3.6.3</a>	<a href="#">The &lt;removed&gt; Element . . . . .</a>	<a href="#">10</a>
<a href="#">4.</a>	<a href="#">XML Schema Extensibility . . . . .</a>	<a href="#">10</a>
<a href="#">5.</a>	<a href="#">Syntax for Referencing XML Items and Making Logical Expressions . . . . .</a>	<a href="#">11</a>
<a href="#">6.</a>	<a href="#">Examples . . . . .</a>	<a href="#">13</a>
<a href="#">6.1</a>	<a href="#">Filter Criteria Using &lt;what&gt; Element . . . . .</a>	<a href="#">13</a>
<a href="#">6.2</a>	<a href="#">Filter Criteria Using &lt;trigger&gt; Element . . . . .</a>	<a href="#">14</a>
<a href="#">6.3</a>	<a href="#">Filter Criteria Using &lt;what&gt; and &lt;trigger&gt; Elements . . . . .</a>	<a href="#">14</a>
<a href="#">6.4</a>	<a href="#">Content Filter Using Namespaces . . . . .</a>	<a href="#">15</a>
<a href="#">6.5</a>	<a href="#">Content Filter Using Only &lt;include&gt; Elements . . . . .</a>	<a href="#">16</a>
<a href="#">6.6</a>	<a href="#">Two Content Filters as Filter Criteria . . . . .</a>	<a href="#">16</a>
<a href="#">7.</a>	<a href="#">XML Schema for Filter Criteria . . . . .</a>	<a href="#">17</a>

<a href="#">8.</a>	Security Considerations . . . . .	<a href="#">20</a>
<a href="#">9.</a>	IANA Considerations . . . . .	<a href="#">20</a>
<a href="#">9.1</a>	application/simple-filter+xml MIME TYPE . . . . .	<a href="#">20</a>
9.2	URN Sub-Namespace Registration for urn:ietf:params:xml:ns:simple-filter . . . . .	<a href="#">21</a>

Khartabil, et al.                      Expires September 16, 2005                      [Page 2]

---

Internet-Draft                      XML Based Format for Filtering                      March 2005

<a href="#">9.3</a>	Schema Registration . . . . .	<a href="#">21</a>
<a href="#">10.</a>	Acknowledgements . . . . .	<a href="#">22</a>
<a href="#">11.</a>	References . . . . .	<a href="#">22</a>
<a href="#">11.1</a>	Normative References . . . . .	<a href="#">22</a>
<a href="#">11.2</a>	Informative References . . . . .	<a href="#">23</a>
	Authors' Addresses . . . . .	<a href="#">23</a>
	Intellectual Property and Copyright Statements . . . . .	<a href="#">25</a>

## 1. Introduction

The SIP event notification framework [\[2\]](#) describes the usage of the Session Initiation Protocol (SIP) for subscriptions and notifications of changes to a state of a resource. The document does not describe a mechanism of how filtering of event notification information can be achieved.

Filtering is a mechanism for defining the preferred notification information, referred to as content, to be delivered and for specifying the rules for when that information should be delivered.

The filtering mechanism is expected to be particularly valuable and primarily applicable to users of mobile wireless access devices. The characteristics of the devices typically include high latency, low bandwidth, low data processing capabilities, small display, and limited battery power. Such devices can benefit from the ability to filter the amount of information generated at the source of the event notification. However, implementers need to be aware of the computational burden on the source of the event notification. This is discussed further in [Section 8](#).

The structure of the filter criteria is described using the XML Schema. The filter criteria is presented as an XML document. The XML document contains the user's preference when notifications are to be sent to it and what they are to contain. The scope of the "when" part is triggering.

The triggering is defined as enabling a subscriber to specify

triggering rules for notifications where the criteria are based on changes of the event package [2] specific state information, e.g., for the presence information document [15] the change in the value of the <status> element.

The functionality of the filtering regarding the SIP event notifications is specified in [3].

## [2.](#) Conventions

In this document, the key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'MAY', and 'OPTIONAL' are to be interpreted as described in [RFC 2119](#) [1] and indicate requirement levels for compliant implementations.

Throughout the document, the "resulting XML document" refers to the final XML document that carries state information to be delivered to the subscriber after the filters have been applied to it.

"Content" refers to the XML document that appears in a notification reflecting the state of a resource.

## [3.](#) Structure of XML-Encoded simple-filter

A simple-filter is an XML document [8] that MUST be well-formed and MUST be valid according to schemas, including extension schemas, available to the validator and applicable to the XML document. The simple-filter documents MUST be based on XML 1.0 and MUST be encoded using UTF-8.

The namespace identifier for elements defined by this specification is a URN [5], using the namespace identifier 'ietf' defined by [6] and extended by [4]. This urn is:  
urn:ietf:params:xml:ns:simple-filter.

This namespace declaration indicates the namespace on which the filter criteria are based on.

### [3.1](#) MIME Type for simple-filter Document

The MIME type for the simple-filter document is

"application/simple-filter+xml". Any transport protocol (SIP [\[12\]](#), for example) that is used to carry the filters that also carries payload type information MUST identify the payload as MIME type "simple-filter+xml" (for example: a Content-Type header field).

### [3.2](#) The <filter-set> Root Element

The root element of the filter criteria is <filter-set>.

The <filter-set> element contains the namespace definition mentioned above. With the optional 'package' attribute, it is possible to define the package to which the filter criteria is applied. This might be especially useful in cases where the XML document containing the filter criteria is separated from the events that make use of it or from the protocol that usually carries it.

The <filter-set> element may contain one <ns-bindings> elements.

The <filter-set> element contains one or more <filter> elements.

### [3.3](#) The <ns-bindings> Element

The <ns-bindings> element is used to bind namespaces to local prefixes used in expressions that select elements or attributes using the syntax in [Section 5](#). Those prefixes apply to the <include>, <exclude>, <changed>, <added> and <removed> elements.

The <ns-bindings> element contains one or more <ns-binding> elements. Each <ns-binding> element has a 'prefix' attribute. The value of the 'prefix' attribute is a prefix used to qualify the elements pointed to by the expression. The <ns-binding> element also has a 'urn' attribute that identifies the namespace that the prefix represents.

### [3.4](#) The <filter> Element

The <filter> element is used to specify the content of an individual filter.

The <filter> element has an 'id' attribute. The value of the 'id' attribute MUST be unique within the <filter-set> element. The <filter> MAY have an 'uri' attribute. The value of the 'uri' attribute is the URI of the resource which the filter applies to. The <filter> MAY have an 'domain' attribute. The value of the 'domain' attribute is the domain of the resources that the filter applies to. The 'uri' attribute and the 'domain' attribute MUST NOT

appear together in a filter.

The URI of the resource is useful in cases where the 'event list' extension [17] is used with a package. Since a subscription to an event package may be addressed to an event list, the 'uri' attribute allows the subscriber to define a filter specific to an individual resource within that list. That resource may be another list. The 'uri' attribute may, of course, carry the URI of the list itself. If the <filter> does not contain the 'uri' attribute, the filter applies to the resource identified in the subscription request.

The 'domain' attribute carries a domain. In this case, the filter applies to resources whose URI has a domain part matching that domain. This can be used when a subscription is for a resource that is an event list with many resources from differing domains.

URI matching is done according to the matching rules defined for a particular scheme. When matching domains, the user part of the URI is ignored for matching purposes.

The <filter> MAY have a 'remove' attribute which indicates together with the 'id' attribute the existing filter to be removed. The value of the 'remove' attribute is of the type "Boolean". The default value is "false".

The <filter> MAY have a 'enabled' attribute which indicates whether a filter is enabled or disabled. The value of the 'enabled' attribute is of the type "Boolean". The default value is "true".

The <filter> element MAY contain a <what> element and MAY contain one or more <trigger> elements, but MUST contain either the <what> element or the <trigger> element when the filter is being enabled for

the first time. When a filter is disabled by setting the 'enabled' attribute to "false", the <what> and <trigger> elements MAY be omitted. Similarly, when a filter is re-enabled by setting the 'enabled' attribute to "true", the <what> and <trigger> elements MAY be omitted.

Filter contents can be changed by changing the contents in the <what> and <trigger> elements and maintaining the value of the filter 'id' attribute.

### [3.5](#) The <what> Element

The <what> element is used to specify the content to be delivered to the user. It does not specify the exact content but the rules that are used to construct that information.

The <what> element may contain one or more <include> elements and one or more <exclude> elements. When more than one <include> element has been defined, the results are additive. I.e. each <include> element contents adds an element or attribute to the resulting XML document. When more than one <exclude> element has been defined, each <exclude> element value depletes the contents of the resulting XML document.

#### [3.5.1](#) The <include> Element

The <include> element is used to select the content to be delivered. Its value can identify an XML element, an attribute or a namespace of XML document to be filtered. This is indicated using the 'type' attribute.

Note that the resulting XML document MUST be valid. Therefore, in addition to including the elements identified with the <include> element value, all other mandatory XML elements and/or attributes must be incorporated in the resulting XML document in order to make it valid. This, in practice, means that a subscriber defining a filter only needs to <include> optional elements and/or attributes, but may <include> mandatory elements and/or attributes as well. There are also cases where a filter selects an attribute that belongs to an optional element. In this case, the optional element needs to appear in the resulting XML document.

The syntax defined in [Section 5](#) (see the definition of "selection".) MUST be used. The following example selects the <basic> element defined in the PIDF [\[13\]](#). This results in the selection of the <basic> element as well as all the ancestors. I.e. <status> and <tuple>.

```
<include type="xpath">/presence/tuple/status/basic</include>.
```

#### [3.5.2](#) The <exclude> Element



The <exclude> element is used to define exceptions to the set of XML elements and/or attributes selected by the <include> elements. Thus, those XML elements (including their lower level "child" elements) and/or attributes defined by the <exclude> element are not delivered. This is most useful when an <include> element identifies a namespace.

The <exclude> element has the optional 'type' attribute (see the definition of the 'type' in [Section 3.5.3](#)).

Note that the resulting XML document MUST be valid. Therefore, if the step in applying the <exclude> element value to an XML document results in an invalid document according to the schema, that step MUST be reversed resulting in the elements and/or attributes being re-introduced into the resulting XML document, with their previous values, in order to make it valid. This, in practice, means that a subscriber defining a filter only needs to <exclude> optional elements and/or attributes, but SHOULD NOT <exclude> mandatory elements and/or attributes.

The syntax MUST follow [Section 5](#).

### [3.5.3](#) The 'type' Attribute

The 'type' attribute is used to describe the value of the <include> and <exclude> elements. The following values are pre-defined: "xpath" and "namespace". The 'type' attribute is optional, and, if omitted, the default value is "xpath".

The "xpath" value is used when the <include> or <exclude> element contains a value following the syntax in [Section 5](#) that selects an element or an attribute.

The "namespace" value is used when the <include> or <exclude> element contains a value of a namespace. The value is the URI of the namespace. The resulting XML document is comprised of the elements defined within the namespace.

### [3.6](#) The <trigger> Element

The <trigger> element is used to identify the package specific changes that a resource has to encounter before the content is delivered to the subscriber. It can appear more than once in a <filter> element. Multiple appearances of this element denotes the "OR" operation. This means that updates to a resource that satisfy any of the <trigger> elements criteria constitute the content to be delivered.

The <trigger> element MAY contain the <changed> element, the <added> element or the <removed>, but MUST contain at least one of the three elements. Any combination of the 3 elements is possible. Multiple appearances of those elements within a <trigger> element denotes the "AND" operation. This means that updates to a resource that satisfy ALL of the <changed>, <added> and <removed> elements' criteria within the <trigger> element constitute the content to be delivered.

### [3.6.1](#) The <changed> Element

The <changed> element is used to identify the XML element or attribute, from the package specific XML document, whose value MUST change, compared to the "previous XML document", in order to activate the trigger and cause the content to be delivered. Previous XML document in this context refers to the last XML document that was selected for delivery to that specific subscription before any filter was applied to it. The XML element or attribute MUST be expressed using the syntax defined in [Section 5](#) for the "reference" ABNF.

The <changed> element MAY contain the 'from' attribute, 'to' attribute, 'by' attribute, or any combination of the three. The absence of all those attributes means a change of any sort to the value of the element or attribute activates the trigger. An update to the element or attribute value with an identical value is not a change.

Comparison of a change is done the element or attribute's lexical rules.

#### [3.6.1.1](#) The 'from' Attribute

A trigger is active when the XML element or attribute identified with the <changed> element has changed from the value indicated by this attribute to a different value.

#### [3.6.1.2](#) The 'to' Attribute

A trigger is active when the XML element or attribute identified with the <changed> element has changed to the value indicated by this attribute from a different value.

#### [3.6.1.3](#) The 'by' Attribute

A trigger is active when the XML element or attribute identified with the <changed> element has changed by at least the amount indicated by this attribute from a different value. I.e. The 'by' attribute applies only to numerical values and indicates a delta with respect the current value that an attribute or element (identified in the <changed> element) needs to change before it is selected. For example: if the 'by' attribute is set to 2, and the current value of

the element/attribute is 6, the element/attribute is selected when it reaches (or exceeds) the value 8 or when it decreases to 4 or lower value.

#### [3.6.1.4](#) Combination of Attributes

Any combination of the 'from', 'to', and 'by' attributes in the <changed> element is possible. For example, if the 'from' attribute was combined with the 'to' attribute it is interpreted as: the trigger is active when the XML element or attribute identified with the <changed> element has changed from the 'from' value to the 'to' value. Note that if the 'by' attribute is used in combination with the other attributes, the other attribute types MUST match the 'by' type of decimal.

#### [3.6.2](#) The <added> Element

The <added> element triggers content delivery when the XML element it identifies has been added to the document being filtered (that is, this instance of that element appears in the current document, but not the previous document). It can be used, for example, to learn of new services and/or capabilities subscribed to by the user, or services and/or capabilities that the user has now allowed the subscriber to see. The XML element or attribute MUST be expressed using the syntax defined in [Section 5](#) for the "reference" ABNF.

Note that if a filter includes both the content filter (<what>) part and the <added> element then the definitions of the <what> part SHOULD cover also the added elements, or otherwise the content is delivered without the items defined in the <added> element.

#### [3.6.3](#) The <removed> Element

The <removed> element triggers content delivery when the XML element it identifies has been removed from the document being filtered (that is, this instance of that element appeared in the previous document, but not the this document). The XML element or attribute MUST be expressed using the syntax defined in [Section 5](#) for the "reference" ABNF.

### [4.](#) XML Schema Extensibility

The filter-set document is meant to be extended. An extension takes place by defining a new set of elements in a new namespace, governed by a new schema. Every extension MUST have an appropriate XML namespace assigned to it. The XML namespace of the extension MUST be different from the namespaces defined in this specification. The extension MUST NOT change the syntax or semantics of the schemas

defined in this document. All XML tags and attributes that are part of the extension MUST be appropriately qualified so as to place them within that namespace and MUST be designed such that receivers can safely ignore such extensions.

This specification defines explicit places where new elements or attributes from an extension can be placed. These are explicitly indicated in the schemas by the `<any>` and `<anyAttribute>` elements. Extensions to this specification MUST specify where their elements can be placed within the document.

As a result, a document that contains extensions will require multiple schemas in order to determine its validity – a schema defined in this document, along with those defined by extensions present in the document. Because extensions occur by adding new elements and attributes governed by new schemas, the schemas defined in this document are fixed and would only be changed by a revision to this specification. Such a revision, should it take place, would endeavor to allow documents compliant to the previous schema to remain compliant to the new one. As a result, the schemas defined here don't provide explicit schema versions, as this is not expected to be needed.

## [5.](#) Syntax for Referencing XML Items and Making Logical Expressions

The ABNF [\[10\]](#) is used to describe the syntax for the expressions. The syntax is defined to be XPATH [\[9\]](#) compatible, but has only a restricted set of capabilities of the XPATH. More information about the meaning of the items of the syntax can be found in [\[9\]](#). The "abbreviated syntax" of the "node test" is used in the references ("reference"). The expression in the syntax relates to the predicate, comparison and logical expressions of the XPATH. If an XPATH expression evaluates to more than one element at a certain step, the filter applies to all the elements that are evaluated.

I.e. If a filter including a element evaluates to 2 elements, both elements are included as a result.

```
selection = reference [expression]
expression = "[" (elem-expr / attr-expr)
              1*[oper (elem-expr / attr-expr)] "]"
elem-expr = (elem-path / "." / "..") compar value
elem-path = (element / "*" ) 1*["/" / "*" / element] ["*" / element]
attr-expr = [elem-path "/" ] attribute compar value

reference = elem-reference / attr-reference
elem-reference = "/" 1*("/" / "/"* / ("/" element))
attr-reference = reference attribute

oper = "and" / "or"
compar = "=" / "<" / ">"
element = [ns] string
attribute = "@" [ns] string
ns = string ":"
string = <any sequence of data supported by XML in names of XML
element, and/or attribute or prefixes of namespaces>
value = <any sequence of data supported by XML as a value of the
XML element and/or attribute>
```

When identifying XML elements or attributes, the value may consist of two parts: the XML element/attribute selector and the condition (comparison and logical expressions). The XML element selector appears first followed by the condition part in square brackets. In the XML element selector part the XML elements may be referenced by giving the full hierarchical path as: "/presence/tuple/status/basic",

or by denoting the selection to cover any hierarchical level by its name as: `//tuple/status/basic` or using the wildcard `*` denoting any value in a certain level as `/*/watcher`.

Example references are listed as follows:

- o Selecting an element by using an XML element as a condition:

- \* `//*[status/basic="open"]`

- \* `/presence/tuple[*/basic="open"]`

- o Selecting an element by using XML attributes as a condition :

- \* `//watcher[@duration-subscribed<500]`

- \* `/*/watcher[@event="rejected"]`

- o Selecting an element by using two XML elements as a condition :

- \* `//tuple[status/basic="open" and type="device"]`

- o Selecting an attribute :

- \* `//watcher/@duration-subscribed`

In some cases, due to the design of the XML schema, the XPATH-like expression results in identifying more than one element with the same name (the XPATH expression may not have uniquely identified an element at every step). In those cases, all elements identified are selected.

When evaluating XPath location steps, namespace expansion follows XPath 1.0 [\[9\]](#) semantics, i.e. if the QName does not have a prefix then the namespace URI in the expanded name is null. With non-default namespaces, expansion is done according to the given `<ns-bindings>` definitions. When there's a default namespace used in the document, `<ns-binding>` element SHOULD be used to define an equal URI with some prefix in order to have a valid XPath evaluation in

location steps.

## [6.](#) Examples

The XML Schema for the XML document examples is specified in the [Section 7](#).

### [6.1](#) Filter Criteria Using <what> Element

A user wishes to get to know his friend's availability and willingness for messaging (SMS, IM and MMS) in order to know whether the friend is able to receive a message, the address to contact and the type of the message to be used.

This example shows how to define a content filter. The <basic> element as well as all parent elements are selected based on a condition defined by a logical expression. The condition is: <class> elements that have a value "MMS", "SMS" or "IM".

The <class> element is defined in [\[14\]](#) as an extension to PIDF [\[13\]](#).

```
<?xml version="1.0" encoding="UTF-8"?>
<filter-set xmlns="urn:ietf:params:xml:ns:simple-filter">
  <ns-bindings>
    <ns-binding prefix="pidf" urn="urn:ietf:params:xml:ns:pidf"/>
    <ns-binding prefix="rpid"
                urn="urn:ietf:params:xml:ns:pidf:rpid-tuple"/>
  </ns-bindings>
  <filter id="123" uri="sip:presentity@example.com">
    <what>
      <include type="xpath">
        /pidf:presence/pidf:tuple[rpid:class="IM" or rpid:class="SMS"
          or rpid:class="MMS"]/pidf:status/pidf:basic
      </include>
```

```

    </what>
  </filter>
</filter-set>

```

## 6.2 Filter Criteria Using <trigger> Element

A user requires to get informed when his colleague becomes available by some communication mean(s). The user gets the full presence state of the colleague when a certain PIDF [13] tuple <basic> status changes from 'CLOSED' to 'OPEN'.

```

<?xml version="1.0" encoding="UTF-8"?>
<filter-set xmlns="urn:ietf:params:xml:ns:simple-filter">
  <ns-bindings>
    <ns-binding prefix="pidf" urn="urn:ietf:params:xml:ns:pidf"/>
  </ns-bindings>
  <filter id="123" uri="sip:presentity@example.com">
    <trigger>
      <changed from="CLOSED" to="OPEN">
        /pidf:presence/pidf:tuple/pidf:status/pidf:basic
      </changed>
    </trigger>
  </filter>
</filter-set>

```

## 6.3 Filter Criteria Using <what> and <trigger> Elements

A user wishes to get information about pending and waiting subscriptions in order to be able to authorise watchers to see his presence information.

The filter selects watcher information notifications [16] to be sent when a subscription status has changed to "pending" or "waiting". In

the notification, only the watchers that have a status of "pending" or "waiting" are included.

```

<?xml version="1.0" encoding="UTF-8"?>
<filter-set xmlns="urn:ietf:params:xml:ns:simple-filter">
  <ns-bindings>

```



```

    <ns-binding prefix="wi"
                urn="urn:ietf:params:xml:ns:watcherinfo"/>
</ns-bindings>
<filter id="123" uri="sip:presentity@example.com">
  <what>
    <include>
      /wi:watcherinfo/wi:watcher-list/wi:watcher[@status="pending"
        or @status="waiting"]
    </include>
  </what>
  <trigger>
    <changed to="pending">
      /wi:watcherinfo/wi:watcher-list/wi:watcher/@status
    </changed>
  </trigger>
  <trigger>
    <changed to="waiting">
      /wi:watcherinfo/wi:watcher-list/wi:watcher/@status
    </changed>
  </trigger>
</filter>
</filter-set>

```

#### [6.4](#) Content Filter Using Namespaces

A user turns her terminal on and the terminal automatically fetches general presence status and information about communication means from a certain pre-defined set of her buddies.

The filter is defined to select XML elements belonging to the pidf namespace.

```

<?xml version="1.0" encoding="UTF-8"?>
<filter-set xmlns="urn:ietf:params:xml:ns:simple-filter">
  <filter id="123" uri="sip:buddylist@example.com">
    <what>
      <include type="namespace">
        urn:ietf:params:xml:ns:pidf
      </include>
    </what>
  </filter>

```

</filter-set>

### [6.5](#) Content Filter Using Only <include> Elements

A user wants to know if a group of his friends are available for gaming. He orders notifications about the current status and future changes of the game specific presence information.

This filter is defined to select the game specific tuple to be delivered.

```
<?xml version="1.0" encoding="UTF-8"?>
<filter-set xmlns="urn:ietf:params:xml:ns:simple-filter" >
  <ns-bindings>
    <ns-binding prefix="game-ext"
                  urn="urn:ietf:params:xml:ns:game-ext"/>
  </ns-bindings>
  <filter id="123">
    <what>
      <include>
        /pidf:presence/pidf:tuple/
        pidf:status[game-ext:label="game-X"]
      </include>
    </what>
  </filter>
</filter-set>
```

### [6.6](#) Two Content Filters as Filter Criteria

The user is interested in getting up-to-date information about the communication means and contact addresses of his friends. The user wants to get also more information (e.g. location) about one of the friends in the list named Bob. The PIDF element <note> is filtered out, i.e. excluded. The list was predefined as buddies@example.com.

```
<?xml version="1.0" encoding="UTF-8"?>
<filter-set xmlns="urn:ietf:params:xml:ns:simple-filter">
  <ns-bindings>
    <ns-binding prefix="pidf" urn="urn:ietf:params:xml:ns:pidf"/>
    <ns-binding prefix="rpid"
                  urn="urn:ietf:params:xml:ns:pidf:rpid-tuple"/>
  </ns-bindings>
  <filter id="8439" uri="sip:buddies@example.com">
    <what>
      <include>
        /pidf:presence/pidf:tuple[rpid:class="service"]/pidf:status/
        pidf:basic
      </include>
    </what>
  </filter>
  <filter id="999" uri="sip:bob@example.com">
    <what>
      <include type="namespace">
        urn:ietf:params:xml:ns:pidf
      </include>
      <exclude>
        /pidf:presence/pidf:tuple/pidf:note
      </exclude>
    </what>
  </filter>
</filter-set>
```

## [7.](#) XML Schema for Filter Criteria

### XML Schema Implementation (Normative)

```
<?xml version="1.0" encoding="UTF-8"?>
<xs:schema targetNamespace="urn:ietf:params:xml:ns:simple-filter"
  xmlns="urn:ietf:params:xml:ns:simple-filter"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  elementFormDefault="qualified">

  <xs:import namespace="http://www.w3.org/XML/1998/namespace"
    schemaLocation="http://www.w3.org/2001/xml.xsd"/>

  <xs:annotation>
    <xs:documentation xml:lang="en">
      XML Schema Definition for Filter Criteria.
```

```

    </xs:documentation>
</xs:annotation>

<xs:element name="filter-set" type="FilterSetType"/>

```

```

<xs:complexType name="FilterSetType">
  <xs:sequence>
    <xs:element name="ns-bindings" type="NSBindings"
      minOccurs="0" maxOccurs="1"/>
    <xs:element name="filter" type="FilterType"
      minOccurs="1" maxOccurs="unbounded"/>
  </xs:sequence>
  <xs:attribute name="package" type="xs:string" use="optional"/>
</xs:complexType>

<xs:complexType name="NSBindings">
  <xs:sequence>
    <xs:element name="ns-binding" type="NSBinding"
      minOccurs="1" maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="NSBinding">
  <xs:attribute name="prefix" type="xs:string" use="required"/>
  <xs:attribute name="urn" type="xs:anyURI" use="required"/>
</xs:complexType>

<xs:complexType name="FilterType">
  <xs:sequence>
    <xs:element name="what" type="WhatType"
      minOccurs="0" maxOccurs="1"/>
    <xs:element name="trigger" type="TriggerType"
      minOccurs="0" maxOccurs="unbounded"/>
    <xs:any namespace="##other" processContents="lax"
      minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
  <xs:attribute name="id" type="xs:string" use="required"/>
  <xs:attribute name="uri" type="xs:anyURI" use="optional"/>
  <xs:attribute name="domain" type="xs:string" use="optional"/>
  <xs:attribute name="remove" type="xs:boolean" use="optional"
    default="false"/>

```

```

    <xs:attribute name="enabled" type="xs:boolean" use="optional"
                  default="true"/>
    <xs:anyAttribute namespace="##other" processContents="lax"/>
</xs:complexType>

<xs:complexType name="WhatType">
  <xs:sequence>
    <xs:element name="include" type="InclType"
                  minOccurs="0" maxOccurs="unbounded"/>
    <xs:element name="exclude" type="ExclType"
                  minOccurs="0" maxOccurs="unbounded"/>
    <xs:any namespace="##other" processContents="lax"
  >

```

```

        minOccurs="0" maxOccurs="unbounded"/>
    </xs:sequence>
</xs:complexType>

<xs:complexType name="InclType">
  <xs:simpleContent>
    <xs:extension base="xs:string">
      <xs:attribute name="type" type="TypeType"
                    default="xpath" use="optional"/>
      <xs:anyAttribute namespace="##other" processContents="lax"/>
    </xs:extension>
    </xs:simpleContent>
  </xs:complexType>

<xs:complexType name="ExclType">
  <xs:simpleContent>
    <xs:extension base="xs:string">
      <xs:attribute name="type" type="TypeType"
                    default="xpath" use="optional"/>
      <xs:anyAttribute namespace="##other" processContents="lax"/>
    </xs:extension>
    </xs:simpleContent>
  </xs:complexType>

<xs:simpleType name="TypeType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="xpath"/>
    <xs:enumeration value="namespace"/>
  </xs:restriction>

```

```

</xs:simpleType>

<xs:complexType name="TriggerType">
  <xs:sequence>
    <xs:element name="changed" type="ChangedType"
      minOccurs="0" maxOccurs="unbounded"/>
    <xs:element name="added" type="xs:string"
      minOccurs="0" maxOccurs="unbounded"/>
    <xs:element name="removed" type="xs:string"
      minOccurs="0" maxOccurs="unbounded"/>
    <xs:any namespace="##other" processContents="lax"
      minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="ChangedType">
  <xs:simpleContent>
    <xs:extension base="xs:string">
      <xs:attribute name="from" type="xs:anySimpleType"

```

```

      use="optional"/>
    <xs:attribute name="to" type="xs:anySimpleType"
      use="optional"/>
    <xs:attribute name="by" type="xs:decimal"
      use="optional"/>
    <xs:anyAttribute namespace="##other" processContents="lax"/>
  </xs:extension>
</xs:simpleContent>
</xs:complexType>

</xs:schema>

```

## 8. Security Considerations

The filters in the body in a SIP message has a significant effect on the ways in which the request is handled at a server. As a result, it is especially important that messages containing this extension be authenticated and authorised. Authentication can be achieved using the Digest Authentication mechanism described in [12]. The authorisation decision is made based on the permissions that the resource (notifier) has given to the watcher. An example of such

authorisation policy can be found in [\[18\]](#).

Requests can reveal sensitive information about a UA's capabilities. If this information is sensitive, it SHOULD be encrypted using SIP S/MIME capabilities [\[11\]](#).

All filtering related security measures discussed in [\[2\]](#) MUST be followed along with package specific security.

## [9.](#) IANA Considerations

This document registers a new MIME type "application/simple-filter+xml", and registers a new XML namespace.

This specification follows the guidelines of [RFC3023](#) [\[7\]](#).

### [9.1](#) application/simple-filter+xml MIME TYPE

MIME media type: application

MIME subtype name: simple-filter+xml

Mandatory parameters: none

Optional parameters: Same as charset parameter application/xml as specified in [RFC 3023](#) [\[7\]](#).

Khartabil, et al.	Expires September 16, 2005	[Page 20]
-------------------	----------------------------	-----------

---

Internet-Draft	XML Based Format for Filtering	March 2005
----------------	--------------------------------	------------

Encoding considerations: Same as encoding considerations of application/xml as specified in [RFC 3023](#) [\[7\]](#).

Security considerations: See [section 10 of RFC 3023](#) [\[7\]](#) and [section Section 8](#) of this document.

Interoperability considerations: none.

Published specification: This document.

Applications which use this media type: This document type has been used to support SIP based Event notification framework and its packages.

Additional information:

Magic number: None

File extension: .cl or .xml

Macintosh file type code: "TEXT"

Personal and email address for further information: Hisham Khartabil  
(hisham.khartabil@telio.no)

Intended Usage: COMMON

Author/change controller: The IETF

## [9.2](#) URN Sub-Namespace Registration for urn:ietf:params:xml:ns:simple-filter

This section registers a new XML namespace, as per guidelines in the IETF XML Registry [\[4\]](#).

URI: The URI for this namespace is  
urn:ietf:params:xml:ns:simple-filter.

Registrant Contact: IETF, SIMPLE working group, Hisham Khartabil  
(hisham.khartabil@telio.no)

## [9.3](#) Schema Registration

This section registers a new XML schema per the procedures in [\[4\]](#).

URI: urn:ietf:params:xml:ns:simple-filter

Registrant Contact: IETF, SIMPLE working group, Hisham Khartabil

Khartabil, et al. Expires September 16, 2005 [Page 21]

---

Internet-Draft XML Based Format for Filtering March 2005

(hisham.khartabil@telio.no).

The XML for this schema can be found as the sole content of  
[Section 7](#).

## [10](#). Acknowledgements

The authors would like to thank Jonathan Rosenberg, Henning



Schulzrinne, Tim Moran, Jari Urpalainen, Sreenivas Addagatla, Miguel-Angel Garcia Martin, Mary Barnes, Paul Kyzivat, Robert Sparks and Elwyn Davies for their valuable input and comments.

## 11. References

### 11.1 Normative References

- [1] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [2] Roach, A., "Session Initiation Protocol (SIP)-Specific Event Notification", [RFC 3265](#), June 2002.
- [3] Khartabil, H., "Functional Description of Event Notification Filtering", [draft-simple-event-filter-funct-05.txt](#), February 2005.
- [4] Mealling, M., "The IETF XML Registry", [RFC 3688](#), January 2004.
- [5] Moats, R., "The URN Syntax", [RFC 2141](#), May 1997.
- [6] Moats, R., "The URN Namespace for IETF Documents", [RFC 2648](#), August 1999.
- [7] Murata, M., "XML Media Types", [RFC 3023](#), March 1997.
- [8] Bray, T., "Extensible Markup Language (XML) 1.0 (Second Edition)", W3C CR CR-xml11-20011006, October 2000.
- [9] Clark, J., "XML Path Language (XPath) Version 1.0", W3C REC REC-xpath-19991116, November 1999.
- [10] Crocker, D., "Augmented BNF for Syntax Specifications: ABNF", [RFC 2234](#), November 1997.
- [11] Ramsdell, B., "S/MIME Version 3 Message Specification", [RFC 2633](#), June 1999.

### 11.2 Informative References

- [12] Rosenberg et al., J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M. and E. Schooler, "SIP: Session Initiation Protocol", [RFC 3261](#), June 2002.
- [13] Sugano, H., "Presence Information Data Format", [RFC 3863](#), August 2004.
- [14] Schulzrinne, H., "RPID -- Rich Presence Information Data Format", [draft-ietf-simple-rpid-00.txt](#) (work in progress), May 2004.
- [15] Rosenberg, J., "Session Initiation Protocol (SIP) Extensions for Presence", [RFC 3856](#), July 2004.
- [16] Rosenberg, J., "An Extensible Markup Language (XML) Based Format for Watcher Information", [RFC 3858](#), July 2004.
- [17] Roach, A., "A Session Initiation Protocol (SIP) Event Notification Extension for Resource Lists", [draft-ietf-simple-event-list-04.txt](#), June 2003.
- [18] Rosenberg, J., "Presence Authorization Rules", [draft-ietf-simple-presence-rules-01](#), April 2005.

#### Authors' Addresses

Hisham Khartabil  
Telio  
P.O. Box 1203 Vika  
Oslo  
Norway

Phone: +47 2167 3544  
Email: [hisham.khartabil@telio.no](mailto:hisham.khartabil@telio.no)

Eva Leppanen  
Nokia  
P.O BOX 785  
Tampere  
Finland

Phone: +358 7180 77066  
Email: [eva-maria.leppanen@nokia.com](mailto:eva-maria.leppanen@nokia.com)

Mikko Lonnfors  
Nokia  
Itamerenkatu 00180  
Helsinki  
Finland

Phone: + 358 50 4836402  
Email: mikko.lonnfors@nokia.com

Jose Costa-Requena  
Nokia  
P.O. Box 321  
FIN-00045 NOKIA GROUP  
FINLAND

Phone: +358 71800 8000  
Email: jose.costa-requena@nokia.com

## Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at [ietf-ipr@ietf.org](mailto:ietf-ipr@ietf.org).

## Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

## Copyright Statement

Copyright (C) The Internet Society (2005). This document is subject

to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

#### Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.