

SIMPLE WG
Internet-Draft
Intended status: Standards Track
Expires: May 22, 2008

M. Lonnfors
Nokia
E. Leppanen
Individual
H. Khartabil
Ericsson Australia
J. Urpalainen
Nokia
November 19, 2007

Presence Information Data format (PIDF) Extension for Partial Presence
draft-ietf-simple-partial-pidf-format-10

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on May 22, 2008.

Copyright Notice

Copyright (C) The IETF Trust (2007).

Abstract

The Presence Information Document Format (PIDF) specifies the baseline XML based format for describing presence information. One of the characteristic of the PIDF is that the document always needs

Internet-Draft

Partial PIDF

November 2007

to carry all presence information available for the presentity. In some environments where low bandwidth and high latency links can exist it is often beneficial to limit the amount of transported information over the network. This document introduces a new MIME type which enables transporting of either only the changed parts or the full PIDF based presence information.

Table of Contents

1.	Introduction	3
2.	Conventions	3
3.	Structure of PIDF diff documents	3
3.1.	'version' attribute	5
3.2.	'entity' attribute	5
4.	Usage of 'application/pidf-diff+xml'	5
5.	IANA Considerations	5
5.1.	URN Sub-Namespace registration for 'urn:ietf:params:xml:ns:pidf-diff'	5
5.2.	application/pidf-diff+xml MIME Type	6
5.3.	XML Schema Registration	7
6.	Examples	7
7.	XML Schema	11
8.	Interoperability Considerations	13
9.	Security Considerations	13
10.	Internationalization Considerations	13
11.	Error Handling	13
12.	Acknowledgments	14
13.	References	14
13.1.	Normative references	14
13.2.	Informative references	15
	Authors' Addresses	15
	Intellectual Property and Copyright Statements	17

Internet-Draft

Partial PIDF

November 2007

1. Introduction

The Presence Information Document Format (PIDF) [[RFC3863](#)] specifies the baseline XML based format for describing presence information. One of the characteristic of the PIDF is that the document always needs to carry all presence information available for the presentity. In some environments where low bandwidth and high latency links can exist, it is often beneficial to limit the amount of transported information over the network.

This document introduces a new MIME-Type 'application/pidf-diff+xml' which enables transporting of either only the changed parts or the full PIDF based presence information. The root element of the document distinguishes whether the partial or full PIDF document content was transported.

Note: With this new MIME-Type applications can easily negotiate the support of partial updates of presence by using the Accept-header. If PIDF had initially been designed for partial updates, a new separate MIME-Type would have been unnecessary.

2. Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)] and indicate requirement levels for compliant implementations.

This memo makes use of the vocabulary defined in [RFC2778](#) [[RFC2778](#)]. In addition, the following terms are defined:

Full presence document: A presence document that contains all the presentity's presence information that is available to a particular watcher.

Partial presence document: A presence document that represents a fragment of the full presence document. A partial presence documents can only be understood in the context of the full presence document, i.e. a partial presence document modifies a cached copy of the full presence document.

3. Structure of PIDF diff documents

The MIME type 'application/pidf-diff+xml' defines the new content type for partial PIDF documents.

The XML Schema imports the PIDF [[RFC3863](#)] schema so that the full PIDF document content with the addition of a 'version' attribute can be transported. The root element of the document is then <pidf-full> and the 'version' attribute information can be included within it. Otherwise the content of <pidf-full> element is exactly the same as what would have been if 'application/pidf+xml' content type had been used. Although the XML Schema allows using also <presence> as the document root element it is disallowed from applications utilizing this document format.

When only the changes of the presence document are transported, the model described in XML patch operations [[I-D.ietf-simple-xml-patch-ops](#)] is used. The root element of the document is then <pidf-diff>. The patch operation elements: <add>, <remove> and <replace> allow changing the partial content of the cached local copy of the full presence document. The <add> element is used to add new content, the <replace> element updates and the <remove> element removes existing content.

The optional 'version' attribute within the two possible document root elements contains a sequence number which is incremented by one between subsequent document updates, i.e. a more recent document update has a higher 'version' value than the previous one. This number can be used to ensure consistent updates as the recipient of the document can use the 'version' number to properly order received documents and to ensure that updates have not been lost. The usage of this attribute thus allows "state delta" processing described in [[RFC3265](#)]. Partial notification [[I-D.ietf-simple-partial-notify](#)] uses similar model. This number increments independently regardless

of whether the <pidf-full> or the <pidf-diff> content is transported. In other words, a single version counter is maintained across <pidf-full> and <pidf-diff> documents.

Implementations using this document format MUST follow guidelines specified in the PIDF [[RFC3863](#)] and PIDF extension formats, for example DataModel [[RFC4479](#)], RPID [[RFC4480](#)] and CIPID [[RFC4482](#)] and MUST support the usage of the XML schema data type ID [[W3C.REC-xmlschema-2-20041028](#)] of these listed RFCs. Specifically, the XML document MUST be well formed and SHOULD be valid. This specification makes use of XML namespaces for identifying presence documents and document fragments. The namespace URI for elements defined by this specification is a URN [[RFC2141](#)], using the namespace identifier 'ietf' specified in [RFC 2648](#) [[RFC2648](#)] and extended by [RFC3688](#) [[RFC3688](#)]. This URN is:

urn:ietf:params:xml:ns:pidf-diff

[3.1.](#) 'version' attribute

Every presence document compliant with this specification MAY contain a 'version' attribute within the <pidf-diff> and <pidf-full> element.

[3.2.](#) 'entity' attribute

Every presence document compliant with this specification MAY contain an 'entity' attribute within the <pidf-diff> element. Its content, a presentity URI MUST then be the same as the 'entity' attribute value of the <presence> element described in [[RFC3863](#)]. The usage of this presentity URI is described in more detail in [section 3.1 of \[RFC4479\]](#).

[4.](#) Usage of 'application/pidf-diff+xml'

The partial presence document SHOULD only contain those elements or attributes that have changed. However, when there are a lot of changes the full presence document content can then be transported instead.

5. IANA Considerations

This memo calls for IANA to:

- o register a new XML namespace URN per [[RFC3688](#)].
- o register a new MIME type 'application/pidf-diff+xml' according to the procedures of [RFC 4288](#) [[RFC4288](#)] and guidelines in [RFC 3023](#) [[RFC3023](#)].
- o register a new XML Schema according to the procedures of [RFC 3688](#) [[RFC3688](#)].

5.1. URN Sub-Namespace registration for 'urn:ietf:params:xml:ns:pidf-diff'

This specification registers a new XML namespace, as per the guidelines in [RFC 3688](#) [[RFC3688](#)].

URI:

urn:ietf:params:xml:ns:pidf-diff

Description:

This is the XML namespace for XML elements defined by
[[[RFCXXXX]]] to describe the 'application/pidf-diff+xml' content

type for partial PIDF.

Registrant Contact:

IETF, SIMPLE working group, (simple@ietf.org)
Jari Urpalainen, (jari.urpalainen@nokia.com)

XML:

```
BEGIN
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML Basic 1.0//EN"
  "http://www.w3.org/TR/xhtml-basic/xhtml-basic10.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
  <head>
```

```

    <meta http-equiv="content-type"
          content="text/html; charset=iso-8859-1"/>
    <title>PIDF extension for partial PIDF</title>
  </head>
  <body>
    <h1>Namespace for PIDF extension for partial
      notifications</h1>
    <h2>urn:ietf:params:xml:ns:pidf-diff</h2>
    <p>See <a href="[[URL of published RFC]]">
      RFCXXXX</a>.</p>
  </body>
</html>
END

```

5.2. application/pidf-diff+xml MIME Type

MIME media type name: application

MIME subtype name: pidf-diff+xml

Mandatory parameters: none

Optional parameters:

Same as charset parameter of application/xml as specified in [RFC 3023](#) [RFC3023]. Default value is UTF-8.

Encoding considerations:

Same as encoding considerations of application/xml as specified in See [RFC 3023](#) [RFC3023].

Security considerations:

See [Section 10 of RFC 3023](#) [RFC3023]. This content type is designed to carry presence data, which may be considered private

information. Appropriate precautions should be adopted to limit disclosure of this information.

Interoperability considerations: none

Published specification: [[RFCXXXX]]

Applications which use this media type: SIP-based presence systems

Additional information:

Magic Number: None

File Extension: .xml

Macintosh file type code: "TEXT"

Personal and email address for further information: Jari
Urpalainen, jari.urpalainen@nokia.com

Intended usage: LIMITED USE

Restrictions on usage: Presence [[RFC3863](#)] based systems.

Author:

This specification is a work item of the IETF SIMPLE working
group, with mailing list address <simple@ietf.org>.

Author/Change controller: the IETF.

[5.3.](#) XML Schema Registration

This section calls for IANA to register a new XML Schema, the sole
content of which can be found in [Section 7](#).

URI:

urn:ietf:params:xml:schema:pidf-diff

Registrant Contact:

IETF, SIMPLE working group, <simple@ietf.org>

Jari Urpalainen, <jari.urpalainen@nokia.com>

[6.](#) Examples

An 'application/pidf-diff+xml' document that contains the full state
presence information:


```

<p:pidf-full xmlns="urn:ietf:params:xml:ns:pidf"
  xmlns:p="urn:ietf:params:xml:ns:pidf-diff"
  xmlns:r="urn:ietf:params:xml:ns:pidf:rpid"
  xmlns:ci="urn:ietf:params:xml:ns:pidf:cipid"
  xmlns:c="urn:ietf:params:xml:ns:pidf:caps"
  xmlns:dm="urn:ietf:params:xml:ns:pidf:data-model"
  entity="pres:someone@example.com"
  version="567">

  <tuple id="sg89ae">
    <status>
      <basic>open</basic>
    </status>
    <c:servcaps>
      <c:audio>true</c:audio>
      <c:message>true</c:message>
      <c:video>>false</c:video>
    </c:servcaps>
    <contact priority="0.8">tel:09012345678</contact>
  </tuple>

  <tuple id="cg231jcr">
    <status>
      <basic>open</basic>
    </status>
    <contact priority="1.0">im:pep@example.com</contact>
  </tuple>

  <tuple id="r1230d">
    <status>
      <basic>closed</basic>
    </status>
    <ci:homepage>http://example.com/~pep/</ci:homepage>
    <ci:icon>http://example.com/~pep/icon.gif</ci:icon>
    <ci:card>http://example.com/~pep/card.vcd</ci:card>
    <contact priority="0.9">sip:pep@example.com</contact>
  </tuple>

  <note xml:lang="en">Full state presence document</note>

  <dm:person id="p123">
    <r:activities>
      <r:on-the-phone/>
      <r:busy/>
    </r:activities>
  </dm:person>

```

```
<dm:device id="u600b40c7">
  <c:devcaps>
    <c:mobility>
      <c:supported>
        <c:mobile/>
      </c:supported>
    </c:mobility>
  </c:devcaps>
  <dm:deviceID>urn:esn:600b40c7</dm:deviceID>
</dm:device>

</p:pidf-full>
```

An example partial update document with the <pidf-diff> root element:

```
<?xml version="1.0" encoding="UTF-8"?>
<p:pidf-diff
  xmlns="urn:ietf:params:xml:ns:pidf"
  xmlns:p="urn:ietf:params:xml:ns:pidf-diff"
  xmlns:r="urn:ietf:params:xml:ns:pidf:rpidd"
  xmlns:d="urn:ietf:params:xml:ns:pidf:data-model"
  entity="pres:someone@example.com"
  version="568">

  <p:add sel="presence/note" pos="before">
    <tuple id="ert4773">
      <status>
        <basic>open</basic>
      </status>
      <contact priority="0.4">mailto:pep@example.com</contact>
      <note xml:lang="en">This is a new tuple inserted
        between the last tuple and person element</note>
    </tuple>
  </p:add>

  <p:replace sel="*/tuple[@id='r1230d']/status/basic/text()"
    >open</p:replace>

  <p:remove sel="*/d:person/r:activities/r:busy" ws="after"/>

  <p:replace sel="*/tuple[@id='cg231jcr']/contact/@priority"
    >0.7</p:replace>

</p:pidf-diff>
```

Internet-Draft

Partial PIDF

November 2007

patches:

```
<?xml version="1.0" encoding="UTF-8"?>
<p:pidf-full xmlns="urn:ietf:params:xml:ns:pidf"
  xmlns:p="urn:ietf:params:xml:ns:pidf-diff"
  xmlns:r="urn:ietf:params:xml:ns:pidf:rpidd"
  xmlns:ci="urn:ietf:params:xml:ns:pidf:cipidd"
  xmlns:c="urn:ietf:params:xml:ns:pidf:caps"
  xmlns:dm="urn:ietf:params:xml:ns:pidf:data-model"
  entity="pres:someone@example.com"
  version="568">

  <tuple id="sg89ae">
    <status>
      <basic>open</basic>
    </status>
    <c:servcaps>
      <c:audio>true</c:audio>
      <c:message>true</c:message>
      <c:video>false</c:video>
    </c:servcaps>
    <contact priority="0.8">tel:09012345678</contact>
  </tuple>

  <tuple id="cg231jcr">
    <status>
      <basic>open</basic>
    </status>
    <contact priority="0.7">im:pep@example.com</contact>
  </tuple>

  <tuple id="r1230d">
    <status>
      <basic>open</basic>
    </status>
    <ci:homepage>http://example.com/~pep/</ci:homepage>
    <ci:icon>http://example.com/~pep/icon.gif</ci:icon>
    <ci:card>http://example.com/~pep/card.vcd</ci:card>
    <contact priority="0.9">sip:pep@example.com</contact>
```

</tuple>

```
<tuple id="ert4773">
  <status>
    <basic>open</basic>
  </status>
  <contact priority="0.4">mailto:pep@example.com</contact>
  <note xml:lang="en">This is a new tuple inserted
    between the last tuple and note element</note>
```

</tuple>

<note xml:lang="en">Full state presence document</note>

```
<dm:person id="p123">
  <r:activities>
    <r:on-the-phone/>
  </r:activities>
</dm:person>
```

```
<dm:device id="u600b40c7">
  <c:devcaps>
    <c:mobility>
      <c:supported>
        <c:mobile/>
      </c:supported>
    </c:mobility>
  </c:devcaps>
  <dm:deviceID>urn:esn:600b40c7</dm:deviceID>
</dm:device>
```

</p:pidf-full>

[7.](#) XML Schema

The XML schema for the 'application/pidf-diff+xml' data format. The included schema "urn:ietf:params:xml:schema:xml-patch-ops" is defined in [[I-D.ietf-simple-xml-patch-ops](#)] and the PIDF Schema "pidf.xsd" is imported from [[RFC3863](#)].

```
<?xml version="1.0" encoding="UTF-8"?>
<xsd:schema
  targetNamespace="urn:ietf:params:xml:ns:pidf-diff"
  xmlns:tns="urn:ietf:params:xml:ns:pidf-diff"
  xmlns:pidf="urn:ietf:params:xml:ns:pidf"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  elementFormDefault="qualified">

  <!-- include patch-ops type definitions -->
  <xsd:include
    schemaLocation="urn:ietf:params:xml:schema:patch-ops"/>

  <!-- import PIDF definitions -->
  <xsd:import namespace="urn:ietf:params:xml:ns:pidf"
    schemaLocation="pidf.xsd"/>

  <!-- partial updates -->
  <xsd:element name="pidf-diff">
    <xsd:complexType>
      <xsd:sequence minOccurs="0" maxOccurs="unbounded">
        <xsd:choice>
          <xsd:element name="add" type="tns:add"/>
          <xsd:element name="replace" type="tns:replace"/>
          <xsd:element name="remove" type="tns:remove"/>
        </xsd:choice>
      </xsd:sequence>
    </xsd:complexType>
  </xsd:element>
</xsd:schema>
```

```

    </xsd:sequence>
    <xsd:attribute name="version" type="xsd:unsignedInt"/>
    <xsd:attribute name="entity" type="xsd:anyURI"/>
  </xsd:complexType>
</xsd:element>

<!-- full PIDF in addition to optional version -->
<xsd:element name="pidf-full">
  <xsd:complexType>
    <xsd:complexContent>
      <xsd:extension base="pidf:presence">
        <xsd:attribute name="version" type="xsd:unsignedInt"/>
      </xsd:extension>
    </xsd:complexContent>
  </xsd:complexType>
</xsd:element>

</xsd:schema>

```

8. Interoperability Considerations

Systems compliant with CPP [[RFC3859](#)] will not be by default able to use this specification. However, this will not cause any interoperability problems because all endpoints and gateways must support the default MIME type (application/pidf+xml) regardless if they support this specification. Thus if a gateway or another end point does not understand this specification it will not be used. In SIMPLE based systems use of this MIME type is negotiated using SIP content type negotiation mechanism as specified in partial notification [[I-D.ietf-simple-partial-notify](#)].

Other CPP compliant (other than SIP based) systems can also support this specification if they have a mechanism to indicate support for it. If they do it is possible to build a gateway which will preserve end-to-end integrity with usage of partial PIDF.

[9.](#) Security Considerations

All security considerations identified for PIDF [[RFC3863](#)] apply unchanged for this document as presence information may contain highly sensitive information. Furthermore, the protocol SHOULD provide authorization policies what presence information can be given to which watchers, and when, see [[I-D.ietf-simple-presence-rules](#)].

[10.](#) Internationalization Considerations

The PIDF [[RFC3863](#)] format is represented in XML which performs all character processing in terms of the Universal Character Set (UCS). Conformant XML processors MUST support both UTF-8 and UTF-16 encodings of the UCS. UTF-8 is the RECOMMENDED encoding of this partial presence format.

If the character set of the initial <pidf-full> document has been accepted by a receiving application, it MUST continue to accept the same character set with the subsequent <pidf-diff> documents. However, it MUST NOT need to accept a possible character set change.

[11.](#) Error Handling

Error conditions MAY be indicated by errors defined in [[I-D.ietf-simple-xml-patch-ops](#)]. This document doesn't define any additional error elements. If the 'version' or 'entity' attributes have incorrect content it MAY be indicated by the <invalid-attribute-value> error element.

[12.](#) Acknowledgments

The authors would like to thank Jose Costa-Requena, Jyrki Aarnos, Jonathan Rosenberg, Dean Willis, Miguel Garcia, Krisztian Kiss, Ben Cambell, Robert Sparks, Anders Kristenssen, Aki Niemi, Jon Peterson, Gonzalo Camarillo, Lars Eggert, Lakshminath Dondeti and Chris Newman for their valuable comments and contributions.

[13.](#) References

13.1. Normative references

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC3863] Sugano, H., Fujimoto, S., Klyne, G., Bateman, A., Carr, W., and J. Peterson, "Presence Information Data Format (PIDF)", [RFC 3863](#), August 2004.
- [RFC2141] Moats, R., "URN Syntax", [RFC 2141](#), May 1997.
- [RFC2648] Moats, R., "A URN Namespace for IETF Documents", [RFC 2648](#), August 1999.
- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), January 2004.
- [RFC3023] Murata, M., St. Laurent, S., and D. Kohn, "XML Media Types", [RFC 3023](#), January 2001.
- [RFC4288] Freed, N. and J. Klensin, "Media Type Specifications and Registration Procedures", [BCP 13](#), [RFC 4288](#), December 2005.
- [RFC4479] Rosenberg, J., "A Data Model for Presence", [RFC 4479](#), July 2006.
- [RFC4480] Schulzrinne, H., Gurbani, V., Kyzivat, P., and J. Rosenberg, "RPID: Rich Presence Extensions to the Presence Information Data Format (PIDF)", [RFC 4480](#), July 2006.
- [RFC4482] Schulzrinne, H., "CIPID: Contact Information for the Presence Information Data Format", [RFC 4482](#), July 2006.
- [I-D.ietf-simple-xml-patch-ops]
Urpalainen, J., "An Extensible Markup Language (XML) Patch Operations Framework Utilizing XML Path Language (XPath) Selectors", [draft-ietf-simple-xml-patch-ops-04](#) (work in

Second Edition", World Wide Web Consortium
Recommendation REC-xmlschema-2-20041028, October 2004,
<<http://www.w3.org/TR/2004/REC-xmlschema-2-20041028>>.

13.2. Informative references

- [RFC2778] Day, M., Rosenberg, J., and H. Sugano, "A Model for Presence and Instant Messaging", [RFC 2778](#), February 2000.
- [RFC3265] Roach, A., "Session Initiation Protocol (SIP)-Specific Event Notification", [RFC 3265](#), June 2002.
- [RFC3859] Peterson, J., "Common Profile for Presence (CPP)", [RFC 3859](#), August 2004.
- [I-D.ietf-simple-partial-notify]
Lonnfors, M., "Session Initiation Protocol (SIP) extension for Partial Notification of Presence Information", [draft-ietf-simple-partial-notify-09](#) (work in progress), February 2007.
- [I-D.ietf-simple-presence-rules]
Rosenberg, J., "Presence Authorization Rules", [draft-ietf-simple-presence-rules-10](#) (work in progress), July 2007.

Authors' Addresses

Mikko Lonnfors
Nokia
Itamerenkatu 11-13 00180
Helsinki
Finland

Phone: +358 71 8008000
Email: mikko.lonnfors@nokia.com

Eva Leppanen
Individual
Lempaala
Finland

Email: eva.leppanen@saunalahti.fi

Hisham Khartabil
Ericsson Australia
P.O. Box 256c
Melbourne, VIC 3001
Australia

Email: hisham.khartabil@gmail.com

Jari Urpalainen
Nokia
Itamerenkatu 11-13 00180
Helsinki
Finland

Phone: +358 7180 37686
Email: jari.urpalainen@nokia.com

Internet-Draft

Partial PIDF

November 2007

Full Copyright Statement

Copyright (C) The IETF Trust (2007).

This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY, THE IETF TRUST AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Intellectual Property

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Acknowledgment

Funding for the RFC Editor function is provided by the IETF Administrative Support Activity (IASA).