

SIPCORE
Internet-Draft
Updates: RFC [3263](#) (if approved)
Intended status: Standards Track
Expires: August 26, 2016

O. Johansson
Edvina AB
G. Salgueiro
Cisco Systems
V. Gurbani
Bell Labs, Alcatel-Lucent
D. Worley, Ed.
Ariadne
February 23, 2016

**Locating Session Initiation Protocol (SIP) Servers in a Dual-Stack IP
Network
draft-ietf-sipcore-dns-dual-stack-04**

Abstract

[RFC 3263](#) defines how a Session Initiation Protocol (SIP) implementation, given a SIP Uniform Resource Identifier (URI), should locate the next hop SIP server using Domain Name System (DNS) procedures. As SIP networks increasingly transition from IPv4-only to dual-stack, a quality user experience must be ensured for dual-stack SIP implementations. This document updates the DNS procedures described in [RFC 3263](#) for dual-stack SIP implementations in preparation for forthcoming specifications for applying Happy Eyeballs to SIP.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 26, 2016.

Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
2.	Notational Conventions	3
3.	Terminology	3
4.	DNS Procedures in a Dual-Stack Network	4
4.1.	Dual-Stack SIP UA DNS Record Lookup Procedure	4
4.2.	Indicating Address Family Preference in DNS SRV Records .	5
5.	Clarification of RFC 6157	5
6.	Security Considerations	5
7.	IANA Considerations	6
8.	Acknowledgments	6
9.	Revision History	6
9.1.	Changes from draft-ietf-sipcore-dns-dual-stack-03 to draft-ietf-sipcore-dns-dual-stack-04	6
9.2.	Changes from draft-ietf-sipcore-dns-dual-stack-02 to draft-ietf-sipcore-dns-dual-stack-03	6
10.	References	7
10.1.	Normative References	7
10.2.	Informative References	8
	Authors' Addresses	8

[1.](#) Introduction

The Session Initiation Protocol (SIP, [[RFC3261](#)]) and the additional documents that extended it provide support for both IPv4 and IPv6. However, this support does not fully extend to the highly hybridized environments that are characteristic of the transitional migratory phase from IPv4 to IPv6 networks. During this phase, many server and client implementations run on dual-stack hosts. In such environments, a dual-stack host will likely suffer greater connection delay, and by extension an inferior user experience, than an IPv4-only host. The need to remedy this diminished performance of

dual-stack hosts led to the development of the Happy Eyeballs [[RFC6555](#)] algorithm, which has since been implemented in many protocols and applications.

This document updates the DNS lookup procedures of [RFC 3263](#) [[RFC3263](#)] in preparation for the specification of the application of Happy Eyeballs to SIP to provide enhanced performance, and consequently user experience, in highly hybridized dual-stack SIP networks. The procedures described herein are such that a dual-stack client should look up both A and AAAA records in DNS and then select the best way to set up a network flow. The details of how the latter is done is considered out of scope for this document. See the Happy Eyeballs algorithm and implementation and design considerations in [RFC 6555](#) [[RFC6555](#)] for more information about issues with setting up dual-stack network flows.

This document clarifies the interaction of [[RFC3263](#)] with [[RFC6157](#)] as described in [Section 5](#).

2. Notational Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

3. Terminology

[RFC 3261](#) [[RFC3261](#)] defines additional terms used in this document that are specific to the SIP domain such as "proxy"; "registrar"; "redirect server"; "user agent server" or "UAS"; "user agent client" or "UAC"; "back-to-back user agent" or "B2BUA"; "dialog"; "transaction"; "server transaction".

This document uses the term "SIP Server" that is defined to include the following SIP entities: user agent server, registrar, redirect server, a SIP proxy in the role of user agent server, and a B2BUA in the role of a user agent server.

This document also uses the following terminology to make clear distinction between SIP entities supporting only IPv4, only IPv6 or supporting both IPv4 and IPv6.

IPv4-only UA/UAC/UAS: An IPv4-only UA/UAC/UAS supports SIP signaling and media only on the IPv4 network. It does not understand IPv6 addresses.

IPv6-only UA/UAC/UAS: An IPv6-only UA/UAC/UAS supports SIP signaling and media only on the IPv6 network. It does not understand IPv4 addresses.

IPv4/IPv6 UA/UAC/UAS: A UA/UAC/UAS that supports SIP signaling and media on both IPv4 and IPv6 networks; such a UA/UAC/UAS is known (and will be referred to in this document) as a "dual-stack" [[RFC4213](#)] UA/UAC/UAS.

address records: The DNS records which translate a domain name into addresses within the address family(ies) that the UA supports, as A RR's provide IPv4 addresses and AAAA RR's provide IPv6 addresses.

4. DNS Procedures in a Dual-Stack Network

This specification introduces two normative DNS lookup procedures. These are designed to improve the performance of dual-stack clients in IPv4/IPv6 networks.

4.1. Dual-Stack SIP UA DNS Record Lookup Procedure

Once the transport protocol has been determined, the procedure for discovering an IP address if the TARGET is not a numeric IP address but the port is explicitly stated in the URI, is detailed in [Section 4.2 of RFC 3263](#) [[RFC3263](#)]. The piece relevant to to this discussion is:

If the TARGET was not a numeric IP address, but a port is present in the URI, the client performs an A or AAAA record lookup of the domain name. The result will be a list of IP addresses, each of which can be contacted at the specific port from the URI and transport protocol determined previously.

[Section 4.2 of RFC 3263](#) [[RFC3263](#)] also goes on to describe the procedure for discovering an IP address if the TARGET is not a numeric IP address, and no port is present in the URI. The piece relevant to to this discussion is:

If no SRV records were found, the client performs an A or AAAA record lookup of the domain name. The result will be a list of IP addresses, each of which can be contacted using the transport protocol determined previously, at the default port for that transport. Processing then proceeds as described above for an explicit port once the A or AAAA records have been looked up.

Happy Eyeballs [[RFC6555](#)] documents that looking up the "A or AAAA record" is not an effective practice for dual-stack clients and that

it can add significant connection delay and greatly degrade user experience. Therefore, this document makes the following normative addendum to the DNS lookup procedures of [Section 4.2 of RFC 3263](#) [[RFC3263](#)] for IPv4/IPv6 hybrid SIP networks and recommends it as a best practice for such dual-stack networks:

The dual-stack client SHOULD look up all address records (i.e., for all address family(ies) that it supports) for the domain name and add the resulting addresses to the list of IP addresses to be contacted. A client MUST be prepared for DNS lookups to return addresses in families that it does not support; such addresses MUST be ignored as unusable and the supported addresses used as specified herein.

[4.2.](#) Indicating Address Family Preference in DNS SRV Records

The Happy Eyeballs algorithm [[RFC6555](#)] is particularly effective when dual-stack client applications have significant performance differences in their IPv4 or IPv6 network paths. In this common scenario it is often necessary for a dual-stack client to indicate a preference for either IPv4 or IPv6. A service may use DNS SRV records to indicate such a preference for an address family. This way, a server with a high-latency and/or low-capacity IPv4 tunnel may indicate a preference for being contacted using IPv6. A server that wishes to do this can use the lowest SRV priority to publish hostnames that only resolve in IPv6 and the next priority with host names that resolve in both address families.

[5.](#) Clarification of [RFC 6157](#)

[RFC6157] defers to the Source and Destination Address Selection algorithms defined in [[RFC6724](#)] (the successor of [[RFC3484](#)]) when allowing a client to choose a specific server (c.f. [Section 5 in](#) [\[RFC6157\]](#)).

This document clarifies the process: If SRV lookup is successful, the major ordering of the list of destination addresses is determined by the priority and weight fields of the SRV records as specified in [[RFC2782](#)]. The (minor) ordering among the destinations derived from the "target" field of a single SRV record is determined by [[RFC6724](#)].

[6.](#) Security Considerations

This document introduces two new normative procedures to the existing DNS procedures used to locate SIP servers. While both of these procedures are optimizations designed to improve the performance of dual-stack clients, neither introduces any new security considerations.

The specific security vulnerabilities, attacks and threat models of the various protocols discussed in this document (SIP, DNS, SRV records, Happy Eyeballs requirements and algorithm, etc.) are well documented in their respective specifications.

7. IANA Considerations

This document does not require any actions by IANA.

8. Acknowledgments

The authors would like to acknowledge the support and contribution of the SIP Forum IPv6 Working Group. This document is based on a lot of tests and discussions at SIPit events, organized by the SIP Forum.

This document has benefited from the expertise and review feedback of many participants of the IETF DISPATCH and SIPCORE WG mailing lists as well as those on the SIP Forum IPv6 Task Group mailing list. The authors wish to specifically call out the efforts and express their gratitude for the detailed and thoughtful comments and corrections of Dan Wing, Brett Tate, Rifaat Shekh-Yusef, Carl Klatsky, Mary Barnes, Keith Drage, Cullen Jennings and Simon Perreault.

The authors also thank the SIPCORE WG chairs, Paul Kyzivat and Adam Roach, and assigned Area Director, Richard Barnes, for their support and thorough evaluation of this work.

9. Revision History

[Note to RFC Editor: Please remove this entire section upon publication as an RFC.]

9.1. Changes from [draft-ietf-sipcore-dns-dual-stack-03](#) to [draft-ietf-sipcore-dns-dual-stack-04](#)

Changed the "updates" specification to add [RFC 3263](#) and remove [RFC 6157](#).

Added Simon Perreault to the acknowledgments.

Minor wording changes.

9.2. Changes from [draft-ietf-sipcore-dns-dual-stack-02](#) to [draft-ietf-sipcore-dns-dual-stack-03](#)

Described the relationship to [RFC 3263](#) as "update", since the existing wording in 3263 is not what we want. Arguably, the new

wording is what was intended in 3263, but the existing wording either does not say that or says it in a way that is easily misunderstood.

Described the relationship to [RFC 6157](#) as "clarification", since the described interaction between 3263 and 6157 appears to be the only reasonable interpretation.

Revised wording, punctuation, and capitalization in various places.

Clarified that this draft does not document Happy Eyeballs for SIP, but is preparatory for it.

Attempted to use "update" for text that is definitively a change to the preexisting text and "clarify" for text that is a more clear statement of the (presumed) intention of the preexisting text.

Removed normative words from [section 1](#), the introduction.

Copied definition of "address records" from [RFC 2782](#) (SRV records) to allow the specifications to expand automatically to include any new address families.

Relocated the text requiring a client to ignore addresses that it discovers in address families it does not support from [section 4.2](#) (which describes why the situation arises) to [section 4.1](#) (which describes how clients look up RRs).

Clarified the interaction with [RFC 6157](#) (source and destination address selection in IPv6) to specify what must have been intended: The major sort of the destinations is the ordering determined by priority/weight in the SRV records; the addresses derived from a single SRV record's target are minorly sorted based on [RFC 6157](#).

Removed editor's name from the acknowledgments list.

[10](#). References

[10.1](#). Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC2782] Gulbrandsen, A., Vixie, P., and L. Esibov, "A DNS RR for specifying the location of services (DNS SRV)", [RFC 2782](#), DOI 10.17487/RFC2782, February 2000, <<http://www.rfc-editor.org/info/rfc2782>>.

- [RFC3263] Rosenberg, J. and H. Schulzrinne, "Session Initiation Protocol (SIP): Locating SIP Servers", [RFC 3263](#), DOI 10.17487/RFC3263, June 2002, <<http://www.rfc-editor.org/info/rfc3263>>.
- [RFC6157] Camarillo, G., El Malki, K., and V. Gurbani, "IPv6 Transition in the Session Initiation Protocol (SIP)", [RFC 6157](#), DOI 10.17487/RFC6157, April 2011, <<http://www.rfc-editor.org/info/rfc6157>>.

10.2. Informative References

- [RFC3261] Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M., and E. Schooler, "SIP: Session Initiation Protocol", [RFC 3261](#), DOI 10.17487/RFC3261, June 2002, <<http://www.rfc-editor.org/info/rfc3261>>.
- [RFC3484] Draves, R., "Default Address Selection for Internet Protocol version 6 (IPv6)", [RFC 3484](#), DOI 10.17487/RFC3484, February 2003, <<http://www.rfc-editor.org/info/rfc3484>>.
- [RFC4213] Nordmark, E. and R. Gilligan, "Basic Transition Mechanisms for IPv6 Hosts and Routers", [RFC 4213](#), DOI 10.17487/RFC4213, October 2005, <<http://www.rfc-editor.org/info/rfc4213>>.
- [RFC6555] Wing, D. and A. Yourtchenko, "Happy Eyeballs: Success with Dual-Stack Hosts", [RFC 6555](#), DOI 10.17487/RFC6555, April 2012, <<http://www.rfc-editor.org/info/rfc6555>>.
- [RFC6724] Thaler, D., Ed., Draves, R., Matsumoto, A., and T. Chown, "Default Address Selection for Internet Protocol Version 6 (IPv6)", [RFC 6724](#), DOI 10.17487/RFC6724, September 2012, <<http://www.rfc-editor.org/info/rfc6724>>.

Authors' Addresses

Olle E. Johansson
Edvina AB
Runbovaegen 10
Sollentuna SE-192 48
SE

Email: oej@edvina.net

Gonzalo Salgueiro
Cisco Systems
7200-12 Kit Creek Road
Research Triangle Park, NC 27709
US

Email: gsalguei@cisco.com

Vijay Gurbani
Bell Labs, Alcatel-Lucent
1960 Lucent Lane
Rm 9C-533
Naperville, IL 60563
US

Email: vkg@bell-labs.com

Dale R. Worley (editor)
Ariadne Internet Services
738 Main St.
Waltham, MA 02451
US

Email: worley@ariadne.com

