

SIPPING Working Group	A. Johnston, Ed.	<a href="#">TOC</a>
Internet-Draft	Avaya	
Intended status: BCP	R. Sparks	
Expires: January 12, 2009	Estacado Systems	
	C. Cunningham	
	S. Donovan	
	Cisco Systems	
	K. Summers	
	Sonus	
	July 11, 2008	

## **Session Initiation Protocol Service Examples**

**draft-ietf-sipping-service-examples-15**

### **Status of this Memo**

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with Section 6 of BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on January 12, 2009.

### **Abstract**

This document gives examples of Session Initiation Protocol (SIP) services. This covers most features offered in so-called IP Centrex offerings from local exchange carriers and PBX (Private Branch Exchange) features. Most of the services shown in this document are implemented in the SIP User Agents, although some require the assistance of a SIP Proxy. Some require some extensions to SIP including the REFER, SUBSCRIBE, and NOTIFY methods and the Replaces and Join header fields. These features are not intended to be an exhaustive

---

set, but rather show implementations of common features likely to be implemented on SIP IP telephones in a business environment.

---

## Table of Contents

- [1. Overview](#)
- [2. Service Examples](#)
  - [2.1. Call Hold](#)
  - [2.2. Consultation Hold](#)
  - [2.3. Music On Hold](#)
  - [2.4. Transfer - Unattended](#)
  - [2.5. Transfer - Attended](#)
  - [2.6. Transfer - Instant Messaging](#)
  - [2.7. Call Forwarding Unconditional](#)
  - [2.8. Call Forwarding - Busy](#)
  - [2.9. Call Forwarding - No Answer](#)
  - [2.10. 3-way Conference - Third Party is Added](#)
  - [2.11. 3-way Conference - Third Party Joins](#)
  - [2.12. Find-Me](#)
  - [2.13. Call Management \(Incoming Call Screening\)](#)
  - [2.14. Call Management \(Outgoing Call Screening\)](#)
  - [2.15. Call Park](#)
  - [2.16. Call Pickup](#)
  - [2.17. Automatic Redial](#)
  - [2.18. Click to Dial](#)
- [3. Security Considerations](#)
- [4. IANA Considerations](#)
- [5. Acknowledgements](#)
- [6. References](#)
  - [6.1. Normative References](#)
  - [6.2. Informative References](#)
- [§ Authors' Addresses](#)
- [§ Intellectual Property and Copyright Statements](#)

---

## 1. Overview

[TOC](#)

This document provides example call flows detailing a SIP implementation of the following traditional telephony services:

Call Hold	Music on Hold
Unattended Transfer	Consultation Hold
Unconditional Call Forwarding	Attended Transfer
No Answer Call Forwarding	Busy Call Forwarding
3-way Call	Incoming Call Screening
Find-Me	Call Pickup
Call Park	Outgoing Call Screening
Automatic Redial	Click to Dial

Note that the Single Line Extension call flow has been removed from this document and will be covered in a separate document.

The call flows shown in this document were developed in the design of a SIP IP communications network. They represent an example set of so-called IP Centrex services or PBX services.

It is the hope of the authors that this document will be useful for SIP implementers, designers, and protocol researchers alike and will help further the goal of a standard implementation of [RFC 3261 \(Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M., and E. Schooler, "SIP: Session Initiation Protocol," June 2002.\)](#) [RFC3261] and some of its extensions.

These flows represent carefully checked and working group reviewed scenarios of SIP service examples as a companion to the specifications. These call flows are based on the current version 2.0 of SIP in [RFC 3261 \(Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M., and E. Schooler, "SIP: Session Initiation Protocol," June 2002.\)](#) [RFC3261] with SDP usage described in [RFC 3264 \(Rosenberg, J. and H. Schulzrinne, "An Offer/Answer Model with Session Description Protocol \(SDP\)," June 2002.\)](#) [RFC3264] Other RFCs also form part of the SIP standard and are used and referenced in these call flows.

The SIP specification and the other referenced documents are definitive as far as protocol issues are concerned. Also, these flows do not represent the only way to implement these services - other approaches such as [3pcc \(Third Party Call Control\) \(Rosenberg, J., Peterson, J., Schulzrinne, H., and G. Camarillo, "Best Current Practices for Third Party Call Control \(3pcc\) in the Session Initiation Protocol \(SIP\)," April 2004.\)](#) [RFC3725] or Back-to-Back User Agents (B2BUA) can be used. This specification does not preclude these or other approaches for implementing such services. The peer-to-peer design and principles of these service examples are described in the [Multiparty Framework document \(Mahy, R., Sparks, R., Rosenberg, J., Petrie, D., and A. Johnston, "A Call Control and Multi-party usage framework for the Session Initiation Protocol \(SIP\)," December 2009.\)](#)

[I-D.ietf-sipping-cc-framework].

These flows assume the functionality described in the [SIP Call Flow Examples document \(Johnston, A., Donovan, S., Sparks, R., Cunningham, C., and K. Summers, "Session Initiation Protocol \(SIP\) Basic Call Flow Examples," December 2003.\)](#) [RFC3665], which explores basic SIP

behavior. Some of the scenarios described herein make use of the SIP method extension [REFER \(Sparks, R., "The Session Initiation Protocol \(SIP\) Refer Method," April 2003.\)](#) [RFC3515] and the SIP header extension [Replaces \(Mahy, R., Biggs, B., and R. Dean, "The Session Initiation Protocol \(SIP\) "Replaces" Header," September 2004.\)](#) [RFC3891], and the SIP header extension [Join \(Mahy, R. and D. Petrie, "The Session Initiation Protocol \(SIP\) "Join" Header," October 2004.\)](#) [RFC3911]. The [SIP Events document \(Roach, A., "Session Initiation Protocol \(SIP\)-Specific Event Notification," June 2002.\)](#) [RFC3265] describes the use of SUBSCRIBE and NOTIFY while the [SIP Dialog Event Package \(Rosenberg, J., Schulzrinne, H., and R. Mahy, "An INVITE-Initiated Dialog Event Package for the Session Initiation Protocol \(SIP\)," November 2005.\)](#) [RFC4235] document describes the dialog event package. Some examples make use of the [GRUU \(Globally Routable User Agent URI\) \(Rosenberg, J., "Obtaining and Using Globally Routable User Agent \(UA\) URIs \(GRUU\) in the Session Initiation Protocol \(SIP\)," October 2007.\)](#) [I-D.ietf-sip-gruu] extension.

These flows were prepared assuming a network of proxies, registrars, and other SIP servers. The use of Secure SIP URIs (sips) is shown throughout this document, implying TLS transport on each hop with assumed certificate validation. However, other security approaches can be used. The use of Digest authentication is shown in some examples. The emphasis in these call flows is the SIP signaling exchange. As a result, only very simple SDP offer/answer exchanges are shown with audio media. These flows apply equally well for other media and multi-media sessions. For more advanced examples of SDP offer/answer exchanges, refer to [\[RFC4317\] \(Johnston, A. and R. Sparks, "Session Description Protocol \(SDP\) Offer/Answer Examples," December 2005.\).](#)

Each call flow is presented with a textual description of the scenario, a message flow diagram showing the messages exchanged between separate network elements, and the detailed contents of each message shown in the diagram.

### 1.1 Legend for Message Flows

Dashed lines (---) represent control messages that are mandatory to the call scenario. These control messages can be SIP signaling.

Double dashed lines (==) represent media paths between network elements.

Messages with parenthesis around name represent optional control messages.

Messages are identified in the Figures as F1, F2, etc. This references the message details in the table that follows the Figure.

Lines longer than 72 characters are handled using the <allOneLine> convention defined in Section 2.1 of [RFC 4475 \(Sparks, R., Hawrylyshen, A., Johnston, A., Rosenberg, J., and H. Schulzrinne, "Session Initiation Protocol \(SIP\) Torture Test Messages," May 2006.\)](#) [RFC4475].

Comments in the message details are shown in the following form:

```
/* Comments. */
```


## 2. Service Examples

---

[TOC](#)

[TOC](#)

## **2.1. Call Hold**



In this scenario, Alice calls Bob, then Bob places the call on hold. Bob then takes the call off hold, then Alice hangs up the call. Note that hold is unidirectional in nature. However, a UA that places the other party on hold will generally also stop sending media, resulting in no media exchange between the UAs. Older UAs may set the connection address to 0.0.0.0 when initiating hold. However, this behavior has been deprecated in favor of using the a=sendonly SDP attribute.

Also note the use of the rendering feature tag defined in RFC 4235  
[\[RFC4235\] \(Rosenberg, J., Schulzrinne, H., and R. Mahy, "An INVITE-Initiated Dialog Event Package for the Session Initiation Protocol \(SIP\), November 2005.\)](#) used in F10 and F11 to indicate in that Bob's UA is no longer rendering media to Bob, i.e. that Bob has placed the call on hold.

Message Details

F1 INVITE Alice -> Proxy 1

```
INVITE sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345601@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F2 INVITE Proxy 1 -> Bob

```
INVITE sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.1
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
Max-Forwards: 69
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345601@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
```

```
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F3 (100 Trying) Proxy 1 -> Alice

```
SIP/2.0 100 Trying
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345601@atlanta.example.com
CSeq: 1 INVITE
Content-Length: 0
```

F4 180 Ringing Bob -> Proxy 1

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.1
;received=192.0.2.54
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 12345601@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:bob@client.biloxi.example.com>
Content Length:0
```

F5 180 Ringing Proxy 1 -> Alice

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 12345601@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:bob@client.biloxi.example.com>
Content Length: 0
```

F6 200 OK Bob -> Proxy 1

SIP/2.0 200 OK  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749.1  
;received=192.0.2.54  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
Record-Route: <sips:ss1.example.com;lr>  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=314159  
Call-ID: 12345601@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:bob@client.biloxi.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...  
  
v=0  
o=bob 2890844527 2890844527 IN IP4 client.biloxi.example.com  
s=  
c=IN IP4 client.biloxi.example.com  
t=0 0  
m=audio 3456 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F7 200 OK Proxy 1 -> Alice

SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
Record-Route: <sips:ss1.example.com;lr>  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=314159  
Call-ID: 12345601@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:bob@client.biloxi.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...  
  
v=0  
o=bob 2890844527 2890844527 IN IP4 client.biloxi.example.com

```
s=
c=IN IP4 client.biloxi.example.com
t=0 0
m=audio 3456 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F8 ACK Alice -> Proxy 1

```
ACK sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf92
Route: <sips:ss1.example.com;lr>
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 12345601@atlanta.example.com
CSeq: 1 ACK
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Length: 0
```

F9 ACK Proxy 1 -> Bob

```
ACK sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK837492.1
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf92
;received=192.0.2.103
Max-Forwards: 69
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 12345601@atlanta.example.com
CSeq: 1 ACK
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Length: 0
```

```
/* Bob places Alice on hold. Note that the version is
incremented in the o= field of the SDP */
```

F10 INVITE Bob -> Proxy 1

```
INVITE sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds7
Route: <sips:ss1.example.com;lr>
```

Max-Forwards: 70  
From: Bob <sips:bob@biloxi.example.com>;tag=314159  
To: Alice <sips:alice@atlanta.example.com>;tag=1234567  
Call-ID: 12345601@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:bob@client.biloxi.example.com>;+sip.rendering="no"  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...

v=0  
o=bob 2890844527 2890844528 IN IP4 client.biloxi.example.com  
s=  
c=IN IP4 client.biloxi.example.com  
t=0 0  
m=audio 3456 RTP/AVP 0  
a=rtpmap:0 PCMU/8000  
a=sendonly

F11 INVITE Proxy 1 -> Alice

INVITE sips:alice@client.atlanta.example.com SIP/2.0  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749.1  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds7  
;received=192.0.2.105  
Record-Route: <sips:ss1.example.com;lr>  
Max-Forwards: 69  
From: Bob <sips:bob@biloxi.example.com>;tag=314159  
To: Alice <sips:alice@atlanta.example.com>;tag=1234567  
Call-ID: 12345601@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:bob@client.biloxi.example.com>;+sip.rendering="no"  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...

v=0  
o=bob 2890844527 2890844528 IN IP4 client.biloxi.example.com  
s=  
c=IN IP4 client.biloxi.example.com  
t=0 0  
m=audio 3456 RTP/AVP 0  
a=rtpmap:0 PCMU/8000  
a=sendonly

```
/* Alice replies to hold */

F12 200 OK Alice -> Proxy 1

SIP/2.0 200 OK
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.1
;received=192.0.2.54
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds7
;received=192.0.2.105
Record-Route: <sips:ss1.example.com;lr>
From: Bob <sips:bob@biloxi.example.com>;tag=314159
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345601@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844527 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
a=recvonly
```

```
F13 200 OK Proxy 1 -> Bob

SIP/2.0 200 OK
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds7
;received=192.0.2.105
Record-Route: <sips:ss1.example.com;lr>
From: Bob <sips:bob@biloxi.example.com>;tag=314159
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345601@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...
```

```
v=0
o=alice 2890844526 2890844527 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
a=recvonly
```

F14 ACK Bob -> Proxy 1

```
ACK sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds72
Route: <sips:ss1.example.com;lr>
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=314159
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345601@atlanta.example.com
CSeq: 1 ACK
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Length: 0
```

F15 ACK Proxy 1 -> Alice

```
ACK sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.1
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds72
;received=192.0.2.105
Max-Forwards: 69
From: Bob <sips:bob@biloxi.example.com>;tag=314159
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345601@atlanta.example.com
CSeq: 1 ACK
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Length: 0
```

/\* Bob takes the call off hold \*/

F16 INVITE Bob -> Proxy 1

```
INVITE sips:alice@client.atlanta.example.com SIP/2.0
```

Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds73  
Route: <sips:ss1.example.com;lr>  
Max-Forwards: 70  
From: Bob <sips:bob@biloxi.example.com>;tag=314159  
To: Alice <sips:alice@atlanta.example.com>;tag=1234567  
Call-ID: 12345601@atlanta.example.com  
CSeq: 2 INVITE  
Contact: <sips:bob@client.biloxi.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...  
  
v=0  
o=bob 2890844527 2890844529 IN IP4 client.biloxi.example.com  
s=  
c=IN IP4 client.biloxi.example.com  
t=0 0  
m=audio 3456 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F17 INVITE Proxy 1 -> Alice  
  
INVITE sips:alice@client.atlanta.example.com SIP/2.0  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK837493.1  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds73  
;received=192.0.2.105  
Record-Route: <sips:ss1.example.com;lr>  
Max-Forwards: 69  
From: Bob <sips:bob@biloxi.example.com>;tag=314159  
To: Alice <sips:alice@atlanta.example.com>;tag=1234567  
Call-ID: 12345601@atlanta.example.com  
CSeq: 2 INVITE  
Contact: <sips:bob@client.biloxi.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...  
  
v=0  
o=bob 2890844527 2890844529 IN IP4 client.biloxi.example.com  
s=  
c=IN IP4 client.biloxi.example.com  
t=0 0  
m=audio 3456 RTP/AVP 0

a=rtpmap:0 PCMU/8000

F18 200 OK Alice -> Proxy 1

SIP/2.0 200 OK

Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK837493.1  
;received=192.0.2.54  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds73  
;received=192.0.2.105  
Record-Route: <sips:ss1.example.com;lr>  
From: Bob <sips:bob@biloxi.example.com>;tag=314159  
To: Alice <sips:alice@atlanta.example.com>;tag=1234567  
Call-ID: 12345601@atlanta.example.com  
CSeq: 2 INVITE  
Contact: <sips:alice@client.atlanta.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...

v=0

o=alice 2890844526 2890844528 IN IP4 client.atlanta.example.com  
s=  
c=IN IP4 client.atlanta.example.com  
t=0 0  
m=audio 49170 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F19 200 OK Proxy 1 -> Bob

SIP/2.0 200 OK

Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds73  
;received=192.0.2.105  
Record-Route: <sips:ss1.example.com;lr>  
From: Bob <sips:bob@biloxi.example.com>;tag=314159  
To: Alice <sips:alice@atlanta.example.com>;tag=1234567  
Call-ID: 12345601@atlanta.example.com  
CSeq: 2 INVITE  
Contact: <sips:alice@client.atlanta.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...

v=0

```
o=alice 2890844526 2890844528 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F20 ACK Bob -> Proxy 1

```
ACK sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds74
Route: <sips:ss1.example.com;lr>
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=314159
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345601@atlanta.example.com
CSeq: 2 ACK
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Length: 0
```

F21 ACK Proxy 1 -> Alice

```
ACK sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK837494.1
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds74
;received=192.0.2.105
Max-Forwards: 69
From: Bob <sips:bob@biloxi.example.com>;tag=314159
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345601@atlanta.example.com
CSeq: 2 ACK
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Length: 0
```

/\* RTP Media stream re-established. Alice disconnects. \*/

F22 BYE Alice -> Proxy 1

```
BYE sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf97
Route: <sips:ss1.example.com;lr>
```

Max-Forwards: 70  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:biloxi.example.com>;tag=314159  
Call-ID: 12345601@atlanta.example.com  
CSeq: 2 BYE  
Content-Length: 0

F23 BYE Proxy 1 -> Bob

BYE sips:bob@client.biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK837497.1  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf97  
;received=192.0.2.103  
Max-Forwards: 69  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:biloxi.example.com>;tag=314159  
Call-ID: 12345601@atlanta.example.com  
CSeq: 2 BYE  
Content-Length: 0

F24 200 OK Bob -> Proxy 1

SIP/2.0 200 OK  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK837497.1  
;received=192.0.2.54  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf97  
;received=192.0.2.103  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:biloxi.example.com>;tag=314159  
Call-ID: 12345601@atlanta.example.com  
CSeq: 2 BYE  
Content-Length: 0

F25 200 OK Proxy 1 -> Alice


SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf97  
;received=192.0.2.103  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:biloxi.example.com>;tag=314159  
Call-ID: 12345601@atlanta.example.com


CSeq: 2 BYE  
Content-Length: 0

---

[TOC](#)

## **2.2. Consultation Hold**





In this scenario, Alice calls Bob. Bob places call on hold. Bob calls Carol. Bob then disconnects with Carol, then takes the call with Alice off hold. The call ends when Alice hangs up.

Also note the use of the rendering feature tag defined in RFC 4235  
[\[RFC4235\] \(Rosenberg, J., Schulzrinne, H., and R. Mahy, "An INVITE-Initiated Dialog Event Package for the Session Initiation Protocol \(SIP\)," November 2005.\)](#) used in F10 to indicate in that Bob's UA is no longer rendering media to Bob, i.e. that Bob has placed the call on hold.

Message Details

F1 INVITE Alice -> Proxy 1

```
INVITE sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F2 INVITE Proxy 1 -> Bob

```
INVITE sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.1
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
Max-Forwards: 69
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
```

```
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F3(100 Trying) Proxy 1 -> Alice

```
SIP/2.0 100 Trying
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Content-Length: 0
```

F4 180 Ringing Bob -> Proxy 1

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.1
;received=192.0.2.54
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:bob@client.biloxi.example.com>
Content Length:0
```

F5 180 Ringing Proxy 1 -> Alice

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:bob@client.biloxi.example.com>
Content Length: 0
```

F6 200 OK Bob -> Proxy 1

SIP/2.0 200 OK  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749.1  
;received=192.0.2.54  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
Record-Route: <sips:ss1.example.com;lr>  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=314159  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:bob@client.biloxi.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...  
  
v=0  
o=bob 2890844527 2890844527 IN IP4 client.biloxi.example.com  
s=  
c=IN IP4 client.biloxi.example.com  
t=0 0  
m=audio 3456 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F7 200 OK Proxy 1 -> Alice

SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
Record-Route: <sips:ss1.example.com;lr>  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=314159  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:bob@client.biloxi.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...  
  
v=0  
o=bob 2890844527 2890844527 IN IP4 client.biloxi.example.com

```
s=
c=IN IP4 client.biloxi.example.com
t=0 0
m=audio 3456 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F8 ACK Alice -> Proxy 1

```
ACK sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf45
Route: <sips:ss1.example.com;lr>
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 12345600@atlanta.example.com
CSeq: 1 ACK
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Length: 0
```

F9 ACK Proxy 1 -> Bob

```
ACK sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK837494.1
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf45
;received=192.0.2.103
Max-Forwards: 69
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 12345600@atlanta.example.com
CSeq: 1 ACK
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Length: 0
```

/\* Bob places Alice on hold. \*/

F10 INVITE Bob -> Proxy 1

```
INVITE sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds7
Route: <sips:ss1.example.com;lr>
Max-Forwards: 70
```

From: Bob <sips:bob@biloxi.example.com>;tag=314159  
To: Alice <sips:alice@atlanta.example.com>;tag=1234567  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:bob@client.biloxi.example.com>;+sip.rendering="no"  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...

v=0  
o=bob 2890844527 2890844528 IN IP4 client.biloxi.example.com  
s=  
c=IN IP4 client.biloxi.example.com  
t=0 0  
m=audio 3456 RTP/AVP 0  
a=rtpmap:0 PCMU/8000  
a=sendonly

F11 INVITE Proxy 1 -> Alice

INVITE sips:alice@client.atlanta.example.com SIP/2.0  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK837497.1  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds7  
;received=192.0.2.105  
Record-Route: <sips:ss1.example.com;lr>  
Max-Forwards: 69  
From: Bob <sips:bob@biloxi.example.com>;tag=314159  
To: Alice <sips:alice@atlanta.example.com>;tag=1234567  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:bob@client.biloxi.example.com>;+sip.rendering="no"  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...

v=0  
o=bob 2890844527 2890844528 IN IP4 client.biloxi.example.com  
s=  
c=IN IP4 client.biloxi.example.com  
t=0 0  
m=audio 3456 RTP/AVP 0  
a=rtpmap:0 PCMU/8000  
a=sendonly

F12 200 OK Alice -> Proxy 1

SIP/2.0 200 OK  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK837497.1  
;received=192.0.2.54  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds7  
;received=192.0.2.105  
Record-Route: <sips:ss1.example.com;lr>  
From: Bob <sips:bob@biloxi.example.com>;tag=314159  
To: Alice <sips:alice@atlanta.example.com>;tag=1234567  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:alice@client.atlanta.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...  
  
v=0  
o=alice 2890844526 2890844527 IN IP4 client.atlanta.example.com  
s=  
c=IN IP4 client.atlanta.example.com  
t=0 0  
m=audio 49170 RTP/AVP 0  
a=rtpmap:0 PCMU/8000  
a=recvonly

F13 200 OK Proxy 1 -> Bob

SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds7  
;received=192.0.2.105  
Record-Route: <sips:ss1.example.com;lr>  
From: Bob <sips:bob@biloxi.example.com>;tag=314159  
To: Alice <sips:alice@atlanta.example.com>;tag=1234567  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:alice@client.atlanta.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...  
  
v=0

```
o=alice 2890844526 2890844527 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
a=recvonly
```

F14 ACK Bob -> Proxy 1

```
ACK sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashdsg
Route: <sips:ss1.example.com;lr>
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=314159
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345600@atlanta.example.com
CSeq: 1 ACK
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Length: 0
```

F15 ACK Proxy 1 -> Alice

```
ACK sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK8374.1
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashdsg
;received=192.0.2.105
Max-Forwards: 69
From: Bob <sips:bob@biloxi.example.com>;tag=314159
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345600@atlanta.example.com
CSeq: 1 ACK
Content-Length: 0
```

F16 INVITE Bob -> Proxy 1

```
INVITE sips:carol@chicago.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds22
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>
Call-ID: 9876543210@biloxi.example.com
```

CSeq: 1 INVITE  
Contact: <sips:bob@client.biloxi.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...

v=0  
o=bob 2890844834 2890844834 IN IP4 client.biloxi.example.com  
s=  
c=IN IP4 client.biloxi.example.com  
t=0 0  
m=audio 50170 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F17 INVITE Proxy 1 -> Carol

INVITE sips:carol@client.chicago.example.com SIP/2.0  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749a.1  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds22  
;received=192.0.2.105  
Record-Route: <sips:ss1.example.com;lr>  
Max-Forwards: 69  
From: Bob <sips:bob@biloxi.example.com>;tag=8675309  
To: Carol <sips:carol@chicago.example.com>  
Call-ID: 9876543210@biloxi.example.com  
CSeq: 1 INVITE  
Contact: <sips:bob@client.biloxi.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...

v=0  
o=bob 2890844834 2890844834 IN IP4 client.biloxi.example.com  
s=  
c=IN IP4 client.biloxi.example.com  
t=0 0  
m=audio 50170 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F18 (100 Trying) Proxy 1 -> Bob

SIP/2.0 100 Trying  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds22

;received=192.0.2.105  
From: Bob <sips:bob@biloxi.example.com>;tag=8675309  
To: Carol <sips:carol@chicago.example.com>  
Call-ID: 9876543210@biloxi.example.com  
CSeq: 1 INVITE  
Content-Length: 0

F19 180 Ringing Carol -> Proxy 1

SIP/2.0 180 Ringing  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749a.1  
;received=192.0.2.54  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds22  
;received=192.0.2.105  
Record-Route: <sips:ss1.example.com;lr>  
From: Bob <sips:bob@biloxi.example.com>;tag=8675309  
To: Carol <sips:carol@chicago.example.com>;tag=456654  
Call-ID: 9876543210@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:carol@client.chicago.example.com>  
Content Length:0

F20 180 Ringing Proxy 1 -> Bob

SIP/2.0 180 Ringing  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds22  
;received=client.chicago.example.com  
Record-Route: <sips:ss1.example.com;lr>  
From: Bob <sips:bob@biloxi.example.com>;tag=8675309  
To: Carol <sips:carol@chicago.example.com>;tag=456654  
Call-ID: 9876543210@biloxi.example.com  
CSeq: 1 INVITE  
Contact: <sips:carol@client.chicago.example.com>  
Content Length: 0

F21 200 OK Carol -> Proxy 1

SIP/2.0 200 OK  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749a.1  
;received=192.0.2.54  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds22  
;received=192.0.2.105

Record-Route: <sips:ss1.example.com;lr>  
From: Bob <sips:bob@biloxi.example.com>;tag=8675309  
To: Carol <sips:carol@chicago.example.com>;tag=456654  
Call-ID: 9876543210@biloxi.example.com  
CSeq: 1 INVITE  
Contact: <sips:carol@client.chicago.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...  
  
v=0  
o=carol 2890844922 2890844922 IN IP4 client.chicago.example.com  
s=  
c=IN IP4 client.chicago.example.com  
t=0 0  
m=audio 3456 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F22 200 OK Proxy 1 -> Bob

SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds22  
;received=192.0.2.105  
Record-Route: <sips:ss1.example.com;lr>  
From: Bob <sips:bob@biloxi.example.com>;tag=8675309  
To: Carol <sips:carol@chicago.example.com>;tag=456654  
Call-ID: 9876543210@biloxi.example.com  
CSeq: 1 INVITE  
Contact: <sips:carol@client.chicago.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...  
  
v=0  
o=carol 2890844922 2890844922 IN IP4 client.chicago.example.com  
s=  
c=IN IP4 client.chicago.example.com  
t=0 0  
m=audio 3456 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F23 ACK Bob -> Proxy 1

ACK sips:carol@client.chicago.example.com SIP/2.0  
Via: SIP/2.0/TLS client.biloxi.example.com:5061

```
;branch=z9hG4bKnashds24
Route: <sips:ss1.example.com;lr>
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>;tag=456654
Call-ID: 9876543210@biloxi.example.com
CSeq: 1 ACK
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Length: 0
```

F24 ACK Proxy 1 -> Carol

```
ACK sips:carol@client.chicago.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749b.1
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds24
;received=192.0.2.105
Max-Forwards: 69
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>;tag=456654
Call-ID: 9876543210@biloxi.example.com
CSeq: 1 ACK
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Length: 0
```

F25 BYE Bob -> Proxy 1

```
BYE sips:carol@client.chicago.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds7j
Route: <sips:ss1.example.com;lr>
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>;tag=456654
Call-ID: 9876543210@biloxi.example.com
CSeq: 2 BYE
Content-Length: 0
```

F26 BYE Proxy 1 -> Carol

```
BYE sips:carol@client.chicago.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749k.1
Via: SIP/2.0/TLS client.biloxi.example.com:5061
```

```
;branch=z9hG4bKnashds7j
;received=192.0.2.105
Max-Forwards: 69
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>;tag=456654
Call-ID: 9876543210@biloxi.example.com
CSeq: 2 BYE
Content-Length: 0
```

F27 200 OK Carol -> Proxy 1

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749k.1
;received=192.0.2.54
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds7j
;received=192.0.2.105
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>;tag=456654
Call-ID: 9876543210@biloxi.example.com
CSeq: 2 BYE
Content-Length: 0
```

F28 200 OK Proxy 1 -> Bob

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds7j
;received=192.0.2.105
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>;tag=456654
Call-ID: 9876543210@biloxi.example.com
CSeq: 2 BYE
Content-Length: 0
```

/\* Bob takes the call off hold \*/

F29 INVITE Bob -> Proxy 1

```
INVITE sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds7b
Route: <sips:ss1.example.com;lr>
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=314159
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
```

```
Call-ID: 12345600@atlanta.example.com
CSeq: 2 INVITE
Contact: <sips:bob@client.biloxi.example.com>
Content-Type: application/sdp
Content-Length: ...

v=0
o=bob 2890844527 2890844529 IN IP4 client.biloxi.example.com
s=
c=IN IP4 client.biloxi.example.com
t=0 0
m=audio 3456 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F30 INVITE Proxy 1 -> Alice

```
INVITE sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749q.1
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds7b
;received=192.0.2.105
Record-Route: <sips:ss1.example.com;lr>
Max-Forwards: 69
From: Bob <sips:bob@biloxi.example.com>;tag=314159
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345600@atlanta.example.com
CSeq: 2 INVITE
Contact: <sips:bob@client.biloxi.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...
```

```
v=0
o=bob 2890844527 2890844529 IN IP4 client.biloxi.example.com
s=
c=IN IP4 client.biloxi.example.com
t=0 0
m=audio 3456 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F31 200 OK Alice -> Proxy 1

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749q.1
;received=192.0.2.54
```

Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds7b  
;received=192.0.2.105  
Record-Route: <sips:ss1.example.com;lr>  
From: Bob <sips:bob@biloxi.example.com>;tag=314159  
To: Alice <sips:alice@atlanta.example.com>;tag=1234567  
Call-ID: 12345600@atlanta.example.com  
CSeq: 2 INVITE  
Contact: <sips:alice@client.atlanta.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...  
  
v=0  
o=alice 2890844526 2890844528 IN IP4 client.atlanta.example.com  
s=  
c=IN IP4 client.atlanta.example.com  
t=0 0  
m=audio 49170 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F32 200 OK Proxy 1 -> Bob

SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds7b  
;received=192.0.2.105  
Record-Route: <sips:ss1.example.com;lr>  
From: Bob <sips:bob@biloxi.example.com>;tag=314159  
To: Alice <sips:alice@atlanta.example.com>;tag=1234567  
Call-ID: 12345600@atlanta.example.com  
CSeq: 2 INVITE  
Contact: <sips:alice@client.atlanta.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...  
  
v=0  
o=alice 2890844526 2890844528 IN IP4 client.atlanta.example.com  
s=  
c=IN IP4 client.atlanta.example.com  
t=0 0  
m=audio 49170 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F33 ACK Bob -> Proxy 1

ACK sips:alice@client.atlanta.example.com SIP/2.0  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds7d7  
Route: <sips:ss1.example.com;lr>  
Max-Forwards: 70  
From: Bob <sips:bob@biloxi.example.com>;tag=314159  
To: Alice <sips:alice@atlanta.example.com>;tag=1234567  
Call-ID: 12345600@atlanta.example.com  
CSeq: 2 ACK  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Length: 0

F34 ACK Proxy 1 -> Alice

ACK sips:alice@client.atlanta.example.com SIP/2.0  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK8374.1  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds7d7  
;received=192.0.2.105  
Max-Forwards: 69  
From: Bob <sips:bob@biloxi.example.com>;tag=314159  
To: Alice <sips:alice@atlanta.example.com>;tag=1234567  
Call-ID: 12345600@atlanta.example.com  
CSeq: 2 ACK  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Length: 0

F35 BYE Alice -> Proxy 1

BYE sips:bob@client.biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf10  
Route: <sips:ss1.example.com;lr>  
Max-Forwards: 70  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=314159  
Call-ID: 12345600@atlanta.example.com  
CSeq: 2 BYE  
Content-Length: 0

F36 BYE Proxy 1 -> Bob

```
BYE sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK8379.1
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf10
;received=192.0.2.103
Max-Forwards: 69
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 12345600@atlanta.example.com
CSeq: 2 BYE
Content-Length: 0
```


F37 200 OK Bob -> Proxy 1


```
SIP/2.0 200 OK
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK8379.1
;received=192.0.2.54
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf10
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 12345600@atlanta.example.com
CSeq: 2 BYE
Content-Length: 0
```

F38 200 OK Proxy 1 -> Alice

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf10
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 12345600@atlanta.example.com
CSeq: 2 BYE
Content-Length: 0
```

### **2.3. Music On Hold**





In this flow, Bob places Alice on hold with music. This is performed by Bob sending a REFER to a Music Server which sends an INVITE with Replaces to Alice. The Music Server then sends RTP music to Alice. Bob picks the call up from hold by sending an INVITE with Replaces to Alice.

Note the use of the rendering feature tag defined in RFC 4235 [\[RFC4235\]](#) ([Rosenberg, J., Schulzrinne, H., and R. Mahy, "An INVITE-Initiated Dialog Event Package for the Session Initiation Protocol \(SIP\)," November 2005.](#)) used in F5 to indicate in that Bob's UA is no longer rendering media to Bob, i.e. that Bob has placed the call on hold. Feature tags are also used in F12 with the automaton (defined in RFC 3840 [\[RFC3840\]](#) ([Rosenberg, J., Schulzrinne, H., and P. Kyzivat, "Indicating User Agent Capabilities in the Session Initiation Protocol \(SIP\)," August 2004.](#))) and byeless feature tags (defined in RFC 4235 [\[RFC4235\]](#) ([Rosenberg, J., Schulzrinne, H., and R. Mahy, "An INVITE-Initiated Dialog Event Package for the Session Initiation Protocol \(SIP\)," November 2005.](#))) to describe the capabilities of the Music Server.

Should Alice not wish to receive music on hold, her UA could refuse F12 and she will remain on hold with Bob, but in silence.

#### Message Details

F1 INVITE Alice -> Bob

```
INVITE sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:a8342043f@atlanta.example.com;gr>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces, gruu
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F2 180 Ringing Bob -> Alice

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=23431
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:bob@client.biloxi.example.com>
Content-Length: 0
```

F3 200 OK Bob -> Alice

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=23431
```

```
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:bob@client.biloxi.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...

v=0
o=bob 2890844527 2890844527 IN IP4 client.biloxi.example.com
s=
c=IN IP4 client.biloxi.example.com
t=0 0
m=audio 3456 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F4 ACK Alice -> Bob

```
ACK sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bfd
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=23431
Call-ID: 12345600@atlanta.example.com
CSeq: 1 ACK
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Length: 0
```

/\* Bob places Alice on hold \*/

F5 INVITE Bob -> Alice

```
INVITE sips:a8342043f@atlanta.example.com;gr SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bK874bk
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
From: Bob <sips:bob@biloxi.example.com>;tag=23431
Call-ID: 12345600@atlanta.example.com
CSeq: 712 INVITE
Contact: <sips:bob@client.biloxi.example.com>;+sip.rendering="no"
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...
```

v=0

```
o=bob 2890844527 2890844528 IN IP4 client.biloxi.example.com
s=
c=IN IP4 client.biloxi.example.com
t=0 0
m=audio 3456 RTP/AVP 0
a=rtpmap:0 PCMU/8000
a=sendonly
```

F6 200 OK Alice -> Bob

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bK874bk
;received=192.0.2.105
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
From: Bob <sips:bob@biloxi.example.com>;tag=23431
Call-ID: 12345600@atlanta.example.com
CSeq: 712 INVITE
Contact: <sips:a8342043f@atlanta.example.com;gr>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces, gruu
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844527 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
a=recvonly
```

F7 ACK Bob -> Alice

```
ACK sips:a8342043f@atlanta.example.com;gr SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKq874b
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
From: Bob <sips:bob@biloxi.example.com>;tag=23431
Call-ID: 12345600@atlanta.example.com
CSeq: 712 ACK
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Length: 0
```

```
/* Bob REFERs Music Server to establish session with Alice
```

```
which replaces the established session between
Alice and Bob. */
```

F8 REFER Bob -> Music Server

```
REFER sips:music@server.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds9
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=02134
To: Music Server <sips:music@server.example.com>
Call-ID: 4802029847@biloxi.example.com
CSeq: 1 REFER
<allOneLine>
Refer-To: <sips:a8342043f@atlanta.example.com;gr?Replaces=
12345600%40atlanta.example.com%3Bfrom-tag%3D23431
%3Bto-tag%3D1234567&Require=replaces>
</allOneLine>
Referred-By: <sips:bob@biloxi.example.com>
Contact: <sips:bob@client.biloxi.example.com>
Content-Length: 0
```

F9 202 Accepted Music Server -> Bob

```
SIP/2.0 202 Accepted
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds9
;received=192.0.2.105
From: Bob <sips:bob@biloxi.example.com>;tag=02134
To: Music Server <sips:music@server.example.com>;tag=56323
Call-ID: 4802029847@biloxi.example.com
Contact: <sips:music@server.example.com>
CSeq: 1 REFER
Content-Length: 0
```

F10 NOTIFY Music Server -> Bob

```
NOTIFY sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS server.example.com:5061
;branch=z9hG4bK74bT6
To: Bob <sips:bob@biloxi.example.com>;tag=02134
Max-Forwards: 70
From: Music Server <sips:music@server.example.com>;tag=56323
Call-ID: 4802029847@biloxi.example.com
CSeq: 1 NOTIFY
Event: refer
Subscription-State: active;expires=60
Contact: <sips:music@server.example.com>
```

```
Content-Type: message/sipfrag
Content-Length: ...
```

```
SIP/2.0 100 Trying
```

```
F11 200 OK Bob -> Music Server
```

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS server.example.com:5061
;branch=z9hG4bK74bT6
;received=192.0.2.103
To: Bob <sips:bob@biloxi.example.com>;tag=02134
From: Music Server <sips:music@server.example.com>;tag=56323
Call-ID: 4802029847@biloxi.example.com
CSeq: 1 NOTIFY
Content-Length: 0
```

```
/* Music Server places call to Alice to replace session
   between Alice and Bob. */
```

```
F12 INVITE Music Server -> Alice
```

```
INVITE sips:a8342043f@atlanta.example.com;gr SIP/2.0
Via: SIP/2.0/TLS server.example.com:5061
;branch=z9hG4bK74rf
Max-Forwards: 70
From: <sips:music@server.example.com>;tag=0111
To: <sips:a8342043f@atlanta.example.com;gr>
Call-ID: a5-75-34-12-76@server.example.com
CSeq: 1 INVITE
Referred-By: <sips:bob@biloxi.example.com>
Contact: <sips:music@server.example.com>;automaton
:+sip.byeless;+sip.rendering="no"
Require: replaces
Replaces: 12345600@atlanta.example.com
;from-tag=23431;to-tag=1234567
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, SUBSCRIBE, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...
```

```
v=0
o=MusicServer 2890844576 2890844576 IN IP4 server.example.com
s=
c=IN IP4 server.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

a=sendonly

F13 200 OK Alice -> Music Server

SIP/2.0 200 OK  
Via: SIP/2.0/TLS server.example.com:5061  
;branch=z9hG4bK74rf  
;received=192.0.2.103  
From: <sips:music@server.example.com>;tag=0111  
To: <sips:a8342043f@atlanta.example.com;gr>;tag=098594  
Call-ID: a5-75-34-12-76@server.example.com  
CSeq: 1 INVITE  
Contact: <sips:a8342043f@atlanta.example.com;gr>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, SUBSCRIBE, NOTIFY  
Supported: replaces, gruu  
Content-Type: application/sdp  
Content-Length: ...

v=0  
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com  
S=  
c=IN IP4 client.atlanta.example.com  
t=0 0  
m=audio 49170 RTP/AVP 0  
a=rtpmap:0 PCMU/8000  
a=recvonly

F14 ACK Music Server -> Alice

ACK sips:a8342043f@atlanta.example.com;gr SIP/2.0  
Via: SIP/2.0/TLS server.example.com:5061  
;branch=z9hG4bK7rff  
Max-Forwards: 70  
From: <sips:music@server.example.com>;tag=0111  
To: <sips:a8342043f@atlanta.example.com;gr>;tag=098594  
Call-ID: a5-75-34-12-76@server.example.com  
CSeq: 1 ACK  
Content-Length: 0

F15 BYE Alice -> Bob

BYE sips:bob@client.biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bKnashds7  
Max-Forwards: 70  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=23431

```
Call-ID: 12345600@atlanta.example.com
CSeq: 2 BYE
Content-Length: 0
```

F16 200 OK Bob -> Alice

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bKnashds7
;received=192.0.2.105
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=23431
Call-ID: 12345600@atlanta.example.com
CSeq: 2 BYE
Content-Length: 0
```

```
/* Music Server reports success back to Bob by returning
   a 200 OK response. Bob obtains the dialog identifiers
   from the headers included in the response. */
```

F17 NOTIFY Music Server -> Bob

```
NOTIFY sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS server.example.com:5061
;branch=z9hG4bK74bf9
To: Bob <sips:bob@biloxi.example.com>;tag=02134
Max-Forwards: 70
From: Music Server <sips:music@server.example.com>;tag=56323
Call-ID: 4802029847@biloxi.example.com
CSeq: 2 NOTIFY
Event: refer
Subscription-State: terminated;reason=noresource
Contact: <sips:music@server.example.com>
Content-Type: message/sipfrag
Content-Length: ...
```

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS server.example.com:5061
;branch=z9hG4bK74rf
;received=192.0.2.103
From: <sips:music@server.example.com>;tag=0111
To: <sips:a8342043f@atlanta.example.com;gr>;tag=098594
Call-ID: a5-75-34-12-76@server.example.com
CSeq: 1 INVITE
Contact: <sips:a8342043f@atlanta.example.com;gr>
```

F18 200 OK Bob -> Music Server

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS server.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
To: Bob <sips:bob@biloxi.example.com>;tag=02134
From: Music Server <sips:music@server.example.com>;tag=56323
Call-ID: 4802029847@biloxi.example.com
CSeq: 2 NOTIFY
Content-Length: 0
```

```
/* Alice is now parked at the Music Server */

/* Bob picks up the call by sending an INVITE to Alice who
   replaces the existing session with the Music Server. */
```

F19 INVITE Bob -> Alice

```
INVITE sips:a8342043f@atlanta.example.com;gr SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bK74bf9
From: Bob <sips:bob@biloxi.example.com>;tag=4i323pr
To: Alice <sips:a8342043f@atlanta.example.com;gr>
Call-ID: uioewrjk2k2were
CSeq: 42121 INVITE
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER,
SUBSCRIBE, NOTIFY
Replaces: a5-75-34-12-76@server.example.com
;to-tag=098594;from-tag=0111
Contact: <sips:bob@client.biloxi.example.com>
Supported: replaces
Content-Type: application/sdp
Content-Length: ...
```

```
v=0
o=bob 2890844631 2890844631 IN IP4 client.biloxi.example.com
s=
c=IN IP4 client.biloxi.example.com
t=0 0
m=audio 3458 RTP/AVP 0
a=rtpmap:0 PCMU/8000
a=sendrecv
```

F20 200 OK Alice -> Bob

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.biloxi.example.com:5061
```

```
;branch=z9hG4bK74bf9
;received=192.0.2.105
From: Bob <sips:bob@biloxi.example.com>;tag=4i323pr
To: Alice <sips:a8342043f@atlanta.example.com;gr>;tag=6654323
Call-ID: uioewrjk2k2were
CSeq: 42121 INVITE
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER,
SUBSCRIBE, NOTIFY
Contact: <sips:alice@client.atlanta.example.com>
Supported: replaces
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844576 2890844576 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
a=sendrecv
```

F21 200 ACK Bob -> Alice

```
ACK sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKj974bf9
From: Bob <sips:bob@biloxi.example.com>;tag=4i323pr
To: Alice <sips:a8342043f@atlanta.example.com;gr>;tag=6654323
Call-ID: uioewrjk2k2were
CSeq: 42121 ACK
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER,
SUBSCRIBE, NOTIFY
Supported: replaces
Content-Length: 0
```

F22 BYE Alice -> Music Server

```
BYE sips:music@server.example.com SIP/2.0
Max-Forwards: 70
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74rf
To: <sips:music@server.example.com>;tag=0111
From: <sips:a8342043f@atlanta.example.com;gr>;tag=098594
Call-ID: a5-75-34-12-76@server.example.com
CSeq: 15 BYE
Content-Length: 0
```

F23 200 OK Music Server -> Alice


SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74rf  
;received=192.0.2.103  
To: <sips:music@server.example.com>;tag=0111  
From: <sips:a8342043f@atlanta.example.com;gr>;tag=098594  
Call-ID: a5-75-34-12-76@server.example.com  
CSeq: 15 BYE  
Content-Length: 0

/\* Normal media session between Alice and Bob is resumed \*/

---

[TOC](#)

## 2.4. Transfer - Unattended



In this scenario, Bob calls Alice. Alice then transfers Bob to Carol, then Alice disconnects with Bob. Bob establishes the session to Carol then reports the success back to Alice in the NOTIFY in F15. If the

transfer fails, Bob can send a new INVITE back to Alice to re-establish the session.

Despite the BYE sent by Alice in F9, the dialog between Alice and Bob still exists until the subscription created by the REFER has terminated (either due to a NOTIFY containing a Subscription-State: terminated;reason=noresource header field, as in F15, or a 481 response to a NOTIFY).

For more about call transfer see the [transfer \(Sparks, R. and A. Johnston, "Session Initiation Protocol Call Control - Transfer," March 2009.\)](#) [I-D.ietf-sipping-cc-transfer] document.

Message Details

F1 INVITE Bob -> Alice

```
INVITE sips:alice@atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds7
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=314159
To: Alice <sips:alice@atlanta.example.com>
Call-ID: 12345601@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:bob@client.biloxi.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...

v=0
o=bob 2890844527 2890844527 IN IP4 client.biloxi.example.com
s=
c=IN IP4 client.biloxi.example.com
t=0 0
m=audio 3456 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F2 180 Ringing Alice -> Bob

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds7
;received=192.0.2.113
From: Bob <sips:bob@biloxi.example.com>;tag=314159
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345601@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Content-Length: 0
```

F3 200 OK Alice -> Bob

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds7
;received=192.0.2.113
From: Bob <sips:bob@biloxi.example.com>;tag=314159
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345601@atlanta.example.com
```

```
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F4 ACK Bob -> Alice

```
ACK sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds2
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=314159
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345601@atlanta.example.com
CSeq: 1 ACK
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Length: 0
```

/\* Session is established between Alice and Bob. \*/

/\* Alice performs unattended transfer of Bob to Carol \*/

F5 REFER Alice -> Bob

```
REFER sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds8
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 12345601@atlanta.example.com
CSeq: 101 REFER
Refer-To: <sips:carol@chicago.example.com>
Referred-By: <alice@atlanta.example.com>
Contact: <sips:alice@client.atlanta.example.com>
Content-Length: 0
```

F6 202 Accepted Bob -> Alice

SIP/2.0 202 Accepted  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds8  
;received=192.0.2.105  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=314159  
Call-ID: 12345601@atlanta.example.com  
Contact: <sips:bob@client.biloxi.example.com>  
CSeq: 101 REFER  
Content-Length: 0

F7 NOTIFY Bob -> Alice

NOTIFY sips:alice@client.atlanta.example.com SIP/2.0  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds32  
Max-Forwards: 70  
From: Bob <sips:bob@biloxi.example.com>;tag=314159  
To: Alice <sips:alice@atlanta.example.com>;tag=1234567  
Call-ID: 12345601@atlanta.example.com  
CSeq: 2 NOTIFY  
Event: refer  
Subscription-State: active;expires=60  
Contact: <sips:bob@client.biloxi.example.com>  
Content-Type: message/sipfrag  
Content-Length: ...

SIP/2.0 100 Trying

F8 200 OK Alice -> Bob

SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds32  
;received=192.0.2.113  
From: Bob <sips:bob@biloxi.example.com>;tag=314159  
To: Alice <sips:alice@atlanta.example.com>;tag=1234567  
Call-ID: 12345601@atlanta.example.com  
CSeq: 2 NOTIFY  
Content-Length: 0

/\* Alice now disconnects with Bob. \*/

F9 BYE Alice -> Bob

```
BYE sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds43
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 12345601@atlanta.example.com
CSeq: 102 BYE
Content-Length: 0
```

F10 200 OK Bob -> Alice

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds43
;received=192.0.2.105
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 12345601@atlanta.example.com
CSeq: 102 BYE
Content-Length: 0
```

/\* Bob attempts the transfer to Carol \*/

F11 INVITE Bob -> Carol

```
INVITE sips:carol@chicago.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds1
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>
Call-ID: 7436222@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:bob@client.biloxi.example.com>
Referred-By: <alice@atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...
```

```
v=0
o=bob 2890844539 2890844539 IN IP4 client.biloxi.example.com
s=
c=IN IP4 client.biloxi.example.com
t=0 0
m=audio 3458 RTP/AVP 0
```

a=rtpmap:0 PCMU/8000

F12 180 Ringing Carol -> Bob

SIP/2.0 180 Ringing  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds1  
;received=192.0.2.113  
From: Bob <sips:bob@biloxi.example.com>;tag=8675309  
To: Carol <sips:carol@chicago.example.com>;tag=928287  
Call-ID: 7436222@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:carol@client.chicago.example.com>  
Content-Length: 0

F13 200 OK Carol -> Bob

SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds1  
;received=192.0.2.113  
From: Bob <sips:bob@biloxi.example.com>;tag=8675309  
To: Carol <sips:carol@chicago.example.com>;tag=928287  
Call-ID: 7436222@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:carol@client.chicago.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...  
  
v=0  
o=carol 2890944542 2890844542 IN IP4 client.chicago.example.com  
s=  
c=IN IP4 client.chicago.example.com  
t=0 0  
m=audio 3456 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F14 ACK Bob -> Carol

ACK sips:carol@client.chicago.example.com SIP/2.0  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds9  
Max-Forwards: 70  
From: Bob <sips:bob@biloxi.example.com>;tag=8675309  
To: Carol <sips:carol@chicago.example.com>;tag=928287

```
Call-ID: 7436222@atlanta.example.com
CSeq: 1 ACK
Content-Length: 0
```

```
/* Bob and Carol now have established a session. Bob reports
   success to Alice which Alice probably ignores. */
```

```
F15 NOTIFY Bob -> Alice
```

```
NOTIFY sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds67
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=314159
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345601@atlanta.example.com
CSeq: 3 NOTIFY
Event: refer
Subscription-State: terminated;reason=noresource
Contact: <sips:bob@client.biloxi.example.com>
Content-Type: message/sipfrag
Content-Length: ...
```

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds1
;received=192.0.2.113
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>;tag=928287
Call-ID: 7436222@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:carol@client.chicago.example.com>
Content-Type: application/sdp
Content-Length: ...
```

```
F16 200 OK Alice -> Bob
```


```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds6
;received=192.0.2.113
From: Bob <sips:bob@biloxi.example.com>;tag=314159
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345601@atlanta.example.com
CSeq: 3 NOTIFY
Content-Length: 0
```

---

[TOC](#)

## **2.5. Transfer - Attended**

Alice	Bob	Carol
INVITE F1		
->		
180 Ringing F2		
<-		
200 OK F3		
<-		
ACK F4		
->		
RTP		
<=====		
INVITE (hold) F5		
<-		
200 OK F6		
->		
ACK F7		
<-		
No RTP		
	INVITE F8	
	->	
	180 Ringing F9	
	<-	
	200 OK F10	
	<-	
	ACK F11	
	->	
	RTP	
	<=====	
	INVITE (hold) F12	
	->	
	200 OK F13	
	<-	
	ACK F14	
	->	
	No RTP	
REFER Refer-To: C F15		
<-		
202 Accepted F16		
->		
NOTIFY F17		
->		
200 OK F18		
<-		
INVITE Replaces: B F19		
->		
200 OK F20		



In this scenario, Alice calls Bob. Bob puts Alice on hold then calls Carol to announce transfer, then places Carol on hold. Bob transfers Alice to Carol which replaces the session between Bob and Carol. Carol then disconnects session with Bob. Alice reports success of transfer to Bob, who then disconnects with Alice. In this example, the [Replaces header field \(Mahy, R., Biggs, B., and R. Dean, "The Session Initiation Protocol \(SIP\) "Replaces" Header," September 2004.\) \[RFC3891\]](#) is inserted into the Refer-To URI by Bob. Note that the Refer-To URI is the Contact URI returned by Carol in the 200 OK response F10. This ensures that only the correct instance of Carol is reached. The presence of the gr URI parameter in the Contact URI in message F10 indicates that the Contact URI is a [GRUU \(Rosenberg, J., "Obtaining and Using Globally Routable User Agent \(UA\) URIs \(GRUU\) in the Session Initiation Protocol \(SIP\)," October 2007.\)](#) [I-D.ietf-sip-gruu] and will be globally routable outside of the dialog. Without knowing the Contact URI is a gruu, Bob must be prepared, if the triggered INVITE had failed, to retry the REFER with a Refer-To URI of the URI used to reach Carol but with a Require: replaces header escaped in the Refer-To header field, as discussed in the [transfer \(Sparks, R. and A. Johnston, "Session Initiation Protocol Call Control - Transfer," March 2009.\)](#) [I-D.ietf-sipping-cc-transfer] document.

#### Message Details

F1 INVITE Alice -> Bob

```
INVITE sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F2 180 Ringing Bob -> Alice

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=23431
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:bob@client.biloxi.example.com>
Content-Length: 0
```

F3 200 OK Bob -> Alice

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=23431
Call-ID: 12345600@atlanta.example.com
```

```
CSeq: 1 INVITE
Contact: <sips:bob@client.biloxi.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...

v=0
o=bob 2890844527 2890844527 IN IP4 client.biloxi.example.com
s=
c=IN IP4 client.biloxi.example.com
t=0 0
m=audio 3456 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F4 ACK Alice -> Bob

```
ACK sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=23431
Call-ID: 12345600@atlanta.example.com
CSeq: 1 ACK
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Length: 0
```

```
/* Alice and Bob have established a session.
   Bob puts Alice on Hold */
```

F5 INVITE Bob -> Alice

```
INVITE sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds7
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=23431
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345600@atlanta.example.com
CSeq: 1024 INVITE
Contact: <sips:bob@client.biloxi.example.com>;+sip.rendering="no"
Content-Type: application/sdp
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Length: ...
```

```
v=0
o=bob 2890844527 2890844528 IN IP4 client.biloxi.example.com
s=
c=IN IP4 client.biloxi.example.com
t=0 0
m=audio 3456 RTP/AVP 0
a=rtpmap:0 PCMU/8000
a=sendonly
```

F6 200 OK Alice -> Bob

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds7
;received=192.0.2.113
From: Bob <sips:bob@biloxi.example.com>;tag=23431
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345600@atlanta.example.com
CSeq: 1024 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...
```

```
v=0
o=alice 2890844526 2890844527 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
a=recvonly
```

F7 ACK Bob -> Alice

```
ACK sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds3
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=23431
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345600@atlanta.example.com
CSeq: 1024 ACK
Content-Length: 0
```

```
/* Bob calls Carol */
```

F8 INVITE Bob -> Carol

```
INVITE sips:carol@chicago.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnash
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>
Call-ID: sdjfdjfskdf@biloxi.example.com
CSeq: 42 INVITE
Contact: <sips:bob@client.biloxi.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...

v=0
o=bob 28908445834 2890844834 IN IP4 client.biloxi.example.com
s=
c=IN IP4 client.biloxi.example.com
t=0 0
m=audio 3458 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F9 180 Ringing Carol -> Bob

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnash
;received=192.0.2.113
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>;tag=5f35a3
Call-ID: sdjfdjfskdf@biloxi.example.com
CSeq: 42 INVITE
Contact: <sips:39itp34klkd@chicago.example.com>
Content-Length: 0
```

F10 200 OK Carol -> Bob

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnash
;received=192.0.2.113
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>;tag=5f35a3
Call-ID: sdjfdjfskdf@biloxi.example.com
CSeq: 42 INVITE
```

```
Contact: <sips:39itp34klkd@chicago.example.com;gr>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces, gruu
Content-Type: application/sdp
Content-Length: ...

v=0
o=carol 2890844922 2890844922 IN IP4 client.chicago.example.com
s=
c=IN IP4 client.chicago.example.com
t=0 0
m=audio 3456 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F11 ACK Bob -> Carol

```
ACK sips:39itp34klkd@chicago.example.com;gr SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashd5
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>;tag=5f35a3
Call-ID: sdjfdjfskdf@biloxi.example.com
CSeq: 42 ACK
Content-Length: 0
```

/\* Bob puts Carol on hold \*/

F12 INVITE Bob -> Carol

```
INVITE sips:39itp34klkd@chicago.example.com;gr SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds0
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>;tag=5f35a3
Call-ID: sdjfdjfskdf@biloxi.example.com
CSeq: 43 INVITE
Contact: <sips:bob@client.biloxi.example.com>;+sip.rendering="no"
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...
```

```
v=0
o=bob 289084834 2890844835 IN IP4 client.biloxi.example.com
s=
c=IN IP4 client.biloxi.example.com
```

```
t=0 0
m=audio 3458 RTP/AVP 0
a=rtpmap:0 PCMU/8000
a=sendonly
```

F13 200 OK Carol -> Bob

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds0
;received=192.0.2.113
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>;tag=5f35a3
Call-ID: sdjfdjfskdf@biloxi.example.com
CSeq: 43 INVITE
Contact: <sips:39itp34klkd@chicago.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces, gruu
Content-Type: application/sdp
Content-Length: ...
```

```
v=0
o=carol 2890844922 2890844923 IN IP4 client.chicago.example.com
s=
c=IN IP4 client.chicago.example.com
t=0 0
m=audio 3456 RTP/AVP 0
a=rtpmap:0 PCMU/8000
a=recvonly
```

F14 ACK Bob -> Carol

```
ACK sips:39itp34klkd@chicago.example.com;gr SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnash334
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>;tag=5f35a3
Call-ID: sdjfdjfskdf@biloxi.example.com
CSeq: 43 ACK
Content-Length: 0
```

```
/* Bob Transfers Alice to Carol. */
```

F15 REFER Bob -> Alice

```
REFER sips:alice@client.atlanta.example.com SIP/2.0
```

Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds2g  
Max-Forwards: 70  
From: Bob <sips:bob@biloxi.example.com>;tag=23431  
To: Alice <sips:alice@atlanta.example.com>;tag=1234567  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1025 REFER  
<allOneLine>  
Refer-To: <sips:39itp34klkd@chicago.example.com?Replaces=  
sdjfdjfskdf%40biloxi.example.com%3Bto-tag%3D5f35a3  
%3Bfrom-tag%3D8675309&Require=replaces>  
</allOneLine>  
Referred-By: <sips:bob@biloxi.example.com>  
Contact: <sips:bob@client.biloxi.example.com>  
Content-Length: 0

F16 202 Accepted Alice -> Bob

SIP/2.0 202 Accepted  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashds2g  
;received=192.0.2.113  
From: Bob <sips:bob@biloxi.example.com>;tag=23431  
To: Alice <sips:alice@atlanta.example.com>;tag=1234567  
Call-ID: 12345600@atlanta.example.com  
Contact: <sips:alice@client.atlanta.example.com>  
CSeq: 1025 REFER  
Content-Length: 0

F17 NOTIFY Alice -> Bob

NOTIFY sips:bob@client.biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bfK  
Max-Forwards: 70  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=23431  
Call-ID: 12345600@atlanta.example.com  
CSeq: 2 NOTIFY  
Contact: <sips:alice@client.atlanta.example.com>  
Event: refer  
Subscription-State: active;expires=60  
Content-Type: message/sipfrag  
Content-Length: ...

SIP/2.0 100 Trying

F18 200 OK Bob -> Alice

SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bfK  
;received=192.0.2.103  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=23431  
Call-ID: 12345600@atlanta.example.com  
CSeq: 2 NOTIFY  
Content-Length: 0

/\* Alice establishes session with Carol which replaces the session between Bob and Carol \*/

F19 INVITE Alice -> Carol

INVITE sips:39itp34klkd@chicago.example.com;gr SIP/2.0  
Via: SIP/2.0/TLS chicago.example.com:5061  
;branch=z9hG4bKadfe4ko  
To: Carol <sips:39itp34klkd@chicago.example.com>  
Max-Forwards: 70  
From: Alice <sips:alice@atlanta.example.com>;tag=3461  
Call-ID: 9435674543@atlanta.example.com  
CSeq: 1 INVITE  
Require: replaces  
Referred-By: <sips:bob@biloxi.example.com>  
Replaces: sdjfdjfskdf@biloxi.example.com  
;to-tag=5f35a3;from-tag=8675309  
Contact: <sips:alice@client.atlanta.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...  
  
v=0  
o=alice 2890844989 2890844989 IN IP4 client.atlanta.example.com  
s=  
c=IN IP4 client.atlanta.example.com  
t=0 0  
m=audio 3458 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F20 200 OK Carol -> Alice

SIP/2.0 200 OK  
Via: SIP/2.0/TLS chicago.example.com:5061  
;branch=z9hG4bKadfe4ko

```
;received=192.0.2.103
To: Carol <sips:39itp34klkd@chicago.example.com>;tag=ff3a
From: Alice <sips:alice@atlanta.example.com>;tag=3461
Call-ID: 9435674543@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:39itp34klkd@chicago.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces, gruu
Content-Type: application/sdp
Content-Length: ...

v=0
o=carol 2890844221 2890844221 IN IP4 client.chicago.example.com
s=
c=IN IP4 client.chicago.example.com
t=0 0
m=audio 49172 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F21 ACK Alice -> Carol

```
ACK sips:39itp34klkd@chicago.example.com;gr SIP/2.0
Via: SIP/2.0/TLS chicago.example.com:5061
;branch=z9hG4bKadfe4kU3
To: Carol <sips:39itp34klkd@chicago.example.com>;tag=ff3a
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=3461
Call-ID: 9435674543@atlanta.example.com
CSeq: 1 ACK
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Length: 0
```

/\* Carol then disconnects from Bob \*/

F22 BYE Carol -> Bob

```
BYE sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bfE
To: Bob <sips:bob@biloxi.example.com>;tag=8675309
Max-Forwards: 70
From: Carol <sips:carol@chicago.example.com>;tag=5f35a3
Call-ID: sdjfdjfskdf@biloxi.example.com
CSeq: 1 BYE
Content-Length: 0
```

F23 200 OK Bob -> Carol

SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bfE  
;received=192.0.2.123  
To: Bob <sips:bob@biloxi.example.com>;tag=8675309  
From: Carol <sips:carol@chicago.example.com>;tag=5f35a3  
Call-ID: sdjfdjfskdf@biloxi.example.com  
CSeq: 1 BYE  
Content-Length: 0

/\* Alice tells Bob that the call has been  
successfully transferred \*/

F24 NOTIFY Alice -> Bob

NOTIFY sips:bob@client.biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf2N  
Max-Forwards: 70  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=23431  
Call-ID: 12345600@atlanta.example.com  
CSeq: 3 NOTIFY  
Event: refer  
Subscription-State: terminated;reason=noresource  
Contact: <sips:alice@client.atlanta.example.com>  
Content-Type: message/sipfrag  
Content-Length: ...

SIP/2.0 200 OK  
Via: SIP/2.0/TLS chicago.example.com:5061  
;branch=z9hG4bKadfe4ko  
;received=192.0.2.103  
To: Carol <sips:39itp34klkd@chicago.example.com>;tag=ff3a  
From: Alice <sips:alice@atlanta.example.com>;tag=3461  
Call-ID: 9435674543@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:39itp34klkd@chicago.example.com>

F25 200 OK Bob -> Alice

SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567

```
To: Bob <sips:bob@biloxi.example.com>;tag=23431
Call-ID: 12345600@atlanta.example.com
CSeq: 3 NOTIFY
Content-Length: 0

/* Bob disconnects with Alice */

F26 BYE Bob -> Alice

BYE sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds7P
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=23431
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345600@atlanta.example.com
CSeq: 1026 BYE
Content-Length: 0


F27 200 OK Alice -> Bob

SIP/2.0 200 OK
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds7P
;received=192.0.2.113
From: Bob <sips:bob@biloxi.example.com>;tag=23431
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345600@atlanta.example.com
CSeq: 1026 BYE
Content-Length: 0
```

---

[TOC](#)

## 2.6. Transfer - Instant Messaging



In this scenario, Alice and Bob establish a session between them. Bob wants Carol to take the call so sends an Instant Message (IM) to Carol containing Alice's URI and an embedded Replaces header field. If Carol clicks on the URI, Carol's SIP UA sends an INVITE to Alice which replaces the session with Bob.

This scenario shows the use of the SIP [MESSAGE \(Campbell, B., Rosenberg, J., Schulzrinne, H., Huitema, C., and D. Gurle, "Session Initiation Protocol \(SIP\) Extension for Instant Messaging," December 2002.\)](#) [RFC3428] method to pass the URI. However, another IM protocol or other method could have been used to pass the URI from Bob to Carol.

Message Details

F1 INVITE Alice -> Bob

```
INVITE sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:a8342043f@atlanta.example.com;gr>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces, gruu
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F2 180 Ringing Bob -> Alice

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=3145678
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:bob@client.biloxi.example.com>
Content-Length: 0
```

F3 200 OK Bob -> Alice

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=3145678
Call-ID: 12345600@atlanta.example.com
```

```
Contact: <sips:bob@client.biloxi.example.com>
CSeq: 1 INVITE
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY, MESSAGE
Supported: replaces
Content-Type: application/sdp
Content-Length: ...
```

```
v=0
o=bob 2890844527 2890844527 IN IP4 client.biloxi.example.com
s=
c=IN IP4 client.biloxi.example.com
t=0 0
m=audio 3456 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F4 ACK Alice -> Bob

```
ACK sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74r
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=3145678
Call-ID: 12345600@atlanta.example.com
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
CSeq: 1 ACK
Content-Length: 0
```

/\* Bob IMs Carol \*/

F5 MESSAGE Bob -> Carol

```
MESSAGE sips:carol@chicago.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnash
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>
Call-ID: sdjfdjfskdf@biloxi.example.com
CSeq: 42 MESSAGE
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY, MESSAGE
Supported: replaces
Content-Type: text/html
Content-Length: ...
```

<HTML>Do you want to take this call from  
<allOneLine>

```
<A HREF="sips:a8342043f@atlanta.example.com;gr?Replaces=12345600@atlanta.example.com%3Bto-tag%3D3145678%3Bfrom-tag%3D1234567&Require=replaces">  
Alice</A>?  
</allOneLine>  
</HTML>
```

F6 200 OK Carol -> Bob

```
SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnash  
;received=192.0.2.113  
From: Bob <sips:bob@biloxi.example.com>;tag=8675309  
To: Carol <sips:carol@chicago.example.com>;tag=5f35a3  
Call-ID: sdjfdjfskdf@biloxi.example.com  
CSeq: 42 MESSAGE  
Contact: <sips:carol@client.chicago.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY, MESSAGE  
Supported: replaces  
Content-Length: 0
```

/\* Carol takes the call from Bob \*/

F7 INVITE Carol -> Alice

```
INVITE sips:a8342043f@atlanta.example.com;gr SIP/2.0  
Via: SIP/2.0/TLS pc.biloxi.example.com:5061  
;branch=z9hG4bK74HH  
Max-Forwards: 70  
From: Carol <sips:carol@chicago.example.com>;tag=8675310  
To: Alice <sips:a8342043f@atlanta.example.com;gr>  
Call-ID: 563456212@b2.chicago.example.com  
CSeq: 1 INVITE  
Require: replaces  
Replaces: 12345600@atlanta.example.com  
;to-tag=3145678;from-tag=1234567  
Contact: <sips:carol@client.chicago.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY, MESSAGE  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...
```

```
v=0  
o=carol 2890843122 2890843122 IN IP4 client.chicago.example.com  
s=  
c=IN IP4 client.chicago.example.com  
t=0 0
```

```

m=audio 5342 RTP/AVP 0
a=rtpmap:0 PCMU/8000

/* Alice matches the dialog information in the
   Replaces header and accepts the INVITE */

F8 200 OK Alice -> Carol

SIP/2.0 200 OK
Via: SIP/2.0/TLS pc.biloxi.example.com:5061
;branch=z9hG4bK74HH
;received=192.0.2.114
From: Carol <sips:carol@chicago.example.com>;tag=8675310
To: Alice <sips:a8342043f@atlanta.example.com;gr>;tag=131256
Call-ID: 563456212@b2.chicago.example.com
CSeq: 1 INVITE
Contact: <sips:a8342043f@atlanta.example.com;gr>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces, gruu
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 289084543 289084543 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49172 RTP/AVP 0
a=rtpmap:0 PCMU/8000

F9 ACK Carol -> Alice

ACK sips:a8342043f@atlanta.example.com;gr SIP/2.0
Via: SIP/2.0/TLS b2.biloxi.example.com:5061
;branch=z9hG4bK7435
Max-Forwards: 70
From: Carol <sips:carol@chicago.example.com>;tag=8675310
To: Alice <sips:a8342043f@atlanta.example.com;gr>;tag=131256
Call-ID: 563456212@b2.chicago.example.com
CSeq: 1 ACK
Content-Length: 0

/* RTP streams are established between Alice and Carol.
   Alice Hangs Up with Bob due to the Replaces header field. */

F10 BYE Alice -> Bob

```

```
BYE sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=3145678
Call-ID: 12345600@atlanta.example.com
CSeq: 2 BYE
Content-Length: 0
```


F11 200 OK Bob -> Alice

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=3145678
Call-ID: 12345600@atlanta.example.com
CSeq: 2 BYE
Content-Length: 0
```

---

[TOC](#)

## 2.7. Call Forwarding Unconditional



Bob wants all calls forwarded to the PSTN (which is just another URI to the proxy server). Alice calls Bob. The proxy server rewrites the Request URI, and forwards the INVITE to a Gateway. Details of messaging behind the Gateway are not shown.

Note that the 181 Call is Being Forwarded response does not have a To tag added as the proxy does not wish to establish an early dialog with Alice. Strictly speaking, the proxy is behaving as a User Agent in this case as a proxy can not generate non-100 provisional responses.

Note also that forwarding could be accomplished using a redirect (302 Moved Temporarily response).

Message Details

F1 INVITE Alice -> Proxy

```
INVITE sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F2 (100 Trying) Proxy -> Alice

```
SIP/2.0 100 Trying
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Content-Length: 0
```

F3 (181 Call is Being Forwarded) Proxy -> Alice

```
SIP/2.0 181 Call is Being Forwarded
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=9214d
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Content-Length: 0
```

```
/* Proxy forwards call by rewriting Request-URI */
```

```
F4 INVITE Proxy -> Gateway
```

```
INVITE sips:+19727293660@gw1.example.com;user=phone SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.1
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
Max-Forwards: 69
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

```
F5 180 Ringing Gateway -> Proxy
```

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.1
;received=192.0.2.54
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:+19727293660@gw1.example.com;user=phone>
Content Length:0
```

F6 180 Ringing Proxy -> Alice

SIP/2.0 180 Ringing  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
Record-Route: <sips:ss1.example.com;lr>  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=314159  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:+19727293660@gw1.example.com;user=phone>  
Content Length: 0

F7 200 OK Gateway -> Proxy

SIP/2.0 200 OK  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749.1  
;received=192.0.2.54  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
Record-Route: <sips:ss1.example.com;lr>  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=314159  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:+19727293660@gw1.example.com;user=phone>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Content-Type: application/sdp  
Content-Length: ...  
  
v=0  
o=GATEWAY1 2890844527 2890844527 IN IP4 gatewayone.example.com  
s=  
c=IN IP4 gatewayone.example.com  
t=0 0  
m=audio 3456 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F8 200 OK Proxy -> Alice

SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
Record-Route: <sips:ss1.example.com;lr>

```
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:biloxi.example.com>;tag=314159
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:+19727293660@gw1.example.com;user=phone>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Content-Type: application/sdp
Content-Length: ...

v=0
o=GATEWAY1 2890844527 2890844527 IN IP4 gatewayone.example.com
s=
c=IN IP4 gatewayone.example.com
t=0 0
m=audio 3456 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F9 ACK Alice -> Proxy

```
ACK sips:+19727293660@gw1.example.com;user=phone SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf31
Route: <sips:ss1.example.com;lr>
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:biloxi.example.com>;tag=314159
Call-ID: 12345600@atlanta.example.com
CSeq: 1 ACK
Content-Length: 0
```

F10 ACK Proxy -> Gateway

```
ACK sips:+19727293660@gw1.example.com;user=phone SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749ws.1
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf31
;received=192.0.2.103
Max-Forwards: 69
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:biloxi.example.com>;tag=314159
Call-ID: 12345600@atlanta.example.com
CSeq: 1 ACK
Content-Length: 0
```

F11 BYE Alice -> Proxy

BYE sips:+19727293660@gw1.example.com;user=phone SIP/2.0  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bfJe  
Route: <sips:ss1.example.com;lr>  
Max-Forwards: 70  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:biloxi.example.com>;tag=314159  
Call-ID: 12345600@atlanta.example.com  
CSeq: 2 BYE  
Content-Length: 0

F12 BYE Proxy -> Gateway

BYE sips:+19727293660@gw1.example.com;user=phone SIP/2.0  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749G1  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bfJe  
;received=192.0.2.103  
Max-Forwards: 69  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:biloxi.example.com>;tag=314159  
Call-ID: 12345600@atlanta.example.com  
CSeq: 2 BYE  
Content-Length: 0

F13 200 OK Gateway -> Proxy

SIP/2.0 200 OK  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749G1  
;received=192.0.2.54  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bfJe  
;received=192.0.2.103  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:biloxi.example.com>;tag=314159  
Call-ID: 12345600@atlanta.example.com  
CSeq: 2 BYE  
Content-Length: 0

F14 200 OK Proxy -> Alice

SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bfJe  
;received=192.0.2.103

```


From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 12345600@atlanta.example.com
CSeq: 2 BYE
Content-Length: 0

```

---

## 2.8. Call Forwarding - Busy

[TOC](#)



Bob wants calls to B1 forwarded to B2 if B1 is busy (this information is known to the proxy). Alice calls B1, B1 is busy, the proxy server places call to B2.

## Message Details

F1 INVITE Alice -> Proxy

```
INVITE sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F2 INVITE Proxy -> B1

```
INVITE sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.1
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
Max-Forwards: 69
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
```

```
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F3 (100 Trying) Proxy -> Alice

```
SIP/2.0 100 Trying
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Content-Length: 0
```

F4 486 Busy Here B1 -> Proxy

```
SIP/2.0 486 Busy Here
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.1
;received=192.0.2.54
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=765432
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Content-Length: 0
```

F5 ACK Proxy -> B1

```
ACK sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.1
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=765432
Call-ID: 12345600@atlanta.example.com
CSeq: 1 ACK
Content-Length: 0
```

F6 (181 Call is Being Forwarded) Proxy -> Alice

```
SIP/2.0 181 Call is Being Forwarded
Via: SIP/2.0/TLS client.atlanta.example.com:5061
```

```
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=9214d
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Content-Length: 0
```

```
/* The proxy now forwards the call to B2 */
```

```
F7 INVITE Proxy -> B2
```

```
INVITE sips:bob@client2.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.2
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
Max-Forwards: 69
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Content-Type: application/sdp
Content-Length: ...
```

```
v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

```
F8 180 Ringing B2 -> Proxy
```

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.2
;received=192.0.2.54
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
```

To: Bob <sips:bob@biloxi.example.com>;tag=7654321  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:bob@client2.biloxi.example.com>  
Content-Length: 0

F9 180 Ringing Proxy -> Alice

SIP/2.0 180 Ringing  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
Record-Route: <sips:ss1.example.com;lr>  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=7654321  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:bob@client2.biloxi.example.com>  
Content-Length: 0

F10 200 OK B2 -> Proxy

SIP/2.0 200 OK  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749.2  
;received=192.0.2.54  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
Record-Route: <sips:ss1.example.com;lr>  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=7654321  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:bob@client2.biloxi.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Content-Type: application/sdp  
Content-Length: ...

v=0  
o=bob 2890844527 2890844527 IN IP4 client2.biloxi.example.com  
s=  
c=IN IP4 client2.biloxi.example.com  
t=0 0  
m=audio 3456 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F11 200 OK Proxy -> Alice

SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
Record-Route: <sips:ss1.example.com;lr>  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=7654321  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:bob@client2.biloxi.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Content-Type: application/sdp  
Content-Length: ...  
  
v=0  
o=bob 2890844527 2890844527 IN IP4 client2.biloxi.example.com  
s=  
c=IN IP4 client2.biloxi.example.com  
t=0 0  
m=audio 3456 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F12 ACK Alice -> Proxy

ACK sips:bob@client2.biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bfX  
Route: <sips:ss1.example.com;lr>  
Max-Forwards: 70  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=7654321  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 ACK  
Content-Length: 0

F13 ACK Proxy -> B2

ACK sips:bob@client2.biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83731  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bfX  
;received=192.0.2.103  
Max-Forwards: 69  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=7654321

Call-ID: 12345600@atlanta.example.com  
CSeq: 1 ACK  
Content-Length: 0

/\* RTP streams are established between A and B2 \*/

/\* Alice eventually hangs up with User B2. \*/

F14 BYE Alice -> Proxy

BYE sips:bob@client2.biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bW4  
Route: <sips:ss1.example.com;lr>  
Max-Forwards: 70  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=7654321  
Call-ID: 12345600@atlanta.example.com  
CSeq: 2 BYE  
Content-Length: 0

F15 BYE Proxy -> B2

BYE sips:bob@client2.biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK837493  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bW4  
;received=192.0.2.103  
Max-Forwards: 69  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=7654321  
Call-ID: 12345600@atlanta.example.com  
CSeq: 2 BYE  
Content-Length: 0

F16 200 OK B2 -> Proxy

SIP/2.0 200 OK  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK837493  
;received=192.0.2.54  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bW4  
;received=192.0.2.103  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567

```
To: Bob <sips:bob@biloxi.example.com>;tag=7654321
Call-ID: 12345600@atlanta.example.com
CSeq: 2 BYE
Content-Length: 0
```


```
F17 200 OK Proxy -> Alice
```

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bw4
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=7654321
Call-ID: 12345600@atlanta.example.com
CSeq: 2 BYE
Content-Length: 0
```

---

[TOC](#)

## 2.9. Call Forwarding - No Answer



Bob wants calls to B1 forwarded to B2 if B1 is not answered (information is known to the proxy server). Alice calls B1 and no one answers. The proxy server then places the call to B2.

Message Details

F1 INVITE Alice -> Proxy

```
INVITE sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F2 INVITE Proxy -> B1

```
INVITE sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.1
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
Max-Forwards: 69
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
```

```
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F3 (100 Trying) Proxy -> Alice

```
SIP/2.0 100 Trying
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Content-Length: 0
```

F4 180 Ringing B1 -> Proxy

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.1
;received=192.0.2.54
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=3145678
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:bob@client.biloxi.example.com>
Content-Length: 0
```

F5 180 Ringing Proxy -> Alice

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=3145678
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:bob@client.biloxi.example.com>
Content-Length: 0
```

```
/* B1 rings until a configurable timer expires in the Proxy. The  
Proxy sends Cancel and proceeds down the list of routes. */
```

F6 CANCEL Proxy -> B1

```
CANCEL sips:bob@client.biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749.1  
Max-Forwards: 70  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 CANCEL  
Content-Length: 0
```

F7 200 OK B1 -> Proxy

```
SIP/2.0 200 OK  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749.1  
;received=192.0.2.54  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=329d823  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 CANCEL  
Content-Length: 0
```

F8 487 Request Terminated B1 -> Proxy

```
SIP/2.0 487 Request Terminated  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749.1  
;received=192.0.2.54  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=3145678  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Content-Length: 0
```

F9 ACK Proxy -> B1

```
ACK sips:bob@client.biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749.1
```

Max-Forwards: 70  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:biloxi.example.com>;tag=3145678  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 ACK  
Content-Length: 0

F10 (181 Call is Being Forwarded) Proxy -> Alice

SIP/2.0 181 Call is Being Forwarded  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:biloxi.example.com>;tag=9214d  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Content-Length: 0

F11 INVITE Proxy -> B2

INVITE sips:bob@client2.biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749.2  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
Record-Route: <sips:ss1.example.com;lr>  
Max-Forwards: 69  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:biloxi.example.com>  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:alice@client.atlanta.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Content-Type: application/sdp  
Content-Length: ...

v=0  
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com  
s=  
c=IN IP4 client.atlanta.example.com  
t=0 0  
m=audio 49170 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F12 180 Ringing B2 -> Proxy

SIP/2.0 180 Ringing  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749.2  
;received=192.0.2.54  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
Record-Route: <sips:ss1.example.com;lr>  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=765432  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:bob@client2.biloxi.example.com>  
Content-Length: 0

F13 180 Proxy -> Alice

SIP/2.0 180 Ringing  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
Record-Route: <sips:ss1.example.com;lr>  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=765432  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:bob@client2.biloxi.example.com>  
Content-Length: 0

F14 200 OK B2 -> Proxy

SIP/2.0 200 OK  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749.2  
;received=192.0.2.54  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
Record-Route: <sips:ss1.example.com;lr>  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=765432  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:bob@client2.biloxi.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Content-Type: application/sdp

Content-Length: ...

v=0  
o=bob 2890844527 2890844527 IN IP4 client2.biloxi.example.com  
s=  
c=IN IP4 client2.biloxi.example.com  
t=0 0  
m=audio 3456 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F15 200 OK Proxy -> Alice

SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
Record-Route: <sips:ss1.example.com;lr>  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=765432  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:bob@client2.biloxi.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Content-Type: application/sdp  
Content-Length: ...

v=0  
o=bob 2890844527 2890844527 IN IP4 client2.biloxi.example.com  
s=  
c=IN IP4 client2.biloxi.example.com  
t=0 0  
m=audio 3456 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F16 ACK Alice -> Proxy

ACK sips:bob@client2.biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf3  
Route: <sips:ss1.example.com;lr>  
Max-Forwards: 70  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=765432  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 ACK  
Content-Length: 0

F17 ACK Proxy -> B2

```
ACK sips:bob@client2.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK8374.1
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf3
;received=192.0.2.103
Max-Forwards: 69
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=765432
Call-ID: 12345600@atlanta.example.com
CSeq: 1 ACK
Content-Length: 0
```

```
/* RTP streams are established between A and B2.
Alice Hangs Up with User B2. */
```

F18 BYE Alice -> Proxy

```
BYE sips:bob@client2.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74b3f
Route: <sips:ss1.example.com;lr>
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=765432
Call-ID: 12345600@atlanta.example.com
CSeq: 2 BYE
Content-Length: 0
```

F19 BYE Proxy -> B2

```
BYE sips:bob@client2.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK837.1
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74b3f
;received=192.0.2.103
Max-Forwards: 69
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=765432
Call-ID: 12345600@atlanta.example.com
CSeq: 2 BYE
Content-Length: 0
```

F20 200 OK B2 -> Proxy

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK837.1
;received=192.0.2.54
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74b3f
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=765432
Call-ID: 12345600@atlanta.example.com
CSeq: 2 BYE
Content-Length: 0
```


F21 200 OK Proxy -> Alice

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74b3f
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=765432
Call-ID: 12345600@atlanta.example.com
CSeq: 2 BYE
Content-Length: 0
```

---

[TOC](#)

## 2.10. 3-way Conference - Third Party is Added



In this scenario, Alice and Bob are in a 2-party call (session) when Bob wishes to add Carol into the conversation. Bob is capable of media mixing in a 3-party call. Bob first sends a re-INVITE to Alice changing Contact URIs to one that indicates Bob's mixer and acts like a focus.

As a result, Bob includes the "[isfocus" feature tag \(Rosenberg, J., Schulzrinne, H., and P. Kyzivat, "Indicating User Agent Capabilities in the Session Initiation Protocol \(SIP\)," August 2004.\) \[RFC3840\]](#)" as described in [\[RFC4579\] \(Johnston, A. and O. Levin, "Session Initiation Protocol \(SIP\) Call Control - Conferencing for User Agents," August 2006.\)](#). Bob then INVITEs Carol using the same Contact URI. Note that Bob could wait to re-INVITE Alice until after Carol has answered. Bob could also put Alice on hold before calling Carol

Message Details

F1 INVITE Alice -> Bob

```
INVITE sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F2 180 Ringing Bob -> Alice

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=23431
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:b54gh42f5@biloxi.example.com>
Content-Length: 0
```

F3 200 OK Bob -> Alice

```
SIP/2.0 200 OK

Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=23431
```

```
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:b54gh42f5@biloxi.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces, gruu
Content-Type: application/sdp
Content-Length: ...

v=0
o=bob 2890844527 2890844527 IN IP4 client.biloxi.example.com
s=
c=IN IP4 client.biloxi.example.com
t=0 0
m=audio 3456 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F4 ACK Alice -> Bob

```
ACK sips:b54gh42f5@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bfL
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=23431
Call-ID: 12345600@atlanta.example.com
CSeq: 1 ACK
Content-Length: 0
```

```
/* Alice and Bob have established a session.
   Bob re-INVITEs changing Contact URIs */
```

F5 INVITE Bob -> Alice

```
INVITE sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=23431
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345600@atlanta.example.com
CSeq: 1024 INVITE
Contact: <sips:bob-Mixer@client.biloxi.example.com>;isfocus
Content-Type: application/sdp
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces, gruu
Content-Length: ...
```

v=0

```
o=bob 2890844527 2890844528 IN IP4 client.biloxi.example.com
s=
c=IN IP4 client.biloxi.example.com
t=0 0
m=audio 49172 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F6 200 OK Alice -> Bob

SIP/2.0 200 OK

```
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds7
;received=192.0.2.113
From: Bob <sips:bob@biloxi.example.com>;tag=23431
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345600@atlanta.example.com
CSeq: 1024 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...
```

```
v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F7 ACK Bob -> Alice

```
ACK sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnash3G
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=23431
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345600@atlanta.example.com
CSeq: 1024 ACK
Content-Length: 0
```

/\* Bob calls Carol \*/

F8 INVITE Bob -> Carol

```
INVITE sips:carol@chicago.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashJfd
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>
Call-ID: sdjfdjfskdf@biloxi.example.com
CSeq: 42 INVITE
Contact: <sips:bob-Mixer@client.biloxi.example.com>;isfocus
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces, gruu
Content-Type: application/sdp
Content-Length: ...

v=0
o=bob 28908445834 2890844834 IN IP4 client.biloxi.example.com
s=
c=IN IP4 client.biloxi.example.com
t=0 0
m=audio 48174 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F9 180 Ringing Carol -> Bob

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashJfd
;received=192.0.2.113
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>;tag=341313
Call-ID: sdjfdjfskdf@biloxi.example.com
CSeq: 42 INVITE
Contact: <sips:carol@client.chicago.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Length: 0
```

F10 200 OK Carol -> Bob

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashJfd
;received=192.0.2.113
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>;tag=341313
Call-ID: sdjfdjfskdf@biloxi.example.com
CSeq: 42 INVITE
```

```
Contact: <sips:carol@client.chicago.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...

v=0
o=carol 2890844922 2890844922 IN IP4 client.chicago.example.com
s=
c=IN IP4 client.chicago.example.com
t=0 0
m=audio 3456 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F11 ACK Bob -> Carol


```
ACK sips:carol@client.chicago.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnash431
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>;tag=341313
Call-ID: sdjfdjfskdf@biloxi.example.com
CSeq: 42 ACK
Content-Length: 0
```

```
/* User B's mixer know mixes media from both A and C
   to create the 3-way conference. */
```

---

[TOC](#)

## 2.11. 3-way Conference - Third Party Joins



In this scenario, Alice and Bob are in a 2 party call and Carol wishes to join resulting in a three party call. Carol could have learned Bob's dialog identifier using some non-SIP means, or possibly from a NOTIFY with the dialog package sent by Bob. Carol sends an INVITE to Bob containing a Join header identifying the dialog between Alice and Bob. Bob re-INVITEs Alice to switch to focus mode and includes the ["isfocus" feature tag](#) (Rosenberg, J., Schulzrinne, H., and P. Kyzivat, ["Indicating User Agent Capabilities in the Session Initiation Protocol \(SIP\)," August 2004.](#)) [RFC3840] as described in [\[RFC4579\]](#) (Johnston, A. and O. Levin, ["Session Initiation Protocol \(SIP\) Call Control - Conferencing for User Agents," August 2006.](#)). Bob then accepts the INVITE from Carol, resulting in the 3-way call.

Message Details

F1 INVITE Alice -> Bob

```
INVITE sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F2 180 Ringing Bob -> Alice

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=23431
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:b54gh42f5@biloxi.example.com>
Content-Length: 0
```

F3 200 OK Bob -> Alice

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=23431
Call-ID: 12345600@atlanta.example.com
```

```
CSeq: 1 INVITE
Contact: <sips:b54gh42f5@biloxi.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces, join, gruu
Content-Type: application/sdp
Content-Length: ...

v=0
o=bob 2890844527 2890844527 IN IP4 client.biloxi.example.com
s=
c=IN IP4 client.biloxi.example.com
t=0 0
m=audio 3456 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F4 ACK Alice -> Bob

```
ACK sips:b54gh42f5@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf6
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=23431
Call-ID: 12345600@atlanta.example.com
CSeq: 1 ACK
Content-Length: 0
```

```
/* Alice and Bob have established a session.
   Carol requests to join the session */
```

F5 INVITE Carol -> Bob

```
INVITE sips:carol@chicago.example.com SIP/2.0
Via: SIP/2.0/TLS chicago.example.com:5061
;branch=z9hG4bKnashds7
Max-Forwards: 70
From: Carol <sips:carol@chicago.example.com>;tag=8675309
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 452k499sk@chicago.example.com
CSeq: 99 INVITE
Contact: <sips:carol@client.chicago.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces, join
Join: 12345600@atlanta.example.com;from-tag=1234567;to-tag=23431
Content-Type: application/sdp
Content-Length: ...
```

v=0

```
o=carol 2890844922 2890844922 IN IP4 client.chicago.example.com
s=
c=IN IP4 client.chicago.example.com
t=0 0
m=audio 3456 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F6 180 Ringing Bob -> Carol

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS chicago.example.com:5061
;branch=z9hG4bKnashds7
;received=120.
From: Carol <sips:carol@chicago.example.com>;tag=8675309
To: Bob <sips:bob@biloxi.example.com>;tag=0982
Call-ID: 452k499sk@chicago.example.com
CSeq: 99 INVITE
Contact: <sips:bob-Mixer@client.biloxi.example.com>;isfocus
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Length: 0
```

F7 INVITE Bob -> Alice

```
INVITE sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashdyKL
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=23431
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345600@atlanta.example.com
CSeq: 1024 INVITE
Contact: <sips:bob-Mixer@client.biloxi.example.com>;isfocus
Content-Type: application/sdp
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces, join, gruu
Content-Length: ...
```

```
v=0
o=bob 2890844527 2890844528 IN IP4 client.biloxi.example.com
s=
c=IN IP4 client.biloxi.example.com
t=0 0
m=audio 49172 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F8 200 OK Alice -> Bob

SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnashdyKL  
;received=192.0.2.113  
From: Bob <sips:bob@biloxi.example.com>;tag=23431  
To: Alice <sips:alice@atlanta.example.com>;tag=1234567  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1024 INVITE  
Contact: <sips:alice@client.atlanta.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...  
  
v=0  
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com  
s=  
c=IN IP4 client.atlanta.example.com  
t=0 0  
m=audio 49170 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F9 ACK Bob -> Alice

ACK sips:alice@client.atlanta.example.com SIP/2.0  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bKnash3g  
Max-Forwards: 70  
From: Bob <sips:bob@biloxi.example.com>;tag=23431  
To: Alice <sips:alice@atlanta.example.com>;tag=1234567  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1024 ACK  
Content-Length: 0

F10 200 OK Bob -> Carol

SIP/2.0 200 OK  
Via: SIP/2.0/TLS chicago.example.com:5061  
;branch=z9hG4bKnashds7  
;received=120.  
From: Carol <sips:carol@chicago.example.com>;tag=8675309  
To: Bob <sips:bob@biloxi.example.com>;tag=0982  
Call-ID: 452k499sk@chicago.example.com  
CSeq: 99 INVITE  
Contact: <sips:bob-Mixer@client.biloxi.example.com>;isfocus  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
Supported: replaces, join, gruu

```
Content-Type: application/sdp
Content-Length: ...

v=0
o=bob 28908445834 2890844834 IN IP4 client.biloxi.example.com
s=
c=IN IP4 client.biloxi.example.com
t=0 0
m=audio 48174 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```


F11 ACK OK Carol -> Bob

```
ACK sips:bob-Mixer@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS chicago.example.com:5061
;branch=z9hG4bKnash4Gf
Max-Forwards: 70
From: Carol <sips:carol@chicago.example.com>;tag=8675309
To: Bob <sips:bob@biloxi.example.com>;tag=0982
Call-ID: 452k499sk@chicago.example.com
CSeq: 99 ACK
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces, join
Content-Length:0
```

---

[TOC](#)

## **2.12. Find-Me**





Alice's call to Bob will result in an attempt to locate that user by calling locations from a list of contacts. The location to answer the call becomes the active set, no other sets may join the call.

While this flow shows a sequential search, the search could be accomplished using parallel forking, as in the previous example.

[Message Details](#)

F1 INVITE Alice -> Proxy

```
INVITE sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
S=
c=IN IP4 client.atlanta.example.com
t= 0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F2 INVITE Proxy -> B1

```
INVITE sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.1
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
Max-Forwards: 69
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
S=
c=IN IP4 client.atlanta.example.com
t= 0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F3 (100 Trying) Proxy -> Alice

```
SIP/2.0 100 Trying
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Content-Length: 0
```

F4 180 Ringing B1 -> Proxy

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.1
;received=192.0.2.54
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=765432
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:bob@client.biloxi.example.com>
Content-Length: 0
```

F5 180 Ringing Proxy -> Alice

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=765432
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:bob@client.biloxi.example.com>
Content-Length: 0
```

```
/* B1 rings until a configurable timer in the Proxy
expires. The Proxy then sends Cancel and proceeds down
```

the list of routes. \*/

F6 CANCEL Proxy -> B1

CANCEL sips:bob@client.biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749.1  
Max-Forwards: 70  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 CANCEL  
Content-Length: 0

F7 200 OK B1 -> Proxy

SIP/2.0 200 OK  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749.1  
;received=192.0.2.54  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=765432  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 CANCEL  
Content-Length: 0

F8 487 Request Terminated B1 -> Proxy

SIP/2.0 487 Request Terminated  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749.1  
;received=192.0.2.54  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=765432  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Content-Length: 0

F9 ACK Proxy -> B1

ACK sips:bob@client.biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749.1  
Max-Forwards: 70

```
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=765432
Call-ID: 12345600@atlanta.example.com
CSeq: 1 ACK
Content-Length: 0
```

F10 INVITE Proxy -> B2

```
INVITE sips:bob@client2.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.2
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
Max-Forwards: 69
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F11 480 Not Logged In B2 -> Proxy

```
SIP/2.0 480 Not Logged In
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.2
;received=192.0.2.54
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314756
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Content-Length: 0
```

F12 ACK Proxy -> B2

```
ACK sips:bob@client2.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.2
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314756
Call-ID: 12345600@atlanta.example.com
CSeq: 1 ACK
Content-Length: 0
```

F13 INVITE Proxy -> B3

```
INVITE sips:bob@client3.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.3
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
Max-Forwards: 69
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F14 486 Busy Here B3 -> Proxy

```
SIP/2.0 486 Busy Here
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.3
;received=192.0.2.54
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
```

To: Bob <sips:bob@biloxi.example.com>;tag=7654321  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Content-Length: 0

F15 ACK Proxy -> B3

ACK sips:bob@client3.biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749.3  
Max-Forwards: 70  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=7654321  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 ACK  
Content-Length: 0

F16 INVITE Proxy -> B4

INVITE sips:bob@client4.biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS ss1.example.com:5061  
;branch=z9hG4bK83749.4  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
Record-Route: <sips:ss1.example.com;lr>  
Max-Forwards: 69  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:alice@client.atlanta.example.com>  
Content-Type: application/sdp  
Content-Length: ...

v=0  
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com  
s=  
c=IN IP4 client.atlanta.example.com  
t=0 0  
m=audio 49170 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F17 180 Ringing B4 -> Proxy

SIP/2.0 180 Ringing  
Via: SIP/2.0/TLS ss1.example.com:5061

```
;branch=z9hG4bK83749.4
;received=192.0.2.54
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=7137136
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:bob@client4.biloxi.example.com>
Content-Length: 0
```

F18 180 Ringing Proxy -> Alice

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=7137136
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:bob@client4.biloxi.example.com>
Content-Length: 0
```

F19 200 OK B4 -> Proxy

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83749.4
;received=192.0.2.54
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=7137136
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:bob@client4.biloxi.example.com>
Content-Type: application/sdp
Content-Length: ...
```

v=0

o=bob 2890844527 2890844527 IN IP4 client4.biloxi.example.com

```
s=
c=IN IP4 client4.biloxi.example.com
t=0 0
m=audio 3456 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F20 200 OK Proxy -> Alice

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
Record-Route: <sips:ss1.example.com;lr>
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=7137136
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:bob@client4.biloxi.example.com>
Content-Type: application/sdp
Content-Length: ...
```

```
v=0
o=bob 2890844527 2890844527 IN IP4 client4.biloxi.example.com
s=
c=IN IP4 client4.biloxi.example.com
t=0 0
m=audio 3456 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F21 ACK Alice -> Proxy

```
ACK sips:bob@client4.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf
Route: <sips:ss1.example.com;lr>
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=7137136
Call-ID: 12345600@atlanta.example.com
CSeq: 1 ACK
Content-Length: 0
```

F22 ACK Proxy -> B4

```
ACK sips:bob@client4.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK8374
```

```
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf
;received=192.0.2.103
Max-Forwards: 69
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=7137136
Call-ID: 12345600@atlanta.example.com
CSeq: 1 ACK
Content-Length: 0
```

/\* RTP streams are established between A and B4 \*/

/\* User B4 Hangs Up with User A. \*/

F23 BYE B4 -> Proxy

```
BYE sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS client4.biloxi.example.com:5061
;branch=z9hG4bKnashds7
Route: <sips:ss1.example.com;lr>
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=7137136
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345600@atlanta.example.com
CSeq: 1 BYE
Content-Length: 0
```

F24 BYE Proxy -> Alice

```
BYE sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83754
Via: SIP/2.0/TLS client4.biloxi.example.com:5061
;branch=z9hG4bKnashds7
;received=192.0.2.105
Max-Forwards: 69
From: Bob <sips:bob@biloxi.example.com>;tag=7137136
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345600@atlanta.example.com
CSeq: 1 BYE
Content-Length: 0
```

F25 200 OK Alice -> Proxy

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS ss1.example.com:5061
;branch=z9hG4bK83754
```

```
;received=192.0.2.54
Via: SIP/2.0/TLS client4.biloxi.example.com:5061
;branch=z9hG4bKnashds7
;received=192.0.2.105
From: Bob <sips:bob@biloxi.example.com>;tag=7137136
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345600@atlanta.example.com
CSeq: 1 BYE
Content-Length: 0
```


F26 200 OK Proxy -> B4

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client4.biloxi.example.com:5061
;branch=z9hG4bKnashds7
;received=192.0.2.105
From: Bob <sips:bob@biloxi.example.com>;tag=7137136
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345600@atlanta.example.com
CSeq: 1 BYE
Content-Length: 0
```

---

[TOC](#)

## 2.13. Call Management (Incoming Call Screening)



Bob has an incoming call screening list, Alice is included on the list of addresses Bob will not accept calls from. Alice attempts to call Bob. Messages F1, F2, and F3 are included to show that Bob does not accept INVITEs that have not been screened by the proxy.

Note that call screening can not be done using the From header - instead some form of authentication credentials must be used.

The screening proxy inserts an announcement URI in an Error-Info header field which Alice accesses by sending an INVITE to listen to the

Announcement. The Announcement Server uses the automaton and rendering feature tags in F12 and F13 to indicate that it is a media server only capability of playing announcements.

#### Message Details

F1 INVITE Alice -> Bob

```
INVITE sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000

/* Bob only accepts INVITEs that have been screened
   by the proxy */
```

F2 305 Use Proxy Bob -> Alice

```
SIP/2.0 305 Use Proxy
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=342123
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:ss1.example.com>
Content-Length: 0
```

F3 ACK Alice -> Bob

```
ACK sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
```

```

To: Bob <sips:bob@biloxi.example.com>;tag=342123
Call-ID: 12345600@atlanta.example.com
CSeq: 1 ACK
Content-Length: 0

/* A retries the call through the proxy */

F4 INVITE Alice -> Proxy 1

INVITE sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf0
Max-Forwards: 70
Route: <sips:ss1.example.com>
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 2 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000

/* Proxy 1 challenges Alice for authentication */

F5 407 Proxy Authentication Required Proxy 1 -> Alice

SIP/2.0 407 Proxy Authentication Required
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf0
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=7886765
Call-ID: 12345600@atlanta.example.com
CSeq: 2 INVITE
Proxy-Authenticate: Digest realm="example.com",
nonce="ea9c8e88df84f1cec4341ae6cbe5a359",
qop="auth", nc=00000001, cnonce="0a4f113b",
opaque="", stale=FALSE, qop="auth", algorithm=MD5
Content-Length: 0

```

F6 ACK Alice -> Proxy 1

```
ACK sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf0
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=7886765
Call-ID: 12345600@atlanta.example.com
CSeq: 2 ACK
Content-Length: 0
```

```
/* Alice responds by sending an INVITE with authentication
credentials in it. */
```

F7 INVITE Alice -> Proxy 1

```
INVITE sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf2
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 3 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Proxy-Authorization: Digest username="alice",
realm="example.com", qop="auth",
nc=00000001, cnonce="4gr84543ft2",
nonce="ae9137be1c87d175c2dd63302a0d6e0a",
opaque="", uri="sips:bob@biloxi.example.com",
response="bbaec39f943bdcb3620d90afc548a45c"
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F8 403 Screening Failure (Terminating) Proxy 1 -> Alice

```
SIP/2.0 403 Screening Failure (Terminating)
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf2
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=ffe254
Call-ID: 12345600@atlanta.example.com
CSeq: 3 INVITE
Error-Info: <sips:screen-fail-term-ann@ms.biloxi.example.com>
Content-Length: 0
```

F9 ACK Alice -> Proxy 1

```
ACK sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf2
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=ffe254
Call-ID: 12345600@atlanta.example.com
Proxy-Authorization: Digest username="alice",
realm="example.com", nonce="ae9137be1c87d175c2dd63302a0d6e0a",
opaque="", uri="sips:bob@biloxi.example.com",
response="bbaec39f943bdcb3620d90afc548a45c"
CSeq: 3 ACK
Content-Length: 0
```

/\* To hear the recording, Alice connects to the Error-Info URI \*/

F10 INVITE Alice -> Proxy 1

```
INVITE sips:screen-fail-term-ann@ms.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bfj
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 4 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Content-Type: application/sdp
Content-Length: ...
```

```
v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
```

```
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F11 200 OK Announcement Server -> Proxy 1

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bfj
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=234934
Call-ID: 12345600@atlanta.example.com
CSeq: 4 INVITE
Contact: <sips:ms.biloxi.example.com>
;automaton;+sip.rendering="no"
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Content-Type: application/sdp
Content-Length: ...

v=0
o=annnc 2890844543 2890844543 IN IP4 announce.biloxi.example.com
s=
c=IN IP4 announce.biloxi.example.com
t=0 0
m=audio 49174 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F12 ACK Alice -> Announcement Server

```
ACK sips:ms.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74b32
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=234934
Call-ID: 12345600@atlanta.example.com
CSeq: 4 ACK
Content-Length: 0
```

/\* Announcement Server plays announcement then disconnects \*/

F13 BYE Announcement Server -> Alice

```
BYE sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS announcement.example.com:5061
;branch=z9hG4bK74bKS
```

```

Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=234934
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345600@atlanta.example.com
CSeq: 2334 BYE
Content-Length: 0

```

F14 200 OK Alice -> Announcement Server


```

SIP/2.0 200 OK
Via: SIP/2.0/TLS announcement.example.com:5061
;branch=z9hG4bK74bKS
;received=192.0.2.103
From: Bob <sips:bob@biloxi.example.com>;tag=234934
To: Alice <sips:alice@atlanta.example.com>;tag=1234567
Call-ID: 12345600@atlanta.example.com
CSeq: 2334 BYE
Content-Length: 0

```

## 2.14. Call Management (Outgoing Call Screening)

[TOC](#)



Alice has an outgoing call screening list, Bob is included on the list of addresses Alice will not be able to place a call to. Alice attempts to call Bob.

Alice could establish a session to listen to the announcement in the Error-Info header field.

## Message Details

F1 INVITE Alice -> Proxy 1

```
INVITE sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

/\* Proxy 1 challenges Alice for authentication \*/

F2 407 Proxy Authentication Required Proxy 1 -> Alice

```
SIP/2.0 407 Proxy Authentication Required
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=90210
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Proxy-Authenticate: Digest realm="example.com",
nonce="ea9c8e88df84f1cec4341ae6cbe5a359",
qop=auth, nc=00000001, cnonce="0a4f113b",
opaque="", stale=FALSE, algorithm=MD5
Content-Length: 0
```

F3 ACK Alice -> Proxy 1

```
ACK sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
```

```
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:biloxi.example.com>;tag=90210
Call-ID: 12345600@atlanta.example.com
CSeq: 1 ACK
Content-Length: 0
```

```
/* Alice responds by sending an INVITE with authentication
credentials in it. */
```

```
F4 INVITE Alice -> Proxy 1
```

```
INVITE sips:biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74b4
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 2 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Proxy-Authorization: Digest username="alice", realm="example.com",
nonce="cb360afc54bbaec39f943bd820d9a45c", opaque="",
uri="sips:biloxi.example.com",
response="b9d2e5bcd9f69ab2a9b44f270285a6"
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

```
F5 403 Screening Failure (Originating) Proxy 1 -> Alice
```

```
SIP/2.0 403 Screening Failure (Originating)
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74b4
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:biloxi.example.com>;tag=18017
Call-ID: 12345600@atlanta.example.com
CSeq: 2 INVITE
Error-Info: <sips:screen-fail-orig-ann@announcement.example.com>
```

Content-Length: 0

F6 ACK Alice -> Proxy 1


ACK sips:bob@biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74b4  
Max-Forwards: 70  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=18017  
Call-ID: 12345600@atlanta.example.com  
CSeq: 2 ACK  
Proxy-Authorization: Digest username="alice", realm="example.com",  
nonce="cb360afc54bbaec39f943bd820d9a45c", opaque="",  
uri="sips:bob@biloxi.example.com",  
response="b9d2e5bcdec9f69ab2a9b44f270285a6"


Content-Length: 0

---

[TOC](#)

## **2.15. Call Park**





In this example, Alice calls Bob. Bob then parks the call at the Park Server by sending a REFER to the Park Server. The server sends an INVITE to Alice which replaces the session between Alice and Bob. The Park Server utilizes the automaton, rendering, and byeless feature tags in F9 to indicate its capabilities to Alice. The call is accepted by Alice and causes Alice to send a BYE to Bob. Bob receives notification of the successful park, and also receives the dialog identifiers in the application/sip body of the NOTIFY response.

Carol wishes to retrieve the call, so she sends an INVITE containing the dialog identifiers to Alice which replaces the session with the Park Server. Alice accepts the call and sends a BYE to the Park Server. Carol obtains the dialog identifiers from a NOTIFY from the Park Server.

Note that this call flow is a special case of call transfer.

Note also that this flow could also be used for Music on Hold.

Message Details.

F1 INVITE Alice -> Bob

```
INVITE sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.alice.example.com:5061
;branch=z9hG4bKnashds7
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345601@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:a8342043f@atlanta.example.com;gr>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, SUBSCRIBE, NOTIFY
Supported: replaces, gruu
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F2 180 Ringing Bob -> Alice

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bKnashds7
;received=192.0.2.105
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 12345601@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:bob@client.biloxi.example.com>
Content-Length: 0
```

F3 200 OK Bob -> Alice

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bKnashds7
;received=192.0.2.105
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 12345601@atlanta.example.com
```

```
CSeq: 1 INVITE
Contact: <sips:bob@client.biloxi.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, SUBSCRIBE, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...
```

```
v=0
o=bob 2890844527 2890844527 IN IP4 client.biloxi.example.com
s=
c=IN IP4 client.biloxi.example.com
t=0 0
m=audio 3456 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F4 ACK Alice -> Bob

```
ACK sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bKnashds7
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 12345601@atlanta.example.com
CSeq: 1 ACK
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, SUBSCRIBE, NOTIFY
Supported: replaces
Content-Length: 0
```

```
/* Bob REFERs Park Server to establish session with A
   which replaces the established session between A and B.
   Note that there is no session established between B
   and the Park Server. */
```

F5 REFER Bob -> Park Server

```
REFER sips:park@server.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds9
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=02134
To: Park Server <sips:park@server.example.com>
Call-ID: 4802029847@biloxi.example.com
CSeq: 1 REFER
<allOneLine>
Refer-To: <sips:a8342043f@atlanta.example.com;gr?Replaces=
12345601%40atlanta.example.com%3Bfrom-tag%3D314159
%3Bto-tag%3D1234567&Require=replaces>
```

```
</allOneLine>
    Referred-By: <sips:bob@biloxi.example.com>
    Contact: <sips:bob@client.biloxi.example.com>
    Content-Length: 0
```

F6 202 Accepted Park Server -> Bob

```
SIP/2.0 202 Accepted
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds9
;received=192.0.2.105
From: Bob <sips:bob@biloxi.example.com>;tag=02134
To: Park Server <sips:park@server.example.com>;tag=56323
Call-ID: 4802029847@biloxi.example.com
Contact: <sips:park@server.example.com>
CSeq: 1 REFER
Content-Length: 0
```

F7 NOTIFY Park Server -> Bob

```
NOTIFY sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS server.example.com:5061
;branch=z9hG4bK74bT6
To: Bob <sips:bob@biloxi.example.com>;tag=02134
Max-Forwards: 70
From: Park Server <sips:park@server.example.com>;tag=56323
Call-ID: 4802029847@biloxi.example.com
CSeq: 1 NOTIFY
Event: refer
Contact: <sips:park@server.example.com>
Subscription-State: active;expires=60
Content-Type: message/sipfrag
Content-Length: ...
```

SIP/2.0 100 Trying

F8 200 OK Bob -> Park Server

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS server.example.com:5061
;branch=z9hG4bK74bT6
;received=192.0.2.103
To: Bob <sips:bob@biloxi.example.com>;tag=02134
From: Park Server <sips:park@server.example.com>;tag=56323
Call-ID: 4802029847@biloxi.example.com
CSeq: 1 NOTIFY
Content-Length: 0
```

```

/* Park Server places call to Alice to replace session
   between Alice and Bob. */

F9 INVITE Park Server -> Alice

INVITE sips:a8342043f@atlanta.example.com;gr SIP/2.0
Via: SIP/2.0/TLS server.example.com:5061
;branch=z9hG4bK74rf
Max-Forwards: 70
From: <sips:park@server.example.com>;tag=0111
To: <sips:a8342043f@atlanta.example.com;gr>
Call-ID: a5-75-34-12-76@server.example.com
CSeq: 1 INVITE
Referred-By: <sips:bob@biloxi.example.com>
Contact: <sips:park@server.example.com>;automaton
;+sip.byeless;+sip.rendering="no"
Require: replaces
Replaces: 12345601@atlanta.example.com
;from-tag=314159;to-tag=1234567
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, SUBSCRIBE, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...

v=0
o=ParkServer 2890844576 2890844576 IN IP4 Park.server.example.com
s=
c=IN IP4 server.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000


F10 200 OK Alice -> Park Server

SIP/2.0 200 OK
Via: SIP/2.0/TLS server.example.com:5061
;branch=z9hG4bK74rf
;received=192.0.2.103
From: <sips:park@server.example.com>;tag=0111
To: <sips:a8342043f@atlanta.example.com;gr>;tag=098594
Call-ID: a5-75-34-12-76@server.example.com
CSeq: 1 INVITE
Contact: <sips:a8342043f@atlanta.example.com;gr>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, SUBSCRIBE, NOTIFY
Supported: replaces, gruu
Content-Type: application/sdp
Content-Length: ...

```

```
v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
a=recvonly
```

F11 ACK Park Server -> Alice

```
ACK sips:a8342043f@atlanta.example.com;gr SIP/2.0
Via: SIP/2.0/TLS server.example.com:5061
;branch=z9hG4bK7rfF
Max-Forwards: 70
From: <sips:park@server.example.com>;tag=0111
To: <sips:a8342043f@atlanta.example.com;gr>;tag=098594
Call-ID: a5-75-34-12-76@server.example.com
CSeq: 1 ACK
Content-Length: 0
```

F12 BYE Alice -> Bob

```
BYE sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bKnashds7
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 12345601@atlanta.example.com
CSeq: 2 BYE
Content-Length: 0
```

F13 200 OK Bob -> Alice

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bKnashds7
;received=192.0.2.105
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 12345601@atlanta.example.com
CSeq: 2 BYE
Content-Length: 0
```

```
/* Park Server reports success back to Bob by returning  
a 200 OK response. Bob obtains the dialog identifiers  
from the headers included in the response. */
```

F14 NOTIFY Park Server -> Bob

```
NOTIFY sips:bob@client.biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS server.example.com:5061  
;branch=z9hG4bK74bf9  
To: Bob <sips:bob@biloxi.example.com>;tag=02134  
Max-Forwards: 70  
From: Park Server <sips:park@server.example.com>;tag=56323  
Call-ID: 4802029847@biloxi.example.com  
CSeq: 2 NOTIFY  
Event: refer  
Subscription-State: terminated;reason=noresource  
Contact: <sips:park@server.example.com>;automaton  
:+sip.byeless;+sip.rendering="no"  
Content-Type: message/sipfrag  
Content-Length: ...
```

```
SIP/2.0 200 OK  
Via: SIP/2.0/TLS server.example.com:5061  
;branch=z9hG4bK74rf  
;received=192.0.2.103  
From: <sips:park@server.example.com>;tag=0111  
To: <sips:a8342043f@atlanta.example.com;gr>;tag=098594  
Call-ID: a5-75-34-12-76@server.example.com  
CSeq: 1 INVITE  
Contact: <sips:a8342043f@atlanta.example.com;gr>
```

F15 200 OK Bob -> Park Server

```
SIP/2.0 200 OK  
Via: SIP/2.0/TLS server.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
To: Bob <sips:bob@biloxi.example.com>;tag=02134  
From: Park Server <sips:park@server.example.com>;tag=56323  
Call-ID: 4802029847@biloxi.example.com  
CSeq: 2 NOTIFY  
Content-Length: 0
```

```
/* Alice is now parked at the Park Server */
```

```
/* Carol picks up the call by sending an INVITE to A which  
replaces the existing session with the Park/Park Server.  
Carol needs to know the dialog information to construct
```

the Replaces header. \*/

F16 SUBSCRIBE Carol -> Park Server

SUBSCRIBE sips:bob@biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS client.chicago.example.com:5061  
;branch=z9hG4bK74b232  
Max-Forwards: 70  
From: Carol <sips:carol@chicago.example.com>;tag=158x93461  
To: <sips:park@server.example.com>  
Call-ID: 2d6485356dfaj34dsf  
CSeq: 1 SUBSCRIBE  
Contact: <sips:carol@client.chicago.example.com>  
Event: dialog  
Expires: 0  
Accept: application/dialog-info+xml  
Content-Length: 0

F17 200 OK Park Server -> Carol

SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.chicago.example.com:5061  
;branch=z9hG4bK74b232  
;received=192.0.2.105  
From: Carol <sips:carol@chicago.example.com>;tag=158x93461  
To: <sips:park@server.example.com>;tag=3213j  
Call-ID: 2d6485356dfaj34dsf  
CSeq: 1 SUBSCRIBE  
Contact: <sips:park@server.example.com>;automaton  
;+sip.byeless;+sip.rendering="no"  
Content-Length: 0

F18 NOTIFY Park Server -> Carol

NOTIFY sips:carol@client.example.com SIP/2.0  
Via: SIP/2.0/TLS server.example.com:5061  
;branch=z9hG4bK74b8skd  
Max-Forwards: 70  
To: Carol <sips:carol@chicago.example.com>;tag=158x93461  
From: <sips:park@server.example.com>;tag=3213j  
Call-ID: 2d6485356dfaj34dsf  
CSeq: 1 NOTIFY  
Contact: <sips:park@server.example.com>;automaton  
;+sip.byeless;+sip.rendering="no"  
Event: dialog  
Subscription-State: terminated;reason=timeout

```
Content-Type: application/dialog-info+xml
Content-Length: ...

<?xml version="1.0"?>
<dialog-info xmlns="urn:ietf:params:xml:ns:dialog-info"
    version="0" state="full" entity="sips:park@server.example.com">
    <dialog id="439920143524" call-id="a5-75-34-12-76@server.example.com"
        local-tag="0111" remote-tag="098594"
            direction="initiator">
        <duration>1</duration>
        <local>
            <target>sips:park@server.example.com</target>
        </local>
        <remote>
            <target>sips:a8342043f@atlanta.example.com;gr</target>
        </remote>
        <state>confirmed</state>
    </dialog>
</dialog-info>
```

F19 200 OK Carol -> Park Server

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS server.example.com:5061
;branch=z9hG4bK74b8skd
;received=192.0.2.103
To: Carol <sips:carol@chicago.example.com>;tag=158x93461
From: <sips:park@server.example.com>;tag=3213j
Call-ID: 2d6485356dfaj34dsf
CSeq: 1 NOTIFY
Contact: <sips:carol@client.chicago.example.com>
Content-Length: 0
```

F20 INVITE Carol -> Alice

```
INVITE sips:alice@atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS client.chicago.example.com:5061
;branch=z9hG4bK74bQ2
Max-Forwards: 70
From: Carol <sips:carol@chicago.example.com>;tag=5893461
To: Alice <sips:alice@atlanta.example.com>
Call-ID: 6485356@chicago.example.com
CSeq: 1 INVITE
Contact: <sips:carol@client.chicago.example.com>
Require: replaces
Replaces: a5-75-34-12-76@server.example.com
;to-tag=098594;from-tag=0111
```

Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER,  
SUBSCRIBE, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...

v=0  
o=carol 2890844922 2890844922 IN IP4 client.chicago.example.com  
s=  
c=IN IP4 client.chicago.example.com  
t=0 0  
m=audio 3456 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F21 200 OK Alice -> Carol

SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.chicago.example.com:5061  
;branch=z9hG4bK74bQ2  
;received=192.0.2.105  
From: Carol <sips:carol@chicago.example.com>;tag=5893461  
To: Alice <sips:alice@atlanta.example.com>;tag=222  
Call-ID: 6485356@chicago.example.com  
CSeq: 1 INVITE  
Contact: <sips:a8342043f@atlanta.example.com;gr>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, SUBSCRIBE, NOTIFY  
Supported: replaces, gruu  
Content-Type: application/sdp  
Content-Length: ...

v=0  
o=alice 2890844527 2890844527 IN IP4 client.atlanta.example.com  
s=  
c=IN IP4 client.atlanta.example.com  
t=0 0  
m=audio 49170 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F22 ACK Carol -> Alice

ACK sips:a8342043f@atlanta.example.com;gr SIP/2.0  
Via: SIP/2.0/TLS client.chicago.example.com:5061  
;branch=z9hG4bK74bJ0  
Max-Forwards: 70  
From: Carol <sips:carol@chicago.example.com>;tag=5893461  
To: Alice <sips:alice@atlanta.example.com>;tag=222  
Call-ID: 6485356@chicago.example.com  
CSeq: 1 ACK

Content-Length: 0

```
/* A replaces the session to the Park Server with the new  
session with C and generates a BYE to disconnect the  
Park Server. */
```


F23 BYE Alice -> Park Server

```
BYE sips:park@server.example.com SIP/2.0  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74b4N  
Max-Forwards: 70  
From: Alice <sips:alice@atlanta.example.com>;tag=098594  
To: <sips:park@server.example.com>;tag=0111  
Call-ID: a5-75-34-12-76@server.example.com  
CSeq: 1 BYE  
Content-Length: 0
```

F24 200 OK Park Server -> Alice

```
SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74b4N  
;received=192.0.2.103  
From: Alice <sips:alice@atlanta.example.com>;tag=098594  
To: <sips:park@server.example.com>;tag=0111  
Call-ID: a5-75-34-12-76@server.example.com  
CSeq: 1 BYE  
Content-Length: 0
```

## 2.16. Call Pickup



Bob and Bill are part of a work group at example.com that can pick up each other's calls. Alice calls Bob who does not answer. Bill wishes to pick up the call and sends a SUBSCRIBE to Bob to retrieve the dialog information. Bill then generates an INVITE with a Replaces to Alice. Alice answers the INVITE and sends a CANCEL to stop Bob's phone ringing. Note that the relative order of the 487/ACK sequence (F11/F12) and the 200 OK to the CANCEL (F10) is not deterministic.

This call flow shows the use of the "early-only" parameter [[RFC3891](#)] ([Mahy, R., Biggs, B., and R. Dean, "The Session Initiation Protocol \(SIP\) "Replaces" Header," September 2004.](#)) in the Replaces header field of F7. This parameter prevents Alice from accepting the INVITE if Bob has already accepted the INVITE. If Bill had wished to "take" the call from Bob regardless of whether he had answered, the parameter would not have been present in F7.

Also note that the subscription between Bob and Carol could have been established prior to Alice's call.

Message Details

F1 INVITE Alice -> Bob

```
INVITE sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:a8342043f@atlanta.example.com;gr>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces, gruu
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F2 180 Ringing Bob -> Alice

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bill@biloxi.example.com>;tag=8675309
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:bill@biloxi.example.com>
Content-Length: 0
```

/\* Bill decides to pick up the call. \*/

F3 SUBSCRIBE Bill -> Bob

```
SUBSCRIBE sips:bill@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS pc.biloxi.example.com:5061
;branch=z9hG4bK74bf
Max-Forwards: 70
From: Bill <sips:bill@biloxi.example.com>;tag=8675309
```

```
To: Bob <sips:bob@biloxi.example.com>
Call-ID: rt4353gs2egg@pc.biloxi.example.com
CSeq: 1 SUBSCRIBE
Contact: <sips:bill@pc.biloxi.example.com>
Event: dialog
Expires: 0
Accept: application/dialog-info+xml
Content-Length: 0
```

F4 200 OK Bob -> Bill

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS pc.biloxi.example.com:5061
;branch=z9hG4bK74bf
;received=192.0.2.114
Max-Forwards: 70
From: Bill <sips:bill@biloxi.example.com>;tag=8675309
To: Bob <sips:bob@biloxi.example.com>;tag=31451098
Call-ID: rt4353gs2egg@pc.biloxi.example.com
CSeq: 1 SUBSCRIBE
Content-Length: 0
```

F5 NOTIFY Bob -> Bill

```
NOTIFY sips:bill@pc.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bK74br
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=31451098
To: Bill <sips:bill@biloxi.example.com>;tag=8675309
Call-ID: rt4353gs2egg@pc.biloxi.example.com
CSeq: 1 NOTIFY
Contact: <sips:bill@client.biloxi.example.com>
Event: dialog
Subscription-State: terminated;reason=timeout
Content-Type: application/dialog-info+xml
Content-Length: ...

<?xml version="1.0"?>
<dialog-info xmlns="urn:ietf:params:xml:ns:dialog-info"
    version="0" state="full" entity="sips:bill@biloxi.example.com">
    <dialog id="94992014524" call-id="12345600@atlanta.example.com"
        local-tag="3145678" remote-tag="1234567"
        direction="recipient">
        <duration>1</duration>
        <local>
            <identity display="Bob">sips:bill@biloxi.example.com</identity>
```

```

        <target>sips:bob@client.biloxi.example.com</target>
    </local>
    <remote>
        <identity display="Alice">sips:alice@atlanta.example.com
                                              </identity>
        <target>sips:a8342043@atlanta.example.com;gr</target>
    </remote>
    <state>early</state>
    </dialog>
</dialog-info>
```

F6 200 OK Bill -> Bob

SIP/2.0 200 OK  
 Via: SIP/2.0/TLS client.biloxi.example.com:5061  
 ;branch=z9hG4bK74br  
 ;received=192.0.2.105  
 From: Bob <sips:bob@biloxi.example.com>;tag=31451098  
 To: Bill <sips:bill@biloxi.example.com>;tag=8675309  
 Call-ID: rt4353gs2egg@pc.biloxi.example.com  
 CSeq: 1 NOTIFY  
 Contact: <sips:bill@pc.biloxi.example.com>  
 Content-Length: 0

F7 INVITE Bill -> Alice

INVITE sips:a8342043f@atlanta.example.com;gr SIP/2.0  
 Via: SIP/2.0/TLS pc.biloxi.example.com:5061  
 ;branch=z9hG4bK74HH  
 Max-Forwards: 70  
 From: Bill <sips:bill@biloxi.example.com>;tag=8675310  
 To: Alice <sips:alice@atlanta.example.com>  
 Call-ID: 563456212@b2.biloxi.example.com  
 CSeq: 1 INVITE  
 Require: replaces  
 Replaces: 12345600@atlanta.example.com  
 ;from-tag=314578;to-tag=1234567;early-only  
 Contact: <sips:bill@pc.biloxi.example.com>  
 Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY  
 Supported: replaces  
 Content-Type: application/sdp  
 Content-Length: ...  
  
 v=0  
 o=bill 2890843122 2890843122 IN IP4 pc.biloxi.example.com  
 s=  
 c=IN IP4 pc.biloxi.example.com

```
t=0 0
m=audio 5342 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

```
/* Alice matches the dialog information in the Replaces header
   and accepts the INVITE. */
```

```
F8 200 OK Alice -> Bill
```

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS pc.biloxi.example.com:5061
;branch=z9hG4bK74HH
;received=192.0.2.114
From: Bill <sips:bill@biloxi.example.com>;tag=8675310
To: Alice <sips:alice@atlanta.example.com>;tag=131256
Call-ID: 563456212@b2.biloxi.example.com
CSeq: 1 INVITE
Contact: <sips:a8342043f@atlanta.example.com;gr>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces, gruu
Content-Type: application/sdp
Content-Length: ...
```

```
v=0
o=alice 289084543 289084543 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49172 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

```
/* Alice stops Bob's phone from ringing by sending a CANCEL */
```

```
F9 CANCEL Alice -> Bob
```

```
CANCEL sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 CANCEL
Content-Length: 0
```

```
F10 200 OK Bob -> Alice
```

SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=3145678  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 CANCEL  
Content-Length: 0

F11 487 Request Terminated Bob -> Alice

SIP/2.0 487 Request Terminated  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf9  
;received=192.0.2.103  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=3145678  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 INVITE  
Content-Length: 0

F12 ACK Alice -> Bob

ACK sips:bob@client.biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK83749.1  
Max-Forwards: 70  
From: Alice <sips:alice@atlanta.example.com>;tag=1234567  
To: Bob <sips:bob@biloxi.example.com>;tag=3145678  
Call-ID: 12345600@atlanta.example.com  
CSeq: 1 ACK  
Content-Length: 0

F13 ACK Bill -> Alice

ACK sips:a8342043f@atlanta.example.com;gr SIP/2.0  
Via: SIP/2.0/TLS pc.biloxi.example.com:5061  
;branch=z9hG4bK7435  
Max-Forwards: 70  
From: Bill <sips:bill@biloxi.example.com>;tag=8675310  
To: Alice <sips:alice@atlanta.example.com>;tag=131256  
Call-ID: 563456212@b2.biloxi.example.com  
CSeq: 1 ACK  
Content-Length: 0

```
/* RTP streams are established between Alice and Bill.  
Later, Alice Hangs Up with Bob. */
```

F14 BYE Alice -> Bill

```
BYE sips:bill@pc.biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf2  
Max-Forwards: 70  
To: Bill <sips:bill@biloxi.example.com>;tag=8675310  
From: Alice <sips:alice@atlanta.example.com>;tag=131256  
Call-ID: 563456212@b2.biloxi.example.com  
CSeq: 1 BYE  
Content-Length: 0
```

F15 200 OK Bill -> Alice

```
SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bf2  
;received=192.0.2.105  
To: Bill <sips:bill@biloxi.example.com>;tag=8675310  
From: Alice <sips:alice@atlanta.example.com>;tag=131256  
Call-ID: 563456212@b2.biloxi.example.com  
CSeq: 1 BYE  
Content-Length: 0
```

---

[TOC](#)

## **2.17. Automatic Redial**

Alice Bob

```
|           |
|   INVITE F1   |
|----->|
|486 Busy Here F2|
|<-----| Bob is busy
|   ACK F3   |
|----->|
|   SUBSCRIBE F4   |
|----->|
|   200 OK F5   |
|<-----|
|   NOTIFY F6   |
|<-----|
|   200 OK F7   |
|----->|
|           |
|   NOTIFY F8   | Bob is now available
|<-----|
|   200 OK F9   |
|----->|
|           |
|   INVITE F10  |
|----->| Session setup successfully
|   180 Ringing F11|
|<-----|
|   200 OK F12   |
|<-----|
|   ACK F13   |
|----->|
|   Media Session|
|=====|
|           |
|   NOTIFY F14   |
|<-----|
|   200 OK F15   |
|----->|
|           |
|   SUBSCRIBE F16 | Alice terminates subscription
|----->|
|   200 OK F17   |
|<-----|
|   NOTIFY F18   |
|<-----|
|   200 OK F19   |
|----->|
|           |
```

Bob is initially busy when Alice calls. Alice subscribes to Bob's call state using a SUBSCRIBE F4. Bob sends a NOTIFY F8 when Bob is available. Alice is alerted, then Alice sends an INVITE to Bob to establish the session. The subscription is terminated using SUBSCRIBE F16.

Message Details

F1 INVITE Alice -> Bob

```
INVITE sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:alice@client.atlanta.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, SUBSCRIBE, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...

v=0
o=alice 2890844526 2890844526 IN IP4 client.atlanta.example.com
s=
c=IN IP4 client.atlanta.example.com
t=0 0
m=audio 49170 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F2 486 Busy Here

```
SIP/2.0 486 Busy Here
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=982039i4
Call-ID: 12345600@atlanta.example.com
CSeq: 1 INVITE
Content-Length: 0
```

F3 ACK Alice -> Bob

```
ACK sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK74bf9
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=982039i4
Call-ID: 12345600@atlanta.example.com
CSeq: 1 ACK
```

Content-Length: 0

F4 SUBSCRIBE Alice -> Bob

SUBSCRIBE sips:bob@biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74b8G  
Max-Forwards: 70  
From: Alice <sips:alice@atlanta.example.com>;tag=837348234  
To: Bob <sips:bob@biloxi.example.com>  
Call-ID: 4524526232@atlanta.example.com  
CSeq: 1 SUBSCRIBE  
Contact: sips:alice@client.atlanta.example.com  
Event: dialog  
Accept: application/dialog-info+xml  
Content-Length: 0

F5 200 OK Bob -> Alice

SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74b8G  
;received=192.0.2.103  
From: Alice <sips:alice@atlanta.example.com>;tag=837348234  
To: Bob <sips:bob@biloxi.example.com>;tag=341123  
Call-ID: 4524526232@atlanta.example.com  
Expires: 60  
CSeq: 1 SUBSCRIBE  
Contact: sips:bob@client.biloxi.example.com  
Content-Length: 0

F6 NOTIFY Bob -> Alice

NOTIFY sips:alice@client.atlanta.example.com SIP/2.0  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bK74bn2  
Max-Forwards: 70  
From: Bob <sips:bob@biloxi.example.com>;tag=341123  
To: Alice <sips:alice@atlanta.example.com>;tag=837348234  
Call-ID: 4524526232@atlanta.example.com  
CSeq: 1 NOTIFY  
Contact: <sips:bob@client.biloxi.example.com>  
Event: dialog  
Subscription-State: active;expires=59  
Content-Type: application/dialog-info+xml  
Content-Length: ...

```
<?xml version="1.0"?>
<dialog-info xmlns="urn:ietf:params:xml:ns:dialog-info"
    version="0" state="full" entity="sips:bob@biloxi.example.com">
    <dialog id="562623442g3">
        <duration>1</duration>
        <state>confirmed</state>
    </dialog>
</dialog-info>
```

F7 200 OK Alice -> Bob

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bK74bn2
;received=192.0.2.105
From: Bob <sips:bob@biloxi.example.com>;tag=341123
To: Alice <sips:alice@atlanta.example.com>;tag=837348234
Call-ID: 4524526232@atlanta.example.com
CSeq: 1 NOTIFY
Content-Length: 0
```

/\* Bob is now available. \*/

F8 NOTIFY Bob -> Alice

```
NOTIFY sips:alice@atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bK74bVi
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=341123
To: Alice <sips:alice@atlanta.example.com>;tag=837348234
Call-ID: 4524526232@atlanta.example.com
CSeq: 2 NOTIFY
Event: dialog
Subscription-State: active;expires=27
Contact: <sips:bob@client.biloxi.example.com>
Content-Type: application/dialog-info+xml
Content-Length: ...
```

```
<?xml version="1.0"?>
<dialog-info xmlns="urn:ietf:params:xml:ns:dialog-info"
    version="0" state="full" entity="sips:bob@biloxi.example.com">
    <dialog id="562623442g3">
        <state>terminated</state>
    </dialog>
</dialog-info>
```

F9 200 OK Alice -> Bob

SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bK74bVi  
;received=192.0.2.105  
From: Bob <sips:bob@biloxi.example.com>;tag=341123  
To: Alice <sips:alice@atlanta.example.com>;tag=837348234  
Call-ID: 4524526232@atlanta.example.com  
CSeq: 2 NOTIFY  
Content-Length: 0

F10 INVITE Alice -> Bob

INVITE sips:bob@biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bfq  
Max-Forwards: 70  
From: Alice <sips:alice@atlanta.example.com>;tag=f23fg14k  
To: Bob <sips:bob@biloxi.example.com>  
Call-ID: aoij4i9okitr@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:alice@client.atlanta.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, SUBSCRIBE, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...  
  
v=0  
o=alice 2890844826 2890844826 IN IP4 client.atlanta.example.com  
s=  
c=IN IP4 client.atlanta.example.com  
t=0 0  
m=audio 49170 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F11 180 Ringing Bob -> Alice

SIP/2.0 180 Ringing  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bfq  
;received=192.0.2.103  
From: Alice <sips:alice@atlanta.example.com>;tag=f23fg14k  
To: Bob <sips:bob@biloxi.example.com>;tag=23431  
Call-ID: aoij4i9okitr@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:bob@client.biloxi.example.com>  
Content-Length: 0

F12 200 OK Bob -> Alice

SIP/2.0 200 OK  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bfq  
;received=192.0.2.103  
From: Alice <sips:alice@atlanta.example.com>;tag=f23fg14k  
To: Bob <sips:bob@biloxi.example.com>;tag=23431  
Call-ID: aoij4i9okitr@atlanta.example.com  
CSeq: 1 INVITE  
Contact: <sips:bob@client.biloxi.example.com>  
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, SUBSCRIBE, NOTIFY  
Supported: replaces  
Content-Type: application/sdp  
Content-Length: ...  
  
v=0  
o=bob 2890854527 2890854527 IN IP4 client.biloxi.example.com  
s=  
c=IN IP4 client.biloxi.example.com  
t=0 0  
m=audio 3456 RTP/AVP 0  
a=rtpmap:0 PCMU/8000

F13 ACK Alice -> Bob

ACK sips:bob@client.biloxi.example.com SIP/2.0  
Via: SIP/2.0/TLS client.atlanta.example.com:5061  
;branch=z9hG4bK74bLBJ  
Max-Forwards: 70  
From: Alice <sips:alice@atlanta.example.com>;tag=f23fg14k  
To: Bob <sips:bob@biloxi.example.com>;tag=23431  
Call-ID: aoij4i9okitr@atlanta.example.com  
CSeq: 1 ACK  
Content-Length: 0

F14 NOTIFY Bob -> Alice

NOTIFY sips:alice@client.atlanta.example.com SIP/2.0  
Via: SIP/2.0/TLS client.biloxi.example.com:5061  
;branch=z9hG4bK4bnd2  
Max-Forwards: 70  
From: Bob <sips:bob@biloxi.example.com>;tag=341123  
To: Alice <sips:alice@atlanta.example.com>;tag=837348234  
Call-ID: 4524526232@atlanta.example.com  
CSeq: 3 NOTIFY

```
Contact: <sips:bob@client.biloxi.example.com>
Event: dialog
Subscription-State: active;expires=15
Content-Type: application/dialog-info+xml
Content-Length: ...

<?xml version="1.0"?>
<dialog-info xmlns="urn:ietf:params:xml:ns:dialog-info"
    version="0" state="full" entity="sips:bob@biloxi.example.com">
    <dialog id="62d2623442g3">
        <duration>1</duration>
        <state>confirmed</state>
    </dialog>
</dialog-info>
```

F15 200 OK Alice -> Bob

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bK4bnd2
;received=192.0.2.105
From: Bob <sips:bob@biloxi.example.com>;tag=341123
To: Alice <sips:alice@atlanta.example.com>;tag=837348234
Call-ID: 4524526232@atlanta.example.com
CSeq: 3 NOTIFY
Content-Length: 0
```

/\* Alice terminates the subscription \*/

F16 SUBSCRIBE Alice -> Bob

```
SUBSCRIBE sips:bob@client.biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK474b8
Max-Forwards: 70
From: Alice <sips:alice@atlanta.example.com>;tag=837348234
To: Alice <sips:alice@atlanta.example.com>;tag=837348234
Call-ID: 4524526232@atlanta.example.com
CSeq: 2 SUBSCRIBE
Contact: sips:alice@client.atlanta.example.com
Event: dialog
Expires: 0
Accept: application/dialog-info+xml
Content-Length: 0
```

F17 200 OK Bob -> Alice

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.atlanta.example.com:5061
;branch=z9hG4bK474b8
;received=192.0.2.103
From: Alice <sips:alice@atlanta.example.com>;tag=837348234
To: Bob <sips:bob@biloxi.example.com>;tag=341123
Call-ID: 4524526232@atlanta.example.com
Expires: 0
CSeq: 2 SUBSCRIBE
Contact: sips:bob@client.biloxi.example.com
Content-Length: 0
```


F18 NOTIFY Bob -> Alice

```
NOTIFY sips:alice@client.atlanta.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKb5n2j
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=341123
To: Alice <sips:alice@atlanta.example.com>;tag=837348234
Call-ID: 4524526232@atlanta.example.com
CSeq: 4 NOTIFY
Contact: <sips:bob@client.biloxi.example.com>
Event: dialog
Subscription-State: terminated;reason=noresource
Content-Type: application/dialog-info+xml
Content-Length: ...

<?xml version="1.0"?>
<dialog-info xmlns="urn:ietf:params:xml:ns:dialog-info"
    version="0" state="full" entity="sips:bob@biloxi.example.com">
    <dialog id="62d2623442g3">
        <duration>3</duration>
        <state>confirmed</state>
    </dialog>
</dialog-info>
```

F19 200 OK Alice -> Bob

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKb5n2j
;received=192.0.2.105
From: Bob <sips:bob@biloxi.example.com>;tag=341123
To: Alice <sips:alice@atlanta.example.com>;tag=837348234
Call-ID: 4524526232@atlanta.example.com
CSeq: 4 NOTIFY
```

**2.18. Click to Dial**[TOC](#)

In this example, while browsing the web on his PC, Bob clicks on Carol's SIP URI intending to establish a session with Carol. Bob's web browser passes the SIP URI to the SIP client on Bob's PC. The PC client is configured with the URI of Bob's SIP phone. A REFER is sent to the SIP phone which results in the establishment of the session between Bob and Carol.

Note that Bob's PC requests that no REFER dialog be established by the use of the `Refer-Sub: false` header field [\[RFC4488\] \(Levin, O., "Suppression of Session Initiation Protocol \(SIP\) REFER Method Implicit Subscription," May 2006.\)](#).

This flow is preferable to the 3pcc flow because the end-to-end SIP signaling is not interrupted by the 3pcc controller, and because Bob's experience of the call will not be marred by the lack of ringback tone or possible clipping. Suitable authorization of the REFER and explicit authorization of the triggered INVITE by Bob is necessary.

**Message Details**

```
/* Bob's PC SIP Client sends a REFER to Bob's SIP phone */
```

F1 REFER PC -> Bob

```
REFER sips:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS pc.biloxi.example.com:5061
;branch=z9hG4bKnashds7
Max-Forwards: 70
From: <sips:pc.biloxi.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>
Call-ID: 1234560183434
CSeq: 1 REFER
Refer-To: <sips:carol@chicago.example.com>
Refer-Sub: false
Contact: <sips:pc.biloxi.example.com>
Content-Length: 0
```

F2 202 Accepted Bob -> PC

```
SIP/2.0 202 Accepted
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashds7
;received=192.0.2.103
From: <sips:pc.biloxi.example.com>;tag=1234567
To: Bob <sips:bob@biloxi.example.com>;tag=314159
Call-ID: 1234560183434
Contact: <sips:bob@client.biloxi.example.com>
CSeq: 1 REFER
Refer-Sub: false
Content-Length: 0
```

F3 INVITE Bob -> Carol

```
INVITE sips:carol@chicago.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashdK9
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>
Call-ID: 7436222@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:bob@client.biloxi.example.com>
Referred-By: <sips:pc.biloxi.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...
```

```
v=0
o=bob 2890844539 2890844539 IN IP4 client.biloxi.example.com
s=
c=IN IP4 client.biloxi.example.com
t=0 0
m=audio 3458 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F4 180 Ringing Carol -> Bob

```
SIP/2.0 180 Ringing
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashdK9
;received=192.0.2.113
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>;tag=928287
Call-ID: 7436222@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:carol@client.chicago.example.com>
Content-Length: 0
```

F5 200 OK Carol -> Bob

```
SIP/2.0 200 OK
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashdK9
;received=192.0.2.113
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>;tag=928287
Call-ID: 7436222@atlanta.example.com
CSeq: 1 INVITE
Contact: <sips:carol@client.chicago.example.com>
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, NOTIFY
Supported: replaces
Content-Type: application/sdp
Content-Length: ...
```

```
v=0
o=carol 2890844527 2890844527 IN IP4 client.chicago.example.com
s=
c=IN IP4 client.chicago.example.com
t=0 0
m=audio 3456 RTP/AVP 0
a=rtpmap:0 PCMU/8000
```

F6 ACK Bob -> Carol

```
ACK sips:carol@client.chicago.example.com SIP/2.0
Via: SIP/2.0/TLS client.biloxi.example.com:5061
;branch=z9hG4bKnashd43
Max-Forwards: 70
From: Bob <sips:bob@biloxi.example.com>;tag=8675309
To: Carol <sips:carol@chicago.example.com>;tag=928287
Call-ID: 7436222@atlanta.example.com
CSeq: 1 ACK
Content-Length: 0
```

```
/* Bob and Carol now have established a session. */
```

---

### 3. Security Considerations

[TOC](#)

Since many of the examples in this document involve SIP call control, either peer-to-peer or 3pcc, the security considerations in the [Multiparty Framework document \(Mahy, R., Sparks, R., Rosenberg, J., Petrie, D., and A. Johnston, "A Call Control and Multi-party usage framework for the Session Initiation Protocol \(SIP\)," December 2009.\)](#) [I-D.ietf-sipping-cc-framework] apply.

Many of the services shown in this document rely on a particular user agent being part of a group. Members of a group could be, for example, employees within a particular department, a set of home phone extensions, members of a call center, etc. As such, user agents which are part of the group permit other group members special privileges and features. For example, while a user agent may not in general allow another user agent to learn detailed dialog information, this information might be shared with another group member in order to facilitate a service such as call pickup. Group members must be authenticated using normal SIP means such as certificates or shared secrets.

The service examples in this document make extensive use of the SIP call control primitives REFER, Replaces, Join, and the dialog package. The security considerations associated with each of these extensions [\[RFC3515\] \(Sparks, R., "The Session Initiation Protocol \(SIP\) Refer Method," April 2003.\)](#), [\[RFC3891\] \(Mahy, R., Biggs, B., and R. Dean, "The Session Initiation Protocol \(SIP\) "Replaces" Header," September 2004.\)](#), [\[RFC3911\] \(Mahy, R. and D. Petrie, "The Session Initiation Protocol \(SIP\) "Join" Header," October 2004.\)](#), [\[RFC4235\] \(Rosenberg, J., Schulzrinne, H., and R. Mahy, "An INVITE-Initiated Dialog Event Package for the Session Initiation Protocol \(SIP\)," November 2005.\)](#) apply to the scenarios in this document.

---

#### 4. IANA Considerations

[TOC](#)

None.

---

#### 5. Acknowledgements

[TOC](#)

The authors would like to thank the following reviewers of the document for their detailed comments and corrections: Vijay Gurbani, John Elwell, Joel Repiquet, Nagesh Kumar, Chandra Ravipati, Eric Burger, Jeroen Bemmel, Miguel Garcia, and Dale Worley.

The Transfer - Instant Messaging call flow is based on the "IM-a-call" call flow by Jonathan Rosenberg and Henning Schulzrinne. The Automatic Call Back call flow is based on a call flow by Adam Roach. The authors wish to thank the following individuals for their assistance and review of this call flows document: Joel Repiquet, Aki Neimi, Rohan Mahy, Jonathan Rosenberg, Hemant Agrawal, Henry Sinnreich, Dean Willis, David Devanatham, Joe Pizzimenti, Matt Cannon, John Hearty, the whole MCI WorldCom IPOP Design team, Scott Orton, Greg Osterhout, Pat Sollee, Doug Weisenberg, Danny Mistry, Steve McKinnon, and Denise Ingram, Denise Caballero, Tom Redman, Ilya Slain, Pat Sollee, John Truetken, and others from MCI WorldCom, 3Com, Cisco, Lucent and Nortel.

---

#### 6. References

[TOC](#)

##### 6.1. Normative References

[TOC](#)

[RFC3261]	Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M., and E. Schooler, " <a href="#">SIP: Session Initiation Protocol</a> ," RFC 3261, June 2002 ( <a href="#">TXT</a> ).
[RFC3515]	Sparks, R., " <a href="#">The Session Initiation Protocol (SIP) Refer Method</a> ," RFC 3515, April 2003 ( <a href="#">TXT</a> ).
[RFC3891]	Mahy, R., Biggs, B., and R. Dean, " <a href="#">The Session Initiation Protocol (SIP) "Replaces" Header</a> ," RFC 3891, September 2004 ( <a href="#">TXT</a> ).
[RFC3264]	Rosenberg, J. and H. Schulzrinne, " <a href="#">An Offer/Answer Model with Session Description Protocol (SDP)</a> ," RFC 3264, June 2002 ( <a href="#">TXT</a> ).
[RFC3265]	Roach, A., " <a href="#">Session Initiation Protocol (SIP)-Specific Event Notification</a> ," RFC 3265, June 2002 ( <a href="#">TXT</a> ).

[RFC4235]	Rosenberg, J., Schulzrinne, H., and R. Mahy, " <a href="#">An INVITE-Initiated Dialog Event Package for the Session Initiation Protocol (SIP)</a> ," RFC 4235, November 2005 ( <a href="#">TXT</a> ).
[RFC3911]	Mahy, R. and D. Petrie, " <a href="#">The Session Initiation Protocol (SIP) "Join" Header</a> ," RFC 3911, October 2004 ( <a href="#">TXT</a> ).
[RFC3840]	Rosenberg, J., Schulzrinne, H., and P. Kyzivat, " <a href="#">Indicating User Agent Capabilities in the Session Initiation Protocol (SIP)</a> ," RFC 3840, August 2004 ( <a href="#">TXT</a> ).
[RFC4579]	Johnston, A. and O. Levin, " <a href="#">Session Initiation Protocol (SIP) Call Control - Conferencing for User Agents</a> ," BCP 119, RFC 4579, August 2006 ( <a href="#">TXT</a> ).
[RFC3428]	Campbell, B., Rosenberg, J., Schulzrinne, H., Huitema, C., and D. Gurle, " <a href="#">Session Initiation Protocol (SIP) Extension for Instant Messaging</a> ," RFC 3428, December 2002 ( <a href="#">TXT</a> ).
[RFC4488]	Levin, O., " <a href="#">Suppression of Session Initiation Protocol (SIP) REFER Method Implicit Subscription</a> ," RFC 4488, May 2006 ( <a href="#">TXT</a> ).

## 6.2. Informative References

[TOC](#)

[I-D.ietf-sipping-cc-transfer]	Sparks, R. and A. Johnston, " <a href="#">Session Initiation Protocol Call Control - Transfer</a> ," draft-ietf-sipping-cc-transfer-12 (work in progress), March 2009 ( <a href="#">TXT</a> ).
[I-D.ietf-sipping-cc-framework]	Mahy, R., Sparks, R., Rosenberg, J., Petrie, D., and A. Johnston, " <a href="#">A Call Control and Multi-party usage framework for the Session Initiation Protocol (SIP)</a> ," draft-ietf-sipping-cc-framework-12 (work in progress), December 2009 ( <a href="#">TXT</a> ).
[RFC3665]	Johnston, A., Donovan, S., Sparks, R., Cunningham, C., and K. Summers, " <a href="#">Session Initiation Protocol (SIP) Basic Call Flow Examples</a> ," BCP 75, RFC 3665, December 2003 ( <a href="#">TXT</a> ).
[RFC3725]	Rosenberg, J., Peterson, J., Schulzrinne, H., and G. Camarillo, " <a href="#">Best Current Practices for Third Party Call Control (3pcc) in the Session Initiation Protocol (SIP)</a> ," BCP 85, RFC 3725, April 2004 ( <a href="#">TXT</a> ).
[I-D.ietf-sip-gruu]	Rosenberg, J., " <a href="#">Obtaining and Using Globally Routable User Agent (UA) URIs (GRUU) in the Session Initiation Protocol (SIP)</a> ," draft-ietf-sip-gruu-15 (work in progress), October 2007 ( <a href="#">TXT</a> ).
[RFC4317]	Johnston, A. and R. Sparks, " <a href="#">Session Description Protocol (SDP) Offer/Answer Examples</a> ," RFC 4317, December 2005 ( <a href="#">TXT</a> ).
[RFC4475]	

Sparks, R., Hawrylyshen, A., Johnston, A., Rosenberg, J., and H. Schulzrinne, "[Session Initiation Protocol \(SIP\) Torture Test Messages](#)," RFC 4475, May 2006 ([TXT](#)).

---

## Authors' Addresses

[TOC](#)

Alan Johnston (editor)
Avaya
St. Louis, MO 63124
Email: <a href="mailto:alan@sipstation.com">alan@sipstation.com</a>
Robert J. Sparks
Estacado Systems
Email: <a href="mailto:RJS@estacado.net">RJS@estacado.net</a>
Chris Cunningham
Cisco Systems
Email: <a href="mailto:chrcunni@cisco.com">chrcunni@cisco.com</a>
Steve Donovan
Cisco Systems
Email: <a href="mailto:srd@cisco.com">srd@cisco.com</a>
Kevin Summers
Sonus
Plano, TX 75093
Email: <a href="mailto:ksummers@sonusnet.com">ksummers@sonusnet.com</a>

---

## Full Copyright Statement

[TOC](#)

Copyright © The IETF Trust (2008).

This document is subject to the rights, licenses and restrictions contained in BCP 78, and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY, THE IETF TRUST AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

## **Intellectual Property**

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in BCP 78 and BCP 79.

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at [ietf-ipr@ietf.org](mailto:ietf-ipr@ietf.org).