

S/MIME WG  
Internet Draft  
Intended Status: Informational  
Obsoletes: [3278](#) (once approved)  
Expires: December 5, 2009

Sean Turner, IECA  
Dan Brown, Certicom  
June 5, 2009

**Use of Elliptic Curve Cryptography (ECC) Algorithms  
in Cryptographic Message Syntax (CMS)  
draft-ietf-smime-3278bis-09.txt**

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#). This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at  
<http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at  
<http://www.ietf.org/shadow.html>

This Internet-Draft will expire on December 5, 2009.

## Copyright Notice

Copyright (c) 2009 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents in effect on the date of publication of this document (<http://trustee.ietf.org/license-info>). Please review these documents carefully, as they describe your rights and restrictions with respect to this document.

## Abstract

This document describes how to use Elliptic Curve Cryptography (ECC) public-key algorithms in the Cryptographic Message Syntax (CMS). The ECC algorithms support the creation of digital signatures and the exchange of keys to encrypt or authenticate content. The definition of the algorithm processing is based on the NIST FIPS 186-3 for digital signature, NIST SP800-56A and SEC1 for key agreement, [RFC 3370](#) and [RFC 3565](#) for key wrap and content encryption, NIST FIPS 180-3 for message digest, SEC1 for key derivation, and [RFC 2104](#) and [RFC 4231](#) for message authentication code standards. This document obsoletes [RFC 3278](#).

## Discussion

This draft is being discussed on the 'ietf-smime' mailing list. To subscribe, send a message to [ietf-smime-request@imc.org](mailto:ietf-smime-request@imc.org) with the single word subscribe in the body of the message. There is a Web site for the mailing list at <http://www.imc.org/ietf-smime/>.

## Table of Contents

<a href="#">1.</a>	<a href="#">Introduction.....</a>	<a href="#">3</a>
<a href="#">1.1.</a>	<a href="#">Requirements Terminology.....</a>	<a href="#">4</a>
<a href="#">2.</a>	<a href="#">SignedData using ECC.....</a>	<a href="#">4</a>
<a href="#">2.1.</a>	<a href="#">SignedData using ECDSA.....</a>	<a href="#">4</a>
<a href="#">3.</a>	<a href="#">EnvelopedData using ECC Algorithms.....</a>	<a href="#">5</a>
<a href="#">3.1.</a>	<a href="#">EnvelopedData using (ephemeral-static) ECDH.....</a>	<a href="#">6</a>
<a href="#">3.2.</a>	<a href="#">EnvelopedData using 1-Pass ECMQV.....</a>	<a href="#">8</a>
<a href="#">4.</a>	<a href="#">AuthenticatedData and AuthEnvelopedData using ECC.....</a>	<a href="#">11</a>
<a href="#">4.1.</a>	<a href="#">AuthenticatedData using 1-pass ECMQV.....</a>	<a href="#">11</a>
<a href="#">4.2.</a>	<a href="#">AuthEnvelopedData using 1-pass ECMQV.....</a>	<a href="#">12</a>

<a href="#">5.</a>	<a href="#">Certificates using ECC.....</a>	<a href="#">13</a>
<a href="#">6.</a>	<a href="#">SMIMECapabilities Attribute and ECC.....</a>	<a href="#">13</a>
<a href="#">7.</a>	<a href="#">ASN.1 Syntax.....</a>	<a href="#">21</a>
<a href="#">7.1.</a>	<a href="#">Algorithm Identifiers.....</a>	<a href="#">21</a>
<a href="#">7.2.</a>	<a href="#">Other Syntax.....</a>	<a href="#">25</a>
<a href="#">8.</a>	<a href="#">Recommended Algorithms and Elliptic Curves.....</a>	<a href="#">27</a>
<a href="#">9.</a>	<a href="#">Security Considerations.....</a>	<a href="#">29</a>
<a href="#">10.</a>	<a href="#">IANA Considerations.....</a>	<a href="#">34</a>
<a href="#">11.</a>	<a href="#">References.....</a>	<a href="#">34</a>
<a href="#">11.1.</a>	<a href="#">Normative.....</a>	<a href="#">34</a>
<a href="#">11.2.</a>	<a href="#">Informative.....</a>	<a href="#">36</a>
<a href="#">Appendix A</a>	<a href="#">ASN.1 Modules.....</a>	<a href="#">37</a>
<a href="#">Appendix A.1</a>	<a href="#">1988 ASN.1 Module.....</a>	<a href="#">37</a>
<a href="#">Appendix A.2</a>	<a href="#">2004 ASN.1 Module.....</a>	<a href="#">46</a>
<a href="#">Appendix B</a>	<a href="#">Changes since <a href="#">RFC 3278</a>.....</a>	<a href="#">61</a>
	<a href="#">Acknowledgements.....</a>	<a href="#">63</a>
	<a href="#">Author's Addresses.....</a>	<a href="#">63</a>

## [1.](#) Introduction

The Cryptographic Message Syntax (CMS) is cryptographic algorithm independent. This specification defines a profile for the use of Elliptic Curve Cryptography (ECC) public key algorithms in the CMS. The ECC algorithms are incorporated into the following CMS content types:

- 'SignedData' to support ECC-based digital signature methods (ECDSA) to sign content;
- 'EnvelopedData' to support ECC-based public-key agreement methods (ECDH and ECMQV) to generate pairwise key-encryption keys to encrypt content-encryption keys used for content encryption;
- 'AuthenticatedData' to support ECC-based public-key agreement methods (ECMQV) to generate pairwise key-encryption keys to encrypt message-authentication keys used for content authentication and integrity; and,
- 'AuthEnvelopedData' to support ECC-based public-key agreement methods (ECMQV) to generate pairwise key-encryption keys to encrypt message-authentication and content-encryption keys used for content authentication, integrity, and encryption.

Certification of EC public keys is also described to provide public-key distribution in support of the specified techniques.

The document will obsolete [\[CMS-ECC\]](#). The technical changes performed since [RFC 3278](#) are detailed in [Appendix B](#).

### **[1.1. Requirements Terminology](#)**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [\[MUST\]](#).

## **[2. SignedData using ECC](#)**

This section describes how to use ECC algorithms with the CMS SignedData format to sign data.

### **[2.1. SignedData using ECDSA](#)**

This section describes how to use the Elliptic Curve Digital Signature Algorithm (ECDSA) with SignedData. ECDSA is specified in [\[FIPS186-3\]](#). The method is the elliptic curve analog of the Digital Signature Algorithm (DSA) [\[FIPS186-3\]](#). ECDSA is used with the Secure Hash Algorithm (SHA) [\[FIPS180-3\]](#).

In an implementation that uses ECDSA with CMS SignedData, the following techniques and formats MUST be used.

#### **[2.1.1. Fields of the SignedData](#)**

When using ECDSA with SignedData, the fields of SignerInfo are as in [\[CMS\]](#), but with the following restrictions:

- digestAlgorithm MUST contain the algorithm identifier of the hash algorithm (see [Section 7.1.1](#)) which MUST be one of the following: id-sha1, id-sha224, id-sha256, id-sha384, or id-sha512.
- signatureAlgorithm contains the signature algorithm identifier (see [Section 7.1.3](#)): ecdsa-with-SHA1, ecdsa-with-SHA224, ecdsa-with-SHA256, ecdsa-with-SHA384, or ecdsa-with-SHA512. The hash algorithm identified in the name of the signature algorithm MUST be the same as the digestAlgorithm (e.g., digestAlgorithm is id-sha256 therefore signatureAlgorithm is ecdsa-with-SHA256).

- signature MUST contain the DER encoding (as an octet string) of a value of the ASN.1 type ECDSA-Sig-Value (see [Section 7.2](#)).

When using ECDSA, the SignedData certificates field MAY include the certificate(s) for the EC public key(s) used in the generation of the ECDSA signatures in SignedData. ECC certificates are discussed in [Section 5](#).

#### **[2.1.2](#). Actions of the sending agent**

When using ECDSA with SignedData, the sending agent uses the message digest calculation process and signature generation process for SignedData that are specified in [\[CMS\]](#). To sign data, the sending agent uses the signature method specified in [\[FIPS186-3\]](#).

The sending agent encodes the resulting signature using the ECDSA-Sig-Value syntax (see [Section 7.2](#)) and places it in the SignerInfo signature field.

#### **[2.1.3](#). Actions of the receiving agent**

When using ECDSA with SignedData, the receiving agent uses the message digest calculation process and signature verification process for SignedData that are specified in [\[CMS\]](#). To verify SignedData, the receiving agent uses the signature verification method specified in [\[FIPS186-3\]](#).

In order to verify the signature, the receiving agent retrieves the integers *r* and *s* from the SignerInfo signature field of the received message.

### **[3](#). EnvelopedData using ECC Algorithms**

This section describes how to use ECC algorithms with the CMS EnvelopedData format.

This document does not specify the static-static ECDH, method C(0,2, ECC CDH) from [\[SP800-56A\]](#). Static-static ECDH is analogous to static-static DH, which is specified in [\[CMS-ALG\]](#). Ephemeral-static ECDH and 1-Pass ECMQV were specified because they provide better security due to the originator's ephemeral contribution to the key agreement scheme.

### **3.1. EnvelopedData using (ephemeral-static) ECDH**

This section describes how to use the ephemeral-static Elliptic Curve Diffie-Hellman (ECDH) key agreement algorithm with EnvelopedData, method C(1, 1, ECC CDH) from [SP800-56A] and ECDH with the standard primitive from Section 3.3.1 of [SEC1]. Ephemeral-static ECDH is the elliptic curve analog of the ephemeral-static Diffie-Hellman key agreement algorithm specified jointly in the documents [CMS-ALG] and [CMS-DH].

If an implementation uses ECDH with CMS EnvelopedData, then the following techniques and formats MUST be used.

The fields of EnvelopedData are as in [CMS]; as ECDH is a key agreement algorithm, the RecipientInfo kari choice is used.

#### **3.1.1. Fields of KeyAgreeRecipientInfo**

When using ephemeral-static ECDH with EnvelopedData, the fields of KeyAgreeRecipientInfo are as follows:

- version MUST be 3.
- originator MUST be the alternative originatorKey. The originatorKey algorithm field MUST contain the id-ecPublicKey object identifier (see [Section 7.1.2](#)). The parameters associated with id-ecPublicKey MUST be absent, ECPParameters, or NULL. The parameters associated with id-ecPublicKey SHOULD be absent or ECPParameters, and NULL is allowed to support legacy implementations. The previous version of this document required NULL to be present. If the parameters are ECPParameters, then they MUST be namedCurve. The originatorKey publicKey field MUST contain the DER-encoding of the value of the ASN.1 type ECPoint (see [Section 7.2](#)), which represents the sending agent's ephemeral EC public key. The ECPoint in uncompressed form MUST be supported.
- ukm MAY be present or absent. However, message originators SHOULD include the ukm. As specified in [RFC 3852](#) [CMS], implementations MUST support ukm message recipient processing, so interoperability is not a concern if the ukm is present or absent. The ukm is placed in the entityUInfo field of the ECC-CMS-SharedInfo structure. When present, the ukm is used to ensure that a different key-encryption key is generated, even when the ephemeral private key is improperly used more than

once, by using the ECC-CMS-SharedInfo as an input to the key derivation function (see [Section 7.2](#)).

- keyEncryptionAlgorithm MUST contain the object identifier of the key encryption algorithm, which in this case is a key agreement algorithm (see [Section 7.1.4](#)). The parameters field contains KeyWrapAlgorithm. The KeyWrapAlgorithm is the algorithm identifier that indicates the symmetric encryption algorithm used to encrypt the content-encryption key (CEK) with the key-encryption key (KEK) and any associated parameters (see [Section 7.1.5](#)). Algorithm requirements are found in [Section 8](#).
- recipientEncryptedKeys contains an identifier and an encrypted key for each recipient. The RecipientEncryptedKey KeyAgreeRecipientIdentifier MUST contain either the issuerAndSerialNumber identifying the recipient's certificate or the RecipientKeyIdentifier containing the subject key identifier from the recipient's certificate. In both cases, the recipient's certificate contains the recipient's static ECDH public key. RecipientEncryptedKey EncryptedKey MUST contain the content-encryption key encrypted with the ephemeral-static, ECDH-generated pairwise key-encryption key using the algorithm specified by the KeyWrapAlgorithm.

### **3.1.2. Actions of the sending agent**

When using ephemeral-static ECDH with EnvelopedData, the sending agent first obtains the recipient's EC public key and domain parameters (e.g. from the recipient's certificate). The sending agent then determines an integer "keydatalen", which is the KeyWrapAlgorithm symmetric key-size in bits, and also a bit string "SharedInfo", which is the DER encoding of ECC-CMS-SharedInfo (see [Section 7.2](#)). The sending agent then performs the key deployment and the key agreement operation of the Elliptic Curve Diffie-Hellman Scheme specified in [\[SP800-56A\]](#) or [\[SEC1\]](#); in either case, use the KDF defined in Section 3.6.1 of [\[SEC1\]](#) with the hash algorithm identified in the key agreement algorithm. As a result the sending agent obtains:

- an ephemeral public key, which is represented as a value of the type ECPoint (see [Section 7.2](#)), encapsulated in a bit string and placed in the KeyAgreeRecipientInfo originator originatorKey publicKey field, and

- a shared secret bit string "K", which is used as the pairwise key-encryption key for that recipient, as specified in [CMS].

In a single message, if there are multiple layers for a recipient, then the ephemeral public key can be reused by the originator for that recipient in each of the different layers.

### **3.1.3. Actions of the receiving agent**

When using ephemeral-static ECDH with EnvelopedData, the receiving agent determines the bit string "SharedInfo", which is the DER encoding of ECC-CMS-SharedInfo (see [Section 7.2](#)), and the integer "keydatalen" from the key-size, in bits, of the KeyWrapAlgorithm. The receiving agent retrieves the ephemeral EC public key from the bit string KeyAgreeRecipientInfo originator, with a value of the type ECPoint (see [Section 7.2](#)) encapsulated as a bit string, and if present, originally supplied additional user key material from the ukm field. The receiving agent performs the key agreement operation of the Elliptic Curve Diffie-Hellman Scheme specified in [[SP800-56A](#)] or [[SEC1](#)]; in either case, use the KDF defined in Section 3.6.1 of [[SEC1](#)]. As a result, the receiving agent obtains a shared secret bit string "K", which is used as the pairwise key-encryption key to unwrap the CEK.

### **3.2. EnvelopedData using 1-Pass ECMQV**

This section describes how to use the 1-Pass elliptic curve MQV (ECMQV) key agreement algorithm with EnvelopedData, method C(1, 2, ECC MQV) from [[SP800-56A](#)]. Like the KEA algorithm [[CMS-KEA](#)], 1-Pass ECMQV uses three key pairs: an ephemeral key pair, a static key pair of the sending agent, and a static key pair of the receiving agent. Using an algorithm with the sender static key pair allows for knowledge of the message creator, this means that authentication can, in some circumstances, be obtained for AuthEnvelopedData and AuthenticatedData. This means that 1-Pass ECMQV can be a common algorithm for EnvelopedData, AuthenticatedData and AuthEnvelopedData, while ECDH can only be used in EnvelopedData.

If an implementation uses 1-Pass ECMQV with CMS EnvelopedData, then the following techniques and formats MUST be used.

The fields of EnvelopedData are as in [[CMS](#)]; as 1-Pass ECMQV is a key agreement algorithm, the RecipientInfo kari choice is used. When using 1-Pass ECMQV, the EnvelopedData originatorInfo field MAY include the certificate(s) for the EC public key(s) used in the



formation of the pairwise key. ECC certificates are discussed in [Section 5](#).

### **3.2.1. Fields of KeyAgreeRecipientInfo**

When using 1-Pass ECMQV with EnvelopedData, the fields of KeyAgreeRecipientInfo are:

- version MUST be 3.
- originator identifies the static EC public key of the sender. It SHOULD be one of the alternatives, issuerAndSerialNumber or subjectKeyIdentifier, and point to one of the sending agent's certificates.
- ukm MUST be present. The ukm field is an octet string which MUST contain the DER encoding of the type MQVuserKeyingMaterial (see [Section 7.2](#)). The MQVuserKeyingMaterial ephemeralPublicKey algorithm field MUST contain the id-ecPublicKey object identifier (see [Section 7.1.2](#)). The parameters associated with id-ecPublicKey MUST be absent, ECPParameters, or NULL. The parameters associated with id-ecPublicKey SHOULD be absent or ECPParameters, as NULL is allowed to support legacy implementations. The previous version of this document required NULL to be present. If the parameters are ECPParameters, then they MUST be namedCurve. The MQVuserKeyingMaterial ephemeralPublicKey publicKey field MUST contain the DER-encoding of the ASN.1 type ECPoint (see [Section 7.2](#)) representing the sending agent's ephemeral EC public key. The MQVuserKeyingMaterial addedUkm field, if present, contains additional user keying material from the sending agent.
- keyEncryptionAlgorithm MUST contain the object identifier of the key encryption algorithm, which in this case is a key agreement algorithm (see [Section 7.1.4](#)). The parameters field contains KeyWrapAlgorithm. The KeyWrapAlgorithm indicates the symmetric encryption algorithm used to encrypt the CEK with the KEK generated using the 1-Pass ECMQV algorithm and any associated parameters (see [Section 7.1.5](#)). Algorithm requirements are found in [Section 8](#).
- recipientEncryptedKeys contains an identifier and an encrypted key for each recipient. The RecipientEncryptedKey KeyAgreeRecipientIdentifier MUST contain either the issuerAndSerialNumber identifying the recipient's certificate or

the RecipientKeyIdentifier containing the subject key identifier from the recipient's certificate. In both cases, the recipient's certificate contains the recipient's static ECMQV public key. RecipientEncryptedKey EncryptedKey MUST contain the content-encryption key encrypted with the 1-Pass ECMQV-generated pairwise key-encryption key using the algorithm specified by the KeyWrapAlgorithm.

### **3.2.2. Actions of the sending agent**

When using 1-Pass ECMQV with EnvelopedData, the sending agent first obtains the recipient's EC public key and domain parameters (e.g. from the recipient's certificate), and checks that the domain parameters are the same as the sender's domain parameters. The sending agent then determines an integer "keydatalen", which is the KeyWrapAlgorithm symmetric key-size in bits, and also a bit string "SharedInfo", which is the DER encoding of ECC-CMS-SharedInfo (see [Section 7.2](#)). The sending agent then performs the key deployment and key agreement operations of the Elliptic Curve MQV Scheme specified in [SP800-56A], but uses the KDF defined in Section 3.6.1 of [SEC1]. As a result, the sending agent obtains:

- an ephemeral public key, which is represented as a value of type ECPoint (see [Section 7.2](#)), encapsulated in a bit string, placed in an MQVuserKeyingMaterial ephemeralPublicKey publicKey field (see [Section 7.2](#)), and
- a shared secret bit string "K", which is used as the pairwise key-encryption key for that recipient, as specified in [CMS].

In a single message, if there are multiple layers for a recipient, then the ephemeral public key can be reused by the originator for that recipient in each of the different layers.

### **3.2.3. Actions of the receiving agent**

When using 1-Pass ECMQV with EnvelopedData, the receiving agent determines the bit string "SharedInfo", which is the DER encoding of ECC-CMS-SharedInfo (see [Section 7.2](#)), and the integer "keydatalen" from the key-size, in bits, of the KeyWrapAlgorithm. The receiving agent then retrieves the static and ephemeral EC public keys of the originator, from the originator and ukm fields as described in [Section 3.2.1](#), and its static EC public key identified in the rid field and checks that the originator's domain parameters are the same as the recipient's domain parameters. The receiving agent then

performs the key agreement operation of the Elliptic Curve MQV Scheme [SP800-56A], but uses the KDF defined in Section 3.6.1 of [SEC1]. As a result, the receiving agent obtains a shared secret bit string "K", which is used as the pairwise key-encryption key to unwrap the CEK.

#### **4. AuthenticatedData and AuthEnvelopedData using ECC**

This section describes how to use ECC algorithms with the CMS AuthenticatedData format. AuthenticatedData lacks non-repudiation, and so in some instances is preferable to SignedData. (For example, the sending agent might not want the message to be authenticated when forwarded.)

This section also describes how to use ECC algorithms with the CMS AuthEnvelopedData format [CMS-AUTHENV]. AuthEnvelopedData supports authentication and encryption, and in some instances is preferable to signing and then encrypting data.

For both AuthenticatedData and AuthEnvelopedData, data origin authentication with 1-Pass ECMQV can only be provided when there is one and only one recipient. When there are multiple recipients, an attack is possible where one recipient modifies the content without other recipients noticing [BON]. A sending agent who is concerned with such an attack SHOULD use a separate AuthenticatedData or AuthEnvelopedData for each recipient.

Using an algorithm with the sender static key pair allows for knowledge of the message creator; this means that authentication can, in some circumstances, be obtained for AuthEnvelopedData and AuthenticatedData. This means that 1-Pass ECMQV can be a common algorithm for EnvelopedData, AuthenticatedData, and AuthEnvelopedData while ECDH can only be used in EnvelopedData.

##### **4.1. AuthenticatedData using 1-pass ECMQV**

This section describes how to use the 1-Pass elliptic curve MQV (ECMQV) key agreement algorithm with AuthenticatedData. ECMQV is method C(1, 2, ECC MQV) from [SP800-56A].

When using ECMQV with AuthenticatedData, the fields of AuthenticatedData are as in [CMS], but with the following restrictions:

- macAlgorithm MUST contain the algorithm identifier of the message authentication code (MAC) algorithm (see [Section 7.1.7](#)) which

MUST be one of the following: hmac-SHA1, id-hmacWITHSHA224, id-hmacWITHSHA256, id-hmacWITHSHA384, or id-hmacWITHSHA512.

- digestAlgorithm MUST contain the algorithm identifier of the hash algorithm (see [Section 7.1.1](#)) which MUST be one of the following: id-sha1, id-sha224, id-sha256, id-sha384, and id-sha512.

As 1-Pass ECMQV is a key agreement algorithm, the RecipientInfo kari choice is used in the AuthenticatedData. When using 1-Pass ECMQV, the AuthenticatedData originatorInfo field MAY include the certificate(s) for the EC public key(s) used in the formation of the pairwise key. ECC certificates are discussed in [Section 5](#).

#### **[4.1.1](#). Fields of the KeyAgreeRecipientInfo**

The AuthenticatedData KeyAgreeRecipientInfo fields are used in the same manner as the fields for the corresponding EnvelopedData KeyAgreeRecipientInfo fields of [Section 3.2.1](#) of this document.

#### **[4.1.2](#). Actions of the sending agent**

The sending agent uses the same actions as for EnvelopedData with 1-Pass ECMQV, as specified in [Section 3.2.2](#) of this document.

In a single message, if there are multiple layers for a recipient, then the ephemeral public key can be reused by the originator for that recipient in each of the different layers.

#### **[4.1.3](#). Actions of the receiving agent**

The receiving agent uses the same actions as for EnvelopedData with 1-Pass ECMQV, as specified in [Section 3.2.3](#) of this document.

### **[4.2](#). AuthEnvelopedData using 1-pass ECMQV**

This section describes how to use the 1-Pass elliptic curve MQV (ECMQV) key agreement algorithm with AuthEnvelopedData. ECMQV is method C(1, 2, ECC MQV) from [\[SP800-56A\]](#).

When using ECMQV with AuthEnvelopedData, the fields of AuthEnvelopedData are as in [\[CMS-AUTHENV\]](#).

As 1-Pass ECMQV is a key agreement algorithm, the RecipientInfo kari choice is used. When using 1-Pass ECMQV, the AuthEnvelopedData

originatorInfo field MAY include the certificate(s) for the EC public key used in the formation of the pairwise key. ECC certificates are discussed in [Section 5](#).

#### **[4.2.1](#). Fields of the KeyAgreeRecipientInfo**

The AuthEnvelopedData KeyAgreeRecipientInfo fields are used in the same manner as the fields for the corresponding EnvelopedData KeyAgreeRecipientInfo fields of [Section 3.2.1](#) of this document.

#### **[4.2.2](#). Actions of the sending agent**

The sending agent uses the same actions as for EnvelopedData with 1-Pass ECMQV, as specified in [Section 3.2.2](#) of this document.

In a single message, if there are multiple layers for a recipient, then the ephemeral public key can be reused by the originator for that recipient in each of the different layers.

#### **[4.2.3](#). Actions of the receiving agent**

The receiving agent uses the same actions as for EnvelopedData with 1-Pass ECMQV, as specified in [Section 3.2.3](#) of this document.

### **[5](#). Certificates using ECC**

Internet X.509 certificates [[PKI](#)] can be used in conjunction with this specification to distribute agents' public keys. The use of ECC algorithms and keys within X.509 certificates is specified in [[PKI-ALG](#)].

### **[6](#). SMIMECapabilities Attribute and ECC**

A sending agent MAY announce to receiving agents that it supports one or more of the ECC algorithms specified in this document by using the SMIMECapabilities signed attribute [[MSG](#)] in either a signed message or a certificate [[CERTCAP](#)].

The SMIMECapabilities attribute value indicates support for one of the ECDSA signature algorithms in a SEQUENCE with the capabilityID field containing the object identifier ecdsa-with-SHA1 with NULL parameters and ecdsa-with-SHA\* (where \* is 224, 256, 384, or 512) with absent parameters. The DER encodings are:

ecdsa-with-SHA1: 30 0b 06 07 2a 86 48 ce 3d 04 01 05 00

ecdsa-with-SHA224: 30 0a 06 08 2a 86 48 ce 3d 04 03 01

ecdsa-with-SHA256: 30 0a 06 08 2a 86 48 ce 3d 04 03 02

ecdsa-with-SHA384: 30 0a 06 08 2a 86 48 ce 3d 04 03 03

ecdsa-with-SHA512: 30 0a 06 08 2a 86 48 ce 3d 04 03 04

NOTE: The SMIMECapabilities attribute indicates that parameters for ECDSA with SHA-1 are NULL; however, the parameters are absent when used to generate a digital signature.

The SMIMECapabilities attribute value indicates support for

- a) the standard ECDH key agreement algorithm,
- b) the cofactor ECDH key agreement algorithm, or
- c) the 1-Pass ECMQV key agreement algorithm and

is a SEQUENCE with the capabilityID field containing the object identifier

- a) dhSinglePass-stdDH-sha\*kdf-scheme,
- b) dhSinglePass-cofactorDH-sha\*kdf-scheme, or
- c) mqvSinglePass-sha\*kdf-scheme

respectively (where \* is 1, 224, 256, 384, or 512) with the parameters present. The parameters indicate the supported key-encryption algorithm with the KeyWrapAlgorithm algorithm identifier.

The DER encodings that indicate capabilities are as follows (KA is key agreement, KDF is key derivation function, and Wrap is key wrap algorithm):

KA=ECDH standard KDF=SHA-1 Wrap=Triple-DES

30 1c 06 09 2b 81 05 10 86 48 3f 00 02 30 0f 06 0b 2a 86 48 86  
f7 0d 01 09 10 03 06 05 00

KA=ECDH standard KDF=SHA-224 Wrap=Triple-DES

30 17 06 06 2b 81 04 01 0B 00 30 0d 06 0b 2a 86 48 86 f7 0d 01  
09 10 03 06

KA=ECDH standard KDF=SHA-256 Wrap=Triple-DES

30 17 06 06 2b 81 04 01 0B 01 30 0d 06 0b 2a 86 48 86 f7 0d 01  
09 10 03 06

KA=ECDH standard KDF=SHA-384 Wrap=Triple-DES

30 17 06 06 2b 81 04 01 0B 02 30 0d 06 0b 2a 86 48 86 f7 0d 01  
09 10 03 06

KA=ECDH standard KDF=SHA-512 Wrap=Triple-DES

30 17 06 06 2b 81 04 01 0B 03 30 0d 06 0b 2a 86 48 86 f7 0d 01  
09 10 03 06

KA=ECDH standard KDF=SHA-1 Wrap=AES-128

30 18 06 09 2b 81 05 10 86 48 3f 00 02 30 0b 06 09 60 86 48 01  
65 03 04 01 05

KA=ECDH standard KDF=SHA-224 Wrap=AES-128

30 15 06 06 2b 81 04 01 0B 00 30 0b 06 09 60 86 48 01 65 03 04  
01 05

KA=ECDH standard KDF=SHA-256 Wrap=AES-128

30 15 06 06 2b 81 04 01 0B 01 30 0b 06 09 60 86 48 01 65 03 04  
01 05

KA=ECDH standard KDF=SHA-384 Wrap=AES-128

30 15 06 06 2b 81 04 01 0B 02 30 0b 06 09 60 86 48 01 65 03 04  
01 05

KA=ECDH standard KDF=SHA-512 Wrap=AES-128

30 15 06 06 2b 81 04 01 0B 03 30 0b 06 09 60 86 48 01 65 03 04  
01 05

KA=ECDH standard KDF=SHA-1 Wrap=AES-192

30 18 06 09 2b 81 05 10 86 48 3f 00 02 30 0b 06 09 60 86 48 01  
65 03 04 01 19

KA=ECDH standard KDF=SHA-224 Wrap=AES-192

30 15 06 06 2b 81 04 01 0B 00 30 0b 06 09 60 86 48 01 65 03 04  
01 19

KA=ECDH standard KDF=SHA-256 Wrap=AES-192

30 15 06 06 2b 81 04 01 0B 01 30 0b 06 09 60 86 48 01 65 03 04  
01 19

KA=ECDH standard KDF=SHA-384 Wrap=AES-192

30 15 06 06 2b 81 04 01 0B 02 30 0b 06 09 60 86 48 01 65 03 04  
01 19

KA=ECDH standard KDF=SHA-512 Wrap=AES-192

30 15 06 06 2b 81 04 01 0B 03 30 0b 06 09 60 86 48 01 65 03 04  
01 19

KA=ECDH standard KDF=SHA-1 Wrap=AES-256

30 18 06 09 2b 81 05 10 86 48 3f 00 02 30 0b 06 09 60 86 48 01  
65 03 04 01 2D

KA=ECDH standard KDF=SHA-224 Wrap=AES-256

30 15 06 06 2b 81 04 01 0B 00 30 0b 06 09 60 86 48 01 65 03 04  
01 2D

KA=ECDH standard KDF=SHA-256 Wrap=AES-256

30 15 06 06 2b 81 04 01 0B 01 30 0b 06 09 60 86 48 01 65 03 04  
01 2D

KA=ECDH standard KDF=SHA-384 Wrap=AES-256

30 15 06 06 2b 81 04 01 0B 02 30 0b 06 09 60 86 48 01 65 03 04  
01 2D 05 00



KA=ECDH standard KDF=SHA-512 Wrap=AES-256

30 15 06 06 2b 81 04 01 0B 03 30 0b 06 09 60 86 48 01 65 03 04  
01 2D

KA=ECDH cofactor KDF=SHA-1 Wrap=Triple-DES

30 1c 06 09 2b 81 05 10 86 48 3f 00 03 30 0f 06 0b 2a 86 48 86  
f7 0d 01 09 10 03 06 05 00

KA=ECDH cofactor KDF=SHA-224 Wrap=Triple-DES

30 17 06 06 2b 81 04 01 0E 00 30 0d 06 0b 2a 86 48 86 f7 0d 01  
09 10 03 06

KA=ECDH cofactor KDF=SHA-256 Wrap=Triple-DES

30 17 06 06 2b 81 04 01 0E 01 30 0d 06 0b 2a 86 48 86 f7 0d 01  
09 10 03 06

KA=ECDH cofactor KDF=SHA-384 Wrap=Triple-DES

30 17 06 06 2b 81 04 01 0E 02 30 0d 06 0b 2a 86 48 86 f7 0d 01  
09 10 03 06

KA=ECDH cofactor KDF=SHA-512 Wrap=Triple-DES

30 17 06 06 2b 81 04 01 0E 03 30 0d 06 0b 2a 86 48 86 f7 0d 01  
09 10 03 06

KA=ECDH cofactor KDF=SHA-1 Wrap=AES-128

30 18 06 09 2b 81 05 10 86 48 3f 00 03 30 0b 06 09 60 86 48 01  
65 03 04 01 05

KA=ECDH cofactor KDF=SHA-224 Wrap=AES-128

30 15 06 06 2b 81 04 01 0E 00 30 0b 06 09 60 86 48 01 65 03 04  
01 05

KA=ECDH cofactor KDF=SHA-256 Wrap=AES-128

30 15 06 06 2b 81 04 01 0E 01 30 0b 06 09 60 86 48 01 65 03 04  
01 05

KA=ECDH cofactor KDF=SHA-384 Wrap=AES-128

30 15 06 06 2b 81 04 01 0E 02 30 0b 06 09 60 86 48 01 65 03 04  
01 05

KA=ECDH cofactor KDF=SHA-512 Wrap=AES-128

30 17 06 06 2b 81 04 01 0E 03 30 0b 06 09 60 86 48 01 65 03 04  
01 05

KA=ECDH cofactor KDF=SHA-1 Wrap=AES-192

30 18 06 09 2b 81 05 10 86 48 3f 00 03 30 0b 06 09 60 86 48 01  
65 03 04 01 19

KA=ECDH cofactor KDF=SHA-224 Wrap=AES-192

30 15 06 06 2b 81 04 01 0E 00 30 0b 06 09 60 86 48 01 65 03 04  
01 19

KA=ECDH cofactor KDF=SHA-256 Wrap=AES-192

30 15 06 06 2b 81 04 01 0E 01 30 0b 06 09 60 86 48 01 65 03 04  
01 19

KA=ECDH cofactor KDF=SHA-384 Wrap=AES-192

30 15 06 06 2b 81 04 01 0E 02 30 0b 06 09 60 86 48 01 65 03 04  
01 19

KA=ECDH cofactor KDF=SHA-512 Wrap=AES-192

30 15 06 06 2b 81 04 01 0E 03 30 0b 06 09 60 86 48 01 65 03 04  
01 19

KA=ECDH cofactor KDF=SHA-1 Wrap=AES-256

30 15 06 09 2b 81 05 10 86 48 3f 00 03 30 0b 06 09 60 86 48 01  
65 03 04 01 2D

KA=ECDH cofactor KDF=SHA-224 Wrap=AES-256

30 15 06 06 2b 81 04 01 0E 00 30 0b 06 09 60 86 48 01 65 03 04  
01 2D

KA=ECDH cofactor KDF=SHA-256 Wrap=AES-256

30 15 06 06 2b 81 04 01 0E 01 30 0b 06 09 60 86 48 01 65 03 04  
01 2D

KA=ECDH cofactor KDF=SHA-384 Wrap=AES-256

30 15 06 06 2b 81 04 01 0E 02 30 0b 06 09 60 86 48 01 65 03 04  
01 2D

KA=ECDH cofactor KDF=SHA-512 Wrap=AES-256

30 15 06 06 2b 81 04 01 0E 03 30 0b 06 09 60 86 48 01 65 03 04  
01 2D

KA=ECMQV 1-Pass KDF=SHA-1 Wrap=Triple-DES

30 1c 06 09 2b 81 05 10 86 48 3f 00 10 30 0f 06 0b 2a 86 48 86  
f7 0d 01 09 10 03 06 05 00

KA=ECMQV 1-Pass KDF=SHA-224 Wrap=Triple-DES

30 17 06 06 2b 81 04 01 0F 00 30 0d 06 0b 2a 86 48 86 f7 0d 01  
09 10 03 06

KA=ECMQV 1-Pass KDF=SHA-256 Wrap=Triple-DES

30 17 06 06 2b 81 04 01 0F 01 30 0d 06 0b 2a 86 48 86 f7 0d 01  
09 10 03 06

KA=ECMQV 1-Pass KDF=SHA-384 Wrap=Triple-DES

30 17 06 06 2b 81 04 01 0F 02 30 0d 06 0b 2a 86 48 86 f7 0d 01  
09 10 03 06

KA=ECMQV 1-Pass KDF=SHA-512 Wrap=Triple-DES

30 17 06 06 2b 81 04 01 0F 03 30 0d 06 0b 2a 86 48 86 f7 0d 01  
09 10 03 06

KA=ECMQV 1-Pass KDF=SHA-1 Wrap=AES-128

30 18 06 09 2b 81 05 10 86 48 3f 00 10 30 0b 06 09 60 86 48 01  
65 03 04 01 05

KA=ECMQV 1-Pass KDF=SHA-224 Wrap=AES-128

30 15 06 06 2b 81 04 01 0F 00 30 0b 06 09 60 86 48 01 65 03 04  
01 05

KA=ECMQV 1-Pass KDF=SHA-256 Wrap=AES-128

30 15 06 06 2b 81 04 01 0F 01 30 0b 06 09 60 86 48 01 65 03 04  
01 05

KA=ECMQV 1-Pass KDF=SHA-384 Wrap=AES-128

30 15 06 06 2b 81 04 01 0F 02 30 0b 06 09 60 86 48 01 65 03 04  
01 05

KA=ECMQV 1-Pass KDF=SHA-512 Wrap=AES-128

30 15 06 06 2b 81 04 01 0F 03 30 0b 06 09 60 86 48 01 65 03 04  
01 05

KA=ECMQV 1-Pass KDF=SHA-1 Wrap=AES-192

30 18 06 09 2b 81 05 10 86 48 3f 00 10 30 0b 06 09 60 86 48 01  
65 03 04 01 19

KA=ECMQV 1-Pass KDF=SHA-224 Wrap=AES-192

30 15 06 06 2b 81 04 01 0F 00 30 0b 06 09 60 86 48 01 65 03 04  
01 19

KA=ECMQV 1-Pass KDF=SHA-256 Wrap=AES-192

30 15 06 06 2b 81 04 01 0F 01 30 0b 06 09 60 86 48 01 65 03 04  
01 19

KA=ECMQV 1-Pass KDF=SHA-384 Wrap=AES-192

30 15 06 06 2b 81 04 01 0F 02 30 0b 06 09 60 86 48 01 65 03 04  
01 19

KA=ECMQV 1-Pass KDF=SHA-512 Wrap=AES-192

30 15 06 06 2b 81 04 01 0F 03 30 0b 06 09 60 86 48 01 65 03 04  
01 19

KA=ECMQV 1-Pass KDF=SHA-1 Wrap=AES-256

30 18 06 09 2b 81 05 10 86 48 3f 00 10 30 0b 06 09 60 86 48 01  
65 03 04 01 2D

KA=ECMQV 1-Pass KDF=SHA-224 Wrap=AES-256

30 15 06 06 2b 81 04 01 0F 00 30 0b 06 09 60 86 48 01 65 03 04  
01 2D

KA=ECMQV 1-Pass KDF=SHA-256 Wrap=AES-256

30 15 06 06 2b 81 04 01 0F 01 30 0b 06 09 60 86 48 01 65 03 04  
01 2D

KA=ECMQV 1-Pass KDF=SHA-384 Wrap=AES-256

30 15 06 06 2b 81 04 01 0F 02 30 0b 06 09 60 86 48 01 65 03 04  
01 2D

KA=ECMQV 1-Pass KDF=SHA-512 Wrap=AES-256

30 15 06 06 2b 81 04 01 0F 03 30 0b 06 09 60 86 48 01 65 03 04  
01 2D

NOTE: The S/MIME Capabilities for the supported AES content encryption key sizes are defined in [[CMS-AES](#)].

NOTE: The S/MIME Capabilities for the supported MAC algorithms are defined in [[CMS-ASN](#)].

## **[7. ASN.1 Syntax](#)**

The ASN.1 syntax [[X.680](#)], [[X.681](#)], [[X.682](#)], [[X.683](#)] used in this document is gathered in this section for reference purposes.

### **[7.1. Algorithm Identifiers](#)**

This section provides the object identifiers for the algorithms used in this document along with any associated parameters.

#### **[7.1.1. Digest Algorithms](#)**

Digest algorithm object identifiers are used in the SignedData digestAlgorithms and digestAlgorithm fields and the AuthenticatedData

digestAlgorithm field. The digest algorithms used in this document are: SHA-1, SHA-224, SHA-256, SHA-384, and SHA-512. The object identifiers and parameters associated with these algorithms are found in [\[CMS-ALG\]](#) and [\[CMS-SHA2\]](#).

#### **7.1.2. Originator Public Key**

The KeyAgreeRecipientInfo originator field uses the following object identifier to indicate an elliptic curve public key:

```
id-ecPublicKey OBJECT IDENTIFIER ::= {
    ansi-x9-62 keyType(2) 1 }
```

where

```
ansi-x9-62 OBJECT IDENTIFIER ::= {
    iso(1) member-body(2) us(840) 10045 }
```

When the object identifier id-ecPublicKey is used here with an algorithm identifier, the associated parameters MUST be either absent or ECPParameters. Implementations MUST accept id-ecPublicKey with absent and ECPParameters parameters. If ECPParameters is present, its value MUST match the recipient's ECPParameters. Implementations SHOULD generate absent parameters for the id-ecPublicKey object identifier in the KeyAgreeRecipientInfo originator field.

[CMS-ECC] indicated the parameters were NULL. Support for this legacy form is OPTIONAL.

#### **7.1.3. Signature Algorithms**

Signature algorithm identifiers are used in the SignedData signatureAlgorithm and signature fields. The signature algorithms used in this document are ECDSA with SHA-1, ECDSA with SHA-224, ECDSA with SHA-256, ECDSA with SHA-384, and ECDSA with SHA-512. The object identifiers and parameters associated with these algorithms are found in [\[PKI-ALG\]](#).

[CMS-ECC] indicated the parameters were NULL. Support for this legacy form is OPTIONAL.

#### **7.1.4. Key Agreement Algorithms**

Key agreement algorithms are used in EnvelopedData, AuthenticatedData, and AuthEnvelopedData in the KeyAgreeRecipientInfo

keyEncryptionAlgorithm field. The following object identifiers indicate the key agreement algorithms used in this document [SP800-56A], [SEC1]:

```
dhSinglePass-stdDH-sha1kdf-scheme OBJECT IDENTIFIER ::= {
    x9-63-scheme 2 }

dhSinglePass-stdDH-sha224kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 11 0 }

dhSinglePass-stdDH-sha256kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 11 1 }

dhSinglePass-stdDH-sha384kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 11 2 }

dhSinglePass-stdDH-sha512kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 11 3 }

dhSinglePass-cofactorDH-sha1kdf-scheme OBJECT IDENTIFIER ::= {
    x9-63-scheme 3 }

dhSinglePass-cofactorDH-sha224kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 14 0 }

dhSinglePass-cofactorDH-sha256kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 14 1 }

dhSinglePass-cofactorDH-sha384kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 14 2 }

dhSinglePass-cofactorDH-sha512kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 14 3 }

mqvSinglePass-sha1kdf-scheme OBJECT IDENTIFIER ::= {
    x9-63-scheme 16 }

mqvSinglePass-sha224kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 15 0 }

mqvSinglePass-sha256kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 15 1 }

mqvSinglePass-sha384kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 15 2 }
```

```
mqvSinglePass-sha512kdf-scheme OBJECT IDENTIFIER ::= {  
    secg-scheme 15 3 }
```

where

```
x9-63-scheme OBJECT IDENTIFIER ::= {  
    iso(1) identified-organization(3) tc68(133) country(16)  
    x9(840) x9-63(63) schemes(0) }
```

and

```
secg-scheme OBJECT IDENTIFIER ::= {  
    iso(1) identified-organization(3) certicom(132) schemes(1) }
```

When the object identifiers are used here within an algorithm identifier, the associated parameters field contains KeyWrapAlgorithm to indicate the key wrap algorithm and any associated parameters.

#### **7.1.5. Key Wrap Algorithms**

Key wrap algorithms are used as part of the parameters in the key agreement algorithm. The key wrap algorithms used in this document are Triple-DES, AES-128, AES-192, and AES-256. The object identifiers and parameters for these algorithms are found in [CMS-ALG] and [CMS-AES].

#### **7.1.6. Content Encryption Algorithms**

Content encryption algorithms are used in EnvelopedData and AuthEnvelopedData in the EncryptedContentInfo contentEncryptionAlgorithm field. The content encryption algorithms used with EnvelopedData in this document are 3-Key Triple DES in CBC mode, AES-128 in CBC mode, AES-192 in CBC mode, and AES-256 in CBC mode. The object identifiers and parameters associated with these algorithms are found in [CMS-ALG] and [CMS-AES]. The content encryption algorithms used with AuthEnvelopedData in this document are AES-128 in CCM mode, AES-192 in CCM mode, AES-256 in CCM mode, AES-128 in GCM mode, AES-192 in GCM mode, and AES-256 in GCM mode. The object identifiers and parameters associated with these algorithms are found in [CMS-AESCG].

#### **7.1.7. Message Authentication Code Algorithms**

Message authentication code algorithms are used in AuthenticatedData in the macAlgorithm field. The message authentication code



algorithms used in this document are HMAC with SHA-1, HMAC with SHA-224, HMAC with SHA-256, HMAC with SHA-384, and HMAC with SHA-512. The object identifiers and parameters associated with these algorithms are found in [[CMS-ALG](#)] and [[HMAC-SHA2](#)].

NOTE: [[HMAC-SHA2](#)] defines the object identifiers for HMAC with SHA-224, HMAC with SHA-256, HMAC with SHA-384, and HMAC with SHA-512, but there is no ASN.1 module from which to import these object identifiers. Therefore, the object identifiers for these algorithms are included in the ASN.1 modules defined in [Appendix A](#).

#### **[7.1.8](#). Key Derivation Algorithm**

The KDF used in this document is as specified in 3.6.1 of [[SEC1](#)]. The hash algorithm is identified in key agreement algorithm. For example, dhSinglePass-stdDH-sha256kdf-scheme uses the KDF from [[SEC1](#)] but uses SHA-256 instead of SHA-1.

#### **[7.2](#). Other Syntax**

The following additional syntax is used here.

When using ECDSA with SignedData, ECDSA signatures are encoded using the type:

```
ECDSA-Sig-Value ::= SEQUENCE {  
    r INTEGER,  
    s INTEGER }
```

ECDSA-Sig-Value is specified in [[PKI-ALG](#)]. Within CMS, ECDSA-Sig-Value is DER-encoded and placed within a signature field of SignedData.

When using ECDH and ECMQV with EnvelopedData, AuthenticatedData, and AuthEnvelopedData, ephemeral and static public keys are encoded using the type ECPoint. Implementations MUST support uncompressed keys, MAY support compressed keys, and MUST NOT support hybrid keys.

```
ECPoint ::= OCTET STRING
```

When using ECMQV with EnvelopedData, AuthenticatedData, and AuthEnvelopedData, the sending agent's ephemeral public key and additional keying material are encoded using the type:

```
MQVuserKeyingMaterial ::= SEQUENCE {  
    ephemeralPublicKey      OriginatorPublicKey,  
    addedukm                [0] EXPLICIT UserKeyingMaterial OPTIONAL }
```

The ECPoint syntax is used to represent the ephemeral public key and is placed in the ephemeralPublicKey publicKey field. The additional user keying material is placed in the addedukm field. Then the MQVuserKeyingMaterial value is DER-encoded and placed within the ukm field of EnvelopedData, AuthenticatedData, or AuthEnvelopedData.

When using ECDH or ECMQV with EnvelopedData, AuthenticatedData, or AuthEnvelopedData, the key-encryption keys are derived by using the type:

```
ECC-CMS-SharedInfo ::= SEQUENCE {  
    keyInfo      AlgorithmIdentifier,  
    entityUInfo [0] EXPLICIT OCTET STRING OPTIONAL,  
    suppPubInfo [2] EXPLICIT OCTET STRING }
```

The fields of ECC-CMS-SharedInfo are as follows:

keyInfo contains the object identifier of the key-encryption algorithm (used to wrap the CEK) and associated parameters. In this specification, 3DES wrap has NULL parameters while the AES wraps have absent parameters.

entityUInfo optionally contains additional keying material supplied by the sending agent. When used with ECDH and CMS, the entityUInfo field contains the octet string ukm. When used with ECMQV and CMS, the entityUInfo contains the octet string addedukm (encoded in MQVuserKeyingMaterial).

suppPubInfo contains the length of the generated KEK, in bits, represented as a 32 bit number, as in [CMS-DH] and [CMS-AES]. (E.g. for AES-256 it would be 00 00 01 00.)

Within CMS, ECC-CMS-SharedInfo is DER-encoded and used as input to the key derivation function, as specified in Section 3.6.1 of [SEC1].

NOTE: ECC-CMS-SharedInfo differs from the OtherInfo specified in [CMS-DH]. Here, a counter value is not included in the keyInfo field

because the key derivation function specified in Section 3.6.1 of [\[SEC1\]](#) ensures that sufficient keying data is provided.

## 8. Recommended Algorithms and Elliptic Curves

It is RECOMMENDED that implementations of this specification support SignedData and EnvelopedData. Support for AuthenticatedData and AuthEnvelopedData is OPTIONAL.

In order to encourage interoperability, implementations SHOULD use the elliptic curve domain parameters specified by [\[PKI-ALG\]](#).

Implementations that support SignedData with ECDSA:

- MUST support ECDSA with SHA-256; and,
- MAY support ECDSA with SHA-1, ECDSA with SHA-224, ECDSA with SHA-384, and ECDSA with SHA-512; other digital signature algorithms MAY also be supported.

When using ECDSA, to promote interoperability it is RECOMMENDED that the P-192, P-224, and the P-256 curves be used with SHA-256, the P-384 curve be used with SHA-384, and the P-521 curve be used with SHA-512.

If EnvelopedData is supported, then ephemeral-static ECDH standard primitive MUST be supported. Support for ephemeral-static ECDH co-factor is OPTIONAL and support for 1-Pass ECMQV is also OPTIONAL.

Implementations that support EnvelopedData with the ephemeral-static ECDH standard primitive:

- MUST support the dhSinglePass-stdDH-sha256kdf-scheme key agreement algorithm, the id-aes128-wrap key wrap algorithm, and the id-aes128-cbc content encryption algorithm; and,
- MAY support the dhSinglePass-stdDH-sha1kdf-scheme, dhSinglePass-stdDH-sha224kdf-scheme, dhSinglePass-stdDH-sha384kdf-scheme and dhSinglePass-stdDH-sha512kdf-scheme key agreement algorithms, the id-alg-CMS3DESwrap, id-aes192-wrap, and id-aes256-wrap key wrap algorithms and the des-ede3-cbc, id-aes192-cbc, and id-aes256-cbc content encryption algorithms; other algorithms MAY also be supported.

Implementations that support EnvelopedData with the ephemeral-static ECDH cofactor primitive:

- MUST support the dhSinglePass-cofactorDH-sha256kdf-scheme key agreement algorithm, the id-aes128-wrap key wrap algorithm, and the id-aes128-cbc content encryption algorithm; and,
- MAY support the dhSinglePass-cofactorDH-sha1kdf-scheme, dhSinglePass-cofactorDH-sha224kdf-scheme, dhSinglePass-cofactorDH-sha384kdf-scheme, and dhSinglePass-cofactorDH-sha512kdf-scheme key agreement, the id-alg-CMS3DESwrap, id-aes192-wrap, and id-aes256-wrap key wrap algorithms and the des-ede3-cbc, id-aes192-cbc, and id-aes256-cbc content encryption algorithms; other algorithms MAY also be supported.

Implementations that support EnvelopedData with 1-Pass ECMQV:

- MUST support the mqvSinglePass-sha256kdf-scheme key agreement algorithm, the id-aes128-wrap key wrap algorithm, and the id-aes128-cbc content encryption algorithm; and,
- MAY support mqvSinglePass-sha1kdf-scheme, mqvSinglePass-sha224kdf-scheme, mqvSinglePass-sha384kdf-scheme, and mqvSinglePass-sha512kdf-scheme key agreement algorithms, the id-alg-CMS3DESwrap, id-aes192-wrap, and id-aes256-wrap key wrap algorithms and the des-ede3-cbc, id-aes192-cbc, and id-aes256-cbc content encryption algorithms; other algorithms MAY also be supported.

Implementations that support AuthenticatedData with 1-Pass ECMQV:

- MUST support the mqvSinglePass-sha256kdf-scheme key agreement, the id-aes128-wrap key wrap, the id-sha256 message digest, and id-hmacWithSHA256 message authentication code algorithms; and,
- MAY support the mqvSinglePass-sha1kdf-scheme, mqvSinglePass-sha224kdf-scheme, mqvSinglePass-sha384kdf-scheme, mqvSinglePass-sha512kdf-scheme key agreement algorithms, the id-alg-CMS3DESwrap, id-aes192-wrap, and id-aes256-wrap key wrap algorithms, the id-sha1, id-sha224, id-sha384, and id-sha512, message digest algorithms, and the hmac-SHA1, id-hmacWithSHA224, id-hmacWithSHA384, and id-hmacWithSHA512 message authentication code algorithms; other algorithms MAY also be supported.

Implementations that support AuthEnvelopedData with 1-Pass ECMQV:

- MUST support the mqvSinglePass-sha256kdf-scheme key agreement, the id-aes128-wrap key wrap, and the id-aes128-ccm authenticated-content encryption; and,
- MAY support the mqvSinglePass-sha1kdf-scheme, mqvSinglePass-sha224kdf-scheme, mqvSinglePass-sha384kdf-scheme, and mqvSinglePass-sha512kdf-scheme key agreement algorithms, the id-alg-CMS3DESwrap, id-aes192-wrap, and id-aes256-wrap key wrap algorithms, the id-aes192-ccm, id-aes256-ccm, id-aes128-gcm, id-aes192-gcm, and id-aes256-ccm authenticated-content encryption algorithms; other algorithms MAY also be supported.

## 9. Security Considerations

Cryptographic algorithms will be broken or weakened over time. Implementers and users need to check that the cryptographic algorithms listed in this document continue to provide the expected level of security. The IETF from time to time may issue documents dealing with the current state of the art.

Cryptographic algorithms rely on random numbers. See [[RANDOM](#)] for guidance on generation of random numbers.

Receiving agents that validate signatures and sending agents that encrypt messages need to be cautious of cryptographic processing usage when validating signatures and encrypting messages using keys larger than those mandated in this specification. An attacker could send keys and/or certificates with keys which would result in excessive cryptographic processing, for example keys larger than those mandated in this specification, which could swamp the processing element. Agents which use such keys without first validating the certificate to a trust anchor are advised to have some sort of cryptographic resource management system to prevent such attacks.

Using secret keys of an appropriate size is crucial to the security of a Diffie-Hellman exchange. For elliptic curve groups, the size of the secret key must be equal to the size of  $n$  (the order of the group generated by the point  $g$ ). Using larger secret keys provides absolutely no additional security, and using smaller secret keys is likely to result in dramatically less security. (See [[SP800-56A](#)] for more information on selecting secret keys.)

This specification is based on [\[CMS\]](#), [\[CMS-AES\]](#), [\[CMS-AESCG\]](#), [\[CMS-ALG\]](#), [\[CMS-AUTHENV\]](#), [\[CMS-DH\]](#), [\[CMS-SHA2\]](#), [\[FIPS180-3\]](#), [\[FIPS186-3\]](#), and [\[HMAC-SHA2\]](#), and the appropriate security considerations of those documents apply.

In addition, implementers of AuthenticatedData and AuthEnvelopedData should be aware of the concerns expressed in [\[BON\]](#) when using AuthenticatedData and AuthEnvelopedData to send messages to more than one recipient. Also, users of MQV should be aware of the vulnerability described in [\[K\]](#).

When implementing EnvelopedData, AuthenticatedData, and AuthEnvelopedData, there are five algorithm related choices that need to be made:

- 1) What is the public key size?
- 2) What is the KDF?
- 3) What is the key wrap algorithm?
- 4) What is the content encryption algorithm?
- 5) What is the curve?

Consideration must be given to the strength of the security provided by each of these choices. Security algorithm strength is measured in bits, where bits is measured in equivalence to a symmetric cipher algorithm. Thus a strong symmetric cipher algorithm with a key of X bits is said to provide X bits of security. For other algorithms, the key size is mapped to an equivalent symmetric cipher strength. It is recommended that the bits of security provided by each are roughly equivalent. The following table provides comparable minimum bits of security [\[SP800-57\]](#) for the ECDH/ECMQV key sizes, KDFs, key wrapping algorithms, and content encryption algorithms. It also lists curves [\[PKI-ALG\]](#) for the key sizes.

Minimum Bits of Security	ECDH or ECQMV Key Size	Key Derivation Function	Key Wrap Alg.	Content Encryption Alg.	Curves
80	160-223	SHA-1	3DES	3DES CBC	sect163k1
		SHA-224	AES-128	AES-128 CBC	secp163r2
		SHA-256	AES-192	AES-192 CBC	secp192r1
		SHA-384	AES-256	AES-256 CBC	
		SHA-512			
112	224-255	SHA-1	3DES	3DES CBC	secp224r1
		SHA-224	AES-128	AES-128 CBC	sect233k1
		SHA-256	AES-192	AES-192 CBC	sect233r1
		SHA-384	AES-256	AES-256 CBC	
		SHA-512			
128	256-383	SHA-1	AES-128	AES-128 CBC	secp256r1
		SHA-224	AES-192	AES-192 CBC	sect283k1
		SHA-256	AES-256	AES-256 CBC	sect283r1
		SHA-384			
		SHA-512			
192	384-511	SHA-224	AES-192	AES-192 CBC	secp384r1
		SHA-256	AES-256	AES-256 CBC	sect409k1
		SHA-384			sect409r1
		SHA-512			
256	512+	SHA-256	AES-256	AES-256 CBC	secp521r1
		SHA-384			sect571k1
		SHA-512			sect571r1

To promote interoperability, the following choices are RECOMMENDED:

Minimum Bits of Security	ECDH or ECQMV Key Size	Key Derivation Function	Key Wrap Alg.	Content Encryption Alg.	Curve
80	192	SHA-256	3DES	3DES CBC	secp192r1
112	224	SHA-256	3DES	3DES CBC	secp224r1
128	256	SHA-256	AES-128	AES-128 CBC	secp256r1
192	384	SHA-384	AES-256	AES-256 CBC	secp384r1
256	512+	SHA-512	AES-256	AES-256 CBC	secp521r1

When implementing SignedData, there are three algorithm related choices that need to be made:

- 1) What is the public key size?
- 2) What is the hash algorithm?
- 3) What is the curve?

Consideration must be given to the bits of security provided by each of these choices. Security is measured in bits, where a strong symmetric cipher with a key of X bits is said to provide X bits of security. It is recommended that the bits of security provided by each choice are roughly equivalent. The following table provides comparable minimum bits of security [[SP800-57](#)] for the ECDSA key sizes and message digest algorithms. It also lists curves [[PKI-ALG](#)] for the key sizes.



Minimum Bits of Security	ECDSA Key Size	Message Digest Algorithm	Curve
80	160-223	SHA-1	sect163k1
		SHA-224	secp163r2
		SHA-256	secp192r1
		SHA-384	
		SHA-512	
112	224-255	SHA-224	secp224r1
		SHA-256	sect233k1
		SHA-384	sect233r1
		SHA-512	
128	256-383	SHA-256	secp256r1
		SHA-384	sect283k1
		SHA-512	sect283r1
192	384-511	SHA-384	secp384r1
		SHA-512	sect409k1
			sect409r1
256	512+	SHA-512	secp521r1
			sect571k1
			sect571r1

To promote interoperability, the following choices are RECOMMENDED:

Minimum Bits of Security	ECDSA Key Size	Message Digest Algorithm	Curve
80	192	SHA-256	sect192r1
112	224	SHA-256	secp224r1
128	256	SHA-256	secp256r1
192	384	SHA-384	secp384r1
256	512+	SHA-512	secp521r1

## **10. IANA Considerations**

This document makes extensive use of object identifiers to register originator public key types and algorithms. The algorithm object identifiers are registered in the ANSI X9.62, ANSI X9.63, NIST, RSA, and SECG arcs. Additionally, object identifiers are used to identify the ASN.1 modules found in [Appendix A](#) (there are two). These are defined by the SMIME WG Registrar in an arc delegated by RSA to the SMIME Working Group: iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9) smime(16) modules(0). No action by IANA is necessary for this document or any anticipated updates.

## **11. References**

### **11.1. Normative**

- [CMS] Housley, R., "Cryptographic Message Syntax", [RFC 3852](#), July 2004.
- [CMS-AES] Schaad, J., "Use of the Advanced Encryption Standard (AES) Encryption Algorithm in Cryptographic Message Syntax (CMS)", [RFC 3565](#), July 2003.
- [CMS-AESCG] Housley, R., "Using AES-CCM and AES-GCM Authenticated Encryption in the Cryptographic Message Syntax (CMS)", [RFC 5084](#), November 2007.
- [CMS-ALG] Housley, R., "Cryptographic Message Syntax (CMS) Algorithms", [RFC 3370](#), August 2002.
- [CMS-AUTHENV] Housley, R. "Cryptographic Message Syntax (CMS) Authenticated-Enveloped-Data Content Type", [RFC 5083](#), November 2007.
- [CMS-DH] Rescorla, E., "Diffie-Hellman Key Agreement Method", [RFC 2631](#), June 1999.
- [CMS-SHA2] Turner, S., "Using SHA2 Algorithms with Cryptographic Message Syntax", [draft-ietf-smime-sha2](#), work-in-progress.
- [FIPS180-3] National Institute of Standards and Technology (NIST), FIPS Publication 180-3: Secure Hash Standard, October 2008.

- [FIPS186-3] National Institute of Standards and Technology (NIST), FIPS Publication 186-3: Digital Signature Standard, (draft) November 2008.
- [HMAC-SHA2] Nystrom, M., "Identifiers and Test Vectors for HMAC-SHA-224, HMAC-SHA-256, HMAC-SHA-384, and HMAC-SHA-512", [RFC 4231](#), December 2005.
- [MUST] Bradner, S., "Key Words for Use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [MSG] Ramsdell, B., and S. Turner, "S/MIME Version 3.2 Message Specification", [draft-ietf-smime-3851bis](#), work-in-progress.
- [PKI] Cooper, D., Santesson, S., Farrell, S., Boeyen, S., Housley, R., and W. Polk, "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", [RFC 5280](#), May 2008.
- [PKI-ALG] Turner, S., Brown, D., Yiu, K., Housley, R., and W. Polk, "Elliptic Curve Cryptography Subject Public Key Information", [RFC 5480](#), March 2009.
- [RANDOM] Eastlake 3rd, D., Crocker, S., and J. Schiller, "Randomness Recommendations for Security", [RFC 4086](#), June 2005.
- [RSAOAEP] Schaad, J., Kaliski, B., and R. Housley, "Additional Algorithms and Identifiers for RSA Cryptography for use in the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", [RFC 4055](#), June 2005.
- [SEC1] SECG, "Elliptic Curve Cryptography", Standards for Efficient Cryptography Group, 2002. Available from <http://www.secg.org/download/aid-780/sec1-v2.pdf>.
- [SP800-56A] National Institute of Standards and Technology (NIST), Special Publication 800-56A: Recommendation Pair-Wise Key Establishment Schemes Using Discrete Logarithm Cryptography (Revised), March 2007.

- [X.680] ITU-T Recommendation X.680 (2002) | ISO/IEC 8824-1:2002. Information Technology - Abstract Syntax Notation One.

### **11.2. Informative**

- [BON] D. Boneh, "The Security of Multicast MAC", Presentation at Selected Areas of Cryptography 2000, Center for Applied Cryptographic Research, University of Waterloo, 2000. Paper version available from <http://crypto.stanford.edu/~dabo/papers/mmac.ps>
- [CERTCAP] Santesson, S., "X.509 Certificate Extension for Secure/Multipurpose Internet Mail Extensions (S/MIME) Capabilities", [RFC 4262](#), December 2005.
- [CMS-ASN] Hoffman, P., and J. Schaad, "New ASN.1 Modules for CMS", [draft-ietf-smime-new-asn1](#), work-in-progress.
- [CMS-ECC] Blake-Wilson, S., Brown, D., and P. Lambert, "Use of Elliptic Curve Cryptography (ECC) Algorithms in Cryptographic Message Syntax (CMS)", [RFC 3278](#), April 2002.
- [CMS-KEA] Pawling, J., "CMS KEA and SKIPJACK Conventions", [RFC 2876](#), July 2000.
- [K] B. Kaliski, "MQV Vulnerability", Posting to ANSI X9F1 and IEEE P1363 newsgroups, 1998.
- [PKI-ASN] Hoffman, P., and J. Schaad, "New ASN.1 Modules for PKIX", [draft-ietf-pkix-new-asn1](#), work-in-progress.
- [SP800-57] National Institute of Standards and Technology (NIST), Special Publication 800-57: Recommendation for Key Management - Part 1 (Revised), March 2007.
- [X.681] ITU-T Recommendation X.681 (2002) | ISO/IEC 8824-2:2002. Information Technology - Abstract Syntax Notation One: Information Object Specification.
- [X.682] ITU-T Recommendation X.682 (2002) | ISO/IEC 8824-3:2002. Information Technology - Abstract Syntax Notation One: Constraint Specification.

[X.683] ITU-T Recommendation X.683 (2002) | ISO/IEC 8824-4:2002. Information Technology - Abstract Syntax Notation One: Parameterization of ASN.1 Specifications, 2002.

## Appendix A ASN.1 Modules

[Appendix A.1](#) provides the normative ASN.1 definitions for the structures described in this specification using ASN.1 as defined in [\[X.680\]](#) for compilers that support the 1988 ASN.1.

[Appendix A.2](#) provides informative ASN.1 definitions for the structures described in this specification using ASN.1 as defined in [\[X.680\]](#), [\[X.681\]](#), [\[X.682\]](#), and [\[X.683\]](#) for compilers that support the 2002 ASN.1. This appendix contains the same information as [Appendix A.1](#) in a more recent (and precise) ASN.1 notation, however [Appendix A.1](#) takes precedence in case of conflict.

NOTE: The values for the TBAs will be included during AUTH48.

/\*\* RFC Editor: Remove this note prior to publication \*\*/

### [Appendix A.1](#) 1988 ASN.1 Module

CMSECCAlgs-2009-88

```
{ iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
  smime(16) modules(0) id-mod-cms-ecc-alg-2009-88(45) }
```

DEFINITIONS IMPLICIT TAGS ::=

BEGIN

```
--
-- Copyright (c) 2009 IETF Trust and the persons identified as
-- authors of the code. All rights reserved.
--
-- Redistribution and use in source and binary forms, with or
-- without modification, are permitted provided that the following
-- conditions are met:
--
-- - Redistributions of source code must retain the above copyright
-- notice, this list of conditions and the following disclaimer.
--
```

```
-- - Redistributions in binary form must reproduce the above
--   copyright notice, this list of conditions and the following
--   disclaimer in the documentation and/or other materials provided
--   with the distribution.
--
-- - Neither the name of Internet Society, IETF or IETF Trust, nor
--   the names of specific contributors, may be used to endorse or
--   promote products derived from this software without specific
--   prior written permission.
--
--
--
-- THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND
-- CONTRIBUTORS 'AS IS' AND ANY EXPRESS OR IMPLIED WARRANTIES,
-- INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
-- MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
-- DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
-- CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
-- SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
-- LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS
-- OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER
-- CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
-- STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
-- ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF
-- ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
--
-- This version of the ASN.1 module is part of RFC XXXX;
-- see the RFC itself for full legal notices.
--
--
-- EXPORTS ALL
```

IMPORTS

```
-- From [PKI]
```

AlgorithmIdentifier

FROM PKIX1Explicit88

```
{ iso(1) identified-organization(3) dod(6)
  internet(1) security(5) mechanisms(5) pkix(7) mod(0)
  pkix1-explicit(18) }
```

-- From [[RSAOAEP](#)]

```
id-sha224, id-sha256, id-sha384, id-sha512
FROM PKIX1-PSS-OAEP-Algorithms
{ iso(1) identified-organization(3) dod(6) internet(1)
  security(5) mechanisms(5) pkix(7) id-mod(0)
  id-mod-pkix1-rsa-pkalg(33) }
```

-- From [[PKI-ALG](#)]

```
id-sha1, ecdsa-with-SHA1, ecdsa-with-SHA224,
ecdsa-with-SHA256, ecdsa-with-SHA384, ecdsa-with-SHA512,
id-ecPublicKey, ECDSA-Sig-Value, ECPoint, ECParameters
FROM PKIX1Algorithms2008
{ iso(1) identified-organization(3) dod(6) internet(1)
  security(5) mechanisms(5) pkix(7) id-mod(0) 45 }
```

-- From [[CMS](#)]

```
OriginatorPublicKey, UserKeyingMaterial
FROM CryptographicMessageSyntax2004
{ iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
  smime(16) modules(0) cms-2004(24) }
```

-- From [[CMS-ALG](#)]

```
hMAC-SHA1, des-ede3-cbc, id-alg-CMS3DESwrap, CBCParameter
FROM CryptographicMessageSyntaxAlgorithms
{ iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
  smime(16) modules(0) cmsalg-2001(16) }
```

-- From [[CMS-AES](#)]

```
id-aes128-CBC, id-aes192-CBC, id-aes256-CBC, AES-IV,
id-aes128-wrap, id-aes192-wrap, id-aes256-wrap
FROM CMSAesRsaesOaep
{ iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
  smime(16) modules(0) id-mod-cms-aes(19) }
```

```
-- From [CMS-AESCG]

id-aes128-CCM, id-aes192-CCM, id-aes256-CCM, CCMPParameters
id-aes128-GCM, id-aes192-GCM, id-aes256-GCM, GCMPParameters
  FROM CMS-AES-CCM-and-AES-GCM
    { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
      smime(16) modules(0) id-mod-cms-aes(32) }

;

--
-- Message Digest Algorithms: Imported from [PKI-ALG] and [RSAOAEP]
--

-- id-sha1 Parameters are preferred absent
-- id-sha224 Parameters are preferred absent
-- id-sha256 Parameters are preferred absent
-- id-sha384 Parameters are preferred absent
-- id-sha512 Parameters are preferred absent

--
-- Signature Algorithms: Imported from [PKI-ALG]
--

-- ecdsa-with-SHA1 Parameters are NULL
-- ecdsa-with-SHA224 Parameters are absent
-- ecdsa-with-SHA256 Parameters are absent
-- ecdsa-with-SHA384 Parameters are absent
-- ecdsa-with-SHA512 Parameters are absent

-- ECDSA Signature Value
-- Contents of SignatureValue OCTET STRING

-- ECDSA-Sig-Value ::= SEQUENCE {
--   r  INTEGER,
--   s  INTEGER
-- }

--
-- Key Agreement Algorithms
--

x9-63-scheme OBJECT IDENTIFIER ::= {
  iso(1) identified-organization(3) tc68(133) country(16) x9(840)
  x9-63(63) schemes(0) }
```



```
secg-scheme OBJECT IDENTIFIER ::= {
    iso(1) identified-organization(3) certicom(132) schemes(1) }

--
-- Diffie-Hellman Single Pass, Standard, with KDFs
--

-- Parameters are always present and indicate the key wrap algorithm
-- with KeyWrapAlgorithm.

dhSinglePass-stdDH-sha1kdf-scheme OBJECT IDENTIFIER ::= {
    x9-63-scheme 2 }

dhSinglePass-stdDH-sha224kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 11 0 }

dhSinglePass-stdDH-sha256kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 11 1 }

dhSinglePass-stdDH-sha384kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 11 2 }

dhSinglePass-stdDH-sha512kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 11 3 }

--
-- Diffie-Hellman Single Pass, Cofactor, with KDFs
--

dhSinglePass-cofactorDH-sha1kdf-scheme OBJECT IDENTIFIER ::= {
    x9-63-scheme 3 }

dhSinglePass-cofactorDH-sha224kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 14 0 }

dhSinglePass-cofactorDH-sha256kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 14 1 }

dhSinglePass-cofactorDH-sha384kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 14 2 }

dhSinglePass-cofactorDH-sha512kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 14 3 }
```

```
--
-- MQV Single Pass, Cofactor, with KDFs
--

mqvSinglePass-sha1kdf-scheme OBJECT IDENTIFIER ::= {
    x9-63-scheme 16 }

mqvSinglePass-sha224kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 15 0 }

mqvSinglePass-sha256kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 15 1 }

mqvSinglePass-sha384kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 15 2 }

mqvSinglePass-sha512kdf-scheme OBJECT IDENTIFIER ::= {
    secg-scheme 15 3 }

--
-- Key Wrap Algorithms: Imported from [CMS-ALG] and [CMS-AES]
--

KeyWrapAlgorithm ::= AlgorithmIdentifier

-- id-alg-CMS3DESwrap Parameters are NULL
-- id-aes128-wrap Parameters are absent
-- id-aes192-wrap Parameters are absent
-- id-aes256-wrap Parameters are absent

--
-- Content Encryption Algorithms: Imported from [CMS-ALG]
-- and [CMS-AES]
--

-- des-ede3-cbc Parameters are CBCParameter
-- id-aes128-CBC Parameters are AES-IV
-- id-aes192-CBC Parameters are AES-IV
-- id-aes256-CBC Parameters are AES-IV
-- id-aes128-CCM Parameters are CCMPParameters
-- id-aes192-CCM Parameters are CCMPParameters
-- id-aes256-CCM Parameters are CCMPParameters
-- id-aes128-GCM Parameters are GCMPParameters
-- id-aes192-GCM Parameters are GCMPParameters
-- id-aes256-GCM Parameters are GCMPParameters
```

```
--  
-- Message Authentication Code Algorithms  
--  
-- HMAC-SHA1 Parameters are preferred absent  
-- HMAC with SHA-224, SHA-256, SHA_384, and SHA-512 Parameters are  
-- absent  
  
id-hmacWithSHA224 OBJECT IDENTIFIER ::= {  
    iso(1) member-body(2) us(840) rsadsi(113549)  
    digestAlgorithm(2) 8 }  
  
id-hmacWithSHA256 OBJECT IDENTIFIER ::= {  
    iso(1) member-body(2) us(840) rsadsi(113549)  
    digestAlgorithm(2) 9 }  
  
id-hmacWithSHA384 OBJECT IDENTIFIER ::= {  
    iso(1) member-body(2) us(840) rsadsi(113549)  
    digestAlgorithm(2) 10 }  
  
id-hmacWithSHA512 OBJECT IDENTIFIER ::= {  
    iso(1) member-body(2) us(840) rsadsi(113549)  
    digestAlgorithm(2) 11 }  
  
--  
-- Originator Public Key Algorithms: Imported from [PKI-ALG]  
--  
-- id-ecPublicKey Parameters are absent, NULL, or ECPParameters  
-- Format for both ephemeral and static public keys: Imported from  
-- [PKI-ALG]  
-- ECPoint ::= OCTET STRING
```

```
-- ECPParameters ::= CHOICE {
--   namedCurve      OBJECT IDENTIFIER
--   commented out in [PKI-ALG]  implicitCurve  NULL
--   commented out in [PKI-ALG]  specifiedCurve  SpecifiedECDomain
--   commented out in [PKI-ALG]  ...
-- }
--   -- implicitCurve and specifiedCurve MUST NOT be used in PKIX.
--   -- Details for SpecifiedECDomain can be found in [X9.62].
--   -- Any future additions to this CHOICE should be coordinated
--   -- with ANSI X9.

-- Format of KeyAgreeRecipientInfo ukm field when used with
-- ECMQV

MQVUserKeyingMaterial ::= SEQUENCE {
    ephemeralPublicKey      OriginatorPublicKey,
    addedukm                [0] EXPLICIT UserKeyingMaterial OPTIONAL
}

-- 'SharedInfo' for input to KDF when using ECDH and ECMQV with
-- EnvelopedData, AuthenticatedData, or AuthEnvelopedData

ECC-CMS-SharedInfo ::= SEQUENCE {
    keyInfo      AlgorithmIdentifier,
    entityUIInfo [0] EXPLICIT OCTET STRING OPTIONAL,
    suppPubInfo  [2] EXPLICIT OCTET STRING
}

--
-- S/MIME Capabilities
-- An identifier followed by type.
--
--
-- S/MIME Capabilities: Message Digest Algorithms
--
-- Found in [CMS-SHA2].
```

```
--
-- S/MIME Capabilities: Signature Algorithms
--

-- ecdsa-with-SHA1 Type NULL
-- ecdsa-with-SHA224 Type absent
-- ecdsa-with-SHA256 Type absent
-- ecdsa-with-SHA384 Type absent
-- ecdsa-with-SHA512 Type absent

--
-- S/MIME Capabilities: ECDH, Single Pass, Standard
--

-- dhSinglePass-stdDH-sha1kdf Type is the KeyWrapAlgorithm
-- dhSinglePass-stdDH-sha224kdf Type is the KeyWrapAlgorithm
-- dhSinglePass-stdDH-sha256kdf Type is the KeyWrapAlgorithm
-- dhSinglePass-stdDH-sha384kdf Type is the KeyWrapAlgorithm
-- dhSinglePass-stdDH-sha512kdf Type is the KeyWrapAlgorithm

--
-- S/MIME Capabilities: ECDH, Single Pass, Cofactor
--

-- dhSinglePass-cofactorDH-sha1kdf Type is the KeyWrapAlgorithm
-- dhSinglePass-cofactorDH-sha224kdf Type is the KeyWrapAlgorithm
-- dhSinglePass-cofactorDH-sha256kdf Type is the KeyWrapAlgorithm
-- dhSinglePass-cofactorDH-sha384kdf Type is the KeyWrapAlgorithm
-- dhSinglePass-cofactorDH-sha512kdf Type is the KeyWrapAlgorithm

--
-- S/MIME Capabilities: ECMQV, Single Pass, Standard
--

-- mqvSinglePass-sha1kdf Type is the KeyWrapAlgorithm
-- mqvSinglePass-sha224kdf Type is the KeyWrapAlgorithm
-- mqvSinglePass-sha256kdf Type is the KeyWrapAlgorithm
-- mqvSinglePass-sha384kdf Type is the KeyWrapAlgorithm
-- mqvSinglePass-sha512kdf Type is the KeyWrapAlgorithm
```

```
--
-- S/MIME Capabilities: Message Authentication Code Algorithms
--

-- hMACSHA1 Type is preferred absent
-- id-hmacWithSHA224 Type is absent
-- if-hmacWithSHA256 Type is absent
-- id-hmacWithSHA384 Type is absent
-- id-hmacWithSHA512 Type is absent

END
```

## [Appendix A.2](#) 2004 ASN.1 Module

```
CMSECCAlgs-2009-02
{ iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
  smime(16) modules(0) id-mod-cms-ecc-alg-2009-02(46) }

DEFINITIONS IMPLICIT TAGS ::=

BEGIN

--
-- Copyright (c) 2009 IETF Trust and the persons identified as
-- authors of the code. All rights reserved.
--
-- Redistribution and use in source and binary forms, with or
-- without modification, are permitted provided that the following
-- conditions are met:
--
-- - Redistributions of source code must retain the above copyright
--   notice, this list of conditions and the following disclaimer.
--
-- - Redistributions in binary form must reproduce the above
--   copyright notice, this list of conditions and the following
--   disclaimer in the documentation and/or other materials provided
--   with the distribution.
--
-- - Neither the name of Internet Society, IETF or IETF Trust, nor
--   the names of specific contributors, may be used to endorse or
--   promote products derived from this software without specific
--   prior written permission.
--
--
--
```

```
-- THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND
-- CONTRIBUTORS 'AS IS' AND ANY EXPRESS OR IMPLIED WARRANTIES,
-- INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
-- MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
-- DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
-- CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
-- SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
-- LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS
-- OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER
-- CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
-- STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
-- ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF
-- ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
```

```
--
```

```
-- This version of the ASN.1 module is part of RFC XXXX;
-- see the RFC itself for full legal notices.
```

```
--
```

```
-- EXPORTS ALL
```

```
IMPORTS
```

```
-- From [PKI-ASN]
```

```
mda-sha1, sa-ecdsaWithSHA1, sa-ecdsaWithSHA224, sa-ecdsaWithSHA256,
sa-ecdsaWithSHA384, sa-ecdsaWithSHA512, id-ecPublicKey,
ECDSA-Sig-Value, ECPPoint, ECPParameters
```

```
FROM PKIXAlgs-2009
```

```
{ iso(1) identified-organization(3) dod(6) internet(1)
  security(5) mechanisms(5) pkix(7) id-mod(0)
  id-mod-pkix1-algorithms2008-02(56) }
```

```
-- From [PKI-ASN]
```

```
mda-sha224, mda-sha256, mda-sha384, mda-sha512
```

```
FROM PKIX1-PSS-OAEP-Algorithms-2009
```

```
{ iso(1) identified-organization(3) dod(6) internet(1)
  security(5) mechanisms(5) pkix(7) id-mod(0)
  id-mod-pkix1-rsa-pkalgs-02(54) }
```

```
-- FROM [CMS-ASN]

KEY-WRAP, SIGNATURE-ALGORITHM, DIGEST-ALGORITHM, ALGORITHM,
PUBLIC-KEY, MAC-ALGORITHM, CONTENT-ENCRYPTION, KEY-AGREE, SMIME-CAPS,
AlgorithmIdentifier{
  FROM AlgorithmInformation-2009
  { iso(1) identified-organization(3) dod(6) internet(1)
    security(5) mechanisms(5) pkix(7) id-mod(0)
    id-mod-algorithmInformation-02(58) }

-- From [CMS-ASN]

OriginatorPublicKey, UserKeyingMaterial
FROM CryptographicMessageSyntax-2009
  { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
    smime(16) modules(0) id-mod-cms-2004-02(41) }

-- From [CMS-ASN]

maca-hMAC-SHA1, cea-3DES-cbc, kwa-3DESWrap, CBCParameter
FROM CryptographicMessageSyntaxAlgorithms-2009
  { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
    smime(16) modules(0) id-mod-cmsalg-2001-02(37) }

-- From [CMS-ASN]

cea-aes128-cbc, cea-aes192-cbc, cea-aes256-cbc, kwa-aes128-wrap,
kwa-aes192-wrap, kwa-aes256-wrap
FROM CMSAesRsaesOaep-2009
  { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
    smime(16) modules(0) id-mod-cms-aes-02(38) }

-- From [CMS-ASN]

cea-aes128-CCM, cea-aes192-CCM, cea-aes256-CCM, cea-aes128-GCM,
cea-aes192-GCM, cea-aes256-GCM
FROM CMS-AES-CCM-and-AES-GCM-2009
  { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
    smime(16) modules(0) id-mod-cms-aes-ccm-gcm-02(44) }

;
```



```
-- Constrains the SignedData digestAlgorithms field
-- Constrains the SignedData SignerInfo digestAlgorithm field
-- Constrains the AuthenticatedData digestAlgorithm field

-- Message Digest Algorithms: Imported from [PKI-ASN]

-- MessageDigestAlgs DIGEST-ALGORITHM ::= {
--   mda-sha1      |
--   mda-sha224    |
--   mda-sha256    |
--   mda-sha384    |
--   mda-sha512,
--   ...
-- }

-- Constrains the SignedData SignerInfo signatureAlgorithm field

-- Signature Algorithms: Imported from [PKI-ASN]

-- SignatureAlgs SIGNATURE-ALGORITHM ::= {
--   sa-ecdsaWithSHA1      |
--   sa-ecdsaWithSHA224    |
--   sa-ecdsaWithSHA256    |
--   sa-ecdsaWithSHA384    |
--   sa-ecdsaWithSHA512,
--   ...
-- }

-- ECDSA Signature Value: Imported from [PKI-ALG]
-- Contents of SignatureValue OCTET STRING

-- ECDSA-Sig-Value ::= SEQUENCE {
--   r  INTEGER,
--   s  INTEGER
-- }

--
-- Key Agreement Algorithms
--

-- Constrains the EnvelopedData RecipientInfo KeyAgreeRecipientInfo
--   keyEncryption Algorithm field
-- Constrains the AuthenticatedData RecipientInfo
--   KeyAgreeRecipientInfo keyEncryption Algorithm field
```

```

-- Constrains the AuthEnvelopedData RecipientInfo
--   KeyAgreeRecipientInfo keyEncryption Algorithm field

-- DH variants are not used with AuthenticatedData or
-- AuthEnvelopedData

KeyAgreementAlgs KEY-AGREE ::= {
  kaa-dhSinglePass-stdDH-sha1kdf-scheme      |
  kaa-dhSinglePass-stdDH-sha224kdf-scheme    |
  kaa-dhSinglePass-stdDH-sha256kdf-scheme    |
  kaa-dhSinglePass-stdDH-sha384kdf-scheme    |
  kaa-dhSinglePass-stdDH-sha512kdf-scheme    |
  kaa-dhSinglePass-cofactorDH-sha1kdf-scheme |
  kaa-dhSinglePass-cofactorDH-sha224kdf-scheme |
  kaa-dhSinglePass-cofactorDH-sha256kdf-scheme |
  kaa-dhSinglePass-cofactorDH-sha384kdf-scheme |
  kaa-dhSinglePass-cofactorDH-sha512kdf-scheme |
  kaa-mqvSinglePass-sha1kdf-scheme           |
  kaa-mqvSinglePass-sha224kdf-scheme         |
  kaa-mqvSinglePass-sha256kdf-scheme         |
  kaa-mqvSinglePass-sha384kdf-scheme         |
  kaa-mqvSinglePass-sha512kdf-scheme,
  ...
}

x9-63-scheme OBJECT IDENTIFIER ::= {
  iso(1) identified-organization(3) tc68(133) country(16) x9(840)
  x9-63(63) schemes(0) }

secg-scheme OBJECT IDENTIFIER ::= {
  iso(1) identified-organization(3) certicom(132) schemes(1) }

--
-- Diffie-Hellman Single Pass, Standard, with KDFs
--

-- Parameters are always present and indicate the Key Wrap Algorithm

kaa-dhSinglePass-stdDH-sha1kdf-scheme KEY-AGREE ::= {
  IDENTIFIER dhSinglePass-stdDH-sha1kdf-scheme
  PARAMS TYPE KeyWrapAlgorithm ARE required
  UKM -- TYPE unencoded data -- ARE preferredPresent
  SMIME-CAPS cap-kaa-dhSinglePass-stdDH-sha1kdf-scheme
}

```

```
dhSinglePass-stdDH-sha1kdf-scheme OBJECT IDENTIFIER ::= {  
    x9-63-scheme 2 }
```

```
kaa-dhSinglePass-stdDH-sha224kdf-scheme KEY-AGREE ::= {  
    IDENTIFIER dhSinglePass-stdDH-sha224kdf-scheme  
    PARAMS TYPE KeyWrapAlgorithm ARE required  
    UKM -- TYPE unencoded data -- ARE preferredPresent  
    SMIME-CAPS cap-kaa-dhSinglePass-stdDH-sha224kdf-scheme  
}
```

```
dhSinglePass-stdDH-sha224kdf-scheme OBJECT IDENTIFIER ::= {  
    secg-scheme 11 0 }
```

```
kaa-dhSinglePass-stdDH-sha256kdf-scheme KEY-AGREE ::= {  
    IDENTIFIER dhSinglePass-stdDH-sha256kdf-scheme  
    PARAMS TYPE KeyWrapAlgorithm ARE required  
    UKM -- TYPE unencoded data -- ARE preferredPresent  
    SMIME-CAPS cap-kaa-dhSinglePass-stdDH-sha256kdf-scheme  
}
```

```
dhSinglePass-stdDH-sha256kdf-scheme OBJECT IDENTIFIER ::= {  
    secg-scheme 11 1 }
```

```
kaa-dhSinglePass-stdDH-sha384kdf-scheme KEY-AGREE ::= {  
    IDENTIFIER dhSinglePass-stdDH-sha384kdf-scheme  
    PARAMS TYPE KeyWrapAlgorithm ARE required  
    UKM -- TYPE unencoded data -- ARE preferredPresent  
    SMIME-CAPS cap-kaa-dhSinglePass-stdDH-sha384kdf-scheme  
}
```

```
dhSinglePass-stdDH-sha384kdf-scheme OBJECT IDENTIFIER ::= {  
    secg-scheme 11 2 }
```

```
kaa-dhSinglePass-stdDH-sha512kdf-scheme KEY-AGREE ::= {  
    IDENTIFIER dhSinglePass-stdDH-sha512kdf-scheme  
    PARAMS TYPE KeyWrapAlgorithm ARE required  
    UKM -- TYPE unencoded data -- ARE preferredPresent  
    SMIME-CAPS cap-kaa-dhSinglePass-stdDH-sha512kdf-scheme  
}
```

```
dhSinglePass-stdDH-sha512kdf-scheme OBJECT IDENTIFIER ::= {  
    secg-scheme 11 3 }
```

```
--
-- Diffie-Hellman Single Pass, Cofactor, with KDFs
--

kaa-dhSinglePass-cofactorDH-sha1kdf-scheme KEY-AGREE ::= {
  IDENTIFIER dhSinglePass-cofactorDH-sha1kdf-scheme
  PARAMS TYPE KeyWrapAlgorithm ARE required
  UKM -- TYPE unencoded data -- ARE preferredPresent
  SMIME-CAPS cap-kaa-dhSinglePass-cofactorDH-sha1kdf-scheme
}

dhSinglePass-cofactorDH-sha1kdf-scheme OBJECT IDENTIFIER ::= {
  x9-63-scheme 3 }

kaa-dhSinglePass-cofactorDH-sha224kdf-scheme KEY-AGREE ::= {
  IDENTIFIER dhSinglePass-cofactorDH-sha224kdf-scheme
  PARAMS TYPE KeyWrapAlgorithm ARE required
  UKM -- TYPE unencoded data -- ARE preferredPresent
  SMIME-CAPS cap-kaa-dhSinglePass-cofactorDH-sha224kdf-scheme
}

dhSinglePass-cofactorDH-sha224kdf-scheme OBJECT IDENTIFIER ::= {
  secg-scheme 14 0 }

kaa-dhSinglePass-cofactorDH-sha256kdf-scheme KEY-AGREE ::= {
  IDENTIFIER dhSinglePass-cofactorDH-sha256kdf-scheme
  PARAMS TYPE KeyWrapAlgorithm ARE required
  UKM -- TYPE unencoded data -- ARE preferredPresent
  SMIME-CAPS cap-kaa-dhSinglePass-cofactorDH-sha256kdf-scheme
}

dhSinglePass-cofactorDH-sha256kdf-scheme OBJECT IDENTIFIER ::= {
  secg-scheme 14 1 }

kaa-dhSinglePass-cofactorDH-sha384kdf-scheme KEY-AGREE ::= {
  IDENTIFIER dhSinglePass-cofactorDH-sha384kdf-scheme
  PARAMS TYPE KeyWrapAlgorithm ARE required
  UKM -- TYPE unencoded data -- ARE preferredPresent
  SMIME-CAPS cap-kaa-dhSinglePass-cofactorDH-sha384kdf-scheme
}

dhSinglePass-cofactorDH-sha384kdf-scheme OBJECT IDENTIFIER ::= {
  secg-scheme 14 2 }
```

```
kaa-dhSinglePass-cofactorDH-sha512kdf-scheme KEY-AGREE ::= {
  IDENTIFIER dhSinglePass-cofactorDH-sha512kdf-scheme
  PARAMS TYPE KeyWrapAlgorithm ARE required
  UKM -- TYPE unencoded data -- ARE preferredPresent
  SMIME-CAPS cap-kaa-dhSinglePass-cofactorDH-sha512kdf-scheme
}

dhSinglePass-cofactorDH-sha512kdf-scheme OBJECT IDENTIFIER ::= {
  secg-scheme 14 3 }

--
-- MQV Single Pass, Cofactor, with KDFs
--

kaa-mqvSinglePass-sha1kdf-scheme KEY-AGREE ::= {
  IDENTIFIER mqvSinglePass-sha1kdf-scheme
  PARAMS TYPE KeyWrapAlgorithm ARE required
  UKM -- TYPE unencoded data -- ARE preferredPresent
  SMIME-CAPS cap-kaa-mqvSinglePass-sha1kdf-scheme
}

mqvSinglePass-sha1kdf-scheme OBJECT IDENTIFIER ::= {
  x9-63-scheme 16 }

kaa-mqvSinglePass-sha224kdf-scheme KEY-AGREE ::= {
  IDENTIFIER mqvSinglePass-sha224kdf-scheme
  PARAMS TYPE KeyWrapAlgorithm ARE required
  UKM -- TYPE unencoded data -- ARE preferredPresent
  SMIME-CAPS cap-kaa-mqvSinglePass-sha224kdf-scheme
}

mqvSinglePass-sha224kdf-scheme OBJECT IDENTIFIER ::= {
  secg-scheme 15 0 }

kaa-mqvSinglePass-sha256kdf-scheme KEY-AGREE ::= {
  IDENTIFIER mqvSinglePass-sha256kdf-scheme
  PARAMS TYPE KeyWrapAlgorithm ARE required
  UKM -- TYPE unencoded data -- ARE preferredPresent
  SMIME-CAPS cap-kaa-mqvSinglePass-sha256kdf-scheme
}

mqvSinglePass-sha256kdf-scheme OBJECT IDENTIFIER ::= {
  secg-scheme 15 1 }
```

```
kaa-mqvSinglePass-sha384kdf-scheme KEY-AGREE ::= {
  IDENTIFIER mqvSinglePass-sha384kdf-scheme
  PARAMS TYPE KeyWrapAlgorithm ARE required
  UKM -- TYPE unencoded data -- ARE preferredPresent
  SMIME-CAPS cap-kaa-mqvSinglePass-sha384kdf-scheme
}

mqvSinglePass-sha384kdf-scheme OBJECT IDENTIFIER ::= {
  secg-scheme 15 2 }

kaa-mqvSinglePass-sha512kdf-scheme KEY-AGREE ::= {
  IDENTIFIER mqvSinglePass-sha512kdf-scheme
  PARAMS TYPE KeyWrapAlgorithm ARE required
  UKM -- TYPE unencoded data -- ARE preferredPresent
  SMIME-CAPS cap-kaa-mqvSinglePass-sha512kdf-scheme
}

mqvSinglePass-sha512kdf-scheme OBJECT IDENTIFIER ::= {
  secg-scheme 15 3 }

--
-- Key Wrap Algorithms: Imported from [CMS-ASN]
--

KeyWrapAlgorithm ::= AlgorithmIdentifier {KEY-WRAP, { KeyWrapAlgs } }

KeyWrapAlgs KEY-WRAP ::= {
  kwa-3DESWrap      |
  kwa-aes128-wrap   |
  kwa-aes192-wrap   |
  kwa-aes256-wrap,
  ...
}
```

```
--
-- Content Encryption Algorithms: Imported from [CMS-ASN]
--

-- Constrains the EnvelopedData EncryptedContentInfo encryptedContent
-- field and the AuthEnvelopedData EncryptedContentInfo
-- contentEncryptionAlgorithm field

-- ContentEncryptionAlgs CONTENT-ENCRYPTION ::= {
--   cea-3DES-cbc |
--   cea-aes128-cbc |
--   cea-aes192-cbc |
--   cea-aes256-cbc |
--   cea-aes128-ccm |
--   cea-aes192-ccm |
--   cea-aes256-ccm |
--   cea-aes128-gcm |
--   cea-aes192-gcm |
--   cea-aes256-gcm,
--   ...
-- }

-- des-ede3-cbc and aes*-cbc are used with EnvelopedData and
-- EncryptedData
-- aes*-ccm are used with AuthEnvelopedData
-- aes*-gcm are used with AuthEnvelopedData
-- (where * is 128, 192, and 256)

--
-- Message Authentication Code Algorithms
--

-- Constrains the AuthenticatedData
-- MessageAuthenticationCodeAlgorithm field
--

MessageAuthAlgs MAC-ALGORITHM ::= {
--   maca-hMAC-SHA1 |
--   maca-hMAC-SHA224 |
--   maca-hMAC-SHA256 |
--   maca-hMAC-SHA384 |
--   maca-hMAC-SHA512,
--   ...
-- }
```

```
maca-hMAC-SHA224 MAC-ALGORITHM ::= {
  IDENTIFIER id-hmacWithSHA224
  PARAMS ARE absent
  IS-KEYED-MAC TRUE
  SMIME-CAPS cap-hMAC-SHA224
}

id-hmacWithSHA224 OBJECT IDENTIFIER ::= {
  iso(1) member-body(2) us(840) rsadsi(113549)
  digestAlgorithm(2) 8 }

maca-hMAC-SHA256 MAC-ALGORITHM ::= {
  IDENTIFIER id-hmacWithSHA256
  PARAMS ARE absent
  IS-KEYED-MAC TRUE
  SMIME-CAPS cap-hMAC-SHA256
}

id-hmacWithSHA256 OBJECT IDENTIFIER ::= {
  iso(1) member-body(2) us(840) rsadsi(113549)
  digestAlgorithm(2) 9 }

maca-hMAC-SHA384 MAC-ALGORITHM ::= {
  IDENTIFIER id-hmacWithSHA384
  PARAMS ARE absent
  IS-KEYED-MAC TRUE
  SMIME-CAPS cap-hMAC-SHA384
}

id-hmacWithSHA384 OBJECT IDENTIFIER ::= {
  iso(1) member-body(2) us(840) rsadsi(113549)
  digestAlgorithm(2) 10 }

maca-hMAC-SHA512 MAC-ALGORITHM ::= {
  IDENTIFIER id-hmacWithSHA512
  PARAMS ARE absent
  IS-KEYED-MAC TRUE
  SMIME-CAPS cap-hMAC-SHA512
}

id-hmacWithSHA512 OBJECT IDENTIFIER ::= {
  iso(1) member-body(2) us(840) rsadsi(113549)
  digestAlgorithm(2) 11 }
```



```
--
-- Originator Public Key Algorithms
--

-- Constraints on KeyAgreeRecipientInfo OriginatorIdentifierOrKey
-- OriginatorPublicKey algorithm field

OriginatorPKAlgorithms PUBLIC-KEY ::= {
    opka-ec,
    ...
}

opka-ec PUBLIC-KEY ::= {
    IDENTIFIER id-ecPublicKey
    KEY ECPublicKey
    PARAMS TYPE CHOICE { n NULL, p ECPParameters } ARE preferredAbsent
}

-- Format for both ephemeral and static public keys: Imported from
-- [PKI-ALG]

-- ECPublicKey ::= OCTET STRING

-- ECPParameters ::= CHOICE {
--     namedCurve          CURVE.&id({NamedCurve})
--     commented out in [PKI-ALG] implicitCurve    NULL
--     commented out in [PKI-ALG] specifiedCurve    SpecifiedECDomain
--     commented out in [PKI-ALG] ...
-- }
-- implicitCurve and specifiedCurve MUST NOT be used in PKIX.
-- Details for SpecifiedECDomain can be found in [X9.62].
-- Any future additions to this CHOICE should be coordinated
-- with ANSI X.9.

-- Format of KeyAgreeRecipientInfo ukm field when used with
-- ECMQV

MQVUserKeyingMaterial ::= SEQUENCE {
    ephemeralPublicKey      OriginatorPublicKey,
    addedukm                [0] EXPLICIT UserKeyingMaterial OPTIONAL
}
```

```
-- 'SharedInfo' for input to KDF when using ECDH and ECMQV with
-- EnvelopedData, AuthenticatedData, or AuthEnvelopedData
```

```
ECC-CMS-SharedInfo ::= SEQUENCE {
    keyInfo          KeyWrapAlgorithm,
    entityUInfo [0] EXPLICIT OCTET STRING OPTIONAL,
    suppPubInfo [2] EXPLICIT OCTET STRING
}
```

```
--
-- S/MIME CAPS for algorithms in this document
--
```

```
SMimeCAPS SMIME-CAPS ::= {
-- mda-sha1.&smimeCaps |
-- mda-sha224.&smimeCaps |
-- mda-sha256.&smimeCaps |
-- mda-sha384.&smimeCaps |
-- mda-sha512.&smimeCaps |
-- sa-ecdsaWithSHA1.&smimeCaps |
-- sa-ecdsaWithSHA224.&smimeCaps |
-- sa-ecdsaWithSHA256.&smimeCaps |
-- sa-ecdsaWithSHA384.&smimeCaps |
-- sa-ecdsaWithSHA512.&smimeCaps |
  kaa-dhSinglePass-stdDH-sha1kdf-scheme.&smimeCaps |
  kaa-dhSinglePass-stdDH-sha224kdf-scheme.&smimeCaps |
  kaa-dhSinglePass-stdDH-sha256kdf-scheme.&smimeCaps |
  kaa-dhSinglePass-stdDH-sha384kdf-scheme.&smimeCaps |
  kaa-dhSinglePass-stdDH-sha512kdf-scheme.&smimeCaps |
  kaa-dhSinglePass-cofactorDH-sha1kdf-scheme.&smimeCaps |
  kaa-dhSinglePass-cofactorDH-sha224kdf-scheme.&smimeCaps |
  kaa-dhSinglePass-cofactorDH-sha256kdf-scheme.&smimeCaps |
  kaa-dhSinglePass-cofactorDH-sha384kdf-scheme.&smimeCaps |
  kaa-dhSinglePass-cofactorDH-sha512kdf-scheme.&smimeCaps |
  kaa-mqvSinglePass-sha1kdf-scheme.&smimeCaps |
  kaa-mqvSinglePass-sha224kdf-scheme.&smimeCaps |
  kaa-mqvSinglePass-sha256kdf-scheme.&smimeCaps |
  kaa-mqvSinglePass-sha384kdf-scheme.&smimeCaps |
  kaa-mqvSinglePass-sha512kdf-scheme.&smimeCaps |
-- kwa-3des.&smimeCaps |
-- kwa-aes128.&smimeCaps |
-- kwa-aes192.&smimeCaps |
-- kwa-aes256.&smimeCaps |
-- cea-3DES-cbc.&smimeCaps |
-- cea-aes128-cbc.&smimeCaps |
}
```

```
-- cea-aes192-cbc.&smimeCaps |
-- cea-aes256-cbc.&smimeCaps |
-- cea-aes128-ccm.&smimeCaps |
-- cea-aes192-ccm.&smimeCaps |
-- cea-aes256-ccm.&smimeCaps |
-- cea-aes128-gcm.&smimeCaps |
-- cea-aes192-gcm.&smimeCaps |
-- cea-aes256-gcm.&smimeCaps |
-- maca-hMAC-SHA1.&smimeCaps |
   maca-hMAC-SHA224.&smimeCaps |
   maca-hMAC-SHA256.&smimeCaps |
   maca-hMAC-SHA384.&smimeCaps |
   maca-hMAC-SHA512.&smimeCaps,
   ...
}

cap-kaa-dhSinglePass-stdDH-sha1kdf-scheme SMIME-CAPS ::= {
  TYPE KeyWrapAlgorithm
  IDENTIFIED BY dhSinglePass-stdDH-sha1kdf-scheme
}

cap-kaa-dhSinglePass-stdDH-sha224kdf-scheme SMIME-CAPS ::= {
  TYPE KeyWrapAlgorithm
  IDENTIFIED BY dhSinglePass-stdDH-sha224kdf-scheme
}

cap-kaa-dhSinglePass-stdDH-sha256kdf-scheme SMIME-CAPS ::= {
  TYPE KeyWrapAlgorithm
  IDENTIFIED BY dhSinglePass-stdDH-sha256kdf-scheme
}

cap-kaa-dhSinglePass-stdDH-sha384kdf-scheme SMIME-CAPS ::= {
  TYPE KeyWrapAlgorithm
  IDENTIFIED BY dhSinglePass-stdDH-sha384kdf-scheme
}

cap-kaa-dhSinglePass-stdDH-sha512kdf-scheme SMIME-CAPS ::= {
  TYPE KeyWrapAlgorithm
  IDENTIFIED BY dhSinglePass-stdDH-sha512kdf-scheme
}

cap-kaa-dhSinglePass-cofactorDH-sha1kdf-scheme SMIME-CAPS ::= {
  TYPE KeyWrapAlgorithm
  IDENTIFIED BY dhSinglePass-cofactorDH-sha1kdf-scheme
}
```

```
cap-kaa-dhSinglePass-cofactorDH-sha224kdf-scheme SMIME-CAPS ::= {  
    TYPE KeyWrapAlgorithm  
    IDENTIFIED BY dhSinglePass-cofactorDH-sha224kdf-scheme  
}  
  
cap-kaa-dhSinglePass-cofactorDH-sha256kdf-scheme SMIME-CAPS ::= {  
    TYPE KeyWrapAlgorithm  
    IDENTIFIED BY dhSinglePass-cofactorDH-sha256kdf-scheme  
}  
  
cap-kaa-dhSinglePass-cofactorDH-sha384kdf-scheme SMIME-CAPS ::= {  
    TYPE KeyWrapAlgorithm  
    IDENTIFIED BY dhSinglePass-cofactorDH-sha384kdf-scheme  
}  
  
cap-kaa-dhSinglePass-cofactorDH-sha512kdf-scheme SMIME-CAPS ::= {  
    TYPE KeyWrapAlgorithm  
    IDENTIFIED BY dhSinglePass-cofactorDH-sha512kdf-scheme  
}  
  
cap-kaa-mqvSinglePass-sha1kdf-scheme SMIME-CAPS ::= {  
    TYPE KeyWrapAlgorithm  
    IDENTIFIED BY mqvSinglePass-sha1kdf-scheme  
}  
  
cap-kaa-mqvSinglePass-sha224kdf-scheme SMIME-CAPS ::= {  
    TYPE KeyWrapAlgorithm  
    IDENTIFIED BY mqvSinglePass-sha224kdf-scheme  
}  
  
cap-kaa-mqvSinglePass-sha256kdf-scheme SMIME-CAPS ::= {  
    TYPE KeyWrapAlgorithm  
    IDENTIFIED BY mqvSinglePass-sha256kdf-scheme  
}  
  
cap-kaa-mqvSinglePass-sha384kdf-scheme SMIME-CAPS ::= {  
    TYPE KeyWrapAlgorithm  
    IDENTIFIED BY mqvSinglePass-sha384kdf-scheme  
}  
  
cap-kaa-mqvSinglePass-sha512kdf-scheme SMIME-CAPS ::= {  
    TYPE KeyWrapAlgorithm  
    IDENTIFIED BY mqvSinglePass-sha512kdf-scheme  
}
```

```
cap-hMAC-SHA224 SMIME-CAPS ::= { IDENTIFIED BY id-hmacWithSHA224 }  
cap-hMAC-SHA256 SMIME-CAPS ::= { IDENTIFIED BY id-hmacWithSHA256 }  
cap-hMAC-SHA384 SMIME-CAPS ::= { IDENTIFIED BY id-hmacWithSHA384 }  
cap-hMAC-SHA512 SMIME-CAPS ::= { IDENTIFIED BY id-hmacWithSHA512 }  
  
END
```

## Appendix B Changes since [RFC 3278](#)

The following summarizes the changes:

- Abstract: The basis of the document was changed to refer to NIST FIPS 186-3 and SP800-56A. However, to maintain backwards compatibility the Key Derivation Function from ANSI/SEC1 is retained.
- [Section 1](#): A bullet was added to address AuthEnvelopedData.
- [Section 2.1](#): A sentence was added to indicate FIPS180-3 is used with ECDSA. Replaced reference to ANSI X9.62 with FIPS186-3.
- [Section 2.1.1](#): The permitted digest algorithms were expanded from SHA-1 to SHA-1, SHA-224, SHA-256, SHA-384, and SHA-512.
- [Section 2.1.2](#) and 2.1.3: The bullet addressing integer "e" was deleted.
- [Section 3](#): Added explanation of why static-static ECDH is not included.
- [Section 3.1](#): The reference for DH was changed from [RFC 3852](#) to [RFC 3370](#). Provided text to indicate fields of EnvelopedData are as in CMS.
- [Section 3.1.1](#): The text was updated to include description of all KeyAgreeRecipientInfo fields. Parameters for id-ecPublicKey field changed from NULL to absent or ECPParameter. Additional information about ukm was added.
- [Section 3.2](#): The sentence describing the advantages of 1-Pass ECMQV was rewritten.

- [Section 3.2.1](#): The text was updated to include description of all fields. Parameters for id-ecPublicKey field changed from NULL to absent or ECPParameters.
- Sections [3.2.2](#) and [4.1.2](#): The re-use of ephemeral keys paragraph was reworded.
- [Section 4.1](#): The sentences describing the advantages of 1-Pass ECMQV was moved to [Section 4](#).
- [Section 4.1.2](#): The note about the attack was moved to [Section 4](#).
- [Section 4.2](#): This section was added to address AuthEnvelopedData with ECMQV.
- [Section 5](#): This section was moved to [Section 8](#). The 1st paragraph was modified to recommend both SignedData and EnvelopedData. The requirements were updated for hash algorithms and recommendations for matching curves and hash algorithms. Also the requirements were expanded to indicate which ECDH and ECMQV variants, key wrap algorithms, and content encryption algorithms are required for each of the content types used in this document. The permitted digest algorithms used in key derivations functions (KDFs) were expanded from SHA-1 to SHA-1, SHA-224, SHA-256, SHA-384, and SHA-512.
- [Section 6](#) (formerly 7): This section was updated to allow for SMIMECapabilities to be present in certificates. The S/MIME capabilities for ECDSA with SHA-224, SHA-256, SHA-384, and SHA-512 were added to the list of S/MIME Capabilities. Also updated to include S/MIME capabilities for ECDH and ECMQV using the SHA-224, SHA-256, SHA-384, and SHA-512 algorithms as the KDF.
- [Section 7.1](#) (formerly 8.1): Added sub-sections for digest, signature, originator public key, key agreement, content encryption, key wrap, and message authentication code algorithms. Pointed to algorithms and parameters in appropriate documents for: SHA-224, SHA-256, SHA-384, and SHA-512 as well as SHA-224, SHA-256, SHA-384, and SHA-512 with ECDSA. Also added algorithm identifiers for ECDH std, ECDH cofactor, and ECMQV with SHA-224, SHA-256, SHA-384, and SHA-512 algorithms as the KDF. Changed id-ecPublicKey parameters to be absent, NULL, or ECPParameters, and if present the originator's ECPParameters must match the recipient's ECPParameters.

- [Section 7.2](#) (formerly 8.2): Updated to include AuthEnvelopedData. Also, added text to address support requirement for compressed, uncompressed, and hybrid keys, changed pointers from ANSI X9.61 to PKIX (where ECDSA-Sig-Value is imported), changed pointers from SECG to NIST specs, and updated example of suppPubInfo to be AES-256. keyInfo's parameters changed from NULL to any associated parameters (AES wraps have absent parameters).
- [Section 9](#): Replaced text, which was a summary paragraph, with an updated security considerations section. Paragraph referring to definitions of SHA-224, SHA-256, SHA-384, and SHA-512 is deleted.
- Updated references.
- Added ASN.1 modules.
- Updated acknowledgements section.

#### Acknowledgements

The methods described in this document are based on work done by the ANSI X9F1 working group. The authors wish to extend their thanks to ANSI X9F1 for their assistance. The authors also wish to thank Peter de Rooij for his patient assistance. The technical comments of Francois Rousseau were valuable contributions.

Many thanks go out to the other authors of [RFC 3278](#): Simon Blake-Wilson and Paul Lambert. Without [RFC 3278](#) this version wouldn't exist.

The authors also wish to thank Alfred Hoenes, Paul Hoffman, Russ Housley, and Jim Schaad for their valuable input.

#### Authors' Addresses

Sean Turner

IECA, Inc.  
3057 Nutley Street, Suite 106  
Fairfax, VA 22031  
USA

Email: [turners@ieca.com](mailto:turners@ieca.com)

Daniel R. L. Brown

Certicom Corp  
5520 Explorer Drive #400  
Mississauga, ON L4W 5L1  
CANADA

Email: [dbrown@certicom.com](mailto:dbrown@certicom.com)