

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: December 29, 2012

O. Troan
W. Dec
Cisco Systems
X. Li
C. Bao
Y. Zhai
CERNET Center/Tsinghua
University
S. Matsushima
SoftBank Telecom
T. Murakami
IP Infusion
June 27, 2012

Mapping of Address and Port (MAP)
draft-ietf-softwire-map-01

Abstract

This document describes a mechanism for transporting IPv4 packets across an IPv6 network, and a generic mechanism for mapping between IPv6 addresses and IPv4 addresses and transport layer ports.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on December 29, 2012.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents

(<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	4
2.	Conventions	5
3.	Terminology	5
4.	Architecture	7
5.	Mapping Algorithm	8
5.1.	Port mapping algorithm	10
5.1.1.	Bit Representation of the Algorithm	11
5.1.2.	GMA examples	11
5.1.3.	Algorithm Provisioning Considerations	12
5.2.	Basic mapping rule (BMR)	12
5.3.	Forwarding mapping rule (FMR)	15
5.4.	Default mapping rule (DMR)	16
6.	The IPv6 Interface Identifier	17
7.	MAP Configuration	18
7.1.	MAP CE	18
7.2.	MAP BR	19
7.3.	Backwards compatibility	19
8.	Forwarding Considerations	19
8.1.	Receiving rules	20
8.2.	MAP BR	20
8.2.1.	IPv6 to IPv4	20
8.2.2.	IPv4 to IPv6	20
9.	ICMP	21
9.1.	Translating ICMP/ICMPv6 Headers	21
10.	Fragmentation and Path MTU Discovery	22
10.1.	Fragmentation in the MAP domain	22
10.2.	Receiving IPv4 Fragments on the MAP domain borders	23
10.3.	Sending IPv4 fragments to the outside	23
11.	NAT44 Considerations	23
12.	Deployment Considerations	23
12.1.	Use cases	23
12.1.1.	Mesh Model	23
12.1.2.	Hub & Spoke Model	24
12.1.3.	Communication with IPv6 servers in the MAP-T domain	24
13.	IANA Considerations	24
14.	Security Considerations	24
15.	Contributors	25
16.	Acknowledgements	26
17.	References	26
17.1.	Normative References	26
17.2.	Informative References	27
Appendix A.	Example of MAP-T translation	30
	Authors' Addresses	32

1. Introduction

Mapping IPv4 addresses in IPv6 addresses has been described in numerous mechanisms dating back to 1996 [[RFC1933](#)]. The Automatic tunneling mechanism described in [RFC1933](#), assigned a globally unique IPv6 address to a host by combining the host's IPv4 address with a well-known IPv6 prefix. Given an IPv6 packet with a destination address with an embedded IPv4 address, a node could automatically tunnel this packet by extracting the IPv4 tunnel end-point address from the IPv6 destination address.

There are numerous variations of this idea, described in 6over4 [[RFC2529](#)], 6to4 [[RFC3056](#)], ISATAP [[RFC5214](#)], and 6rd [[RFC5969](#)].

The commonalities of all these IPv6 over IPv4 mechanisms are:

- o Automatically provisions an IPv6 address for a host or an IPv6 prefix for a site
- o Algorithmic or implicit address resolution for tunneling or encapsulation. Given an IPv6 destination address, an IPv4 tunnel endpoint address can be calculated. Likewise for translation, an IPv4 address can be calculated from an IPv6 destination address and vice versa.
- o Embedding of an IPv4 address or part thereof and optionally transport layer ports into an IPv6 address.

In phases of IPv4 to IPv6 migration, IPv6 only networks will be common, while there will still be a need for residual IPv4 deployment. This document describes a generic mapping of IPv4 to IPv6, and mechanisms for encapsulation (IPv4 over IPv6) and translation between the two protocols that use this mapping.

Just as the IPv6 over IPv4 mechanisms referred to above, the residual IPv4 over IPv6 mechanisms must be capable of:

- o Provisioning an IPv4 prefix, an IPv4 address or a shared IPv4 address.
- o Algorithmically map between an IPv4 prefix, IPv4 address or a shared IPv4 address and an IPv6 address.

The unified mapping scheme described here supports translation mode, encapsulation mode, in both mesh and hub and spoke topologies.

This document describes delivery of IPv4 unicast service across an IPv6 infrastructure. IPv4 multicast is not considered further in

this document.

The A+P (Address and Port) architecture of sharing an IPv4 address by distributing the port space is described in [[RFC6346](#)]. Specifically [section 4 of \[RFC6346\]](#) covers stateless mapping. The corresponding stateful solution DS-lite is described in [[RFC6333](#)]. The motivation for the work is described in [[I-D.ietf-softwire-stateless-4v6-motivation](#)].

A companion document defines a DHCPv6 option for provisioning of MAP [[I-D.mdt-softwire-map-dhcp-option](#)]. Other means of provisioning is possible. Deployment considerations are described in [[I-D.mdt-softwire-map-deployment](#)].

MAP relies on IPv6 and is designed to deliver production-quality dual-stack service while allowing IPv4 to be phased out within the SP network. The phasing out of IPv4 within the SP network is independent of whether the end user disables IPv4 service or not. Further, "Greenfield"; IPv6-only networks may use MAP in order to deliver IPv4 to sites via the IPv6 network.

[2. Conventions](#)

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

[3. Terminology](#)

MAP domain:	One or more MAP CEs and BRs connected to the same virtual link. A service provider may deploy a single MAP domain, or may utilize multiple MAP domains.
MAP Rule	A set of parameters describing the mapping between an IPv4 prefix, IPv4 address or shared IPv4 address and an IPv6 prefix or address. Each domain uses a different mapping rule set.
MAP node	A device that implements MAP.
MAP Border Relay (BR):	A MAP enabled router managed by the service provider at the edge of a MAP domain. A Border Relay router has at least an IPv6-enabled interface and an IPv4 interface

connected to the native IPv4 network. A MAP BR may also be referred to simply as a "BR" within the context of MAP.

MAP Customer Edge (CE): A device functioning as a Customer Edge router in a MAP deployment. A typical MAP CE adopting MAP rules will serve a residential site with one WAN side interface, and one or more LAN side interfaces. A MAP CE may also be referred to simply as a "CE" within the context of MAP.

Port-set: Each node has a separate part of the transport layer port space; denoted as a port-set.

Port-set ID (PSID): Algorithmically identifies a set of ports exclusively assigned to the CE.

Shared IPv4 address: An IPv4 address that is shared among multiple CEs. Only ports that belong to the assigned port-set can be used for communication. Also known as a Port-Restricted IPv4 address.

End-user IPv6 prefix: The IPv6 prefix assigned to an End-user CE by other means than MAP itself. E.g. Provisioned using DHCPv6 PD [[RFC3633](#)] or configured manually. It is unique for each CE.

MAP IPv6 address: The IPv6 address used to reach the MAP function of a CE from other CEs and from BRs.

Rule IPv6 prefix: An IPv6 prefix assigned by a Service Provider for a mapping rule.

Rule IPv4 prefix: An IPv4 prefix assigned by a Service Provider for a mapping rule.

Embedded Address (EA) bits: The IPv4 EA-bits in the IPv6 address identify an IPv4 prefix/address (or part thereof) or a shared IPv4 address (or part thereof) and a port-set identifier.

MRT: MAP Rule table. Address and Port aware data structure, supporting longest match lookups. The MRT is used by the MAP forwarding function.

MAP-T: Mapping of Address and Port - Translation mode. MAP-T utilizes IPv4/IPv6 translation as per [\[RFC6145\]](#).

MAP-E: Mapping of Address and Port - Encapsulation mode. MAP-E utilizes a simple IPv4-in-IPv6 tunneling [\[RFC2473\]](#).

4. Architecture

The MAP mechanism is largely built up using existing standard building blocks. The existing NAT44 on the CE is used with additional support for restricting transport protocol ports, ICMP identifiers and fragment identifiers to the configured port set. MAP supports two forwarding modes, one using stateless NAT64 as specified in [\[RFC6145\]](#) and one encapsulation mode specified in [\[RFC2473\]](#). In addition MAP specifies an algorithm to do "address resolution" from an IPv4 address and port to an IPv6 address. This algorithmic mapping is specified in [section 5](#).

A full IPv4 address or IPv4 prefix can be used like today, e.g. for identifying an interface or as a DHCP pool. A shared IPv4 address on the other hand, MUST NOT be used to identify an interface. While it is theoretically possible to make host stacks and applications port-aware, that is considered a too drastic change to the IP model [\[RFC6250\]](#).

The MAP architecture described here, restricts the use of the shared IPv4 address to only be used as the global address (outside) of the NAPT [\[RFC2663\]](#) running on the CE. The NAPT MUST in turn be connected to a MAP aware forwarding function, that does encapsulation/decapsulation or translation to IPv6.

When MAP is used to provision a full IPv4 address or an IPv4 prefix to the CE, these restrictions do not apply.

For packets outbound from the private IPv4 network, the CE NAPT MUST translate transport identifiers (e.g. TCP and UDP port numbers) so that they fall within the assigned CE's port-range.

The forwarding function uses the Mapping Rule Table (MRT) to make forwarding decisions. The table consist of the mapping rules. An entry in the table consists of an IPv4 prefix and PSID. The normal best matching prefix algorithm is used. With a maximum key length of 48 (Length of IPv4 address (32) + Length of Transport layer port field (16)). E.g. with a sharing ratio of 64 (6 bit PSID length) a "host route" for this CE would be a /38 (32 + 6).




Figure 1: Network Topology

The MAP BR is responsible for connecting external IPv4 networks to all devices in one or more MAP domains.

The translation mode allows communication between both IPv4-only and any IPv6 enabled end hosts, with native IPv6-only servers which are using IPv4-mapped IPv6 address based on DMR in the MAP-T domain. In this mode, the IPv6-only servers SHOULD have both A and AAAA records in the authorities DNS server [RFC6219]. DNS64 [RFC6147] become required only when IPv6 servers in the MAP-T domain are expected themselves to initiate communication to external IPv4-only hosts.

5. Mapping Algorithm

A MAP node is provisioned with one or more mapping rules.

Mapping rules are used differently depending on their function. Every MAP node must be provisioned with a Basic mapping rule. This is used by the node to configure its IPv4 address, IPv4 prefix or

shared IPv4 address. This same basic rule can also be used for forwarding, where an IPv4 destination address and optionally a destination port is mapped into an IPv6 address or prefix. Additional mapping rules are specified to allow for e.g. multiple different IPv4 subnets to exist within the domain and optimize forwarding between them.

Traffic outside of the domain (i.e. when the destination IPv4 address does not match (using longest matching prefix) any Rule IPv4 prefix in the Rules database) will be forward using the Default mapping rule. The Default mapping rule maps outside destinations to the BR's IPv6 address or prefix.

Note: The forwarding mode is intended to apply uniformly for rules in a domain - subject to further WG feedback in this area.

There are three types of mapping rules:

1. Basic Mapping Rule - used for IPv4 prefix, address or port set assignment. There can only be one Basic Mapping Rule per End-user IPv6 prefix. The Basic Mapping Rule is used to configure the MAP IPv6 address or prefix.
 - * Rule IPv6 prefix (including prefix length)
 - * Rule IPv4 prefix (including prefix length)
 - * Rule EA-bits length (in bits)
 - * Rule Port Parameters (optional)
 - * Forwarding mode
2. Forwarding Mapping Rule - used for forwarding. The Basic Mapping Rule is also a Forwarding Mapping Rule. Each Forwarding Mapping Rule will result in an entry in the MRT for the Rule IPv4 prefix. The FMR consists of the same parameters as the BMR.
3. Default Mapping Rule - used for destinations outside the MAP domain. A 0.0.0.0/0 entry is installed in the MRT for this rule.
 - * IPv6 prefix of address of BR
 - * Forwarding mode

A MAP node finds its Basic Mapping Rule by doing a longest match between the End-user IPv6 prefix and the Rule IPv6 prefix in the Mapping Rule database. The rule is then used for IPv4 prefix,

address or shared address assignment.

A MAP IPv6 address (or prefix) is formed from the BMR Rule IPv6 prefix. This address MUST be assigned to an interface of the MAP node and is used to terminate all MAP traffic being sent or received to the node.

Port-aware IPv4 entries in the MRT are installed for all the Forwarding Mapping Rules and an IPv4 default route for the Default Mapping Rule.

In hub and spoke mode, all traffic MUST be forwarded using the Default Mapping Rule.

5.1. Port mapping algorithm

The port mapping algorithm is used in domains whose rules allow IPv4 address sharing. Different Port-Set Identifiers (PSID) MUST have non-overlapping port-sets. The two extreme cases are: (1) the port numbers are not contiguous for each PSID, but uniformly distributed across the port range (0-65535); (2) the port numbers are contiguous in a single range for each PSID. The port mapping algorithm proposed here is called the Generalized Modulus Algorithm (GMA) and supports both these cases.

For a given sharing ratio (R) and the maximum number of contiguous ports (M), the GMA algorithm is defined as:

1. The port number (P) of a given PSID (K) is composed of:

$$P = R * M * j + M * K + i$$

Where:

- * PSID: $K = 0$ to $R - 1$
- * Port range index: $j = (4096 / M) / R$ to $((65536 / M) / R) - 1$, if the port numbers (0 - 4095) are excluded.
- * Contiguous Port index: $i = 0$ to $M - 1$

2. The PSID (K) of a given port number (P) is determined by:

$$K = (\text{floor}(P/M)) \% R$$

Where:

* % is the modulus operator

* floor(arg) is a function that returns the largest integer not greater than arg.

5.1.1. Bit Representation of the Algorithm

Given a sharing ratio ($R=2^k$), the maximum number of contiguous ports ($M=2^m$), for any PSID (K) and available ports (P) can be represented as:




Figure 2: Bit representation

Where j and i are the same indexes defined in the port mapping algorithm.

For any port number, the PSID can be obtained by bit mask operation.

For $a > 0$, j MUST be larger than 0. This ensures that the algorithm excludes the system ports ([[I-D.ietf-tsvwg-iana-ports](#)]). For $a = 0$, j MAY be 0 to allow for the provisioning of the system ports.

5.1.2. GMA examples

For example, for $R = 1024$, PSID offset: $a = 4$ and PSID length: $k = 10$ bits

	Port-set-1	Port-set-2
PSID=0	4096, 4097, 4098, 4099,	8192, 8193, 8194, 8195, ...
PSID=1	4100, 4101, 4102, 4103,	8196, 8197, 8198, 8199, ...
PSID=2	4104, 4105, 4106, 4107,	8200, 8201, 8202, 8203, ...
PSID=3	4108, 4109, 4110, 4111,	8204, 8205, 8206, 8207, ...
...		
PSID=1023	8188, 8189, 8190, 8191,	12284, 12285, 12286, 12287, ...

Example 1: with offset = 4 ($a = 4$)

For example, for $R = 64$, $a = 0$ (PSID offset = 0 and PSID length = 6 bits):

	Port-set
PSID=0	[0 - 1023]
PSID=1	[1024 - 2047]
PSID=2	[2048 - 3071]
PSID=3	[3072 - 4095]
...	
PSID=63	[64512 - 65535]

Example 2: with offset = 0 ($a = 0$)

5.1.3. Algorithm Provisioning Considerations

The number of offset bits (a) and excluded ports are optionally provisioned via the "Rule Port Mapping Parameters" in the Basic Mapping Rule.

The defaults are:

- o Excluded ports : 0-4095
- o Offset bits (a) : 4

To simplify the port mapping algorithm the defaults are chosen so that the PSID field starts on a nibble boundary and the excluded port range (0-1023) is extended to 0-4095.

5.2. Basic mapping rule (BMR)




Figure 3: IPv6 address format

The Embedded Address bits (EA bits) are unique per end user within a Rule IPv6 prefix. The Rule IPv6 prefix is the part of the End-user IPv6 prefix that is common among all CEs using the same Basic Mapping Rule within the MAP domain. The EA bits encode the CE specific IPv4

address and port information. The EA bits can contain a full or part of an IPv4 prefix or address, and in the shared IPv4 address case contains a Port-Set Identifier (PSID).

The MAP IPv6 address is created by concatenating the End-user IPv6 prefix with the MAP subnet-id and the interface-id as specified in [Section 6](#).

The MAP subnet ID is defined to be the first subnet (all bits set to zero). A MAP node **MUST** reserve the first IPv6 prefix in a End-user IPv6 prefix for the purpose of MAP.

The MAP IPv6 is created by combining the End-User IPv6 prefix with the all zeros subnet-id and the MAP IPv6 interface identifier.

Shared IPv4 address:




Figure 4: Shared IPv4 address

Complete IPv4 address:




Figure 5: Complete IPv4 address

IPv4 prefix:




Figure 6: IPv4 prefix

The length of r MAY be zero, in which case the complete IPv4 address or prefix is encoded in the EA bits. If only a part of the IPv4 address/prefix is encoded in the EA bits, the Rule IPv4 prefix is provisioned to the CE by other means (e.g. a DHCPv6 option). To create a complete IPv4 address (or prefix), the IPv4 address suffix (p) from the EA bits, are concatenated with the Rule IPv4 prefix (r bits).

The offset of the EA bits field in the IPv6 address is equal to the BMR Rule IPv6 prefix length. The length of the EA bits field (o) is given by the BMR Rule EA-bits length. The sum of the Rule IPv6 Prefix length and the Rule EA-bits length MUST be less or equal than the End-user IPv6 prefix length.

If $o + r < 32$ (length of the IPv4 address in bits), then an IPv4 prefix is assigned.

If $o + r$ is equal to 32, then a full IPv4 address is to be assigned. The address is created by concatenating the Rule IPv4 prefix and the EA-bits.

If $o + r$ is > 32 , then a shared IPv4 address is to be assigned. The number of IPv4 address suffix bits (p) in the EA bits is given by $32 - r$ bits. The PSID bits are used to create a port-set. The length of the PSID bit field within EA bits is: $o - p$.

In the following examples, only the suffix (last 8 bits) of the IPv4 address is embedded in the EA bits ($r = 24$), while the IPv4 prefix (first 24 bits) is given in the BMR Rule IPv4 prefix.

Example:

Given:

End-user IPv6 prefix: 2001:db8:0012:3400::/56
 Basic Mapping Rule: {2001:db8:0000::/40 (Rule IPv6 prefix),
 192.0.2.0/24 (Rule IPv4 prefix),
 16 (Rule EA-bits length)}
 Sharing ratio: 256 ($16 - (32 - 24) = 8$. $2^8 = 256$)
 PSID offset: 4 (default value as per [section 5.1.3](#))

We get IPv4 address and port-set:

EA bits offset: 40
 IPv4 suffix bits (p): Length of IPv4 address (32) -
 IPv4 prefix length (24) = 8
 IPv4 address: 192.0.2.18 (0x12)

 PSID start: $40 + p = 40 + 8 = 48$
 PSID length: $o - p = 16 (56 - 40) - 8 = 8$
 PSID: 0x34
 Port-set-1: 4928, 4929, 4930, 4931, 4932, 4933, 4934, 4935,
 4936, 4937, 4938, 4939, 4940, 4941, 4942, 4943
 Port-set-2: 9024, 9025, 9026, 9027, 9028, 9029, 9030, 9031,
 9032, 9033, 9034, 9035, 9036, 9037, 9038, 9039
 ...
 Port-set-15: 62272, 62273, 62274, 62275,
 62276, 62277, 62278, 62279,
 62280, 62281, 62282, 62283,
 62284, 62285, 62286, 62287,

[5.3.](#) Forwarding mapping rule (FMR)

On adding an FMR rule, an IPv4 route is installed in the MRT for the Rule IPv4 prefix.

On forwarding an IPv4 packet, a best matching prefix lookup is done in the MRT and the correct FMR is chosen.




Figure 7: Deriving of MAP IPv6 address

Example:

Given:

IPv4 destination address: 192.0.2.18

IPv4 destination port: 9030

Forwarding Mapping Rule: {2001:db8:0000::/40 (Rule IPv6 prefix),
192.0.2.0/24 (Rule IPv4 prefix),
16 (Rule EA-bits length)}

PSID offset: 4 (default value as per [section 5.1.3](#))

We get IPv6 address:

IPv4 suffix bits (p): 32 - 24 = 8 (18 (0x12))

PSID length: 8

PSID: 0x34 (9030 (0x2346))

EA bits: 0x1234

MAP IPv6 address: 2001:db8:0012:3400:00c0:0002:1200:3400

5.4. Default mapping rule (DMR)

The Default Mapping rule is used to reach IPv4 destinations outside of the MAP domain. Traffic using this rule will be sent from a CE to a BR.

The DMR consist of the IPv6 address or IPv6 prefix of the BR. Which is used, is dependent on the forwarding mode used. Translation mode requires that the IPv4 destination address is encoded in the BR IPv6 address, so only a prefix is used in the DMR to allow for a generated

interface identifier. For the encapsulation mode the complete IPv6 address of the BR is used.

6. The IPv6 Interface Identifier

The Interface identifier format of a MAP node is based on the format specified in [section 2.2 of \[RFC6052\]](#), with the added PSID field if present, as shown in figure Figure 8.

```

+---+---+---+---+---+---+---+---+
|PL|  8  16  24  32  40  48  56  |
+---+---+---+---+---+---+---+---+
|64| u | IPv4 address  |  PSID | 0  |
+---+---+---+---+---+---+---+---+

```

Figure 8

For traffic destined outside of a MAP domain (i.e. for traffic following the default mapping rule), the destination IPv4 address is mapped to the IPv6 address or prefix of the BR. For MAP-E this is the IPv6 tunnel end point address of the BR, while for MAP-T this is the IPv6 converted representation of the IPv6 address per [RFC6052](#), shown in the form of an example in figure Figure 9 below. Note that the BR prefix-length is variable and can be both shorter or longer than 64 bits, up to 96 bits.

```

<----- 64 ----->< 8 ><----- 32 -----><--- 24 --->
+-----+---+---+---+---+---+---+---+
|          BR prefix          | u | IPv4 address |          0          |
+-----+---+---+---+---+---+---+---+

```

Figure 9

The encoding of the full IPv4 address into the interface identifier, both for the source and destination IPv6 addresses have been shown to be useful for troubleshooting.

In the case of an IPv4 prefix, the IPv4 address field is right-padded with zeroes up to 32 bits. The PSID field is left-padded to create a 16 bit field. For an IPv4 prefix or a complete IPv4 address, the PSID field is zero.

If the End-user IPv6 prefix length is larger than 64, the most significant parts of the interface identifier is overwritten by the prefix.

7. MAP Configuration

For a given MAP domain, the BR and CE MUST be configured with the following MAP elements. The configured values for these elements are identical for all CEs and BRs within a given MAP domain.

- o The End-User IPv6 prefix (Part of the normal IPv6 provisioning).
- o The Basic Mapping Rule and optionally the Forwarding Mapping Rules, including the Rule IPv6 prefix, Rule IPv4 prefix, Length of EA bits, and Forwarding mode
- o The Default Mapping Rule with the BR IPv6 prefix or address
- o The domain's MAP-E or MAP-T forwarding mode.

7.1. MAP CE

The MAP elements are set to values that are the same across all CEs within a MAP domain. The values may be configured in a variety of manners, including provisioning methods such as the Broadband Forum's "TR-69" Residential Gateway management interface, an XML-based object retrieved after IPv6 connectivity is established, or manual configuration by an administrator. This document describes how to configure the necessary parameters via a single DHCPv6 option. A CE that allows IPv6 configuration by DHCP SHOULD implement this option. Other configuration and management methods may use the format described by this option for consistency and convenience of implementation on CEs that support multiple configuration methods.

The only remaining provisioning information the CE requires in order to calculate the MAP IPv4 address and enable IPv4 connectivity is the IPv6 prefix for the CE. The End-user IPv6 prefix is configured as part of obtaining IPv6 Internet access.

A single MAP CE MAY be connected to more than one MAP domain, just as any router may have more than one IPv4-enabled service provider facing interface and more than one set of associated addresses assigned by DHCP. Each domain a given CE operates within would require its own set of MAP configuration elements and would generate its own IPv4 address.

The MAP DHCP option is specified in

[\[I-D.mdt-softwire-map-dhcp-option\]](#).

7.2. MAP BR

The MAP BR MUST be configured with the same MAP elements as the MAP CEs operating within the same domain.

For increased reliability and load balancing, the BR IPv6 address may be an anycast address shared across a given MAP domain. As MAP is stateless, any BR may be used at any time. If the BR IPv6 address is anycast the relay MUST use this anycast IPv6 address as the source address in packets relayed to CEs.

Since MAP uses provider address space, no specific routes need to be advertised externally for MAP to operate, neither in IPv6 nor IPv4 BGP. However, if anycast is used for the MAP IPv6 relays, the anycast addresses must be advertised in the service provider's IGP.

7.3. Backwards compatibility

A MAP-E CE provisioned with only a Default Mapping Rule makes a MAP-E CE compatible for use with DS-Lite [\[RFC6333\]](#) AFTRs, whose addresses are configured as the MAP BR.

A MAP-T CE, in all configuration modes, is by default compatible with stateful NAT64 gateways, whose prefixes are passed as the BR prefixes. Furthermore, when a MAP-T CE configured to operate without address sharing (no PSID), is compatible with stateless NAT64 elements acting as BRs.

8. Forwarding Considerations

Figure 1 depicts the overall MAP architecture with IPv4 users (N and M) networks connected to a routed IPv6 network.

MAP supports two forwarding modes. Translation mode as specified in [\[RFC6145\]](#) and Encapsulation mode as specified in [\[RFC2473\]](#).

A MAP CE forwarding IPv4 packets from the LAN SHOULD perform NAT44 functions first and create appropriate NAT44 bindings. The resulting IPv4 packets MUST contain the source IPv4 address and source transport number defined by MAP. The resulting IPv4 packet is forwarded to the CE's MAP forwarding function. The IPv6 source and destination addresses MUST then be derived as per [Section 5](#) of this draft.

A MAP CE receiving an IPv6 packet to its MAP IPv6 address are

forwarded to the CE's MAP function. All other IPv6 traffic is forwarded as per the CE's IPv6 routing rules. In other cases, the MAP-T function MUST derive the IPv4 source and destination addresses as per [Section 6](#) of this draft and MUST replace the IPv6 header with an IPv4 header in accordance with [\[RFC6145\]](#). The resulting IPv4 packet is then forwarded to the CE's NAT44 function where the destination port number MUST be checked against the stateful port mapping session table and the destination port number MUST be mapped to its original value.

[8.1.](#) Receiving rules

The CE SHOULD check that MAP received packets' transport-layer destination port number is in the range configured by MAP for the CE and the CE SHOULD drop any non conforming packet and respond with an ICMPv6 "Address Unreachable" (Type 1, Code 3).

[8.2.](#) MAP BR

[8.2.1.](#) IPv6 to IPv4

A MAP BR receiving IPv6 packets selects a best matching MAP domain rule based on a longest address match of the packets' source address against the BR's configured MAP BMR prefix(es), as well as a match of the packet destination address against the configured BR prefixes or FMR prefix(es). The selected MAP rule allows the BR to determine the EA-bits from the source IPv6 address. The BR MUST perform a validation of the consistency of the source IPv6 address and source port number for the packet using BMR. If the packets source port number is found to be outside the range allowed for this CE and the BMR, the BR MUST drop the packet and respond with an ICMPv6 "Destination Unreachable, Source address failed ingress/egress policy" (Type 1, Code 5).

For packets that are to be forwarded outside of a MAP domain, the BR MUST derive the source and destination IPv4 addresses as per [Section 7](#) of this draft and translate the IPv6 to IPv4 headers following [\[RFC6145\]](#). The resulting IPv4 packets are then passed to regular IPv4 forwarding.

[8.2.2.](#) IPv4 to IPv6

A MAP BR receiving IPv4 packets uses a longest match IPv4 lookup to select the target MAP domain and rule. The BR MUST then derive the IPv6 source and destination addresses from the IPv4 source and destination address and port as per [Section 7](#) of this draft. Following this, the BR MUST translate the IPv4 to IPv6 headers following [\[RFC6145\]](#). The resulting IPv6 packets are then passed to

regular IPv6 forwarding.

Note that the operation of a BR when forwarding to MAP domains that do not utilize IPv4 address sharing, is the same as stateless IPv4/IPv6 translation.

9. ICMP

ICMP message should be supported in MAP domain. Hence, the NAT44 in MAP CE must implement the behavior for ICMP message conforming to the best current practice documented in [[RFC5508](#)].

If a MAP CE receives an ICMP message having ICMP identifier field in ICMP header, NAT44 in the MAP CE must rewrite this field to a specific value assigned from the port-set. BR and other CEs must handle this field similar to the port number in the TCP/UDP header upon receiving the ICMP message with ICMP identifier field.

If a MAP node receives an ICMP error message without the ICMP identifier field for some errors that is detected inside a IPv6 tunnel, a MAP BR and CE should replay the ICMP error message to the original source. This behavior should be implemented conforming to the [section 8 of \[RFC2473\]](#). The MAP-E BR and CE obtain the original IPv6 tunnel packet storing in ICMP payload and then decapsulate IPv4 packet. Finally the MAP-E BR and CE generate a new ICMP error message from the decapsulated IPv4 packet and then forward it.

9.1. Translating ICMP/ICMPv6 Headers

MAP-T CEs and BRs MUST follow ICMP/ICMPv6 translation as per [[RFC6145](#)], with the following extension to cover the address sharing/port-range feature.

Unlike TCP and UDP, which each provide two port fields to represent both source and destination, the ICMP/ICMPv6 Query message header has only one ID field [[RFC0792](#)], [[RFC4443](#)]. Thus, if the ICMP Query message is originated from an IPv4 host behind a MAP-T CE, the ICMP ID field SHOULD be used to exclusively identify that IPv4 host. This means that the MAP-T CE SHOULD rewrite the ID field to a port-set value obtained via the BMR during the IPv4 to IPv6 ICMPv6 translation operation. A BR can translate the resulting ICMPv6 packets back to ICMP preserving the ID field on its way to an IPv4 destination. In the return path, when MAP-T BR receives an ICMP packet containing an ID field which is bound for a shared address in the MAP-T domain, the MAP-T BR SHOULD use the ID value as a substitute for the destination port in determining the IPv6 destination address according to [Section 5.1](#). In all other cases, the MAP-T BR MUST derive the destination

IPv6 address by simply mapping the destination IPv4 address without additional port info.

If a MAP BR receives an ICMP error message on its IPv4 interface, the MAP BR should replay the ICMP message to an appropriate MAP CE. If IPv4 address is not shared, the MAP BR generates a CE IPv6 address from the IPv4 destination address in the ICMP error message and encapsulates the ICMP message in IPv6. If IPv4 address is shared, the MAP BR derives an original IPv4 packet from the ICMP payload and generates a CE IPv6 address from the source address and the source port in the original IPv4 packet. If the MAP BR can generate the CE IPv6 address, the MAP BR encapsulates the ICMP error message in IPv6 and then forward it to its IPv6 interface.

10. Fragmentation and Path MTU Discovery

Due to the different sizes of the IPv4 and IPv6 header, handling the maximum packet size is relevant for the operation of any system connecting the two address families. There are three mechanisms to handle this issue: Path MTU discovery (PMTUD), fragmentation, and transport-layer negotiation such as the TCP Maximum Segment Size (MSS) option [[RFC0897](#)]. MAP uses all three mechanisms to deal with different cases.

10.1. Fragmentation in the MAP domain

Encapsulating or translating an IPv4 packet to carry it across the MAP domain will increase its size (40 bytes and 20 bytes respectively). It is strongly recommended that the MTU in the MAP domain is well managed and that the IPv6 MTU on the CE WAN side interface is set so that no fragmentation occurs within the boundary of the MAP domain.

Fragmentation on MAP domain entry is described for encapsulation in [section 7.2 of \[RFC2473\]](#) and in [section 4 and 5 of \[RFC6145\]](#) for translation mode.

The use of an anycast source address could lead to any ICMP error message generated on the path being sent to a different BR. Therefore, using dynamic tunnel MTU [Section 6.7 of \[RFC2473\]](#) is subject to IPv6 Path MTU blackholes.

Multiple BRs using the same anycast source address could send fragmented packets to the same CE at the same time. If the fragmented packets from different BRs happen to use the same fragment ID, incorrect reassembly might occur.

10.2. Receiving IPv4 Fragments on the MAP domain borders

Forwarding of an IPv4 packet received from the outside of the MAP domain requires the IPv4 destination address and the transport protocol destination port. The transport protocol information is only available in the first fragment received. As described in [section 5.3.3 of \[RFC6346\]](#) a MAP node receiving an IPv4 fragmented packet from outside has to reassemble the packet before sending the packet onto the MAP link. If the first packet received contains the transport protocol information, it is possible to optimize this behaviour by using a cache and forwarding the fragments unchanged. A description of this algorithm is outside the scope of this document.

10.3. Sending IPv4 fragments to the outside

If two IPv4 host behind two different MAP CE's with the same IPv4 address sends fragments to an IPv4 destination host outside the domain. Those hosts may use the same IPv4 fragmentation identifier, resulting in incorrect reassembly of the fragments at the destination host. Given that the IPv4 fragmentation identifier is a 16 bit field, it could be used similarly to port ranges. A MAP CE SHOULD rewrite the IPv4 fragmentation identifier to be within its allocated port set.

11. NAT44 Considerations

The NAT44 implemented in the MAP CE SHOULD conform with the behavior and best current practice documented in [\[RFC4787\]](#), [\[RFC5508\]](#), [\[RFC5382\]](#) and [\[RFC5383\]](#). In MAP address sharing mode (determined by the MAP domain/rule configuration parameters) the operation of the NAT44 MUST be restricted to the available port numbers derived via the basic mapping rule.

12. Deployment Considerations

12.1. Use cases

Editorial Note: Carried over from Use-cases/forwarding considerations in previous drafts.

12.1.1. Mesh Model

MAP allows the mesh model in order for all CEs to communicate each others directly. If one mapping rules is applied to a given MAP domain, all CEs can communicate each others directly. If multiple mapping rules are applied to a given MAP domain, or if multiple MAP

domains exist, CE can communicate with each other directly when the CEs know the respective mapping rules. When a CE receives an IPv4 packet from its LAN side, the CE looks up a mapping rule corresponding to an IPv4 destination address in the received IPv4 packet. If the corresponding mapping rule is found, CE can communicate to another CE directly based on the Forwarding mapping rule (FMR). If the corresponding mapping rule is not found, CE must forward the packet to a given BR using the Default Mapping rule (DMR).

12.1.2. Hub & Spoke Model

In order to achieve the hub & spoke mode fully, Forwarding mapping rule (FMR) should be disabled. In this case, all CEs do not look up the mapping rules upon receiving an IPv4 packet from its LAN side and then CE must encapsulate the IPv4 packet with IPv6 whose destination must be a given BR using the Default Mapping Rule (DMR).

12.1.3. Communication with IPv6 servers in the MAP-T domain

MAP-T allows communication between both IPv4-only and any IPv6 enabled end hosts, with native IPv6-only servers which are using IPv4-mapped IPv6 address based on DMR in the MAP-T domain. In this mode, the IPv6-only servers SHOULD have both A and AAAA records in DNS [[RFC6219](#)]. DNS64 [[RFC6147](#)] become required only when IPv6 servers in the MAP-T domain are expected themselves to initiate communication to external IPv4-only hosts.

13. IANA Considerations

This specification does not require any IANA actions.

14. Security Considerations

Spoofing attacks: With consistency checks between IPv4 and IPv6 sources that are performed on IPv4/IPv6 packets received by MAP nodes, MAP does not introduce any new opportunity for spoofing attacks that would not already exist in IPv6.

Denial-of-service attacks: In MAP domains where IPv4 addresses are shared, the fact that IPv4 datagram reassembly may be necessary introduces an opportunity for DOS attacks. This is inherent to address sharing, and is common with other address sharing approaches such as DS-Lite and NAT64/DNS64. The best protection against such attacks is to accelerate IPv6 enablement in both clients and servers so that, where MAP is supported, it is less

and less used.

Routing-loop attacks: This attack may exist in some automatic tunneling scenarios are documented in [\[RFC6324\]](#). They cannot exist with MAP because each BRs checks that the IPv6 source address of a received IPv6 packet is a CE address based on Forwarding Mapping Rule.

Attacks facilitated by restricted port set: From hosts that are not subject to ingress filtering of [\[RFC2827\]](#), some attacks are possible by an attacker injecting spoofed packets during ongoing transport connections ([\[RFC4953\]](#), [\[RFC5961\]](#), [\[RFC6056\]](#)). The attacks depend on guessing which ports are currently used by target hosts, and using an unrestricted port set is preferable, i.e. using native IPv6 connections that are not subject to MAP port range restrictions. To minimize this type of attacks when using a restricted port set, the MAP CE's NAT44 filtering behavior SHOULD be "Address-Dependent Filtering". Furthermore, the MAP CEs SHOULD use a DNS transport proxy function to handle DNS traffic, and source such traffic from IPv6 interfaces not assigned to MAP-T. Practicalities of these methods are discussed in [Section 5.9](#) of [\[I-D.dec-stateless-4v6\]](#).

[\[RFC6269\]](#) outlines general issues with IPv4 address sharing.

[15. Contributors](#)

Mohamed Boucadair, Gang Chen, Maoke Chen, Wojciech Dec, Xiaohong Deng, Jouni Korhonen, Tomasz Mrugalski, Jacni Qin, Chunfa Sun, Qiong Sun, Leaf Yeh.

This document is the result of the IETF Softwire MAP design team effort and numerous previous individual contributions in this area initiated by dIVI [\[I-D.xli-behave-divi\]](#) along with a similar idea proposed by [\[I-D.murakami-softwire-4v6-translation\]](#). The following are the authors who contributed in a major way to this document:

Chongfeng Xie (China Telecom)

Room 708, No.118, Xizhimennei Street Beijing 100035 CN

Phone: +86-10-58552116

Email: xiechf@ctbri.com.cn

Qiong Sun (China Telecom)

Room 708, No.118, Xizhimennei Street Beijing 100035 CN

Phone: +86-10-58552936

Email: sunqiong@ctbri.com.cn

Gang Chen (China Mobile)

53A,Xibianmennei Ave. Beijing 100053 P.R.China

Email: chengang@chinamobile.com

Wentao Shang (CERNET Center/Tsinghua University)

Room 225, Main Building, Tsinghua University Beijing 100084 CN

Email: wentaoshang@gmail.com

Guoliang Han (CERNET Center/Tsinghua University)

Room 225, Main Building, Tsinghua University Beijing 100084 CN

Email: bupthgl@gmail.com

Rajiv Asati (Cisco Systems)

7025-6 Kit Creek Road Research Triangle Park NC 27709 USA

Email: rajiva@cisco.com

16. Acknowledgements

This document is based on the ideas of many. In particular Remi Despres, who has tirelessly worked on generalized mechanisms for stateless address mapping.

The authors would like to thank Guillaume Gottard, Dan Wing, Jan Zorz, Necj Scoberne, Tina Tsou for their thorough review and comments.

17. References

17.1. Normative References

[I-D.mdt-software-map-dhcp-option]

Mrugalski, T., Boucadair, M., Deng, X., Troan, O., and C.

Bao, "DHCPv6 Options for Mapping of Address and Port", [draft-mdt-softwire-map-dhcp-option-02](#) (work in progress), January 2012.

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2473] Conta, A. and S. Deering, "Generic Packet Tunneling in IPv6 Specification", [RFC 2473](#), December 1998.
- [RFC6052] Bao, C., Huitema, C., Bagnulo, M., Boucadair, M., and X. Li, "IPv6 Addressing of IPv4/IPv6 Translators", [RFC 6052](#), October 2010.
- [RFC6145] Li, X., Bao, C., and F. Baker, "IP/ICMP Translation Algorithm", [RFC 6145](#), April 2011.
- [RFC6346] Bush, R., "The Address plus Port (A+P) Approach to the IPv4 Address Shortage", [RFC 6346](#), August 2011.

[17.2. Informative References](#)

- [I-D.dec-stateless-4v6]
Dec, W., Asati, R., and H. Deng, "Stateless 4Via6 Address Sharing", [draft-dec-stateless-4v6-04](#) (work in progress), October 2011.
- [I-D.ietf-softwire-stateless-4v6-motivation]
Boucadair, M., Matsushima, S., Lee, Y., Bonness, O., Borges, I., and G. Chen, "Motivations for Carrier-side Stateless IPv4 over IPv6 Migration Solutions", [draft-ietf-softwire-stateless-4v6-motivation-03](#) (work in progress), June 2012.
- [I-D.ietf-tsvwg-iana-ports]
Cotton, M., Eggert, L., Touch, J., Westerlund, M., and S. Cheshire, "Internet Assigned Numbers Authority (IANA) Procedures for the Management of the Service Name and Transport Protocol Port Number Registry", [draft-ietf-tsvwg-iana-ports-10](#) (work in progress), February 2011.
- [I-D.murakami-softwire-4v6-translation]
Murakami, T., Chen, G., Deng, H., Dec, W., and S. Matsushima, "4via6 Stateless Translation", [draft-murakami-softwire-4v6-translation-00](#) (work in progress), July 2011.

[I-D.xli-behave-divi]

Shang, W., Li, X., Zhai, Y., and C. Bao, "dIVI: Dual-Stateless IPv4/IPv6 Translation", [draft-xli-behave-divi-04](#) (work in progress), October 2011.

[RFC0792] Postel, J., "Internet Control Message Protocol", STD 5, [RFC 792](#), September 1981.

[RFC0897] Postel, J., "Domain name system implementation schedule", [RFC 897](#), February 1984.

[RFC1933] Gilligan, R. and E. Nordmark, "Transition Mechanisms for IPv6 Hosts and Routers", [RFC 1933](#), April 1996.

[RFC2529] Carpenter, B. and C. Jung, "Transmission of IPv6 over IPv4 Domains without Explicit Tunnels", [RFC 2529](#), March 1999.

[RFC2663] Srisuresh, P. and M. Holdrege, "IP Network Address Translator (NAT) Terminology and Considerations", [RFC 2663](#), August 1999.

[RFC2827] Ferguson, P. and D. Senie, "Network Ingress Filtering: Defeating Denial of Service Attacks which employ IP Source Address Spoofing", [BCP 38](#), [RFC 2827](#), May 2000.

[RFC3056] Carpenter, B. and K. Moore, "Connection of IPv6 Domains via IPv4 Clouds", [RFC 3056](#), February 2001.

[RFC3633] Troan, O. and R. Droms, "IPv6 Prefix Options for Dynamic Host Configuration Protocol (DHCP) version 6", [RFC 3633](#), December 2003.

[RFC4443] Conta, A., Deering, S., and M. Gupta, "Internet Control Message Protocol (ICMPv6) for the Internet Protocol Version 6 (IPv6) Specification", [RFC 4443](#), March 2006.

[RFC4787] Audet, F. and C. Jennings, "Network Address Translation (NAT) Behavioral Requirements for Unicast UDP", [BCP 127](#), [RFC 4787](#), January 2007.

[RFC4953] Touch, J., "Defending TCP Against Spoofing Attacks", [RFC 4953](#), July 2007.

[RFC5214] Templin, F., Gleeson, T., and D. Thaler, "Intra-Site Automatic Tunnel Addressing Protocol (ISATAP)", [RFC 5214](#), March 2008.

[RFC5382] Guha, S., Biswas, K., Ford, B., Sivakumar, S., and P.

- Srisuresh, "NAT Behavioral Requirements for TCP", [BCP 142](#), [RFC 5382](#), October 2008.
- [RFC5383] Gellens, R., "Deployment Considerations for Lemonade-Compliant Mobile Email", [BCP 143](#), [RFC 5383](#), October 2008.
- [RFC5508] Srisuresh, P., Ford, B., Sivakumar, S., and S. Guha, "NAT Behavioral Requirements for ICMP", [BCP 148](#), [RFC 5508](#), April 2009.
- [RFC5961] Ramaiah, A., Stewart, R., and M. Dalal, "Improving TCP's Robustness to Blind In-Window Attacks", [RFC 5961](#), August 2010.
- [RFC5969] Townsley, W. and O. Troan, "IPv6 Rapid Deployment on IPv4 Infrastructures (6rd) -- Protocol Specification", [RFC 5969](#), August 2010.
- [RFC6056] Larsen, M. and F. Gont, "Recommendations for Transport-Protocol Port Randomization", [BCP 156](#), [RFC 6056](#), January 2011.
- [RFC6147] Bagnulo, M., Sullivan, A., Matthews, P., and I. van Beijnum, "DNS64: DNS Extensions for Network Address Translation from IPv6 Clients to IPv4 Servers", [RFC 6147](#), April 2011.
- [RFC6219] Li, X., Bao, C., Chen, M., Zhang, H., and J. Wu, "The China Education and Research Network (CERNET) IVI Translation Design and Deployment for the IPv4/IPv6 Coexistence and Transition", [RFC 6219](#), May 2011.
- [RFC6250] Thaler, D., "Evolution of the IP Model", [RFC 6250](#), May 2011.
- [RFC6269] Ford, M., Boucadair, M., Durand, A., Levis, P., and P. Roberts, "Issues with IP Address Sharing", [RFC 6269](#), June 2011.
- [RFC6324] Nakibly, G. and F. Templin, "Routing Loop Attack Using IPv6 Automatic Tunnels: Problem Statement and Proposed Mitigations", [RFC 6324](#), August 2011.
- [RFC6333] Durand, A., Droms, R., Woodyatt, J., and Y. Lee, "Dual-Stack Lite Broadband Deployments Following IPv4 Exhaustion", [RFC 6333](#), August 2011.

Appendix A. Example of MAP-T translation

Example 1:

Given the MAP domain information and an IPv6 address of an endpoint:

IPv6 prefix assigned to the end user: 2001:db8:0012:3400::/56
 Basic Mapping Rule: {2001:db8:0000::/40 (Rule IPv6 prefix),
 192.0.2.0/24 (Rule IPv4 prefix), 16 (Rule EA-bits length)}
 Sharing ratio: 256 ($16 - (32 - 24) = 8$. $2^8 = 256$)
 PSID offset: 4

A MAP node (CE or BR) can via the BMR determine the IPv4 address and port-set as shown below:

EA bits offset: 40
 IPv4 suffix bits (p) Length of IPv4 address (32) - IPv4 prefix
 length (24) = 8
 IPv4 address 192.0.2.18 (0xc0000212)
 PSID start: 40 + p = 40 + 8 = 48
 PSID length: o - p = 16 (56 - 40) - 8 = 8
 PSID: 0x34

Port-set-1: 4928, 4929, 4930, 4931, 4932, 4933, 4934, 4935, 4936,
 4937, 4938, 4939, 4940, 4941, 4942, 4943

Port-set-2: 9024, 9025, 9026, 9027, 9028, 9029, 9030, 9031, 9032,
 9033, 9034, 9035, 9036, 9037, 9038, 9039

... ..

Port-set-15 62272, 62273, 62274, 62275, 62276, 62277, 62278,
 62279, 62280, 62281, 62282, 62283, 62284, 62285, 62286, 62287

The BMR information allows a MAP CE also to determine (complete) its IPv6 address within the indicated IPv6 prefix.

IPv6 address of MAP-T CE: 2001:db8:0012:3400:00c0:0002:1200:3400

Example 2:

Another example can be made of a hypothetical MAP-T BR, configured with the following FMR when receiving a packet with the following characteristics:

IPv4 source address: 1.2.3.4 (0x01020304)
IPv4 source port: 80
IPv4 destination address: 192.0.2.18 (0xc0000212)
IPv4 destination port: 9030

Configured Forwarding Mapping Rule: {2001:db8:0000::/40
(Rule IPv6 prefix), 192.0.2.0/24 (Rule IPv4 prefix),
16 (Rule EA-bits length)}

MAP-T BR Prefix 2001:db8:ffff::/64

The above information allows the BR to derive as follows the mapped destination IPv6 address for the corresponding MAP-T CE, and also the mapped source IPv6 address for the IPv4 source.

IPv4 suffix bits (p) $32 - 24 = 8$ (18 (0x12))
PSID length: 8
PSID: 0x34 (9030 (0x2346))

The resulting IPv6 packet will have the following key fields:

IPv6 source address 2001:db8:ffff:0:0001:0203:0400::
IPv6 destination address: 2001:db8:0012:3400:00c0:0002:1200:3400
IPv6 source Port: 80
IPv6 destination Port: 9030

Example 3:

An IPv4 host behind the MAP-T CE (addressed as per the previous examples) corresponding with IPv4 host 1.2.3.4 will have its packets converted into IPv6 using the DMR configured on the MAP-T CE as follows:

Default Mapping Rule used by MAP-T CE: {2001:db8:ffff::/64 (Rule IPv6 prefix), 0.0.0.0/0 (Rule IPv4 prefix), null (BR IPv4 address)}

IPv4 source address (post NAT44 if present) 192.0.2.18

IPv4 destination address: 1.2.3.4

IPv4 source port (post NAT44 if present): 9030

IPv4 destination port: 80

IPv6 source address of MAP-T CE:

2001:db8:0012:3400:00c0:0002:1200:3400

IPv6 destination address: 2001:db8:ffff:0:0001:0203:0400::

Authors' Addresses

Ole Troan
Cisco Systems
Oslo
Norway

Email: ot@cisco.com

Wojciech Dec
Cisco Systems
Haarlerbergpark Haarlerbergweg 13-19
Amsterdam, NOORD-HOLLAND 1101 CH
Netherlands

Phone:

Email: wdec@cisco.com

Xing Li
CERNET Center/Tsinghua University
Room 225, Main Building, Tsinghua University
Beijing 100084
CN

Email: xing@cernet.edu.cn

Congxiao Bao
CERNET Center/Tsinghua University
Room 225, Main Building, Tsinghua University
Beijing 100084
CN

Email: congxiao@cernet.edu.cn

Yu Zhai
CERNET Center/Tsinghua University
Room 225, Main Building, Tsinghua University
Beijing 100084
CN

Email: jacky.zhai@gmail.com

Satoru Matsushima
SoftBank Telecom
1-9-1 Higashi-Shinbashi, Munato-ku
Tokyo
Japan

Email: satoru.matsushima@tm.softbank.co.jp

Tetsuya Murakami
IP Infusion
1188 East Arques Avenue
Sunnyvale
USA

Email: tetsuya@ipinfusion.com

