

Software
Internet-Draft
Intended status: Standards Track
Expires: June 25, 2016

S. Jiang
Huawei Technologies Co., Ltd
Y. Fu
CNNIC
B. Liu
Huawei Technologies Co., Ltd
P. Deacon
IEA Software, Inc.
December 23, 2015

RADIUS Attribute for MAP
draft-ietf-software-map-radius-05

Abstract

Mapping of Address and Port (MAP) is a stateless mechanism for running IPv4 over IPv6-only infrastructure. It provides both IPv4 and IPv6 connectivity services simultaneously during the IPv4/IPv6 co-existing period. The Dynamic Host Configuration Protocol for IPv6 (DHCPv6) MAP options has been defined to configure MAP Customer Edge (CE). However, in many networks, the configuration information may be stored in Authentication Authorization and Accounting (AAA) servers while user configuration is mainly from Broadband Network Gateway (BNG) through DHCPv6 protocol. This document defines a Remote Authentication Dial In User Service (RADIUS) attribute that carries MAP configuration information from AAA server to BNG. The MAP RADIUS attribute are designed following the simplify principle. It provides just enough information to form the correspondent DHCPv6 MAP option.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on June 25, 2016.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

Table of Contents

1.	Introduction	3
2.	Terminology	3
3.	MAP Configuration process with RADIUS	3
4.	Attributes	6
4.1.	MAP-Configuration Attribute	6
4.2.	MAP Rule Options	6
4.3.	Sub Options for MAP Rule Option	7
4.3.1.	Rule-IPv6-Prefix Sub Option	7
4.3.2.	Rule-IPv4-Prefix Sub Option	8
4.3.3.	EA Length Sub Option	9
4.3.4.	BR-IPv6-Address Sub Option	9
4.3.5.	PSID Sub Option	9
4.3.6.	PSID Length Sub Option	10
4.3.7.	PSID Offset Sub Option	10
4.4.	Table of attributes	11
5.	Diameter Considerations	11
6.	IANA Considerations	12
7.	Security Considerations	12
8.	Acknowledgements	12

9.	References	13
9.1.	Normative References	13
9.2.	Informative References	13
	Authors' Addresses	14

[1.](#) Introduction

Recently providers start to deploy IPv6 and consider how to transit to IPv6. Mapping of Address and Port (MAP)[\[I-D.ietf-softwire-map\]](#) is a stateless mechanism for running IPv4 over IPv6-only infrastructure. It provides both IPv4 and IPv6 connectivity services simultaneously during the IPv4/IPv6 co-existing period. MAP has adopted Dynamic Host Configuration Protocol for IPv6 (DHCPv6) [\[RFC3315\]](#) as auto-configuring protocol. The MAP Customer Edge (CE) uses the DHCPv6 extension options [\[I-D.ietf-softwire-map-dhcp\]](#) to discover MAP Border Relay (in tunnel model only) and to configure relevant MAP rules.

In many networks, user configuration information may be stored by AAA (Authentication, Authorization, and Accounting) servers. Current AAA servers communicate using the Remote Authentication Dial In User Service (RADIUS) [\[RFC2865\]](#) protocol. In a fixed line broadband network, the Broadband Network Gateways (BNGs) act as the access gateway of users. The BNGs are assumed to embed a DHCPv6 server function that allows them to locally handle any DHCPv6 requests initiated by hosts.

Since the MAP configuration information is stored in AAA servers and user configuration is mainly transmitted through DHCPv6 protocol between BNGs and hosts/CEs, new RADIUS attributes are needed to propagate the information from AAA servers to BNGs. The MAP RADIUS attributes designed in this document are especially for the MAP encapsulation mode, while providing enough information to form the correspondent DHCPv6 MAP option [\[I-D.ietf-softwire-map-dhcp\]](#).

[2.](#) Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [\[RFC2119\]](#).

The terms MAP CE and MAP Border Relay are defined in [\[I-D.ietf-softwire-map\]](#).

[3.](#) MAP Configuration process with RADIUS

The below Figure 1 illustrates how the RADIUS protocol and DHCPv6 cooperate to provide MAP CE with MAP configuration information.




Figure 1: the cooperation between DHCPv6 and RADIUS combining with RADIUS authentication

The BNG acts as a RADIUS client and as a DHCPv6 server. First, the MAP CE MAY initiate a DHCPv6 Solicit message that includes an Option Request option (6) [RFC3315] with the MAP option [I-D.ietf-softwire-map-dhcp] from the MAP CE. But note that the ORO (Option Request option) with the MAP option could be optional if the network was planned as MAP-enabled as default. When BNG receives the SOLICIT, it SHOULD initiate radius Access-Request message, in which the User-Name attribute (1) SHOULD be filled by the MAP CE MAC address or interface-id or both, to the RADIUS server and the User-password attribute (2) SHOULD be filled by the shared MAP password that has been preconfigured on the DHCPv6 server, requesting authentication as defined in [RFC2865] with MAP-Configuration attribute, which will be defined in the next Section. If the authentication request is approved by the AAA server, an Access-Accept message MUST be acknowledged with the IPv6-MAP-Configuration Attribute. After receiving the Access-Accept message with MAP-Configuration Attribute, the BNG SHOULD respond the user an Advertisement message. Then the user can requests for a MAP Option, and the BNG SHOULD reply the user with the message containing the MAP option. The recommended format of the MAC address is defined as Calling-Station-Id (Section 3.20 in [RFC3580] without the SSID (Service Set Identifier) portion.

Figure 2 describes another scenario, in which the authorization operation is not coupled with authentication. Authorization relevant to MAP is done independently after the authentication process. As similar to above scenario, the ORO with the MAP option in the initial DHCPv6 request could be optional if the network was planned as MAP-enabled as default.




Figure 2: the cooperation between DHCPv6 and RADIUS decoupled with RADIUS authentication

In the above mentioned scenario, the Access-Request packet SHOULD contain a Service-Type attribute (6) with the value Authorize Only (17); thus, according to [\[RFC5080\]](#), the Access-Request packet MUST contain a State attribute that obtained from the previous authentication process.

In both above-mentioned scenarios, Message-authenticator (type 80) [\[RFC2869\]](#) SHOULD be used to protect both Access-Request and Access-Accept messages.

After receiving the MAP-Configuration Attribute in the initial Access-Accept, the BNG SHOULD store the received MAP configuration parameters locally. When the MAP CE sends a DHCPv6 Request message to request an extension of the lifetimes for the assigned address, the BNG does not have to initiate a new Access-Request towards the AAA server to request the MAP configuration parameters. The BNG could retrieve the previously stored MAP configuration parameters and use them in its reply.

If the BNG does not receive the MAP-Configuration Attribute in the Access-Accept it MAY fallback to a pre-configured default MAP configuration, if any. If the BNG does not have any pre-configured default MAP configuration or if the BNG receives an Access-Reject, the tunnel cannot be established.

As specified in [\[RFC3315\]](#), section 18.1.4, "Creation and Transmission of Rebind Messages ", if the DHCPv6 server to which the DHCPv6 Renew message was sent at time T1 has not responded by time T2, the MAP CE (DHCPv6 client) SHOULD enter the Rebind state and attempt to contact any available server. In this situation, the secondary BNG receiving the DHCPv6 message MUST initiate a new Access-Request towards the AAA

server. The secondary BNG MAY include the MAP-Configuration Attribute in its Access-Request.


4. Attributes

This section defines MAP-Rule Attribute which is used in the MAP scenario. The attribute design follows [\[RFC6158\]](#) and refers to [\[RFC6929\]](#).

The MAP RADIUS attribute are designed following the simplify principle. The sub options are organized into two categories: the necessary and the optional.


4.1. MAP-Configuration Attribute

The MAP-Configuration Attribute is structured as follows:



4.2. MAP Rule Options

Depending on deployment scenario, one Basic Mapping Rule and zero or more Forwarding Mapping Rules MUST be included in one MAP-Configuration Attribute.



Type

- 1 Basic Mapping Rule (Not Forwarding Mapping Rule)
- 2 Forwarding Mapping Rule (Not Basic Mapping Rule)
- 3 Basic & Forwarding Mapping Rule

Length

2 + the length of the sub options

Sub Option


A variable field that contains necessary sub options defined in [Section 4.3](#) and zero or several optional sub options, defined in [Section 4.4](#)

4.3. Sub Options for MAP Rule Option

4.3.1. Rule-IPv6-Prefix Sub Option

The Rule-IPv6-Prefix Sub Option is necessary for every MAP Rule option. It should appear for once and only once.

The IPv6 Prefix sub option is followed the framed IPv6 prefix designed in [\[RFC3162\]](#).



SubType

1 (SubType number, for the Rule-IPv6-Prefix6 sub option)

SubLen

20 (the length of the Rule-IPv6-Prefix6 sub option)

Reserved

Reserved for future usage. It should be set to all zero


prefix6-len

length of the IPv6 prefix, specified in the rule-ipv6-prefix field, expressed in bits

rule-ipv6-prefix

a 128-bits field that specifies an IPv6 prefix that appears in a MAP rule

4.3.2. Rule-IPv4-Prefix Sub Option



SubType

2 (SubType number, for the Rule-IPv4-Prefix6 sub option)

SubLen

8 (the length of the Rule-IPv4-Prefix6 sub option)

Reserved


Reserved for future usage. It should be set to all zero

Prefix4-len

length of the IPv6 prefix, specified in the rule-ipv6-prefix field, expressed in bits

rule-ipv4-prefix

a 32-bits field that specifies an IPv4 prefix that appears in a MAP rule

4.3.3. EA Length Sub Option

SubType


3 (SubType number, for the EA Length sub option)

SubLen

4 (the length of the EA Length sub option)

EA-len

16 bits long field that specifies the Embedded-Address (EA) bit length. Allowed values range from 0 to 48

4.3.4. BR-IPv6-Address Sub Option

SubType

4 (SubType number, for the BR-ipv6-address sub option)

SubLen

20 (the length of the BR-ipv6-address sub option)

BR-ipv6-address

a 128-bits field that specifies the IPv6 address for the BR.

4.3.5. PSID Sub Option


```

0                               1                               2                               3
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|   SubType   |   SubLen   |               PSID               |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

SubType

5 (SubType number, for the PSID Sub Option sub option)

SubLen

4 (the length of the PSID Sub Option sub option)

PSID (Port-set ID)

Explicit 16-bit (unsigned word) PSID value. The PSID value algorithmically identifies a set of ports assigned to a CE. The first k-bits on the left of this 2-octets field is the PSID value. The remaining (16-k) bits on the right are padding zeros.

[4.3.6.](#) PSID Length Sub Option

```

0                               1                               2                               3
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|   SubType   |   SubLen   |           PSID-len           |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

SubType

6 (SubType number, for the PSID Length sub option)

SubLen

4 (the length of the PSID Length sub option)

PSID-len

Bit length value of the number of significant bits in the PSID field. (also known as 'k'). When set to 0, the PSID field is to be ignored. After the first 'a' bits, there are k bits in the port number representing valid of PSID. Subsequently, the address sharing ratio would be 2^k .

[4.3.7.](#) PSID Offset Sub Option

This attribute is usable within either RADIUS or Diameter [[RFC6733](#)]. Since the Attributes defined in this document will be allocated from the standard RADIUS type space, no special handling is required by Diameter entities.

6. IANA Considerations

This document requires the assignment of two new RADIUS Attributes Types in the "Radius Types" registry (currently located at <http://www.iana.org/assignments/radius-types> for the following attributes:

- o MAP-Configuration TBD1

IANA should allocate the numbers from the standard RADIUS Attributes space using the "IETF Review" policy [[RFC5226](#)].

7. Security Considerations

In MAP scenarios, both CE and BNG are within a provider network, which can be considered as a closed network and a lower security threat environment. A similar consideration can be applied to the RADIUS message exchange between BNG and the AAA server.

Known security vulnerabilities of the RADIUS protocol are discussed in [[RFC2607](#)], [[RFC2865](#)], and [[RFC2869](#)]. Use of IPsec [[RFC4301](#)] for providing security when RADIUS is carried in IPv6 is discussed in [[RFC3162](#)].

A malicious user may use MAC address proofing and/or dictionary attack on the shared MAP password that has been preconfigured on the DHCPv6 server to get unauthorized MAP configuration information.

Security considerations for MAP specific between MAP CE and BNG are discussed in [[I-D.ietf-softwire-map](#)]. Furthermore, generic DHCPv6 security mechanisms can be applied DHCPv6 intercommunication between MAP CE and BNG.

Security considerations for the Diameter protocol are discussed in [[RFC6733](#)].

8. Acknowledgements

The authors would like to thank the valuable comments made by Peter Lothberg, Wojciech Dec, Suresh Krishnan and Ross Chandler for this document.

This document was produced using the xml2rfc tool [[RFC2629](#)].

9. References

9.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC2865] Rigney, C., Willens, S., Rubens, A., and W. Simpson, "Remote Authentication Dial In User Service (RADIUS)", [RFC 2865](#), DOI 10.17487/RFC2865, June 2000, <<http://www.rfc-editor.org/info/rfc2865>>.
- [RFC3162] Aboba, B., Zorn, G., and D. Mitton, "RADIUS and IPv6", [RFC 3162](#), DOI 10.17487/RFC3162, August 2001, <<http://www.rfc-editor.org/info/rfc3162>>.
- [RFC3315] Droms, R., Ed., Bound, J., Volz, B., Lemon, T., Perkins, C., and M. Carney, "Dynamic Host Configuration Protocol for IPv6 (DHCPv6)", [RFC 3315](#), DOI 10.17487/RFC3315, July 2003, <<http://www.rfc-editor.org/info/rfc3315>>.
- [RFC3580] Congdon, P., Aboba, B., Smith, A., Zorn, G., and J. Roesse, "IEEE 802.1X Remote Authentication Dial In User Service (RADIUS) Usage Guidelines", [RFC 3580](#), DOI 10.17487/RFC3580, September 2003, <<http://www.rfc-editor.org/info/rfc3580>>.
- [RFC5080] Nelson, D. and A. DeKok, "Common Remote Authentication Dial In User Service (RADIUS) Implementation Issues and Suggested Fixes", [RFC 5080](#), DOI 10.17487/RFC5080, December 2007, <<http://www.rfc-editor.org/info/rfc5080>>.
- [RFC6158] DeKok, A., Ed. and G. Weber, "RADIUS Design Guidelines", [BCP 158](#), [RFC 6158](#), DOI 10.17487/RFC6158, March 2011, <<http://www.rfc-editor.org/info/rfc6158>>.
- [RFC6929] DeKok, A. and A. Lior, "Remote Authentication Dial In User Service (RADIUS) Protocol Extensions", [RFC 6929](#), DOI 10.17487/RFC6929, April 2013, <<http://www.rfc-editor.org/info/rfc6929>>.

9.2. Informative References

[I-D.ietf-softwire-map]

Troan, O., Dec, W., Li, X., Bao, C., Matsushima, S., Murakami, T., and T. Taylor, "Mapping of Address and Port with Encapsulation (MAP)", [draft-ietf-softwire-map-13](#) (work in progress), March 2015.

[I-D.ietf-softwire-map-dhcp]

Mrugalski, T., Troan, O., Farrer, I., Perreault, S., Dec, W., Bao, C., Yeh, L., and X. Deng, "DHCPv6 Options for configuration of Softwire Address and Port Mapped Clients", [draft-ietf-softwire-map-dhcp-12](#) (work in progress), March 2015.

[RFC2607] Aboba, B. and J. Vollbrecht, "Proxy Chaining and Policy Implementation in Roaming", [RFC 2607](#), DOI 10.17487/RFC2607, June 1999, <<http://www.rfc-editor.org/info/rfc2607>>.

[RFC2629] Rose, M., "Writing I-Ds and RFCs using XML", [RFC 2629](#), DOI 10.17487/RFC2629, June 1999, <<http://www.rfc-editor.org/info/rfc2629>>.

[RFC2869] Rigney, C., Willats, W., and P. Calhoun, "RADIUS Extensions", [RFC 2869](#), DOI 10.17487/RFC2869, June 2000, <<http://www.rfc-editor.org/info/rfc2869>>.

[RFC4301] Kent, S. and K. Seo, "Security Architecture for the Internet Protocol", [RFC 4301](#), DOI 10.17487/RFC4301, December 2005, <<http://www.rfc-editor.org/info/rfc4301>>.

[RFC5226] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 5226](#), DOI 10.17487/RFC5226, May 2008, <<http://www.rfc-editor.org/info/rfc5226>>.

[RFC6733] Fajardo, V., Ed., Arkko, J., Loughney, J., and G. Zorn, Ed., "Diameter Base Protocol", [RFC 6733](#), DOI 10.17487/RFC6733, October 2012, <<http://www.rfc-editor.org/info/rfc6733>>.

Authors' Addresses

Sheng Jiang
Huawei Technologies Co., Ltd
Q14, Huawei Campus, No.156 Beiqing Road
Hai-Dian District, Beijing, 100095
P.R. China

Email: jiangsheng@huawei.com

Yu Fu
CNNIC
No.4 South 4th Street, Zhongguancun
Hai-Dian District, Beijing, 100190
P.R. China

Email: fuyu@cnnic.cn

Bing Liu
Huawei Technologies Co., Ltd
Q14, Huawei Campus, No.156 Beiqing Road
Hai-Dian District, Beijing, 100095
P.R. China

Email: leo.liubing@huawei.com

Peter Deacon
IEA Software, Inc.
P.O. Box 1170
Veradale, WA 99037
USA

Email: peterd@iea-software.com

