

Softwire WG
Internet-Draft
Intended status: Standards Track
Expires: July 16, 2017

M. Boucadair
Orange
J. Qin
Cisco
T. Tsou
Philips Lighting
X. Deng
The University of New South Wales
January 12, 2017

DHCPv6 Option for IPv4-Embedded Multicast and Unicast IPv6 Prefixes
draft-ietf-softwire-multicast-prefix-option-12

Abstract

This document defines a Dynamic Host Configuration Protocol version 6 (DHCPv6) Option for multicast IPv4 service continuity solutions, which is used to carry the IPv6 prefixes to be used to build unicast and multicast IPv4-embedded IPv6 addresses.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on July 16, 2017.

Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Requirements Language	2
2.	Terminology	2
3.	OPTION_V6_PREFIX64 DHCPv6 Option	3
4.	Configuration Guidelines for the Server	5
5.	DHCPv6 Client Behavior	5
6.	Security Considerations	6
7.	Acknowledgments	6
8.	IANA Considerations	6
9.	References	7
9.1.	Normative References	7
9.2.	Informative References	7
	Authors' Addresses	8

[1.](#) Introduction

Several solutions (e.g., [[I-D.ietf-softwire-dslite-multicast](#)]) are proposed for the delivery of multicast services in the context of transition to IPv6. Even if these solutions may have different applicable use cases, they all use specific IPv6 addresses that embed IPv4 addresses, for both multicast group and source addresses.

This document defines a DHCPv6 option [[RFC3315](#)] that carries the IPv6 prefixes to be used for constructing these IPv4-embedded IPv6 addresses.

In particular, this option can be used in the context of DS-Lite [[RFC6333](#)], Stateless A+P [[RFC6346](#)], and other IPv4-IPv6 transition techniques.

[1.1.](#) Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

[2.](#) Terminology

This document makes use of the following terms:

IPv4-embedded IPv6 address: an IPv6 address which embeds a 32 bit-encoded IPv4 address [[RFC6052](#)]. An IPv4-embedded IPv6 address can be a unicast or a multicast address.

Prefix64: is an IPv6 prefix used for synthesizing IPv4-embedded IPv6 addresses. A Prefix64 can be of unicast or multicast.

Note: "64" is used as an abbreviation for IPv6-IPv4 interconnection.

ASM_mPrefix64: a multicast Prefix64 which belongs to the Any-Source Multicast (ASM) range.

SSM_mPrefix64: a multicast Prefix64 which belongs to the Source-Specific Multicast (SSM) [[RFC4607](#)] range.

uPrefix64: a unicast Prefix64 for building the IPv4-embedded IPv6 addresses of multicast sources in SSM mode.

3. OPTION_V6_PREFIX64 DHCPv6 Option

OPTION_V6_PREFIX64 (Figure 1) conveys the IPv6 prefix(es) to be used (e.g., by an mB4 [[I-D.ietf-softwire-dslite-multicast](#)]) to synthesize IPv4-embedded IPv6 addresses.




Figure 1: OPTION_V6_PREFIX64: Option Format

The fields of the option shown in Figure 1 are as follows:

option-code: OPTION_V6_PREFIX64 (see [Section 8](#)).

option-length: length of the option, in octets.

asm-length: the prefix-length for the ASM IPv4-embedded prefix, as an 8-bit unsigned integer. This field represents the number of valid leading bits in the prefix. This field MUST be set to 96.

ASM_mPrefix64: this field identifies the IPv6 multicast prefix to be used to synthesize the IPv4-embedded IPv6 addresses of the multicast groups in the ASM mode. The conveyed multicast IPv6 prefix MUST belong to the ASM range.

ssm-length: the prefix-length for the SSM IPv4-embedded prefix, as an 8-bit unsigned integer. This field represents the number of valid leading bits in the prefix. This field MUST be set to 96.

SSM_mPrefix64: this field identifies the IPv6 multicast prefix to be used to synthesize the IPv4-embedded IPv6 addresses of the multicast groups in the SSM mode. The conveyed multicast IPv6 prefix MUST belong to the SSM range.

unicast-length: the prefix-length for the IPv6 unicast prefix to be used to synthesize the IPv4-embedded IPv6 addresses of the multicast sources, as an 8-bit unsigned integer (0 to 128). This field represents the number of valid leading bits in the prefix.

uPrefix64: this field identifies the IPv6 unicast prefix to be used in SSM mode for constructing the IPv4-embedded IPv6 addresses representing the IPv4 multicast sources in the IPv6 domain. uPrefix64 may also be used to extract the IPv4 address from the received multicast data flows. It is a variable size field with the length of the field defined by the unicast-length field and is rounded up to the nearest octet boundary. In this case, any additional padding bits must be zeroed. The address mapping MUST follow the guidelines documented in [[RFC6052](#)].

Multiple instances of OPTION_V6_PREFIX64 may be returned to a DHCPv6 client.

Note that it was tempting to define three distinct DHCPv6 options, but that approach was not adopted because it has a side effect: the specification of a DHCPv6 option that could be used to discover unicast Prefix64s in environments where multicast is not enabled. Such side effect conflicts with the recommendation to support the Well-Known DNS Name heuristic discovery-based method for unicast-only environments ([Section 6 of \[RFC7051\]](#)).

4. Configuration Guidelines for the Server

This section is not normative but specifies a set of configuration guidelines.

DHCP servers supporting `OPTION_V6_PREFIX64` must be configured with `ASM_mPrefix64` or `SSM_mPrefix64`, and may be configured with both. `uPrefix64` must also be configured when `SSM_mPrefix64` is provided. `uPrefix64` may be configured when `ASM_mPrefix64` is provided. Note that `uPrefix64` is not mandatory for the ASM case if, for example, a local address mapping algorithm is supported or the Well-Know Prefix (`64:ff9b::/96`) is used.

When a multicast Prefix64 (`ASM_mPrefix64` or `SSM_mPrefix64`) is configured, the length of the prefix must be `/96`.

Both `ASM_mPrefix64` and `SSM_mPrefix64` may be configured and therefore be returned to a requesting DHCP client in the same `OPTION_V6_PREFIX64`. In particular, if both SSM and ASM modes are supported, `ASM_mPrefix64` and `SSM_mPrefix64` prefixes must be configured. For SSM deployments, both `SSM_mPrefix64` and `uPrefix64` must be configured.

When distinct IPv6 multicast address scopes [[RFC7346](#)] are required to preserve the scope when translating IPv4 multicast addresses ([Section 8 of \[RFC2365\]](#)), each scope is configured as a separate `OPTION_V6_PREFIX64`. How DHCP servers are configured to separate multicast Prefix64 per scope is implementation-specific and not covered by this document.

When scope preservation is not required, only one instance of `OPTION_V6_PREFIX64` is configured.

5. DHCPv6 Client Behavior

To retrieve the IPv6 prefixes that will be used to synthesize unicast and multicast IPv4-embedded IPv6 addresses, the DHCPv6 client MUST include `OPTION_V6_PREFIX64` code in its `OPTION_ORO`. If the DHCPv6 client receives more than one `OPTION_V6_PREFIX64` option from the DHCPv6 server:

- o If each enclosed IPv6 multicast prefix has a distinct scope [[RFC7346](#)], the client MUST select the appropriate IPv6 multicast prefix whose scope matches the IPv4 multicast address used to synthesize an IPv4-embedded IPv6 multicast address.

- o If at least two of the received options convey IPv6 multicast prefixes that have the same scope, the said options MUST be discarded.

If asm-length, ssm-length and unicast-length fields are all set to 0, the DHCPv6 client MUST behave as if OPTION_V6_PREFIX64 had not been received in the response received from the DHCPv6 server.

If the asm-length field is non-null, the IPv6 prefix identified by ASM_mPrefix64 is used to synthesize IPv4-embedded IPv6 multicast addresses in the ASM range. This is achieved by concatenating the ASM_mPrefix64 and the IPv4 multicast address; the IPv4 multicast address is inserted in the last 32 bits of the IPv4-embedded IPv6 multicast address.

If the ssm-length field is non-null, the IPv6 prefix identified by SSM_mPrefix64 is used to synthesize IPv4-embedded IPv6 multicast addresses in the SSM range. This is achieved by concatenating the SSM_mPrefix64 and the IPv4 multicast address; the Pv4 multicast address is inserted in the last 32 bits of the IPv4-embedded IPv6 multicast address.

If the unicast-length field is non-null, the IPv6 prefix identified by uPrefix64 is used to synthesize IPv4-embedded IPv6 unicast addresses as specified in [RFC6052].

6. Security Considerations

The security considerations documented in [RFC3315] and [RFC6052] are to be considered.

7. Acknowledgments

Thanks to C. Jacquenet, S. Venaas, B. Volz, T. Taylor, R. Weber, R. Even, J. Sheng, and T. Mrugalski for their review.

Many thanks to I. Farrer and T. Lemon for the comments.

8. IANA Considerations

Authors of this document request IANA to assign a new DHCPv6 option code in the registry maintained in <http://www.iana.org/assignments/dhcpv6-parameters>:

Option Name	Value
OPTION_V6_PREFIX64	TBA

9. References

9.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC3315] Droms, R., Ed., Bound, J., Volz, B., Lemon, T., Perkins, C., and M. Carney, "Dynamic Host Configuration Protocol for IPv6 (DHCPv6)", [RFC 3315](#), DOI 10.17487/RFC3315, July 2003, <<http://www.rfc-editor.org/info/rfc3315>>.
- [RFC4607] Holbrook, H. and B. Cain, "Source-Specific Multicast for IP", [RFC 4607](#), DOI 10.17487/RFC4607, August 2006, <<http://www.rfc-editor.org/info/rfc4607>>.
- [RFC6052] Bao, C., Huitema, C., Bagnulo, M., Boucadair, M., and X. Li, "IPv6 Addressing of IPv4/IPv6 Translators", [RFC 6052](#), DOI 10.17487/RFC6052, October 2010, <<http://www.rfc-editor.org/info/rfc6052>>.

9.2. Informative References

- [I-D.ietf-softwire-dslite-multicast] Boucadair, M., Qin, J., Jacquenet, C., Lee, Y., and Q. Wang, "Delivery of IPv4 Multicast Services to IPv4 Clients over an IPv6 Multicast Network", [draft-ietf-softwire-dslite-multicast-15](#) (work in progress), January 2017.
- [RFC2365] Meyer, D., "Administratively Scoped IP Multicast", [BCP 23](#), [RFC 2365](#), DOI 10.17487/RFC2365, July 1998, <<http://www.rfc-editor.org/info/rfc2365>>.
- [RFC6333] Durand, A., Droms, R., Woodyatt, J., and Y. Lee, "Dual-Stack Lite Broadband Deployments Following IPv4 Exhaustion", [RFC 6333](#), DOI 10.17487/RFC6333, August 2011, <<http://www.rfc-editor.org/info/rfc6333>>.
- [RFC6346] Bush, R., Ed., "The Address plus Port (A+P) Approach to the IPv4 Address Shortage", [RFC 6346](#), DOI 10.17487/RFC6346, August 2011, <<http://www.rfc-editor.org/info/rfc6346>>.

[RFC7051] Korhonen, J., Ed. and T. Savolainen, Ed., "Analysis of Solution Proposals for Hosts to Learn NAT64 Prefix", [RFC 7051](https://www.rfc-editor.org/info/rfc7051), DOI 10.17487/RFC7051, November 2013, <<http://www.rfc-editor.org/info/rfc7051>>.

[RFC7346] Droms, R., "IPv6 Multicast Address Scopes", [RFC 7346](https://www.rfc-editor.org/info/rfc7346), DOI 10.17487/RFC7346, August 2014, <<http://www.rfc-editor.org/info/rfc7346>>.

Authors' Addresses

Mohamed Boucadair
Orange
Rennes 35000
France

Email: mohamed.boucadair@orange.com

Jacni Qin
Cisco
P.R. China

Email: jacni@jacni.com

Tina Tsou
Philips Lighting
United States of America

Email: tina.tsou@philips.com

Xiaohong Deng
The University of New South Wales
Sydney NSW 2052
Australia

Email: dxhbupt@gmail.com

