

SPEERMINT
Internet-Draft
Intended status: BCP
Expires: May 24, 2009

T. Creighton
J. Livingood
Comcast
November 20, 2008

Use of DNS SRV and NAPTR Records for SPEERMINT
draft-ietf-speermint-srv-naptr-use-03

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on May 24, 2009.

Abstract

The objective of this document is to specify the Best Current Practice (BCP) adopted by a service provider providing multimedia communication services such as Voice over Internet Protocol (VoIP) in order to locate another service provider to peer with in the context of Session PEERING for Multimedia INTERconnect.

Internet-Draft DNS SRV and NAPTR Records for SPEERMINT November 2008

Table of Contents

1.	Requirements Language	3
2.	Introduction	3
3.	Session Peering Setup	3
3.1.	Target Determination	6
3.2.	NAPTR Lookup	7
3.3.	SRV Lookup	7
3.4.	Using SRV Results	8
4.	High Availability	8
4.1.	SBE1 Fails to Reach SBE2	8
4.2.	Using SRV Results	9
5.	Caching/TTL	9
5.1.	Caching	9
5.2.	TTL	9
6.	Security Considerations	9
7.	IANA Considerations	9
8.	Acknowledgements	10
9.	References	10
9.1.	Normative References	10
9.2.	Informative References	10
Appendix A.	Document Changelog	11
Appendix B.	Open Issues	11
	Authors' Addresses	11
	Intellectual Property and Copyright Statements	12

Internet-Draft DNS SRV and NAPTR Records for SPEERMINT November 2008

1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

2. Introduction

A service provider needs to identify the ingress Session Initiation Protocol (SIP) ([RFC 3261](#) [[RFC3261](#)]) server of a peering network before it can signal and route SIP based real-time communication sessions. This function of locating the ingress SIP server of peering network is typically performed by the egress SIP server of the service provider originating the SIP session. Also, the ingress server in the peering network needs to locate the originating service provider's egress server in situations where the peering connection to it gets terminated after receiving the SIP requests or if the egress SIP server of originating service provider fails. The SIP servers at originating and peering side use the DNS procedures, using both SRV [[RFC3261](#)] and NAPTR [[RFC3404](#)] records, in order to locate each other.

3. Session Peering Setup

SIP systems are represented by user agents (UA). The diagram below shows the case of direct peering where a user agent (UA1), hosted by a service provider SP1, initiates a SIP session to a User Agent (UA2), hosted by service provider SP2. The egress SIP server of SP1 is a SIP signaling path border element (SBE) as defined in section 3 of [[SPEERMINT-Terminology](#)], called SBE1, that interfaces with session peering service provider SP2. The SIP session initiated by UA1 is received by this network element SBE1. The resource to which the SIP request needs to be routed by SBE1 is identified by a SIP or SIPS URI. This could be the SIP URI of UA2 found in the Request-URI of

the SIP request received by SBE1, or the next hop from SBE1 found in the topmost Route header of SIP request. In order to determine the resource to route the request to, SP1 MAY make use of ENUM [[RFC3761](#)] lookup services or an internal lookup to determine the SIP URI of the resource. This lookup MAY be performed by SBE1 or another network element of SP1.




Figure 1

In order to route the SIP request to this resource in SP2, SBE1 needs to determine the ingress SIP signaling path border element for SP2, called SBE2, by resolving the SIP or SIPS URI in DNS. SBE1 makes use of the NAPTR and DNS SRV mechanism defined in [[RFC3263](#)] to determine the IP address, port, and transport protocol for peering with the SP2 ingress SIP proxy server (i.e. SBE2). SBE1 and SBE2 which are




Figure 3

The target, to which the request is sent, is determined by SBE1 as follows:

3.1. Target Determination

The target resource is identified with a SIP or SIPS URI. This is the URI in the Route header, if present, or the URI from the request URI of the SIP request received by SBE1. The host value of the

hostport component of the URI is the TARGET. This TARGET is the domain to be contacted. The NAPTR/SRV/A lookup as described in the following section should be skipped if transport/port/ip address is already specified for the target URI.

3.2. NAPTR Lookup

Next the SBE1 determines the transport protocol of the TARGET by

performing a NAPTR query for the TARGET. NAPTR processing as described in [\[RFC2915\]](#) will result in the discovery of the most preferred transport protocol of a server instance of SBE2 and SRV records.

Considering our example call flow setup above, SBE1 wishes to resolve sip:alice@sp2.com and performs a NAPTR query for that TARGET domain sp2.com, and the following NAPTR records are returned:

```
;          order    pref    flags  service      regexp  replacement
IN NAPTR   50        50     "s"    "SIPS+D2T"   ""      _sips._tcp.sp2.com
IN NAPTR   90        50     "s"    "SIP+D2T"   ""      _sip._tcp.sp2.com
IN NAPTR  100        50     "s"    "SIP+D2U"   ""      _sip._udp.sp2.com
```

Figure 4

DNS MUST return at least three records - one with "SIP+D2T", one with "SIP+D2U" and one with "SIPS+D2T" service type for the case of direct and indirect peering (section 4.3 in [\[SPEERMINT-Terminology\]](#)). For indirect (transit) peering (section 4.4 in [\[SPEERMINT-Terminology\]](#)) since domain validation as specified in [section 26.3.2.2 of \[RFC3261\]](#) for TLS at layer 5 will not work, SIPS over TLS cannot be used.

[3.3.](#) SRV Lookup

Depending on what transport protocols SBE1 supports, SBE1 selects one from the preference list of NAPTR results and performs the SRV lookup to obtain a list of available server instances for SBE2. TLS SHOULD be the preferred transport protocol for peering between SBE1 and SBE2.

In our example SBE1 uses TCP, the SRV lookup for _sip._tcp.sp2.com would return list of available servers :

```
;;      Priority Weight  Port  Target
IN SRV  0           1     5060  server1.sp2.com
IN SRV  0           2     5060  server2.sp2.com
```

Figure 5

Alternatively, if no NAPTR records are found, then SBE1 uses the

preferred transport protocol and issues an SRV query for that specific transport using "sips" for SIPS URI and SIP URI with TLS and "sip" for SIP URI as the SRV domain prefix.

In our example, SBE1 prefers to use TCP and target SIP URI of SP2 is sip:alice@sp2.com, it sends a SRV query for _sip._tcp.sp2.com.

The SRV responses MAY also include A records with it.

3.4. Using SRV Results

If A records are not returned with the SRV responses, procedure from [RFC 2782](#) describes how to use and interpret the results obtained from the SRV query. The target entry of the SRV RRs is looked up by querying the DNS for address records. If the SRV response from DNS includes A records with it, it will cut down on round trips and lookup of DNS again for target entry. On determining the transport protocol, service, port and address record from the SRV RRs as described above, the SBE1 will try to connect to the (protocol, address, service). Once the connection is established to an available instance of SBE2, SBE1 sends the SIP request to SBE2. SBE1 MUST act in a stateful manner and any retransmission of SIP requests for a specific SIP transaction, including ACKS for non-2xx response or CANCEL for that SIP transaction MUST go to the same server instance of SBE2.

When SBE1 sends the SIP request to SBE2, it SHOULD set the sent-by parameter of the topmost Via header in the SIP request to a domain that identifies SBE1. It MUST NOT specify the port.

4. High Availability

High Availability is ensured by detecting failures in the ability to connect to SBE1 and SBE2 server instances. In the event of a failure, when SBE1 tries to send SIP INVITE to SBE2, the following failures could occur:

4.1. SBE1 Fails to Reach SBE2

A 503 error response is reported by the transaction layer, or failure can occur at the transport layer due to TCP disconnect in connection, ICMP error in UDP or time out at transport layer or SIP layer timeout when its not receiving any SIP response. In such situations, SBE1 tries a new SIP request transaction to the next available server instance of SBE2 as determined by SRV RRs entry. The SIP T1 timer on SBE1 SHOULD be configurable with a upper limit value of 500ms. A

shorter value of T1, say 100ms, reflects a faster failover support.

[4.2.](#) Using SRV Results

Failure may also occur after the request is received by SBE2 from SBE1 due to closure of the transport connection the request came in on at SBE2, before the response can be sent back to SBE1. In this situation, SBE2 uses the domain value present in the 'sent-by' parameter in the top most Via header of the received SIP INVITE, and queries for SRV records at this domain name using the service identifier "_sips" if the Via transport is "TLS", "_sip" otherwise. The sorted list of SRV RRs are obtained and used as described in [\[RFC2782\]](#) to send the response back to SBE1. If the topmost element in the list of server instances of SBE1 fails, the next available one is tried.

[FOR NEXT REV: SHOULD WE ADD CALL FLOW FOR FAILURE SCENARIO DESCRIBED IN 4.1 AND 4.2]

[5.](#) Caching/TTL

[5.1.](#) Caching

SBE SHOULD use caching of DNS results to eliminate unnecessary DNS queries.

[5.2.](#) TTL

SRV RRs have a TTL value based on which the SBE1 caches the entry for that duration, if it supports caching, and any further requests to the same TARGET domain are delivered to the cached server instance. The TTL recommended for SRV is about 1 hr. The TTL for NAPTR is much higher, about 1 day (24hrs) since the NAPTR records do not vary that often as compared to SRV.

[6.](#) Security Considerations

This document introduces no new security considerations.

[7.](#) IANA Considerations

There are no IANA considerations in this document.

Internet-Draft DNS SRV and NAPTR Records for SPEERMINT November 2008

8. Acknowledgements

Special thanks go to Yiu Lee for his valuable input to this document.

9. References

9.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2782] Gulbrandsen, A., Vixie, P., and L. Esibov, "A DNS RR for specifying the location of services (DNS SRV)", [RFC 2782](#), February 2000.
- [RFC2915] Mealling, M. and R. Daniel, "The Naming Authority Pointer (NAPTR) DNS Resource Record", [RFC 2915](#), September 2000.
- [RFC3261] Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M., and E. Schooler, "SIP: Session Initiation Protocol", [RFC 3261](#), June 2002.
- [RFC3263] Rosenberg, J. and H. Schulzrinne, "Session Initiation Protocol (SIP): Locating SIP Servers", [RFC 3263](#), June 2002.
- [RFC3404] Mealling, M., "Dynamic Delegation Discovery System (DDDS) Part Four: The Uniform Resource Identifiers (URI)", [RFC 3404](#), October 2002.
- [RFC3667] Bradner, S., "IETF Rights in Contributions", [RFC 3667](#), February 2004.
- [RFC3761] Faltstrom, P. and M. Mealling, "The E.164 to Uniform Resource Identifiers (URI) Dynamic Delegation Discovery System (DDDS) Application (ENUM)", [RFC 3761](#), April 2004.

[SPEERMINT-Terminology]
Malas, D. and D. Meyer, "SPEERMINT Terminology",
February 2008.

9.2. Informative References

[RFC2434] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 2434](#), October 1998.

Creighton & Livingood

Expires May 24, 2009

[Page 10]

Internet-Draft DNS SRV and NAPTR Records for SPEERMINT November 2008

Appendix A. Document Changelog

[RFC Editor: This section is to be removed before publication]

[draft-ietf-speermint-srv-naptr-use-03](#):

- o jason: converted from MS Word template to XML

Appendix B. Open Issues

Several in queue. These will be dealt with shortly in -04, so please hold comments until that document is released.

Authors' Addresses

Tom Creighton
Comcast Cable Communications
One Comcast Center
1701 John F. Kennedy Boulevard
Philadelphia, PA 19103
US

Email: tom_creighton@cable.comcast.com
URI: <http://www.comcast.com>

Jason Livingood
Comcast Cable Communications
One Comcast Center
1701 John F. Kennedy Boulevard

Philadelphia, PA 19103
US

Email: jason_livingood@cable.comcast.com

URI: <http://www.comcast.com>

Creighton & Livingood

Expires May 24, 2009

[Page 11]

Internet-Draft DNS SRV and NAPTR Records for SPEERMINT November 2008

Full Copyright Statement

Copyright (C) The IETF Trust (2008).

This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY, THE IETF TRUST AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Intellectual Property

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information

on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.