

Network Working Group  
Ed.  
Internet-Draft  
Canada  
Intended status: Standards Track  
Filsfils  
Expires: May 2, 2021  
Parekh  
Inc.  
Bidgoli  
Nokia  
Zhang  
Networks  
2020

D. Voyer,  
Bell  
C.  
R.  
Cisco Systems,  
H.  
Z.  
Juniper  
October 29,

**SR Replication Segment for Multi-point Service Delivery  
draft-ietf-spring-sr-replication-segment-03**

Abstract

This document describes the SR Replication segment for Multi-point service delivery. A SR Replication segment allows a packet to be replicated from a replication node to downstream nodes.

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months

and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 2, 2021.



Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with

respect

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

- [1](#) [1](#). Introduction . . . . .
- [2](#) [2](#). Replication Segment . . . . .
- [3](#) [3](#). Use Cases . . . . .
- [4](#) [4](#). IANA Considerations . . . . .
- [5](#) [5](#). Security Considerations . . . . .
- [5](#) [6](#). Acknowledgements . . . . .
- [5](#) [7](#). Contributors . . . . .
- [6](#) [8](#). References . . . . .
  - [6](#) [8.1](#). Normative References . . . . .
  - [7](#) [8.2](#). Informative References . . . . .
- [7](#) [Appendix A](#). Illustration of a Replication Segment . . . . .
- [9](#) Authors' Addresses . . . . .

**[1](#). Introduction**

We define a new type of segment for Segment Routing [[RFC8402](#)], called

Replication segment, which allows a node (henceforth called as Replication Node) to replicate packets to a set of other nodes (called Downstream Nodes) in a Segment Routing Domain. Replication segments provide building blocks for Point-to-Multipoint Service delivery via SR Point-to-Multipoint (SR P2MP) policy. A Replication

segment can replicate packet to directly connected nodes or to downstream nodes (without need for state on the transit routers). This document focuses on the Replication Segment building block.

The

use of one or more stitched Replication Segments constructed for SR P2MP Policy tree is specified in [[I-D.voyer-pim-sr-p2mp-policy](#)].

## 2. Replication Segment

In a Segment Routing Domain, a Replication segment is a logical construct which connects a Replication Node to a set of Downstream Nodes. A Replication segment is a local segment instantiated at a Replication node. It can be either provisioned locally on a node or programmed by a PCE. Replication segments apply equally to both SR-MPLS and SRv6 instantiations of Segment Routing.

A Replication segment is identified by the tuple <Replication-ID, Node-ID>, where:

- o Replication-ID: An identifier for a Replication segment that is unique in context of the Replication Node.
- o Node-ID: The address of the Replication Node that the Replication segment is for. Note that the root of a multi-point service is also a replication node.

In simplest case, Replication-ID can be a 32-bit number, but it can be extended or modified as required based on specific use of a Replication segment. When the PCE signals a Replication segment to its node, the <Replication-ID, Node-ID> tuple identifies the segment.

Examples of such signaling and extension are described in [[I-D.voyer-pim-sr-p2mp-policy](#)].

A Replication segment includes the following elements:

- o Replication SID: The Segment Identifier of a Replication segment. This is a SR-MPLS label or a SRv6 SID [[RFC8402](#)].
- o Downstream Nodes: Set of nodes in Segment Routing domain to which a packet is replicated by the Replication segment.
- o Replication State: See below.

The Downstream Nodes and Replication State of a Replication segment can change over time, depending on the network state and leaf nodes of a multi-point service that the segment is part of.

Replication State is a list of replication branches to the Downstream

Nodes. In this document, each branch is abstracted to a <Downstream Node, Downstream Replication SID> tuple. A Downstream Node is represented by a SID-list or a Segment Routing Policy [[I-D.ietf-spring-segment-routing-policy](#)] that specifies the explicit path from the Replication Node to the Downstream Node, or even represented by another Replication segment. The SID-list MAY just



have one SID. If a downstream node is adjacent to a Replication node, it MAY also be represented by an interface.

Replication SID identifies the Replication segment in the forwarding plane. At a Replication node, the Replication SID is the equivalent of Binding SID [[I-D.ietf-spring-segment-routing-policy](#)] of a Segment Routing Policy.

A packet steered into a Replication segment at a Replication node is replicated to each Downstream Node with the Downstream Replication SID that is relevant at that node. A packet is steered into a Replication Segment in two ways:

- o When the Active Segment [[RFC8402](#)] is the Replication SID. In this case, the operation is NEXT followed by a PUSH for a replicated copy.
- o On the root of a multi-point service, based on local policy-based routing. In this case, the operation for a replicated copy is PUSH.

If a Downstream Node is an egress (aka leaf) of the multi-point service, i.e. no further replication is needed, then that leaf node's

Replication segment will not have any Replication State and the operation is NEXT. At an egress node, the Replication SID MAY be used to identify that portion of the multi-point service. Notice that the segment on the leaf node is still referred to as a Replication segment for the purpose of generalization.

A node can be a bud node, i.e. it is a replication node and a leaf node of a multi-point service at the same time [[I-D.voyer-pim-sr-p2mp-policy](#)]. In this case, the Replication segment's Replication State includes a branch with the Downstream Node being itself and the operation for the replicated copy is NEXT.

The Replication SID MUST be the last SID (at the bottom of stack for SR-MPLS) in a packet that is steered out from a Replication node of

a Replication Segment. The behavior at Downstream nodes of a Replication Segment is undefined If there are any SIDs after the Replication SID and is outside the scope of this document.

### **3. Use Cases**

In the simplest use case, a single Replication segment includes the root node of a multi-point service and the egress/leaf nodes of the the service as all the Downstream Nodes. This achieves Ingress Replication [[RFC7988](#)] that has been widely used for MVPN [[RFC6513](#)] and EVPN [[RFC7432](#)] BUM (Broadcast, Unknown and Multicast) traffic.





Replication segments can also be used as building blocks for replication trees when Replication segments on the root, intermediate replication nodes and leaf nodes are stitched together to achieve efficient replication. That is specified in [[I-D.voyer-pim-sr-p2mp-policy](#)].

#### **4. IANA Considerations**

This document makes no request of IANA.

#### **5. Security Considerations**

There are no additional security risks introduced by this design.

#### **6. Acknowledgements**

The authors would like to acknowledge Siva Sivabalan, Mike Koldychev, Vishnu Pavan Beeram, Alexander Vainshtein, Bruno Decraene and Joel Halpern for their valuable inputs.

#### **7. Contributors**

Clayton Hassen  
Bell Canada  
Vancouver  
Canada

Email: [clayton.hassen@bell.ca](mailto:clayton.hassen@bell.ca)

Kurtis Gillis  
Bell Canada  
Halifax  
Canada

Email: [kurtis.gillis@bell.ca](mailto:kurtis.gillis@bell.ca)

Arvind Venkateswaran  
Cisco Systems, Inc.  
San Jose  
US

Email: [arvvenka@cisco.com](mailto:arvvenka@cisco.com)

Zafar Ali  
Cisco Systems, Inc.  
US

Email: [zali@cisco.com](mailto:zali@cisco.com)



Swadesh Agrawal  
Cisco Systems, Inc.  
San Jose  
US

Email: swaagraw@cisco.com

Jayant Kotalwar  
Nokia  
Mountain View  
US

Email: jayant.kotalwar@nokia.com

Tanmoy Kundu  
Nokia  
Mountain View  
US

Email: tanmoy.kundu@nokia.com

Andrew Stone  
Nokia  
Ottawa  
Canada

Email: andrew.stone@nokia.com

Tarek Saad  
Juniper Networks  
Canada

Email: tsaad@juniper.net

## **8. References**

### **8.1. Normative References**

- [I-D.ietf-spring-segment-routing-policy]  
Filsfils, C., Talaulikar, K., Voyer, D., Bogdanov, A.,  
and  
P. Mattes, "Segment Routing Policy Architecture", [draft-ietf-spring-segment-routing-policy-08](#) (work in progress),  
July 2020.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate  
Requirement Levels", [BCP 14](#), [RFC 2119](#),  
DOI 10.17487/RFC2119, March 1997,  
<<https://www.rfc-editor.org/info/rfc2119>>.



- [RFC8402] Filsfils, C., Ed., Previdi, S., Ed., Ginsberg, L., Decraene, B., Litkowski, S., and R. Shakir, "Segment Routing Architecture", [RFC 8402](#), DOI 10.17487/RFC8402, July 2018, <<https://www.rfc-editor.org/info/rfc8402>>.

## 8.2. Informative References

- [I-D.voyer-pim-sr-p2mp-policy] Voyer, D., Filsfils, C., Parekh, R., Bidgoli, H., and Z. Zhang, "Segment Routing Point-to-Multipoint Policy", [draft-voyer-pim-sr-p2mp-policy-02](#) (work in progress), July 2020.
- [RFC6513] Rosen, E., Ed. and R. Aggarwal, Ed., "Multicast in MPLS/BGP IP VPNs", [RFC 6513](#), DOI 10.17487/RFC6513, February 2012, <<https://www.rfc-editor.org/info/rfc6513>>.
- [RFC7432] Sajassi, A., Ed., Aggarwal, R., Bitar, N., Isaac, A., Uttaro, J., Drake, J., and W. Henderickx, "BGP MPLS-Based Ethernet VPN", [RFC 7432](#), DOI 10.17487/RFC7432, February 2015, <<https://www.rfc-editor.org/info/rfc7432>>.
- [RFC7988] Rosen, E., Ed., Subramanian, K., and Z. Zhang, "Ingress Replication Tunnels in Multicast VPN", [RFC 7988](#), DOI 10.17487/RFC7988, October 2016, <<https://www.rfc-editor.org/info/rfc7988>>.

## Appendix A. Illustration of a Replication Segment

This section illustrates an example of a single Replication Segment. Examples showing Replication Segment stitched together to form P2MP tree (based on SR P2MP policy) are in [[I-D.voyer-pim-sr-p2mp-policy](#)].

Consider the following topology:




Figure 1

In this example, the Node-SID of a node Rn is N-SIDn and Adjacency-SID from node Rm to node Rn is A-SIDmn. Interface between Rm and Rn is Lmn.



Assume a Replication Segment identified with R-ID at replication node R1 and downstream Nodes R2, R6 and R7. The Replication SID at node n is R-SIDn. A packet replicated from R1 to R7 has to traverse R4.

The Replication Segment state at nodes R1, R2, R6 and R7 is shown below. Note nodes R3, R4 and R5 do not have state for the Replication Segment.

Replication Segment at R1:

```
Replication Segment <R-ID,R1>:
  Replication SID: R-SID1
  Replication State:
    R2: <R-SID2->L12>
    R6: <N-SID6, R-SID6>
    R7: <N-SID4, A-SID47, R-SID7>
```

Replication to R2 steers packet directly to R2 on interface L12. Replication to R6, using N-SID6, steers packet via IGP shortest path to that node. Replication to R7 is steered via R4, using N-SID4 and then adjacency SID A-sid47 to R7.

Replication Segment at R2:

```
Replication Segment <R-ID,R2>:
  Replication SID: R-SID2
  Replication State:
    R2: <Leaf>
```

Replication Segment at R6:

```
Replication Segment <R-ID,R6>:
  Replication SID: R-SID6
  Replication State:
    R6: <Leaf>
```

Replication Segment at R7:

```
Replication Segment <R-ID,R7>:
  Replication SID: R-SID7
  Replication State:
    R7: <Leaf>
```

When a packet is steered into the replication segment at R1:

- o Since R1 is directly connected to R2, R1 performs PUSH operation with just <R-SID2> label for the replicated copy and sends it to





R2 on interface L12. R2, as Leaf, performs NEXT operation, pops R-SID2 label and delivers the payload.

- o R1 performs PUSH operation with <N-SID6, R-SID6> label stack for the replicated copy to R6 and sends it to R2, the nexthop on IGP shortest path to R6. R2 performs CONTINUE operation on N-SID6

and

forwards it to R3. R3 is the penultimate hop for N-SID6; it performs penultimate hop popping, which corresponds to the NEXT operation and the packet is then sent to R6 with <R-SID6> in the label stack. R6, as Leaf, performs NEXT operation, pops R-SID6 label and delivers the payload.

- o R1 performs PUSH operation with <N-SID4, A-SID47, R-SID7> label stack for the replicated copy to R7 and sends it to R2, the nexthop on IGP shortest path to R4. R2 is the penultimate hop

for

N-SID4; it performs penultimate hop popping, which corresponds to the NEXT operation and the packet is then sent to R4 with <A-SID47, R-SID1> in the label stack. R4 performs NEXT

operation,

pops A-SID47, and delivers packet to R7 with <R-SID7> in the

label

stack. R7, as Leaf, performs NEXT operation, pops R-SID7 label and delivers the payload.

#### Authors' Addresses

Daniel Voyer (editor)  
Bell Canada  
Montreal  
CA

Email: [daniel.voyer@bell.ca](mailto:daniel.voyer@bell.ca)

Clarence Filsfils  
Cisco Systems, Inc.  
Brussels  
BE

Email: [cfilsfil@cisco.com](mailto:cfilsfil@cisco.com)

Rishabh Parekh  
Cisco Systems, Inc.  
San Jose  
US

Email: [riparekh@cisco.com](mailto:riparekh@cisco.com)



Internet-Draft  
2020

SR Replication Segment

October

Hooman Bidgoli  
Nokia  
Ottawa  
CA

Email: [hooman.bidgoli@nokia.com](mailto:hooman.bidgoli@nokia.com)

Zhaohui Zhang  
Juniper Networks

Email: [zzhang@juniper.net](mailto:zzhang@juniper.net)

