

Storage Maintenance (StorM) Working Group
Internet Draft
Intended status: Standards Track
Expires: January 2014

Frederick Knight
NetApp
M. Chadalapaka
Microsoft
July 2013

**Internet Small Computer Systems Interface (iSCSI) SCSI Features
Update
draft-ietf-storm-iscsi-sam-08.txt**

Abstract

Internet Small Computer Systems Interface (iSCSI) is a SCSI transport protocol that maps the SCSI family of protocols onto TCP/IP. The iSCSI protocol as specified in RFCxxx (and as previously specified by the combination of [RFC 3720](#) and [RFC 5048](#)) is based on the SAM-2 (SCSI Architecture Model - 2) version of the SCSI family of protocols. This document defines enhancements to the iSCSI protocol to support certain additional features of the SCSI protocol that were defined in SAM-3, SAM-4, and SAM-5.

This document is a companion document to RFCxxx.

RFC EDITORS NOTE: The above two references to RFCxxx should reference the RFC number assigned to the [draft-ietf-storm-iscsi-cons-xx](#) document, and this note should be removed.

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/1id-abstracts.html>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire January, 2014.

Knight, et al.

Expires January, 2014

[Page 1]

Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction.....	3
2.	Definitions, Acronyms, and Document Summary.....	3
2.1	Definitions	3
2.2	Acronyms	3
2.3	New Semantics	3
3.	Terminology Mapping.....	4
4.	New Feature Use.....	7
4.1	Negotiation of New Feature Use.....	7
4.2	Impact on standard INQUIRY data.....	7
5.	SCSI Commands.....	8
5.1	SCSI Command Additions	8
5.1.1	Command Priority (byte 2)	9
5.2	SCSI Response Additions	10
5.2.1	Status Qualifier	11
5.2.2	Data Segment - Sense and Response Data Segment ...	11
6.	Task Management Functions.....	12
6.1	Existing Task Management Functions	12
6.2	Task Management Function Additions	13
6.2.1	LUN field	14
6.2.2	Referenced Task Tag	14
6.2.3	RefCmdSN	15
6.3	Task Management Function Responses	16
6.3.1	Task Management Function Response Additions	17
6.4	Task Management Requests Affecting Multiple Tasks	18
7.	Login/Text Operational Text Keys.....	18
7.1	New Operational Text Keys	18
7.1.1	iSCSIProtocolLevel	18
8.	Security Considerations.....	19
9.	IANA Considerations.....	19
10.	References.....	22
11.	Acknowledgements.....	23

1. Introduction

The original iSCSI protocol [[RFC3720](#)] was built based on the [[SAM2](#)] model for SCSI. Several new features and capabilities have been added to the SCSI Architecture Model in the intervening years (at the time of publication of this document, SAM-5 was the current version of the SCSI Architecture Model). This document is not a complete revision of [[RFC3720](#)]. Instead, this document is intended as a companion document to [[draft-ietf-storm-iscsi-cons-xx](#)]; this document may also be used as a companion document to the combination of [[RFC3720](#)] and [[RFC5048](#)], although both of those RFCs have been obsolete by [[draft-ietf-storm-iscsi-cons-xx](#)].

RFC EDITORS NOTE: The above references to [[draft-ietf-storm-iscsi-cons-xx](#)] should reference the RFC number assigned to that document, and this note should be removed.

2. Definitions, Acronyms, and Document Summary

2.1 Definitions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

2.2 Acronyms

ISID	Initiator Session Identifier
LU	Logical Unit
PDU	Protocol Data Unit
SAM-5	SCSI Architecture Model - 5 (see [SAM5])
TMF	Task Management Function

2.3 New Semantics

This document specifies new iSCSI semantics. This section summarizes the contents of the document.

[Section 3](#): The mapping of iSCSI objects to SAM-5 objects
The iSCSI node may contain both initiator and target capabilities.

[Section 4](#): The protocol used to negotiate the use of the new capabilities described in this document.

[Section 5](#): New Command operations

Knight, et al.	Expires January, 2014	Page 3
Internet-Draft	iSCSI SCSI Features Update	July 13

The PRI field for SCSI command priority has been added to the SCSI command PDU (see 5.1.1).
The Status Qualifier field has been added to the SCSI response PDU (see 5.2.1).
Sense data may be returned (via autosense) for any SCSI status, not just CHECK CONDITION (see 5.2.2).

[Section 6](#): New Task Management Functions

Four new task management functions (QUERY TASK, QUERY TASK SET, I_T NEXUS RESET, and QUERY ASYNCHRONOUS EVENT have been added (see 6.3).
A new "function succeeded" response has been added (see 6.4.2).

[Section 7](#): New Negotiation key

A new negotiation key has been added to enable the use of the new features in [section 5](#) and [section 6](#).

3. Terminology Mapping

The iSCSI model (defined in [RFC-cons]) uses different terminology than the SCSI Architecture Model. In some cases, iSCSI uses multiple terms to describe what in the SCSI Architecture Model is described with a single term. The iSCSI terms and SAM-5 terms are not necessarily equivalent, but rather, the iSCSI terms represent examples of the objects or classes described in SAM-5 as follows:

RFC EDITORS NOTE: The above reference to [RFC-cons] should reference the RFC number assigned to [[draft-ietf-storm-iscsi-cons-xx](#)], and this note should be removed.

Knight, et al.	Expires January, 2014	Page 4
Internet-Draft	iSCSI SCSI Features Update	July 13

+-----+


RFCxxx Terminology	SAM-5 Terminology
Network Entity	none
iSCSI Node	SCSI Device
iSCSI Name	SCSI Device Name
iSCSI Node Name	SCSI Device Name
iSCSI Initiator Node	SCSI Initiator Device
iSCSI Initiator Name	SCSI Device Name
iSCSI Initiator Port Identifier; (i.e., iSCSI Node Name + ,,,i, + ISID)*1	SCSI Initiator Port Identifier
iSCSI Initiator Port Name; (i.e., iSCSI Node Name + ,,,i, + ISID)*1	SCSI Initiator Port Name
iSCSI Target Node	SCSI Target Device
iSCSI Target Name	SCSI Device Name
iSCSI Target Port Identifier; (i.e., iSCSI Node Name + ,,,t, + Target Portal Group Tag)*1	SCSI Target Port Identifier
iSCSI Target Port Name; (i.e., iSCSI Node Name + ,,,t, + Target Portal Group Tag)*1	SCSI Target Port Name
iSCSI Target Portal Group	SCSI Target Port
iSCSI Initiator Name + ',i,' + ISID + iSCSI Target Name + ',t,' + Target Portal Group Tag	I_T Nexus Identifier
Target Portal Group Tag	Relative Port ID

*1 The text encoding of the ISID value and the Target Portal Group Tag value includes an initial ,0X or ,0x (see [RFC-cons]).

RFC EDITORS NOTE: The above reference (in row 1) to [RFCxxx]
should reference this RFC, and this note should be removed.

The above reference to [RFC-cons] should reference the RFC
number assigned to [[draft-ietf-storm-iscsi-cons-xx](#)], and this
note should be removed.

The following diagram shows an example of a combination target
device and initiator device. Such a configuration may exist in a
target device that implements a SCSI Copy Manager. This example
shows how a session that shares Network Portals within a Portal
Group may be established (see Target Portal Group 1). In
addition, this example shows the Initiator using a different
Portal Group than the Target Portal Group, but the Initiator
Portal group sharing Network Portal A with the Target Portal
Group.



4. New Feature Use

4.1 Negotiation of New Feature Use

The `iSCSIProtocolLevel` operational text key (see 7.1.1) containing a value of "2" MUST be negotiated to enable the use of features described in this RFC.

This is an iSCSI negotiation mechanism that enabled iSCSI support for corresponding SCSI capabilities (see [SAM5] and [SPC4]). For this reason, negotiation of this key to a value of "2" is necessary, but not sufficient for use of the SCSI capabilities enabled by the iSCSI features in this RFC.

For example, an iSCSI implementation may negotiate this new key to "2" but respond to the new task management functions (see 6.3) with a "Task management function not supported" (which indicates a SCSI error that prevents the function from being performed). In contrast, if the key is negotiated to "2", an iSCSI implementation MUST NOT reject a task management function request PDU that requests one of the new task management functions (as such a reject would report an iSCSI protocol error).

4.2 Impact on standard INQUIRY data

The negotiated value of the `iSCSIProtocolLevel` key is an increment from the base iSCSI version descriptor value (0960h)(see [SPC4]). If the SCSI device server returns an iSCSI version descriptor in the standard INQUIRY data, then the value returned in that iSCSI version descriptor MUST be set to the sum of the base value (0960h) plus the negotiated value of the `iSCSIProtocolLevel` key (for example, if the negotiated `iSCSIProtocolLevel`=2, then if an iSCSI version descriptor is returned in the standard INQUIRY data it is set to 0962h).

RFC EDITORS NOTE: The specification text in this section requires corresponding changes in a SCSI standard (SPC-4 or SPC-5) that is developed by INCITS Technical Committee T10. Confirmation that these T10 changes have been made is necessary before publishing this draft as an RFC; the contacts for obtaining this confirmation are the primary draft author (Frederick Knight) and storm WG chair (David Black).

5. SCSI Commands

5.1 SCSI Command Additions

The format of the SCSI Command PDU is:

Byte/	0	1	2	3	
/					
0 1 2 3 4 5 6 7	0 1 2 3 4 5 6 7	0 1 2 3 4 5 6 7	0 1 2 3 4 5 6 7		
0 . I 0x01	F R W . . ATTR	PRI	Reserved		
4 TotalAHSLength	DataSegmentLength				
8 Logical Unit Number (LUN)					
12					
16 Initiator Task Tag					
20 Expected Data Transfer Length					
24 CmdSN					
28 ExpStatSN					
32 / SCSI Command Descriptor Block (CDB)					/
+ /					/
48 / AHS (Optional)					/
x / Header Digest (Optional)					/
y / (DataSegment, Command Data) (Optional)					/
+ /					/
z / Data Digest (Optional)					/
+ /					/

The SCSI Command PDU above is duplicated from [RFC-cons] for reference to show the PRI field. For any field other than the PRI field, the text in [RFC-cons] supersedes the text in [section 5.1](#) of this document in the event the two documents conflict.

RFC EDITORS NOTE: The above references to [RFC-cons] should
reference the RFC number assigned to [[draft-ietf-storm-iscsi-
cons-xx](#)], and this note should be removed.

[5.1.1](#) Command Priority (byte 2)

The Command Priority (PRI) is a four (4) bit field that specifies the relative scheduling importance of this command in relation to other commands already in the task set with SIMPLE task attributes(see [[SAM5](#)]).

[Section 11](#), iSCSI PDU Formats of [RFC-cons], requires that senders set this field to zero. A sender MUST NOT set this field to a value other than zero unless the iSCSIProtocolLevel text key defined in [section 7.1.1](#) has been negotiated on the session with a value of "2".

RFC EDITORS NOTE: The above reference to [RFC-cons] should
reference the RFC number assigned to [[draft-ietf-storm-iscsi-
cons-xx](#)], and this note should be removed.

This field MUST be ignored by iSCSI targets unless the iSCSIProtocolLevel text key with a value of "2" as defined in [section 7.1.1](#) was negotiated on the session.

See [[SAM5](#)] for additional considerations on the use of the command priority field.

[5.2](#) SCSI Response Additions

The format of the SCSI Response PDU is:

Byte/	0		1		2		3	
/								
	0 1 2 3 4 5 6 7	0 1 2 3 4 5 6 7	0 1 2 3 4 5 6 7	0 1 2 3 4 5 6 7				

```

+-----+-----+-----+-----+
0|.|.| 0x21      |1|. .|o|u|0|U|.| Response      | Status      |
+-----+-----+-----+-----+
4|TotalAHSLength | DataSegmentLength |
+-----+-----+-----+-----+
8| Status Qualifier      | Reserved      |
+-----+-----+-----+-----+
12| Reserved      |
+-----+-----+-----+-----+
16| Initiator Task Tag      |
+-----+-----+-----+-----+
20| SNACK Tag or Reserved      |
+-----+-----+-----+-----+
24| StatSN      |
+-----+-----+-----+-----+
28| ExpCmdSN      |
+-----+-----+-----+-----+
32| MaxCmdSN      |
+-----+-----+-----+-----+
36| ExpDataSN or Reserved      |
+-----+-----+-----+-----+
40| Bidirectional Read Residual Count or Reserved      |
+-----+-----+-----+-----+
44| Residual Count or Reserved      |
+-----+-----+-----+-----+
48| Header-Digest (Optional)      |
+-----+-----+-----+-----+
/ Data Segment (Optional)      /
+/-/
+-----+-----+-----+-----+
| Data-Digest (Optional)      |
+-----+-----+-----+-----+

```

The SCSI Response PDU above is duplicated from [RFC-cons] for reference to show the Status Qualifier field. For any field other than the Status field, the Status Qualifier field, and the Data Segment - Sense and Response Data Segment field, the text in [RFC-cons] supersedes the text in [section 5.2](#) of this document in the event the two documents conflict.

```

-----
RFC EDITORS NOTE: The above references to [RFC-cons] should
reference the RFC number assigned to [draft-ietf-storm-iscsi-cons-xx], and this note should be removed.
-----

```

[5.2.1](#) Status Qualifier

The Status Qualifier provides additional status information (see [\[SAM5\]](#)).

As defined in [Section 11](#), iSCSI PDU Formats of [RFC-cons], compliant senders already set this field to zero. Compliant senders MUST NOT set this field to a value other than zero unless the iSCSIProtocolLevel text key with a value of "2" as defined in [section 7.1.1](#) was negotiated on the session.

RFC EDITORS NOTE: The above reference to [RFC-cons] should reference the RFC number assigned to [\[draft-ietf-storm-iscsi-cons-xx\]](#), and this note should be removed.

This field MUST be ignored by receivers unless the iSCSIProtocolLevel text key with a value of "2" as defined in [section 7.1.1](#) was negotiated on the session.

5.2.2 Data Segment - Sense and Response Data Segment

[Section 11.4.7](#) of [RFC-cons] specifies that iSCSI targets MUST support and enable autosense. If Status is CHECK CONDITION (0x02), then the Data Segment MUST contain sense data for the failed command. While [RFC-cons] does not make any statements about the state of the Data Segment when the Status is not CHECK CONDITION (0x02)(i.e., the Data Segment is not prohibited from containing sense data when the Status is not CHECK CONDITION), negotiation of the iSCSIProtocolLevel text key with a value of "2" as defined in [section 7.1.1](#) explicitly indicates that the Data Segment MAY contain sense data at any time, no matter what value is set in the Status field.

RFC EDITORS NOTE: The above references to [RFC-cons] should reference the RFC number assigned to [\[draft-ietf-storm-iscsi-cons-xx\]](#), and this note should be removed.

6. Task Management Functions

6.1 Task Management Function Request PDU

Byte/	0		1		2		3	
-------	---	--	---	--	---	--	---	--

/			
0 1 2 3 4 5 6 7	0 1 2 3 4 5 6 7	0 1 2 3 4 5 6 7	0 1 2 3 4 5 6 7
+	+	+	+
0 . I 0x02	1 Function	Reserved	
+	+	+	+
4 TotalAHSLength	DataSegmentLength		
+	+	+	+
8 Logical Unit Number (LUN)			
+			+
12			
+	+	+	+
16 Initiator Task Tag			
+	+	+	+
20 Referenced Task Tag or 0xffffffff			
+	+	+	+
24 CmdSN			
+	+	+	+
28 ExpStatSN			
+	+	+	+
32 RefCmdSN or Reserved			
+	+	+	+
36 ExpDataSN or Reserved			
+	+	+	+
40 Reserved			/
+/			/
+	+	+	+
48 Header-Digest (Optional)			
+	+	+	+

The Task Management Function Request PDU above is duplicated from [RFC-cons] for reference only. [RFC-cons] supersedes the text in [section 6.1](#) and 6.2 of this document in the event the two documents conflict.

RFC EDITORS NOTE: The above references to [RFC-cons] should reference the RFC number assigned to [[draft-ietf-storm-iscsi-cons-xx](#)], and this note should be removed.

6.2 Existing Task Management Functions

[Section 11.5](#) of [RFC-cons] defines the semantics used to request SCSI Task Management Functions be performed. The following task management functions are defined:

- 1 - ABORT TASK
- 2 - ABORT TASK SET
- 3 - CLEAR ACA
- 4 - CLEAR TASK SET
- 5 - LOGICAL UNIT RESET
- 6 - TARGET WARM RESET
- 7 - TARGET COLD RESET
- 8 - TASK REASSIGN

RFC EDITORS NOTE: The above references to [RFC-cons] should reference the RFC number assigned to [[draft-ietf-storm-iscsi-cons-xx](#)], and this note should be removed.

6.3 Task Management Function Additions

Additional task Management function codes are listed below. For a more detailed description of SCSI task management, see [[SAM5](#)].

- 9 - QUERY TASK - determines if the command identified by the Referenced Task Tag field is present in the task set.
- 10 - QUERY TASK SET - determine if any command is present in the task set for the I_T_L Nexus on which the task management function was received.
- 11 - I_T NEXUS RESET - perform an I_T nexus loss function (see [[SAM5](#)]) for the I_T nexus on which the task management function was received.
- 12 - QUERY ASYNCHRONOUS EVENT - determine if there is a unit attention condition or a deferred error pending for the I_T_L nexus on which the task management function was received.

These task management function requests MUST NOT be sent unless the iSCSIProtocolLevel text key with a value of "2" as defined in [section 7.1.1](#) was negotiated on the session.

Any compliant initiator that sends any of the new task management functions defined in this section MUST also support all new task management function responses (as specified in [section 6.4.2](#)).

For all of the task management functions detailed in this section, the Task Management function response MUST be returned as detailed in [section 6.4](#).

The iSCSI target MUST ensure that no responses for the commands covered by a task management function are sent to the iSCSI initiator port after the Task Management response except for a commands covered by a TASK REASSIGN, QUERY TASK, or QUERY TASK SET.

If a QUERY TASK is issued for a task created by an immediate command then RefCmdSN MUST be that of the Task Management request itself (i.e., CmdSN and RefCmdSN are equal); otherwise RefCmdSN MUST be set to the CmdSN of the task to be queried (lower than CmdSN).

If the connection is still active (it is not undergoing an implicit or explicit logout), QUERY TASK MUST be issued on the same connection to which the task to be queried is allegiant at the time the Task Management request is issued. If the connection is implicitly or explicitly logged out (i.e., no other request will be issued on the failing connection and no other response will be received on the failing connection), then a QUERY TASK function request may be issued on another connection. This Task Management request will then establish a new allegiance for the command being queried.

At the target a QUERY TASK function MUST NOT be executed on a Task Management request; such a request MUST result in Task Management response of "Function rejected".

For the I_T NEXUS RESET function, the target device MUST respond to the function as defined in [SAM5]. Each logical unit accessible via the receiving I_T NEXUS MUST behave as dictated by the I_T nexus loss function in [SAM5] for the I_T nexus on which the task management function was received. The target device MUST drop all connections in the session over which this function is received. Independent of the DefaultTime2Wait and DefaultTime2Retain value applicable to the session over which this function is received, the target device MUST consider each participating connection in the session to have immediately timed out, leading to FREE state. The resulting timeouts cause the session timeout event defined in [RFC-cons], which in turn triggers the I_T nexus loss notification to the SCSI layer as described in [RFC-cons].

RFC EDITORS NOTE: The above references to [RFC-cons] should reference the RFC number assigned to [[draft-ietf-storm-iscsi-cons-xx](#)], and this note should be removed.

[6.3.1](#) LUN field

This field is required for functions that address a specific LU (i.e., ABORT TASK, CLEAR TASK SET, ABORT TASK SET, CLEAR ACA,

LOGICAL UNIT RESET, QUERY TASK, QUERY TASK SET, and QUERY ASYNCHRONOUS EVENT) and is reserved in all others.

6.3.2 Referenced Task Tag

Knight, et al.
 Internet-Draft

Expires January, 2014
 iSCSI SCSI Features Update

Page 14
 July 13

The Initiator Task Tag of the task to be aborted for the ABORT TASK function, reassigned for the TASK REASSIGN function, or queried for the QUERY TASK function. For all other functions this field MUST be set to the reserved value 0xffffffff.

6.3.3 RefCmdSN

If a QUERY TASK is issued for a task created by an immediate command then RefCmdSN MUST be that of the Task Management request itself (i.e., CmdSN and RefCmdSN are equal).

For a QUERY TASK of a task created by non-immediate command RefCmdSN MUST be set to the CmdSN of the task identified by the Referenced Task Tag field. Targets must use this field as described in [section 11.6.1](#) of [RFC-cons] when the task identified by the Referenced Task Tag field is not in the task set.

 RFC EDITORS NOTE: The above references to [RFC-cons] should reference the RFC number assigned to [[draft-ietf-storm-iscsi-cons-xx](#)], and this note should be removed.


Knight, et al.
 Internet-Draft

Expires January, 2014
 iSCSI SCSI Features Update

Page 15
 July 13

6.4 Task Management Function Responses

6.4.1 Task Management Function Response PDU




```

4|TotalAHSLength | DataSegmentLength |
+-----+-----+-----+-----+
8| Additional Response Information | Reserved |
+-----+-----+-----+-----+
12| Reserved |
+-----+-----+-----+-----+
16| Initiator Task Tag |
+-----+-----+-----+-----+
20| Reserved |
+-----+-----+-----+-----+
24| StatSN |
+-----+-----+-----+-----+
28| ExpCmdSN |
+-----+-----+-----+-----+
32| MaxCmdSN |
+-----+-----+-----+-----+
36/ Reserved /
+ / /
+-----+-----+-----+-----+
48| Header-Digest (Optional) |
+-----+-----+-----+-----+

```

[Section 11.6](#) of [RFC-cons] defines the semantics used for responses to SCSI Task Management Functions. The following responses are defined in [RFC-cons]:

- 0 - Function Complete.
- 1 - Task does not exist.
- 2 - LUN does not exist.
- 3 - Task still allegiant.
- 4 - Task allegiance reassignment not supported.
- 5 - Task management function not supported.
- 6 - Function authorization failed.
- 255 - Function rejected.

The Task Management Function Response PDU above and the list of task management function responses above are duplicated from [RFC-cons] for reference only. [RFC-cons] supersedes the text in [section 6.4.1](#) of this document in the event the two documents conflict.

```

-----
RFC EDITORS NOTE: The above references to [RFC-cons] should
reference the RFC number assigned to [draft-ietf-storm-iscsi-
cons-xx], and this note should be removed.
-----

```

Responses to new task management functions (see 6.4.2) are listed below. In addition, a new task Management response is listed below. For a more detailed description of SCSI task management responses, see [[SAM5](#)].

For the functions QUERY TASK, QUERY TASK SET, I_T NEXUS RESET, and QUERY ASYNCHRONOUS EVENT, the target performs the requested Task Management function and sends a Task Management response back to the initiator.

6.4.2 Task Management Function Response Additions

The new response is listed below:

7 - Function succeeded.

In symbolic terms Response value 7 maps to the SCSI service response of FUNCTION SUCCEEDED in [[SAM5](#)].

The task management function response of "Function succeeded" MUST be supported by an initiator that sends any of the new task management functions (see 6.3).

For the QUERY TASK function, if the specified task is in the task set, then the logical unit returns a Response value of Function succeeded and additional response information is returned as specified in [[SAM5](#)]. If the specified task is not in the task set, then the logical unit returns a Response value of Function complete.

For the QUERY TASK SET function, if there is any command present in the task set from the specified I_T_L nexus, then the logical unit returns a Response value of Function succeeded. If there are no commands present in the task set from the specified I_T_L nexus, then the logical unit returns a Response value of Function complete.

For the I_T NEXUS RESET function, after completion of the events described in [section 6.3](#) for this function, the logical unit returns a Response value of Function complete. However, because the target drops all connections, the Service Response (defined by [[SAM5](#)]) for this SCSI task management function may not be reliably delivered to the issuing initiator port.

For the QUERY ASYNCHRONOUS EVENT, if there is a unit attention condition or deferred error pending for the specified I_T_L

nexus, then the logical unit returns a Response value of Function

succeeded and additional response information is returned as specified in [SAM5]. If there is no unit attention or deferred error pending for the specified I_T_L nexus then the logical unit returns a Response value of Function complete.

6.5 Task Management Requests Affecting Multiple Tasks

[Section 4.1 of \[RFC5048\]](#) defines the notion of "affected tasks" in multi-task abort scenarios. This section adds to the list include in that section by defining the tasks affected by the I_T NEXUS RESET function.

I_T NEXUS RESET: All outstanding tasks received on the I_T nexus on which the function request was received for all logical units accessible to the I_T nexus.

[Section 4.1.2 of \[RFC5048\]](#) and [section 4.1.3 of \[RFC5048\]](#) identify semantics for task management functions that involve multi-task abort operations. If an iSCSI implementation supports the I_T NEXUS RESET function, it MUST also support the protocol behavior as defined in those sections and follow the sequence of actions as described in those sections when processing the I_T NEXUS RESET function.

7. Login/Text Operational Text Keys

7.1 New Operational Text Keys

7.1.1 iSCSIProtocolLevel

Use: L0, IO

Irrelevant when: SessionType = Discovery

Senders: Initiator and Target

Scope: SW

iSCSIProtocolLevel=<numerical-value-from-0-to-31>

Default is 1.

Result function is Minimum.

This key is used to negotiate the use of iSCSI features that require different levels of protocol support (e.g., PDU formats, end node semantics) for proper operation.

Negotiation of the iSCSIProtocolLevel key to a value corresponding to an RFC indicates that both negotiating parties are compliant to the RFC in question, and agree to support the corresponding PDU formats and semantics on that iSCSI session. Features using this key are expected to be cumulative.

An `iSCSIProtocolLevel` key negotiated to "0" indicates that the implementation does not claim a specific iSCSI protocol level.

An `iSCSIProtocolLevel` key negotiated to "1" indicates that the implementation claims compliance with [RFC-cons].

RFC EDITORS NOTE: The above reference to [RFC-cons] should reference the RFC number assigned to [[draft-ietf-storm-iscsi-cons-xx](#)], and this note should be removed.

An `iSCSIProtocolLevel` key negotiated to "2" is required to enable use of features defined in this RFC.

If the negotiation answer is ignored by the acceptor, or the answer from the remote iSCSI end point is `key=NotUnderstood`, then the features defined in this RFC, and the features defined in any RFC requiring a key value greater than "2" MUST NOT be used.

8. Security Considerations

Command priorities are relative values, not absolute values (see [SAM5] and affect collections of commands, not necessarily individual commands (see [SAM5]); if command priority is supported, it should be implemented in a fashion that avoids unwanted reduction or denial of service.

All the iSCSI-related security text in [RFC3723] and the security text in [RFC-cons] is also directly applicable to this document.

RFC EDITORS NOTE: The above reference to [RFC-cons] should reference the RFC number assigned to [[draft-ietf-storm-iscsi-cons-xx](#)], and this note should be removed.

9. IANA Considerations

This document modifies or creates a number of iSCSI-related registries. The following iSCSI-related registries are modified:

1. iSCSI Task Management Functions Codes

Name of the existing registry: "iSCSI TMF Codes"

The name of this registry should be changed to: "iSCSI Task

Management Function Codes".

Additional entries:

Knight, et al.	Expires January, 2014	Page 19
Internet-Draft	iSCSI SCSI Features Update	July 13

9, QUERY TASK, [RFCxxx]

10, QUERY TASK SET, [RFCxxx]

11, I_T NEXUS RESET, [RFCxxx]

12, QUERY ASYNCHRONOUS EVENT, [RFCxxx]

RFC EDITORS NOTE: The above reference to [RFCxxx] should
reference this RFC, and this note should be removed.

2. iSCSI Login/Text Keys

Name of the existing registry: "iSCSI Text Keys"

Fields to record in the registry: Assigned value and its
associated RFC reference:

iSCSIProtocolLevel, [RFCxxx]

RFC EDITORS NOTE: The above references to [RFCxxx] should
reference this RFC, and this note should be removed.

This document creates the following iSCSI-related registries for
IANA to manage.

3. iSCSI Protocol Level

Name of new registry: "iSCSI Protocol Level"

Namespace details: Numerical values from 0 to 31

Information that must be provided to assign a new value: An
IESG-approved standards track specification defining the
semantics and interoperability requirements of the proposed
new value and the fields to be recorded in the registry.

Assignment policy:

The assignments of these values must be coordinated with the

INCITS T10 committee; therefore review by an expert that maintains an association with that committee is required prior to IESG approval of the associated specification. After creation of the registry, values are to be assigned sequentially (for example, any value greater than 4 will not be assigned until after the value 4 has been assigned).

Knight, et al.
Internet-Draft

Expires January, 2014
iSCSI SCSI Features Update

Page 20
July 13

Special care must be taken in the assignment of new values in this registry. Compatibility and interoperability will be adversely impacted if proper care is not exercised. Features using this key are expected to be cumulative. For example, since this draft explicitly lists only value 2 for the features listed in this draft, it is expected that a new RFC assigning value 3 will also have the features listed in this RFC and therefore such an RFC is expected to either revise or replace this RFC. Assignments that do not follow this policy should be reviewed and approved by the INCITS T10 committee.

3-31: range reserved by IANA for assignment in this registry.

Fields to record in the registry: Assigned value, description, and its associated RFC reference.

0, No version claimed, [RFCxxx]

1, RFC-cons, [RFCxxx]

2, RFCxxx, [RFCxxx]

RFC EDITORS NOTE: The above references to [RFCxxx] should reference this RFC, and this note should be removed. The above reference to RFC-cons should be replaced with the name of the [[draft-ietf-storm-iscsi-cons-xx](#)] document, and this note should be removed. All associated RFC references are to this document; even the reference for value 1. The description for value 1 however contains the RFC-cons name but should not have [] around the description (it is a description not a formal reference). The description for value 2 is the name of this RFC but should not contain the [] (again, a description not a formal reference). This note should be removed.

Allocation Policy:

Expert review ([\[IANA\]](#)) and Standards Action ([\[IANA\]](#))

4. iSCSI Task Management Response Codes

Name of new registry: "iSCSI Task Management Function Response Codes"

Namespace details: Numerical values that can fit in 8 bits.

Information that must be provided to assign a new value: An IESG-approved specification defining the semantics and interoperability requirements of the proposed new value and the fields to be recorded in the registry.

Knight, et al.
Internet-Draft

Expires January, 2014
iSCSI SCSI Features Update

Page 21
July 13

Assignment policy:

If the requested value is not already assigned, it may be assigned to the requester.

8-254: Range reserved by IANA for assignment in this registry.

Fields to record in the registry: Assigned value, Operation Name, and its associated RFC reference.

0x0, Function complete, [RFC-cons]

0x1, Task does not exist, [RFC-cons]

0x2, LUN does not exist, [RFC-cons]

0x3, Task still allegiant, [RFC-cons]

0x4, Task allegiance reassignment not supported, [RFC-cons]

0x5, Task management function not supported, [RFC-cons]

0x6, Function authorization failed, [RFC-cons]

0x7, Function succeeded, [RFCxxx]

255, Function rejected, [RFC-cons]

RFC EDITORS NOTE: The above reference to [RFCxxx] should reference this RFC, and this note should be removed.

The above references to [RFC-cons] should reference the [\[draft-ietf-storm-iscsi-cons-xx\]](#) document, and this note

should be removed.

Allocation Policy:

Standards Action ([[IANA](#)])

10. References

10.1 Normative References

[RFC2119] Bradner, S. "Key Words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

[RFC3723] Aboba, B., Tseng, J., Walker, J., Rangan, V., and Travostino, F., "Securing Block Storage Protocols over IP", [RFC 3723](#), April 2004.

Knight, et al.	Expires January, 2014	Page 22
Internet-Draft	iSCSI SCSI Features Update	July 13

[RFC5048] Chadalapaka, M., "Internet Small Computer System Interface (iSCSI) Corrections and Clarifications", [RFC 5048](#), October 2007.

[[draft-ietf-storm-iscsi-cons-xx](#)] Chadalapaka, M., Satran, J., Kalman, M., "iSCSI Protocol (consolidated)", RFC xxx, Date 2013.

RFC EDITORS NOTE: The above references to [[draft-ietf-storm-iscsi-cons-xx](#)] and RFC xxx should reference the RFC number assigned to that draft, and this note should be removed.

[IANA] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 5226](#), May 2008.

[SAM2] T10/1157D, SCSI Architecture Model - 2 (SAM-2).

[SAM5] T10/2104D rev r04, SCSI Architecture Model - 5 (SAM-5), Committee Draft.

[SPC4] T10/1731D rev r36, SCSI Primary Commands - 4 (SPC-4), Committee Draft.

10.2 Informative References

[RFC3720] Satran, J., Meth, K., Sapuntzakis, C., Chadalapaka, M., and E. Zeidner, "Internet Small Computer Systems

Interface (iSCSI)", [RFC 3720](#), April 2004.

10.3 Additional Reference Sources

For more information on the SCSI Architecture Model and SCSI Primary Commands - 4, contact the INCITS T10 Technical Committee for SCSI Storage Interfaces at <http://www.t10.org>.

11. Acknowledgements

The Storage Maintenance (STORM) Working Group in the Transport Area of the IETF has been responsible for defining these additions to the iSCSI protocol (apart from other relevant IP Storage protocols). The editor acknowledges the contributions of the entire working group and other IETF reviewers. The following individuals directly contributed to identifying [RFCxxx] issues and/or suggesting resolutions to the issues clarified in this document: David Black, Rob Elliott. This document benefited from all of these contributions.

Knight, et al.	Expires January, 2014	Page 23
Internet-Draft	iSCSI SCSI Features Update	July 13

RFC EDITORS NOTE: The above reference to [RFCxxx] should reference this RFC, and this note should be removed.

Author's Addresses:
Frederick Knight
7301 Kit Creek Road
P.O. Box 13917
Research Triangle Park, NC 27709, USA
Phone: +1-919-476-5362
Email: knight@netapp.com

Mallikarjun Chadalapaka
Microsoft
One Microsoft Way
Redmond, WA 98052 USA
Email: cbm@chadalapaka.com

Knight, et al. Expires January, 2014 Page 24