

Network Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: January 2, 2014

P. Saint-Andre  
Cisco Systems, Inc.  
S. Loreto  
E. Gavita  
N. Hossain  
Ericsson  
July 1, 2013

## **Interworking between the Session Initiation Protocol (SIP) and the Extensible Messaging and Presence Protocol (XMPP): One-to-One Text Chat**

[\*\*draft-ietf-stox-chat-00\*\*](#)

## Abstract

This document defines a bidirectional protocol mapping for the exchange of instant messages in the context of a one-to-one chat session between a user of the Session Initiation Protocol (SIP) and a user of the Extensible Messaging and Presence Protocol (XMPP). Specifically for SIP text chat, this document specifies a mapping to the Message Session Relay Protocol (MSRP).

### Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 2, 2014.

## Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents

carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	<a href="#">Introduction</a>	<a href="#">3</a>
<a href="#">2.</a>	<a href="#">Terminology</a>	<a href="#">3</a>
<a href="#">3.</a>	<a href="#">XMPP to MSRP</a>	<a href="#">4</a>
<a href="#">4.</a>	<a href="#">MSRP to XMPP</a>	<a href="#">7</a>
<a href="#">5.</a>	<a href="#">Security Considerations</a>	<a href="#">10</a>
<a href="#">6.</a>	<a href="#">IANA Considerations</a>	<a href="#">11</a>
<a href="#">7.</a>	<a href="#">References</a>	<a href="#">11</a>
<a href="#">7.1.</a>	<a href="#">Normative References</a>	<a href="#">11</a>
<a href="#">7.2.</a>	<a href="#">Informative References</a>	<a href="#">12</a>
	<a href="#">Appendix A. Acknowledgements</a>	<a href="#">12</a>
	<a href="#">Authors' Addresses</a>	<a href="#">12</a>



## [1. Introduction](#)

Both the Session Initiation Protocol [[RFC3261](#)] and the Extensible Messaging and Presence Protocol [[RFC6120](#)] can be used for the purpose of one-to-one text chat over the Internet. To ensure interworking between these technologies, it is important to define bidirectional protocol mappings.

The architectural assumptions underlying such protocol mappings are provided in [[I-D.ietf-stox-core](#)], including mapping of addresses and error conditions. This document specifies mappings for one-to-one text chat sessions (sometimes called "session-mode" messaging); in particular, this document specifies mappings between XMPP messages of type "chat" and the Message Session Relay Protocol [[RFC4975](#)]. Mappings for single instant messages and groupchat are provided in separate documents.

The approach taken here is to directly map syntax and semantics from one protocol to another. The mapping described herein depends on the protocols defined in the following specifications:

- o XMPP chat sessions using message stanzas of type "chat" are specified in [[RFC6121](#)].
- o SIP-based chat sessions using the SIP INVITE and SEND request types are specified in [[RFC4975](#)].

In SIMPLE, a chat session is formally negotiated just as any other session type is using SIP. By contrast, a one-to-one chat "session" in XMPP is an informal construct and is not formally negotiated: a user simply sends a message of type "chat" to a contact, the contact then replies to the message, and the sum total of such messages exchanged during a defined period of time is considered to be a chat session. To overcome the disparity between these approaches, a gateway that wishes to map between SIP and XMPP for one-to-one chat sessions needs to maintain some additional state, as described below.

The discussion venue for this document is the mailing list of the STOX WG; visit <https://www.ietf.org/mailman/listinfo/stox> for subscription information and discussion archives.

## [2. Terminology](#)

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

Saint-Andre, et al.


Expires January 2, 2014

[Page 3]

### 3. XMPP to MSRP

In XMPP, the "informal session" approach is to simply send someone a <message/> of type "chat" without starting any session negotiation ahead of time (as described in [[RFC6121](#)]). The XMPP "informal session" approach maps very well into a SIP MESSAGE request, as described in [[I-D.ietf-stox-core](#)]. However, the XMPP informal session approach can also be mapped to MSRP if the XMPP-to-SIP gateway maintains additional state.

The order of events is as follows.



First the XMPP user would generate an XMPP chat message.

Saint-Andre, et al.

Expires January 2, 2014

[Page 4]

Example: (F1) Juliet sends an XMPP message

```
<message from='juliet@example.com/balcony'
      to='romeo@example.net'
      type='chat'>
<thread>711609sa</thread>
<body>Art thou not Romeo, and a Montague?</body>
</message>
```

The local SIP-to-XMPP gateway at the SIMPLE server would then determine if Romeo supports MSRP. If so, the SIP-to-XMPP gateway would initiate an MSRP session with Romeo on Juliet's behalf.

Example: (F2) Gateway starts a formal session on behalf of Juliet

```
INVITE sip:romeo@example.net SIP/2.0
To: <sip:romeo@example.net>
From: <sip:juliet@example.com>
Contact: <sip:juliet@example.com>;gr=balcony
Subject: Open chat with Juliet?
Call-ID: 711609sa
Content-Type: application/sdp

c=IN IP4 x2s.example.com
m=message 7654 TCP/MSRP *
a=accept-types:text/plain
a=lang:en
a=lang:it
a=path:msrp://x2s.example.com:7654/jshA7weztas;tcp
```

Here we assume that Romeo accepts the MSRP session request.

Example: (F3) Romeo accepts the request

```
SIP/2.0 200 OK
To: <sip:juliet@example.com>;gr=balcony
From: <sip:romeo@example.net>
Contact: <sip:romeo@example.net>;gr=orchard
Call-ID: 711609sa
Content-Type: application/sdp

c=IN IP4 s2x.example.net
m=message 12763 TCP/MSRP *
a=accept-types:text/plain
a=lang:it
a=path:msrp://s2x.example.net:12763/kjhd37s2s20w2a;tcp
```

The XMPP-to-SIP gateway then acknowledges the session acceptance on

Saint-Andre, et al.

Expires January 2, 2014

[Page 5]

behalf of Romeo.

Example: (F4) Gateway sends ACK to Romeo's UA

```
ACK sip:juliet@example.com SIP/2.0
To: <sip:romeo@example.net>;gr=orchard
From: <sip:juliet@example.com>
Contact: <sip:juliet@example.com>;gr=balcony
Call-ID: 711609sa
```

The XMPP-to-SIP gateway then transforms the original XMPP chat message into MSRP.

Example: (F5) Gateway transforms XMPP message to MSRP

```
MSRP a786hjs2 SEND
From-Path: msrp://x2s.example.com:7654/jshA7weztas;tcp
To-Path: msrp://s2x.example.net:12763/kjhd37s2s20w2a;tcp
Message-ID: 87652491
Byte-Range: 1-25/25
Content-Type: text/plain
```

```
Art thou not Romeo, and a Montague?
-----a786hjs2$
```

Romeo can then send a reply using his MSRP user agent.

Example: (F6) Romeo sends a reply

```
MSRP a786hjs2 SEND
To-Path: msrp://x2s.example.com:7654/jshA7weztas;tcp
From-Path: msrp://s2x.example.net:12763/kjhd37s2s20w2a;tcp
Message-ID: 87652491
Byte-Range: 1-25/25
Failure-Report: no
Content-Type: text/plain
```

```
Neither, fair saint, if either thee dislike.
-----a786hjs2$
```

The SIP-to-XMPP gateway would then transform that message into appropriate XMPP syntax for routing to the intended recipient.



Example: (F7) Gateway transforms MSRP message to XMPP

```
<message from='romeo@example.net/orchard'
          to='juliet@example.com/balcony'
          type='chat'>
  <thread>711609sa</thread>
  <body>Neither, fair saint, if either thee dislike.</body>
</message>
```

When the MSRP user wishes to end the chat session, the user's MSRP client sends a SIP BYE.

Example: (F8) Romeo terminates the chat session

```
BYE juliet@example.com sip: SIP/2.0
Max-Forwards: 70
From: <sip:romeo@example.net>;tag=087js
To: <sip:juliet@example.com>;tag=786
Call-ID: 711609sa
Cseq: 1 BYE
Content-Length: 0
```

The BYE is then acknowledged by the XMPP-to-SIP gateway.

Example: (F9) Gateway acknowledges termination

```
SIP/2.0 200 OK
From: <sip:juliet@example.com>;tag=786
To: <sip:romeo@example.net>;tag=087js
Call-ID: 711609sa
CSeq: 1 BYE
Content-Length: 0
```

#### 4. MSRP to XMPP

When an MSRP client sends messages through a gateway to an XMPP client that does not support formal sessions, the order of events is as follows.





Example: (F1) SIP user starts the session

```

INVITE sip:juliet@example.com SIP/2.0
To: <sip:juliet@example.com>
From: <sip:romeo@example.net>
Contact: <sip:romeo@example.net>;gr=orchard
Subject: Open chat with Romeo?
Call-ID: 742507no
Content-Type: application/sdp

```

```

c=IN IP4 s2x.example.net
m=message 7313 TCP/MSRP *
a=accept-types:text/plain
a=lang:en
a=lang:it
a=path:msrp://s2x.example.net:7313/ansp71weztas;tcp

```

Saint-Andre, et al.

Expires January 2, 2014

[Page 8]

Example: (F2) Gateway accepts session on Juliet's behalf

```
SIP/2.0 200 OK
To: <sip:romeo@example.net>;gr=orchard
From: <sip:juliet@example.com>
Contact: <sip:juliet@example.com>;gr=balcony
Call-ID: 742507no
Content-Type: application/sdp

c=IN IP4 x2s.example.com
m=message 8763 TCP/MSRP *
a=accept-types:text/plain
a=lang:it
a=path:msrp://x2s.example.com:8763/1kjh37s2s20w2a;tcp
```

Example: (F3) Romeo sends ACK

```
ACK sip:juliet@example.com SIP/2.0
To: <sip:juliet@example.com>;gr=balcony
From: <sip:romeo@example.net>
Contact: <sip:romeo@example.net>;gr=orchard
Call-ID: 742507no
```

Example: (F4) Romeo sends a message

```
MSRP ad49kswow SEND
To-Path: msrp://x2s.example.com:8763/1kjh37s2s20w2a;tcp
From-Path: msrp://s2x.example.net:7313/ansp71weztas;tcp
Message-ID: 44921zaqwsx
Byte-Range: 1-32/32
Failure-Report: no
Content-Type: text/plain
```

I take thee at thy word ...

-----ad49kswow\$

Example: (F5) Romeo sends a message (XMPP translation)

```
<message from='romeo@example.net'
          to='juliet@example.com'
          type='chat'>
  <thread>742507no</thread>
  <body>I take thee at thy word ...</body>
</message>
```

Saint-Andre, et al.

Expires January 2, 2014

[Page 9]

Example: (F6) Juliet sends a reply

```
<message from='juliet@example.com'  
         to='romeo@example.net'  
         type='chat'>  
<thread>711609sa</thread>  
<body>What man art thou ...?</body>  
</message>
```

Example: (F8) Gateway transforms XMPP message to MSRP

```
MSRP a786hjs2 SEND  
To-Path: msrp://s2x.example.net:7313/jshA7weztas;tcp  
From-Path: msrp://x2s.example.com:8763/lkj37s2s20w2a;tcp  
Message-ID: 87652491  
Byte-Range: 1-25/25  
Failure-Report: no  
Content-Type: text/plain  
  
What man art thou ...?  
-----a786hjs2$
```

Example: (F9) Romeo terminates the session

```
BYE juliet@example.com sip: SIP/2.0  
Max-Forwards: 70  
To: <sip:juliet@example.com>;gr=balcony  
From: <sip:romeo@example.net>  
Contact: <sip:romeo@example.net>;gr=orchard  
Call-ID: 742507no  
Cseq: 1 BYE  
Content-Length: 0
```

Example: (F10) Gateway acknowledges the termination of the session on behalf of XMPP user

```
SIP/2.0 200 OK  
To: <sip:juliet@example.com>;gr=balcony  
From: <sip:romeo@example.net>  
Contact: <sip:romeo@example.net>;gr=orchard  
Call-ID: 742507no  
CSeq: 1 BYE
```

## 5. Security Considerations

Detailed security considerations for instant messaging protocols are given in [[RFC2779](#)], for SIP-based instant messaging in [[RFC3428](#)] (see

Saint-Andre, et al.

Expires January 2, 2014

[Page 10]

also [[RFC3261](#)]), and for XMPP-based instant messaging in [[RFC6121](#)] (see also [[RFC6120](#)]).

This document specifies methods for exchanging instant messages through a gateway that translates between SIP and XMPP. Such a gateway MUST be compliant with the minimum security requirements of the instant messaging protocols for which it translates (i.e., SIP and XMPP). The addition of gateways to the security model of instant messaging specified in [[RFC2779](#)] introduces some new risks. In particular, end-to-end security properties (especially confidentiality and integrity) between instant messaging user agents that interface through a SIMPLE-XMPP gateway can be provided only if common formats are supported. Specification of those common formats is out of scope for this document, although it is recommended to use [[RFC3862](#)] for instant messages.

## [6. IANA Considerations](#)

This document requests no actions of IANA.

## [7. References](#)

### [7.1. Normative References](#)

- [I-D.ietf-stox-core]  
Saint-Andre, P., Houry, A., and J. Hildebrand, "Interworking between the Session Initiation Protocol (SIP) and the Extensible Messaging and Presence Protocol (XMPP): Core", [draft-ietf-stox-core-00](#) (work in progress), July 2013.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC3261] Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M., and E. Schooler, "SIP: Session Initiation Protocol", [RFC 3261](#), June 2002.
- [RFC3862] Klyne, G. and D. Atkins, "Common Presence and Instant Messaging (CPIM): Message Format", [RFC 3862](#), August 2004.
- [RFC4975] Campbell, B., Mahy, R., and C. Jennings, "The Message Session Relay Protocol (MSRP)", [RFC 4975](#), September 2007.
- [RFC6120] Saint-Andre, P., "Extensible Messaging and Presence

Saint-Andre, et al.

Expires January 2, 2014

[Page 11]

Protocol (XMPP): Core", [RFC 6120](#), March 2011.

- [RFC6121] Saint-Andre, P., "Extensible Messaging and Presence Protocol (XMPP): Instant Messaging and Presence", [RFC 6121](#), March 2011.

## **7.2. Informative References**

- [RFC2779] Day, M., Aggarwal, S., and J. Vincent, "Instant Messaging / Presence Protocol Requirements", [RFC 2779](#), February 2000.
- [RFC3428] Campbell, B., Rosenberg, J., Schulzrinne, H., Huitema, C., and D. Gurle, "Session Initiation Protocol (SIP) Extension for Instant Messaging", [RFC 3428](#), December 2002.

## **Appendix A. Acknowledgements**

Some text in this document was borrowed from [[I-D.ietf-stox-core](#)].

Thanks to Adrian Georgescu, Saul Ibarra, and Tory Patnoe for their feedback.

## Authors' Addresses

Peter Saint-Andre  
Cisco Systems, Inc.  
1899 Wynkoop Street, Suite 600  
Denver, CO 80202  
USA

Phone: +1-303-308-3282  
Email: [psaintan@cisco.com](mailto:psaintan@cisco.com)

Salvatore Loreto  
Ericsson  
Hirsalantie 11  
Jorvas 02420  
Finland

Email: [Salvatore.Loreto@ericsson.com](mailto:Salvatore.Loreto@ericsson.com)



Eddy Gavita  
Ericsson  
Decarie Boulevard  
Town of Mount Royal, Quebec  
Canada

Email: [eddy.gavita@ericsson.com](mailto:eddy.gavita@ericsson.com)

Nazin Hossain  
Ericsson  
Decarie Boulevard  
Town of Mount Royal, Quebec  
Canada

Email: [Nazin.Hossain@ericsson.com](mailto:Nazin.Hossain@ericsson.com)

