

Network Working Group
Internet-Draft
Obsoletes: [1323](#)
Intended Status: Standards Track
File: [draft-ietf-tcpm-1323bis-01.txt](#)

Network Working Group
D. Borman
Wind River Systems
R. Braden
ISI
V. Jacobson
Packet Design
March 4, 2009

TCP Extensions for High Performance

Status of This Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on September 4, 2009.

Copyright

Copyright (c) 2009 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents in effect on the date of publication of this document (<http://trustee.ietf.org/license-info>). Please review these documents carefully, as they describe your rights and restrictions with respect to this document.

Abstract

This memo presents a set of TCP extensions to improve performance over large bandwidth*delay product paths and to provide reliable operation over very high-speed paths. It defines TCP options for scaled windows and timestamps, which are designed to provide compatible interworking with TCP's that do not implement the extensions. The timestamps are used for two distinct mechanisms: RTTM (Round Trip Time Measurement) and PAWS (Protection Against Wrapped Sequences). Selective acknowledgments are not included in this memo.

This memo updates and obsoletes [RFC 1323](#).

TABLE OF CONTENTS

1. Introduction	2
2. TCP Window Scale Option	9
3. RTTM -- Round-Trip Time Measurement	12
4. PAWS -- Protection Against Wrapped Sequence Numbers	18
5. Conclusions and Acknowledgments	26
6. Security Considerations	27
7. IANA Considerations	27
8. References	27
APPENDIX A: Implementation Suggestions	30
APPENDIX B: Duplicates from Earlier Connection Incarnations	31
APPENDIX C: Changes from RFC 1072 , RFC 1185 , RFC 1323	34
APPENDIX D: Summary of Notation	36
APPENDIX E: Pseudo-code Summary	37
APPENDIX F: Event Processing	40
APPENDIX G: Timestamps Edge Cases	46
Authors' Addresses	47

1. INTRODUCTION

The TCP protocol [[Postel81](#)] was designed to operate reliably over

almost any transmission medium regardless of transmission rate, delay, corruption, duplication, or reordering of segments. Production TCP implementations currently adapt to transfer rates in the range of 100 bps to 10^{10} bps and round-trip delays in the range 1 ms to 100 seconds. Work on TCP performance has shown that TCP without the extensions described in this memo can work well over a variety of Internet paths, ranging from 800 Mbit/sec I/O channels to 300 bit/sec dial-up modems [[Jacobson88a](#)].

Over the years, advances in networking technology has resulted in ever-higher transmission speeds, and the fastest paths are well beyond the domain for which TCP was originally engineered. This memo defines a set of modest extensions to TCP to extend the domain of its application to match this increasing network capability. It is an update to and obsoletes [RFC 1323](#) [[Jacobson92d](#)], which in turn is based upon and obsoletes [RFC 1072](#) [[Jacobson88b](#)] and [RFC 1185](#) [[Jacobson90b](#)].

There is no one-line answer to the question: "How fast can TCP go?". There are two separate kinds of issues, performance and reliability, and each depends upon different parameters. We discuss each in turn.

1.1 TCP Performance

TCP performance depends not upon the transfer rate itself, but rather upon the product of the transfer rate and the round-trip delay. This "bandwidth*delay product" measures the amount of data that would "fill the pipe"; it is the buffer space required at sender and receiver to obtain maximum throughput on the TCP connection over the path, i.e., the amount of unacknowledged data that TCP must handle in order to keep the pipeline full. TCP performance problems arise when the bandwidth*delay product is large. We refer to an Internet path operating in this region as a "long, fat pipe", and a network containing this path as an "LFN" (pronounced "elephan(t)").

High-capacity packet satellite channels are LFN's. For example, a DS1-speed satellite channel has a bandwidth*delay product of 10^6 bits or more; this corresponds to 100 outstanding TCP segments of 1200 bytes each. Terrestrial fiber-optical paths will also fall into the LFN class; for example, a cross-country delay of 30 ms at a DS3 bandwidth (45Mbps) also exceeds 10^6 bits.

There are three fundamental performance problems with the current TCP over LFN paths:

(1) Window Size Limit

The TCP header uses a 16 bit field to report the receive

window size to the sender. Therefore, the largest window

that can be used is $2^{16} = 65K$ bytes.

To circumvent this problem, [Section 2](#) of this memo defines a new TCP option, "Window Scale", to allow windows larger than 2^{16} . This option defines an implicit scale factor, which is used to multiply the window size value found in a TCP header to obtain the true window size.

(2) Recovery from Losses

Packet losses in an LFN can have a catastrophic effect on throughput. In the past, properly-operating TCP implementations would cause the data pipeline to drain with every packet loss, and require a slow-start action to recover. The Fast Retransmit and Fast Recovery algorithms [[Jacobson90c](#)] [[Allman99](#)] were introduced, and their combined effect was to recover from one packet loss per window, without draining the pipeline. However, more than one packet loss per window typically resulted in a retransmission timeout and the resulting pipeline drain and slow start.

Expanding the window size to match the capacity of an LFN results in a corresponding increase of the probability of more than one packet per window being dropped. This could have a devastating effect upon the throughput of TCP over an LFN. In addition, since the publication of [RFC 1323](#), congestion control mechanism based upon some form of random dropping have been introduced into gateways, and randomly spaced packet drops have become common; this increases the probability of dropping more than one packet per window.

To generalize the Fast Retransmit/Fast Recovery mechanism to handle multiple packets dropped per window, selective acknowledgments are required. Unlike the normal cumulative acknowledgments of TCP, selective acknowledgments give the sender a complete picture of which segments are queued at the receiver and which have not yet arrived.

Since the publication of [RFC 1323](#), selective acknowledgments have become important in the LFN regime. [RFC 1072](#) defined a new TCP "SACK" option to send a selective acknowledgment, but at the time that [RFC 1323](#) was published, important technical issues still had to be worked out concerning both the format and semantics of the SACK option, so it was split off from [RFC 1323](#). SACK has now been published as a separate document, [RFC 2018](#) [[Mathis96](#)]. Additional information about SACK can be found in [RFC 2883](#), "An Extension to the Selective Acknowledgement (SACK) option for TCP" [[Floyd00](#)] and [RFC](#)

[3517](#), "A Conservative Selective Acknowledgment (SACK)-based Loss Recovery Algorithm for TCP" [[Blanton03](#)].

(3) Round-Trip Measurement

TCP implements reliable data delivery by retransmitting segments that are not acknowledged within some retransmission timeout (RTO) interval. Accurate dynamic determination of an appropriate RTO is essential to TCP performance. RTO is determined by estimating the mean and variance of the measured round-trip time (RTT), i.e., the time interval between sending a segment and receiving an acknowledgment for it [[Jacobson88a](#)].

[Section 4](#) introduces a new TCP option, "Timestamps", and then defines a mechanism using this option that allows nearly every segment, including retransmissions, to be timed at negligible computational cost. We use the mnemonic RTTM (Round Trip Time Measurement) for this mechanism, to distinguish it from other uses of the Timestamps option.

1.2 TCP Reliability

Now we turn from performance to reliability. High transfer rate enters TCP performance through the bandwidth*delay product. However, high transfer rate alone can threaten TCP reliability by violating the assumptions behind the TCP mechanism for duplicate detection and sequencing.

An especially serious kind of error may result from an accidental reuse of TCP sequence numbers in data segments. Suppose that an "old duplicate segment", e.g., a duplicate data segment that was delayed in Internet queues, is delivered to the receiver at the wrong moment, so that its sequence numbers falls somewhere within the current window. There would be no checksum failure to warn of the error, and the result could be an undetected corruption of the data. Reception of an old duplicate ACK segment at the transmitter could be only slightly less serious: it is likely to lock up the connection so that no further progress can be made, forcing an RST on the connection.

TCP reliability depends upon the existence of a bound on the lifetime of a segment: the "Maximum Segment Lifetime" or MSL. An MSL is generally required by any reliable transport protocol, since every sequence number field must be finite, and therefore any sequence number may eventually be reused. In the Internet protocol suite, the MSL bound is enforced by an IP-layer mechanism, the "Time-to-Live" or TTL field.

Duplication of sequence numbers might happen in either of two ways:

(1) Sequence number wrap-around on the current connection

A TCP sequence number contains 32 bits. At a high enough transfer rate, the 32-bit sequence space may be "wrapped" (cycled) within the time that a segment is delayed in queues.

(2) Earlier incarnation of the connection

Suppose that a connection terminates, either by a proper close sequence or due to a host crash, and the same connection (i.e., using the same pair of sockets) is immediately reopened. A delayed segment from the terminated connection could fall within the current window for the new incarnation and be accepted as valid.

Duplicates from earlier incarnations, Case (2), are avoided by enforcing the current fixed MSL of the TCP spec, as explained in [Section 5.3](#) and [Appendix B](#). However, case (1), avoiding the reuse of sequence numbers within the same connection, requires an MSL bound that depends upon the transfer rate, and at high enough rates, a new mechanism is required.

More specifically, if the maximum effective bandwidth at which TCP is able to transmit over a particular path is B bytes per second, then the following constraint must be satisfied for error-free operation:

$$2^{31} / B > \text{MSL (secs)} \quad [1]$$

The following table shows the value for $T_{\text{wrap}} = 2^{31}/B$ in seconds, for some important values of the bandwidth B:

Network	B*8 bits/sec	B bytes/sec	Twrap secs
Dialup	56kbps	7KBps	$3 \cdot 10^{**5}$ (~3.6 days)
DS1	1.5Mbps	190KBps	10^{**4} (~3 hours)
10mbit Ethernet	10Mbps	1.25MBps	1700 (~30 mins)
DS3	45Mbps	5.6MBps	380
100mbit Ethernet	100Mbps	12.5MBps	170
Gigabit Ethernet	1Gbps	125MBps	17
10GigE	10Gbps	1.25GBps	1.7

It is clear that wrap-around of the sequence space is not a problem for 56kbps packet switching or even 10Mbps Ethernets. On the other hand, at DS3 and 100mbit speeds, Twrap is comparable to the 2 minute MSL assumed by the TCP specification [[Postel81](#)]. Moving towards and beyond gigabit speeds, Twrap becomes too small for reliable enforcement by the Internet TTL mechanism.

The 16-bit window field of TCP limits the effective bandwidth B to $2^{**16}/RTT$, where RTT is the round-trip time in seconds [[McKenzie89](#)]. If the RTT is large enough, this limits B to a value that meets the constraint [1] for a large MSL value. For example, consider a transcontinental backbone with an RTT of 60ms (set by the laws of physics). With the bandwidth*delay product limited to 64KB by the TCP window size, B is then limited to 1.1MBps, no matter how high the theoretical transfer rate of the path. This corresponds to cycling the sequence number space in $Twrap = 2000$ secs, which is safe in today's Internet.

It is important to understand that the culprit is not the larger window but rather the high bandwidth. For example, consider a (very large) FDDI LAN with a diameter of 10km. Using the speed of light, we can compute the RTT across the ring as $(2 \cdot 10^{**4}) / (3 \cdot 10^{**8}) = 67$ microseconds, and the delay*bandwidth product is then 833 bytes. A TCP connection across this LAN using a window of only 833 bytes will run at the full 100mbps and can wrap the sequence space in about 3 minutes, very close to the MSL of TCP. Thus, high speed alone can cause a reliability problem with sequence number wrap-around, even without extended windows.

Watson's Delta-T protocol [[Watson81](#)] includes network-layer mechanisms for precise enforcement of an MSL. In contrast, the IP mechanism for MSL enforcement is loosely defined and even more loosely implemented in the Internet. Therefore, it is unwise to depend upon active enforcement of MSL for TCP connections, and it is unrealistic to imagine setting MSL's smaller than the current values (e.g., 120 seconds specified for TCP).

A possible fix for the problem of cycling the sequence space would be to increase the size of the TCP sequence number field. For example, the sequence number field (and also the acknowledgment field) could be expanded to 64 bits. This could be done either by changing the TCP header or by means of an additional option.

[Section 5](#) presents a different mechanism, which we call PAWS (Protect Against Wrapped Sequence numbers), to extend TCP reliability to transfer rates well beyond the foreseeable upper limit of network bandwidths. PAWS uses the TCP Timestamps option defined in [Section 4](#) to protect against old duplicates from the same connection.

1.3 Using TCP options

The extensions defined in this memo all use new TCP options. We must address two possible issues concerning the use of TCP options: (1) compatibility and (2) overhead.

We must pay careful attention to compatibility, i.e., to interoperation with existing implementations. The only TCP option defined previously, MSS, may appear only on a SYN segment. Every implementation should (and we expect that most will) ignore unknown options on SYN segments. When [RFC 1323](#) was published, there was concern that some buggy TCP implementation might be crashed by the first appearance of an option on a non-SYN segment. However, bugs like that can lead to DOS attacks against a TCP, so it is now expected that most TCP implementations will properly handle unknown options on non-SYN segments. But it is still prudent to be conservative in what you send, and avoiding buggy TCP implementation is not the only reason for negotiating TCP options on SYN segments. Therefore, for each of the extensions defined below, TCP options will be sent on non-SYN segments only after an exchange of options on the SYN segments has indicated that both sides understand the extension. Furthermore, an extension option will be sent in a <SYN,ACK> segment only if the corresponding option was received in the initial <SYN> segment.

A question may be raised about the bandwidth and processing overhead for TCP options. Those options that occur on SYN

segments are not likely to cause a performance concern. Opening a TCP connection requires execution of significant special-case

code, and the processing of options is unlikely to increase that cost significantly.

On the other hand, a Timestamps option may appear in any data or ACK segment, adding 12 bytes to the 20-byte TCP header. We believe that the bandwidth saved by reducing unnecessary retransmissions will more than pay for the extra header bandwidth.

There is also an issue about the processing overhead for parsing the variable byte-aligned format of options, particularly with a RISC-architecture CPU. [Appendix A](#) contains a recommended layout of the options in TCP headers to achieve reasonable data field alignment. In the spirit of Header Prediction, a TCP can quickly test for this layout and if it is verified then use a fast path. Hosts that use this canonical layout will effectively use the options as a set of fixed-format fields appended to the TCP header. However, to retain the philosophical and protocol framework of TCP options, a TCP must be prepared to parse an arbitrary options field, albeit with less efficiency.

Finally, we observe that most of the mechanisms defined in this memo are important for LFN's and/or very high-speed networks. For low-speed networks, it might be a performance optimization to NOT use these mechanisms. A TCP vendor concerned about optimal performance over low-speed paths might consider turning these extensions off for low-speed paths, or allow a user or installation manager to disable them.

2. TCP WINDOW SCALE OPTION

2.1 Introduction

The window scale extension expands the definition of the TCP window to 32 bits and then uses a scale factor to carry this 32-bit value in the 16-bit Window field of the TCP header (SEG.WND in [RFC 793](#)). The scale factor is carried in a new TCP option, Window Scale. This option is sent only in a SYN segment (a segment with the SYN bit on), hence the window scale is fixed in each direction when a connection is opened. (Another design choice would be to specify the window scale in every TCP segment. It would be incorrect to send a window scale option only when the scale factor changed, since a TCP option in an acknowledgement segment will not be delivered reliably (unless the ACK happens to be piggy-backed on data in the other direction). Fixing the scale when the connection is opened has the advantage of lower overhead but the disadvantage that the scale factor cannot be changed during the connection.)

The maximum receive window, and therefore the scale factor, is

determined by the maximum receive buffer space. In a typical modern implementation, this maximum buffer space is set by default but can be overridden by a user program before a TCP connection is opened. This determines the scale factor, and therefore no new user interface is needed for window scaling.

2.2 Window Scale Option

The three-byte Window Scale option may be sent in a SYN segment by a TCP. It has two purposes: (1) indicate that the TCP is prepared to do both send and receive window scaling, and (2) communicate a scale factor to be applied to its receive window. Thus, a TCP that is prepared to scale windows should send the option, even if its own scale factor is 1. The scale factor is limited to a power of two and encoded logarithmically, so it may be implemented by binary shift operations.

TCP Window Scale Option (WSopt):

Kind: 3

Length: 3 bytes

```
+-----+-----+-----+
| Kind=3 |Length=3 |shift.cnt|
+-----+-----+-----+
```

This option is an offer, not a promise; both sides must send Window Scale options in their SYN segments to enable window scaling in either direction. If window scaling is enabled, then the TCP that sent this option will right-shift its true receive-window values by 'shift.cnt' bits for transmission in SEG.WND. The value 'shift.cnt' may be zero (offering to scale, while applying a scale factor of 1 to the receive window).

This option may be sent in an initial <SYN> segment (i.e., a segment with the SYN bit on and the ACK bit off). It may also be sent in a <SYN,ACK> segment, but only if a Window Scale option was received in the initial <SYN> segment. A Window Scale option in a segment without a SYN bit should be ignored.

The Window field in a SYN (i.e., a <SYN> or <SYN,ACK>) segment itself is never scaled.

2.3 Using the Window Scale Option

A model implementation of window scaling is as follows, using the

notation of [RFC 793](#) [[Postel81](#)]:

- * All windows are treated as 32-bit quantities for storage in the connection control block and for local calculations. This includes the send-window (SND.WND) and the receive-window (RCV.WND) values, as well as the congestion window.
- * The connection state is augmented by two window shift counts, Snd.Wind.Scale and Rcv.Wind.Scale, to be applied to the incoming and outgoing window fields, respectively.
- * If a TCP receives a <SYN> segment containing a Window Scale option, it sends its own Window Scale option in the <SYN,ACK> segment.
- * The Window Scale option is sent with shift.cnt = R, where R is the value that the TCP would like to use for its receive window.
- * Upon receiving a SYN segment with a Window Scale option containing shift.cnt = S, a TCP sets Snd.Wind.Scale to S and sets Rcv.Wind.Scale to R; otherwise, it sets both Snd.Wind.Scale and Rcv.Wind.Scale to zero.
- * The window field (SEG.WND) in the header of every incoming segment, with the exception of SYN segments, is left-shifted by Snd.Wind.Scale bits before updating SND.WND:

SND.WND = SEG.WND << Snd.Wind.Scale

(assuming the other conditions of [RFC 793](#) are met, and using the "C" notation "<<" for left-shift).

- * The window field (SEG.WND) of every outgoing segment, with the exception of SYN segments, is right-shifted by Rcv.Wind.Scale bits:

SEG.WND = RCV.WND >> Rcv.Wind.Scale.

TCP determines if a data segment is "old" or "new" by testing whether its sequence number is within 2^{31} bytes of the left edge of the window, and if it is not, discarding the data as "old". To insure that new data is never mistakenly considered old and vice-versa, the left edge of the sender's window has to be at most 2^{31} away from the right edge of the receiver's window. Similarly with the sender's right edge and receiver's left edge. Since the right and left edges of either the sender's or receiver's window differ by the window size, and since the sender and receiver windows can be out of phase by at most the window size, the above constraints imply that $2 \times$ the max window size

must be less than 2^{31} , or

Network Working Group Expires September 4, 2009

[Page 11]

$\text{max window} < 2^{30}$

Since the max window is 2^S (where S is the scaling shift count) times at most $2^{16} - 1$ (the maximum unscaled window), the maximum window is guaranteed to be $< 2^{30}$ if $S \leq 14$. Thus, the shift count must be limited to 14 (which allows windows of $2^{30} = 1$ Gbyte). If a Window Scale option is received with a shift.cnt value exceeding 14, the TCP should log the error but use 14 instead of the specified value.

The scale factor applies only to the Window field as transmitted in the TCP header; each TCP using extended windows will maintain the window values locally as 32-bit numbers. For example, the "congestion window" computed by Slow Start and Congestion Avoidance is not affected by the scale factor, so window scaling will not introduce quantization into the congestion window.

When a non-zero scale factor is in use, there are instances when a retracted window can be offered [Mathis08]. The end of the window will be on a boundary based on the granularity of the scale factor being used. If the sequence number is then updated by a number of bytes smaller than that granularity, the TCP will have to either advertise a new window that beyond what it previously advertised (and perhaps beyond the buffer), or will have to advertise a smaller window, which will cause the TCP window to shrink. Implementations should ensure that they handle a shrinking window, as specified in [section 4.2.2.16 of RFC 1122](#) [Braden89].

3. RTTM: ROUND-TRIP TIME MEASUREMENT

3.1 Introduction

Accurate and current RTT estimates are necessary to adapt to changing traffic conditions and to avoid an instability known as "congestion collapse" [Nagle84] in a busy network. However, accurate measurement of RTT may be difficult both in theory and in implementation.

Many TCP implementations base their RTT measurements upon a sample of one packet per window or less. While this yields an adequate approximation to the RTT for small windows, it results in an unacceptably poor RTT estimate for an LFN. If we look at RTT estimation as a signal processing problem (which it is), a data signal at some frequency, the packet rate, is being sampled at a lower frequency, the window rate. This lower sampling frequency violates Nyquist's criteria and may therefore introduce "aliasing" artifacts into the estimated RTT [Hamming77].

A good RTT estimator with a conservative retransmission timeout

calculation can tolerate aliasing when the sampling frequency is

"close" to the data frequency. For example, with a window of 8 packets, the sample rate is 1/8 the data frequency -- less than an order of magnitude different. However, when the window is tens or hundreds of packets, the RTT estimator may be seriously in error, resulting in spurious retransmissions.

If there are dropped packets, the problem becomes worse. Zhang [[Zhang86](#)], Jain [[Jain86](#)] and Karn [[Karn87](#)] have shown that it is not possible to accumulate reliable RTT estimates if retransmitted segments are included in the estimate. Since a full window of data will have been transmitted prior to a retransmission, all of the segments in that window will have to be ACKed before the next RTT sample can be taken. This means at least an additional window's worth of time between RTT measurements and, as the error rate approaches one per window of data (e.g., 10^{-6} errors per bit for the Wideband satellite network), it becomes effectively impossible to obtain a valid RTT measurement.

A solution to these problems, which actually simplifies the sender substantially, is as follows: using TCP options, the sender places a timestamp in each data segment, and the receiver reflects these timestamps back in ACK segments. Then a single subtract gives the sender an accurate RTT measurement for every ACK segment (which will correspond to every other data segment, with a sensible receiver). We call this the RTTM (Round-Trip Time Measurement) mechanism.

It is vitally important to use the RTTM mechanism with big windows; otherwise, the door is opened to some dangerous instabilities due to aliasing. Furthermore, the option is probably useful for all TCP's, since it simplifies the sender.

3.2 TCP Timestamps Option

TCP is a symmetric protocol, allowing data to be sent at any time in either direction, and therefore timestamp echoing may occur in either direction. For simplicity and symmetry, we specify that timestamps always be sent and echoed in both directions. For efficiency, we combine the timestamp and timestamp reply fields into a single TCP Timestamps Option.

TCP Timestamps Option (TSopt):

Kind: 8

Length: 10 bytes

```
+-----+-----+-----+-----+
|Kind=8 |  10  | TS Value (TSval) |TS Echo Reply (TSecr)|
```


+-----+-----+-----+-----+

1

1

4

4

The Timestamps option carries two four-byte timestamp fields. The Timestamp Value field (TSval) contains the current value of the timestamp clock of the TCP sending the option.

The Timestamp Echo Reply field (TSecr) is valid if the ACK bit is set in the TCP header; if it is valid, it echos a timestamp value that was sent by the remote TCP in the TSval field of a Timestamps option. When TSecr is not valid, its value must be zero. The TSecr value will generally be from the most recent Timestamp option that was received; however, there are exceptions that are explained below.

A TCP may send the Timestamps option (TSopt) in an initial <SYN> segment (i.e., a segment containing a SYN bit and no ACK bit), and may send a TSopt in other segments only if it received a TSopt in the initial <SYN> or <SYN,ACK> segment for the connection. Once a TSopt has been sent or received in a non <SYN> segment, it must be sent in all segments. Once a TSopt has been received in a non <SYN> segment, then any successive segment that is received without the RST bit and without a TSopt may be dropped without further processing, and an ACK of the current SND.UNA generated.

In the case of crossing SYN packets where one SYN contains a TSopt and the other doesn't, both sides should put a TSopt in the <SYN,ACK> segment.

3.3 The RTTM Mechanism

RTTM places a Timestamps option in every segment, with a TSval that is obtained from a (virtual) "timestamp clock". Values of this clock values must be at least approximately proportional to real time, in order to measure actual RTT.

These TSval values are echoed in TSecr values in the reverse direction. The difference between a received TSecr value and the current timestamp clock value provides an RTT measurement.

When timestamps are used, every segment that is received will contain a TSecr value; however, these values cannot all be used to update the measured RTT. The following example illustrates why. It shows a one-way data flow with segments arriving in sequence without loss. Here A, B, C... represent data blocks occupying successive blocks of sequence numbers, and ACK(A),... represent the corresponding cumulative acknowledgments. The two timestamp fields of the Timestamps option are shown symbolically as <TSval=x,TSecr=y>. Each TSecr field contains the value most recently

received in a TSval field.

TCP A

TCP B

```

                <A,TSval=1,TSecr=120> ----->

<----- <ACK(A),TSval=127,TSecr=1>

                <B,TSval=5,TSecr=127> ----->

<----- <ACK(B),TSval=131,TSecr=5>

. . . . .

                <C,TSval=65,TSecr=131> ----->

<----- <ACK(C),TSval=191,TSecr=65>

                (etc)

```

The dotted line marks a pause (60 time units long) in which A had nothing to send. Note that this pause inflates the RTT which B could infer from receiving TSecr=131 in data segment C. Thus, in one-way data flows, RTTM in the reverse direction measures a value that is inflated by gaps in sending data. However, the following rule prevents a resulting inflation of the measured RTT:

RTTM Rule: A TSecr value received in a segment is used to update the averaged RTT measurement only if the segment acknowledges some new data, i.e., only if it advances the left edge of the send window.

Since TCP B is not sending data, the data segment C does not acknowledge any new data when it arrives at B. Thus, the inflated RTTM measurement is not used to update B's RTTM measurement.

Implementors should note that with Timestamps multiple RTTMs can be taken per RTT. Many RTO estimators have a weighting factor based on an implicit assumption that at most one RTTM will be gotten per RTT. When using multiple RTTMs per RTT to update the RTO estimator, the weighting factor needs to be decreased to take into account the more frequent RTTMs. For example, an implementation could choose to just use one sample per RTT to update the RTO estimator, or vary the gain based on the congestion window, or take an average of all the RTTM measurements received over one RTT, and then use that value to update the RTO estimator. This document does not prescribe any particular method for modifying the RTO estimator, the important point is that the implementation should do something more than just feeding additional RTTM samples from one RTT into the RTO estimator.

3.4 Which Timestamp to Echo

If more than one Timestamps option is received before a reply segment is sent, the TCP must choose only one of the TSvals to echo, ignoring the others. To minimize the state kept in the receiver (i.e., the number of unprocessed TSvals), the receiver should be required to retain at most one timestamp in the connection control block.

There are three situations to consider:

(A) Delayed ACKs.

Many TCP's acknowledge only every Kth segment out of a group of segments arriving within a short time interval; this policy is known generally as "delayed ACKs". The data-sender TCP must measure the effective RTT, including the additional time due to delayed ACKs, or else it will retransmit unnecessarily. Thus, when delayed ACKs are in use, the receiver should reply with the TSval field from the earliest unacknowledged segment.

(B) A hole in the sequence space (segment(s) have been lost).

The sender will continue sending until the window is filled, and the receiver may be generating ACKs as these out-of-order segments arrive (e.g., to aid "fast retransmit").

The lost segment is probably a sign of congestion, and in that situation the sender should be conservative about retransmission. Furthermore, it is better to overestimate than underestimate the RTT. An ACK for an out-of-order segment should therefore contain the timestamp from the most recent segment that advanced the window.

The same situation occurs if segments are re-ordered by the network.

(C) A filled hole in the sequence space.

The segment that fills the hole represents the most recent measurement of the network characteristics. On the other hand, an RTT computed from an earlier segment would probably include the sender's retransmit time-out, badly biasing the sender's average RTT estimate. Thus, the timestamp from the latest segment (which filled the hole) must be echoed.

An algorithm that covers all three cases is described in the following rules for Timestamps option processing on a synchronized connection:

(1) The connection state is augmented with two 32-bit slots:

TS.Recent holds a timestamp to be echoed in TSecr whenever a segment is sent, and Last.ACK.sent holds the ACK field from the last segment sent. Last.ACK.sent will equal RCV.NXT except when ACKs have been delayed.

(2) If:

SEG.TSval >= TSrecent and SEG.SEQ <= Last.ACK.sent

then SEG.TSval is copied to TS.Recent; otherwise, it is ignored.

(3) When a TSopt is sent, its TSecr field is set to the current TS.Recent value.

The following examples illustrate these rules. Here A, B, C... represent data segments occupying successive blocks of sequence numbers, and ACK(A),... represent the corresponding acknowledgment segments. Note that ACK(A) has the same sequence number as B. We show only one direction of timestamp echoing, for clarity.

o Packets arrive in sequence, and some of the ACKs are delayed.

By Case (A), the timestamp from the oldest unacknowledged segment is echoed.

	TS.Recent
<A, TSval=1> ----->	1
<B, TSval=2> ----->	1
<C, TSval=3> ----->	1
<---- <ACK(C), TSecr=1>	
(etc)	

o Packets arrive out of order, and every packet is acknowledged.

By Case (B), the timestamp from the last segment that advanced the left window edge is echoed, until the missing segment arrives; it is echoed according to Case (C). The same sequence would occur if segments B and D were lost and retransmitted..

	TS.Recent
<A, TSval=1> ----->	
<---- <ACK(A), TSecr=1>	1
<C, TSval=3> ----->	1
<---- <ACK(A), TSecr=1>	1
<B, TSval=2> ----->	1
<---- <ACK(C), TSecr=2>	2
<E, TSval=5> ----->	2
<---- <ACK(C), TSecr=2>	2
<D, TSval=4> ----->	2
<---- <ACK(E), TSecr=4>	4
(etc)	

4. PAWS: PROTECTION AGAINST WRAPPED SEQUENCE NUMBERS

4.1 Introduction

[Section 4.2](#) describes a simple mechanism to reject old duplicate segments that might corrupt an open TCP connection; we call this mechanism PAWS (Protection Against Wrapped Sequence numbers). PAWS operates within a single TCP connection, using state that is saved in the connection control block. [Section 4.3](#) and [Appendix C](#) discuss the implications of the PAWS mechanism for avoiding old duplicates from previous incarnations of the same connection.

4.2 The PAWS Mechanism

PAWS uses the same TCP Timestamps option as the RTTM mechanism described earlier, and assumes that every received TCP segment (including data and ACK segments) contains a timestamp SEG.TSval whose values are monotonically non-decreasing in time. The basic idea is that a segment can be discarded as an old duplicate if it is received with a timestamp SEG.TSval less than some timestamp recently received on this connection.

In both the PAWS and the RTTM mechanism, the "timestamps" are

32-bit unsigned integers in a modular 32-bit space. Thus, "less

than" is defined the same way it is for TCP sequence numbers, and the same implementation techniques apply. If s and t are timestamp values, $s < t$ if $0 < (t - s) < 2^{31}$, computed in unsigned 32-bit arithmetic.

The choice of incoming timestamps to be saved for this comparison must guarantee a value that is monotonically increasing. For example, we might save the timestamp from the segment that last advanced the left edge of the receive window, i.e., the most recent in-sequence segment. Instead, we choose the value `TS.Recent` introduced in [Section 3.4](#) for the RTTM mechanism, since using a common value for both PAWS and RTTM simplifies the implementation of both. As [Section 3.4](#) explained, `TS.Recent` differs from the timestamp from the last in-sequence segment only in the case of delayed ACKs, and therefore by less than one window. Either choice will therefore protect against sequence number wrap-around.

RTTM was specified in a symmetrical manner, so that `TSval` timestamps are carried in both data and ACK segments and are echoed in `TSecr` fields carried in returning ACK or data segments. PAWS submits all incoming segments to the same test, and therefore protects against duplicate ACK segments as well as data segments. (An alternative non-symmetric algorithm would protect against old duplicate ACKs: the sender of data would reject incoming ACK segments whose `TSecr` values were less than the `TSecr` saved from the last segment whose ACK field advanced the left edge of the send window. This algorithm was deemed to lack economy of mechanism and symmetry.)

`TSval` timestamps sent on `{SYN}` and `{SYN,ACK}` segments are used to initialize PAWS. PAWS protects against old duplicate non-SYN segments, and duplicate SYN segments received while there is a synchronized connection. Duplicate `{SYN}` and `{SYN,ACK}` segments received when there is no connection will be discarded by the normal 3-way handshake and sequence number checks of TCP.

[RFC 1323](#) recommended that RST segments NOT carry timestamps, and that they be acceptable regardless of their timestamp. At that time, the thinking was that old duplicate RST segments should be exceedingly unlikely, and their cleanup function should take precedence over timestamps. More recently, discussion about various blind attacks on TCP connections have raised the suggestion that if the Timestamps option is present, `SEG.TSecr` could be used to provide stricter acceptance tests for RST packets. While still under discussion, to enable research into this area it is now recommended that when generating a RST, that if the packet causing the RST to be generated contained a

Timestamps option that the RST also contain a Timestamps option.
In the RST segment, SEG.TSecr should be set to SEG.TSval from the

incoming packet and SEG.TSval should be set to zero. If a RST is being generated because of a user abort, and Snd.TS.OK is set, then a Timestamps option should be included in the RST. When a RST packet is received, it must not be subjected to PAWS checks, and information from the Timestamps option must not be used to update connection state information. SEG.TSecr may be used to provide stricter RST acceptance checks.

4.2.1 Basic PAWS Algorithm

The PAWS algorithm requires the following processing to be performed on all incoming segments for a synchronized connection:

- R1) If there is a Timestamps option in the arriving segment, $\text{SEG.TSval} < \text{TS.Recent}$, TS.Recent is valid (see later discussion) and the RST bit is not set, then treat the arriving segment as not acceptable:

Send an acknowledgement in reply as specified in [RFC 793](#) page 69 and drop the segment.

Note: it is necessary to send an ACK segment in order to retain TCP's mechanisms for detecting and recovering from half-open connections. For example, see Figure 10 of [RFC 793](#).

- R2) If the segment is outside the window, reject it (normal TCP processing)
- R3) If an arriving segment satisfies: $\text{SEG.SEQ} \leq \text{Last.ACK.sent}$ (see [Section 3.4](#)), then record its timestamp in TS.Recent.
- R4) If an arriving segment is in-sequence (i.e., at the left window edge), then accept it normally.
- R5) Otherwise, treat the segment as a normal in-window, out-of-sequence TCP segment (e.g., queue it for later delivery to the user).

Steps R2, R4, and R5 are the normal TCP processing steps specified by [RFC 793](#).

It is important to note that the timestamp is checked only when a segment first arrives at the receiver, regardless of whether it is in-sequence or it must be queued for later delivery.

Consider the following example.

Suppose the segment sequence: A.1, B.1, C.1, ..., Z.1 has been sent, where the letter indicates the sequence number and the digit represents the timestamp. Suppose also that segment B.1 has been lost. The timestamp in TS.TStamp is 1 (from A.1), so C.1, ..., Z.1 are considered acceptable and are queued. When B is retransmitted as segment B.2 (using the latest timestamp), it fills the hole and causes all the segments through Z to be acknowledged and passed to the user. The timestamps of the queued segments are **not** inspected again at this time, since they have already been accepted. When B.2 is accepted, TS.Stamp is set to 2.

This rule allows reasonable performance under loss. A full window of data is in transit at all times, and after a loss a full window less one packet will show up out-of-sequence to be queued at the receiver (e.g., up to 2^{30} bytes of data); the timestamp option must not result in discarding this data.

In certain unlikely circumstances, the algorithm of rules R1-R5 could lead to discarding some segments unnecessarily, as shown in the following example:

Suppose again that segments: A.1, B.1, C.1, ..., Z.1 have been sent in sequence and that segment B.1 has been lost. Furthermore, suppose delivery of some of C.1, ... Z.1 is delayed until AFTER the retransmission B.2 arrives at the receiver. These delayed segments will be discarded unnecessarily when they do arrive, since their timestamps are now out of date.

This case is very unlikely to occur. If the retransmission was triggered by a timeout, some of the segments C.1, ... Z.1 must have been delayed longer than the RTT time. This is presumably an unlikely event, or there would be many spurious timeouts and retransmissions. If B's retransmission was triggered by the "fast retransmit" algorithm, i.e., by duplicate ACKs, then the queued segments that caused these ACKs must have been received already.

Even if a segment were delayed past the RTT, the Fast Retransmit mechanism [[Jacobson90c](#)] will cause the delayed packets to be retransmitted at the same time as B.2, avoiding an extra RTT and therefore causing a very small performance penalty.

We know of no case with a significant probability of occurrence
in which timestamps will cause performance degradation by

unnecessarily discarding segments.

4.2.2 Timestamp Clock

It is important to understand that the PAWS algorithm does not require clock synchronization between sender and receiver. The sender's timestamp clock is used to stamp the segments, and the sender uses the echoed timestamp to measure RTT's. However, the receiver treats the timestamp as simply a monotonically increasing serial number, without any necessary connection to its clock. From the receiver's viewpoint, the timestamp is acting as a logical extension of the high-order bits of the sequence number.

The receiver algorithm does place some requirements on the frequency of the timestamp clock.

- (a) The timestamp clock must not be "too slow".

It must tick at least once for each 2^{31} bytes sent. In fact, in order to be useful to the sender for round trip timing, the clock should tick at least once per window's worth of data, and even with the window extension defined in [Section 2.2](#), 2^{31} bytes must be at least two windows.

To make this more quantitative, any clock faster than 1 tick/sec will reject old duplicate segments for link speeds of ~8 Gbps. A 1ms timestamp clock will work at link speeds up to 8 Tbps (8×10^{12} bps!)

- (b) The timestamp clock must not be "too fast".

Its recycling time must be greater than MSL seconds. Since the clock (timestamp) is 32 bits and the worst-case MSL is 255 seconds, the maximum acceptable clock frequency is one tick every 59 ns.

However, it is desirable to establish a much longer recycle period, in order to handle outdated timestamps on idle connections (see [Section 4.2.3](#)), and to relax the MSL requirement for preventing sequence number wrap-around. With a 1 ms timestamp clock, the 32-bit timestamp will wrap its sign bit in 24.8 days. Thus, it will reject old duplicates on the same connection if MSL is 24.8 days or less. This appears to be a very safe figure; an MSL of 24.8 days or longer can probably be assumed by the gateway system without requiring precise MSL enforcement by the TTL value in the IP layer.

Based upon these considerations, we choose a timestamp clock

frequency in the range 1 ms to 1 sec per tick. This range also matches the requirements of the RTTM mechanism, which does not need much more resolution than the granularity of the retransmit timer, e.g., tens or hundreds of milliseconds.

The PAWS mechanism also puts a strong monotonicity requirement on the sender's timestamp clock. The method of implementation of the timestamp clock to meet this requirement depends upon the system hardware and software.

- * Some hosts have a hardware clock that is guaranteed to be monotonic between hardware resets.
- * A clock interrupt may be used to simply increment a binary integer by 1 periodically.
- * The timestamp clock may be derived from a system clock that is subject to being abruptly changed, by adding a variable offset value. This offset is initialized to zero. When a new timestamp clock value is needed, the offset can be adjusted as necessary to make the new value equal to or larger than the previous value (which was saved for this purpose).

4.2.3 Outdated Timestamps

If a connection remains idle long enough for the timestamp clock of the other TCP to wrap its sign bit, then the value saved in TS.Recent will become too old; as a result, the PAWS mechanism will cause all subsequent segments to be rejected, freezing the connection (until the timestamp clock wraps its sign bit again).

With the chosen range of timestamp clock frequencies (1 sec to 1 ms), the time to wrap the sign bit will be between 24.8 days and 24800 days. A TCP connection that is idle for more than 24 days and then comes to life is exceedingly unusual. However, it is undesirable in principle to place any limitation on TCP connection lifetimes.

We therefore require that an implementation of PAWS include a mechanism to "invalidate" the TS.Recent value when a connection is idle for more than 24 days. (An alternative solution to the problem of outdated timestamps would be to send keep-alive segments at a very low rate, but still more often than the wrap-around time for timestamps, e.g., once a day. This would impose negligible overhead. However, the TCP specification has never included keep-alives, so the solution based upon

invalidation was chosen.)

Note that a TCP does not know the frequency, and therefore, the wraparound time, of the other TCP, so it must assume the worst. The validity of TS.Recent needs to be checked only if the basic PAWS timestamp check fails, i.e., only if $SEG.TSval < TS.Recent$. If TS.Recent is found to be invalid, then the segment is accepted, regardless of the failure of the timestamp check, and rule R3 updates TS.Recent with the TSval from the new segment.

To detect how long the connection has been idle, the TCP may update a clock or timestamp value associated with the connection whenever TS.Recent is updated, for example. The details will be implementation-dependent.

4.2.4 Header Prediction

"Header prediction" [[Jacobson90a](#)] is a high-performance transport protocol implementation technique that is most important for high-speed links. This technique optimizes the code for the most common case, receiving a segment correctly and in order. Using header prediction, the receiver asks the question, "Is this segment the next in sequence?" This question can be answered in fewer machine instructions than the question, "Is this segment within the window?"

Adding header prediction to our timestamp procedure leads to the following recommended sequence for processing an arriving TCP segment:

- H1) Check timestamp (same as step R1 above)
- H2) Do header prediction: if segment is next in sequence and if there are no special conditions requiring additional processing, accept the segment, record its timestamp, and skip H3.
- H3) Process the segment normally, as specified in [RFC 793](#). This includes dropping segments that are outside the window and possibly sending acknowledgments, and queueing in-window, out-of-sequence segments.

Another possibility would be to interchange steps H1 and H2, i.e., to perform the header prediction step H2 FIRST, and perform H1 and H3 only when header prediction fails. This could be a performance improvement, since the timestamp check in step H1 is very unlikely to fail, and it requires unsigned modulo arithmetic, a relatively expensive operation. To perform this check on every single segment is contrary to the

philosophy of header prediction. We believe that this change

might produce a measurable reduction in CPU time for TCP protocol processing on high-speed networks.

However, putting H2 first would create a hazard: a segment from 2^{32} bytes in the past might arrive at exactly the wrong time and be accepted mistakenly by the header-prediction step. The following reasoning has been introduced [[Jacobson90b](#)] to show that the probability of this failure is negligible.

If all segments are equally likely to show up as old duplicates, then the probability of an old duplicate exactly matching the left window edge is the maximum segment size (MSS) divided by the size of the sequence space. This ratio must be less than 2^{-16} , since MSS must be $< 2^{16}$; for example, it will be $(2^{12})/(2^{32}) = 2^{-20}$ for an FDDI link. However, the older a segment is, the less likely it is to be retained in the Internet, and under any reasonable model of segment lifetime the probability of an old duplicate exactly at the left window edge must be much smaller than 2^{-16} .

The 16 bit TCP checksum also allows a basic unreliability of one part in 2^{16} . A protocol mechanism whose reliability exceeds the reliability of the TCP checksum should be considered "good enough", i.e., it won't contribute significantly to the overall error rate. We therefore believe we can ignore the problem of an old duplicate being accepted by doing header prediction before checking the timestamp.

However, this probabilistic argument is not universally accepted, and the consensus at present is that the performance gain does not justify the hazard in the general case. It is therefore recommended that H2 follow H1.

4.2.5 IP Fragmentation

At high data rates, the protection against old packets provided by PAWS can be circumvented by errors in IP fragment reassembly [[Heffner07](#)]. The only way to protect against incorrect IP fragment reassembly is to not allow the packets to be fragmented. This is done by setting the Don't Fragment (DF) bit in the IP header. Setting the DF bit implies the use of Path MTU Discovery as described in [RFC 1191](#) [[Mogul90](#)], thus any TCP implementation that implements PAWS must also implement Path MTU Discovery.

4.3. Duplicates from Earlier Incarnations of Connection

The PAWS mechanism protects against errors due to sequence number wrap-around on high-speed connection. Segments from an earlier incarnation of the same connection are also a potential cause of old duplicate errors. In both cases, the TCP mechanisms to prevent such errors depend upon the enforcement of a maximum segment lifetime (MSL) by the Internet (IP) layer (see Appendix of [RFC 1185](#) for a detailed discussion). Unlike the case of sequence space wrap-around, the MSL required to prevent old duplicate errors from earlier incarnations does not depend upon the transfer rate. If the IP layer enforces the recommended 2 minute MSL of TCP, and if the TCP rules are followed, TCP connections will be safe from earlier incarnations, no matter how high the network speed. Thus, the PAWS mechanism is not required for this case.

We may still ask whether the PAWS mechanism can provide additional security against old duplicates from earlier connections, allowing us to relax the enforcement of MSL by the IP layer. [Appendix B](#) explores this question, showing that further assumptions and/or mechanisms are required, beyond those of PAWS. This is not part of the current extension.

5. CONCLUSIONS AND ACKNOWLEDGMENTS

This memo presented a set of extensions to TCP to provide efficient operation over large-bandwidth*delay-product paths and reliable operation over very high-speed paths. These extensions are designed to provide compatible interworking with TCP's that do not implement the extensions.

These mechanisms are implemented using new TCP options for scaled windows and timestamps. The timestamps are used for two distinct mechanisms: RTTM (Round Trip Time Measurement) and PAWS (Protect Against Wrapped Sequences).

The Window Scale option was originally suggested by Mike St. Johns of USAF/DCA. The present form of the option was suggested by Mike Karels of UC Berkeley in response to a more cumbersome scheme defined by Van Jacobson. Lixia Zhang helped formulate the PAWS mechanism description in [RFC 1185](#).

Finally, much of this work originated as the result of discussions within the End-to-End Task Force on the theoretical limitations of transport protocols in general and TCP in particular. Task force members and other on the end2end-interest list have made valuable contributions by pointing out flaws in the algorithms and the documentation. Continued discussion and development since the publication of [RFC 1323](#) originally occurred in the IETF TCP Large

Windows Working Group, later on in the End-to-End Task Force, and most recently in the IETF TCP Maintenance Working Group. The authors

are grateful for all these contributions.

6. SECURITY CONSIDERATIONS

The TCP sequence space is a fixed size, and as the window becomes larger it becomes easier for an attacker to generate forged packets that can fall within the TCP window, and be accepted as valid packets. While use of Timestamps and PAWS can help to mitigate this, when using PAWS, if an attacker is able to forge a packet that is acceptable to the TCP connection, a timestamp that is in the future would cause valid packets to be dropped due to PAWS checks. Hence, implementors should take care to not open the TCP window drastically beyond the requirements of the connection.

Middle boxes and options If a middle box removes TCP options from the SYN, such as TSopt, a high speed connection that needs PAWS would not have that protection. In this situation, an implementor could provide a mechanism for the application to determine whether or not PAWS is in use on the connection, and chose to terminate the connection if that protection doesn't exist.

Mechanisms to protect the TCP header from modification should also protect the TCP options.

Expanding the TCP window beyond 64K for IPv6 allows Jumbograms [Borman99] to be used when the local network supports packets larger than 64K. When larger TCP packets are used, the TCP checksum becomes weaker.

7. IANA CONSIDERATIONS

This document has no actions for IANA.

8. REFERENCES

Normative References

[Mogul90] Mogul, J. and Deering, S., "Path MTU Discovery", [RFC 1191](#), November 1990.

[Postel81] Postel, J., "Transmission Control Protocol - DARPA Internet Program Protocol Specification", [RFC 793](#), DARPA, September 1981.

Informative References

[Allman99] Allman, M., Paxson, V., Stevens, W., "TCP Congestion Control", [RFC 2581](#), NASA Glenn/Sterling Software, ACIRI / ICSI, April 1999.

[Borman99] Borman, D., Deering, S., and Hinden, R, "IPv6 Jumbograms" [RFC 2675](#), August 1999.

[Braden89] Braden, R., editor, "Requirements for Internet Hosts -- Communication Layers", [RFC 1122](#), October, 1989

[Floyd00] Floyd, S., Mahdavi, J., Mathis, M., Podolsky, M., "An Extension to the Selective Acknowledgement (SACK) Option for TCP", [RFC 2883](#), July 2000.

[Blanton03] Blanton, E., Allman, M., Fall, K., Wang, L., "A Conservative Selective Acknowledgment (SACK)-based Loss Recovery Algorithm for TCP", [RFC 3517](#), April 2003.

[Garlick77] Garlick, L., R. Rom, and J. Postel, "Issues in Reliable Host-to-Host Protocols", Proc. Second Berkeley Workshop on Distributed Data Management and Computer Networks, May 1977.

[Hamming77] Hamming, R., "Digital Filters", ISBN 0-13-212571-4, Prentice Hall, Englewood Cliffs, N.J., 1977.

[Heffner07] Heffner, J., Mathis, M., and Chandler, B., "IPv4 Reassembly Errors at High Data Rates" [RFC 4963](#), PSC, July 2007.

[Jacobson88a] Jacobson, V., "Congestion Avoidance and Control", SIGCOMM '88, Stanford, CA., August 1988.

[Jacobson88b] Jacobson, V., and R. Braden, "TCP Extensions for Long-Delay Paths", [RFC 1072](#), LBL and USC/Information Sciences Institute, October 1988.

[Jacobson90a] Jacobson, V., "4BSD Header Prediction", ACM Computer Communication Review, April 1990.

[Jacobson90b] Jacobson, V., Braden, R., and Zhang, L., "TCP Extension for High-Speed Paths", [RFC 1185](#), LBL and USC/Information Sciences Institute, October 1990.

[Jacobson90c] Jacobson, V., "Modified TCP congestion avoidance algorithm", Message to end2end-interest mailing list, April 1990.

[Jacobson92d] Jacobson, V., Braden, R., and Borman, D., "TCP Extension for High Performance", [RFC 1323](#), LBL, USC/Information Sciences Institute and Cray Research, May 1992.

[Jain86] Jain, R., "Divergence of Timeout Algorithms for Packet Retransmissions", Proc. Fifth Phoenix Conf. on Comp. and Comm., Scottsdale, Arizona, March 1986.

[Karn87] Karn, P. and C. Partridge, "Estimating Round-Trip Times in Reliable Transport Protocols", Proc. SIGCOMM '87, Stowe, VT, August 1987.

[Martin03] Martin, D., "[Tsvwg] [RFC 1323](#).bis" Message to tsvwg mailing list, September 30, 2003.

[Mathis96] Mathis, M., Mahdavi, J., Floyd, S., and Romanow, A., "TCP Selective Acknowledgment Options", [RFC 2018](#), October, 1996.

[Mathis08] Mathis, M., "[tcpm] Example of 1323 window retraction problemPer my comments at the microphone at TCPM...", Message to the tcpm mailing list, March 2008.

[McKenzie89] McKenzie, A., "A Problem with the TCP Big Window Option", [RFC 1110](#), BBN STC, August 1989.

[Nagle84] Nagle, J., "Congestion Control in IP/TCP Internetworks", [RFC 896](#), FACC, January 1984.

[Watson81] Watson, R., "Timer-based Mechanisms in Reliable Transport Protocol Connection Management", Computer Networks, Vol. 5, 1981.

[Zhang86] Zhang, L., "Why TCP Timers Don't Work Well", Proc. SIGCOMM '86, Stowe, Vt., August 1986.

APPENDIX A: IMPLEMENTATION SUGGESTIONS

TCP Option Layout

The following layouts are recommended for sending options on non-SYN segments, to achieve maximum feasible alignment of 32-bit and 64-bit machines.

```

+-----+-----+-----+-----+
|  NOP  |  NOP  | TSopt |  10  |
+-----+-----+-----+-----+
|                TSval timestamp                |
+-----+-----+-----+-----+
|                TSecr timestamp                |
+-----+-----+-----+-----+

```

Interaction with the TCP Urgent Pointer

The TCP Urgent pointer, like the TCP window, is a 16 bit value. Some of the original discussion for the TCP Window Scale option included proposals to increase the Urgent pointer to 32 bits. As it turns out, this is unnecessary. There are two observations that should be made:

- (1) With IP Version 4, the largest amount of TCP data that can be sent in a single packet is 65495 bytes (64K - 1 - size of fixed IP and TCP headers).
- (2) Updates to the urgent pointer while the user is in "urgent mode" are invisible to the user.

This means that if the Urgent Pointer points beyond the end of the TCP data in the current packet, then the user will remain in urgent mode until the next TCP packet arrives. That packet will update the urgent pointer to a new offset, and the user will never have left urgent mode.

Thus, to properly implement the Urgent Pointer, the sending TCP only has to check for overflow of the 16 bit Urgent Pointer field before filling it in. If it does overflow, than a value of 65535 should be inserted into the Urgent Pointer.

The same technique applies to IP Version 6, except in the case of IPv6 Jumbograms. When IPv6 Jumbograms are supported, [RFC 2675](#) [[Borman99](#)] requires additional steps for dealing with the

Urgent Pointer, these are described in [section 5.2 of RFC 2675](#).

APPENDIX B: DUPLICATES FROM EARLIER CONNECTION INCARNATIONS

There are two cases to be considered: (1) a system crashing (and losing connection state) and restarting, and (2) the same connection being closed and reopened without a loss of host state. These will be described in the following two sections.

B.1 System Crash with Loss of State

TCP's quiet time of one MSL upon system startup handles the loss of connection state in a system crash/restart. For an explanation, see for example "When to Keep Quiet" in the TCP protocol specification [[Postel81](#)]. The MSL that is required here does not depend upon the transfer speed. The current TCP MSL of 2 minutes seems acceptable as an operational compromise, as many host systems take this long to boot after a crash.

However, the timestamp option may be used to ease the MSL requirements (or to provide additional security against data corruption). If timestamps are being used and if the timestamp clock can be guaranteed to be monotonic over a system crash/restart, i.e., if the first value of the sender's timestamp clock after a crash/restart can be guaranteed to be greater than the last value before the restart, then a quiet time will be unnecessary.

To dispense totally with the quiet time would require that the host clock be synchronized to a time source that is stable over the crash/restart period, with an accuracy of one timestamp clock tick or better. We can back off from this strict requirement to take advantage of approximate clock synchronization. Suppose that the clock is always re-synchronized to within N timestamp clock ticks and that booting (extended with a quiet time, if necessary) takes more than N ticks. This will guarantee monotonicity of the timestamps, which can then be used to reject old duplicates even without an enforced MSL.

B.2 Closing and Reopening a Connection

When a TCP connection is closed, a delay of $2 \times \text{MSL}$ in TIME-WAIT state ties up the socket pair for 4 minutes (see Section 3.5 of [[Postel81](#)]). Applications built upon TCP that close one connection and open a new one (e.g., an FTP data transfer connection using Stream mode) must choose a new socket pair each time. The TIME-WAIT delay serves two different purposes:

- (a) Implement the full-duplex reliable close handshake of TCP.

The proper time to delay the final close step is not really related to the MSL; it depends instead upon the RTO for the FIN segments and therefore upon the RTT of the path. (It could be argued that the side that is sending a FIN knows what degree of reliability it needs, and therefore it should be able to determine the length of the TIME-WAIT delay for the FIN's recipient. This could be accomplished with an appropriate TCP option in FIN segments.)

Although there is no formal upper-bound on RTT, common network engineering practice makes an RTT greater than 1 minute very unlikely. Thus, the 4 minute delay in TIME-WAIT state works satisfactorily to provide a reliable full-duplex TCP close. Note again that this is independent of MSL enforcement and network speed.

The TIME-WAIT state could cause an indirect performance problem if an application needed to repeatedly close one connection and open another at a very high frequency, since the number of available TCP ports on a host is less than 2^{16} . However, high network speeds are not the major contributor to this problem; the RTT is the limiting factor in how quickly connections can be opened and closed. Therefore, this problem will be no worse at high transfer speeds.

- (b) Allow old duplicate segments to expire.

To replace this function of TIME-WAIT state, a mechanism would have to operate across connections. PAWS is defined strictly within a single connection; the last timestamp (TS.Recent) is kept in the connection control block, and discarded when a connection is closed.

An additional mechanism could be added to the TCP, a per-host cache of the last timestamp received from any connection. This value could then be used in the PAWS mechanism to reject old duplicate segments from earlier incarnations of the connection, if the timestamp clock can be guaranteed to have ticked at least once since the old connection was open. This would require that the TIME-WAIT delay plus the RTT together must be at least one tick of the sender's timestamp clock. Such an extension is not part of the proposal of this RFC.

Note that this is a variant on the mechanism proposed by Garlick, Rom, and Postel [[Garlick77](#)], which required each host to maintain connection records containing the highest sequence numbers on every connection. Using timestamps

instead, it is only necessary to keep one quantity per remote host, regardless of the number of simultaneous connections to

that host.

APPENDIX C: CHANGES FROM [RFC 1072](#), [RFC 1185](#), [RFC 1323](#)

The protocol extensions defined in [RFC 1323](#) document differ in several important ways from those defined in [RFC 1072](#) and [RFC 1185](#).

- (a) SACK has been split off into a separate document, [RFC 2018](#) [[Mathis96](#)].
- (b) The detailed rules for sending timestamp replies (see [Section 3.4](#)) differ in important ways. The earlier rules could result in an under-estimate of the RTT in certain cases (packets dropped or out of order).
- (c) The same value TS.Recent is now shared by the two distinct mechanisms RTTM and PAWS. This simplification became possible because of change (b).
- (d) An ambiguity in [RFC 1185](#) was resolved in favor of putting timestamps on ACK as well as data segments. This supports the symmetry of the underlying TCP protocol.
- (e) The echo and echo reply options of [RFC 1072](#) were combined into a single Timestamps option, to reflect the symmetry and to simplify processing.
- (f) The problem of outdated timestamps on long-idle connections, discussed in [Section 4.2.2](#), was realized and resolved.
- (g) [RFC 1185](#) recommended that header prediction take precedence over the timestamp check. Based upon some skepticism about the probabilistic arguments given in [Section 4.2.4](#), it was decided to recommend that the timestamp check be performed first.
- (h) The spec was modified so that the extended options will be sent on <SYN,ACK> segments only when they are received in the corresponding <SYN> segments. This provides the most conservative possible conditions for interoperation with implementations without the extensions.

In addition to these substantive changes, the present RFC attempts to specify the algorithms unambiguously by presenting modifications to the Event Processing rules of [RFC 793](#); see [Appendix F](#).

There are additional changes in this document from [RFC 1323](#). These changes are:

- (a) The description of which TSecr values can be used to update the measured RTT has been clarified. Specifically, with Timestamps,

the Karn algorithm [[Karn87](#)] is disabled. The Karn algorithm

disables all RTT measurements during retransmission, since it is ambiguous whether the ACK is for the original packet, or the retransmitted packet. With Timestamps, that ambiguity is removed since the TSecr in the ACK will contain the TSval from whichever data packet made it to the destination.

- (b) In [RFC 1323, section 3.4](#), step (2) of the algorithm to control which timestamp is echoed was incorrect in two regards:

- (1) It failed to update TSrecent for a retransmitted segment that resulted from a lost ACK.

- (2) It failed if SEG.LEN = 0.

In the new algorithm, the case of SEG.TSval = TSrecent is included for consistency with the PAWS test.

- (c) One correction was made to the Event Processing Summary in [Appendix F](#). In SEND CALL/ESTABLISHED STATE, RCV.WND is used to fill in the SEG.WND value, not SND.WND.
- (d) New pseudo-code summary has been added in [Appendix E](#).
- (e) [Appendix A](#) has been expanded with information about the TCP MSS option and the TCP Urgent Pointer.
- (f) It is now recommended that Timestamps options be included in RST packets if the incoming packet contained a Timestamps option.
- (g) RST packets are explicitly excluded from PAWS processing.
- (h) Snd.TSoffset and Snd.TSclock variables have been added. Snd.TSoffset is the sum of my.TSclock and Snd.TSoffset. This allows the starting points for timestamps to be randomized on a per-connection basis. Setting Snd.TSoffset to zero yields the same results as [RFC 1323](#).

APPENDIX D: SUMMARY OF NOTATION

The following notation has been used in this document.

Options

WSopt: TCP Window Scale Option
TSopt: TCP Timestamps Option

Option Fields

shift.cnt: Window scale byte in WSopt.
TSval: 32-bit Timestamp Value field in TSopt.
TSecr: 32-bit Timestamp Reply field in TSopt.

Option Fields in Current Segment

SEG.TSval: TSval field from TSopt in current segment.
SEG.TSecr: TSecr field from TSopt in current segment.
SEG.WSopt: 8-bit value in WSopt

Clock Values

my.TSclock: System wide source of 32-bit timestamp values
my.TSclock.rate: Period of my.TSclock (1 ms to 1 sec).
Snd.TSoffset: A offset for randomizing Snd.TSclock
Snd.TSclock: my.TSclock + Snd.TSoffset

Per-Connection State Variables

TS.Recent: Latest received Timestamp
Last.ACK.sent: Last ACK field sent

Snd.TS.OK: 1-bit flag
Snd.WS.OK: 1-bit flag

Rcv.Wind.Scale: Receive window scale power
Snd.Wind.Scale: Send window scale power

Start.Time: Snd.TSclock value when segment being
timed was sent (used by pre-1323 code).

Procedure

Update_SRTT(m) Procedure to update the smoothed RTT and RTT
variance estimates, using the rules of
[\[Jacobson88a\]](#), given m, a new RTT measurement.

APPENDIX E: PSEUDO-CODE SUMMARY

```
Create new TCB => {
  Rcv.wind.scale =
    MIN( 14, MAX(0, floor(log2(receive buffer space)) - 15) );
  Snd.wind.scale = 0;
  Last.ACK.sent = 0;
  Snd.TS.OK = Snd.WS.OK = FALSE;
  Snd.TSoffset = random 32 bit value
}
```

```
Send initial {SYN} segment => {

  SEG.WND = MIN( RCV.WND, 65535 );
  Include in segment: TSopt(TSval=Snd.TSclock, TCecr=0);
  Include in segment: WSopt = Rcv.wind.scale;
}
```

```
Send {SYN, ACK} segment => {

  SEG.ACK = Last.ACK.sent = RCV.NXT;
  SEG.WND = MIN( RCV.WND, 65535 );
  if (Snd.TS.OK) then
    Include in segment:
      TSopt(TSval=Snd.TSclock, TSecr=TS.Recent);
  if (Snd.WS.OK) then
    Include in segment: WSopt = Rcv.wind.scale;
}
```

```
Receive {SYN} or {SYN,ACK} segment => {

  if (Segment contains TSopt) then {
    TS.Recent = SEG.TSval;
    Snd.TS.OK = TRUE;
    if (is {SYN,ACK} segment) then
      Update_SRTT(
        (Snd.TSclock - SEG.TSecr)/my.TSclock.rate);
  }

  if (Segment contains WSopt) then {
    Snd.wind.scale = SEG.WSopt;
    Snd.WS.OK = TRUE;
    if (the ACK bit is not set, and Rcv.wind.scale has not been
        initialized by the user) then
      Rcv.wind.scale = Snd.wind.scale;
  }
}
```


else

```
        Rcv.wind.scale = Snd.wind.scale = 0;
    }
```

```
Send non-SYN segment => {
```

```
    SEG.ACK = Last.ACK.sent = RCV.NXT;
    SEG.WND = MIN( RCV.WND >> Rcv.wind.scale, 65535 );
    if (Snd.TS.OK) then
        Include in segment:
            TSopt(TSval=Snd.TSclock, TSecr=TS.Recent);
}
```

```
Receive non-SYN segment in (state >= ESTABLISHED) => {
```

```
    Window = (SEG.WND << Snd.wind.scale);
    /* Use 32-bit 'Window' instead of 16-bit 'SEG.WND'
       * in rest of processing.
       */

    if (Segment contains TSopt) then {
        if (SEG.TSval < TS.Recent && Idle less than 24 days) then {
            if (Send.TS.OK AND (NOT RST) ) then {
                /* Timestamp too old =>
                   * segment is unacceptable.
                   */
                Send ACK segment;
                Discard segment and return;
            }
        }
        else {
            if (SEG.SEQ <= Last.ACK.sent) then
                TS.Recent = SEG.TSval;
        }
    }

    if (SEG.ACK > SND.UNA) then {
        /* (At least part of) first segment in
           * retransmission queue has been ACKd
           */
        if (Segment contains TSopt) then
            Update_SRTT(
                (Snd.TSclock - SEG.TSecr)/my.TSclock.rate);
        else
            Update_SRTT( /* for compatibility */
                (Snd.TSclock - Start.Time)/my.TSclock.rate);
    }
}
```

}

APPENDIX F: EVENT PROCESSING SUMMARY

Event Processing

OPEN Call

...

An initial send sequence number (ISS) is selected. Send a SYN segment of the form:

<SEQ=ISS><CTL=SYN><TSval=Snd.TSclock><WSopt=Rcv.Wind.Scale>

...

SEND Call

CLOSED STATE (i.e., TCB does not exist)

...

LISTEN STATE

If the foreign socket is specified, then change the connection from passive to active, select an ISS. Send a SYN segment containing the options: <TSval=Snd.TSclock> and <WSopt=Rcv.Wind.Scale>. Set SND.UNA to ISS, SND.NXT to ISS+1. Enter SYN-SENT state. ...

SYN-SENT STATE

SYN-RECEIVED STATE

...

ESTABLISHED STATE

CLOSE-WAIT STATE

Segmentize the buffer and send it with a piggybacked acknowledgment (acknowledgment value = RCV.NXT). ...

If the urgent flag is set ...

If the Snd.TS.OK flag is set, then include the TCP Timestamps option <TSval=Snd.TSclock,TSecr=TS.Recent> in each data segment.

Scale the receive window for transmission in the segment header:

SEG.WND = (RCV.WND >> Rcv.Wind.Scale).

SEGMENT ARRIVES

...

If the state is LISTEN then

first check for an RST

...

second check for an ACK

...

third check for a SYN

if the SYN bit is set, check the security. If the ...

...

If the SEG.PRC is less than the TCB.PRC then continue.

Check for a Window Scale option (WSopt); if one is found, save SEG.WSopt in Snd.Wind.Scale and set Snd.WS.OK flag on. Otherwise, set both Snd.Wind.Scale and Rcv.Wind.Scale to zero and clear Snd.WS.OK flag.

Check for a TSopt option; if one is found, save SEG.TSval in the variable TS.Recent and turn on the Snd.TS.OK bit.

Set RCV.NXT to SEG.SEQ+1, IRS is set to SEG.SEQ and any other control or text should be queued for processing later. ISS should be selected and a SYN segment sent of the form:

<SEQ=ISS><ACK=RCV.NXT><CTL=SYN,ACK>

If the Snd.WS.OK bit is on, include a WSopt option <WSopt=Rcv.Wind.Scale> in this segment. If the Snd.TS.OK bit is on, include a TSopt <TSval=Snd.TSclock,TSocr=TS.Recent> in this segment. Last.ACK.sent is set to RCV.NXT.

SND.NXT is set to ISS+1 and SND.UNA to ISS. The connection state should be changed to SYN-RECEIVED. Note that any other incoming control or data (combined with SYN) will be processed in the SYN-RECEIVED state, but processing of SYN and ACK should not be repeated. If the listen was not fully specified (i.e., the foreign socket was not fully specified), then the unspecified fields should be filled in now.

fourth other text or control

Network Working Group Expires September 4, 2009

[Page 41]

...

If the state is SYN-SENT then

first check the ACK bit

...

fourth check the SYN bit

...

If the SYN bit is on and the security/compartments and precedence are acceptable then, RCV.NXT is set to SEG.SEQ+1, IRS is set to SEG.SEQ, and any acknowledgements on the retransmission queue which are thereby acknowledged should be removed.

Check for a Window Scale option (WSopt); if is found, save SEG.WSopt in Snd.Wind.Scale; otherwise, set both Snd.Wind.Scale and Rcv.Wind.Scale to zero.

Check for a TSopt option; if one is found, save SEG.TSval in variable TS.Recent and turn on the Snd.TS.OK bit in the connection control block. If the ACK bit is set, use Snd.TSclock - SEG.TSecr as the initial RTT estimate.

If SND.UNA > ISS (our SYN has been ACKed), change the connection state to ESTABLISHED, form an ACK segment:

<SEQ=SND.NXT><ACK=RCV.NXT><CTL=ACK>

and send it. If the Snd.Echo.OK bit is on, include a TSopt option <TSval=Snd.TSclock,TSecr=TS.Recent> in this ACK segment. Last.ACK.sent is set to RCV.NXT.

Data or controls which were queued for transmission may be included. If there are other controls or text in the segment then continue processing at the sixth step below where the URG bit is checked, otherwise return.

Otherwise enter SYN-RECEIVED, form a SYN,ACK segment:

<SEQ=ISS><ACK=RCV.NXT><CTL=SYN,ACK>

and send it. If the Snd.Echo.OK bit is on, include a TSopt option <TSval=Snd.TSclock,TSecr=TS.Recent> in this segment. If the Snd.WS.OK bit is on, include a WSopt option <WSopt=Rcv.Wind.Scale> in this segment. Last.ACK.sent is set to

RCV.NXT.

If there are other controls or text in the segment, queue them for processing after the ESTABLISHED state has been reached, return.

fifth, if neither of the SYN or RST bits is set then drop the segment and return.

Otherwise,

First, check sequence number

SYN-RECEIVED STATE
ESTABLISHED STATE
FIN-WAIT-1 STATE
FIN-WAIT-2 STATE
CLOSE-WAIT STATE
CLOSING STATE
LAST-ACK STATE
TIME-WAIT STATE

Segments are processed in sequence. Initial tests on arrival are used to discard old duplicates, but further processing is done in SEG.SEQ order. If a segment's contents straddle the boundary between old and new, only the new parts should be processed.

Rescale the received window field:

TrueWindow = SEG.WND << Snd.Wind.Scale,

and use "TrueWindow" in place of SEG.WND in the following steps.

Check whether the segment contains a Timestamps option and bit Snd.TS.OK is on. If so:

If SEG.TSval < TS.Recent and the RST bit is off, then test whether connection has been idle less than 24 days; if all are true, then the segment is not acceptable; follow steps below for an unacceptable segment.

If SEG.SEQ is equal to Last.ACK.sent, then save SEG.ECopt in variable TS.Recent.

There are four cases for the acceptability test for an incoming segment:

...

If an incoming segment is not acceptable, an acknowledgment should be sent in reply (unless the RST bit is set, if so drop the segment and return):

<SEQ=SND.NXT><ACK=RCV.NXT><CTL=ACK>

Last.ACK.sent is set to SEG.ACK of the acknowledgment. If the Snd.Echo.OK bit is on, include the Timestamps option <TSval=Snd.TSclock, TSecr=TS.Recent> in this ACK segment. Set Last.ACK.sent to SEG.ACK and send the ACK segment. After sending the acknowledgment, drop the unacceptable segment and return.

...

fifth check the ACK field.

if the ACK bit is off drop the segment and return.

if the ACK bit is on

...

ESTABLISHED STATE

If $SND.UNA < SEG.ACK \leq SND.NXT$ then, set $SND.UNA \leftarrow SEG.ACK$. Also compute a new estimate of round-trip time. If Snd.TS.OK bit is on, use $Snd.TSclock - SEG.TSecr$; otherwise use the elapsed time since the first segment in the retransmission queue was sent. Any segments on the retransmission queue which are thereby entirely acknowledged...

...

Seventh, process the segment text.

ESTABLISHED STATE

FIN-WAIT-1 STATE

FIN-WAIT-2 STATE

...

Send an acknowledgment of the form:

<SEQ=SND.NXT><ACK=RCV.NXT><CTL=ACK>

If the Snd.TS.OK bit is on, include Timestamps option

<TSval=Snd.TSclock,TSecr=TS.Recent> in this ACK segment. Set Last.ACK.sent to SEG.ACK of the acknowledgment, and send it. This acknowledgment should be piggy-backed on a segment being transmitted if possible without incurring undue delay.

...

APPENDIX G: Timestamps Edge Cases

While the rules laid out for when to calculate RTTM produce the correct results most of the time, there are some edge cases where an incorrect RTTM can be calculated. All of these situations involve the loss of packets. It is felt that these scenarios are rare, and that if they should happen, they will cause a single RTTM measurement to be inflated, which mitigates its effects on RTO calculations.

[Martin03] cites two similar cases when the returning ACK is lost, and before the retransmission timer fires, another returning packet arrives, which ACKs the data. In this case, the RTTM calculated will be inflated:

```

clock
tc=1  <A, TSval=1> ----->

tc=2  (lost) <---- <ACK(A), TSecr=1, win=n>
      (RTTM would have been 1)

      (receive window opens, window update is sent)
tc=5  <---- <ACK(A), TSecr=1, win=m>
      (RTTM is calculated at 4)

```

One thing to note about this situation is that it is somewhat bounded by $RTO + RTT$, limiting how far off the RTTM calculation will be. While more complex scenarios can be constructed that produce larger inflations (e.g., retransmissions are lost), those scenarios involve multiple packet losses, and the connection will have other more serious operational problems than using an inflated RTTM in the RTO calculation. -----

Authors' Addresses

David Borman
Wind River Systems
Mendota Heights, MN 55120

Phone: (651) 454-3052
Email: david.borman@windriver.com

Bob Braden
University of Southern California
Information Sciences Institute
4676 Admiralty Way
Marina del Rey, CA 90292

Phone: (310) 448-9173
EMail: Braden@ISI.EDU

Van Jacobson
Packet Design
2465 Latham Street
Mountain View, CA 94040

EMail: van@packetdesign.com

