

Workgroup: TCPM

Internet-Draft: draft-ietf-tcpm-yang-tcp-09

Published: 11 September 2022

Intended Status: Standards Track

Expires: 15 March 2023

Authors: M. Scharf                      M. Jethanandani      V. Murgai  
          Hochschule Esslingen      Kloud Services      Samsung

## **A YANG Model for Transmission Control Protocol (TCP) Configuration and State**

### **Abstract**

This document specifies a minimal YANG model for TCP on devices that are configured and managed by network management protocols. The YANG model defines a container for all TCP connections, and groupings of authentication parameters that can be imported and used in TCP implementations or by other models that need to configure TCP parameters. The model also includes basic TCP statistics. The model is compliant with Network Management Datastore Architecture (NMDA) (RFC 8342).

### **Status of This Memo**

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 15 March 2023.

### **Copyright Notice**

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with

respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

## Table of Contents

- [1. Introduction](#)
- [2. Requirements Language](#)
  - [2.1. Note to RFC Editor](#)
- [3. YANG Module Overview](#)
  - [3.1. Scope](#)
  - [3.2. Model Design](#)
  - [3.3. Tree Diagram](#)
- [4. TCP YANG Model](#)
- [5. IANA Considerations](#)
  - [5.1. The IETF XML Registry](#)
  - [5.2. The YANG Module Names Registry](#)
- [6. Security Considerations](#)
- [7. References](#)
  - [7.1. Normative References](#)
  - [7.2. Informative References](#)
- [Appendix A. Acknowledgements](#)
- [Appendix B. Examples](#)
  - [B.1. Keepalive Configuration](#)
  - [B.2. TCP-AO Configuration](#)
- [Appendix C. Complete Tree Diagram](#)
- [Authors' Addresses](#)

## 1. Introduction

The [Transmission Control Protocol \(TCP\)](#) [[RFC9293](#)] is used by many applications in the Internet, including control and management protocols. As such, TCP is implemented on network elements that can be configured and managed via network management protocols such as [NETCONF](#) [[RFC6241](#)] or [RESTCONF](#) [[RFC8040](#)].

This document specifies a minimal [YANG 1.1](#) [[RFC7950](#)] model for configuring and managing TCP on network elements that support YANG, a TCP connection table, a TCP listener table containing information about a particular TCP listener, and an augmentation of the [YANG Data Model for Key Chains](#) [[RFC8177](#)] to support authentication. The YANG module specified in this document is compliant with [Network Management Datastore Architecture \(NMDA\)](#) [[RFC8342](#)].

The YANG module has a narrow scope and focuses on a subset of fundamental TCP functions and basic statistics. It defines a container for a list of TCP connections that includes definitions from [YANG Groupings for TCP Clients and TCP Servers](#) [[I-D.ietf-](#)

[netconf-tcp-client-server](#)]. The model adheres to the recommendation in [BGP/MPLS IP Virtual Private Networks \[RFC4364\]](#). Therefore it allows enabling of [TCP-AO \[RFC5925\]](#), and accommodates the installed base that makes use of MD5. The module can be augmented or updated to address more advanced or implementation-specific TCP features in the future.

This specification does not deprecate the [Management Information Base \(MIB\) for the Transmission Control Protocol \(TCP\) \[RFC4022\]](#). The basic statistics defined in this document follow the model of the TCP MIB. An [TCP Extended Statistics MIB \[RFC4898\]](#) is also available, but this document does not cover such extended statistics. The YANG module also omits some selected parameters included in TCP MIB, most notably Retransmission Timeout (RTO) configuration and a maximum connection limit. This is a conscious decision as these parameters hardly matter in a state-of-the-art TCP implementation. It would also be possible to translate a MIB into a YANG module, for instance using [Translation of Structure of Management Information Version 2 \(SMIV2\) MIB Modules to YANG Modules \[RFC6643\]](#). However, this approach is not used in this document, because a translated model would not be up-to-date.

There are other existing TCP-related YANG models, which are orthogonal to this specification. Examples are:

- \*TCP header attributes are modeled in other security-related models, such as [YANG Data Model for Network Access Control Lists \(ACLs\) \[RFC8519\]](#), [Distributed Denial-of-Service Open Thread Signaling \(DOTS\) Data Channel Specification \[RFC8783\]](#), [I2NSF Capability YANG Data Model \[I-D.ietf-i2nsf-capability-data-model\]](#), or [I2NSF Network Security Function-Facing Interface YANG Data Model \[I-D.ietf-i2nsf-nsf-facing-interface-dm\]](#).

- \*TCP-related configuration of a NAT (e.g., NAT44, NAT64, Destination NAT) is defined in [A YANG Module for Network Address Translation \(NAT\) and Network Prefix Translation \(NPT\) \[RFC8512\]](#) and [A YANG Data Model for Dual-Stack Lite \(DS-Lite\) \[RFC8513\]](#).

- \*TCP-AO and TCP MD5 configuration for Layer 3 VPNs is modeled in [A Layer 3 VPN Network YANG Model \[RFC9182\]](#). This model assumes that TCP-AO specific parameters are preconfigured in addition to the keychain parameters.

## 2. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in

BCP 14 [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

## 2.1. Note to RFC Editor

This document uses several placeholder values throughout the document. Please replace them as follows and remove this note before publication.

RFC XXXX, where XXXX is the number assigned to this document at the time of publication.

2022-09-11 with the actual date of the publication of this document.

## 3. YANG Module Overview

### 3.1. Scope

TCP is implemented on different system architectures. As a result, there are many different and often implementation-specific ways to configure parameters of the TCP engine. In addition, in many TCP/IP stacks configuration exists for different scopes:

\*System-wide configuration: Many TCP implementations have configuration parameters that affect all TCP connections from or to this TCP stack. Typical examples include enabling or disabling optional protocol features. For instance, many implementations can turn on or off use of window scaling [Transmission Control Protocol \(TCP\) Specification \[RFC9293\]](#) for all TCP connections.

\*Interface configuration: It can be useful to use different TCP parameters on different interfaces, e.g., different device ports or IP interfaces. In that case, TCP parameters can be part of the interface configuration. Typical examples are the Maximum Segment Size (MSS) or configuration related to hardware offloading.

\*Connection parameters: Many implementations have means to influence the behavior of each TCP connection, e.g., on the programming interface used by applications. Typical examples are socket options in the socket API, such as disabling the Nagle algorithm [Transmission Control Protocol \(TCP\) Specification \[RFC9293\]](#) by TCP\_NODELAY. If an application uses such an interface, it is possible that the configuration of the application or application protocol includes TCP-related parameters. An example is the [BGP YANG Model for Service Provider Networks \[I-D.ietf-idr-bgp-model\]](#).

\*Application preferences: Setting of TCP parameters can also be part of application preferences, templates, or profiles. An example would be the preferences defined in [An Abstract](#)

[Application Layer Interface to Transport Services \[I-D.ietf-taps-interface\]](#).

As a result, there is no ground truth for setting certain TCP parameters, and traditionally different TCP implementations have used different modeling approaches. For instance, one implementation may define a given configuration parameter globally, while another one uses per-interface settings, and both approaches work well for the corresponding use cases. Also, different systems may use different default values. In addition, TCP can be implemented in different ways and design choices by the protocol engine often affect configuration options.

Nonetheless, a number of TCP stack parameters require configuration by YANG models. This document therefore defines a minimal YANG model with fundamental parameters. An important use case is the TCP configuration on network elements such as routers, which often use YANG data models. The model therefore specifies TCP parameters that are important on such TCP stacks.

This in particular applies to the support of [TCP-AO \[RFC5925\]](#) and the corresponding [cryptographic algorithms \[RFC5926\]](#). TCP Authentication Option (TCP-AO) is used on routers to secure routing protocols such as BGP. In that case, a YANG model for TCP-AO configuration is required. The model defined in this document includes the required parameters for TCP-AO configuration, such as the values of SendID and RecvID. The keychain for TCP-AO can be modeled by the [YANG Data Model for Key Chains \[RFC8177\]](#). The groupings defined in this document can be imported and used as part of such a preconfiguration.

Given an installed base, the model also allows enabling of the legacy [TCP MD5 \[RFC2385\]](#) signature option. The TCP MD5 signature option was obsoleted by TCP-AO in 2010. If current implementations require TCP authentication, it is RECOMMENDED to use [TCP-AO \[RFC5925\]](#).

Similar to the [TCP MIB \[RFC4022\]](#), this document also specifies basic statistics, a TCP connection list, and a TCP listener list.

\*Statistics: Counters for the number of active/passive opens, sent and received TCP segments, errors, and possibly other detailed debugging information

\*TCP connection list: Access to status information for all TCP connections. Note, the connection table is modeled as a list that is read-writeable, even though a connection cannot be created by adding entries to the table. Similarly, deletion of connections from this list is implementation-specific.

\*TCP listener list: A list containing information about TCP listeners, i.e., applications willing to accept connections.

This allows implementations of [TCP MIB \[RFC4022\]](#) to migrate to the YANG model defined in this memo. Note that the TCP MIB does not include means to reset statistics, which are defined in this document. This is not a major addition, as a reset can simply be implemented by storing offset values for the counters.

This version of the module does not model details of [Multipath TCP \[RFC8684\]](#). This could be addressed in a later version of this document.

### 3.2. Model Design

The YANG model defined in this document includes definitions from the [YANG Groupings for TCP Clients and TCP Servers \[I-D.ietf-netconf-tcp-client-server\]](#). Similar to that model, this specification defines YANG groupings. This allows reuse of these groupings in different YANG data models. It is intended that these groupings will be used either standalone or for TCP-based protocols as part of a stack of protocol-specific configuration models. An example could be the [BGP YANG Model for Service Provider Networks \[I-D.ietf-idr-bgp-model\]](#).

### 3.3. Tree Diagram

This section provides an abridged tree diagram for the YANG module defined in this document. Annotations used in the diagram are defined in [YANG Tree Diagrams \[RFC8340\]](#). A complete tree diagram can be found in the Appendix.

```
module: ietf-tcp
  +-rw tcp!
    +-rw connections
      |   ...
    +-ro tcp-listeners* [type address port]
      |   ...
    +-ro statistics {statistics}?
      ...

augment /key-chain:key-chains/key-chain:key-chain:key:
  +-rw authentication {authentication}?
    +-rw keychain?    key-chain:key-chain-ref
    +-rw (authentication)?
      ...
```

#### 4. TCP YANG Model

This YANG module references [The TCP Authentication Option \[RFC5925\]](#), [Protection of BGP Sessions via the TCP MD5 Signature \[RFC2385\]](#), [Transmission Control Protocol \(TCP\) Specification \[RFC9293\]](#), and imports [Common YANG Data Types \[RFC6991\]](#), [The NETCONF Access Control Model \[RFC8341\]](#), and [YANG Groupings for TCP Clients and TCP Servers \[I-D.ietf-netconf-tcp-client-server\]](#).

```
<CODE BEGINS> file "ietf-tcp@2022-09-11.yang"
```

```
module ietf-tcp {
  yang-version "1.1";
  namespace "urn:ietf:params:xml:ns:yang:ietf-tcp";
  prefix "tcp";

  import ietf-yang-types {
    prefix "yang";
    reference
      "RFC 6991: Common YANG Data Types.";
  }
  import ietf-tcp-common {
    prefix "tcpcmn";
    reference
      "I-D.ietf-netconf-tcp-client-server: YANG Groupings for TCP
      Clients and TCP Servers.";
  }
  import ietf-inet-types {
    prefix "inet";
    reference
      "RFC 6991: Common YANG Data Types.";
  }
  import ietf-netconf-acm {
    prefix nacm;
    reference
      "RFC 8341: Network Configuration Access Control Model";
  }
  import ietf-key-chain {
    prefix key-chain;
    reference
      "RFC 8177: YANG Key Chain.";
  }

  organization
    "IETF TCPM Working Group";

  contact
    "WG Web: <https://datatracker.ietf.org/wg/tcpm/about>
    WG List: <tcpm@ietf.org>

    Authors: Michael Scharf (michael.scharf at hs-esslingen dot de)
            Mahesh Jethanandani (mjethanandani at gmail dot com)
            Vishal Murgai (vmurgai at gmail dot com)";

  description
    "This module focuses on fundamental TCP functions and basic
    statistics. The model can be augmented to address more advanced
```



or implementation specific TCP features.

Copyright (c) 2022 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX (<https://www.rfc-editor.org/info/rfcXXXX>); see the RFC itself for full legal notices.

The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED', 'MAY', and 'OPTIONAL' in this document are to be interpreted as described in BCP 14 (RFC 2119) (RFC 8174) when, and only when, they appear in all capitals, as shown here.";

```
revision "2022-09-11" {
  description
    "Initial Version";
  reference
    "RFC XXXX, A YANG Model for Transmission Control Protocol (TCP)
    Configuration and State.";
}

// Typedefs
typedef mss {
  type uint16;
  description
    "Type definition for Maximum Segment Size.";
}

// Features
feature statistics {
  description
    "This implementation supports statistics reporting.";
}

feature authentication {
  description
    "This implementation supports authentication.";
}

// Identities
identity aes-128 {
```

```

base key-chain:crypto-algorithm;
description
  "AES128 authentication algorithm used by TCP-AO.";
reference
  "RFC 5926: Cryptographic Algorithms for the TCP
  Authentication Option (TCP-AO).";
}

// TCP-AO Groupings

grouping ao {
  leaf send-id {
    type uint8 {
      range "0..max";
    }
    description
      "The SendID is inserted as the KeyID of the TCP-AO option
      of outgoing segments. In a consistent configuration, the
      SendID matches the RecvID at the other endpoint.";
    reference
      "RFC 5925: The TCP Authentication Option, Section 3.1.";
  }

  leaf recv-id {
    type uint8 {
      range "0..max";
    }
    description
      "The RecvID is matched against the TCP-AO KeyID of incoming
      segments. In a consistent configuration, the RecvID matches
      the SendID at the other endpoint.";
    reference
      "RFC 5925: The TCP Authentication Option, Section 3.1.";
  }

  leaf include-tcp-options {
    type boolean;
    default true;
    description
      "When set to true, TCP options are included in MAC
      calculation.";
    reference
      "RFC 5925: The TCP Authentication Option, Section 3.1.";
  }

  leaf accept-key-mismatch {
    type boolean;
    description
      "Accept, when set to true, TCP segments with a Master Key

```

```

    Tuple (MKT) that is not configured.";
  reference
    "RFC 5925: The TCP Authentication Option, Section 7.3.";
}

leaf r-next-key-id {
  type uint8;
  config false;
  description
    "A field indicating the Master Key Tuple (MKT) that is ready
    at the sender to be used to authenticate received segments,
    i.e., the desired 'receive next' key ID.";
  reference
    "RFC 5925: The TCP Authentication Option.";
}

description
  "Authentication Option (AO) for TCP.";
reference
  "RFC 5925: The TCP Authentication Option.";
}

// TCP configuration

container tcp {
  presence "The container for TCP configuration.";

  description
    "TCP container.";

  container connections {
    list connection {
      key "local-address remote-address local-port remote-port";

      leaf local-address {
        type inet:ip-address;
        description
          "Identifies the address that is used by the local
          endpoint for the connection, and is one of the four
          elements that form the connection identifier.";
      }

      leaf remote-address {
        type inet:ip-address;
        description
          "Identifies the address that is used by the remote
          endpoint for the connection, and is one of the four
          elements that form the connection identifier.";
      }
    }
  }
}

```

```

leaf local-port {
    type inet:port-number;
    description
        "Identifies the local TCP port used for the connection,
        and is one of the four elements that form the
        connection identifier.";
}

leaf remote-port {
    type inet:port-number;
    description
        "Identifies the remote TCP port used for the connection,
        and is one of the four elements that form the
        connection identifier.";
}

leaf mss {
    type mss;
    description
        "Maximum Segment Size (MSS) desired on this connection.
        Note, the 'effective send MSS' can be smaller than
        what is configured here.";
    reference
        "RFC 9293: Transmission Control Protocol (TCP)
        Specification.";
}

leaf pmtud {
    type boolean;
    default false;
    description
        "Turns Path Maximum Transmission Unit Discovery (PMTUD)
        on (true) or off (false).";
    reference
        "RFC 9293: Transmission Control Protocol (TCP)
        Specification.";
}

uses tcpcmn:tcp-common-grouping;

leaf state {
    type enumeration {
        enum closed {
            value 1;
            description
                "Connection is closed. Connections in this state
                may not appear in this list.";
        }
        enum listen {

```

```
value 2;
description
    "Represents waiting for a connection request from any
    remote TCP peer and port.";
}
enum syn-sent {
value 3;
description
    "Represents waiting for a matching connection request
    after having sent a connection request.";
}
enum syn-received {
value 4;
description
    "Represents waiting for a confirming connection
    request acknowledgment after having both received
    and sent a connection request.";
}
enum established {
value 5;
description
    "Represents an open connection, data received can be
    delivered to the user. The normal state for the data
    transfer phase of the connection.";
}
enum fin-wait-1 {
value 6;
description
    "Represents waiting for a connection termination
    request from the remote TCP peer, or an
    acknowledgment of the connection termination request
    previously sent.";
}
enum fin-wait-2 {
value 7;
description
    "Represents waiting for a connection termination
    request from the remote TCP peer.";
}
enum close-wait {
value 8;
description
    "Represents waiting for a connection termination
    request from the local user.";
}
enum last-ack {
value 9;
description
    "Represents waiting for an acknowledgment of the
```

```

        connection termination request previously sent to
        the remote TCP peer (this termination request sent
        to the remote TCP peer already included an
        acknowledgment of the termination request sent from
        the remote TCP peer)";
    }
    enum closing {
        value 10;
        description
            "Represents waiting for a connection termination
            request acknowledgment from the remote TCP peer.";
    }
    enum time-wait {
        value 11;
        description
            "Represents waiting for enough time to pass to be
            sure the remote TCP peer received the acknowledgment
            of its connection termination request, and to avoid
            new connections being impacted by delayed segments
            from previous connections.";
    }
}
config false;
description
    "The state of this TCP connection.";
}
description
    "List of TCP connections with their parameters.

    The list is modeled as writeable even though only some of
    the nodes are writeable, e.g. keepalive. Connections
    that are created and match this list SHOULD apply the
    writeable parameters. At the same time, implementations
    may not allow creation of new TCP connections simply by
    adding entries to the list. Furthermore, the behavior
    upon removal is implementation-specific. Implementations
    may not support closing or resetting a TCP connection
    upon an operation that removes the entry from the list.

    The operational state of this list SHOULD reflect
    connections that have configured, but not created, and
    connections that have been created. Connections in
    CLOSED state are not reflected on this list.";
}
description
    "A container of all TCP connections.";
}

list tcp-listeners {

```

```

key "type address port";
config false;

description
  "A table containing information about a particular
  TCP listener.";

leaf type {
  type inet:ip-version;
  description
    "The address type of address. The value
    should be unspecified (0) if connection initiations
    to all local IP addresses are accepted.";
}

leaf address {
  type union {
    type inet:ip-address;
    type string {
      length 0;
    }
  }
  description
    "The local IP address for this TCP connection.

    The value of this node can be represented in three
    possible ways, depending on the characteristics of the
    listening application:

    1. For an application willing to accept both IPv4 and
    IPv6 datagrams, the value of this node must be
    'h (a zero-length octet-string), with the value
    of the corresponding 'type' object being
    unspecified (0).

    2. For an application willing to accept only IPv4 or
    IPv6 datagrams, the value of this node must be
    '0.0.0.0' or '::' respectively, with
    'type' representing the appropriate address type.

    3. For an application which is listening for data
    destined only to a specific IP address, the value
    of this node is the specific local address, with
    'type' representing the appropriate address type.";
}

leaf port {
  type inet:port-number;
  description
    "The local port number for this TCP connection.";
}

```

```

    }
}

container statistics {
    if-feature statistics;
    config false;

    leaf active-opens {
        type yang:counter64;
        description
            "The number of times that TCP connections have made a
            direct transition to the SYN-SENT state from the CLOSED
            state.";
        reference
            "RFC 9293: Transmission Control Protocol (TCP)
            Specification.";
    }

    leaf passive-opens {
        type yang:counter64;
        description
            "The number of times TCP connections have made a direct
            transition to the SYN-RCVD state from the LISTEN state.";
        reference
            "RFC 9293: Transmission Control Protocol (TCP)
            Specification.";
    }

    leaf attempt-fails {
        type yang:counter64;
        description
            "The number of times that TCP connections have made a
            direct transition to the CLOSED state from either the
            SYN-SENT state or the SYN-RCVD state, plus the number of
            times that TCP connections have made a direct transition
            to the LISTEN state from the SYN-RCVD state.";
        reference
            "RFC 9293: Transmission Control Protocol (TCP)
            Specification.";
    }

    leaf establish-resets {
        type yang:counter64;
        description
            "The number of times that TCP connections have made a
            direct transition to the CLOSED state from either the
            ESTABLISHED state or the CLOSE-WAIT state.";
        reference
            "RFC 9293: Transmission Control Protocol (TCP)

```



```
        Specification.";
    }

    leaf currently-established {
        type yang:gauge32;
        description
            "The number of TCP connections for which the current state
            is either ESTABLISHED or CLOSE-WAIT.";
        reference
            "RFC 9293: Transmission Control Protocol (TCP)
            Specification.";
    }

    leaf in-segments {
        type yang:counter64;
        description
            "The total number of TCP segments received, including those
            received in error. This count includes TCP segments
            received on currently established connections.";
        reference
            "RFC 9293: Transmission Control Protocol (TCP)
            Specification.";
    }

    leaf out-segments {
        type yang:counter64;
        description
            "The total number of TCP segments sent, including those on
            current connections but excluding those containing only
            retransmitted octets.";
        reference
            "RFC 9293: Transmission Control Protocol (TCP)
            Specification.";
    }

    leaf retransmitted-segments {
        type yang:counter64;
        description
            "The total number of TCP segments retransmitted; that is,
            the number of TCP segments transmitted containing one or
            more previously transmitted octets.";
        reference
            "RFC 9293: Transmission Control Protocol (TCP)
            Specification.";
    }

    leaf in-errors {
        type yang:counter64;
        description
```

```

        "The total number of TCP segments received in error
        (e.g., bad TCP checksums).";
    reference
        "RFC 9293: Transmission Control Protocol (TCP)
        Specification.";
}

leaf out-resets {
    type yang:counter64;
    description
        "The number of TCP segments sent containing the RST flag.";
    reference
        "RFC 9293: Transmission Control Protocol (TCP)
        Specification.";
}

leaf auth-failures {
    if-feature authentication;
    type yang:counter64;
    description
        "The number of times that authentication has failed either
        with TCP-AO or MD5.";
}

action reset {
    nacm:default-deny-all;
    description
        "Reset statistics action command.";
    input {
        leaf reset-at {
            type yang:date-and-time;
            description
                "Time when the reset action needs to be
                executed.";
        }
    }
    output {
        leaf reset-finished-at {
            type yang:date-and-time;
            description
                "Time when the reset action command completed.";
        }
    }
}
description
    "Statistics across all connections.";
}
}

```

```

augment "/key-chain:key-chains/key-chain:key-chain:key" {
  description
    "Augmentation of the key-chain model to add TCP-AO and TCP-MD5
    authentication.";

  container authentication {
    if-feature authentication;
    leaf keychain {
      type key-chain:key-chain-ref;
      description
        "Reference to the key chain that will be used by
        this model. Applicable for TCP-AO and TCP-MD5
        only";
      reference
        "RFC 8177: YANG Key Chain.";
    }

    choice authentication {
      container ao {
        presence "Presence container for all TCP-AO related" +
          " configuration";
        uses ao;
        description
          "Use TCP-AO to secure the connection.";
      }

      container md5 {
        presence "Presence container for all MD5 related" +
          " configuration";
        description
          "Use TCP-MD5 to secure the connection. As the TCP MD5
          signature option is obsoleted by TCP-AO, it is
          RECOMMENDED to use TCP-AO instead.";
        reference
          "RFC 2385: Protection of BGP Sessions via the TCP MD5
          Signature.";
      }
    }
    description
      "Choice of TCP authentication.";
  }
  description
    "Authentication definitions for TCP configuration.
    This includes parameters such as how to secure the
    connection, that can be part of either the client
    or server.";
}
}
}

```

<CODE ENDS>

## 5. IANA Considerations

### 5.1. The IETF XML Registry

This document registers an URI in the "ns" subregistry of the [IETF XML Registry](#) [RFC3688]. Following the format in [IETF XML Registry](#) [RFC3688], the following registration is requested:

URI: urn:ietf:params:xml:ns:yang:ietf-tcp  
Registrant Contact: The IESG.  
XML: N/A, the requested URI is an XML namespace.

### 5.2. The YANG Module Names Registry

The following entry is requested to be added to the "YANG Module Names" registry created by [YANG - A Data Modeling Language for the Network Configuration Protocol \(NETCONF\)](#) [RFC6020]:

name: ietf-tcp  
namespace: urn:ietf:params:xml:ns:yang:ietf-tcp  
prefix: tcp  
reference: RFC XXXX (this document)

The registration is not maintained by IANA.

## 6. Security Considerations

The YANG module specified in this document defines a schema for data that is designed to be accessed via network management protocols such as [NETCONF](#) [RFC6241] or [RESTCONF](#) [RFC8040]. The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure transport is Secure Shell (SSH) described in [Using the NETCONF protocol over SSH](#) [RFC6242]. The lowest RESTCONF layer is HTTPS, and the mandatory-to-implement secure transport is [TLS](#) [RFC8446].

The [Network Configuration Access Control Model \(NACM\)](#) [RFC8341] provides the means to restrict access for particular NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

There are a number of data nodes defined in this YANG module that are writable/creatable/deletable (i.e., "config true", which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config)

to these data nodes without proper protection can have a negative effect on network operations. These are the subtrees and data nodes and their sensitivity/vulnerability:

\*Common configuration included from [NETCONF Client and Server Models \[I-D.ietf-netconf-tcp-client-server\]](#). Unrestricted access to all the nodes, e.g., keepalive idle-timer, can cause connections to fail or to timeout prematurely.

\*Authentication configuration. Unrestricted access to the nodes under authentication configuration can prevent the use of authenticated communication and cause connection setups to fail. This can result in massive security vulnerabilities and service disruption for the traffic requiring authentication.

Some of the readable data nodes in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes. These are the subtrees and data nodes and their sensitivity/vulnerability:

\*Unrestricted access to connection information of the client or server can be used by a malicious user to launch an attack.

\*Similarly, unrestricted access to statistics of the client or server can be used by a malicious user to exploit any vulnerabilities of the system.

Some of the RPC operations in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control access to these operations. These are the operations and their sensitivity/vulnerability:

\*The YANG module allows for the statistics to be cleared by executing the reset action. This action should be restricted to users with the right permission.

The module specified in this document supports MD5 to basically accommodate the installed BGP base. MD5 suffers from the security weaknesses discussed in Section 2 of [RFC 6151 \[RFC6151\]](#) or Section 2.1 of [RFC 6952 \[RFC6952\]](#).

## 7. References

### 7.1. Normative References

[I-D.ietf-netconf-tcp-client-server] Watsen, K. and M. Scharf, "YANG Groupings for TCP Clients and TCP Servers", Work in Progress, Internet-Draft, draft-ietf-netconf-tcp-client-

server-13, 24 May 2022, <<https://www.ietf.org/archive/id/draft-ietf-netconf-tcp-client-server-13.txt>>.

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC2385] Heffernan, A., "Protection of BGP Sessions via the TCP MD5 Signature Option", RFC 2385, DOI 10.17487/RFC2385, August 1998, <<https://www.rfc-editor.org/info/rfc2385>>.
- [RFC3688] Mealling, M., "The IETF XML Registry", BCP 81, RFC 3688, DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.
- [RFC5925] Touch, J., Mankin, A., and R. Bonica, "The TCP Authentication Option", RFC 5925, DOI 10.17487/RFC5925, June 2010, <<https://www.rfc-editor.org/info/rfc5925>>.
- [RFC5926] Lebovitz, G. and E. Rescorla, "Cryptographic Algorithms for the TCP Authentication Option (TCP-AO)", RFC 5926, DOI 10.17487/RFC5926, June 2010, <<https://www.rfc-editor.org/info/rfc5926>>.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", RFC 6020, DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", RFC 6241, DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", RFC 6242, DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC6991] Schoenwaelder, J., Ed., "Common YANG Data Types", RFC 6991, DOI 10.17487/RFC6991, July 2013, <<https://www.rfc-editor.org/info/rfc6991>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", RFC 7950, DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", RFC 8040, DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.

- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8177] Lindem, A., Ed., Qu, Y., Yeung, D., Chen, I., and J. Zhang, "YANG Data Model for Key Chains", RFC 8177, DOI 10.17487/RFC8177, June 2017, <<https://www.rfc-editor.org/info/rfc8177>>.
- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", BCP 215, RFC 8340, DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.
- [RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, RFC 8341, DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.
- [RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture (NMDA)", RFC 8342, DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", RFC 8446, DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.
- [RFC9293] Eddy, W., Ed., "Transmission Control Protocol (TCP)", STD 7, RFC 9293, DOI 10.17487/RFC9293, August 2022, <<https://www.rfc-editor.org/info/rfc9293>>.

## 7.2. Informative References

- [I-D.ietf-i2nsf-capability-data-model] Hares, S., Jeong, J. P., Kim, J. T., Moskowitz, R., and Q. Lin, "I2NSF Capability YANG Data Model", Work in Progress, Internet-Draft, draft-ietf-i2nsf-capability-data-model-32, 23 May 2022, <<https://www.ietf.org/archive/id/draft-ietf-i2nsf-capability-data-model-32.txt>>.
- [I-D.ietf-i2nsf-nsf-facing-interface-dm] Kim, J. T., Jeong, J. P., Park, J., Hares, S., and Q. Lin, "I2NSF Network Security Function-Facing Interface YANG Data Model", Work in Progress, Internet-Draft, draft-ietf-i2nsf-nsf-facing-interface-dm-29, 1 June 2022, <<https://www.ietf.org/archive/id/draft-ietf-i2nsf-nsf-facing-interface-dm-29.txt>>.

**[I-D.ietf-idr-bgp-model]**

Jethanandani, M., Patel, K., Hares, S., and J. Haas, "BGP YANG Model for Service Provider Networks", Work in Progress, Internet-Draft, draft-ietf-idr-bgp-model-14, 3 July 2022, <<https://www.ietf.org/archive/id/draft-ietf-idr-bgp-model-14.txt>>.

**[I-D.ietf-taps-interface]**

Trammell, B., Welzl, M., Enghardt, T., Fairhurst, G., Kuehlewind, M., Perkins, C., Tiesel, P. S., and T. Pauly, "An Abstract Application Layer Interface to Transport Services", Work in Progress, Internet-Draft, draft-ietf-taps-interface-16, 31 August 2022, <<https://www.ietf.org/archive/id/draft-ietf-taps-interface-16.txt>>.

**[RFC4022]** Raghunarayan, R., Ed., "Management Information Base for the Transmission Control Protocol (TCP)", RFC 4022, DOI 10.17487/RFC4022, March 2005, <<https://www.rfc-editor.org/info/rfc4022>>.

**[RFC4364]** Rosen, E. and Y. Rekhter, "BGP/MPLS IP Virtual Private Networks (VPNs)", RFC 4364, DOI 10.17487/RFC4364, February 2006, <<https://www.rfc-editor.org/info/rfc4364>>.

**[RFC4898]** Mathis, M., Heffner, J., and R. Raghunarayan, "TCP Extended Statistics MIB", RFC 4898, DOI 10.17487/RFC4898, May 2007, <<https://www.rfc-editor.org/info/rfc4898>>.

**[RFC6151]** Turner, S. and L. Chen, "Updated Security Considerations for the MD5 Message-Digest and the HMAC-MD5 Algorithms", RFC 6151, DOI 10.17487/RFC6151, March 2011, <<https://www.rfc-editor.org/info/rfc6151>>.

**[RFC6643]** Schoenwaelder, J., "Translation of Structure of Management Information Version 2 (SMIV2) MIB Modules to YANG Modules", RFC 6643, DOI 10.17487/RFC6643, July 2012, <<https://www.rfc-editor.org/info/rfc6643>>.

**[RFC6952]** Jethanandani, M., Patel, K., and L. Zheng, "Analysis of BGP, LDP, PCEP, and MSDP Issues According to the Keying and Authentication for Routing Protocols (KARP) Design Guide", RFC 6952, DOI 10.17487/RFC6952, May 2013, <<https://www.rfc-editor.org/info/rfc6952>>.

**[RFC8512]** Boucadair, M., Ed., Sivakumar, S., Jacquenet, C., Vinapamula, S., and Q. Wu, "A YANG Module for Network Address Translation (NAT) and Network Prefix Translation (NPT)", RFC 8512, DOI 10.17487/RFC8512, January 2019, <<https://www.rfc-editor.org/info/rfc8512>>.



- [RFC8513] Boucadair, M., Jacquenet, C., and S. Sivakumar, "A YANG Data Model for Dual-Stack Lite (DS-Lite)", RFC 8513, DOI 10.17487/RFC8513, January 2019, <<https://www.rfc-editor.org/info/rfc8513>>.
- [RFC8519] Jethanandani, M., Agarwal, S., Huang, L., and D. Blair, "YANG Data Model for Network Access Control Lists (ACLs)", RFC 8519, DOI 10.17487/RFC8519, March 2019, <<https://www.rfc-editor.org/info/rfc8519>>.
- [RFC8684] Ford, A., Raiciu, C., Handley, M., Bonaventure, O., and C. Paasch, "TCP Extensions for Multipath Operation with Multiple Addresses", RFC 8684, DOI 10.17487/RFC8684, March 2020, <<https://www.rfc-editor.org/info/rfc8684>>.
- [RFC8783] Boucadair, M., Ed. and T. Reddy, K., Ed., "Distributed Denial-of-Service Open Threat Signaling (DOTS) Data Channel Specification", RFC 8783, DOI 10.17487/RFC8783, May 2020, <<https://www.rfc-editor.org/info/rfc8783>>.
- [RFC9182] Barguil, S., Gonzalez de Dios, O., Ed., Boucadair, M., Ed., Munoz, L., and A. Aguado, "A YANG Network Data Model for Layer 3 VPNs", RFC 9182, DOI 10.17487/RFC9182, February 2022, <<https://www.rfc-editor.org/info/rfc9182>>.
- [RFC9235] Touch, J. and J. Kuusisaari, "TCP Authentication Option (TCP-AO) Test Vectors", RFC 9235, DOI 10.17487/RFC9235, May 2022, <<https://www.rfc-editor.org/info/rfc9235>>.

## Appendix A. Acknowledgements

Michael Scharf was supported by the StandICT.eu project, which is funded by the European Commission under the Horizon 2020 Programme.

The following persons have contributed to this document by reviews (in alphabetical order): Mohamed Boucadair, Gorry Fairhurst, Jeffrey Haas, and Tom Petch.

## Appendix B. Examples

### B.1. Keepalive Configuration

This particular example demonstrates how both a particular connection can be configured for keepalives.

NOTE: '\\' line wrapping per RFC 8792

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<!--
```

This example shows how TCP keepalive, MSS and PMTU can be configured \

for a given connection. An idle connection is dropped after  
idle-time + (max-probes \* probe-interval).

```
-->
```

```
<tcp
```

```
  xmlns="urn:ietf:params:xml:ns:yang:ietf-tcp">
```

```
  <connections>
```

```
    <connection>
```

```
      <local-address>192.0.2.1</local-address>
```

```
      <remote-address>192.0.2.2</remote-address>
```

```
      <local-port>1025</local-port>
```

```
      <remote-port>22</remote-port>
```

```
      <mss>1400</mss>
```

```
      <pmtud>true</pmtud>
```

```
      <keepalives>
```

```
        <idle-time>5</idle-time>
```

```
        <max-probes>5</max-probes>
```

```
        <probe-interval>10</probe-interval>
```

```
      </keepalives>
```

```
    </connection>
```

```
  </connections>
```

```
</tcp>
```

## B.2. TCP-AO Configuration

The following example demonstrates how to model a [TCP-AO \[RFC5925\]](#) configuration for the example in [TCP-AO Test Vectors \[RFC9235\]](#). The IP addresses and other parameters are taken from the test vectors.

NOTE: '\\' line wrapping per RFC 8792

```
<?xml version="1.0" encoding="UTF-8"?>
<!--
This example sets TCP-AO configuration parameters similar to
the examples in RFC 9235.
-->

<key-chains
  xmlns="urn:ietf:params:xml:ns:yang:ietf-key-chain">
  <key-chain>
    <name>ao-config</name>
    <description>"An example for TCP-AO configuration."</description>

    <key>
      <key-id>55</key-id>
      <lifetime>
        <send-lifetime>
          <start-date-time>2017-01-01T00:00:00Z</start-date-time>
          <end-date-time>2017-02-01T00:00:00Z</end-date-time>
        </send-lifetime>
        <accept-lifetime>
          <start-date-time>2016-12-31T23:59:55Z</start-date-time>
          <end-date-time>2017-02-01T00:00:05Z</end-date-time>
        </accept-lifetime>
      </lifetime>
      <crypto-algorithm
        xmlns:tcp=
          "urn:ietf:params:xml:ns:yang:ietf-tcp">tcp:aes-128</crypto-alg
hm>
      <key-string>
        <keystring>testvector</keystring>
      </key-string>
      <authentication
        xmlns="urn:ietf:params:xml:ns:yang:ietf-tcp">
        <keychain>ao-config</keychain>
        <ao>
          <send-id>61</send-id>
          <recv-id>84</recv-id>
        </ao>
      </authentication>
    </key>
  </key-chain>
</key-chains>
```

## Appendix C. Complete Tree Diagram

Here is the complete tree diagram for the TCP YANG model.

```

module: ietf-tcp
+--rw tcp!
  +--rw connections
  | +--rw connection*
  |   [local-address remote-address local-port remote-port]
  |   +--rw local-address      inet:ip-address
  |   +--rw remote-address     inet:ip-address
  |   +--rw local-port         inet:port-number
  |   +--rw remote-port        inet:port-number
  |   +--rw mss?                mss
  |   +--rw pmtud?              boolean
  |   +--rw keepalives! {keepalives-supported}?
  |   | +--rw idle-time         uint16
  |   | +--rw max-probes        uint16
  |   | +--rw probe-interval    uint16
  |   +--ro state?              enumeration
+--ro tcp-listeners* [type address port]
  | +--ro type      inet:ip-version
  | +--ro address   union
  | +--ro port      inet:port-number
+--ro statistics {statistics}?
  +--ro active-opens?          yang:counter64
  +--ro passive-opens?         yang:counter64
  +--ro attempt-fails?         yang:counter64
  +--ro establish-resets?      yang:counter64
  +--ro currently-established? yang:gauge32
  +--ro in-segments?           yang:counter64
  +--ro out-segments?          yang:counter64
  +--ro retransmitted-segments? yang:counter64
  +--ro in-errors?             yang:counter64
  +--ro out-resets?            yang:counter64
  +--ro auth-failures?         yang:counter64
  |   {authentication}?
+---x reset
  +---w input
  | +---w reset-at?  yang:date-and-time
  +--ro output
  | +--ro reset-finished-at? yang:date-and-time

augment /key-chain:key-chains/key-chain:key-chain:key:
+--rw authentication {authentication}?
  +--rw keychain?      key-chain:key-chain-ref
  +--rw (authentication)?
  +--:(ao)
  | +--rw ao!
  |   +--rw send-id?      uint8
  |   +--rw recv-id?      uint8
  |   +--rw include-tcp-options? boolean
  |   +--rw accept-key-mismatch? boolean

```

```
|      +--ro r-next-key-id?      uint8
+--:(md5)
  +--rw md5!
```

## Authors' Addresses

Michael Scharf  
Hochschule Esslingen - University of Applied Sciences  
Kanalstr. 33  
73728 Esslingen  
Germany

Email: [michael.scharf@hs-esslingen.de](mailto:michael.scharf@hs-esslingen.de)

Mahesh Jethanandani  
Kloud Services

Email: [mjethanandani@gmail.com](mailto:mjethanandani@gmail.com)

Vishal Murgai  
Samsung

Email: [vmurgai@gmail.com](mailto:vmurgai@gmail.com)